

**EN** - For pricing and availability in your local country please visit one of the below links:

**DE** - Informationen zu Preisen und Verfügbarkeit in Ihrem Land erhalten Sie über die unten aufgeführten Links:

**FR** - Pour connaître les tarifs et la disponibilité dans votre pays, cliquez sur l'un des liens suivants:

[ST7200USBM](#)

[ST7200USBM](#)

[ST7200USBM..](#)

**EN**  
This Datasheet is presented by  
the manufacturer

**DE**  
Dieses Datenblatt wird vom  
Hersteller bereitgestellt

**FR**  
Cette fiche technique est  
présentée par le fabricant

## Mountable Rugged Industrial 7 Port USB Hub

StarTech ID: ST7200USBM



This sturdy, industrial grade USB 2.0 hub can be wall mounted or installed onto a DIN rail for convenient access to its 7 female USB 2.0 ports, providing a work area, server room, or industrial environment with USB 2.0 connectivity.

With support for Hi-Speed USB 2.0 data transfer rates of up to 480 Mbps, this 7 port USB hub is backwards compatible with USB 1.1 specifications and can be powered through the host USB bus, or self powered using a three wire terminal block connector (7-24V).

### Applications

- Add additional, easy to access USB ports to rack mounted equipment
- Install a USB hub that can be securely mounted to a surface or inside an equipment rack DIN rail

### Features

- Provides 7 USB 2.0 ports
- USB bus powered or external terminal block with support for 7 ~ 24VDC input
- Compact and lightweight design with surface or DIN rail mounting options
- Industrial strength, all-metal enclosure
- High Speed USB 2.0 compliant, with transfer rates up to 480 Mbps
- 350W surge protection on each USB port
- Plug-and-Play and Hot-Swap compatible
- Includes a 2 meter screw-locking USB cable

**Technical Specifications**

Warranty	2 Years
Interface	USB 2.0
Ports	7
Industry Standards	USB 2.0
Chipset ID	Renesas/NEC - uPD720113
External Ports	1 - Terminal Block (2 Wire)
External Ports	1 - USB B (4 pin) Female
External Ports	7 - USB A (4 pin) Female
Maximum Data Transfer Rate	Up to 480Mbps
Surge Protection	350W per port
OS Compatibility	OS independent; No software or drivers required
System and Cable Requirements	Any computer with a USB 2.0 port
Color	Black
Enclosure Type	Steel
Product Length	133 mm [5.2 in]
Product Width	61.5 mm [2.4 in]
Product Height	36.3 mm [1.4 in]
Product Weight	500 g [17.6 oz]
LED Indicators	1 - Power
Input Voltage	7 ~ 24 DC
Operating Temperature	0°C to 55°C (32°F to 131°F)
Storage Temperature	-20°C to 85°C (-4°F to 185°F)
Humidity	5~95% RH
Shipping (Package) Weight	0.5 kg [1.1 lb]
Included in Package	1 - USB 2.0 Hub
Included in Package	2 - DIN rail mounting bracket
Included in Package	1 - Locking USB Cable
Included in Package	1 - Screw kit
Included in Package	1 - Instruction Manual

Certifications, Reports and Compatibility



Operating System  
Independent

 **RoHS Compliant**  
Available

**EN** - For pricing and availability in your local country please visit one of the below links:

**DE** - Informationen zu Preisen und Verfügbarkeit in Ihrem Land erhalten Sie über die unten aufgeführten Links:

**FR** - Pour connaître les tarifs et la disponibilité dans votre pays, cliquez sur l'un des liens suivants:

[ST7200USBM](#)

[ST7200USBM](#)

[ST7200USBM..](#)

**EN**

This Datasheet is presented by  
the manufacturer

**DE**

Dieses Datenblatt wird vom  
Hersteller bereitgestellt

**FR**

Cette fiche technique est  
présentée par le fabricant