

**EN** - For pricing and availability in your local country please visit one of the below links:

**DE** - Informationen zu Preisen und Verfügbarkeit in Ihrem Land erhalten Sie über die unten aufgeführten Links:

**FR** - Pour connaître les tarifs et la disponibilité dans votre pays, cliquez sur l'un des liens suivants:

[U442-DOCK1](#)

**EN**

This Datasheet is presented by  
the manufacturer

**DE**

Dieses Datenblatt wird vom  
Hersteller bereitgestellt

**FR**

Cette fiche technique est  
présentée par le fabricant

In the case of first time connection to speakers, headphones or other devices, the sound channel will take precedence. Audio preference can be changed via your System Preference Menu.

## USB-C Dual Display Dock, 4K HDMI, VGA, 4K Mini DP, Gbe, Card Reader, 3x USB-A Ports, PD Charging, Silver

MODEL NUMBER: **U442-DOCK1**



Convert your MacBook, Chromebook, tablet or laptop into a versatile workstation via its USB-C or Thunderbolt 3 port. Recommended for connecting an external display, accessing Gigabit Ethernet, transferring data and displaying video.

### Description

The U442-DOCK1 USB 3.1 Gen 1 USB-C Docking Station turns your MacBook, Chromebook, tablet or laptop into a versatile workstation. By connecting its built-in cable to your device's USB-C or Thunderbolt 3 port, you'll be able to add an external display, access Gigabit Ethernet networks, transfer data, display video and more.

Mini DisplayPort (mDP), VGA and HDMI ports allow you to connect an external display (one display at a time). With the addition of adapters (sold separately), you can also add a DVI or DisplayPort display to the U442-DOCK1. The mDP and HDMI ports support UHD video resolutions up to 3840 x 2160 (4K x 2K) at 30 Hz. The VGA port supports HD video resolutions up to 1920 x 1200, including 1080p, at 60 Hz.

Connect a Gigabit Ethernet cable (sold separately) to the RJ45 port to access true 10/100/1000 Mbps network speeds. Three USB-A hub ports are convenient for connecting peripherals to your device. Each supports data transfer rates up to 5 Gbps. A dedicated BC 1.2-compliant USB port provides up to 1.5A of fast-charging power.

The U442-DOCK1 also features a USB-C Power Delivery (PD) port that supports power input up to 20V 3A (60W). It connects to a USB-C wall charger to power the device it's plugged into, as well as peripherals plugged into the USB-A ports.

### Highlights

- Mini DisplayPort, VGA and HDMI ports
- Ethernet port supports 10/100/1000 Mbps speeds
- USB-A ports support data transfer rates up to 5 Gbps
- Memory card slots for external memory access
- USB-C Power Delivery port supports power input up to 20V 3A

### System Requirements

- MacBook, Chromebook, tablet or laptop with USB-C or Thunderbolt 3 port that supports USB DisplayPort Alternate Mode
- DisplayPort\*, Mini DisplayPort, VGA, DVI\* or HDMI external display
- Ethernet network

### Package Includes

- U442-DOCK1 USB 3.1 Gen 1 USB-C Docking Station
- Owner's manual

Micro SD and SD/MMC memory card slots also provide access to external memory. A 3.5 mm audio jack is convenient for connecting speakers, headphones or a microphone to your connected device.

## Features

### Convert a Computer into a Versatile Workstation via USB-C or Thunderbolt 3 Port

- Recommended for connecting an external display, accessing Gigabit Ethernet, transferring data and displaying video

### Supports USB DisplayPort Alternate Mode

- Connects a Mini DisplayPort, VGA or HDMI external display (one display at a time)
- Supports connection of DVI display via HDMI to DVI adapter (sold separately)
- Supports connection of DisplayPort display via mDP to DisplayPort adapter (sold separately)
- mDP and HDMI ports support video resolutions up to 3840 x 2160 (4K x 2K) @ 30 Hz
- VGA port supports video resolutions up to 1920 x 1200, including 1080p, @ 60 Hz

### Gigabit Ethernet Port

- Supports true 10/100/1000 Mbps network speeds

### 3 USB-A Hub Ports

- Support data transfer rates up to 5 Gbps
- Connect USB peripherals, such as a thumb drive or printer, to your device
- Backward compatible with previous USB generations
- BC 1.2-compliant port provides up to 1.5A of fast-charging power to mobile devices

### USB-C Power Delivery Port for Charging Portable Devices

- Connects to USB-C wall charger to power the connected computer
- Supports power input up to 20V 3A (60W)
- 15W dedicated to unit and USB-A hub ports
- 45W dedicated to USB-C device the unit is connected to

### 3.5 mm Mini Stereo Jack

- Supports connection of speakers, headphones or microphone

### Micro SD and SD/MMC Card Slots

- Memory card slots provide external memory access

### Advanced Operation

- Plug-and-play—no software, drivers or external power sources needed
- Automatically resumes operation from hibernation and suspend modes
- Complies with IEEE 802.3az standards
- Supports full- and half-duplex operations



- Supports IPv4 and IPv6 pack COE to reduce CPU loading
- Supports Wake-on-LAN

## Specifications

OVERVIEW	
UPC Code	037332193834
OUTPUT	
Charging Ports / Amps	1.5A; 3A
Charging Watts	60
INPUT	
Bus Powered	Yes
Product Length (in.)	8.3
Product Length (cm.)	21.08
Product Length (ft.)	0.69
Product Length (m.)	0.21
BATTERY	
Battery Charging (1.2 Port)	Yes
PHYSICAL	
Cable Jacket Rating	VW-1
Color	Silver; White
Material of Construction	PVC and Aluminum
Shipping Dimensions (hwd / cm)	2.54 x 13.21 x 16.51
Shipping Dimensions (hwd / in.)	1.00 x 5.20 x 6.50
Shipping Weight (kg)	0.23
Shipping Weight (lbs.)	0.50
Unit Dimensions (hwd / cm)	1,7 x 7,5 x 13,7
Unit Dimensions (hwd / in.)	0.67 x 2.95 x 5.39
Unit Packaging Type	Box
Unit Weight (kg)	0.10
Unit Weight (lbs.)	0.22
ENVIRONMENTAL	



Operating Temperature Range	32 to 113 F (0 to 45 C)
Storage Temperature Range	14 to 158 F (-10 to 70 C)
BTUs	17.1 BTU/Hr
Power Consumption (Watts)	5
Operating Humidity Range	10% to 85% RH, Non-Condensing
Storage Humidity Range	5% to 90% RH, Non-Condensing
<b>COMMUNICATIONS</b>	
Network Speed	1Gbps
IEEE Standards Supported	802.3; 802.3u; 802.3az; 802.3x
<b>CONNECTIONS</b>	
Ports	11
Dock Connectors	3 x USB3.0, 3.5mm Stereo, RJ45 LAN, HDMI, MINI DISPLAYPORT, VGA, MICRO SD, SD, USB-C CHARGING
Side A - Connector 1	USB C (MALE)
Side B - Connector 1	HD15 (FEMALE); HDMI (FEMALE); MINI DISPLAYPORT (FEMALE)
Side B - Connector 2	(3) USB 3.0 A (FEMALE)
Side B - Connector 3	MICRO SD (FEMALE); SD (FEMALE)
Side B - Connector 4	RJ45 (FEMALE)
Side B - Connector 5	USB Type-C (FEMALE)
Side B - Connector 6	3.5MM (FEMALE)
Connector Plating	Nickel
<b>FEATURES &amp; SPECIFICATIONS</b>	
Max Supported Video Resolution	MDP/HDMI: 3840 X 2160 (4K X 2K) @ 30HZ; VGA: 1920 X 1200 (1080P) @ 60HZ
Displayport Specification	1.2
HDMI Specification	1.4
HDCP Specification	1.4
USB Specification	USB 3.0 (up to 5 Gbps); USB 3.1 Gen 1 (up to 5 Gbps)
Driver Required	No
Recommended Category Cable	Cat5/Cat5e/Cat6 Cables
USB Power Delivery (PD) Charging Support	Yes
Auto MDIX Support	Yes
Full Duplex Support	Yes
Suspend Mode Support	Yes
Remote Wakeup Support	Yes



Technology	Cat5/5e; Cat6; DisplayPort; HDMI; Stereo Audio; USB; USB 3.0 (SuperSpeed); USB 3.1 (Gen 1); VGA/SVGA; PD Charging
SD Card Specification	SD; Micro SD
USB Power Delivery (PD) Charging Specification	2.0
<b>CERTIFICATIONS</b>	
Certifications	Tested to CE, FCC, RoHS, REACH
<b>WARRANTY</b>	
Product Warranty Period (Worldwide)	3-year limited warranty

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>

**EN** - For pricing and availability in your local country please visit one of the below links:

**DE** - Informationen zu Preisen und Verfügbarkeit in Ihrem Land erhalten Sie über die unten aufgeführten Links:

**FR** - Pour connaître les tarifs et la disponibilité dans votre pays, cliquez sur l'un des liens suivants:

[U442-DOCK1](#)

**EN**

This Datasheet is presented by  
the manufacturer

**DE**

Dieses Datenblatt wird vom  
Hersteller bereitgestellt

**FR**

Cette fiche technique est  
présentée par le fabricant