Fujitsu recommends Windows 10 Pro.



# Data Sheet FUJITSU Workstation CELSIUS H770 Workstations

## Mobile Workstation Meets Security

If you are looking for workstation power on-the-go packed in a 39.6 cm (15.6-inch) stylish form factor, then the FUJITSU CELSIUS H770 mobile workstation is the right choice. Its port replicator is compatible with seven LIFEBOOK devices and thus ideal for a shared desk environment. Maximum data security is guaranteed by the unique PalmSecure™ technology.

### Mobile Workstation Meets Security

When true workstation performance meets the elegant style of a laptop

- Choose between Intel® Core™ processors or powerful Intel® Xeon processor ® E3-1500M family supporting ECC memory
- Support of Windows 10 Pro
- UHD/4k and Full HD LED anti-glare displays
- Up to 64 GB DDR4 2400 MHz memory (ECC optional)
- M.2 SSDs PCIe NVMe technology supports quick loading of core applications

### Full connectivity and worry-free docking experience

No compromise in terms of port connectivities, regardless of whether you are away, in a meeting or at your desk

- USB Type-C<sup>™</sup> connector offering more speed (40 Gbps), more protocols (including Thunderbolt 3) and charging capabilities (power delivery of 15W)
- Full monitor connectivity support: 1x VGA and 1x DisplayPort (full size)
- 1 port replicator shared across 8 mobile devices: Notebooks, Ultrabook™, 2 in 1 and mobile workstations

### Maximum Security

Data security and peace of mind

- Optional PalmSecure™, a leading-edge highly secure authentication system using biometric technology that authenticates users through vein pattern recognition
- Optional fingerprint sensor
- Integrated SmartCard reader
- TPM 2.0 and Advanced Theft Protection









# Components

Base unit	CELSIUS H770
Operating systems	
Operating system pre-installed	Windows 10 Pro
Operating system compatible	Windows 10 Pro
Processor	Intel® Xeon® processor E3-1535M v6 (3.1 GHz, Up to 4.2 GHz, 8 MB, Intel® HD Graphics P630)
	Intel® Xeon® processor E3-1505M v6 (3.0 GHz, up to 4.0 GHz, 8 MB, Intel® HD Graphics P630)
	Intel® Core™ i7-7920HQ processor (3.1 GHz, up to 4.1 GHz, 8 GB, Intel® HD Graphics 630)
	Intel® Core™ i7-7820HQ processor (2.9 GHz, up to 3.9 GHz, 8 GB, Intel® HD Graphics 630)
	Intel® Core™ i7-7700HQ processor (2.8 GHz, up to 3.8 GHz, 6 MB, Intel® HD Graphics 630)
Memory modules	8 GB (2 module(s) 4 GB) DDR4, 2,400 MHz, SO DIMM
	16 GB (2 module(s) 8 GB) DDR4, 2,400 MHz, SO DIMM
	16 GB (2 module(s) 8 GB) DDR4, ECC, 2,400 MHz, SO DIMM
	32 GB (2 module(s) 16 GB) DDR4, 2,400 MHz, SO DIMM
	32 GB (2 module(s) 16 GB) DDR4, ECC, 2,400 MHz, SO DIMM
Hard disk drives (internal)	SSD SATA III, 1024 GB, 2.5-inch, SED
	SSD SATA III, 512 GB, 2.5-inch, SED
	SSD SATA III, 256 GB, 2.5-inch, SED
	SSD SATA III, 5,400 rpm, 1000 GB
	SSD SATA III, 5,400 rpm, 500 GB
	PCIe-SSD, 1024 GB, M.2 module, SED
	PCIe-SSD, 512 GB, M.2 module, SED
	PCIe-SSD, 256 GB, M.2 module, SED
	SSD SATA, 1024 GB, M.2 module, SED
	SSD SATA, 512 GB, M.2 module, SED
	SSD SATA, 256 GB, M.2 module, SED
Hard disk notes	One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. Accessible capacity may vary, also depending on used software.
Modular bay options	2nd battery
	Blu-ray Disc™ Triple Writer
	DVD Super Multi
	Weight saver
Interface add on cards/components (optional)	
3G/4G (optional)	Sierra Wireless AirPrime® EM7305 LTE/HSPA+ (LTE/UMTS module)
WLAN (optional)	Intel® Dual Band Wireless-AC8260 11ac with integrated Bluetooth 4.2
	Import and usage according to country-specific regulations.
	2 Dual Band WLAN antennas, 2 UMTS antennas
Display	$39.6 \text{ cm } (15.6\text{-inch}), \text{IPS LED backlit}, (\text{UHD/4K}), \text{Anti-glare display, magnesium}, 3,840 \times 2,160 \text{ pixel, min. } 700:1, typ. 300 \text{ cd/m}^2, 85/85/85$
	$39.6 \text{ cm } (15.6\text{-inch}), \text{IPS LED backlit}, (\text{Full HD}), \text{Anti-glare display, magnesium}, 1,920 \times 1,080 \text{ pixel, min. } 700:1, typ. 300 \text{ cd/m}^2, 85/85/85$
	39.6 cm (15.6-inch),IPS LED backlit,(Full HD),Anti-glare display,magnesium,1,920 x 1,080 pixel
Camera	Optional: Built-in webcam, 2.0 megapixel
Microphone	2x digital (optional)

Page 2 / 7 www.fujitsu.com/fts/CELSIUS

# Base unit

Base unit	CELSIUS H770
Mainboard	
Chipset	Intel® QM175 or CM238 (depending on CPU)
Supported capacity RAM (min.)	8 GB
Supported capacity RAM (max.)	64 GB
Memory slots	4 SO DIMM (DDR4, 2133 MHz)
LAN	10/100/1,000 MBit/s Intel® I219LM
BIOS features	InsydeH20 Bios
Audio type	On board
Audio codec	Realtek ALC255 with MaxxAudio
Audio features	Stereo speakers, 2 digital microphones
Display	
Display notes	ISO 9241-307 - Pixel class II - anti-glare level
	130 3241-307 - Fixel class II - dilu-glate level
Graphics	
Base unit	CELSIUS H770
Graphics brand name	NVIDIA® Quadro® M2200, NVIDIA® Quadro® M1200, NVIDIA® Quadro® M620
Graphics features	NVIDIA® Quadro® M2200: 4GB (1024 CUDA Cores) NVIDIA® Quadro® M1200: 4GB (640 CUDA Cores)
	NVIDIA® Quadro® M620: 2GB (512 CUDA Cores)
Interfaces	
DC-in	1
Audio: line-in / microphone	1
Audio: line-out	1
Internal microphones	2 digital array microphones
USB 2.0 total	1
USB 3.1 Gen1 (USB 3.0) total	2
USB Type-C	1 (USB 3.1 Gen2 (10 Gbps), Thunderbolt 3 (20/40Gbps), Power Delivery (15W), DP 1.2)
VGA	1
DisplayPort	1
Ethernet (RJ-45)	1
SmartCard slot	1
SIM card slot	1
Multicardreader	1 (SD/SDHC) SD/microSD = 2GB, SDHC/micro SDHC = 32GB, SDXC = 64GB
Interface Module notes	1x Kensington Lock support, 1x Docking connector
Port Replicator interfaces (optional)	
DC-in	1 (19V)
Power on switch	1
Audio: headphone	1
Audio: microphone	1
USB 3.1 Gen1 (USB 3.0) total	4
DisplayPort	2 - 1 DP (next to DVI) is shared with DVI, works when DVI not connected
VGA	1
DVI	1 - shared with DP (next to DVI) - works when DP (next to DVI) not connected
Ethernet (RJ-45)	1 (10/100/1000)
Kensington Lock support	1 (Portrep & System)
eSATA	1
Notes	Port replicator supports 0-Watts functionality
	1 11 /

Page 3 / 7 www.fujitsu.com/fts/CELSIUS

Vouhoard	
Keyboard	Touchand with three mouse buttons
Input devices (optional)	Touchpad with three mouse buttons  TouchStick
<u> </u>	IOUCIISUCK
Power supply	
AC adapter	19 V / 150 W (7.89 A)
Rated voltage range	100 V - 240 V (AC Input)
Rated frequency range	50 Hz - 60 Hz
Runtime 1st battery	up to 11 hours
Runtime 1st + 2nd battery	up to 14 hours
Dimensions / Weight / Environmental	
Dimensions (W $\times$ D $\times$ H)	380.0 x 257.0 x 24.8-31.9 mm w/o bump / with rubber feet 35.0 mm
	14.96 x 10.12 x 0.98-1.26 inch w/o bump / with rubber feet 1.38 inch
Weight	2.75 kg
Weight (lbs)	6.1 lbs
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	5 - 35 °C (41 - 95 °F)
Operating relative humidity	20 - 80 % (relative humidity, non-condensing)
Compliance	
Product	CELSIUS H770
Europe	CE Marking
USA/Canada	CULUS
Global	FCC Class B part 15C/E + 22 + 24 (depending on wireless configuration)  RoHS (EU & China)
ulobal	Medical EMC standard IEC60601-1-2 in combination with medical kit EPEAT® Gold (dedicated regions) ENERGY STAR® 6.1 (dedicated regions)
Compliance link	https://sp.ts.fujitsu.com/sites/certificates
Additional Software	
Additional software (preinstalled)	Adobe® Reader® (pdf reader) McAfee Multi Access Security (anti-virus and internet security software; 60 days trial version) Fujitsu Display Manager EasyGuide online user documentation Power Saving Utility ShockSensor Utility SmartAccess Fujitsu Plugfree Network (network management utility) Intel® SBA (manageability suite for local administration) DTS® Sound Enhance Software Fujitsu Application Button Utility Fujitsu DeskUpdate (driver and utility tool) Microsoft Office (buy license to activate the pre-installed Microsoft Office)
Additional software (optional)	Drivers & Utilities DVD (DUDVD) LTE / UMTS Connection Manager (if configured with 4G/LTE or 3G/UMTS)
Manageability	
Manageability technology	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) iAMT 11.0 (depending on processor) Intel® vPro™ technology WoL (Wake on LAN)
Manageability software	DeskView Client DeskView Instant BIOS Management DeskView Integration for Symantec Management Platform

Page 4 / 7 www.fujitsu.com/fts/CELSIUS

Manageability	
DeskView components	Inventory Management BIOS Management Driver Management Security Management Alarm Management
Supported standards	WMI PXE BootP (made4you)
Manageability link	http://www.fujitsu.com/fts/solutions/high-tech/dynamic-infrastructure/solutions/workplace/manageability/feature-finder.html
Security	
Physical Security	Kensington Lock support
System and BIOS Security	Advanced Theft Protection Computrace® enabled BIOS Optional: Trusted platform module (TPM 1.2 or 2.0) EraseDisk (optional) Write protect option for the Flash EPROM
User Security	Embedded fingerprint sensor (optional) Embedded palm vein sensor (optional) Separate SmartCard slot Hard disk password User and supervisor BIOS password Preboot Authentification with SystemLock 3
Warranty	
Warranty period	3 years (depending on country)
Warranty type	Collect & Return Service / Bring-in Service (depending on country)

warranty period	3 years (depending on country)
Warranty type	Collect & Return Service / Bring-in Service (depending on country)
Warranty Terms & Conditions Product Support Services - the perfe	http://support.ts.fujitsu.com/warranty
Product Support Services - the pent	ett exterision
Recommended Service	9x5, Onsite Response Time: Next Business Day
Spare Parts availability	5 years after end of product life
Service Weblink	http://www.fujitsu.com/fts/services/support

## Recommended Accessories

Port Replicator for LIFEBOOK U745, T7, E5, E7 Series and **CELSIUS H730, H760** 



Flexibility, expandability, desktop replacement, investment protection – to Order Code: name just a few benefits of Fujitsu's docking options.

S26391-F1337-L109

### Prestige Top Case 15



The Prestige Top Case 15 protects notebooks with up to 15.6-inch screens. A Order Code: padded top-loading notebook compartment made of shock-absorbing foam S26391-F1194-L50 ensures additional protection. It's front pouch is ideal for storing of power adaptors, office supplies or personal items. It is the perfect business case in a practical design.

Page 5 / 7 www.fujitsu.com/fts/CELSIUS

### Wireless Mouse Touch WI910



The Fujitsu Wireless Mouse Touch WI910 has a special touch sensitive surface that recognizes when your hand touches the mouse even before you move it. This provides nearly instantaneous wake-up from the intelligent energy saving sleep mode. Unbeatable responsiveness combines with features like switchable resolution, and three programmable buttons for a unique user experience.

Order Code: S26381-K465-L100

Page 6 / 7 www.fujitsu.com/fts/CELSIUS

## More information

#### Fujitsu OPTIMIZATION Services

In addition to the FUJITSU Workstation CELSIUS H770, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

### Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

### **Computing Products**

www.fujitsu.com/global/products/computing/

### Software

www.fujitsu.com/software/

### More information

Learn more about the FUJITSU Workstation CELSIUS H770, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. www.fujitsu.com/fts/CELSIUS

### Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www.fujitsu.com/global/about/environment



### Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/

© 2017 Fujitsu Technology Solutions GmbH

### Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

#### Contact

Fujitsu Technology Solutions Website: www.fujitsu.com/fts 2017-05-16 CE-EN All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/terms

© 2017 Fujitsu Technology Solutions GmbH