

Fujitsu recommends Windows 10 Pro.

Data Sheet

FUJITSU Desktop ESPRIMO D958

Combines High Efficiency with Manageability

The FUJITSU ESPRIMO D958 Desktop provides maximum manageability, performance and expandability. The 8th Gen Intel® Core™ processor and Intel® vPro™ technology combined with the DeskView manageability suite support professional computing and advanced manageability. The low-noise design (optional Zero Noise PC function) supports a pleasant working environment. Its innovative Low Power Active Mode feature ensures instant communication in the office. Made in Germany, the high production quality helps extend the product lifetime and 94%-efficient power supplies reduce your energy bills. Finally, the Fujitsu EraseDisk function ensures your data is securely wiped on retirement.



Expandability

Easily customizable and highly expandable business desktop PC

- 10 I/O housing, more I/O slots, serial connector to help you build your own desktop systems, tailored to your specific business needs

Zero Noise PC

Pleasant working environment due to completely quiet system (solid state disk required)

- Fan stop in standard operations (for E94+ only)

Always Available Office PC - stay connected and save power

Be ready for instant communication and a significantly reduced energy bill

- Innovative Low Power Active Mode and energy-efficient integrated power supply

Superior system management

Simple system administration for complex IT infrastructures

- Intel® vPro™ technology (depending on processor) and DeskView manageability suite

Easy serviceability and usability

Features designed for easy access, control and use of the system

- Tool-less access to components; front connectors and interfaces for ease of use with USB Type-C (USB 3.1 Gen2) front connector



Components

| | ESPRIMO D958/E85+ | ESPRIMO D958/E94+ |
|---------------------------------------|--|--|
| Processor | Intel® Core™ i3-8100 processor (4 Cores / 4 Threads, 3.60 GHz, 6 MB, Intel® UHD Graphics 630) Intel® Core™ i5-8500 processor (6 Cores / 6 Threads, 3.00 GHz, up to 4.1 GHz, 9 MB, Intel® UHD Graphics 630) * Intel® Core™ i5-8600 processor (6 Cores / 6 Threads, 3.10 GHz, up to 4.3 GHz, 9 MB, Intel® UHD Graphics 630) * Intel® Core™ i7-8700 processor (6 Cores / 12 Threads, 3.20 GHz, up to 4.6 GHz, 12 MB, Intel® UHD Graphics 630) * *with Intel® Turbo Boost Technology (clock speed and performance will vary depending on workload and other variables) Intel® vPro™ Logo with Intel® Core i5 and Core i7 processors | |
| Operating systems | | |
| Operating system pre-installed | Windows 10 Pro. Fujitsu recommends Windows 10 Pro. Windows 10 Home | Windows 10 Pro. Fujitsu recommends Windows 10 Pro. Windows 10 Home |
| Memory modules | ESPRIMO D958/E85+ 4 GB (1 module(s) 4 GB) DDR4, unbuffered, non-ECC, 2,666 MHz, UDIMM 8 GB (1 module(s) 8 GB) DDR4, unbuffered, non-ECC, 2,666 MHz, UDIMM 16 GB (1 module(s) 16 GB) DDR4, unbuffered, non-ECC, 2,666 MHz, UDIMM | ESPRIMO D958/E94+ 4 GB (1 module(s) 4 GB) DDR4, unbuffered, non-ECC, 2,666 MHz, UDIMM 8 GB (1 module(s) 8 GB) DDR4, unbuffered, non-ECC, 2,666 MHz, UDIMM 16 GB (1 module(s) 16 GB) DDR4, unbuffered, non-ECC, 2,666 MHz, UDIMM |
| Graphics | ESPRIMO D958/E85+ Entry 3D: NVIDIA® Quadro® P400 , 2 GB, PCIe x16, 3x miniDP Entry 3D: AMD® Radeon R7 340, 2 GB, 1x Dual Link DVI-I, 1x DisplayPort Others: VGA Extension Card | ESPRIMO D958/E94+ Entry 3D: NVIDIA® Quadro® P400 , 2 GB, PCIe x16, 3x miniDP Entry 3D: AMD® Radeon R7 340, 2 GB, 1x Dual Link DVI-I, 1x DisplayPort Others: VGA Extension Card |
| Hard disk drive | ESPRIMO D958/E85+ HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch, business critical HDD SATA III, 7,200 rpm, 2,000 GB, 3.5-inch HDD SATA III, 7,200 rpm, 500 GB, 3.5-inch Intel Optane Memory (16 GB) RAID1 Bundle 2x256GB M.2 NVMe Highend RAID1 Bundle 2x512GB M.2 NVMe Highend SSD PCIe, 1024 GB M.2 NVMe Highend module SSD PCIe, 1024 GB M.2 NVMe module SSD PCIe, 1024 GB M.2 NVMe module, SED SSD PCIe, 256 GB M.2 NVMe Highend module SSD PCIe, 256 GB M.2 NVMe module SSD PCIe, 256 GB M.2 NVMe module, SED SSD PCIe, 512 GB M.2 NVMe Highend module SSD PCIe, 512 GB M.2 NVMe module SSD PCIe, 512 GB M.2 NVMe module, SED SSD SATA III, 1024 GB, 2.5-inch SSD SATA III, 128 GB, 2.5-inch SSD SATA III, 256 GB, 2.5-inch SSD SATA III, 512 GB, 2.5-inch | ESPRIMO D958/E94+ HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch, business critical HDD SATA III, 7,200 rpm, 2,000 GB, 3.5-inch HDD SATA III, 7,200 rpm, 500 GB, 3.5-inch Intel Optane Memory (16 GB) RAID1 Bundle 2x256GB M.2 NVMe Highend RAID1 Bundle 2x512GB M.2 NVMe Highend SSD PCIe, 1024 GB M.2 NVMe Highend module SSD PCIe, 1024 GB M.2 NVMe module SSD PCIe, 1024 GB M.2 NVMe module, SED SSD PCIe, 256 GB M.2 NVMe Highend module SSD PCIe, 256 GB M.2 NVMe module SSD PCIe, 256 GB M.2 NVMe module, SED SSD PCIe, 512 GB M.2 NVMe Highend module SSD PCIe, 512 GB M.2 NVMe module SSD PCIe, 512 GB M.2 NVMe module, SED SSD SATA III, 1024 GB, 2.5-inch SSD SATA III, 128 GB, 2.5-inch SSD SATA III, 256 GB, 2.5-inch SSD SATA III, 512 GB, 2.5-inch |
| Hard disk notes | SSD (Solid State Disk) SED (Self-Encrypting Drive) | |
| Optical drive | ESPRIMO D958/E85+ MultiCard Reader 24in1 USB 2.0 3.5", USB 2.0 DVD Super Multi ultra slim (tray), SATA BD Triple Writer SATA ultra slim (tray), SATA | ESPRIMO D958/E94+ MultiCard Reader 24in1 USB 2.0 3.5", USB 2.0 DVD Super Multi ultra slim (tray), SATA BD Triple Writer SATA ultra slim (tray), SATA |

| | ESPRIMO D958/E85+ | ESPRIMO D958/E94+ |
|---|--|--|
| Interfaces add on cards / components | Parallel Interface M.2 WLAN 802.11ac (2x2) and BT 5 (dedicated regions only) Gigabit Ethernet PCIe x1 eSATA Interface Dual serial card PCIe x1 | Parallel Interface M.2 WLAN 802.11ac (2x2) and BT 5 (dedicated regions only) Gigabit Ethernet PCIe x1 eSATA Interface Dual serial card PCIe x1 |
| Base unit | ESPRIMO D958/E85+ | ESPRIMO D958/E94+ |
| Mainboard | | |
| Mainboard type | D3632 | |
| Formfactor | proprietary | |
| Chipset | Intel® Q370 | |
| Processor socket | LGA 1151 | |
| Processor quantity maximum | 1 | |
| Supported capacity RAM (max.) | 64 GB | |
| Memory slots | 4 DIMM (DDR4) | |
| Memory frequency | 2,666 MHz | |
| Memory notes | Dual channel support For dual channel performance, 2 memory modules have to be ordered. Capacity per channel has to be the same. 2666 MHz may be clocked down to 2400 MHz depending on processor and memory configuration | |
| LAN | 10/100/1,000 MBit/s Intel® I219LM | |
| Integrated WLAN | 1 (optional with Bluetooth together) | |
| BIOS version | AMI Aptio V UEFI Specification 2.6 | |
| BIOS features | BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI) | |
| Audio type | On board | |
| Audio codec | Realtek ALC671 | |
| Audio features | Internal speaker supports audio playback (optional), High Definition audio, 5.1 surround sound | |
| I/O controller on board | | |
| Serial ATA total | 5 | |
| thereof SATA III | 5 | |
| thereof eSATA | 2 | |
| Controller functions | Serial ATA III (6 Gbit) NCQ AHCI RAID 0/1/5/10 | |
| Interfaces | | |
| Audio: line-in | 1 | |
| Audio: line-out | 1 | |
| Front audio: microphone | 1 | |
| Front audio: headphone | 1 | |
| USB 2.0 total | 4 | |
| USB 3.1 Gen1 (USB 3.0) total | 4 | |
| USB 3.1 Gen2 total | 3 and 2 optional via add on card | |
| USB front | 1x USB 2.0; 2x USB 3.1 (gen 2); 1x USB 3.1 (gen2) Type C; optional: additional 1x USB 3.1 Type C (Gen2) via add on card and front adapter bay | |
| USB rear | 2x USB 2.0; 4x USB 3.1 (gen1); optional: additional 1x USB 3.1 Type C (Gen2) via add on card | |
| USB internal | 1x USB 2.0 | |
| VGA | optional: via adapter card | |
| DisplayPort | 2 | |

Interfaces

| | |
|-------------------------|--|
| DVI | 1 (DVI-D) |
| Serial (RS-232) | optional: serial port (9pin, 16 byte FIFO, 16550 compatible) |
| Mouse / Keyboard (PS/2) | 2 |
| Ethernet (RJ-45) | 1 |
| Parallel | 1 (optional) (25pin with EPP and ECP) |
| eSATA | 1 (optional) |
| Interface Module notes | Anytime USB charge functionality, USB Typ C connector supports up to 15W |

Input device / components

| | |
|--------------------------|--|
| Input devices (optional) | Keyboard Mouse KBPC PX ECO Mouse M440 ECO |
|--------------------------|--|

Drive bays

| | |
|-------------------------|---|
| 3.5-inch internal bays | 1 |
| 3.5-inch external bays | 1 |
| 5.25-inch external bays | 1 |
| Drive bay notes | 5,25" bay: for slim optical disc drive only; internal 3.5" bay: 1x 3.5" drive (screwless) or 1x 2.5" drive (screws) or optional via adapter for 1x or 2x 2.5" drives (screwless); external 3.5" bay: optional as internal 3.5" bay (screws) |
| M.2-2280 | 1 x on mainboard for SSD NVMe (PCIe 3.0 x4; up to 32Gbit/s; supports Intel® Optane™ technology) |

Slots

| | |
|--------------------------------|--------------------------------------|
| PCI-Express 3.0 x1 | 2 x (174 mm / 6.85 inch) Low profile |
| PCI-Express 3.0 x4 (mech. x16) | 1 x (174 mm / 6.85 inch) |
| PCI-Express 3.0 x16 | 1 x (174 mm / 6.85 inch) Low profile |
| M.2-2230 | on mainboard for WLAN module |

Graphics on board

| | |
|------------------------------|--|
| Graphics brand name | Intel® UHD Graphics 610, Intel® UHD Graphics 630 |
| Shared video memory | Up to half size of total system memory |
| TFT resolution (VGA) | 1,024 x 768 pixel 1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,600 x 1,200 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel |
| TFT resolution (DVI) | 1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel |
| TFT resolution (DisplayPort) | 1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel 2,560 x 1,440 pixel 2,560 x 1,600 pixel 3,440 x 1,440 pixel 3,840 x 2,160 pixel 4,096 x 2,304 pixel |

Graphics on board

| | | |
|--------------------------|--|-------------------|
| Graphics features | Support for up to three independent displays DirectX® 12 HDCP support OpenCL™ 2.0 (requires Intel® Core™ i3, i5 or i7 processors) OpenGL® 4.4 For multi monitoring mode, graphics card and integrated graphics run in parallel DisplayPort interface supports Ver. 1.2 incl. Multi-Stream DVI-D interface supports audio output for HDMI monitors | |
| Graphics notes | up to 1 GB dedicated video memory (main memory owned and locked for graphics use) Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size and operating system Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz | |
| Base unit | ESPRIMO D958/E85+ | ESPRIMO D958/E94+ |

Electrical values

| | | |
|---|---|---|
| Power efficiency note | power supply efficiency at 10% / 20% / 50% / 100% load for 230V: 80% / 85% / 88% / 87%; for 115V: 79% / 84% / 87% / 84% | power supply efficiency at 10% / 20% / 50% / 100% load for 230V: 87% / 91% / 94% / 93%; for 115V: 86% / 90% / 92% / 90% |
| Rated voltage range | 100 V - 240 V | 100 V - 240 V |
| Rated frequency range | 50 Hz - 60 Hz | 50 Hz - 60 Hz |
| Operating voltage range | 90 V - 264 V | 90 V - 264 V |
| Operating line frequency range | 47 Hz - 63 Hz | 47 Hz - 63 Hz |
| Max. output of single power supply | 210 W | 280 W |
| Power factor correction/active power | active | active |
| Monitor outlet | No | Switched |
| Base unit | ESPRIMO D958/E85+ | ESPRIMO D958/E94+ |

Power consumption

| | | |
|-------------------------------|------------------------------------|--|
| Power consumption note | See white paper Energy Consumption | |
|-------------------------------|------------------------------------|--|

Noise emission

| | | |
|---|--|---|
| Related Processors for noise | Intel® Core™ i7 8700 | Intel® Core™ i7 8700 |
| Standard noise emission | 2x4 GB, HDD, ODD, Windows According to ISO 7779:2010, ECMA-74 | 2x4 GB, HDD, ODD, Windows According to ISO 7779:2010, ECMA-74 |
| Standard noise notes / description | A-weighted sound power level Lwad (in B) / Workplace related A-weighted sound pressure level LpAm (in dB(A)) | A-weighted sound power level Lwad (in B) / Workplace related A-weighted sound pressure level LpAm (in dB(A)) |
| Standard noise operation mode: CPU 50% load | 3.5 B / 21 dB(A) Bystander; 23 dB(A) Operator position | 3.5 B / 21 dB(A) Bystander; 23 dB(A) Operator position (HDD 3.5"); 3.3 B / 19 dB(A) Bystander; 22 dB(A) Operator position (SSD M.2) |
| Standard noise operation mode: HDD load | 3.5 B / 21 dB(A) Bystander; 22 dB(A) Operator position | 3.4 B / 21 dB(A) Bystander; 22 dB(A) Operator position (HDD 3.5"); 3.2 B / 18 dB(A) Bystander; 21 dB(A) Operator position (SSD M.2) |
| Standard noise operation mode: Idle mode | 3.3 B / 20 dB(A) Bystander; 20 dB(A) Operator position | 3.3 B / 19 dB(A) Bystander; 19 dB(A) Operator position (HDD 3.5"); 3.0 B / 16 dB(A) Bystander; 16 dB(A) Operator position (SSD M.2) |
| Standard noise operation mode: ODD load | 4.4 B / 31 dB(A) Bystander; 36 dB(A) Operator position | 4.4 B / 31 dB(A) Bystander; 36 dB(A) Operator position (HDD 3.5"); 4.4 B / 30 dB(A) Bystander; 35 dB(A) Operator position (SSD M.2) |
| Standard noise operation mode: Office applications 2.0 | 3.3 B / 20 dB(A) Bystander; 20 dB(A) Operator position | 3.3 B / 19 dB(A) Bystander; 19 dB(A) Operator position (HDD 3.5"); 3.0 B / 17 dB(A) Bystander; 18 dB(A) Operator position (SSD M.2) |

Dimensions / Weight / Environmental

| | |
|-------------------------------|--|
| Dimensions (W x D x H) | 332 x 338 x 89 mm 12.68 x 13.31 x 3.51 inch |
| Operating position | horizontal / vertical (optional, feet needed) |
| Weight | 8 kg |

Dimensions / Weight / Environmental

| | |
|-------------------------------|---|
| Weight (lbs) | 17.64 lbs |
| Weight notes | Actual weight may vary depending on configuration |
| Operating ambient temperature | 10 - 35 °C (50 - 95 °F) |
| Operating relative humidity | 5 - 85 % (relative humidity) |

Compliance

| | | |
|-----------------|--|-------------------|
| Product | ESPRIMO D958/E85+ | ESPRIMO D958/E94+ |
| Model | DTF | |
| Germany | GS (planned) | |
| Europe | CE | |
| USA/Canada | FCC Class B cTUVus | |
| Global | RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® in progress EPEAT® in progress (dedicated regions) | |
| China | CCC (planned) CCC (depending on configuration) CEL (Chinese energy label) TPM 2.0 for China (optional) | |
| Compliance link | https://sp.ts.fujitsu.com/sites/certificates | |

Additional Software

| | | |
|------------------------------------|---|-------------------|
| Additional software (preinstalled) | Adobe® Reader® (pdf reader) McAfee Multi Access Security (anti-virus and internet security software; 60 days trial version) Microsoft Office (buy license to activate the pre-installed Microsoft Office) | |
| Additional software (optional) | Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink PowerDVD BD (playback software for Blu-ray Disc™) CyberLink PowerDVD DVD (playback software for DVD) Nero Essentials XL | |
| Base unit | ESPRIMO D958/E85+ | ESPRIMO D958/E94+ |

Security

| | | |
|--------------------------|--|--|
| Physical Security | Kensington Lock support Eye for padlock Integrated cabinet lock (optional) | Kensington Lock support Eye for padlock Integrated cabinet lock (optional) |
| System and BIOS Security | Embedded security (TPM 2.0) EraseDisk (optional) Credential Guard Ready and Device Guard Capable (Windows 10, v. 1709) Boot sector virus protection Write protect option for the Flash EPROM Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces | Embedded security (TPM 2.0) EraseDisk (optional) Credential Guard Ready and Device Guard Capable (Windows 10, v. 1709) Boot sector virus protection Write protect option for the Flash EPROM Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces |
| User Security | User and supervisor BIOS password Hard disk password Access protection via external SmartCard reader (optional) Access protection via internal SmartCard reader (optional) Workplace Protect (secure authentication solution) | User and supervisor BIOS password Hard disk password Access protection via external SmartCard reader (optional) Access protection via internal SmartCard reader (optional) Workplace Protect (secure authentication solution) |
| Workplace Embedded Tools | Auto BIOS Update via Fujitsu Server Auto BIOS Update via customer server Easy PC Protection | Auto BIOS Update via Fujitsu Server Auto BIOS Update via customer server Easy PC Protection |

Manageability

| | |
|---------------------------------|--|
| Manageability technology | DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) Intrusion switch (optional) WoL (Wake on LAN) iAMT 12.0 (depending on processor) |
| Manageability software | DeskView Client DeskView Instant BIOS Management |
| DeskView components | BIOS Management incl. Security Inventory Management Driver Management Alarm Management |
| Supported standards | DMI (Desktop Management Interface) SMBIOS (System Management BIOS) PXE (Preboot Execution Environment) WMI (Windows Management Instrumentation) WBEM (Web Based Enterprise Management) CIM (Common Information Model) |
| Manageability link | http://www.fujitsu.com/fts/manageability |

Miscellaneous

| | |
|---|---|
| Keyboard on (Special Fujitsu keyboard required) | Keyboard on (Special Fujitsu keyboard required) |
| Keyboard on with one key (KBPX Eco, KB521) | Keyboard on with one key (KBPX Eco, KB521) |
| Keyboard on with 2 keys (CTRL+CTRL) with PS2 or special USB keyboards | Keyboard on with 2 keys (CTRL+CTRL) with PS2 or special USB keyboards |
| Keyboard on with any key (USB) | Keyboard on with any key (USB) |
| Thermal management | Thermal management |
| Low Power Active Mode | Low Power Active Mode |
| | Extended lifetime |

Warranty

| | |
|---|--|
| Warranty period | 3 years (depending on country) |
| Warranty type | Bring-In / Onsite Service (for countries within region EMEA, for all other countries depending on local regulations) |
| Warranty Terms & Conditions | http://support.ts.fujitsu.com/warranty |
| Product Related Services - the perfect extension | |
| Recommended Service | - 9x5, Onsite Response Time: Next Business Day |
| Spare Parts availability | 5 years after end of product life |
| Service Weblink | http://www.fujitsu.com/fts/services/support |

Recommended Accessories

Wireless Mouse Touch WI910

The Fujitsu Wireless Mouse Touch WI910 has a special touch sensitive surface that recognizes when your hand touches the mouse even before you move it. This provides nearly instantaneous wake-up from the intelligent energy saving sleep mode. Unbeatable responsiveness combines with features like switchable resolution, and three programmable buttons for a unique user experience.

Order Code:
S26381-K465-L100

SOUNDSYSTEM DS E2000 Air

The new more powerful SOUNDSYSTEM DS E2000 Air gives you impressive, well-balanced sound throughout the frequency band. It is an unbeatable USB speaker set with a surprisingly small form factor. The robust satellite speakers are decorated with a deluxe piano finish and the base is adorned with warm ambient lighting.

Order Code:
S26391-F7128-L600

Keyboard KB950 Phone

The KB950 Phone is a modern and slim line USB keyboard with integrated Skype for business features. This extremely reliable, high-speed input device is the perfect way to manage incoming and outgoing calls, even when the system is locked. Three additional keys make it easy to accept and end calls and mute your microphone during a call. Easy number dialing is assured with the numpad. The integrated 61 x 12 mm display shows the time and date, the user status and shows incoming call data in the form of the calling number and caller ID.

S26381-F950-L4** (**:
Country specific variation)

More information

Fujitsu products, solutions & services

In addition to FUJITSU Desktop ESPRIMO D958, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Desktop ESPRIMO D958, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/fts/ESPRIMO

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright 2018 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions GmbH
Website: www.fujitsu.com/fts
2018-07-04 EM-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright 2018 Fujitsu Technology Solutions GmbH