

IN128HDx

High Value Network Projector

Part #: IN128HDx

InFocus

The InFocus IN128HDx projector features high brightness and contrast, low cost, and strong sound—perfect for classrooms, offices, or anywhere you need to capture your audience's attention.

Key Features

- ◆ Full HD (1920 x 1080) native resolution
- ◆ 4,000 lumens of brightness
- ◆ 15,000:1 contrast ratio
- ◆ Long 5,000-hour lamp life
- ◆ Compact and lightweight for easy portability
- ◆ HDMI connectivity
- ◆ Manage over the network
- ◆ Powerful built-in 10-watt speaker
- ◆ Instant on/off
- ◆ Blu-ray 3D capable (over HDMI)



High Brightness and High Contrast

The image quality of the projector will not disappoint. Get bright, clear images in any light, plus exceptional sharpness, darker blacks, and whiter whites thanks to a high contrast ratio. Presenters can also instantly dim the projector with the remote control to divert the audience's attention on to the presenter and extend lamp life.



3D Support

The IN128HDx supports multiple forms of 3D—including HDMI, Blu-ray, 3D broadcasting, video games, and PC connectivity. All your audience needs are 144Hz DLP link 3D glasses to seamlessly synchronize with the image for an awesome 3D experience.

Save Now and in the Future

The ultra-low purchase price is just the beginning. The lamp is long-lasting and there are no filters to replace. Use the Eco Blanking feature to instantly dim the screen to divert your audience's attention onto you. Activate this feature when the projector isn't being used and lower the lamp's power usage down to 30%. This saves energy and significantly extends the life of the lamp, saving you even more money.

Compact powerhouse

Weighing in at only 5.1 pounds (2.3 kg), this projector's compact size makes it easy to move from room to room. The

IN128HDx is also installation-ready, offering Crestron RoomView and AMX Device Discovery. Simply use the RJ45 connection to access these networking features.

Specifications*

Projector	IN128HDx
Resolution – Native	Full HD (1920 x 1080)
Resolution – Maximum	WUXGA (1920 x 1200)
Display Technology	DLP
Video Standard Compatibility	NTSC, PAL, SECAM, 480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Speakers	Mono 10W x 1
Lamp Brightness	4,000 lumens
Lamp Brightness – Low Power	3,200 lumens
Lamp Life	2,000 hours
Lamp Life – Low Power	5,000 hours
Lamp Power	260W
Lamp Power – Eco Mode	65W
Replacement Lamp	SP-LAMP-094
Contrast Ratio	15,000:1
Color Wheel	6 segment, 2x speed
Number of Colors	1.07 billion
Aspect Ratio	16:9
Aspect Ratio Compatibility	4:3, 16:10
Lens Type	Manual focus
Projection Offset	15
Keystone Correction	± 40°
Connectors – Inputs	3.5mm stereo audio x2, HDMI 1.4 (rear), Composite video, S-video, VGA x2
Connectors – Outputs	3.5mm audio output, Monitor out (VGA)
Audible Noise	< 34 dBA at 0°F / -17.8°C
Audible Noise – Eco Mode	< 32 dBA at 0°F / -17.8°C
Included Accessories	Power cord, Remote, VGA cable, Documentation
3D Support	1080p @ 120 HZ via HDMI, DLP Link 3D glasses required
Product Warranty	2 years
Lamp Warranty	6 months
Accessories Warranty	90 days
Operating Conditions	32 to 104°F at 0 to 10000 ft / 0 to 40°C at 0 to 3048 m
Menu Languages	English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Swedish, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Persian, Portuguese, Vietnamese, Czech, Romanian, Hungarian
Security Features	User PIN, Security bar, Security lock slot
Approvals	UL and c-UL, FCC, CE, CCC+CECP, KCC, NOM, PCT/CU/EAC, PSB, SABS, SASO, CB, Nemco/GS, KC
Throw and Zoom	
Throw Ratio – Minimum	1.15:1
Throw Ratio – Maximum	1.50:1
Zoom Ratio	1.3:1
Shipping	
Product Dimensions	3.9 x 11.5 x 8.7 in / 99.1 x 292.1 x 221 mm
Product Weight	5.1 lbs / 2.3 kg
Shipping Dimensions	7.8 x 14.3 x 12 in / 196.9 x 362 x 304.8 mm
Shipping Weight	7.1 lbs / 3.2 kg

* Product specifications, terms, and offerings are subject to change at any time without notice.

Accessories

Universal Projector Ceiling Mount (PRJ-MNT-UNIV)
Motorized Electric Projector Screen: 130 in., 16:10 (SC-MOTW-130)
Projector Lamp for the IN120x, IN120STx, and IN2120x Series (SP-LAMP-094)
LiteShow 4 DB+ Dual Band Wireless Adapter (INLITESHOW4DB+)
Presenter 4 RF Remote with Laser Pointer (HW-PRESENTER-4)
Replacement Remote for Meeting Room Projectors (HW-NAVIGATOR-4)
Soft Carry Case for Value Projectors (CA-SOFTVAL-2)
Projector Ceiling Mount System (Black) (PRJ-MNTKIT-UNIVB)
Projector Ceiling Mount System (White) (PRJ-MNTKIT-UNIVW)
VGA Cable (36 ft / 11 m) (SP-VGA-11M)
Projector Lock by PC Guardian (SEC-LOCK-01)
Manual Pull Down Projector Screen: 92 in., 16:9 (SC-PDHD-92)
Manual Pull Down Projector Screen: 106 in., 16:9 (SC-PDHD-106)
DLP Link 3D Glasses by XPAND (X103-EDUX3-R1)
SMART Mount Adapter (INA-SMRTADPT)
1 Year Extended Warranty for IN1XX Projectors (EPW-PJV1)
2 Year Extended Warranty for IN1XX Projectors (EPW-PJV2)