

















































AKG DMS700 V2 DIGITAL WIRELESS SYSTEM A professional system for broadcast, installed and live sound applications. Features 155MHz frequency range for RF flexibility, 512-bit encryption, IR link setup data, low-cut filter, 3-band EQ, dbx compressor/limiter and all metal construction. The DSR 700 receiver has a frequency response of 25Hz-20kHz, (2) XLR balanced, (2) 1/4" TS unbalanced outs, (1) AES/EBU XLR socket (48kHz) and BNC wordclock in. Both the handheld and bodypack transmitters feature 8 hour battery life, 7-segment battery status indicator and variable output power (10/20/30/50mW).

The DPT700 bodypack transmitter has a 25Hz-20kHz frequency DPT700 DHT700 response, manual 10dB and 20dB additional gain and a proprietary TB3M/3-pol. mini-XLR socket input. The DHT700 handheld transmitter has a frequency range of 35Hz-20kHz and a choice of D5, D7 or C5 elements. D5, D7 or C5 elements. All components selectable in Band 1: 548.1 - 697.9 MHz; Band 2: 710.1 - 864.9 MHz.

ITEM	DESCRIPTION	PRICE
D2K/UU	. 2-channel true diversity wireless receiver with 2 antennas and power cord	1799.00
DPT700	. Bodypack transmitter with (2) AA batteries and belt clip	1099.00
DHT700D5	. Handheld transmitter with AKG D5 dynamic supercardioid	
	element, (2) AA batteries, stand adapter, windscreen	1099.00
DHT700D7	. Handheld transmitter with AKG D7 dynamic supercardioid	
	element (2) AA batteries, stand adapter, windscreen	
DHT700C5	. Handheld transmitter with AKG C5 condenser cardioid elemer (2) AA batteries, stand adapter, windscreen	

SR4500

PT4500

HT4500

AKG WMS4500 SERIES UHF WIRELESS **SYSTEMS** The SR4500 diversity receiver features

auto-setup and scan functions that analyze the local RF environment and make it easy

to find usable frequency groups. Using multiple bands, and in ideal conditions it is possible to use up

to 70 channels simultaneously. Audio outputs include a balanced XLR, and unbalanced 1/4" jack connector. It may be integrated into a HiQnet<sup>TM</sup> system with the optional HUB4000Q. With special PC control software the SR4500 receiver can be remotely controlled and monitored from a PC. The PT4500



WMS4500 Band 3, TVCH 30-35	570.000-600.000MHz
WMS4500 Band 2, TVCH 19-23	500.000-530.000MHz
WMS4500 Band 1, TVCH 44-48	650.100-680.000MHz
ORDERING INFO:	OPERATES IN THIS RANGE:
(sold separately, options shown below).	

WINS4300 Ballu 3	, 17011 30-33	370.000-000.000MHZ	
ITEM	DESCRIPTION	V A	PRICE
SR4500	. UHF diversity receiver only, wi	th (2) 1/4-wave antennas,	
	rack hardware, power supply,	HiQNet™ compatible	749.00
HT4500	. UHF handheld transmitter only	(no capsule), up to 50mW RF output	599.00
		y	
CU4000	. Optional charging unit, holds	up to (2) HT4500 or PT4500	
	transmitters for battery back	to be charged inside transmitter,	
	1hr quick charging, includes	2 batteries	569.00
PS4000-W	. Multi-coupler for SR4500 rece	eiver, (2) BNC antenna in,	
			529.00
PSU4000	. Central power supply, powers	up to (12) SR4500 plus antennas	
		tters or (3) CU4000 chargers,	
	also powers HPA4000/HUB400	00Q	479.00
001=3004Z00030.	. BP4000 rechargeable battery	for WMS4000/4500 series	116.64
HUB4000Q	. Ethernet interface - connect i	up to (8) SR4500 receivers to	
	HiQnet™ network, includes P	SU01/4000 power supply 1	199.00
SRA2B-W	. Active, directional antenna (n	eed 2) use only with MKA5 cabling	379.00
		a (need 2)	
AB4000	. In-line signal amplifier for AK	G wireless systems (need 2)	249.00
		g active antennas to PS4000W (need 2)	
C520L	. Headworn mic, cardioid conde	enser w/mini XLR connector	
	for PT4500 bodypack		179.00
HT4500 UHF Ha	ndheld Transmitter Capsule	es	
D5WL/1	. Supercardioid dyn. mic capsule	for HT4500 transmitter, 70Hz-20kHz.	99.00
C5WL/1	. Cardioid cond. mic capsule fo	r HT4500 transmitter, 65Hz-20kHz	199.00
		r HT4500 transmitter, 20Hz-20kHz	
C417/L	. Omni lavalier mic w/mini XLR	connector for PT4500 bodypack	99.00
		(LR connector for PT4500 bodypack	

**AKG WMS40 MINI VOCAL &** INSTRUMENTAL WIRELESS

**SYSTEMS** Both systems are easy to use and share the same brilliant sound. Unique HDAP (High Definition Audio Performance) technology ensures the best possible, realistic sound at any time. The receiver features 3 LEDs (ON/OFF, RF OK, CLIP), switched mode power supply and (1) 1/4" output. The cardioid



handheld transmitter features metal grill cap, ON/OFF/MUTE switch. The bodypack transmitter is compatible with all AKG micromics. Transmitters operate for 30hrs on a single AA battery.

ORDERING INFO:	OPERATES IN THIS FIXED FREQUENCY:
WMS40 US Band A: 45A	660.700MHz
WMS40 US Band B: 45B	661.100MHz
WMS40 US Band C: 45C	662.300MHz

ITEM	DESCRIPTION	PRICE
WMS40-INST-MINI	.UHF wireless instrument system with bodypack	99.00
WMS40-VOCAL-MINI	.UHF wireless vocal system with handheld mic	99.00




AKG WMS470 UHF WIRELESS MIC SYSTEM High performance frequency agile multi-channel wireless mic system for clubs, stage, seminars and house of worship applications. Features 30Hz-20kHz frequency range, auto frequency setup, 16 pre-programmed frequencies within the same band, pilot tone, IR link for frequency and setup data and 14 hours battery life (with single AA lithium battery). The receiver has (1) XLR balanced, (1) 1/4" TS unbalanced outputs and is compatible with WMS4500 antenna splitters. Transmitters feature battery status info in hours, low battery data transmission to receiver, up to 50 mW RF output power and more. The handheld transmitter comes with either a C5 or D5 element and stand adapter. Each system ships with rackmount kit, (2) 1/4 wave UHF antennas, (1) AA LR6 battery and power supply

and power supprj.	
ORDERING INFO:	OPERATES IN THIS RANGE
WMS470 BAND 1	650.000-680.000MHz
WMS470 BAND 7	500.100-530.500MHz
WMS470 BAND 8	570.100-600.500MHz
WMS470 BAND 9	600.100-605.900MHz & 614.100-630.500MHz

ITEM	DESCRIPTION	PRICE
WMS470-D5/VOCAL	Handheld system w/D5 dynamic supercardioid capsule	499.00
WMS470-C5/VOCAL	. Handheld system w/C5 condenser cardioid capsule	559.00
WMS470-INSTRUMENTAL.	. Instrumental system with instrument cable	499.00
	. Lav/Headmic system with CK99 lavalier, C555 headmic	629.00
WMS470-SPORT	. Headmic system with C544L headmic	579.00
SR470	. Receiver only	299.00
HT470/C5	. Handheld transmitter only, with C5 dynamic capsule	279.00
HT470/D5	. Handheld transmitter only, with D5 condenser capsule	219.00
PT470	. Bodypack transmitter only	219.00
CU400	. Fast charger for both the HT470	
	and PT470 transmitters, 2 slots	279.00
SRA2B-W	. Active directional antenna	379.00
RA4000B/W	. Active omnidirectional antenna	179.00
PS4000-W	. Active antenna splitter	529.00
	. Antenna booster	
	. Antenna cable, 2ft	
	.Antenna cable, 20ft	

Follow us!





AKG PERCEPTION SERIES UHF WIRELESS The SR45 receiver features XLR and 1/4" jack outputs, 8 selectable frequencies, up to 30MHz bandwidth selection, as well as adjustable squelch threshold and audio level controls. The PT45 bodypack is compact, has 10mW of RF output, and the battery compartment cover doubles as a tool for setting input gain. The PT45 bodypack, and HT45 handheld transmitters offer up to 8 hours of operation on a single AA cell.

ORDERING INFO		OPERATES IN THIS RANGE:	
Default "A" Band		530.025-559.000 MHz	
ITEM	DESCRIPTION		PRICE
		K99L cardioid lapel mic	299.00
PERCEPTION-INST-SET	Instrument system v	v/MKG-L guitar cable	
		/C544L cardioid, condenser mic	
PERCEPTION-VOCAL-SET	Handheld system w/	/HT45 cardioid, dynamic mic	249.00



### **AUDIO-TECHNICA ARTIST ELITE SERIES FREQUENCY AGILE UHF WIRELESS**

SYSTEMS The AEW 4000 single channel and AEW 5000 dual channel systems feature 996 selectable UHF channels per band with True Diversity, dual compander circuitry, Tone Lok<sup>TM</sup> squelch, multiple channel coordination, highly visible white-on-blue LCD displays, and Intelliscan  $^{\mathrm{TM}}$ , which finds and sets the best available frequencies on all linked receivers. Stores up to 5 presets with names. Bodypack transmitters feature locking battery doors. The AEW 3000 receiver has XLR and 1/4" TS outputs as well as 1/4" headphone out. The AEW 5000 features an onboard Ethernet interface for monitoring/controlling system parameters (includes software), XLR, 1/4" TRS and 1/4" headphone out. (Models shown below are in the "AD" band. For the "AC" band, replace the "AD" with "AC" at end of part number.) Please call for assistance in configuring systems.

AC band, TVCH 25-30	ORDERING INFO:	OPERATES IN THIS RANGE:
ITEM DESCRIPTION PRICE  Single-Channel UHF Systems  AEW-4110AD Bodypack system, no mic	AC band, TVCH 25-30	541.500-566.375 MHz
Single-Channel UHF Systems  AEW-4110AD  Bodypack system, no mic.  AEW-4230AD  Handheld system w/AEW-T3300a cardioid condenser mic.  1119.00  AEW-4240AD  Handheld system w/AEW-T34100a cardioid dynamic mic.  969.00  AEW-4250AD  Handheld system w/AEW-T5400a cardioid condenser mic.  1289.00  AEW-4250AD  Handheld system w/AEW-T6100a hypercardioid dynamic mic.  969.00  AEW-4313AD  Combo system w/1 bodypack, (no lapel mic),  & AEW-T3300a HH  1479.00  Dual-Channel UHF Systems (partial listing, more combo systems available)  AEW-5244AD  Dual-handheld system w/2 AEW-T4100a cardioid dynamic mics.  2939.00  AEW-5255AD  Dual-handheld system w/2 AEW-T400a cardioid condenser mics  CALL  AEW-5266AD  Dual-handheld system w/2 AEW-T6100a  hypercardioid dynamic mics.  2939.00  AEW-5313AD  Dual-combo system w/1 bodypack,  (no lapel mic) & 1 AEW-T3300a HH  3119.00  AEW-5413AD  Dual-combo system w/2 bdypacks,  (no lapel mic) & 2 AEW-T3300a HH  CALL  Components (partial listing)  AEW-F3200D  Dual-channel UHF diversity receiver only  AEW-F3200D  Dual-channel UHF diversity receiver only  AEW-T3200A  AEW-T3200D  AEW-T3200B  AEW-T3200B  Bodypack transmitter only for 4000/5000 series.  439.00	AD band, TVCH 44-49	655.500-680.375 MHz
AEW-4110AD Bodypack system, no mic. 899.00 AEW-4230AD Handheld system w/AEW-T3300a cardioid condenser mic. 1119.00 AEW-4240AD Handheld system w/AEW-T4100a cardioid dynamic mic. 969.00 AEW-4250AD Handheld system w/AEW-T4100a cardioid dynamic mic. 969.00 AEW-4250AD Handheld system w/AEW-T6100a hypercardioid dynamic mic. 969.00 AEW-4260AD Handheld system w/AEW-T6100a hypercardioid dynamic mic. 969.00 AEW-4313AD Combo system w/1 bodypack, (no lapel mic),	ITEM DESCRIPTION	PRICE
AEW-4230AD Handheld system w/AEW-T3300a cardioid condenser mic 1119.00 AEW-4240AD Handheld system w/AEW-T4100a cardioid dynamic mic 969.00 AEW-4250AD Handheld system w/AEW-T6100a cardioid condenser mic 1289.00 AEW-4260AD Handheld system w/AEW-T6100a hypercardioid dynamic mic 969.00 AEW-4313AD Combo system w/1 bodypack, (no lapel mic), 1479.00  Dual-Channel UHF Systems (partial listing, more combo systems available) AEW-5244AD Dual-handheld system w/2 AEW-T4100a cardioid dynamic mics 2939.00 AEW-5255AD Dual-handheld system w/2 AEW-T5400a cardioid condenser mics CALL AEW-5266AD Dual-handheld system w/2 AEW-T6100a hypercardioid dynamic mics 2939.00 AEW-5313AD Dual-combo system w/1 bodypack, (no lapel mic) & 1 AEW-T3300a HH 3119.00 AEW-5413AD Dual-combo system w/2 bodypacks, (no lapel mic) & 2 AEW-T3300a HH CALL Components (partial listing) AEW-R4100D Single-channel UHF diversity receiver only 669.00 AEW-R5200D Dual-cannel UHF diversity receiver only 2129.00 AEW-T1000AD Bodypack transmitter only for 4000/5000 series 439.00	Single-Channel UHF Systems	
AEW-4240AD Handheld system w/AEW-T4100a cardioid dynamic mic	AEW-4110ADBodypack system, no mic	
AEW-4250ADHandheld system w/AEW-T5400a cardioid condenser mic		
AEW-4260ADHandheld system w/AEW-T6100a hypercardioid dynamic mic	AEW-4240ADHandheld system w/AEW-T4	100a cardioid dynamic mic 969.00
AEW-4313ADCombo system w/1 bodypack, (no lapel mic), & AEW-T3300a HH	AEW-4250AD Handheld system w/AEW-T5	400a cardioid condenser mic 1289.00
& AEW-T3300a HH	AEW-4260ADHandheld system w/AEW-T6	100a hypercardioid dynamic mic 969.00
Dual-Channel UHF Systems (partial listing, more combo systems available)         AEW-5244AD       Dual-handheld system w/2 AEW-T4100a cardioid dynamic mics       2939.00         AEW-5255AD       Dual-handheld system w/2 AEW-T5400a cardioid condenser mics       CALL         AEW-5266AD       Dual-handheld system w/2 AEW-T6100a         hypercardioid dynamic mics       2939.00         AEW-5313AD       Dual-combo system w/1 bodypack,       3119.00         AEW-5413AD       Dual-combo system w/2 bodypacks,       CALL         (no lapel mic) & 2 AEW-T3300a HH       CALL         Components (partial listing)         AEW-R4100D       Single-channel UHF diversity receiver only       669.00         AEW-R5200D       Dual-channel UHF diversity receiver only       2129.00         AEW-T1000AD       Bodypack transmitter only for 4000/5000 series       439.00	AEW-4313ADCombo system w/1 bodypac	k, (no lapel mic),
AEW-5244ADDual-handheld system w/2 AEW-T4100a cardioid dynamic mics 2939.00 AEW-5255ADDual-handheld system w/2 AEW-T5400a cardioid condenser mics CALL AEW-5266ADDual-handheld system w/2 AEW-T6100a hypercardioid dynamic mics		
AEW-5255ADDual-handheld system w/2 AEW-T5400a cardioid condenser micsCALL AEW-5266ADDual-handheld system w/2 AEW-T6100a hypercardioid dynamic mics	Dual-Channel UHF Systems (partial listin	g, more combo systems available)
AEW-5266AD        Dual-handheld system w/2 AEW-T6100a hypercardioid dynamic mics         2939.00           AEW-5313AD        Dual-combo system w/1 bodypack, (no lapel mic) & 1 AEW-T3300a HH        3119.00           AEW-5413AD        Dual-combo system w/2 bodypacks, (no lapel mic) & 2 AEW-T3300a HH        CALL           Components (partial listing)        CALL           AEW-R4100D        Single-channel UHF diversity receiver only        669.00           AEW-R5200D        Dual-channel UHF diversity receiver only        2129.00           AEW-T1000AD        Bodypack transmitter only for 4000/5000 series        439.00	AEW-5244ADDual-handheld system w/2 /	AEW-T4100a cardioid dynamic mics 2939.00
hypercardioid dynamic mics   2939.00	AEW-5255ADDual-handheld system w/2 /	AEW-T5400a cardioid condenser micsCALL
AEW-5313AD        Dual-combo system w/1 bodypack, (no lapel mic) & 1 AEW-T3300a HH.        3119.00           AEW-5413AD        Dual-combo system w/2 bodypacks, (no lapel mic) & 2 AEW-T3300a HH        CALL           Components (partial listing)         AEW-R4100D        Single-channel UHF diversity receiver only.        669.00           AEW-R5200D        Dual-channel UHF diversity receiver only.        2129.00           AEW-T1000AD        Bodypack transmitter only for 4000/5000 series.        439.00	AEW-5266ADDual-handheld system w/2 /	AEW-T6100a
(no lapel mic) & 1 AEW-T3300a HH       3119.00         AEW-5413AD      Dual-combo system w/2 bodypacks,	hypercardioid dynamic mics	2939.00
AEW-5413ADDual-combo system w/2 bodypacks, (no lapel mic) & 2 AEW-T3300a HH	AEW-5313ADDual-combo system w/1 bod	ypack,
(no lapel mic) & 2 AEW-T3300a HH         CALL           Components (partial listing)         669.00           AEW-R4100D         Single-channel UHF diversity receiver only         669.00           AEW-R5200D         Dual-channel UHF diversity receiver only         2129.00           AEW-T1000AD         Bodypack transmitter only for 4000/5000 series         439.00		00a HH 3119.00
Components (partial listing)       AEW-R4100D     Single-channel UHF diversity receiver only     669.00       AEW-R5200D     Dual-channel UHF diversity receiver only     2129.00       AEW-11000AD     Bodypack transmitter only for 4000/5000 series     439.00		
AEW-R4100DSingle-channel UHF diversity receiver only		00a HHCALL
AEW-R5200DDual-channel UHF diversity receiver only		
<b>AEW-T1000AD</b> Bodypack transmitter only for 4000/5000 series	AEW-R4100DSingle-channel UHF diversity	y receiver only
	AEW-R5200DDual-channel UHF diversity	receiver only
AT8628AJoining plate for two 4000/5000 series receivers		
	AT8628AJoining plate for two 4000/5	000 series receivers

### (A) audio-technica. always listening...

**AUDIO-TECHNICA 2000 SERIES UHF** 

FREQUENCY-AGILE SYSTEMS This series delivers professional performance, easy setup, automatic scanning, true diversity reception, Tone LockTM tone squelch & other advanced features. Any of its 10

ORDERING INFO:



channels may be used together, eliminating frequency coordination problems. The metal half-rack receiver features XLR & unbalanced 1/4" outputs, ground lift switch, an included rackmount kit and detachable UHF antennas. The ATW-T220a handheld transmitter features the PRO 41 capsule for maximum feedback rejection & lasting dependability. Bodypack transmitter has switchable 10mW/30mW RF output. Both bodypack & handheld transmitters operate on 2 AA cells for up to 9hrs of use. Under ideal conditions, it has up to a 300' operating range. Models shown below are in the "AD" band. For opposite band substitute "AI" for "AD".

OPERATES IN THIS RANGE

AD Band, TVCH 45-48	656.125-678.500 MH	Z
Al Band, TVCH 16-19	487.125-506.500 MH	Z
ITEM DESCR	RIPTION	PRICE
ATW-2110AD Bodyp	oack system, no mic	299.00
ATW-2129AD Lavali	ier system w/AT829CW unidirectio	nal lapel mic 349.00
ATW-2192AD Heady	worn system w/AT892CW omni con	idenser head mic, black 549.00
ATW-2192AD-TH Same	as above but beige	549.00
ATW-2193AD Earset	t system w/BP893CW MicroEarset	
	condenser mic, black	
	as above but beige	
	held system w/ATW-T220 cardioid	
	recharging station for ATW-T220	
and/o	or ATW-T210 bodypack transmitter	s in any combination.
w/auti	to shut-off feature	199.00
	wideband 400-900MHz) active un	
	m. provides (2) 1-in/4-out RF char	
	W-2000/3000 series	
	g plate kit for (2) 2000 series rec	

**AUDIO-TECHNICA 3000 SERIES UHF** WIRELESS SYSTEMS This series features 996 (C/D bands) and 1001 (I band) selectable UHF frequencies in 25kHz spacing over 3 bands with true diversity protection from RF hits and dropouts. Nine precoordinated frequency scan groups simplify selection of usable frequencies. Maximum operating range is up to 300'. Frequency response is 70Hz-15kHz. Receiver features



OPERATES IN THIS RANGE

XLR and 1/4" TS outs and a ground lift switch. Transmitters are powered by (2) AA batteries, for 6-8hrs of operation. Bodypack features a backlit screen for low-light situations, a locking battery door, and 3-position sliding cover to prevent accidental shutoff or channel switching. It has a switchable RF power output of 10mW or 30mW. The handheld transmitter in the ATW-3141 system features the same dynamic capsule as the AE4100 microphone. The handheld transmitter in the ATW-3171 system features the same condenser capsule as the ATM710. The handhelds also feature dual color LED's power/mute LED to indicate on/mute status. Systems are backed with a 2-year manufacturer warranty. (Models shown below are in the "BD" band. For the "BC" or "BI" bands, replace the "BD" with "BC" or "BI".) Please call for assistance configuring systems.

BC band, TVCH 25-30	541.500-566.375MHz
BD band, TVCH 44-49	655.500-680.375MHz
BI band, TVCH 16-20	482.000-507.000MHz
ITEM DESCRIPTION	PRICE
ATW-3110BDBodypack system, no mi	ic399.00
ATW-3131BDBodypack system w/AT8	31CW cardioid lapel mic
ATW-3192BDHeadworn system w/AT8	392CW omni condenser headmic, black 639.00
ATW-3192BD-THAs above but beige	639.00
ATW-3193BDEarset system w/BP893	CW MicroEarset omni condenser mic, black 579.00
	re579.00
ATW-3141BDHandheld system w/ATV	V-T341 dynamic cardioid mic transmitter 499.00
ATW-3171BDHandheld system w/ATV	V-T371 condenser cardioid mic transmitter. 599.00
ATW-T341BDHandheld transmitter w	ith cardioid dynamic element
and stand clamp	259.70
ATW-T371BDHandheld transmitter w	ith cardioid condenser element
and stand clamp	
	OMHz) active unity-gain antenna distribution
	n/4-out RF ch, for ATW-2000/3000 series 399.00
	ng (2) 3000 Series receivers 26.79





















































ORDERING INFO:

Quick Purchase: 800-476-9886





























ATW-A49

ATW-A54P

ATW-A64P

ATW-A3C

ATW-A3D

ATW-DA49





















### (A) audio-technica. always listening...

**AUDIO-TECHNICA FREEWAY 700** 

SERIES UHF WIRELESS These diversity UHF wireless systems have 8 selectable frequency-coordinated channels. You can use up to 8 systems simultane-

ously under ideal conditions. The ATW-R700 diversity receiver has a button for

automatically selecting an open channel, LED channel display, antenna and AF peak indicators, balanced XLR and unbalanced 1/4" output connections. The transmitters operate on AA cells with battery life yielding 8-12hrs. The ATW-T701 bodypack transmitter has a separate guitar/mic trim control. ORDERING INFO: **OPERATES IN THIS RANGE:** 

Default Dan	a TV CH OC OO	542.125-561.250MHz	_
ITEM	<b>DESCRIPTION</b> Bodypack system — ATW	P	RIC
ATW-701	Bodypack system – ATW	-R700 receiver,	
	ATW-T701 bodypack, no	microphone22	29.9
ATW-701/G	Instrument system - ATV	N-701 w/AT-GCW guitar cable 24	19.9
		-701 w/PR08HECW mic29	
ATW-701/H92	2 Headworn system — ATW-	-701 w/Pro92cW omni condenser, black 33	39.9
		beige33	
		-701 w/lavalier mic26	
	Handheld system – ATW		,
	dynamic unidirectional l	HH transmitter mic24	19 9
TW-R7NN	IJHE receiver only		16.1
TW_T702	Handhald dynamic unic	directional transmitter only	20.1
		ES FOR AT WIRELESS SYSTEMS	
ITEM	DESCRIPTION		RIC
		tor for AT Unipak bodypacks)	20.0
418296W	Lapel mic, cardioid condens	er	)Z./
		ni w/out power module14	
		d dynamicS	
TRUONE-GW. NTM75CW	Hoodworn mic, cardioid con	denser	72.U 15.0
		ing condenser	
		iser	
PRN92CW	Headworn mic omni conden	iser, black	29 N
PRN92CW-TH	As PR092CW but beige		29.0
Accessories			
T-GCW	Guitar input cable for AT IIn	iPak body-packs1	197
AFW-DA550C	UHF (540-565MHz) active III	nity-gain antenna distribution system	/
2110000	for "C" band, provides two		
	up to 4 receivers (for 3000/	1000/5000 series) 63	33.7
AEW-DA660D	As AEW-DA550C but (655-6	80MHz) for "D" band	33.7
	WELL LE LE LOID	:	

# Kaltman (reations

for ATW-3000 series wireless.

As ATW-A3C but 655-680MHz operation.

"First to Market" Audio Products .



.Wideband directional 6dB gain antenna, mounts on wall/mic stand .. 283.22

.UHF (wide-band 440-900MHz) active unity-gain antenna distribution

system, provides two 1 in-4 out RF channels for up to 4 receivers (for 2000/3000 series)

592 41

592.41

35.87

35 87

.Pair of UHF (541-567MHz) powered dipole antennas.... .As ATW-A54P but 655-681MHz

Pair of UHF (540-565MHz) 1/2 wave antennas w/BNC conn

SOFTWARE This software program is a PC-based RF spectrum analyzer that automatically charts open white space to aid those operating wireless mic systems, in-ear monitors, etc. Software features include split-screen displays, priority monitored frequencies, instant-save custom profiles, logging with date & time stamps, etc. All

KALTMAN CREATIONS INVISIBLE WAVES RF SPECTRUM ANALYZER

system packages include an electronics/receiver package, built-in rechargeable battery pack, AC adapter/charger, multiple antennas, USB-PC cable and a carrying case. DESCRIPTION ITEM IW1800 ....RF Spectrum Analyzer Software for VHF/UHF analysis, 9kHz-1.8GHz .... 1554.80

IW3500 ......RF Spectrum Analyzer Software, 9kHz-3.5GHz ......

Follow us!

R300-RX HT-300
EV R300 SERIES UHF WIRELESS SYSTEMS This series features ClearScan™

ŧ

for finding the next open channel available, and EZsync<sup>TM</sup> which allows for infrared transfer from receiver to transmitter for error-free setup. The R300 receiver has 32 preset channels, with compatible groups allowing up to 8 systems to operate simultaneously under ideal conditions. It has 1/4" TS, and XLR outputs, and a frequency response of 80Hz-18kHz (±2dB). The BP-300 bodypack terminates to a TA4 connector for use with all EV lapel/headworn mics. The HT-300 handheld transmitter features a PL22 cardioid, dynamic head. All transmitters feature metal construction, have 8mW RF outputs, and operate up to 14 hours using 2 AA alkaline cells. Please specify band A or B when ordering, or call for assistance.

ORDERING INFO:		OPERATES IN THIS RANGE:	
A Band - TVCH 38-41		618.000-634.000 MHz	
B Band - TVCH 48	3-51	678.000-694.000 MHz	
ITEM	DESCRIPTION		PRICE
R300-L	Bodypack system w/ULM1	8 unidirectional lapel mic	299.00
R300-E	Headworn system w/HM-3	3 omnidirectional headworn mic	309.00
R300-HD	Handheld system w/PL22	cardioid, dynamic mic	299.00
R300-RX	R300 series receiver only		199.00
		y, w/PL22 head	
BP-300	Bodypack transmitter onl	y	109.00
APD4+	Antenna/Power distribution	on for up to (4) R300 receivers	419.00
RM-300	Rackmount kit for (1) R30	00 receiver	27.00
RMD-300	Rackmount kit for (2) R30	00 receivers	36.00

### EV RE2 WIRELESS MICROPHONE

**SYSTEM** Features include Advanced ClearScan<sup>TM</sup> Auto Channel Select, over 1,112 selectable channels, automatic or manual group and channel selection, LCD display, balanced XLR and 1/4" outputs (mic/line switchable), battery level status, and more. The RE2 Pro versions feature dual "high/low" power switching on the transmitters, & interchangeable capsules on the handheld transmitters. Bodypack specific features include magnesium case and detachable antenna. The



Pro receiver features rack-mount kit with front antenna extensions. Please call to determine best frequency band when ordering. Please note that the RE2 Pro series components are only available in the "A" band.

ITEM DESCRIPTION PRICE

RE2 UHF Series Single Channel Systems ORDERING INFO: **OPERATES IN THIS RANGE:** G Band, TVCH38-42 614.000-642.000MHz A Band, TVCH 43-48 648.00-676.000MHz 449.00 RE2-N2. Handheld system w/ND267A dynamic cardioid head. Handheld system w/ND767A dynamic supercardioid head RE2-N7 499.00 RE2-410 Handheld system w/RE410 cardioid condenser head.... 519.00 RE2-510 Handheld system w/RE510 supercardioid condenser head 519.00 RE2-COMBO Combo system w/ND267A HH, & bodypack w/ULM21 lav mic 699.00 RE2-BP Bodypack system, no mic... 449.00 RE2-L10 Lavalier system, w/OLM10 omni lapel mic 489.00 RE2-L21 Lavalier system, w/ULM21 unidirectional lapel mic 519.00 RE2-E-BEIGE Bodypack system, w/RE97 headworn mic, omni, beige. 699.00 RE2-G... Guitar/instrument system w/cable... 469 00 Antenna/power distro system for up to (4) RE2 series receivers.... 419.00

RE2-PRO UHF Series - sold as components		
ORDERING INFO:	OPERATES IN THIS RANGE:	
A Band, TVCH 43-48	648.00-676.000MHz	
RE2-PR0-71910X1 Single-channel UHF receiver only, includes rackmt kit, antennas		
PHTU-2D7 HH transmitter only w/ND2	767A dynamic supercardioid head 399.00	
PHTU-2C5 HH transmitter only w/RE5	510 supercardioid condenser head 359.94	
WTIL 2 Magnasium hadunaak	240.07	







Audio-Technica's upgraded 2000 Series wireless systems take care of you on stage. The setup is easy and the sound is clear, so you can focus all your energy where it belongs. Forget about its 10 compatible channels, two available frequency bands. Tone Lock squelch, true diversity operation, switchable antenna power & optional charger. And connect with your audience. Wherever your love for performance leads you, experience more.

- Clear sound and rock-solid, dependable performance
  Automatic frequency scanning
  10 compatible user-switchable channels in one of
  two UHF frequency ranges
  Automa power available for powered antennes
  & other in-line RF devices

- Charger available for ATW T220a & ATW T210a transmitte
  True Diversity operation & Tone Lock \*\* tone squelch
  Metal half-rack receiver with XLR & 1/4\* output jacks
  Switchable transmitter power & ground-lift switch
  Available in handheld, headworn, lavaller and
  body-pack system configurations.

















































**LECTROSONICS** DIGITAL **HYBRID** WIRELESS™ Combines 24bit digital audio with an analog FM radio link to provide outstanding audio quality and the extended operat-

ing range of the best analog wireless systems. Overcomes channel noise in a dramatically new way, digitally encoding the audio bit-stream in the transmitter and decoding it in the receiver, yet sending the encoded information via an analog FM wireless link. This proprietary DSP algorithm eliminates a compander circuit and its artifacts, and preserves the RF spectral footprint of analog FM designs to simplify multi-channel coordination with existing analog wireless systems. Here are the frequency blocks/ detailed choices for most of the Lectrosonics products shown in this section:

ORDERING INFO:	OPERATES IN THIS RANGE:
Block 470, TVCH 14-18	470.100-495.600MHz
Block 19, TVCH 16-20	486.400-511.900MHz
Block 20. TVCH 21-25	512.000-537.500MHz
Block 21, TVCH 25-29	537.600-563.100MHz
Block 22, TVCH 29-33	563.200-588.700MHz
Block 23, TVCH 34-37 (note 608-614MHz	
may not be used in US for wireless)	588.800-614.300MHz
Block 24, TVCH 38-42	614.400-639.900MHz
Block 25, TVCH 42-46	640.00-665.500MHz
Block 26, TVCH 46-50	665.600-691.100MHz



LECTROSONICS DIGITAL HYBRID WIRELESS™ TRANSMITTERS Includes a wide array of compatible transmitters to work with their portable and studio receivers. Models with the prefix "SM" are part of the "Super Mini" series of transmitters which are ideal when concealment is a primary concern. They feature membrane switches, LCD interfaces, current servo input for maximum dynamic range, accept a wide variety of mic types, and have an aluminum splash-proof housing. The RM remote unit allows you to change settings while units are hidden on the talent. The "UM" model features spring loaded belt clips, servo-input amps for a wide range of gain, and a tough extruded powder-coated housing. The MM400C is a water-resistant mini transmitter with 100mW RF output for long range w/minimal interference. Bodypacks have locking Switchcraft TA5 connections unless otherwise noted. Please specify frequency block when ordering - it must match the receiver's frequency in order to work. Call for assistance.

ORDERING INFO:	OPERATES IN THIS RANGE:
Blocks 470, 19, 20, 21, 22, 23, 24, 25, 26	See chart above in this column
ITEM DESCRIPTION	PRICE
Bodypack Transmitters/Accessories	
SMQVSuper miniature, variable outpu	
	es up to 7.5hrs of operationCALL
SMVSuper miniature, variable outpu	
	ICALL
	9V cellCALL
MM400CWater-tight transmitter, 100mW	
	CALL
	/ cellCALL
	M" modelsCALL
	SM w/antenna pointing upCALL
	SM w/antenna pointing downCALL
SMDBCBelt clip for SMD/SMQ models Handheld & Plug-On Transmitters	UALL
UTHandheld transmitter, no capsu	le 100mW RF output nower switch can be
	uator & tone controls, uses (1) 9V cell, uses
	CALL
	nsmitterCALL
	itterCALL
HHHandheld transmitter only, w/o	
power, uses (2) AA lithium cells	for approx 10hrs battery life,
requires capsule (options below	)CALL
HHCCardioid capsule for the HH	CALL
	HCALL
HMPlug-on transmitter, for 100/20	
	uick-lock XLR connector, (2) AA cells
(up to 12hrs using lithium cells)	). 40Hz-20kHz +1dBCALL

### **LECTROSONICS** R400 **STUDIO**

**RECEIVER** The R400A is a tabletop UHF receiver fully compatible with all Lectrosonics 400 Series Digital Hybrid Wireless<sup>TM</sup> transmitters, 200 Series and 100 Series analog transmitters and IFB transmitters. It features 256 user selectable frequencies, and its proprietary audio processing includes a digital signal processor (DSP) for very low distortion, a superior signal to noise ratio and 2 independent audio outputs (1 balanced XLR,



and lunbalanced.1/4"). A built-in RF spectrum analyzer is included to conduct site surveys and find interference-free operating frequencies. Please specify frequency block when ordering, or call for assistance.

ORDERING INFO:		OPERATES IN THIS RANGE:	
Blocks 470, 19, 20,	21, 22, 23, 24, 25, 26	See chart in previous colun	nn
ITEM	DESCRIPTION		PRICE
R400A	Table-top receiver with A	A500RA whip antennas,	
	and power supply		CALL
R4NNA/RMPR4NN-1		nanel w/front_mount antennas	CALL



### LECTROSONICS VENUE SERIES/VF FIELD MODULAR RECEIVER SYSTEMS


The Venue receiver system is a modular UHF design that operates with Digital Hybrid Wireless<sup>TM</sup> transmitters, and DSP modes to support a variety of analog transmitters. It consists of a master assembly that accepts 1 to 6 plug-in receiver modules (VRS or VRT modules, not included with base unit). The VRMWB master assembly includes an antenna multi-coupler, computer communications interface, and the rackmount for the receiver modules. It has 6 balanced XLR audio outputs, 50ohm BNC antenna inputs and outputs, USB, RS232 port for the computer interface, as well as an LCD interface for setup and monitoring. Operates on 10 to 18 VDC from external power supply (included). Includes LecNet2<sup>TM</sup> software for simplifying setup and monitoring your system. All functions and settings can be made via software, including firmware updates through the USB and serial ports. System requires a pair of antennas with coax feed cables. The VR-FIELD assembly is a portable version that shares most of the feature set, but operates on 10-18VDC from an external power supply or NP1style battery. Choose from the ALP models of Log Periodic Dipole Array wideband directional antennas or the SNA600 omnidirectional collapsible dipole listed below.

ORDERING IN		OPERATES IN THIS RANGE:
Blocks 470,	19, 20, 21, 22, 23, 24, 25, 26	See chart in previous column
ITEM VRM-WB-MST	DESCRIPTION R-ASSEMBLY	PRIC
	230MHz wideband master asser	
	(no receivers or antennas includ	
VR-FIELD-ASS		ow)CAI
VICTIEED AGO	230MHz wideband field assemb (no receivers or antennas includ	
		ow)CAI
VRS		fixed bandwidth front-end design
VDT		nts, select frequency blockCAI
VK1	.Tracking receiver module only- s of advanced frequency tracking	
		uency blockCAI
ALP500		model for fixed applicationsCAI
		gn for decreased wind loadingCAI
	.Shark fin antenna, with onboard	
	Phantom powered from Venue n	naster assemblyCAI
SNA600		adjustable from 550MHz to 800MHz
		n. Includes mounting kitCAI
		x, BNC/BNC 2ftCAI
		ght angle BNCCAI
		BNC/BNC, 15ftCAI
		NC/BNC, 25ftCAI
		NC/BNC, 50ftCAI NC/BNC, 100ftCAI
ARU 100	LUW 1055 AIITEIIITA CADIE, COAX DI	NO/DNO, 10011

Follow us!

# LECTROSONICS TM400 WIRELESS SYSTEM FOR TEST & MEASUREMENT

This system was designed to provide the ideal link between calibrated test microphones and



ORDERING	INFO:	OPERATES IN THIS RANGE:	
Blocks 47	0, 19, 20, 21 ,22, 23, 24, 25, 26	See chart on previous page	
ITEM	DESCRIPTION		PRICE
R400A	Receiver only		CALL
HM	Plug-on transmitter only, 100ml	V RF output, multi-voltage	
	phantom power, quick-lock XLR	connector, 2AA cells	
	(up to 12hrs using lithium cells	, 40Hz-20kHz ±1dB	CALL

### LECTROSONICS SYSTEMS MICS/ACCESSORIES (PARTIAL LISTING)

ITEM		PRICE
Lectrosonics N		
	Omni lapel mic, w/locking TA5-F connector	
	High-performance omni lapel mic, w/locking TA5-F connector	
M119MC	Omni lapel mic, w/locking micro plug (for MM400C beltpack)	CALL
M152/MC	High-performance omni lapel, w/locking micro plug (for MM400C)	)CALL
M152/WP	Waterproof version of M152/MC (for MM400C beltpack)	CALL
HM172P	Earset mic, single boom (4.15"),	
	omni, condenser, beige, w/TA5-F connector	CALL
RK119	Windscreen for M119 style mics	CALL
RK150	Windscreen for M150/M152 style mics	CALL
Third Party Mo	dels	
AT899CT5	Audio-Technica sub-mini omni lapel mic, w/TA5-F connector, black	CALL
AT899CT5-TH	As AT899CT5 but in "beige" finish	CALL
BP892CT5	Earset mic, single boom, sub-mini,	
	omni condenser, w/TA5-F connector, black	CLL
BP892CT5-TH	As BP892CT5 but in "beige" finish	
B6W4FF05B-LS	Countryman B6 mini lavalier mic, omni, TA5-F connector, black	CALL
MEMWF05B-LS	Countryman EMW (square) lavalier mic,	
	omni, TA5-F connector, black	CALL
E610W5L-LS	Countryman E6 headset mic, w/replaceable cable,	
	omni, TA5-F connector, light beige	CALL



LINE 6 XD-V30/XD-V70 SERIES DIGITAL WIRELESS SYSTEMS These systems commonly offer 24bit conversion, a frequency response of 10Hz-20kHz, latency of less than 4ms, up to >120dB of dynamic range (XD-V70L model), and do not utilize a compander. They utilize two proprietary technologies – DCL<sup>TM</sup> (Digital Channel Lock), which provides an encoded digital transmission that ensures against all types of RF interference from interrupting your audio, and PDP<sup>TM</sup> (Proprietary Data Placement) that incorporates a hybrid frequency-hopping spread-spectrum technology. Each user channel is split into 4 frequencies before being transmitted. The receiver reassembles the signal and the result is reliable operation, even in hostile RF environments. The XD-V30 series has 6 channels always available, a 100' range (line-of-sight), a polycarbonate desktop receiver chassis, internal antennas, and metal transmitter bodies. The handheld transmitter has modeling based on the Shure® SM58® microphone. The XD-V70 series has 12 channels always available, a 300' range (line-of-sight), metal 1/2RU receiver and transmitter bodies, and built-in loop-through antenna distribution system. The V70 handheld transmitter has 7 total mic models (Line 6 DC7, Shure® SM58®, Shure® Beta 58A, Sennheiser® e835, Audio-Technica® AE4100, Audix® OM5, and Electro Voice® N/D767). V70 series systems ship with rack hardware, and antenna front-mount kit w/necessary accessories. All V30V70 series transmitters operate on 2 AA cells (2 included), for up to 8 hours of operation.

ORDERING INFO:	OPERATES AT:
Default Band	2.4GHz
ITEM DESCRIPTION	PRICE
XD-V30Handheld syste	m, 6 channels, table-top, w/cardioid capsule349.99
XD-V30LBeltpack system	n, 6 channels, table-top, w/lav mic, tie clip/windscreen 349.99
XD-V30HSHeadworn syste	m, 6 channels, table-top,
w/uni-direction	al headmic, windscreen
XD-V70Handheld syste	m, 12 channels, 1/2RU w/kit, cardioid capsule499.99
XD-V70LBeltpack system	n, 12 channels, 1/2RU w/kit,
w/lav mic, tie c	lip/windscreen
XD-V70HSHeadworn syste	m, 12 channels, 1/2RU w/kit,
w/omni headmi	c, windscreen 579.99
HS70Headset mic for	r XD-V70 beltpack, comes in beige or black



LINE 6 RELAY SERIES The G30 & G50 are stompbox style systems, while the G90 is a 1RU receiver style system. They all commonly feature Line 6's proprietary companderless digital audio transmission in the 2.4GHz carrier frequency.

2.4GHz carrier frequency. Relay systems use uniquely addressed and encoded signals that are impervious to WiFi networks and Bluetooth® signals. They



produce full-range tones, 10Hz-20kHz frequency response, are low noise with up to 120dB dynamic range, and provide studio-quality resolution with 24-bit A/D conversion. The G30 has a polycarbonate style chassis, 118dB dynamic range, 6 compatible channels, and up to 100° operating range. The bodypack has a 1/4" TS input and operates on 2xAA cells for up to 8hrs use. The receiver has a 1/4" output and controls for channel select and cable tone simulator. The G50 upgrades to a metal chassis, 120dB dynamic range, 12 compatible channels, and up to 200° operating range. The bodypack features a TA4F connection, LED power/audio status, and a LCD power/battery life display. The receiver has a 1/4" output, tuner-pass thru, and channel number/battery life LCD display. The G90 upgrades to a 300° operating range, XLR output, audio status/ transmitter battery life/mute/RF LEDs, and a control for receiver setup. All Relay systems ship with transmitter, receiver, antennas (when applicable), guitar cable, power supply, and batteries.

ORDERING INFO:		OPERATES AT:	
Default Band		2.4GHz	
ITEM	DESCRIPTION		PRICE
RELAY-G30	.6-channel 2.4GHz digital gu w/stompbox receiver		299.99
RELAY-G50	.12-channel 2.4GHz digital g w/pro-stompbox receiver		399.99
RELAY-G90	.12-channel 2.4GHz digital gu	itar wireless system w/1RU receiver	599.99

























































FULLCOMPASS.COM



















































WIRELESS MIC SYSTEMS These systems use the same high definition audio, and DFS20™ technology found in the HD Executive series. They have some audio processing EQ and mixing capability, eliminating the need for external equipment in most cases. Each system ships with a charger base (1- or 2-mic charging docks) and a base station. Mics are purchased separately. The HD Single Channel System has an analog input and output (1/8" TRS), and the HD Dual Channel System has 2 of each, plus the ability to mix both outputs into one. All outputs can be line or mic level. This provides maximum flexibility to use the HD Single/Dual Channel System wherever a wired microphone can be used, making the system perfect for videoconferencing, voice lift and PA applications. Other features include 128-bit encryption, 2hr charge time, and 65' operating range.

ORDERING INFO:	OPERATES IN THIS RANGE:
Default Band	1.92GHz-1.93GHz (UPCS North America)
ITEM DESCRIPTION	PRICE
02-HDSGL-NM HD wireless mic sys	tem, single-channel, analog I/O, no mics 395.00
02-HDDUAL-NM HD wireless mic sys	tem, 2-channel, analog I/O, no mics 595.00



### REVOLABS EXECUTIVE WIRELESS SYSTEMS These systems are ideal for churches, business presen-

tations or any other situation where intelligible speech is a must. They have high-definition audio, 50Hz-20kHz,

CHARGER BASE MICS NOT INCLUDED.

and use the new Revolabs Designed for Speech technology (DFS20 $^{\mathrm{TM}}$ ) for improved intelligibility. HD Executive Systems are available in 4- or 8-channel models. Two systems can be linked together in High Definition Mode to support up to 16 HD wireless mics. Four systems can be linked in Maximum Density Mode to support up to 32 microphones. Connections on the HD base station include terminal block inputs and outputs, terminal block sync bus input and output, DB9 control port, and an Ethernet port. The Venue system is an easy-to-use 2-channel system intended for smaller installations. Connections on the Venue base station consist of 1/4" and balanced XLR inputs and outputs. All models include free HD Control Panel software (available as a download), rackmount ability, 128-bit encryption, 2hr charging time, and 100' operating range.

ORDERING INFO:		OPERATES IN THIS RANGE:	
Default Band		1.92GHz-1.93GHz (UPCS North America	a)
	DESCRIPTION		PRICE
		m, includes receiver and 2-bay charger,	
			751.28
		m, includes receiver and 4-bay charger,	0.411
			CALL
		m, includes receiver and 8-bay charger,	
			CALL
01-HDEXEMIC-11l	Lapel mic/transr	nitter, rechargeable	349.00
01-HDTBLMIC-OM-11	Omnidirectional	tabletop mic/transmitter, rechargeable	349.00
01-HDTBLMIC-DR-11	Directional table	top mic/transmitter, rechargeable	349.00
01-HDXLRMIC-11	KLR adapter for	handheld dynamic mic	349.00
01-HDCOMAN-11	Countryman mic	adapter for earset mic	349.00





REVOLABS MICROPHONES FOR REVOLABS SINGLE/DUAL HD. AND **EXECUTIVE HD SYSTEMS** These feature RF Armor (impervious to RF interference), CD-quality 50Hz-20kHz frequency response, built-in rechargeable battery that yields up to 8hrs of talk time after a full charge, and 128-bit encryption for security.

Jiordo ap to omo or	tam time arter a ran enarge, and rae are energetion for eet	Jan Ity.
ITEM	DESCRIPTION	PRICE
01-HDEXEMIC-11	Wearable lapel style mic, rotatable clip, with earbud, lanyard	349.00
01-HDTBLMIC-OM-11	Tabletop mic, omnidirectional	349.00
01-HDTBLMIC-DR-11	Tabletop mic, unidirectional	349.00
01-HDXLRMIC-11	XLR plug-on transmitter for dynamic mics only (no phantom)	349.00
01-HDCOMAN-11	HD microphone adapter for Countryman E6 or	
	B6 style microphones	349.00
B6W4FF05BRV	Countryman B6 omni mini-lav mic, black, for Revolabs	282.69
E610W5B2RV	Countryman E6i omni headset mic, black, for Revolabs	325.76
E610W5L2RV	Countryman E6i omni headset mic, light beige, for Revolabs	325.76

### REVOLABS SOLO DESKTOP USB WIRELESS

MICROPHONE SYSTEM These are USB microphones with monitoring operating in the 1.9GHz band, that are full duplex wireless up to 100', and encrypted for privacy. The mics themselves are available as a personal clip on, a desktop boundary type in cardioid or omni versions, or even a plug on unit for XLR dynamic mics. Each mic has a 2.5mm phone jack in for headphone or earphone monitoring. Internal rechargeable batteries provide 8 hours talk time. Up to 16 systems can operate together without interference. The base station receiver/charging unit (sold separately) has USB output to connect to any computer (PC including Vista or Mac OS) without the need for special drivers (but do not include mics). RF armor versions have special shielding to eliminate interference from cell phones and other RF devices.



ORDERING INFO: Default Band		OPERATES IN THIS RANGE: 1.92-1.93 GHz (UPCS North America)	
ITEM	DESCRIPTION		PRICE
01-EXEMICEX-BLK-11	. Clip on lapel wire	eless USB mic, w/RF armor	299.00
05-TBLMICEX-DR-11	. Cardioid wireless	tabletop boundary mic, w/RF armor	299.00
05-TBLMICEX-OM-11	. Omni wireless tal	bletop boundary mic, w/RF armor	299.00
06-XLRMIC-BLK-11	. Solo wireless plu	g on for XLR dynamic mics	199.00
02-DSKSYS-LN-NM	Desktop charger,	single chan. USB base station	296.00



# ANSMANN NIMH 1.2V RECHARGEABLE CELLS / CHARGING SYSTEMS FOR

<b>WIRELESS SYSTEM</b>	S	
ITEM	DESCRIPTION	PRICE
AA-RECHARGEABLES	. AA cell, 4-pack, 2850mAh, runs in wirelesss	
	systems 10+ hrs, recycle 1000 times	. 17.99
9VOLT-RECHARGEABLES.	. 9V, 1-pack, 250mAh, runs in wireless systems 4-6 hrs,	
	recycle 1000 times	. 14.50
ENERGY-8-PLUS		
	and 6 AA/AAA's, 3-year warranty	. 84.00
PROFESSIONAL-16	. 1RU charge station for up to 16AA cells (NiCD/NiMH),	
	700mA charge current per cell, charge time 2-3 hours	535.00
PROFESSIONAL-8	. 1RU charge station for up to 8 9V cells, 75mA charge	
	current per cell, charge time 2 hours	495.00
4000042	. Underload capacity tester for alkaline cells and NiMH	
	rechargeables in sizes AAA, AA, C, D and 9V. Indicators in	
	25% steps — determination of the actual remaining cell	
	capacity; includes (1) 9V-battery; 3-year warranty	. 24.99





### SABINE

SABINE SWM4000 (915MHZ) SERIES WIRELESS SYSTEMS Two receivers commonly offer DTV and license free frequencies in the 902-928MHz band, automatic frequency selection, and infra-red transmitter links to make finding clear channels easily. 2 receiver systems choices — a 1/2 rack single channel receiver, and a 1RU frame system that accepts up to 4 tuner modules. The SW40-RH 1/2 rack



receiver has detachable 1/2 wave antennas, 5 segment audio and RF display meters, 25MHz bandwidth, XLR and 1/4" outs, rack hardware and a carrying case are included. The 1RU frame chassis shares the feature set of the rack receiver, but adds XLR and 1/4" per channel, and a simplified audio and RF display meter section on the tuner modules. Handheld transmitters feature IR port for sync, programmable LCD screen, and programmable on/off /mute switch, and mute indicator. Bodypack transmitters feature replaceable antenna, backlit LCD display, on-off/mute switch/mute indicator, IR port for sync, gain adjustment switch, and TA4-F mic input jack.

ORDERING INFO:	OPERATES IN THIS RANGE:
ISM band	902.000-928.000MHz
ITEM DESCRIPTION	PRICE
SWS40-RH-H10-U-M9151-channel handh	neld system,
1/2 rack receiver	, w/Sabine dynamic head395.95
SWS40-RH-T10-U-M915 1-channel lavalie	er system,
1/2 rack receiver	, w/SW10L omni mic
SWS40-R2-H10-U-M915 2-channel handh	neld system,
w/2 modular rcvi	rs, w/Sabine dynamic heads724.95
SWS40-R2-T10-U-M9152-channel lavalie	er system,
w/2 modular rcvi	rs, w/SW10L omni mics724.95
SWS40-R4-H10-U-M915 4-channel handh	neld system,
w/4 modular rcvi	rs, w/Sabine dynamic heads 1295.95
SWS40-R4-T10-U-M9154-channel lavalie	
w/4 modular rcvi	rs, w/SW10L omni mics1295.95



such as Crestron/AMX, and include free remote control software for Windows. They offer up to 34 (6000 series), or 70 (7000 series) channels simultaneously under ideal conditions. Each receiver comes with built-in DSP in the RF circuit. DSP includes FBX Feedback Exterminator, parametric filters, high/low cut filters, compressor/limiter, de-esser, channel mixing (dual receiver only), and modeling of certain popular dynamic and condenser mics, all with instant recall of the settings. Transmitters come with rechargeable batteries which charge in the unit. Outputs are XLR/TRS mic or line level. NDR version has digital audio outputs, RS232 and USB inputs, & is networkable.

ITEM DESCRIPTION PRICE

6000 Series Components	
ORDERING INFO:	OPERATES IN THIS RANGE:
ISM band	902.000-928.000MHz
SW61-R-U-M9 Single channel receiver of	only, 1RU817.97
SW62-R-U-M9 Two-channel receiver on	ly, 1RU 1143.97
SW62-NDR-U-M9 Two-channel receiver on	ly, w/network & digital I/O, 1RU 1588.97
SW65-T-U-M9 Beltpack transmitter only	y 327.97
SW60-H13-U-M9 HH transmitter w/Audix (	DM3 element (w/cradle charger, clip) 436.97
SW60-H15-U-M9 HH transmitter w/Audix (	OM5 element (w/cradle charger, clip) 527.97
SW60-H19-U-M9 HH transmitter w/Sabine	condenser (w/cradle charger, clip) 617.97
SWAGSS-U-M9 Antenna distributor amp	lifier, w/cables & terminators711.97
SWASS-EXT-3-M9 Extension antenna kit (2	), w/connector — gain pot 159.97
7000 Series Components	

7000 Series Components	,,
ORDERING INFO:	OPERATES IN THIS RANGE:
ISM Band	2.400-2.483 GHz
SW71-R-U-M1 Single-channel receiver	only, 1RU817.97
SW72-R-U-M1 Two-channel receiver on	ly, 1RU 1143.97
SW72-NDR-U-M1 Two-channel receiver on	
	y 327.97
SW70H13UM1 HH transmitter w/Audix	
SW70H15UM1 HH transmitter w/Audix	
SW70H19UM1 HH transmitter w/Sabine	
SWA6SS-U-M1 Antenna distributor amp	
SWASS-EXT-3-M1 Extension antenna kit (2	) w/connector-gain pot 159.97
Mics for 6000/7000 Series Transmitters	
SWT41L-C-TA4 Audio-Technica lavalier	
SWT70G-TA4 Instrument cable for bel	tpack35.97



### SACOM DIGITAL SPECTRUM (DS) SERIES DIGITAL WIRELESS MICROPHONE

SYSTEMS Series uses a completely digital wireless signal from transmitter to receiver. Features encrypted signal, 100+ channels, 24-bit/48kHz audio with low latency, rechargeable batteries and docking station. The DS88R modular receiver mainframe is a full 1RU unit, 8 channels, antenna in/out to loop up to 4 (or 32 channels) of receivers with no external antenna (no hub required), a distribution amp, PC or 3rd party remote control (RS232/USB/GPIO/ETHERNET), integrated headphone monitoring system, digital sync and comes with either XLR or Euro-style analog output connections. The DS88R receiver also features OLED screen, auto frequency/ channel allocation, infrared sync feature to link transmitter to receiver channel, bright LED connections status and more. The DS80-T transmitter comes standard with TA4 connection, built-in defeatable omni mic (great for low profile video conference). The DS80H handheld transmitter is designed with a Polane™ soft-touch finish minimizing slippage and has 4 available mic elements. Both the handheld or bodypack transmitters come with soft switches for low/high power modes, PAD and high pass filters, "hard switch" configurable to be on/off, on, mute or bypass. All transmitters include charger.

ITEM	DESCRIPTION	PRICE
DS88R	8-channel receiver mainframe, (8) XLR or	
	Euro-blocks output, wordclock I/O BNC,	
	(2) TNC antenna I/O and docking station charger	CALL
DS80-T	Beltpack transmitter, TA4 connector w/omni mic	505.60
DS80-H-H10	Handheld mic w/Sabine H10 dynamic cardioid capsule	505.60
DS80-H-0M3	Handheld mic w/Audix OM3 dynamic supercardioid capsule	597.37
DS80-H-0M5	Handheld mic w/Audix OM5 dynamic cardioid capsule	615.73
DS80-H-H19	Handheld mic w/Sabine H19 condenser cardioid capsule	634.08



**SAMSON CONCERT 77 UHF SERIES** These are true diversity systems operating on a fixed UHF frequency. The CR77 receiver features a front panel display with large multi-segment audio level and RF level LED meters, and a large rotary volume knob allows easy adjustment of audio output. Its rear panel features balanced XLR and unbalanced 1/4" outputs. The transmitters feature mute switch, gain controls, LED battery level meters, and operate on a single 9V alkaline. 6 systems may be used simultaneously under ideal conditions.

ORDERING INFO:	OPERATES IN THIS FIXED FREQUENCY:
N1, TV CH 42	642.375MHz
N2. TV CH 42	642.875MHz
N3. TV CH 43	644.125MHz
N4. TV CH 43	644.750MHz
N5. TV CH 43	645.500MHz
N6. TV CH 43	645.750MHz

ITEM	DESCRIPTION	PRICE
SW77VSGT	Instrument system, w/CT7 beltpack, GC32 instrument cable	149.00
SW77VSHQ7	Handheld system, w/HT7 supercardioid dynamic element	149.00
SW77VSLM	Lavalier system, w/CT7 beltpack, LM10 omni mic	149.00
222V77W2	Farset system, w/CT7 heltnack, SE10 omni earset mic	179 00





















































5*AMSON* 

















































packs. The transmitter for the lavalier is built into the microphone package. In the headset aerobic system, the transmitter is part of the headband. In the wind instrument system, the transmitter is part of the mic boom. Airline 77 systems operate on  $6\ UHF$  frequencies and use PLL technology for trouble-free reception. All systems come with AC500 power supply, CR77 receiver, and case.

ORDERING INFO:	OPERATES IN THIS FIXED FREQUENCY:
N1, TV CH 42	642.375MHz
N2, TV CH 42	642.875MHz
N3, TV CH 43	644.125MHz
N4, TV CH 43	644.750MHz
N5, TV CH 43	645.500MHz
N6, TV CH 43	645.750MHz

ITEM	DESCRIPTION	PRICE
SW7AVSGF	. Instrument system, w/AF1 (Fender style) transmitter	. 249.00
	. Instrument system, w/AG1 (Gibson style) transmitter	. 249.00
SW7AVSHX	. Handheld system, w/AX1 plug-on transmitter,	
	Q7 supercardioid dynamic mic	. 269.00
SW7AVSCV10	<ul> <li>Vocal/Fitness headworn mic system, w/AH1/Qv10e transmitter,</li> </ul>	
	Qv10e cardioid condenser head mic	. 299.99
SW7AVSCE	. Vocal/Fitness headworn mic system, w/AH1Qv transmitter,	
	Qe hypercardioid condenser head mic	. 349.00
SW7AVSW4	. Wind instrument system, w/AH1/HM40 transmitter, HM40 mic .	. 299.00

### SAMSON AIRLINE MICRO -**UHF WIRELESS SYSTEMS**

These UHF systems are fully rechargeable with included

lithium ion batteries charged by USB DC power inputs on the transmitters and the AR2 receiver. A dock station for the AR2 also has a USB DC input and 1/8" audio output (camera system has a dual dock with same features to secure both the AR2 receiver & AL2 transmitter). The Earset system has an AH2/SE10 transmitter that houses an omni microphone. It is water resistant; a good choice for fitness instructors. The lithium ion battery system offers up to 5-6 hours of operation for the AH2/SE10 and 7-8hrs for the AR2 receiver. The AR2 receiver also has a 1/8" balanced mic/line output, tone squelch auto mute, and includes an AC adapter, charging cables, and a system carrying case. The camera system shares the same AR2 receiver. The AL2 micro transmitter for the camera system includes a LM10 omni lapel mic, and a lithium battery system for 7-8hrs of operation. The camera system is ideal for most small camcorders or DSLR cameras.

ORDERING INFO:		OPERATES AT THIS FIXED FREQUENCY:
N1. TV CH 42		642.375MHz
N2. TV CH 42		642.875MHz
N3. TV CH 43		644.125MHz
N4. TV CH 43		644.750MHz
N5. TV CH 43		645.500MHz
N6, TV CH 43		645.750MHz
ITEM	DESCRIPTION	PRICE
SWAM2SES	EarSet system, w/AH2 mid	ro x-mitter w/built-in SE10 mic,
	AR2 micro receiver, AR2D	dock, accessory cables, and case 249.00
SWAM2SLM10	Camera/Lav system, w/AL	2 micro x-mitter, AR2 micro receiver,
	LM10 lav mic w/3.5mm pl	ug, AR2DT dock, accessory cables,
		er supply, case299.00
Components		
SWAR2	AR2 receiver w/AR2D dock	
SWAH2	AH2/SE10 Earset transmit	ter 114.75

LM10 lav mic w/3.5mm plug

AR2DT double charging dock ..

AD51U power supply & USB Y cable..

Camera kit - w/shoe mount adapter & cables .

AL2 beltpack transmitter.



SENNHEISER EVOLUTION G3 UHF WIRELESS SYSTEMS The receivers commonly feature 1/2 rack width metal housings, true diversity operation, 42MHz bandwidth with 1,680 switchable frequencies (except for LE models), LCD displays, AutoScan for frequency selection, sound check mode to check audio and RF signal during setup, HDX compander, wireless sync of transmitters via infrared interface, integrated EQ, XLR and 1/4" TS output jacks. The compact transmitters have integrated charging contacts (for use with optional charging accessories), use AA cells and will operate up to 8 hours. Frequency response is 25Hz-18kHz. Backwards compatible with G1/G2 series

**EVOLUTION 100 SERIES-G3** The EM100-G3 receiver has a SN ratio of >110dB, and has up to 12 compatible frequencies per bank. It also has a built-in guitar tuner, and cable emulation.

**EVOLUTION 100 LE SERIES-G3** Shares most of the feature set of the 100 Series G3 models but the receiver has a switching 36MHz bandwidth w/1440 available frequencies (no "G" range available, see table below), up to 6 compatible frequencies per bank, and is limited to the MD815 capsule for the handheld transmitter.

**EVOLUTION 300 SERIES-G3** The EM300-G3 receiver has a SN Ratio of >112dB, an ethernet port that allows you to control settings via a computer, and has up to 24 compatible frequencies per bank. No guitar tuner or cable emulation. Bodypack transmitters have configurable mute modes, and switchable RF output power

EVOLUTION 500 SERIES-G3 The EM500-G3 receiver shares the feature of the 300 series but improves to a SN Ratio of 115dB, and has 32 compatible frequencies per bank. 500 series handheld transmitters feature 900 series Sennheiser capsules. Like the 100 series the receivers have a built-in guitar tuner and cable emulation.

ORDERING INFO::	OPERATES IN THIS RANGE:		
A Range, TVCH 21-28	516.000-558.000MHz		
G Range, TVCH 30-37 (except for LE models)	566.000-608.000MHz		
B Range, TVCH 40-47	626.000-668.000MHz		
ITEM DESCRIPTION	PRICE		
100 LE Series Sets with rackmountable receiver (GA3 rackears not included)			
FW110 C2 Presentation act w/hadwacak & ME2 ampi land mis			

ITEM	DESCRIPTION	PRICE
	es Sets with rackmountable receiver (GA3 rackears not include	
EW110-G3	Presentation set w/bodypack & ME2 omni lapel mic	499.95
EW114-G3	Presentation set w/ bodypack & ME4 cardioid lapel mic	499.95
EW115-G3	Vocal set, handheld w/E815 cardioid dynamic capsule	499.95
100 Series S	Sets with rackmountable EM100 receiver (GA3 rackears not inc	luded)
EW112-G3	Presentation set w/SK100-G3 bodypack & ME2 omni lapel mic	599.95
EW122-G3	Presentation set w/SK100-G3 bodypack & ME4 cardioid lapel mic	599.95
EW152-G3	Headworn set w/SK100-G3 bodypack & ME3 cardioid,	
	condenser headset	649.95
EW172-G3	Instrument set w/SK100-G3 bodypack & Ci1 instrument cable	499.95
EW135-G3	Vocal set, handheld w/E835 cardioid dynamic capsule	599.95
EW145-G3	Vocal set, handheld w/E845 supercardioid dynamic capsule	649.95
EW165-G3	Vocal set, handheld w/E865 supercardioid condenser capsule	749.95
100 Series S	Sets with portable EK100 receiver (for camera use) – includes	Ci1
1/8" output c	cable, CL 100 XLR unbalanced output cable, CA2 camera mount	t
EW100ENG-G3	JENG set w/SK100-G3 bodypack, ME2 omni lapel mic,	
	& SKP100 plug-on transmitter (no phantom power)	799.95
EW112P-G3	ENG set w/SK100-G3 bodypack, & ME2 omni lapel mic	599.95
EW122P-G3	ENG set w/SK100-G3 bodypack, & ME4 cardioid lapel mic	599.95
EW135P-G3	ENG set w/SKM835 handheld transmitter, cardioid, dynamic capsule	599.95
300 Series S	Sets with rackmountable EM300 receiver (GA3 rack ears included	ded)
EW312-G3	Presentation set w/SK300-G3 bodypack & ME2 omni lapel mic	849.95
	Presentation set w/SK300-G3 bodypack & ME4 cardioid lapel mic	849.95
EW352-G3	Headworn set w/ SK300-G3 bodypack &	
	ME3 cardioid condenser headset	
	Vocal set, handheld w/E835 cardioid dynamic capsule	
	Vocal set, handheld w/E845 supercardioid dynamic capsule	
	Vocal set, handheld w/E865 supercardioid condenser capsule	
	Sets with rackmountable EM500 receiver (GA3 rack ears included	
	Presentation set w/SK500-G3 bodypack & ME2 omni lapel mic 1	
	Instrument set w/SK500-G3 bodypack, & Ci1 instrument cable	
	3Vocal set, handheld w/E935 cardioid dynamic capsule	
	3Vocal set, handheld w/E945 supercardioid dynamic capsule	999.95
EW500/965-G3	3Vocal set, handheld w/E965 — switchable cardioid or	
	supercardioid condenser capsule1	429.95





SWAL2

SWAR2DT

SWAD51U

SWAR2CAM

SWAS5I M10B

20 24

16.86

COMPUTER AV

SENNHEISER 2000 SERIES UHF WIRELESS SYSTEMS Series features include backwards compatibility with Evolution G1/G2/G3 trans-

mitters, true diversity operation (rackmount receivers only), built-in Ethernet port for linking to PCs, switching bandwidth between 42-75MHz in 25kHz steps, and up to 64 compatible presets per

band. The rack mount receivers (EM2000/ EM2050) feature integrated power supply, and active splitter (up to 8 receivers may be linked w/out using

additional splitters), transformer balanced XLR and 1/4" outputs, scan feature for compatible frequency selection, 4



OPERATES IN THIS RANGE:

selectable EQ presets, HDX compander, built-in guitar tuner, Soundcheck mode for monitoring transmission conditions, and IR sync with compatible transmitters. The EK2000 is a single channel camera mount receiver that uses Adaptive Diversity, and also offers IR sync to all compatible transmitters. The bodypack and handheld transmitters all feature selectable output power of 10/30/50/100mW, external charging contacts, and operate on 2 AA batteries, or optional BA2015 accupack rechargeables. The SK2000 bodypack specifically features cable emulation mode (low, medium, high), sensitivity in 3dB steps, max -60dB, extended frequency response of 25Hz-20kHz, low cut filter, and 3 pin Lemo socket.

A Range, TVCH 21-28	516.000-558.000MHz	
G Range, TVCH 28-40	558.000-626.000MHz	
B Range, TVCH 40-51	626.000-698.000MHz	
ITEM DESCRIPTION	PRICE	
EM2000Single-channel UHF wireless	receiver, 1RU1849.95	
EM2050Dual-channel UHF wireless re	eceiver, 1RU	
EK2000Camera-mount UHF wireless	receiver 899.95	
SK2000XPUHF bodypack transmitter on	ly (no mic)799.95	
SKM2000Handheld transmitter, nickel	or black (note: no capsule included) 786.95	

...Plug-on transmitter, 10/30/50/100mW RF output, supplies phantom pwr... 799.95

SKP2000

ORDERING INFO:

ACCESSORIES (Note: partial listing, call for more info)
Antenna Distribution
AC3200Active broadband antenna combiner for up to 8 dual receivers
or 16 channels may be linked to one antenna, 1RU,
Max input 250mW. Cables not includedCALL
A3700Omni-directional antenna w/integrated AB3700 booster, (each) 1030.50
AD3700Directional antenna w/integrated AB3700 booster, (each) 1117.38
<b>AB3700</b> Antenna booster (each)
A5000CPPassive circularly-polarized UHF antenna (each)
Transmitter Options/Battery Charging Related
MMD835-1BKe835 dynamic cardioid module for G3/SKM2000, black
MMD845-1BKe845 dynamic super-cardioid module for G3/SKM2000, black 189.95
MME865-1BKe865 condenser super-cardioid module for G3/SKM2000, black 299.95
MMD935-1BKe935 dynamic cardioid module for G3/SKM2000, black
MMD945-1BKe945 dynamic super-cardioid module for G3/SKM2000, black 259.95
MMK965-1BKe965 switchable condenser module for G3/SKM2000, black
<b>CL1</b> Instrument cable for SK2000, Neutrik Silent Plug to Lemo connector. 17.22
L2015-G2Charger for 2 BA2015-G2 (requires NT1-120 pwr supply
for 1 station, or NT3-120 for two or three stations)
LA2Charging adapter for SKM2000 handheld transmitters
(requires L2015-G2)
KEN2Color-coded ID rings for SKM2000 handheld transmitters (set of 8) 19.69
Microphones
HSP2Lightweight headmic, w/omni MKE platinum capsule, black, Lemo3 conn.549.95
<b>HSP2-3</b> As HSP2, but in beige
HSP4Lightweight headmic, w/cardioid MKE platinum capsule,
black, Lemo3 conn
<b>HSP4-3</b> As HSP4, but in beige
<b>MKE1-4-3KIT</b> As MKE1-4KIT, but in beige



M-F: 8:30-5:30 CST

# SENNHEISER



SENNHEISER FREEPORT UHF WIRELESS SERIES An easy-to-use diversity wireless system with dynamic processing, 4 switchable frequencies, and capability to operate up to 4 systems without interference in ideal conditions. The EM1 receivers have front mounted antennas, adjustable squelch, balanced XLR and 1/4" output, and have rugged metal housings. The SK2 bodypack transmitter, and SKM3 handheld transmitter operate on one 9V cell yielding up to 10 hrs of use, and have 10mW of RF output power. Frequency response is 80Hz-16kHz.

ORDERING INFO:	OPERATES IN THIS RANGE:
Default Band "B" TVCH 50-51	691.000-693.000MHz
ITEM DESCRIPTION	PRICE
FP12-B Bodypack system w/SK2	bodypack & ME2 omni lapel mic 249.95
FP72-BInstrument system w/SK	2 bodypack & instrument cable 249.95
FP35-B Handheld system w/SKN	3 handheld transmitter,
dynamic cardioid head	249.95
FP72-BInstrument system w/SK FP35-BHandheld system w/SKN	2 bodypack & instrument cable 249.99 13 handheld transmitter,



w/	TSA locking latches	99.99
GM-7W-TSAHo	lds 7 wireless mics w/battery storage, polyethylene construction,	
2 1	ift-out trays with 4 adjustable dividers, w/TSA locking latches 1	49.99
Nylon or EVA R	Pubber Foam Exterior Cases	
GM-1WEVAAEV	A rubber foam, for single 1/2 rack system, front & rear unzips	
for	access, storage for receiver, beltpack, hh x-mitter,	
fle	xible foam receiver cavity dims: 8" L x 8" W x1.75" H	59.99
<b>GM2W</b> Fo	r 2 wireless systems, 600-denier nylon construction,	
2 (	extra-deep 8.5" mic drops, and compartments,	
int	erior receiver dimensions: 8.5" L x 8.5" W x 3.25" H	49.99
CMSW Fo	r 5 wireless systems, nylon construction, 8.5" mic dron	

54 99




LIGHTS

man

ACCESSORIES





For 5 wireless systems, nylon construction, 8.5" mic drop,

Wireless Mic Rack Drawer - 3RU drawer, black powder-coat finish, 16ga steel

Stores 4 wireless mics/bodypacks, foam storage holds 16 AA cells, accessory compartment, plywood dividers, inc lock and key ...

storage compartment for receivers & accessories, interior receiver dimensions: 8.5" x 7" W x 4" H ....

GM5W

GF-WIRFI FSSDRWR



















































SHURE UHF-R SERIES WIRELESS MICS A UHF series with 2400 selectable frequencies (only 320 in X1 band) spanning across 60 MHz bandwidth. Up to 40preset compatible systems per band (11 in X1 band) and up to 160 systems with multiple bands. Stores six 60-channel custom frequency groups. Has a multi-function bit-mapped backlit LCD and includes Wireless Workbench™ software for PC management of networked wireless systems with USB and Ethernet network options. Models shown are components in the G1 band – for alternate bands replace the "G1" with bands shown below on chart, or call for assistance.

ORDERING INFO:	OPERATES IN THIS RANGE:
Band G1, TVCH 14-24 (Note: some metro areas	
have Public Safety Channels in this band –	
call for assistance if using this band)	470.000-530.000MHz
Band H4, TVCH 22-31	518.000-578.000MHz
Band J5, TVCH 32-41	578.000-638.000MHz
Band L3, TVCH 42-51	638.000-698.000MHz
Band X1, (8MHz- 32 channels, max number of	
compatible channels is 11)	944.000-952.000MHz

ITEM	DESCRIPTION	PRICE
UR4S+-G1	. Single-channel receiver, w/2 half-wave antennas,	
	accessory cables, pwr supply	1954.00
UR4D+-G1	. Dual-channel receiver, w/2 half-wave antennas,	
	accessory cables, pwr supply	2889.00
UR5-G1	. Portable ENG bodypack receiver w/TA3M jack, camera	
	shoe mount, stand strap mount, 1/8" headphone out	1199.00
UR2/SM58-G1	. Handheld transmitter w/SM58 head	929.00
UR2/SM86-G1	. Handheld transmitter w/SM86 head	1039.00
UR2/SM87-G1	. Handheld transmitter w/SM87 head	1159.00
UR2/BETA58-G1	. Handheld transmitter w/Beta 58 head	1039.00
	. Handheld transmitter w/Beta 87A head	
UR2/BETA87C-G1	. Handheld transmitter w/Beta 87C head	1159.00
UR2/KSM9/BK-G1	. HH transmitter w/KSM9 condenser head, black	1799.00
UR2/KSM9/SL-G1	. HH transmitter w/KSM9 condenser head, champagne	1799.00
UR1-G1	. Bodypack transmitter w/threaded TA4-F connector	799.00
UR1M-G1	. Micro bodypack transmitter,	
	10mW or 50mW RF power, TA4-F conn	1699.00
UR1MLEM03-G1	. As UR1M but with Lemo connector	
UR3-G1	. Plug-On transmitter for XLR mics	COMING SOON!

### SHURE LAVALIER AND HEADMICS FOR SHURE BODYPACKS

ITEM		PRICE
Lavalier Micropho		
	Omni-directional subminiature lav mic, condenser, black	
WL50T	. As WL50B but tan	. 189.58
WL50W	. As WL50B but white	. 186.71
WL51B	Cardioid subminiature lav mic, condenser, black	. 222.71
WL51W	. As WL51B but white	. 222.71
WL93	Omni-directional micro-lavalier mic, condenser, black	68.54
	. As WL93 but tan	
WL93-6	. As WL93 but w/6' cable	73.11
WL93-6T	. As WL93T but w/6' cable	73.11
WL183	Omni-directional lavalier mic, condenser, black	91.74
WL184	. Supercardioid lavalier mic, condenser, black	. 113.70
WL185	Cardioid lavalier mic, condenser, black	. 107.24
Headset Micropho	nnes	
WH20TQG	Cardioid headworn dynamic mic, black	79.95
	Cardioid headworn condenser mic, black	
	Beta 53 omnidirectional condenser headworn mic. black	
	As WBH53B but tan	
	. Beta 98 condenser instrument microphone, black	



# SHURE

### SHURE PGX PERFORMANCE GEAR® UHF WIRELESS

Performance Gear Wireless brings the superior sound of Shure Microphones together with automatic and IR linked setup features and audio reference companding for easy-to-use systems. The transmitters operate on 2 AA batteries for 8hrs of continuous use.

Have12 channels in simultaneous use (across multiple bands) without interference. The PGX4 is a microprocessor controlled diversity receiver with automatic frequency selection, LED channel display, XLR and 1/4" outputs

ORDERING INFO:	OPERATES IN THIS RANGE:	
Band H6, TVCH 23-25	524.000-542.000MHz	
Band J6, TVCH 31-33	572.000-590.000MHz	
Band L5, TVCH 43-45	644.000-662.000MHz	

ITEM	DESCRIPTION			PRICE
Single Channel	Systems			
PGX14	Bodypack system – PGX1/	PGX4 w/WA302 instru	ment cable, no mic	379.00
PGX14/93	Lavalier system – PGX1/P	GX4 w/WL93 omni lav	v mic	419.00
PGX14/BETA98H	Instrument system – PGX	1/PGX4 w/BETA98H/C	clip-on mic	499.00
PGX14/PG30	Headworn system – PGX1	/PGX4 w/WH20TQG he	eadworn mic	429.00
PGX24/PG58	Handheld system - PGX4	w/PGX2/PG58 HH tra	nsmitter	379.00
PGX24/58	Handheld system - PGX4	w/PGX2/58 HH transi	mitter	399.00
PGX24/BETA58	Handheld system - PGX4	w/PGX2/BETA58 HH t	ransmitter	449.00
PGX24/86	Handheld system - PGX4	w/PGX2/86 HH transi	mitter	449.00
Individual Comp	ponents			
PGX4	Single-channel diversity r	eceiver only		201.00
PGX1	.Bodypack transmitter only	, no mic		198.00
PGX2/PG58	Handheld transmitter w/P	G58 cardioid head		178.00
PGX2/58	Handheld transmitter w/S	M58 cardioid head		198.00
	Handheld transmitter w/E			
PGX2/86	Handheld transmitter w/S	M86 condenser cardi	oid head	268.00
				/

### SHURE SLX UHF WIRELESS SYSTEM

This series offers Shure's patented Audio Reference Companding technology. Utilizing Auto Frequency Selection and Auto Transmitter Setup, the system scans the wireless landscape and identifies a clear channel instantly. With over 960 operating frequencies across 24MHz of UHF bandwidth, users can easily set up to 20 systems (across multiple bands) in a given location. Each rugged metal SLX Wireless receiver uses diver-



sity technology to improve reception and minimize dropouts. The receiver is outfitted with rackmount hardware, detachable 1/4-wave antennas, a backlit LCD display, 1/4" and XLR output connectors, frequency and power lockouts, an inline power supply, and a rear-panel volume control. SLX's handheld and bodypack transmitters have a 300ft operating range, and run on 2 AA batteries for 8hrs of continuous use.

ORDERING INFO:	OPERATES IN THIS RANGE:
Band G5, TVCH 17-22	494.000-518.000MHz
Band H5, TVCH 22-25	518.000-542.000MHz
Band J3, TVCH 31-34	572.000-596.000MHz
Band L4, TVCH 42-45	638.000-662.000MHz
ITEM DECODIDATION	DDIOC

ITEM DESCRIPTION PRICE
Single Channel Systems
SLX14Bodypack system — SLX1/SLX4 w/WA302 instrument cable, no mic 559.00
SLX14/93Lavalier system — SLX1/SLX4 w/WL93 omni lavalier mic 599.00
SLX14/84Lavalier system — SLX1/SLX4 w/WL184 hypercardioid lavalier mic 659.00
SLX14/85Lavalier system — SLX1/SLX4 w/WL185 cardioid lavalier mic 659.00
SLX14/BETA98HInstrument system — SLX1/SLX4 w/BETA98H/C clip-on mic
SLX14/WH30Headworn system — SLX1/SLX4 w/WH30TQG headworn mic
SLX24/58Handheld system — SLX4 w/SLX2/58 HH transmitter
SLX24/BETA58Handheld system — SLX4 w/SLX2/BETA58 HH transmitter
SLX24/BETA87AHandheld system — SLX4 w/SLX2/BETA87A HH transmitter
SLX24/BETA87CHandheld system — SLX4 w/SLX2/BETA87C HH transmitter
SLX24/86Handheld system — SLX4 w/SLX2/86 HH transmitter
SLX124/85/58Combo system — SLX4 w/SLX1, WL185 lavalier mic
and SLX2/SM58 HH transmitter
Individual Components
SLX4Single-channel diversity receiver only
SLX4LAs SLX4 receiver but with logic output for use w/software echo cancellation
& remote battery life monitoring (works with MX690 & MX890) 380.00
SLX1Bodypack transmitter only, no mic
SLX2/58Handheld transmitter w/SM58 cardioid head
SLX2/BETA58Handheld transmitter w/Beta 58 supercardioid head
SLX2/BETA87AHandheld transmitter w/Beta 87A condenser supercardioid head 379.00
SLX2/BETA87CHandheld transmitter w/Beta 87C condenser cardioid head 379.00
SLX2/86Handheld transmitter w/SM86 condenser cardioid head
MX690Boundary mic, cardioid – works with SLX4L
MX890Wireless desktop base (for MX405/MX410 goosenecks) – works with SLX4L338.02







The UR5 is a premium portable wireless microphone receiver component, designed to provide Shure UHF-R\*-class wireless technology, performance and quality for professional broadcast and media production applications. Featuring wide-band frequency tuning, hands-on navigation, rechargeability and a wide variety of mounting options, the UR5 is the clearest choice for wireless portability.

- · Full bandwidth scan & sync at the touch of a button
- 2400 selectable frequencies across 60 MHz bandwidth
- · Audio Reference Companding for crystal-clear audio
- · Feature-rich, hands-on navigation control
- MTx (Multi-transmitter) Mode: Populate multiple transmitter with open frequencies
- · Headphone monitoring output jack
- . Mic & Aux-level balanced output
- Full range of mounting and power options, including Anton/Bauer plate mounting accessories



UR5 Portable Wireless Microphone Receiver



Also available:



VP68 (RPW124) Omnidirectional Wireless Capsule

FULL COMPASS

PRO AUDIO I VIDEO I AV I LIGHTING MUSICAL INSTRUMENTS

800-356-5844
FULLCOMPASS.COM

SHURE

© 2011 Shure Incorporated



















































ORDERING INFO:



**OPERATES IN THIS RANGE:** 

SHURE PG UHF WIRELESS SERIES Single and dual channel frequency-agile UHF wireless systems. Both single and dual receivers feature 1/4" and XLR outputs, microprocessor controlled diversity, internal 1/4" antennas, ABS molded construction, and channel display LED indicators. Handheld and bodypack transmitters feature multi-function LED indicator (power, lockout, mute, low battery), 9V battery operation for 8hrs of continuous use, and a 250ft maximum operating range. A maximum of 9 compatible systems (across multiple bands) may be used at once, with up to 10 selectable frequencies per band available.

DAIIU N7, TVGN ZU-ZO	330.000-340.000WHZ
Band K7, TVCH 34-35	590.000-602.000MHz
Band M7, TVCH 46-47	662.000-674.000MHz
ITEM DESCRIPTION	PRICE
Single Channel Systems	
PG14 Bodypack system – PG1	/PG4 w/WA302 instrument cable, no mic 299.00
PG14/PG185 Lavalier system - PG1	/PG4 w/PG185 cardioid lavalier mic 299.00
PG14/PG30 Headset system - PG1	/PG4 w/PG30 cardioid headset mic 299.00
<b>PG24/PG58</b> Handheld system – PG	4 w/PG2/PG58 handheld transmitter 299.00
Dual Channel Systems	
PG1288/PG185 Combo system w/PG2/	PG58 handheld & PG1/PG185 lavalier 549.00
PG1288/PG30 Combo system w/PG2/	PG58 handheld & PG1/PG30 headworn 549.00
PG188/PG185 Dual-lapel system w/P	G1 bodypacks & PG185 lav mics549.00
PG288/PG58 Dual-handheld system	with PG2/PG58 handheld transmitters 549.00
Individual Components	
PG4 Single-channel diversi	ty receiver 165.00
PG88 Dual-channel diversity	receiver
	only, no mic95.00
	with PG58 cardioid head134.00
PG185-TQG Cardioid condenser lav	valier mic

.... Cardioid condenser headworn mic

SHURE PGX-D SERIES DIGITAL WIRELESS SYSTEMS This series is utilizing 24bit/48kHz digital technology at the 900MHz frequency range, to avoid interference from TV signals. It offers true digital diversity, frequency response of 20Hz-20kHz, (±2dB), an operating range of up to 200', and the ability to use up to 5 systems simultaneously. The PGXD4 receiver features an automatic scan and sync system for easy



setup, durable ABS housing, padded carrying case, and 1/4" and XLR audio outputs. Bodypack and handheld transmitters operate on 2 AA cells, yielding up to 9 hours (handheld models), or 10 hours (PGXD1 bodypack) of operation.

ORDERING INFO:	OPERATES IN THIS RANGE:
Default Band - X8	902.000-928.000 MHz
ITEM DESCRIPTION	PRICE
Single Channel Systems	
PGXD14Instrument system - PGX	D4/PGXD1,
w/WA302 (1/4" to TA4-F)	guitar cable
PGXD14/85 Lavalier system - PGXD4/	
PGXD14/93Lavalier system - PGXD4	
PGXD14/BETA98H Instrument system - PGX	D4/PGXD1, w/Beta98H/C clip-on mic 549.00
PGXD14/PG30 Headworn system - PGXD	
	ser mic479.00
PGXD24/PG58 Handheld system - PGXD	
PGXD24/SM58 Handheld system - PGXD	
PGXD24/BETA58 Handheld system - PGXD	
PGXD24/SM86 Handheld system - PGXD	4 w/PGXD2/SM86 transmitter 499.00
Individual Components	
PGXD4Single-channel digital re	
PGXD1 Bodypack transmitter on	
PGXD2/PG58 Handheld transmitter on	
PGXD2/SM58 Handheld transmitter on	
PGXD2/BETA58 Handheld transmitter on	
PGXD2/SM86 Handheld transmitter on	ly, w/SM86 condenser cardioid head 318.00



### SKB 3I-1711-XLX WATERPROOF CASE FOR SHURE SLX/ULX SYSTEMS A spe-

cialized case with customized foam cut-outs for Shure SLX or ULX wireless systems. Interior foam can hold the receiver, quarter and half wave antennae, handheld mic, bodypack, lavalier mic, batteries, mic clip, and power supply. Complete gasket seal makes



the case watertight (MIL-STD-C-4150J). Other features include trigger-release latch system, rubber over-molded cushion grip handle, and locking loop to accept a customer supplied lock.

ITEM	DESCRIPTION	PRICE
3I-1711-XLX	Waterproof case for SLX/ULX,	
	interior dimensions: 17" L x 11.5" W x 6" D	. 124.99



OPERATES IN THIS RANGE:

470.000-506.000MHz

# SHURE

ORDERING INFO:

Band G3, TVCH 14-20 - Note: some metro areas

have Public Safety Channels in this band -

call for assistance if using this band

SHURE ULX SERIES WIRELESS SYSTEMS These are frequency agile UHF wireless systems with 1400 user-selectable channels, and auto frequency selection. Up to 60 systems are simultaneously compatible within the 3 frequency groups (up to 20 per band). ULX Transmitters feature a 3-segment battery gauge, on/off switch lockout, and frequency lockout. Other features include 8hr battery life, and a -20dB pad on the ULX1 bodypack. ULX standard receivers feature RF presence LED, 5-segment audio meter, 3-segment battery gauge, detachable 1/4 wave antennas, plastic chassis, XLR and 1/4" outputs, mic/line switchable. Rack hardware not included. ULX professional receivers feature 5-segment audio meter, advanced multi-function LCD, 3-segment transmitter battery gauge, squelch adjustment, removable 1/2-wave antennas, frequency and volume lockout, rugged metal chassis, furnished rack hardware, XLR and 1/4" out, mic/line switchable. Components shown are in the G3 band - for alternate bands replace the "G3" with bands shown below on chart, or call for assistance.

Band JI, IVCH 28-3	3	334.UUU-39U.UUUMHZ	
Band M1, TVCH 46-	51	662.000-698.000MHz	
ITEM	DESCRIPTION	F	RICE
ULXS4-G3	. Standard receiver, plastic chas	ssis, no rack hardware included 4	46.00
ULXP4-G3	. Professional receiver, metal ch	assis, rack hardware included 6	16.00
ULXP4D-G3	. Dual Pro receiver, metal chass	is, rack hardware included 12	13.00
ULX1-G3	. Bodypack transmitter		93.00
ULX2/58-G3	. Handheld transmitter w/SM58	head 2	53.00
ULX2/87-G3	. Handheld transmitter w/SM87	hea 30	63.00
ULX2/BETA58-G3	. Handheld transmitter w/Beta5	8 head3	03.00
ULX2/BETA87A-G3	. Handheld transmitter w/Beta8	7A head 30	63.00
ULX2/BETA87C-G3	. Handheld transmitter w/Beta8	7C head30	63.00
UA506	. Rack hardware for single ULXS	34 receiver	25.03
UA507	. Rack hardware for Dual ULXS4	receiver	25.03



# E LEXIBLE SCAUSS DEPENDABLE.



**ULX® WIRELESS** Wireless applications of increased complexity and scale require powerful solutions. Experienced audio engineers and sound contractors rely on Shure ULX wireless systems to achieve clear, dependable wireless sound. An ultra-wide tuning range with up to 62 compatible systems\* guarantees confidence at demanding installations and live sound productions.

\* Dependent on frequency regulations by country and actual spectrum usage including TV.















































SHURE WIRELESS ANTENNAS & ANTENNA DISTRIBUTION ACCESSORIES

Antennas and receivers must be from the same band. Please call us to assist you in choosing the exact part you need.

*= Frequency	choice needed, please call.	
ITEM DE	SCRIPTION	PRICE
SLX/ULX Series	S	
UA844SWB Wi	ideband UHF 4-way active antenna splitter & power distr for SLX	/ULX
se	ries, 470-952MHz, external PS, includes power antenna cables	437.65
<b>UA830USTV</b> In	line RF Amplifier for UA844SWB (470-698MHz)	175.23
UA860SWB 1/	2-wave omni wideband antenna SLX/ULX (470-1100MHz)	278.30
<b>UA400</b> Re	eplacement 1/4-wave antenna (774-865MHz)	23.56
<b>UA400B</b> Re	eplacement 1/4-wave antenna (518-752MHz)	23.56
<b>UA221</b> Pa	ssive antenna/splitter combiner kit for 2 receivers	148.72
UA5051/	2-wave antenna remote mount kit	22.09
UA820*1/	2-wave antenna (required if remote mounting)	30.92
<b>UA440</b> Fro	ont mount antenna kit w/4 2' BNC-BNC coax cables, adapters	111.91
UA806Co	paxial antenna cable, 6'	22.09
<b>UHF-R Series</b>		
UA845SWB Wi	ideband UHF 5-way active antenna & power distr, 470-952MHz,	
int	ternal switching power supply (NOTE: not for use with ULX)	787.51
<b>UA830USTV</b> In	line RF Amplifier for UA845SWB (470-698MHz)	175.23
<b>UA600</b> Fro	ont mount antenna kit for U4S/U4D receivers	47.12
UA820*1/	2-wave antenna (specify frequency band)	30.92
UA870USTV Ac	tive directional antenna (470-698MHz)	239.00
PA805SWB Pa	ssive directional antenna (470-870MHz)	242.39
UA860SWB 1/	2-wave omni wideband antenna UC/UHF-R (470-1100MHz)	278.30
	tive directional wideband antenna (470-698MHz)	
	emote antenna mounting hardware	



SONY UHF SYNTHESIZED WIRELESS MIC SYSTEMS Features of Sony wireless include 188 PLL synthesized tuning, auto frequency search and setup on modular series, tone squelch circuitry that detects Sony transmitters from others, industry-proven channel plan and preprogrammed groups, low battery alarm, LCD screen and user friendly operation. Receivers are available in multiple configurations for permanent install, camera mount, or portable applications. All transmitter and receivers are completely compatible with each other when ordered in same channel group. The MB8N/F base unit frame has a standard Ethernet connection that allows full monitoring of operating status remotely w/supplied software. The bodypack transmitters are compatible with any Sony 4-pin microphone with the "BC" suffix. Please call for system selection assistance

TEM	DECUDIDION		DDICE
<u>42/44, TVCH 42-45</u>		638.000MHz-662.000MHz	
30/32, TVCH 30-33		566.000MHz-590.000MHz	
ORDERING INFO:		OPERATES IN THIS RANGE:	
icase can for syst	CIII 3CICCHOII a3313tailCC	•	

2/44, TVCH 42-45 638.000MHz-662.000MHz	
ITEM DESCRIPTION	PRICE
Receivers/Base Units	
MB8N/F 4-bay networked frame v	
divider for WRU8N receiv	er modulesCALL
MBX66-bay frame, use with W	RU806 receiver modules,
w/built in antenna divide	erCALL
WRU8N(30/32) UHF receiver module only	, for use w/MB8N base unitCALL
WRU806B(30/32) UHF receiver module only	, for use w/MBX6 base unitCALL
WRR861B(30/32) Single-channel UHF cam	era mount receiver onlyCALL
WRR862B(30/32) Dual-channel UHF came	a mount receiver onlyCALL
Transmitters	
WRT8B(30/32) Compact bodypack trans	mitter, 50mW RF
output for long distance	transmissionCALL
WRT822B(30/32) Bodypack transmitter, 20	
WRT8P(30/32) Plug-on transmitter for v	
WRT807B(30/32) HH transmitter for vocals	s (F780 dynamic capsule)CALL
WRT847B(30/32) HH transmitter base unit	
CUF780 Dynamic cardioid capsul	
CUG780 Dynamic supercardioid c	
CUE700 Condenser supercardioid	capsule unit, for critical vocalsCALL
CUE672 Condenser hyper-cardioid s	
CUF117 Dynamic omnidirectional	capsule unit, for interviewsCALL
Accessories/Distribution	
ECM44BC Omni lapel mic	CALL
K1161 Guitar cable for Sony boo	lypacksCALL
	oter cable for Sony bodypacksCALL
WD850/9F UHF antenna divider, out	put for 4 receivers/tunerCALL

# SONY



### SONY UWP SERIES UHF WIRELESS MIC SYSTEMS

This series consists of 4 core elements - a lavalier/body-

pack transmitter, a handheld microphone transmitter, a portable tuner (w/mic stand or hot shoe mount for video), and a tuner module (for a rack chassis). Improved features from the previous generation include metal chassis for use in harsh conditions, auto channel scanning, selectable mic/line inputs, and extended operating time. There are 5 packages, ready-to-go out-of-the-box or configure your own system. The PLL Synthesis technology features stability and low noise transmission for clarity, tone squelch, diversity reception, multi-channel operation (up to 16 simultaneously) and pre-programmed frequencies. Systems operate in 2 frequency bands, TV channels 30-33 (models listed below) or channels 42-45. Please call for system configuration help.

ORDERING INFO:	OPERATES IN THIS RANGE:
30/32, TVCH 30-33	566.000MHz-590.000MHz
42/44, TVCH 42-45	638.000MHz-662.000MHz
ITEM DESCRIPTION	PRICE
Single-channel portable systems-w/came	ra-mounted receivers
UWP-V1/3032 Bodypack system w/omni	-directional lapel micCALL
UWP-V2/3032 Handheld system w/uni-d	lirectional dynamic headCALL
UWP-V6/3032 Combo system w/bodypk & p	plug-on transmitter (no phantom power)CALL
Single-channel systems - w/tuner module	
(use MBX6 frame or SRP-X500/700 mixe	
UWP-X7/3032 Bodypack system w/uni-d	
UWP-X8/3032 Handheld system w/uni-d	
Individual components (partial listing)	
MBX66-bay frame (use with UF	RXM2 tuner modules
	CALL
	y w/omni-directional lapel micCALL
UTX-B2X/3032 Bodypack transmitter onl	
UTX-H2/3032 Handheld transmitter onl	
UTX-P1/3032Plug-on transmitter only	(no phantom power)CALL
URX-P2/3032 Portable receiver only	CALL
URX-M2/3032 Tuner module only (use w	
ORA-INZ/JUJZ rullet illoudle offly (use w	THIDNO OF SINI ASSOCITOR HILLER ATTIPS)OALL



PECIAL PROJECTS AUDIO

SPECIAL PROJECTS AUDIO EVO™ WATER RESISTANT UHF SERIES Headworn model only series with a patent pending design that eliminates the need for a beltpack transmitter. The electronics are placed behind the ear, and not hanging off the back



of the headband. The headband is water and sweat resistant, and comfortable to wear. It has an internal lithium ion rechargeable battery that operates for 2.5hrs (requires 30-minute recharge time), has 10mW of RF output power, and a flexible boom with a noise-canceling bi-directional mic element. The Scan16 receiver has an auto-scan button feature for convenience in finding open frequencies, 16 FCC safe UHF channels, front panel volume control, transmitter recharge port, audio and RF signal metering, and 1/4" TS and XLR outputs.

URDERING IN-F	·U:	UPERATES IN THIS RANGE:	
Default Band, T	VCH 49-51	682.000-698.000MHz	
ITEM	DESCRIPTION		PRICE
SP-EV0-25	Headworn UHF system, w.	/SP-EVO transmitter	649.00
SP-2EV0-25		ransmitters – for fitness installs sets. Note – only one headset	
	may function at a time w	ith one receiver	999.00
SP-EV0	Evo™ UHF headworn tran	smitter/mic only	419.00





**EXPERIENCE MORE :: TRANSPARENCY :.** 



Introducing Audio-Technica's smallest-ever headworn microphone. With its unobtrusive one-inch boom, our new BP893 MicroEarset practically disappears on the face, combining inconspicuous placement and design with clear, natural vocal pickup. Wherever your passion for communication leads you, experience more.

### BP893 MicroEurset Features

- Outstanding clarity and intelligibility
- Lightweight, ergonomic design
- Unabtrusive, 1-inch flexible boom
- · Secure over-the-ear placement
- Extended frequency response for natural vocal reproduction
- For theatrical performances, houses of worship
   & broadcast studios
- · Available in wired and wireless models

















































sule diameters of just 2.6mm, these are ideal for low profile applications. Features an ergonomic under ear hook design that may be used behind either ear, and be worn for hours w/out fatigue. Features a flat 20Hz-20kHz frequency response, high pass filter (power module versions only), and a Parylene protective coating to prolong its life, and stand up to rigors of day-to-day use. All models below are in black; for beige, add -TH to end of part number.

ITEM	DESCRIPTION	PRICE
Wired Versions		
BP892	Headmic, omni condenser, w/55" cable w/locking 4-pin HRS conn. includes AT8539 pwr module, 2 element covers, 2 windscreens, moisture guard, cable clip, case, black	399.00
BP892C	As BP892, less power module, w/55" cable unterminated	289.00
Models for use wit	h Wireless Bodypack Transmitters	
(all are w/out power	er modules, and have 55" cables)	
BP892CW	Black, terminated w/locking 4-pin connector for AT UniPak	299.00
BP892CL4	Black, terminated for Sennheiser systems	
	utilizing Lemo connectors	359.00
BP892CLM3	Black, terminated for Sennheiser Evolution,	
	locking 3.5mm connector	329.00
BP892CT4	Black, terminated for Shure TA4F-type connetor	329.00
	Black, terminated for Lectrosonics TA5F type connector	

**AUDIO-TECHNICA BP893 HEADWORN** CONDENSER MICROPHONE With an ergonomically molded earpiece and 1" boom, this headworn microphone offers inconspicuous placement along with clear, natural vocal pickup. It positions unobtrusively over the ear and its omnidirectional miniature condenser capsule offers outstanding pickup tailored for natural vocals.

DESCRIPTION



It is also ideal for use in violin pickup; wear it over the ear as usual, with no need for clamps on the violin. It has a frequency response of 20Hz-20kHz, and a max SPL of 114dB. The standard model has a locking 4-pin connector and power module, and is compatible with all Audio-Technica UniPack transmitters. All models below are in black; for beige, add -TH to end of part number.

Wired Versions		
BP893	Omni headworn condenser mic w/power module, black	. 349.00
	Headworn condenser mic. no power module.	
DI 0000	55" un-terminated cable	. 239.00
Wireless Bodypa	ck Transmitter Versions	
(all are w/out por	wer modules, and have 55" cables)	
BP893CW	No power module, 55" cable w/ 4-pin connector	
	for AT Uni-Pak systems	. 249.00
BP893CL4	Includes Lemo connector for Sennheiser wireless	
BP893CLM3	Includes locking 1/8" connector for Sennheiser wireless	. 279.00
BP893CT4	Includes TA4F connector for Shure wireless	. 279.00
BP893CT5	Includes TA5F connector for Lectrosonics wireless	. 279.00

### AUDIO-TECHNICA PROSHEX HYPERCARDIOID DYNAMIC

MIC Professional-quality vocal pickup with hands-free operation with a Hi-ENERGY® neodymium element for crisp sound reproduction. It features a low-visibility headband for stable, comfortable fit, and a pivot-mounted flexible mic boom.



CALL

PRICE

ITEM	DESCRIPTION	PRICE
PR08HEX	. Dynamic mic, with XLR	92.67
PRO8HE-CW	. Dynamic mic, for AT bodypacks	92.67



COUNTRYMAN E6/E6I/E6S SERIES EARSET MICS Light and springy, Isomax Earsets clip around the ear, not around the head and never interfere with hairstyles, headphones or hats. Available in hardwired XLR or pre-wired for most wireless bodypack transmitters. The standard E6 series is recommended for daily use by one person, due to its stiff, shape-holding

construction. For users sharing the mic, the E6i series is ideal. It features a soft, flexible boom and a larger silicone rubber earpiece. The E6s series models are made of durable stainless steel and resists makeup and sweat. Ideal for theatre applications, these ultra-compact mics are an alternative to taping a lavalier to the face or hiding it in the hair. The new E6 Flex series combines the slim, springy ear section of a classic E6, while retaining the flexible boom design of the E6i series. All models come standard with 1mm diameter cable. For a thicker, 2mm dia.

cable, add "DURAMAX" to the part number suffix. Please call for part number verification (E6s r

ITEM DESCRIPTION PRICE  ### FIGURE 15	create most comm	non Countryman E6 part numbers.	
caps (flat, bright & very bright), cable, (2) clips (black & white)  E60P[A][B].	ITEM	DESCRIPTION	PRICE
E6DWIAI[B]	E6 Omnidirectiona	al Earset – ships with storage case, windscreen, (3)	protective
E60W[A][B]-[C]	caps (flat, bright &	& very bright), cable, (2) clips (black & white)	
E6 Directional Earset — ships with storage case, windscreen, (2) protective caps (hypercardiod & cardioid), cable, (2) clips (black & white)  E6DP[A][B]			
caps (hypercardiod & cardioid), cable, (2) clips (black & white)  EBDP[A][B].			
EBDP[A][B]. E6 Earset, directional, hardwired			ive
E6DW[A][B]-[C]			
E6i Omnidirectional Earset – ships with storage case, windscreen, (3) protective caps (flat, bright & very bright), cable, 2 clips (black & white)  E6iOP[A][B]. E6i Earset, omni, w/ flex boom, hardwired. CALL  E6iOW[A][B]-[C]. E6i Earset, omni, w/ flex boom, pre-wired for wireless. CALL  E6i Directional Earset – ships with storage case, windscreen, (2) protective caps (hypercardiod & cardioid), cable, (2) clips (black & white)  E6iDP[A][B]. E6i Earset, directional, with flex boom, pre-wired for wireless. CALL  E6iDW[A][B]-[C]. E6i Earset, directional, with flex boom, pre-wired for wireless. CALL  E6s Omnidirectional Earset – ships with storage case, (3) protective caps (flat, bright & very bright), cable, (2) clips (black & white)  E6sOP[A][B]. E6s Earset, omnidirectional, hardwired  E6sOW[A][B] [CHOOSE 1 FOR 1MM CABLE OR 2 FOR 2MM][C]  E6s Earset, omni, pre-wired for wireless bodypack. CALL  E6f Flex Omnidirectional Earset – ships with storage case, windscreen, (3) protective caps (flat, bright & very bright), cable, (2) clips (black & white)  E6XOP[A][B]. E6 Flex Earset, omnidirectional, w/flex boom, hardwired. CALL  E6XOP[A][B] [CHOOSE 1 FOR 1MM CABLE OR 2 FOR 2MM][C]			
caps (flat, bright & very bright), cable, 2 clips (black & white)  E6I0P[A][B]			
EBIOP[A][B]			rotective
EGIOW[A][B]-[C] EGI Earset, omni, w/ flex boom, pre-wired for wireless			
E6i Directional Earset — ships with storage case, windscreen, (2) protective caps (hypercardiod & cardioid), cable, (2) clips (black & white) E6iDP[A][B]. — E6i Earset, directional, with flex boom, pre-wired for wireless. —CALL E6iDW[A][B]-[C]. — E6i Earset, directional, with flex boom, pre-wired for wireless. —CALL E6s Omnidirectional Earset — ships with storage case, (3) protective caps (flat, bright & very bright), cable, (2) clips (black & white) E6sOP[A][B]. — E6s Earset, omnidirectional, hardwired — CALL E6sOW[A][B] [CHOOSE 1 FOR 1MM CABLE OR 2 FOR 2MM][C] E6s Earset, omni, pre-wired for wireless bodypack — CALL E6 Flex Omnidirectional Earset — ships with storage case, windscreen, (3) protective caps (flat, bright & very bright), cable, (2) clips (black & white) E6XOP[A][B]. — E6 Flex Earset, omnidirectional, wflex boom, hardwired — CALL E6XOP[A][B] [CHOOSE 1 FOR 1MM CABLE OR 2 FOR 2MM][C]			
caps (hypercardiod & cardioid), cable, (2) clips (black & white)  EBIDP[A][B]. E6i Earset, directional, with flex boom, hardwired			
E6iDP[A][B]			tive
EGIDW[A][B]-[C] EGi Earset, directional, with flex boom, pre-wired for wireless			
E6s Omnidirectional Earset — ships with storage case, (3) protective caps (flat, bright & very bright), cable, (2) clips (black & white) E6SOP[A][B]			
bright & very bright), cable, (2) clips (black & white) E6SDP[A][B]			
E6SOP[A][B]			aps (flat,
E6SOW[A][B] [CHOOSE 1 FOR 1MM CABLE OR 2 FOR 2MM][C]  E6s Earset, omni, pre-wired for wireless bodypack			0.411
E6s Earset, omni, pre-wired for wireless bodypack			CALL
E6 Flex Omnidirectional Earset – ships with storage case, windscreen, (3) protective caps (flat, bright & very bright), cable, (2) clips (black & white) E6XOP[A][B]	FP20M[V][R] [CHOO?		OALL
tive caps (flat, bright & very bright), cable, (2) clips (black & white)  E6XOP[A][B]	E0 E1 0		
E6XOP[A][B]E6 Flex Earset, omnidirectional, w/flex boom, hardwired			3) protec-
E6XOW[A][B] [CHOOSE 1 FOR 1MM CABLE OR 2 FOR 2MM][C]			0.41.1
	EDYOM[A][B] [PHOOS		CVII
LO FICK Edisci, Ollilli, pic Wilcu for Wilciess bodypack		LO FIEX Laiset, Ollilli, pie-wileu IOI Wileless Douypack	UALL

	50	E6S	00
EG	EGI		7
models have their own part r	numbering scheme.) See	"GUIDE" in this	s listing to help

PRICE DESCRIPTION E6 Flex Directional Model Template - ships with storage case, windscreen 2 protective caps (hypercardiod & cardioid), cable, 2 clips (black & white) . E6 Flex Earset, directional, w/flex boom, hardwired...... E6XDW[A][B][C] ...... As above, pre-wired for wireless bodypack... E6-EARCLIP. . Comfortable, adjustable, extremely low-profile 2-ear support for all Countryman Earsets. Available in left or right mic placement

### — GUIDE —

For Hardwired Versions:

Sensitivity [A] = 5 for normal speech, 6 for theater, 7 for very loud vocals Color [B] = L for Light Beige, T for Tan, C for Cocoa, B for Black

For Pre-Wired Versions for Wireless Bodypack Transmitters:

and tan or black color ..

Sensitivity [A] = 5 for normal speech, 6 for theater, 7 for very loud vocals (on E6s models use HG for general speech, MG for vocals, LG for strong vocals) Color [B] = L for Light Beige, T for Tan, C for Cocoa, B for Black

Connector [C] = Choose based on brand/type of connector and common brand suffixes are listed below. Call to verify which is right for your bodypack.

AKE AKG (TASF), AT = Audio-Technica (Hirose 4 pin), ET = Electro-Voice (TA4F), LS = Lectrosonics (TA5F - M Series over 185), LW = Lectrosonics (MM400), SM = Lectrosonics (TA5F for SM Series), L4 = Lectrosonics (TA5F for UM/LM series),

ST = Sabine (TA4F for SW70), SV = Samson (TA3F for CT3,VT2L, UT1L,T32), AS = Samson (2.5mm for Airline AL1), SL = Shure (all w/TA4F), S3 = Shure (all w/Lemo 3-pin), SR = Sennheiser Evolution (3.5mm), SN = Sony (3.5mm locking - for WRT805, 806,UTXB1, UWP806), NC = pigtail/bare leads





Microphones should be heard, not seen.



# **®** COUNTRYMAN E2 EARSET

At Countryman we make microphones that practically disappear, like our worldfamous E2 Earset. It comes in four colors to blend against a wide range of skin tones and delivers an incredibly even, transparent sound. That's one reason why we're the clear choice in theatres, houses of worship, and everywhere you've never noticed.



Everywhere you've never noticed.



### **HEADWORN MICROPHONES**
















































boom, with a unidirectional element. It provides a similar level of isolation as the E6 omni model at the mouth, but offers a near invisible appearance. It has an equalizing circuit built into the audio connector. Ships with a cable, carrying case, black and white cable clips, windscreen, and protective cap. (NOTE: E2 and E6 cables are not interchangeable.) This series is available for Sennheiser Evo, Lectrosonics, and Shure



TA4F packs.		
ITEM	DESCRIPTION	PRICE
E2P[A][B][C]	E2 Earset mic, unidirectional, hardwired	CALL
E2W[A][B][C][D]	As above, but terminated for wireless body packs	CALL

### How to specify which Earset you need for hardwired versions:

[A]=Sensitivity: 5 for normal speaking, 6 for theater

[B]=Color option: L=Light Beige, T=Tan, C=Cocoa, B=Black

[C]= Cable diameter: 1 = 1mm cable, 2 = 2mm cable

How to specify pre-wired versions for wireless bodypack transmitters:

[A]=Sensitivity: 5 for normal speaking, 6 for theater

[B]=Color option: L=Light Beige, T=Tan, C=Cocoa, B=Black [C]= Cable diameter: 1 = 1mm cable, 2 = 2mm cable

[D]=Connector suffix: SL=Shure (all w/TA4F), SR=Sennheiser Evolution (3.5mm), SM=Lectrosonics SM, UMa and LMa



CROWN CM311A/CM312A/E HEAD-WORN MICS The CM311A increases gainbefore-feedback by as much as 6-12dB, transmitting only the differential of the

front and back elements, increasing rejection of distant sound sources such as monitor loudspeakers and instruments. The CM311A terminates in a belt clip housing that can be phantom powered or battery powered. It has XLR out, as well as a line out, to feed a wireless transmitter. CM312A/E has a standard cardioid element, and has a stripped cable for terminating to various wireless systems.



ITEM	DESCRIPTION	PRICE
CM311A	. Differoid (cardioid element w/noise canceling), XLR connector .	349.00

# **DPA**

DPA 4066/4065 HEADBAND MICS The 4066 headset mic uses an omni cartridge element with 5.4mm vertical diaphragm. The lightweight band is easily bent to fit any head shape in a tight, fixed position and can be used on its own when a headband is not needed. Mic can be worn on both the left and right side of the face. The 4065 models come in a unique flexible design to be worn on either the left or right side of the face. It offers clean, transparent sound quality in addition to lots




of headroom and can handle SPL of up to 144 dB. All models have a double vent protection system with water-resistant materials to prevent humidity-related problems and an input sensitivity of 6 mV/Pa. They terminate with DPA's standard microdot connector. Choose the XLR adapter or an adapter for your wireless beltpack (partial list below.)

ITEM	DESCRIPTION	PRICE
4066-B	. Omni-directional headband mic, 20Hz-20kHz, black	635.00
4066-C	. Omni-directional headband mic, 20Hz-20kHz, brown	635.00
4066-F	. Omni-directional headband mic, 20Hz-20kHz, beige	635.00
4065-BL	. Omni-directional headband mic, 20Hz-20kHz, black, left	568.00
4065-BR	. Omni-directional headband mic, 20Hz-20kHz, black, right	568.00
4065-FL	. Omni-directional headband mic, 20Hz-20kHz, beige, left	568.00
4065-FR	. Omni-directional headband mic, 20Hz-20kHz, beige, right	568.00
Micro-Dot Adapter	S	
DAD6001BC	. XLR, 48V phantom, w/belt clip	99.00
	. For Sennheiser sk50/250/3063	80.00
DAD6003	For Sennheiser sk50/250/3063 For Sony WRT8020/860	
DAD6003DAD6008		93.00
DAD6003 DAD6008 DAD6010	. For Sony WRT8020/860	93.00 87.00
DAD6003	For Sony WRT8020/860For Shure TA4F	93.00 87.00 73.00
DAD6003	For Sony WRT8020/860 For Shure TA4F  for AKG PT40/60/80/81, Samson UT1L/VT2L For Sony WRT805, Sennheiser Evolution/SK300 For Telex TA4F	93.00 87.00 73.00 87.00 73.00
DAD6003	. For Sony WRT8020/860 For Shure TA4F	93.00 87.00 73.00 87.00 73.00



### **EV RE97 SERIES HEADWORN**

MIC These are ultra low-profile,




ITEM	DESCRIPTION	PRICE
RE97TX-BEIGE	. Omni headmic, for EV wireless, beige	. 299.00
RE97TX-BROWN	. Omni headmic, for EV wireless, brown	. 299.00
RE97TX-BLACK	. Omni headmic, for EV wireless, black	. 299.00
RE97S-BEIGE	. Omni headmic, for Shure wireless, beige	. 299.00
RE97S-BROWN	. Omni headmic, for Shure wireless, brown	. 299.00
RE97S-BLACK	. Omni headmic, for Shure wireless, black	. 299.00

### G A 🕰 🗖

### **GALAXY AUDIO ESS LIGHTWEIGHT HEADSETS**

The super lightweight design makes the ESS mics comfortable to wear long periods of time. It rests on one ear and is flexible for easy formation. The mic is omnidirectional with a 1.5" boom and has a 20Hz-20kHz frequency response and -65dB sensitivity. Includes your choice of detachable cable to terminate to wireless transmitters made by Galaxy, Shure, Sennheiser,



PRICE

199 99

199 99

199.99

### **GALAXY AUDIO HSE SERIES HEADSET MICS**

These come as omnidirectional or unidirectional mics in single or dual-ear hook versions. Comes with choice of one cable for use with either Galaxy, Sennheiser, Audio-Technica, Shure or AKG products. Additional cables may be purchased separately. All models have an operating voltage of 1V-10V. Models listed below are beige; please call to order mics and adapters in black or cocoa.

ITEM	DESCRIPTION	PRICE
HSE-OBG	Omnidirectional headset mic, single ear hook, -65dB, 20Hz-20kHz	199.99
HSE-UBG	Unidirectional headset mic, single ear hook, -67dB, 70Hz-16kHz	199.99
HSD-OBG	Omnidirectional headset mic, dual ear hook, -65dB, 20Hz-20kHz	199.99
HSD-UBG	Unidirectional headset mic, dual ear hook, -67dB, 70Hz-16kHz	199.99
CBLSHU	Replacement cable w/TA4F connector for Shure	49.99
CBLAT	Replacement cable w/HIROSE 4-pin connector for Audio-Technica	49.99
CBLSEN	Replacement cable w/3.5mm locking connector for Sennheiser	49.99
CBLAKG	Replacement cable w/TA3F connector for AKG	49.99
CBL25MM	Replacement cable w/2.5mm connector for Galaxy	49.99
AS-HSCLIP	Cable clip for headset mics	9.99
	•	



### LINE 6 HS70 HEADSET MIC HS70 is an adjustable headset micro-

phone for use with XD-series TBP06 and TBP12 belt pack transmitters and other compatible belt packs with a TA4F. Its integrated compact omni-directional condenser microphone helps resist feedback and minimize background noise. Windscreen included.



IIEM	DESCRIPTION	PRICE
HS70	Headset Mic with TA4F connector, comes in beige	
	(shown in picture) or black	139.99





Follow us!



### QUE AUDIO PERFORMANCE SERIES

MICS The performance series includes 3 quality condenser mics; one lavalier and two headworn. All mics feature the 2.5mm full frequency capsule with water resistant enclosure and interchangeable adapter options. The DA04 is an omni lavalier mic with tie clip, case and windsock. The DA12 is an omni, high




SPL headworn mic with adjustable earpiece/boom, with zipper pouch, cable, cable clip and (2) windscreens. The DA15 is an omni headworn mic with an in-ear monitor piece suitable for news, sports, theater, music on stage and a communication headset. It includes (2) detachable cables, (2) windscreens, tie clip and leatherette zip pouch. All models require termination adapters (not included). See listings below.

ITEM	DESCRIPTION	PRICE
DA04A	. Lavalier mic, -35dB sensitivity, black	. 229.00
DA04B	. Lavalier mic, -45dB sensitivity, black	. 229.00
DA12	. Headworn mic, -35dB sensitivity, 140dB max SPL, beige	309.00
DA15	. As above, but with in-ear monitor, beige	. 339.00

QUE AUDIO Q THE TALENT EAR MIC KIT A single ear omni directional headworn mic on a fixed flexible boom. It has a high SPL, -35dB sensitivity and comes with a detachable cable, (2) foam windscreens, (1) tie clip and (1) leatherette carry case. Requires termination adapters (not included). See listings below.

ITEM QTALENT-KIT	DESCRIPTION Earset mic, omni	PRICE 199.00
Adapters (sold	l separately)	
QAD3	Q compact thread (female) to 90° male XLR, requires 48V p	
	power, balanced low impedance connection to digital record	lers,
	standard or camera-mount mixers and pro video camcorder	s 34.99
DAADATL	Audio-Technica adapter, black	34.99
DAADAKL	AKG adapter, Black	34.99
DAADSEL	Sennheiser adapter, black	34.99
DAADSHL	Shure adapter, black	34.99
DAADMIL	Mipro adapter, black	34.99
	Mipro adapter, beige	
DAADJTL	JTS adapter, black	34.99
DAADEVL	Electro-voice adapter, black	34.99
	Sony adapter, black	
DAADSAL	Samson adapter, black	34.99
DAADCHL	Chaiyo adapter, black	34.99
	Chaiyo adapter, beige	
DAADTOL	TOA adapter, black	34.99
DAADSKL	Sennheiser SK50 adapter, black	40.99
DAADLEL	Lectrosonics adapter, black	34.99



RODE HS1 HEADSET CONDENSER MICROPHONE Versatile in application, this headset mic has an ergonomic design that includes 3 axes of adjustment and features a lightweight and flexible tube arm and headband. The MiCon™ connector system allows you to connect your HS1 mic to a variety of wireless systems. Includes, storage case, pop filter, furry windshield, cable, lapel-style clip, adjustment tools, and cleaning wipes.

ITEM	DESCRIPTION	PRICE
HS1-B	. Black headset condenser mic, omni-directional, 60Hz-18kHz	. 299.00
HS1-P	. As above but pink/flesh-colored	. 299.00
MICON-1	. Adapter for Sennheiser SK500, SK300G3, SK100G3,	
	SK500G2, SK300G2, SK2-Freeport	18.00
MICON-2	. 3.5 stereo mini jack adapter (1V minimum power supply)	18.00
MICON-3	. Adapter for Shure UR1, UR1M, ULX1, SLX1, PGX1, PG1	23.00
MICON-4	. Adapter for Audio Technica UniPak	
	Body-Pack Series 1800, 2000, 3000	
MICON-5	. 48V phantom power adapter, 3-pin XLR	27.00
MICON-CABLE-1.2M.	. 1.2m MiCon cable	32.00
MICON-CABLE-3M	. 3m MiCon cable	39.00

## *SAMSON'*

SAMSON SE10/SE50 OMNI **HEADWORN MICS** These are low profile, miniature condenser models. The SE10T offers a 3mm capsule, while SE50 has a 2.5mm capsule. They may be shaped to fit the left or right ear and the retaining band is suitable for fitness applications. The mic has been treated with a water resistant coating for extra protection against sweat and other moisture. They also have a moisture-guard drip ring to further protect the capsule. Includes 3 windscreens, clothing



cable clip, carry case & detachable cable for Samson wireless beltpack transmitters. Mics also include 4 adapters for use with other manufacturer's beltpack systems (Shure, AT, AKG and Sennheiser).

ITEM	DESCRIPTION	PRICE
SE10T	Omni headmic, 3mm capsule, beige	. 99.00
	Omni headmic, 2.5mm capsule, beige	

### **SENNHEISER**

SENNHEISER NB2 HEADMIC ADAPTER The NB2 headmic adapter is designed for the unobtrusive attachment of most other clip-on microphones. The mic cable is easily inserted into the flexible construction of the adapter. The adapter is constructed of flexible metal,




coated with plastic and may be adjusted for either the right or left side of the head.

ITEM	DESCRIPTION		PRICE
NB2	. Headmic adapter,	black or beige finish	59.95

### SHURE

SHURE SM10A-CN HEADWORN MICROPHONE A low-impedance, unidirectional dynamic microphone designed for close-talk, head-worn applications. It is very lightweight with superior noise rejection and a smooth, natural-sounding frequency response. An adjustable pivot on the headband allows the boom to be moved 20° in any direction. The boom also slides out so the mic can be positioned up to 3.5" from the pivot housing. Close-talk design provides excellent isola-



ITEM	DESCRIPTION	PRICE
SM10A-CN	. Headworn dynamic cardioid mic	134.65
RK184WS	. Windscreen	15.68
	(DETAEA The Date 59/54 amoids in male	

SHURE BETA53/BETA54 The Beta 53/54 provides incredible sound quality in an impressively light, inconspicuous and secure headworn design. Features include a detachable and adjustable headband, flexible wireframe with ultra-thin boom blends into jawline for minimal visibility. Versions exist for both hardwired and wireless applications. The wired versions have a detachable in line preamp and require phantom power.

ITEM	DESCRIPTION	PRICE
BETA53	Omni-directional condenser headworn mic, hardwired	349.00
BETA54	Supercardioid condenser headworn mic, hardwired	349.00
WBH53B	. Beta53, omni with TA4F connector for wireless, black	299.00
WBH53T	. Beta53, omni with TA4F connector for wireless, tan	299.00
WBH54B	. Beta54, super-cardioid with TA4F conn. for wireless, black	299.00
WBH54T	Beta54, super-cardioid, with TA4F conn. for wireless, tan	299.00

SHURE WH20/WH30 CARDIOID HEADWORN MICS The WH20 is a cardioid mic that includes a voice-frequency presence peak and a low-frequency roll-off to compensate for proximity effect. An integrated elastic CROAKIES® headband secures the headset comfortably. Includes foam windscreen and clothing clip. The WH30's frequency response is 40Hz-20kHz and included accessories are a

ITEM	DESCRIPTION	PRICE
WH20TQG	Dynamic headset mic with TA4F connector	79.95
WH20QTR	Dynamic headset mic with 1/4" connector	82.68
WH20XLR	Dynamic headset mic with XLR connector	69.77
WH30TQG	Cardioid condenser headset mic with TA4F connector	92.66
WH30XLR	Cardioid condenser headset mic with XLR connector	151.52

foam windscreen and clothing clip. Wired version comes with inline preamplifier.



















































Quick Purchase: 800-476-9886



































ACCESSORIES

















a lapel on in clothing. It comes with a lapel clip and windscreen. Requires 48V phantom power.

ITEM	DESCRIPTION	PRICE
C417/L	.Mic w/mini-XLR connector and integrated phantom power	99.00
B29L	Battery pack for C417	99.00

# (A) audio-technica.

always listening.

AUDIO-TECHNICA ATR3350 OMNI LAPEL The affordable ATR3350 omnidirectional lapel mic is reliable and effective. The newscaster-style electret condenser design has a 50Hz-18kHz frequency response and -54dB sensitivity at a 1000ohm




impedance. Includes battery, 1/4" plug adapter, tie clip, and foam windscreen.

•	• •	•	-	•		
ITEM	DESCRIPTION					PRICE
ATR3350	Omni lapel mic	<b>;</b> .			 	 23.51

AUDIO-TECHNICA PRO70 CARDIOID **CONDENSER LAVALIER MIC This minia**ture condenser microphone provides natural vocal reproduction and is also excellent for full sounding acoustic guitar pickup. It is equipped with a low-frequency roll-off switch to reduce low frequency room noise and a cardioid polar pattern that further isolates the desired sound source. Operates on battery or phantom power and has a 6' cable attached between the mic and power module. Includes mic clip, instrument adapter, windscreen, battery, and soft pouch.

ITEM	DESCRIPTION	PRICE
PR070	Lav/instrument mic, 100Hz-14kHz	. 119.06

AUDIO-TECHNICA AT803/AT831 LAPEL MICS These clip-on lavalier mics were specifically designed for professional video, broadcast and performance applications. Specially tailored response assures crisp, natural voice and instrument pickup in an unobtrusive package. The omni-directional AT803



ITEM	DESCRIPTION	PRICE
AT803	Miniature omni lapel, phantom power or battery	166.97
AT831B	Miniature cardioid lapel, phantom power or battery	179.00
AT831C	Miniature cardioid lapel, phantom only, unterminated	93.99
AT831R	Miniature cardioid lapel, phantom only, no power module	192.77

AUDIO-TECHNICA MT830R OMNI-DIRECTIONAL CONDENSER **LAVALIER MICROPHONE** Designed to be worn as a lavalier or hidden in loose clothing or in the hair, the MT830R provides high intelligibility for lecturers, stage/TV performers and singers. The mic's wide-range capability ensures clean, accurate reproduction. It operates on phantom power only. Clothing clip and windscreen included.

	· ·	
ITEM	DESCRIPTION	PRICE
MT830R	. Includes AT8533 power module, black finish	183.68
MT830C	Includes 55" cable, unterminated, black finish	84.77
MT830CT5	Includes 55" cable with TA5F connector for ATW-U101	
	and Lectrosonics bodypack systems, black finish	118.66
MT830CT5-TH	Same as MT830CT5 with beige finish	118.66
MT830CW	Includes 55" cable with locking 4-pin connector	
	for Audio-Technica UniPak wireless, black finish	93.99
MT830CW-TH	Same as MT830CW with beige finish	93.99

# AUDIO-TECHNICA AT899 SUBMINI OMNI LAPEL MICROPHONE

Only 5mm in diameter with clean, accurate reproduction. Includes 12 accessories. Available in black or beige.

ITEM	DESCRIPTION	PRICE
AT899	With battery/phantom power module and low-cut switch	220.39
AT899CW	With 4-pin AT wireless connector	145.81
AT899CT5	5-pin connector for AT wireless	150.27
AT899C	With bare end cable for custom termination	133.57

# beyerdynamic)

BEYERDYNAMIC TG L55C CONDENSER LAVALIER CLIP-ON MIC This omnidirectional clip-on mic works well for television, film, presentations and theatre applications. The omni



polar pattern of this acoustically balanced lavalier mic allows a lot of flexibility in positioning - it can be worn on a lapel or on the face and disguised with makeup. It is also water and sweat-proof, and is exceedingly insensitive to pop noises. Hardwired with a mini XLRF 4-pin connector for beltpacks. Available in black or tan.

ITEM	DESCRIPTION	PRICE
TG-L55C	Omni lavalier mic. 20Hz-20kHz. 118dB max SPL	189.00

CRI
COUNTRYMAN ISOMAX-B3 OMNI
MICRO LAVALIER MIC The B3
lavalier mic is an amazing 4.6mm
in diameter and virtu-
ally disappears on the
wearer. An omni-direc-
tional condenser mic, the B3 has
an ultra-flat frequency response from
10Hz-25kHz with SPL handling to 150dB. A rug-
ged Kevlar-reinforced cable provides extremely low
handling noise. The B3 is moisture and makeup resistant
with an easily washable protective screen. Five colors are available: Black

k, White, Light Skin, Cocoa and Gray (models listed below are Black). The B3 may be ordered with XLR/phantom termination or pre-wired for a variety of wireless transmitters.

•		
ITEM	DESCRIPTION	PRICE
B3P4FF05B	B3 lavalier mic, XLR	180.24
B3W4FF05B-AT	B3 for Audio-Technica, 4-pin	182.67
B3W4FF05B-SA	B3 for Samson, 6-pin	182.67
B3W4FF05B-SV	B3 for Samson, 3-pin	174.07
B3W4FF05B-S3	B3 for Sennheiser, 3-pin	203.80
B3W4FF05B-SL	B3 for Shure TA4F	174.07
B3W4FF05B-S0	B3 for Sony, 4-pin	203.80
B3W4FF05B-TS	B3 for Telex TA4F	174.07
B3W4FF05B-TT	B3 for Telex LEMO, 4-pin	182.67
B3W4FF05B-VS	B3 for Vega TA4F	174.07
B3W4FF05B-NC	B3 with 2-wire pigtails	148.33
B3WSB	Replacement windscreen	8.00
ABCBELTCLIP	Replacement beltclip	13.03
AXBPM	Battery module	110.54

COUNTRYMAN ISOMAX-B6 MICRO LAPEL MIC The B6 is the world's smallest lapel mic. At only .1" in diameter, the B6 offers a 40Hz- 25kHz response, is available in four colors and has a Kevlar reinforced cable for high strength and ultra-low noise. Get the visual effect of a hidden mic without the hassle and loss of sound quality you get from hiding one in clothing. The B6 is resistant to sweat and makeup and can be custom configured with connectors for most wireless transmitters



**COUNTRYMAN ISOMAX-II** The Isomax-II series of precision electret condenser microphones are equally suited for recording and sound reinforcement. Available in 3 polar patterns (omni, cardioid, hypercardioid), they have extremely low noise, a uniform frequency response from 10Hz-25kHz and are capable of handling high SPLs to 150dB.



The subtle black finish and miniature size allow for unobtrusive use in television and theater applications. Comes with a 10' cord with XLR output, mounting clip and windscreen. Phantom power required.

ITEM	DESCRIPTION	PRICE
M2CP6FF10	. Cardioid lavalier mic, 50Hz-20kHz	189.16
	. Omni lavalier mic, 20Hz-20kHz	
M2HP6FF10	. Hypercardioid lavalier mic, 50Hz-20kHz	189.16
A2WS-BLK	. Replacement windscreen, black	9.99
AXBPM	. Battery module	110.54





# SMALL LAVALIER. BIG POSSIBILITIES.

Countryman's B2D-the world's smallest directional lav-opens up huge options. How will you use it?





















































COUNTRYMAN B2D DIRECTIONAL LAVALIER One of the smallest directional lavaliers in the world. Features a tight hypercardioid pattern with an extra 6-10 dB of headroom, has moisture resistance and a rugged build, is tuned for speech, and has detachable cables for a wide variety of wireless and wired applications. Its hypercardioid pattern means less problems with feedback, ambient noise, room rumble, and phase cancellations with multiple mics. Supplied with wireless adapter, carrying case, shock mount clip, windscreen and protective cap. There are 3 sensitivity options — standard for general, mid for head miking/theater and low for head miking powerful vocals/opera. Five colors are available: Black, White, Light Skin, Cocoa and Gray (models listed below are Black). The B2D may be ordered with XLR/phantom termination (shown below) or pre-wired for a variety of wireless transmitters. Please call for options.

ITEM	DESCRIPTION	PRICE
B2DP4FF05B-HW	Hypercardioid lavalier, XLR male, standard sensitivity, black	432.84
B2DP5FF05B-HW	Hypercardioid lavalier, XLR male, mid sensitivity, black	432.84
B2DP6FF05B-HW	Hypercardioid lavalier, XLR male, low sensitivity, black	432.84

COUNTRYMAN EMW LAPEL MIC This electret condenser mic offers an omni-directional polar pattern, uniform pickup and a wide frequency range of 20Hz-20kHz. A mere 1/8" thick, the flat EMW offers discreet placement for broadcast and performance. Other features include: Kevlar-reinforced cable with low handling noise, sealed design for excellent mois-



ture resistance and a variety of clip options. Three frequency response patterns are available: "F" Flat-response, "S" Shelved-up response (6dB curve, 2kHz-15kHz) and "P" Peaked-response (sharp upward curve at 12kHz). All versions are available pre-wired for wireless use.

ITEM	<b>DESCRIPTION</b> .EMW, XLR, flat response	PRICE
MEMWP4F05B	.EMW, XLR, flat response	178.58
MEMWP4P05B	.EMW, XLR, peaked response	178.58
MEMWP4S05B	.EMW, XLR, shelved-up response	178.58
AEMWCLIP-B	.Replacement tie clip, black	14.54
AEMWVIPER-B	.Viper clothing clip	13.02
A3B3WS-L-LIGHT-SKIN	.Replacement windscreen	7.39



DPA MINIATURE MICS Miniature mics with 5.4mm diaphragms, resistant to humidity, sweat, wind and popping, all models require remote power and should be used with adapters listed below. Available in white, beige and black.



ITEM	DESCRIPTION	PRICE
4060	Lapel high sensitivity, MicroDot connector	443.00
4061	Lapel low sensitivity, MicroDot connector	443.00
4062	Lapel extra-low sensitivity, MicroDot connector	443.00
4065	Headband mic, MicroDot connector	568.00
4066	Adjustable headband mic, MicroDot connector	635.00
Micro-Dot Adapte	rs	
DAD6001BC	XLR, 48V phantom with belt clip	99.00
DAD6003	For Sennheiser SK50/250/3063	80.00
DAD6008	For Sony WRT820/860	93.00
DAD6010	For Shure TA4F	87.00
DAD6011	For Vega, Lemo, Shure U1L	93.00
DAD6012	For Lectrosonics M185	73.00
DAD6017	For AKG PT40/60/80/81,Samson UT1L/VT2L	73.00
DAD6019	For Sony WRT805, Sennheiser Evolution/SK300	87.00
DAD6020	For Telex TA4F	73.00
DAD6021	For ATW-T101, TA5F, Lectrosonics	73.00



RØDE LAVALIER MIC Røde's lavalier mic features low handling noise and designed to be worn discreetly. Includes a mic clip, detachable cable, a water-resistant pop filter, mini furry windscreen, adjustment tools, cleaning wipes, and an anti-trauma water-resis-




tant case. Mic is compatible with Røde's MiCon<sup>TM</sup> adapters (see below).

ITEM	DESCRIPTION	PRICE
LAVALIER	Omnidirectional lav mic, black, 60Hz-18kHz	249.00



**RØDE PINMIC WEARABLE MIC**Røde's discrete PINMIC features a removable capsule and a mesh head.
Features a mic clip and is designed for use with Røde's MiCon™ adapter system (see below).



ITEM	DESCRIPTION	PRICE
PINMIC	. Miniature omni lapel mic, black, 60Hz-18kHz	249.00

# MIC@N<sup>®</sup>

MICON ACCESSORIES FOR RØDE LAVALIER/PINMIC SYSTEMS Adapters and cables to connect Røde Pinmic and Lavalier to various wireless systems.

ITEM	DESCRIPTION	PRICE
MICON-1	. Adapter for Sennheiser SK500, SK300G3, SK100G3,	
	SK500G2, SK300G2, SK2-Freeport	18.00
MICON-2	. 3.5 stereo mini jack adapter (1V minimum power supply)	18.00
MICON-3	. Adapter for Shure UR1, UR1M, ULX1, SLX1, PGX1, PG1	23.00
MICON-4	. Adapter for Audio Technica UniPak	
	Body-Pack Series 1800, 2000, 3000	27.00
MICON-5	. 48V phantom power adapter, 3-pin XLR	27.00
MICON-CABLE-1.2M.	. 4ft MiCon cable	32.00
MICON-CABLE-3M	. 9ft MiCon cable	39.00



# SHURE

SHURE MICROFLEX LAPEL MICS The Microflex lapel condenser mics feature high sensitivity, a frequency response of 50Hz-17kHz, interchangeable condenser cartridges (MX models), & a variety of low-visibility mounting options. MX models are terminated to XLR & include a belt-clip preamp. MC models are terminated to XLR & include a detachable preamp. WL versions are terminated with TA4F connectors for Shure wireless systems.

ITEM	DESCRIPTION	PRICE
MX183	. Omni-directional condenser lapel mic, phantom only	160.52
MX184	. Supercardioid condenser lapel mic, phantom only	178.61
MX185	. Cardioid condenser lapel mic, phantom only	172.97
MC50B	. Omni-directional sub-miniature lapel with preamp	266.27
MC51B	. Omni-directional sub-miniature lapel with preamp	278.99
WL183	. Omni-directional, terminated for Shure wireless (TA4F)	91.74
WL184	. Supercardioid, terminated for Shure wireless (TA4F)	113.70
WL185	. Cardioid, terminated for Shure wireless (TA4F)	107.24
R183B	. Omni-directional cartridge option for MX184/MX185	32.54
R184B	. Supercardioid cartridge option for MX183/MX185	52.57
R185B	. Cardioid cartridge option for MX183/MX184	45.06



# SHURE

SHURE SM11 OMNI DYNAMIC LAVALIER For those who need a dynamic lavalier microphone, the SM11 is the smallest model available. Shure ruggedness and dependability in a mic no longer than a paper clip.

ITEM	DESCRIPTION	PRICE
SM11CN	Omni lavalier	. 101.84

### **SHURE SM93 OMNI MICRO CONDENSER** LAPEL The SM93 lapel microphone is ideal for

broadcast, stage and film because of its tiny size and clear, tailored frequency response. Features: Omni-directional pattern, a variety



of low-visibility mounting options, 80Hz-20kHz frequency response, windscreen and in-line preamp with XLR output.

ITEM	DESCRIPTION	PRICE
SM93	. Omni-directional lapel mic, preamp, XLR out	135.58
WL93	. Omni-directional lapel mic for Shure wireless (TA4F)	68.54
WL93T	. Same as WL93 with tan finish	68.54

**SANKEN COS 11D MINI LAVALIER** 

MICS Specifically to diminish the instances where interference is an issue, this omnidirectional, selfpolarized condenser mic has a frequency range of 50Hz-20kHz, and a



sensitivity rating of -35dB. It is ideal for live broadcasting, location recording and studio applications and operates on 48V phantom power (COS-11D) or battery power (COS-11D-BP). Includes clip, windscreen, rubber mount, AA battery and vinyl case. Available in black, gray, beige and white.

ITEM	DESCRIPTION	PRICE
COS-11D	Mini lavalier mic, 48V, XLR	469.00
COS-11D-BP	Mini lavalier mic, battery powered, XLR	469.00

# "SENNHEISER"

### SENNHEISER MKE2 OMNI MICRO LAPEL CONDENSER

Available unwired for a variety of wireless applications, wired to an XLR connector or as part of the K6 modular system. 6mm in diameter and flat from 20Hz-20kHz. Gold versions have reduced sensitivity and improved moisture resistance.

ITEM	DESCRIPTION	PRICE
MKE2-5-K	Pigtail, black finish	364.60
MKE2-5-3C-GOLD	Pigtail, buff finish	349.95
MKE2-5C-GOLD	Pigtail, black finish	349.95
MKE2-60-GOLD	For use with the K6 power unit	329.95
MKE2-EW-GOLD	For EW wireless, black finish	389.95
MKE2-P-C	With XLR for phantom power	349.95
K6	Power module for MKE2-60	249.95
MZQ222	Replacement clip for MKE2	12.85



### SONY

### SONY ELECTRET SERIES CONDENSER MICS

These mics operate on a single AA battery and come with a urethane windscreen and clip.

SONY ECM44B OMNIDIRECTIONAL Mic head 8.5x14.5mm. Freq. resp. 40Hz-15kHz. Max input: 122dB SPL. Dynamic range: 90+dB.

ITEM	DESCRIPTION	PRICE
ECM44B	Omnidirectional lapel mic, XLR	CALL
ECM44BC	Omnidirectional for Sony 4-pin wireless	CALL
ECM44BMP	Omnidirectional for Sony 1/8" mini-lock wireless	CALL
ADR44B	Replacement windscreen	CALL
SADH44B	Replacement tie clip for ECM44	CALL

SONY ECM55B OMNI-DIRECTIONAL Mic head 10.6x21mm. Freq. resp. 30Hz-18kHz. max input: 126dB SPL. Dynamic range: 98+dB. Connector: XLR.

ITEM	DESCRIPTION	PRICE
ECM55B	Omni-directional lapel mic	CALL
	Replacement tie clip for ECM55B	
	·	

SONY ECM77B ULTRA MINI OMNI-DIRECTIONAL Mic head 5.6x12.55mm. Freq. resp. 40Hz-20kHz. Max input: 120dB SPL. Dynamic range: 90+dB. Connector: XLR.

ITEM	DESCRIPTION	PRICE
ECM77B	. Mini omni-directional lapel mic	CALL
ECM77BC/9X	. Mini omni-directional for Sony 4-pin wireless	CALL
ADR77B	. Replacement windscreen	CALL
	. Replacement tie clip for ECM77B	

SONY ECM88B ELECTRET CONDENSER MICS A miniature omnidirectional electret-condenser microphone ideally suited for qualitycritical applications in broadcasting, theater and field production. A dualcapsule design effectively nulls out cable and handling noises and delivers wide, flat frequency response which makes it useful for lapel speech pickup and music recording applications. Has a Sony 4-pin connector (SMC9-4P) to connect with WRT-8B or WRT-822B wireless transmitters and DC78 power supply with XLR output.

ITEM	DESCRIPTION	PRICE
ECM88B	Mini omni-directional condenser mic	CALL
DC78	Replacement power supply/XLR adapter	CALL
ADR88B	Optional urethane windscreen	CALL

TRAM TR50 LAVALIER MICROPHONE With minimum sound coloration, this omni-directional MICROPHONES electret condenser microphone easily combines with

boom microphones and has an extensive range of mounting options. It provides a wide frequency response and very low rubbing noise. It includes a detachable 250W power supply and is available in black, gray, tan or white.

ITEM	DESCRIPTION	PRICE
TR50LX	. Lavalier mic with Telex lemo, 4-pin	244.11
TR50ML	. Lavalier mic with Lectrosonics TA5F	234.83
TR50-MS	. Lavalier mic with Shure TA4F	234.83
TR50SET	. Lavalier mic with Sennheiser 3.5mm TRS	235.76
TR50PS	Lavalier mic, XLR, hardwired to power supply,	
	can use internal battery power	323.94
TR50NCM0	. Lavalier mic with no connector	181.00
TR50PSNCMO	Lavalier mic with no connector, hardwired to power	
	supply can use internal hattery power	185 64



























































































### **AUDIX OM SERIES VOCAL MICROPHONES**

Dynamic hypercardioid handheld vocal microphones for maximum gain before feedback.

ITEM	DESCRIPTION	PRICE
OM2	50Hz-16kHz, warmth and mid boost	99.00
OM2S	. OM2 with switch	119.00
OM3	50Hz-18kHz, natural accurate	129.00
OM3-S	. OM3 with switch	149.00
OM5	48Hz-19kHz, gentle presence rise	159.00
OM6	. 40Hz-19kHz, flat response	219.00
OM7	45Hz-19kHz, low gain, pro-touring	229.00
OM11	. Reissue of the flagship OM1,	
	lead vocal, solid brass housing,	
	50Hz-18kHz, hypercardioid	239.00





Features metal casing, a spring steel grille, scratch resistant finish, high max SPL and a carrying case.

ITEM	DESCRIPTION	PRICE
P3S	. Cardioid, dynamic, on/off switch,	
	40Hz-20kHz	49.00
P5	.Supercardioid, dynamic, 40Hz-20kHz	59.00

AKG C535EB CONDENSER VOCAL MICRO-PHONE A classic design from AKG. This rugged condenser vocal mic has excellent response well past 20kHz. A switchable pad and filter allow 14dB of pre-attenuation and either a 500Hz 6dB/ Oct roll-off or a 100Hz 12dB/Oct roll-off. Ideal for singers who often change their working distance. Matte black finish, requires phantom power and includes the SA41 flexible stand adapter.

ITEM	DESCRIPTION	PRICE
C535EB	Microphone	299.00
001=H30	Elastic suspension mount	90.50
001=6000H06210	Replacement foam windscreer	1 27.00

AKG C5/D5 HANDHELD VOCAL MICROPHONES The C5 features a

24-carat gold-sputtered housing that protects the condenser capsule against moisture and humidity, plus a removable Presence Boost adapter for increased intelligibility. The D5 dynamic mic includes new Laminate Varimotion diaphragm tech-

nology to deliver a smooth frequency response and the highest gain-before-feedback

the ingliest fam before recubacit.		
ITEM	DESCRIPTION	PRICE
C5	. Condenser, cardioid, 65Hz-20kHz	149.00
D5	. Dynamic, supercardioid, 70Hz-20kHz	99.00
D5S	.D5 with on/off switch	129.00

AKG D7 DYNAMIC HANDHELD MIC With the Laminated Varimotion diaphragm, this mic creates a subtle and open sound, but also has the powerful resonance of a dynamic mic. An integrated hi-pass filter eliminates handling noise, provides clear vocal intelligibility and a built-in hum-canceling coil minimizes electrical interference.

ITEM	DESCRIPTION	PRICE
D7	.Supercardioid, 70Hz-20kHz,	170.00
D7-LTD	matte gray blue	179.00
	w/chrome-plated finish	199.00

# (A) audio-technica. always listening...

AT2010 **AUDIO-TECHNICA** HANDHELD CONDENSER VOCAL MICROPHONE Designed to bring the studio-quality articulation and intelligibility of AT's renowned 20 Series to the stage. Featuring the same 16mm low-mass diaphragm found in the AT2020 studio condenser, the AT2010 excels wherever articulate vocals are needed such as in houses of worship, for solo performances, jazz vocalists and singer/songwriters.

3 3		
ITEM	DESCRIPTION	PRICE
AT2010	Cardioid, 40Hz-20kHz	99.00

### **AUDIO-TECHNICA ARTIST ELITE**

State-of-the-art line performance vocal microphones with excellent noise isolation. The AE5400 has a cardioid true condenser large-diaphragm element and a switchable HP filter and pad switch. The AE3300 is a cardioid condenser with HP filter and pad switch. AE6100 is a hypercardioid dynamic, the AE4100 a cardioid

ajmammor		
ITEM	DESCRIPTION	PRICE
AE4100	Cardioid dynamic	189.00
AE6100	Hypercardioid dynamic	189.00
AE3300	Cardioid condenser mic	279.00
AF5/100	Cardinid condenser mic	379 00

### **AUDIO-TECHNICA ARTIST** SERIES VOCAL MICS ATM410

The ATM410 cardioid dynamic is designed for smooth, natural vocal reproduction and features a neodymium magnet for high output, and a multi-stage grille. The ATM610 is hypercardioid and



ITEM	DESCRIP	TION			PRICE
switchable	10dB pad.				
denser mic	with an inte	egral 80H	z hi-pas	s filte	er and a
noise. The	ATM710 is	a high-fi	delity c	ardio	id con-
shell, provi	ding outsta	nding iso	lation fr	om h	andling
back-cavity	assembly	"floats"	inside	the	handle

ITEM	DESCRIPTION	PRICE
ATM410	Cardioid dynamic mic with	
	neodymium magnet	79.00
ATM610	Hypercardioid dynamic mic	149.00
ATM710	Cardioid condenser mic w/HP	
	filter and 10dB nad	199 00

# beyerdynamic)

BEYERDYNAMIC M88TG HYPERCAR-DIOID DYNAMIC MIC With a frequencyindependent pickup pattern which reduces feedback and off-axis coloration to a minimum and delivers high output over a wide range of working distances. Its wide frequency response and fast transient response enhance the presence and articulation of voices, while accurately reproducing bass frequencies. The M88 has a natural, well-balanced sound and its rugged design virtually eliminates non-linear distortion at extreme SPLs. The integral humbucking coil reduces interference from stray magnetic fields by as much as 20dB. Comes with black leatherette foam-lined carry case and MKV8

ITEM	DESCRIPTION	PRICE
M88TG	. Hypercardioid dynamic mic	388.00
PS88	.Pop filter, dark grey polyurethane foam.	20.00
WS59	.Windscreen, charcoal grey	25.00

300



### **ENCORE** HANDHELD VOCAL MICS Starting with Blue's Aria Capsule technology, each mic capsule is

hand-tuned for the utmost in detail and clarity. Blue's proprietary capsule mount delivers minimal handling noise

without pads or filters. From its heavy-gauge grill and barrel to its reinforced ring and durable plated finishes, every enCORE mic can take a beating and still deliver amazing performances. Each mic includes clip & storage pouch.

ITEM	DESCRIPTION	PRICE
ENCORE-100.	.Dynamic, cardioid, 50Hz-15kHz	99.99
ENCORE-200.	.Dynamic, cardioid, electronically-	
	transformed output, 50Hz-16kHz	.149.99
ENCORE-300.	.Condenser. cardioid. 35Hz-20kHz	199.99



### CAD C195 HANDHELD CONDENSER MIC A car-

ASTATIC COMMERCIAL dioid condenser mic for live vocals, acoustic instruments, strings, piano, cymbals and overheads. Features a transformerless drive and durable metal screen, non-reflective polyurethane finish, MAX SPL of 132dB, and self noise of 22dBA. Comes with 15ft XLR-XLR cable and mic clip.

EM	DESCRIPTION	PRICE
195	Handheld cardioid condenser mic,	
	55Hz-20kHz	99 00

# **Earthworks**

**EARTHWORKS SR40V HIGH DEFINITION** VOCAL MICROPHONE With a self-noise rating of just 22dB SPL (A-weighted), a sensitivity rating of 10 mV/Pa (-40 dBV/Pa), and a Peak Acoustic Output rating of 145dB SPL, the SR40V combines extremely low handling noise with robust performance and output capability that enables vocal performers to have the natural sounding, up-front presence they've always wanted. Features a 9mm back electret condenser-type transducer with a 5 micron diaphragm. Each microphone is handmade in the USA

and features a rugged stainless steel body that feels great in the hand.			
ITEM SR40V	<b>DESCRIPTION</b> Vocal condenser mic,	PRICE	

hypercardioid, 80Hz-40kHz ......999.00





# THE WAIT IS OVER.



# THE WORLD'S FIRST HIGH DEFINITION VOCAL MICROPHONE™ WITH A 15 YEAR WARRANTY

Engineered for use on stage or in the studio, the hand-tuned and tested Earthworks SR40V allows you to capture and reproduce your vocals with unmatched clarity and depth. With a frequency response of 30Hz to 40kHz, an extremely fast impulse response and a very short diaphragm settling time you will hear subtle details that conventional vocal microphones miss. Designed to make your vocals sound crisp, clear and natural, there is no need for excessive EQ or effects when using the SR40V. Staying true to the Earthworks cornerstone of True Live Sound™. the SR40V delivers accuracy of reproduction that will let you truly capture your vocals.

> All Earthworks products are handmade in the USA.



Scan this tag with your smartphone to find out more about the SR40V from a Full Compass Sales Pro. Get the free smartphone app at the Unaffian mobil.



www.fullcompass.com • 800-356-5844





















































# **EV PL SERIES DYNAMIC**



ITEM	DESCRIPTION	PRICE
PL24	Dynamic vocal mic, supercardioid,	
	80Hz-16kHz	59.00
PL24S	Dynamic vocal mic, supercardioid,	
	80Hz-16kHz, on/off switch	65.00
PL44	Dynamic vocal mic, supercardioid,	
	80Hz-18kHz	79.00
PL80A	Dynamic vocal mic, supercardioid,	
	80Hz-16kHz, black finish	99.00
PL80C	Dynamic vocal mic, supercardioid,	
	80Hz-16kHz, "Classic PL" beige finish	99.00
PL84	Condenser vocal mic, cardioid,	
	50Hz-20kHz	89.00
PL84S	Condenser vocal mic, cardioid,	
	50Hz-20kHz, on/off switch	95.00

EV N/DYM PERFORMANCE MICS EV was N/D267AS the first to use neodymium-based magnets in microphones and is the only manufacturer that offers Vocal-Optimized-Bass technology, providing a clear vocal sound that cuts through the mix. Mics feature very low handling noise, high output, and extended frequency response.

ITEM	DESCRIPTION	PRICE
N/D267A	Cardioid 45Hz-15kHz, vocal mic	99.00
N/D267AS	Same as above, with switch	104.00
N/D367S	Cardioid for female vocals,	
	with switch	129.00
N/D478	Cardioid 45Hz-15kHz,	
	vocal/instrument mic	119.00
N/D767A	Supercardioid, 35Hz-22kHz,	
	vocal mic	129.00
N/D967	Supercardioid, 50Hz-13kHz,	
	w/rolloff switch, concert vocal	199.00



HEIL SOUND PR PR20 SERIES DYNAMIC MIC The PR20 and PR22 feature neodymi-

um, iron, boron magnet construction and steel case structures. Both models have a large 1 1/8" low mass voice coil assembly, 50Hz-18kHz frequency response and

a 3-pin XLR output connection. The PR20 is recommended for live vocal and snare drum applications. The PR22 includes the ISO Band, a Sorbothane rubber suspension system to eliminate low frequency handling noise. Both mics come with a carrying bag, mic clip and set of 3 metal windscreens (black, silver and gold). The PR20-UT is a "utility" package and has only the mic clip and a silver mesh windscreen.

and time only and a current moon windoor com				
DESCRIPTION	PRICE			
Cardioid mic with black, silver and	gold			
mesh head windscreen	150.00			
PR20 microphone with silver (only)				
windscreen head, clip and pouch	99.00			
Cardioid mic w/Sorbothane				
suspension	182.00			
	DESCRIPTIONCardioid mic with black, silver and mesh head windscreen			

HEIL SOUND PR35 SUPERCARDIOID **DYNAMIC VOCAL MIC** Features neodymium, iron & boron magnet structures. The PR35 utilizes the PR30 capsule in a rubber internal suspension specifically designed for handheld vocal applications. It has a 3-position LF rolloff switch.

1 1		
ITEM	DESCRIPTION	PRICE
PR35	Vocal mic, 40Hz-18kHz	274.00



### NEUMANN KMS104/105 HANDHELD VOCAL

MICS These handheld condenser microphones are designed with superlative vocal reproduction in mind. Available in cardioid pattern as the KMS104, or in supercardioid as the KMS105, these microphones combine low noise and colorless off-axis pickup for outstanding live stage vocal work. A unique 4-layer acoustic filter plus electrical filtering remove most popping and handling noise. Response is 20Hz-20kHz, 150dB maximum SPL. 48V phantom power required. Available in choice of black or nickel finishes.

ITI	EM	DESCRIPTION	PRICE
K۸	1S104-NI	Cardioid vocal condenser, nickel .	699.95
K۸	IS104-MT	Cardioid vocal condenser, black	699.95
K۸	1S105-NI	Supercardioid vocal condenser,	
		nickel finish	699.95
K۸	1S105-MT	Supercardioid vocal condenser,	
		black finish	699.95







LEWITT MTP SERIES MICS Suited for live performance and studio situations, these mics have a uniform cardioid pickup pattern which rejects off-axis sound and ensures high gain before feedback. They are minimally affected by varying load impedance. The MTP44DM is best suited for instrument recording. The MTP540DM has an internal shockmount and builtin spherical wind and pop filter. All models have goldplated 3-pin XLR connectors, die-cast bodies, steel mesh grills and include a stand clip and leather bag.

ITEM	DESCRIPTION	PRICE
MTP240DM	.Dynamic cardioid vocal mic,	
	60Hz-18kHz, 280ohms	59.00
MTP340CM	.Electret condenser vocal mic.	
	90Hz-20kHz, 200ohms	139.00
MTP440DM	.Dynamic cardioid instrument mic,	
	60Hz-16kHz, 500ohms	79.00
MTP540DM	.Dynamic cardioid vocal mic,	
	60hz-16kHz, 350ohms	89.00





MICROPHOME DISINFECTANT FOAM & MIC CLEANING KIT Designed to disinfect exterior mic surfaces while not touching sensitive inner electronics. Microphome is antimicrobial, alcohol-free, fastdrying and leaves no residue. One 50 mL bottle is good for 100 disinfections. Cleaning kit comes with a bottle of Microphome, microfiber cleaning cloth, soft nylon scouring pad, two-sided cleaning brush and zippered black vinyl mic bag.

•••		DESCRIPTION	PRICI
M			8 9!
M	ICROPHOME-KIT	Disinfectant, cloth, brush, scour pad & mic bag	
	ICROPHOME-KIT		

MILAB LSR SERIES CONDENSER MICROPHONES These transformerless mics feature built-in pop protection, shockabsorbing rubber-fitted capsules, gold-plated XLR connectors and are virtually insensitive to hand noise. The LSR-1000 features a cardioid pattern and 132dB max SPL and the LSR-3000 has a -12dB switchable pad and is capable of handling 150dB max SPL.

ITEM	<b>DESCRIPTION</b> Cardioid, 40Hz-20kHz,	PRICE
LSR-1000	Cardioid, 40Hz-20kHz,	
	12-52V phantom power	
LSR-3000	Cardioid, 20Hz-20kHz, 48V ph	antom
	power, -12dB pad, 80Hz filter.	

# **SENNHEISER**

SENNHEISER MD431-II The ability to provide high gain-before-feedback, handle high sound pressure levels and produce a clean, open sound have made the MD431-U famous among discerning musicians and engineers alike. Features include supercardioid pattern, triple-layer steel mesh grille, shocksuspended capsule, specially contoured low frequency response, humbucking coil, and a removable magnetic-reed on/off switch.

ITEM	DESCRIPTION	PRICE
MD431-II	Supercardioid dynamic mic,	
	with low handling noise	449.95
A25DM	Replacement stand adapter	45.60
MZW4032	Foam windscreen	35.54





# SENNHEISER® SENNHEISER EVOLUTION SERIES

Evolution mics offer Sennheiser's highest standards of performance and construction at affordable prices. Each mic features a rugged steel-blue metal housing and removable capsule. The E825S offers a silent on/off switch, cardioid pattern and is well suited for general vocal and instruments. The E835 cardioid mic features a subtle



presence boost for lead/stage vocals and an extended frequency response. The E865 is a condenser supercardioid with great transient response. The E835 and E845 are also available with a silent on/off switch. The E965 is a large diaphragm condenser mic, with switchable cardioid/supercardioid polar patterns and a -10dB cut switch. All models are dynamic except for the E865 and E965 which are condenser mics.

ITEM	DESCRIPTION	PRICE
E815S-C	.Cardioid vocal mic with	
	switch and clip, 80Hz-12kHz	59.95
E825S	.Cardioid vocal/instrument mic	
	w/ switch, 80Hz-15kHz	79.95
E835	.Cardioid vocal mic, 40Hz-18kHz	99.95
E835S	.E835 w/ switch	.109.95
E840	.Cardioid vocal mic, 40Hz-18kHz	.129.95
E845	.Supercardioid vocal mic, 40Hz-16kHz	.139.95
E845S	.E845 w/switch	.149.95
E865	.Supercardioid condenser vocal mic,	
	40Hz-20kHz	.269.95
E935	Dynamic cardioid vocal mic, 40Hz-18kHz	.169.95
E945	Dynamic supercardioid vocal mic,	
	40Hz-18kHz	.219.95
E965	Large diaphragm condenser vocal mic,	
	selectable cardioid/supercardioid	
	patterns, 40Hz-20kHz	.699.95
THREEPAC	K835Three 835 mics w/pouches	.249.95
300-BLAC	KBlack foam windscreen	
	(by WindTech)	5.80

### SHURE PERFORMANCE GEAR MIC

microphones. Designed for specific applications, they come complete with a 25-ft cable, clip and storage bag. The onstage vocal microphones feature a convenient on/off switch.



ITEM	DESCRIPTION	PRICE 🖤
PG48-QTR	.Dynamic cardioid, speech/karaoke	
	mic with XLR-1/4" cable	39.00
PG48-XLR	.Dynamic, speech/karaoke mic,	
	with XLR-XLR cable	39.00
PG52-XLR	.Kick drum mic	.119.00
PG56-XLR	.Drum mic	69.00
PG57-XLR	.Instrument mic	59.00
PG58-QTR	.Dynamic, vocal performance mic,	
	with XLR-1/4" cable	59.00
PG58-XLR	.Dynamic, vocal performance mic,	
	with XLR-XLR cable	59.00

SHURE 565SD-LC Perfect for sound reinforcement applications such as voice reproduction on lecterns, stages, church and school sound systems. Dual impedance and locking on/ off switch.

ITEM 565SD-LC	<b>DESCRIPTION</b> Cardioid dynamic vocal mic.	PRICE 102.82
	Foam windscreen Replacement stand adapter	

SHURE 588SDX The versatility and economy champ for general sound reinforcement. Switch selectable dual-impedance design with locking on/off switch.


ITEM	DESCRIPTION	PRICE
588SDX	Cardioid dynamic vocal mic	57.12
A58WS	Foam windscreen	7.44
A25D	Replacement stand adapter	r 5.76

# SHURE

SHURE **SERIES** MICROPHONES These entry-level

microphones are cost-effective yet don't sacrifice sound quality. The SV100 is a dynamic vocal microphone that is ideal for vocal performance, spoken word presentations, karaoke, multimedia and instrument use. The

sory pack.



SV100

SV200

ITEM	DESCRIPTION	PRICE
SV100-W	Dynamic cardioid mic, XLR-1/4" cable	e29.99
SV100-WA	As above, with XLR-1/4" cable,	
	clip, thread adapter, pouch	34.99
SV200-W	Dynamic cardioid mic, XLRM-XLRF cabl	e34.99
SV200-WA	As above, with XLRM-XLRF cable,	
	clip, thread adapter, pouch	39.99

### **SHURE 55SH SERIES II AND SUPER 55 DELUXE VOCAL MICROPHONES** Both

models feature vintage design with modern performance. The 55SH-II iconic unidyne mic features a satin chrome-plated die-cast casing and a cardioid directional pattern that minimizes sound pickup from the rear of the mic. It has a 50Hz-15kHz frequency response, swivel base with on/off switch, and XLR con-

nector. The Super 55 Deluxe features the same casing but a supercardioid polar pattern and includes a blue foam pop filter. It offers additional clarity and high gain-before-feedback, has a 60Hz-17kHz frequency response and includes a swivel stand mount.

ITEM	DESCRIPTION	PRICE
55SH-II	Cardioid vocal mic	179.00
SUPER-55	Supercardioid vocal mic,	
	blue foam pop filter	249.00

### SHURE SM48LC DYNAMIC CARDIOID

MIC Designed for pro sound reinforcement, studio recording, and broadcasting applications. Both include a shockmounted cartridge, a steel mesh grille, and an integral "pop" filter. The SM48S also includes a lockable on/off switch. Includes stand adapter and carrying/ storage bag.

ITEM	DESCRIPTION	PRICE
SM48LC	Cardioid dynamic	49.95
SM48S-LC	Cardioid dynamic with switch	55.09

SHURE SM58 DYNAMIC VOCAL MICROPHONE This cardioid mic has a dynamic range of 50Hz-15kHz, features built-in spherical wind and pop filter, and a pneumatic shock-mount system to reduce handling noise. Its frequency response is tailored for vocals, with brightened midrange and bass roll-off. Ships with stand adapter and storage bag.

-	0 0	
ITEM	DESCRIPTION	PRICE
SM58CN	.Cardioid dynamic vocal mic, w/cable	109.00
SM58LC	.Cardioid dynamic vocal mic, no cable .	99.00
SM58S	.Same as SM58LC, but with switch	104.00
SM58X2U	.SM58LC packaged w/X2U	
	XLR to USB adapter	199.00
A25D	.Replacement stand clamp	5.76
A58WS-BK	.Foam windscreen, black	
	(other colors available)	7.44
300-BLACK	.Optional Windtech windscreen, black	(
	(other colors available)	5.80

### SHURE SM86 CONDENSER VOCAL MIC

The SM86's condenser capsule provides studioquality sound and tailored frequency response for clear reproduction of vocals. Cardioid polar pattern, built-in 3-point shock mount, 2-stage filter reduces wind and "pop" noise.

ITEM	DESCRIPTION	PRICE
SM86LC	.Condenser vocal mi	149.00

SHURE BETA-87 Studio-quality sound in live vocals w/ smooth, tailored response and an extremely accurate supercardioid pattern at all frequencies providing greater gain before feedback. A break-resistant stand adapter is included for the new larger handle. Also includes high sound level capability, a 3-stage pop filter, low noise electronics and full magnetic shielding. Ideal for concert sound and music production.

ITEM	DESCRIPTION	PRICE
BETA87A	Supercardioid condenser microphone	249.00
BETA87C	Cardioid microphone	249.00
A85WS	Windscreen	11.97

SM87A SUPERCARDIOID CONDENSER MIC Tailored for warm, rich, vocal reproduction. Includes the A25D breakresistant swivel adapter. Requires phantom power. Frequency response is 50Hz-18kHz.

ITEM	DESCRIPTION	PRICE
SM87A	.Supercardioid condenser	mic.203.39

### SHURF KSM9 **HANDHELD CONDENSER MICROPHONE** Provides

extraordinary vocal reproduction for critical applications. The KSM9 features a dual-diaphragm design with choice of cardioid and supercardioid patterns, smooth response, minimal proximity effect, and maximum gain-before-feedback. A 2-stage shock mount greatly reduces handling noise. 50Hz-20kHz response, 153dB SPL, 22 dBA self-noise A-weighted.

ITEM	DESCRIPTION	PRICE
KSM9/CG	Dual-pattern, handheld condens	er
	mic in gray	699.00
KSM9/SL	Champagne colored version	699.00
OUUDE D	ETAFOA N.	,

SHURE BETA58A A true supercardioid polar pattern at all frequencies gives you unprecedented gain-before-feedback. Extended high frequency response provides clarity normally only found in condenser mics.

ITEM	DESCRIPTION	PRICE
BETA58A	Supercardioid dynamic vocal mic	159.00
A58WS	Foam windscreen	7.44



SONTRONICS STC-80 DYNAMIC MICROPHONE This handheld microphone boasts superb sound quality and low handling noise to deliver first class results. It has a rugged construction and a high quality dynamic capsule. The microphone offers a frequency response from 50Hz-15kHz and incorporates an internal pop filter that reduces plosives.

ITEM	DESCRIPTION
STC80	Dynamic handheld microphone
	w/non filter























































PRICE .159.00 ATM250DE

ATM650

ATM250
















































AKG D112 BASS MIC Ideal for kick drum and bass guitar applications. It features zero distortion even at high sound pressure levels, very low dia-

phragm resonance, a relatively narrow-band rising high frequency response at 4kHz, frequency response range of 20Hz-17kHz and extremely robust construction. Perfect for both studio and live applications.

		-
ITEM	DESCRIPTION	PRICE
D112	Bass microphone	199.00

### (A) audio-technica. always listening...

**AUDIO-TECHNICA ARTIST SERIES** INSTRUMENT MICS The ATM250 is a hypercardioid neodymium magnet dynamic instrument mic, with high SPL capability. Ideal for kick drum, percussion, brass and other highly dynamic



thread adap	ter and pouch.	
ITEM	DESCRIPTION	PRICE
ATM250	High SPL mic for kick drum or percus	ssion
	or brass, hypercardioid dynamic	.179.00
ATM250DE	Dual-element kick drum microphone	,
	hypercardioid dynamic/cardioid	
	condenser	.299.00
ATM650	Instrument microphone,	
	hypercardioid dynamic	99.00

### **AUDIX I-5 DYNAMIC CARDIOID**

A dynamic microphone that can be used for any instrument miking application for stage and studio. With its sleek styling and unique probe cap design, the I-5 features a durable cast zinc alloy body and black E-coat finish. The I-5 is designed with a cardioid polar pattern, allowing it to focus on the particular instrument without picking up other

instruments or ambient noise on stage. With a smooth and uniform frequency response of 50Hz-16kHz and an ability to handle sound pressure levels in excess of 140dB, the I-5 can be used for a wide variety of applications and for all genres of music.

	· ·	
ITEM	DESCRIPTION	PRICE
I-5	Cardioid	99.00
	Mic clamp for guitar amps	
	and cabinate	10 05

### **D-SERIES** INSTRUMENT

The D-Series dynamic mics feature very low-mass diaphragms for accurate and sensitive pickup of instrument harmonics and subtle nuances. Housed in tooled aluminum cases, these mics are extremely rugged, yet lightweight and compact. A tight hypercardioid pickup pattern allows for clear definition and excellent feedback rejection. All four microphones feature high SPL handling to 144dB.

ITEM	DESCRIPTION	PRICE
D2	Hypercardioid microphone	
	(toms, kick drum, conga, sax)	129.00
D4	Hypercardioid microphone	
	(low frequency instruments)	169.00
D6	Kick drum mic	199.00
D6-NICKEL	Kick drum mic, nickel finish	299.00



# beyerdynamic)



### BEYERDYNAMIC M201TG HYPERCARDIOID

Low-mass moving coil transducer design, high SPL handling, and rugged construction make the M201 an excellent choice for drum and percussion miking. High sensitivity provides excellent intelligibility and transient response. 40Hz-18kHz.

ITEM	DESCRIPTION	PRICE
M201TG	. Tour group version (int shock mounting)	299.00

### BEYERDYNAMIC TG-I50D DYNAMIC **CARDIOID**

**INSTRUMENT MIC** Developed specifically for electric guitar/bass amps, Leslie speakers, woodwinds, brass, percussion and snare drums and for live situations where feedback reduction is required. Features enhanced space behind the diaphragm for improved bass reproduction, treble resonator for optimal highfrequencies and special sound holes for a frequency-independent polar pattern.

TEM	DESCRIPTION	PRICE
ΓG-150D	.Dynamic cardioid instrument mic,	
	50Hz-17kHz, hi-pass filter, mic clip	189.00

### BEYERDYNAMIC M69TG

The M69's tight hypercardioid pattern and reduced proximity effect make it an excellent choice for vocals or instruments

CHOICC IV	choice for vocals of matruments.		
ITEM	DESCRIPTION	PRICE	
M69TG	Hypercardioid moving coil		
	dynamic microphone	299.00	
WS59	Replacement foam windscreen	25.00	
MKV8	Replacement stand adapter	20.00	
	Replacement pop-screen		



### EV RE20/RE27N/D **DYNAMIC CARDIOID**

The legendary RE20 is designed for critical recording and broadcast. Peak free response even up close, it is ideal for the studio as well as voice overs, announce booths. Features include a bass roll-off switch and Variable-D cardioid pattern which



RF27N/D

has no proximity effect for the same response at any distance. RE27N/D is a modernized version of the RE20, with a neodymium alloy magnet, and extended high frequency response for a condenser like sound.

ITEM	DESCRIPTION	PRICE
RE20	Dynamic cardioid, 45Hz-18kHz	429.00
RE27N/D	Dynamic cardioid, 45Hz-20kHz	479.00
309A	Spider shockmount	99.00
320-EV	Replacement stand clamp	50.00
20/421	Windtech windscreen	31.95
VAC-RE20	Integrated dual 3.5" screen pop	
	filter & mount for RE20/RE27	58.02

### EV RE320 VARIABLE-D DYNAMIC

MICROPHONE Designed for recording and reinforcement applications requiring extremely low noise as well as predictable tonal and transient response. The "Variable-D" proximity control minimizes positional and off-axis tonal shifts. Its unique "Dual-Personality" switch effectively creates 2 microphones in 1 body. One switch position delivers voice, electric and acoustic instruments with a lively, yet

natural tonal response. The other position delivers an "insta-kick" curve designed specifically for kick drums. Other features include integrated humbucking coil, built-in pop filter, neodymium magnet structure, cardioid pickup pattern, dynamic element and frequency responses of 30Hz-18kHz (insta-kick mode) and 45Hz-18kHz (voice/instrument mode).

	•	-
ITEM	DESCRIPTION	PRICE
RF320	Dynamic cardioid microphone	299 00



CAD D12 DYNAMIC KICK DRUM MIC A large-diaphragm neodymium, cardioid, moving-coil dynamic microphone designed and equalized for kick drum capture and reinforcement. The ASTATIC COMMERCIAL neodymium magnetics allow reduced coil mass for transient agility and impedance reduction. A die-cast metal body and protective steel screen provide

durability. Can also be used for floor toms, electric guitar and bass cabinets. ITEM DESCRIPTION PRICE Kick drum mic, cardioid, x30Hz-12kHz, -66dBV, 60ohms.....







### LEWITT DTP SERIES DRUM MICROPHONES

The entry level DTP340REX and its big brother, the DTP640REX, are designed specifically for bass instruments. They are equally at home onstage or in the studio. The DTP640REX model uses an innovative dualelement design, with a dynamic and back-electret condenser capsules. It also has a switchable 10-20dB preattenuation pad, selectable HPF settings, a 12dB/ octave at 40Hz and 80Hz bass cut filter slope and a custom 5-pin XLR to two 3-pin XLR Y-cable. Both models feature gold-plated 3-pin XLR connectors, integrated stand adapters and hexagonal steel-mesh grills.

orania anapress		
ITEM	DESCRIPTION	PRICE
DTP340REX	Dynamic supercardioid bass drum.	
	mic, 20Hz-12kHz, 500ohms	149.00
DTP640REX	.Dual-element bass drum mic, 20Hz	-16kHz,
	500ohms (dynamic) / 20Hz-20kHz,	
	200ohms (condenser)	299.00





# **HEIL SOUND PR SERIES** SUPERCARDIOID

DYNAMIC MICS All feature neodymium, iron, boron magnet structures and steel case structures. The PR20 is recommended for many applications from voice to snare drums. The PR22 has a sorbothane suspension system to reduce undesirable handling noise. The PR28 has a unique dual suspension system between element,



grill and body for vibration reduction and is best for toms and snare. The PR30 features the largest dynamic element available and is good for broadcast studios and guitar amps. The PR35 is a handheld vocal mic with an enhanced shockmount and 3-position LF rolloff switch. The PR40 has a large low-mass aluminum voice coil and is recommended for studio voice applications.

ITEM	DESCRIPTION	PRICE
PR20	.50Hz-18kHz, cardioid, includes pouch, se	et of
	interchangeable silver, gold & black colo	red
	metal windscreens, stand clip	150.00
PR20-UT	.PR20 "Utility" package with clip, pouch,	
	and silver (only) windscreen	99.00
PR22	.50Hz-18kHz, cardioid, internal	
	sorbothane suspension system	182.00
PR28	.55Hz-18kHz, cardioid, black finish,	
	internal dual suspension	
PR30	.40Hz-18kHz, super cardioid, anodized ma	
	champagne, includes stand clip	
PR35	.40Hz-18kHz, super cardioid, PR30 eleme	nt in a
	rubberized internally shock-mounted	
	body for handheld vocal applications	
PR40	.28Hz-18kHz, super cardioid, anodized ma	
	champagne, includes metal carrying cas	e
	and stand clip	325.00

### **SENNHEISER** SENNHEISER E602II BASS DRUM MIC A big fat bottom end with very smooth top-end. Can be used with no EQ. 20Hz-16kHz response, cardioid pat-



# **SENNHEISER**°

**SENNHEISER** E609-SILVER **INSTRUMENT MIC** This super-cardioid mic with a response of 40Hz-18kHz has the

unique shape which allows it to be hung on the amp. No SPL limits on this mic. DESCRIPTION ITFM PRICE E609-SILVER.... ..Silver finish super cardioid...... .109.95



SENNHEISER E900 SERIES CARDIOID **DYNAMIC INSTRUMENT MICS** Cardioid pattern dynamic microphones designed for instrument pick up in live performance and recording applications. Each has been specifically optimized for a particular family of instruments.

ITEM	DESCRIPTION	PRICE
E902	. For deep bass frequencies-kick drums, b	ass
	guitar amps, and tuba, 20Hz-18kHz	199.95
E904	.For drums — includes MZH 604 drum clip	),
	40Hz-18kHz	199.95
E905	. High SPL, excellent transient response, s	uitable
	for a wide range of instruments, ideal fo	r snare
	drums, 40Hz-18kHz	169.95
E906	. For guitar amps, percussion and horns.	
	Features a flat shape and three switchal	ole
	presence filter levels, 40Hz-18kHz	189.95

### SENNHEISER MD421-II **DYNAMIC CARDIOID** One of the most versatile and pop-

ular of Sennheiser's dynamic microphones. The MD421-II

is renowned for its sonic quality, ability to handle high sound pressure levels and durability. A favorite of musicians, broadcasters, recording studios and sound contractors. Five position bass roll-off switch provides equalization control up to 1000Hz. Humbucking coil to reduce interference from equipment and power.

ITEM	DESCRIPTION	PRICE
MD421-II	Dynamic cardioid	379.95
MZA421	Replacement stand bracket	27.33
	Windscreen	
20/421	Windtech windscreen	31 95

# **SENNHEISER**

### SENNHEISER MD441 **DYNAMIC SUPERCARDIOID** The MD 441 is acknowledged as the most

accurate and versatile dynamic mic available. It has a nearly textbook perfect supercardioid pattern, a five-position low frequency contour switch, a two-position high frequency switch, a critically dampened internal shock suspension, and a hum-bucking coil. Perfect for vocals and virtually every instrument.

ITEM	DESCRIPTION		PRICE
MD441U	Supercardioid,	30Hz-20kHz	899.95

# SHURE

SHURE 545SD-LC This microphone's remarkably faithful response makes it a favorite choice for instrument pickup, lecterns, speakers and entertainers. Dual impedance for use with most sound equipment. With locking on/off switch.

ITEM 545SD-LC	DESCRIPTION .Microphone	PRICE 92.54
	.Foam windscreen with	52.57
	locking feature (gray)	17.28
A2WS-BLK	.Foam windscreen with	
	locking feature (black).	17.28
A25D	.Replacement stand	
	adapter	5.76

SHURE BETA52A Its specially tailored, low frequency response is designed to deliver a new level of low-end punch on kick drums and other bass instruments. Adjustable, locking mount makes for fast, easy set up-even in the confines of a kick drum. It is designed to withstand the wear and tear of life on the road, with

	o o	
ITEM	DESCRIPTION	PRICE
BFTA52A	Supercardioid microphone	189 00

features like a hardened grille and shockmount.

SHURE BETA56A It mounts quickly and easily, thanks to its adjustable locking base and compact swivel head design. Features a wear-resistant, hardened grille and a unique shock mount that minimizes mechanical noise and pickup even in abusive environments both on and off stage

abusive ciivi	connicius both on and on stage	·•
ITEM	DESCRIPTION	PRICE
BETA56A	Supercardioid microphone	159.00
A1WS	Foam windscreen (gray)	6.33

SHURE BETA57A All the impact of the original SM57 with extended low bass response plus smoother, more gradual presence and extended high frequency response. With a steel grille and a true supercardioid polar pattern providing maximum isolation and minimum feedback this mic is excellent for instruments, studio and live performance.

ITEM	DESCRIPTION	PRICE
BETA57A	Supercardioid microphone	139.00
A57AWS	Locking magnetic windscreen	9.98
A25D	Replacement stand adapter	5.76





































































































SHURE PERFORMANCE **MICROPHONES** GEAR

Performance-Gear microphones, the Shure name and Shure quality at a great price. The PG57 is for both amplified and acoustic instruments. The PG52 is for kick drum for low-



end punch. The PG56 is for snare or tom and includes the A50D drum mount. All are dynamic cardioid and include stand mounts and 25' cable.

ITEM PG52-XI R	DESCRIPTION  Kick drum mic	PRICE 119 00
PG56-XLR	Drum mic	69.00

SHURE SM7B The smooth and silky unidirectional SM7 is famous for making voices and other sources sound their best. A humbucking coil has been added to this classic to help reject



interference in environments where computers are present. Extremely popular for radio and television, especially voice-overs. Unique graphic EQ tailoring switches permit the choice of four different response curves. Yoke assembly allows exact positioning.

ITEM	DESCRIPTION	PRICE
SM7B	.Cardioid microphone	.349.00
RK345	.Replacement foam windscreen	13.78
A7WS	.Closetalk windscreen	22.80



SM57 DYNAMIC CARDIOID MIC Exceptional for musical instrument pickup and vocals. With its bright, clean sound and contoured frequency response, the SM57 is ideal for musical instruments or vocals, live sound reinforcement and recording. It has an extremely effective cardioid pickup pattern which isolates the main sound source while minimizing background noise. In the studio, it is excellent for recording drums, guitar, and woodwinds.

ITEM	DESCRIPTION	PRICE
SM57LC	Dynamic mic, cardioid,	
	40Hz-15kHz, no cable	99.00
SM57X2U	SM57LC packaged with X2U	
	XLR to USB adapter	199.00
A2WS-BLK	Optional locking windscreen,	black . 17.28

# **EBYAMAHA**

YAMAHA SUBKICK SUB-FREQUENCY DRUM MIC

A speaker used as a very large diaphragm bidirectional dynamic

microphone, specifically designed to capture the low frequency (under 100Hz) frequency content of a kick drum. This is a 6 1/2" woofer shock mounted in a 7-ply birch/ mahogany black drum shell with mesh heads and tom-mounting bracket mounted directly to the shell. This mounts to a CL-940 ball clamp that slides into the base of a double-braced 800 series snare stand mounting stand (included). When used in conjunction with an in-phase conventional mic in the bass drum, it will deliver a deep punching kick drum sound. Also try it with upright bass, piano, and bass guitar cabinets. XLR output.

ITEM	DESCRIPTION	PRICE
SUBKICK	.Sub-frequency drum	microphone CALL



AUDIX DP SERIES DRUM MIC KITS Each kit contains a minimum of 5 mics. The D2 is designed to be used for toms and the D4 is designed for floor toms or small kick drums. The D6 is the quintessential kick drum mic and the i5 snare drum mic is designed for sonic accuracy, consistency and durability. The ADX51 and SCX condensers are ideal for hi-hat & overheads. The DVICE gooseneck rim mount allows for quick and easy set up and perfect mic placement. DESCRIPTION ITFM

<b>DP5A</b> 5-mic kit with (1) i5 snare, (2) D2-toms, (1) D4 kick/floor tom,
(1) D6 kick, (4) D-vice gooseneck clips
<b>DP7</b> 7-mic kit with (1) i5 snare, (2) D2 toms,
(1) D4 kick/floor tom, (1) D6 kick, (2) ADX51 condensers,
(4) D-vice gooseneck clips899.00
DP-ELITE8-mic kit with (1) i5 snare, (2) D2 toms,
(1) D4 kick/tom, (1) D6 kick, (2) SCX1 condensers,
(1) SCX1-HC hi-hat. (4) D-vice gooseneck clips


AUDIX FUSION SERIES DRUM MIC KITS Designed, assembled and tested in the USA, these mics fulfill all the performance criteria required for professional stage and studio applications. All mics come with high impact stand adapters and a heavyduty foam lined aluminum carrying case.

ITEM	DESCRIPTION	PRICE
FP4-FUSION	Kit includes: (1) F5 snare mic, (2) F2 tom mics, (1) F6 kick mic	249.00
FP5-FUSION	Kit includes: (1) F5 snare mic, (3) F2 tom mics, (1) F6 kick mic	329.00
FP7-FUSION	Kit includes: (1) F5 snare mic, (3) F2 tom mics,	
	(1) F6 kick mic, (2) F9 overhead condenser mics	459.00





AKG GROOVE PACK A complete 6-piece drum-kit mic pack with an aluminum carrying case, all mounting clamps and stand adapters. All PERCEPTION live microphones feature a metal casing, steel microphone grill, scratch-resistant finish, gold



PRICE (3) P4 tom/snare mics, (2) P17 overheads (P17 has identical specifications to P170).



CDMK-7 SHOWN WITH CASE



# AVANTONE DRUM MIC KITS

These rugged, elegantly designed drum microphones excel in live

sound as well as in the recording studio. They have zinc casted bodies, steel mesh grills, rugged SSM metal shockmount and Pro-Klamp drum rim mounts for superior isolation. The series consists of 3 dynamic microphone models: the ADM (snare mic), ATOM (tom mic), and the Mondo (kick mic). The CDMK6/7/8 models also include the CK-1 true

condenser mic for overheads/hi-hat. Each set includes a vintage style tweed case.

ITEM	DESCRIPTION	PRICE
CDMK-4	. (1) Mondo, (1) ADM, (2) ATOM, (4) SSM, (3) Pro-Klamps	. 425.00
CDMK-5	. (1) Mondo, (1) ADM, (3) ATOM, (5) SSM, (4) Pro-Klamps	. 499.00
CDMK-6	. (1) Mondo, (1) ADM, (2) ATOM, (2) CK1, (6) SSM, (3) Pro-Klamps	. 599.00
CDMK-7	. (1) Mondo, (1) ADM, (3) ATOM, (2) CK1, (7) SSM, (4) Pro-Klamps	. 699.00
CDMK-8	. (1) Mondo, (1) ADM, (3) ATOM, (3) CK1, (8) SSM, (4) Pro-Klamps	. 799.00
ADM	. Snare mic, dynamic cardioid (50Hz-16kHz) w/ Pro-Klamp and padded plastic case	79.00
ATOM	. Tom mic, dynamic cardioid (30Hz-15kHz) w/ Pro-Klamp and padded plastic case	89.00
CK-1	. Condenser FET mic with cardioid/hypercardioid capsules, SSM shockmount and wooden case	. 149.00





**PERCUSSION** PACKS Stage4 and

Stage7 feature combinations of the D29 dynamic tom mic, D19 supercardioid

dynamic snare mic, D10 cardioid dynamic kick drum mic and the C9 cardioid condenser overhead mic. Touring7

offers the TSM411 dynamic tom/snare mic, D12 dynamic kick drum mic and GXL1200 over overhead condenser mic.

ITEM	DESCRIPTION	PRICE
STAGE4	. Includes (2) D29 tom mics, (1) D19 snare mic,	
	(1) D12 kick drum mic w/ drum clips and vinyl carry case	119.99
STAGE7	. Includes (3) D29 tom mics, (1) D19 snare mic,	
	(1) D12 kick drum mic, (2) C9 overhead w/ drum/mic clips	
	and hardshell carry case	199.99
TOURING7	. Includes (4) TSM411snare mics, (1) D12 kick drum mic,	
	(2) GXL1200 overhead mic, (4) DMX-1 drum-mounting clips,	
	and metal carry case	299.99



**EARTHWORKS DRUMKIT™ SYSTEM Captures** every nuance of a complete drum kit using only a kick drum mic and a pair of overheads. DK25 kits feature either the SR25 cardioid mic (50Hz-25kHz) or the TC25 omnidirectional mic (9Hz-25kHz) and the KP1 KickPadTM mic, an external in-line module for use



with a bass drum. The DK25/L is for live reinforcement while the DK25/R is for studio recording. The DK50/R is the premium kit with a pair of QTC50 overhead mics with a frequency response of 3Hz-50kHz.

ITEM	DESCRIPTION	PRICE
DK25/L	. For live reinforcement, includes (3) SR25 cardioids,	
	(1) KP1 KickPad™, wood case	1999.00
DK25/R	For recording, includes (2) TC25 omnis, (1) SR25 cardioid	
	w/windscreen, (1) KP1 KickPad™, wood case	1549.00
DK50/R	For recording, includes (2) QTC50 omnis, (1) SR30 cardioid,	
	<ol> <li>KP1 KickPad™, stainless steel windscreen,</li> </ol>	
	(3) foam windscreens, (3) LevelPads™, case	CALL
KP1	.In-line pad and EQ module	99.00



HEIL SOUND HDK **SERIES** DRUM MICROPHONE KITS

These dynamic drum mic

kits feature proven microphones from the Heil Sound product line as well as several brand new mics designed specifically for demanding drummers. They come in a pad-



ded road case (HDK-5) or black hardshell carrying case, and include a new tom mount developed with input from jazz drummer Hunter Herman.

ITEM	DESCRIPTION	PRICE
HDK-5	(4) HMP-Plus, (2) HH-1 tom mounts, (1) PR48 for kick, (4) HM mic clip	ps. 765.00
HDK-7	(2) PR22 snare/hi-hat, (2) PR28 toms, (2) HH-1 tom mounts,	
	(2) PR30B overheads, and (1) PR48 for kick, (2) HM mic clips	1529.00
HDK-8-PRIMO	(2) PR22 snare/hi-hat, (3) PR28 toms, (3) HH-1 tom mounts,	
	(2) PR30B overheads, and (1) PR48 for kick, (2) HM mic clips	1645.00





**LEWITT DTP DRUM MIC KITS** These kits offer a selection of dynamic and condenser drum mics designed to offer performers and

engineers everything they need for live sound reinforcement as well as home and studio recording. All mics in these kits are extremely durable and feature a frequency response tailored for drums and percussion instruments. Both kits include mics. windshields, shock mounts, drum mounts and a rugged aluminum case for travel/ storage.

ITEM	DESCRIPTION	PRICE
DTP-BEAT-KIT-6	. 6-piece kit w/ (1) DTP340REX dynamic bass mic,	
	(3) DTP340TT dynamic tom/percussion mics,	
	and (2) LCT140 condenser overhead mics	699.00
DTP-BEAT-KIT-PRO-7	. 7-piece kit w/ (1) DTP640REX dynamic bass mic, (3) DTP340	OTTS
	dynamic tom/percussion mics, (2) LCT340 condenser overhead mics, and (1) MTP440DM dynamic snare mic 1	299.00

# T SENNHEISER

### SENNHEISER DRUMKIT-600 DRUM

MIC KIT Includes (1) e602-II for the kick drum, (4) e604s for snare and toms, and (2) e614s for overheads. The e602-II is a cardioid mic designed for low frequency instruments. The e604 handles SPL ratings of over 150dB and has a cardioid pattern optimized for use on drum sets. It is housed in a tough, reinforced glass fiber body and has an inte-



grated, pivoting mount that can attach to mic stands or the rim of a drum. The e614's supercardioid pattern, neutral response and moderate sensitivity ensures optimum isolation. The phantom-powered e614 tolerates extremely high SPLs and precisely captures cymbals and hi-hats.

ITEM	DESCRIPTION	PRICI
DRUMKIT-600	Drumset microphone kit	999.95

# SHUR

SHURE DMK57-52 DRUM MIC KIT This kit is ideal for a kick drum, snare drum, and rack/floor toms. Includes (3) SM57 mics, (1) Beta 52A mic, (3) A56D drum-mounting systems, and a lightweight carrying case. The SM57 cardioid dynamic mic is perfect for a snare drum & toms. The supercardioid Beta 52A is perfect for a kick drum and

is designed with an integral locking stand mount for easy set up. The A56D universal mounting system can be used to position mics virtually anywhere.

ITEM	DESCRIPTION	PRICE
DMK57-52	Drum mic kit with (3) SM57 mics, (1) Beta 52A mic,	
	(3) A56D mounts, case	399.00

### SHURE PG SERIES DRUM MIC KITS

All-in-one mic kits including XLR-to-XLR cables, drum mounting hardware, and carrying case. Each mic has a tailored frequency response tuned specifically for drums. The PG56 is a compact drum mic for up-close recording. The PG52 is designed for the kick drum while the PG81 is ideal for overhead & cymbals



i doi is ideal loi o	verneau & cymbais.	PGDMK4-XLR	PGDMK6-XLR
ITEM	DESCRIPTION		PRICE
PGDMK4-XLR	4-mic drum kit with (3) PG56 mid	cs, (1) PG52 mic,	
	(3) A50D drum mounts, (4) XLR c	ables, case	249.00
PGDMK6-XLR	6-mic drum kit with (3) PG56 mid	cs, (1) PG52 mic,	
	(2) PG81 mics, (3) A50D drum mo	ounts, (6) XLR cables,	case 399.00

# Select Accessories for Percussion Mics








































































































AKG MICROMIC™ MINIATURE MICROPHONES Each MicroMic offers a flexible gooseneck for optimal positioning, an elastic suspension to suppress spurious noise, metal capsule housings and detachable cable. These cardioid mics also have an adapter plate that allows them to be attached directly to AKG WMS40PRO and WMS400 bodypack transmitters, eliminating cable run between the mic and wireless transmitter.

ITEM	DESCRIPTION	PRICE
C516ML	.For accordion, guitar speakers, piano and keyboard/organ cabinets	189.00
C518M	.For drums & percussion (external phantom power)	249.00
C518ML	.For drums & percussion, for use with B29L, AKG WMS	
	bodypack transmitter	189.00
C519M	.For woodwinds & brass (external phantom power)	249.00
C519ML	.For woodwinds & brass, for use with B29L,	
	AKG WMS bodypack transmitters	189.00
B29L	.Portable phantom (battery powered)	99.00

AKG C411/L ACOUSTIC PICKUP FOR STRING **INSTRUMENTS** This condenser acoustic pickup with its tailored frequency response is ideal for acoustic guitar, mandolin, violin and most other stringed instruments. Placing the small ultra-light C 411 on or near the bridge will reproduce a clear and uncolored sound without changing tl in

	of the instrument. Attaching it is easy with the -marring reusable adhesive compound.	(	
ITEM	DESCRIPTION	PR	ICE
C411/I	Acoustic instrument nickup Figure-8 polar nattern 1	0Hz-18kHz 139	00



APPLIED MICROPHONE TECHNOLOGY M40 PIANO MICROPHONE This omnidirectional condenser mic is especially suited for piano, but also works well for boundary layer recording. With its mono design, the system can

be used even when the piano lid is closed. The M40's signal can also be split with frequencies rolled off to create a stereo image. It can pick up sound pressure levels up to 141dB, and its rugged construction of anodized aviation aluminum is lightweight and durable. Comes with an AP40 aluminum preamp and protective case.

ITEM	DESCRIPTION	PRICE
M40	. Omni-condenser piano mic	453.00

# 🖾 audio-technica。

always listening...

**AUDIO-TECHNICA ATM350 CARDIOID CONDENSER CLIP-ON** INSTRUMENT MICROPHONE Supplied with Audio-Technica's versatile UniMount® clip and new violin mount, the low-profile ATM350 is an exceptional cardioid condenser microphone designed to clip to brass, reeds, piano, snare, toms, and violin. The microphone offers a crisp, clear, well-balanced response, even at high SPLs. It features an integral 80Hz hi-pass filter and is also equipped with a new in-line power module. Its cardioid polar pattern reduces pickup of sounds from the side and rear

for effective protection against feedback.		
ITEM	DESCRIPTION	PRICE
ATM350	Clip-on condenser mic, 40Hz-20kHz	279.00
AT8418	Replacement instrument mount and windscreen	38 33

AUDIO-TECHNICA PRO35 CARDIOID CONDENSER CLIP-ON **INSTRUMENT MICROPHONE** Designed for saxophones, tom brass and percussion, the PRO35 excels in high-SPL applications and is ideal for active stage performances. A UniMount clip permits accurate positioning, provides shock resistance and protects the element. Switchable low frequency roll-off at 80Hz. 6' cable permanently attached between microphone and power module, XLRM connector on module.

ITEM	DESCRIPTION	PRICE
PR035	. Cardioid, 50Hz-15kHz	146.28



C519

AUDIX ADX10-FL FLUTE MIC A miniature, high performance professional condenser mic with a custom

designed flute head joint mount which keeps the microphone in place, making it ideally suited for live performance. With a smooth uniform response over a frequency range of 40Hz-20kHz, the ADX10-FL offers a warm, rich sound not typical of microphones this size. The ADX10-FL comes in a wired format and can easily be adapted to a wireless system. Operating on phantom power of 9-52V with the provided pre-amp module, this microphone can also be used in battery mode with an optional power supply.

ITEM	DESCRIPTION	PRICE
ADX10-FL	. Flute microphone	199.00
APS-911	. Optional battery power supply	49.95

AUDIX ADX20-IP Pre-polarized condenser microphone designed to handle a wide variety of clip-on applications. It is ideally suited for saxophone, trombone, trumpet and other brass instruments. With a smooth uniform response over a frequency range of 40Hz-20kHz, it provides a rich, warm sound not typical of microphones this size. Low noise electronic circuitry, and balanced low impedance output allow for interference-free performance even with long cable runs. Phantom power required.

1	3 1	
ITEM	DESCRIPTION PR	RICE
ADX20-I		3.00

AUDIX MICRO-D Pre-polarized condenser microphone designed for many applications including drums, percussion, amplified cabinets, speech, vocals and acoustic instruments. Can be used in conjunction with 3 different specialized clips and 2 different interchangeable capsules to fulfill a wide variety of creative needs. Operates on phantom power of 9-52V and is supplied with a phantom power adapter, integral D-vice clamp, cable, windscreen, and carrying pouch.



ITEM	DESCRIPTION	PRICE
MICRO-D	40Hz-20kHz, hypercardioid, 250ohms	189.00

**BARCUS-BERRY 4000 PIANO** DARCUS- & HARP PLANAR WAVE **DERRY** SYSTEM Recording a piano can be a nightmare but this piano

pickup reproduces the keyboard's full frequency range with perfect amplitude balance. It provides excellent

isolation from ambient sounds with superior feedback rejection. It is quick to set-up - no holes to drill. Includes preamp with 1/4" hi-Z and XLR lo-Z outputs, piezo crystal, adhesive patches, 4 rubber feet & instruction guide. Accepts phantom power.

DESCRIPTION PRICE 294.99 Piano pickup



BARCUS-BERRY ACOUSTIC INSTRUMENT PICK-UPS A specialized line of pickups designed for specific instruments to provide high quality pick-up, free of hum and feedback in amplified live performance applications. They are ideal for use with wireless transmitters to permit free movement on the stage.

ITEM	DESCRIPTION	PRICE
1320	Violin bridge w/ built in piezo pickup, 1/4" output jack	99.99
1457	Outsider piezo transducer, 1' cable	54.98
1457XL	Outsider piezo transducer, 2' cable	55.82
1460	Acoustic guitar bridge pickup for 6-string instruments	47.00
3100	Violin clamp-on piezo pickup, 1/4" output jack	111.58
3125	Cello clamp-on piezo transducer w/ pre-amp	227.65
6100	Flute electret mic w/ preamp/power supply, headjoint cork	259.00
B3150	Bass piezo transducer & preamp, clamp style w/ preamp	266.58
DISQ-0S	External mount soundboard transducer	39.00
MAPLEBAR	Single-coil pickup for acoustic guitar w/ 12' cable and 1/4" plu	g 52.95





# SENNHEISER

SENNHEISER E604 INSTRUMENT MIC Designed for instrument miking, this compact microphone has an integrated swivel mount and can easily fit into small spaces like drum kits. Its housing is a new glass fiber composite and its ruggedness makes it ideal for touring. The cardioid pattern, neodymium magnet and featherweight membrane provide enhanced low end response and excellent transient response. Includes integrated stand mount and detachable drum mount.

ITEM F604	DESCRIPTION Cardioid mic. 40Hz-18kHz	PRICE 139 95
	Replacement mic mount	
THREEPACK604P	Three pack of E604s, 3 pouches	349.95



# beyerdynamic)

### BEYERDYNAMIC TOURING GEAR D SERIES CLIP ON DRUM MICS

The TGD52d is a hypercardioid dynamic mic designed for toms and features channel separation reducing crosstalk, high SPL handling, treble resonator for optimal high frequency reproduction and a quick

mounting gooseneck. The TGD57c is a cardioid condenser mic designed for toms, snare or percussion and features expanded frequency range, patented quick mounting, 72mm flexible gooseneck, treble resonator, 2nd treble resonator, and a frequency-independent polar patter. The TGD58C is a cardioid condenser mic for rack toms, snare or percussion has the same features as the TGD57C plus an integrated pre-amplifier, low resonance housing.

ITEM	DESCRIPTION	PRICE
TG-D52D	. Clip-on cardioid dynamic mic	159.00
TG-D57C	. Clip-on cardioid condenser mic	189.00
TG-D58C	. Clip-on cardioid condenser mic with integrated pre-amp	141.75

### **DPA 4099 SERIES INSTRUMENT**

MICS Each 4099 is designed and optimized for one particular instrument family to ensure the finest audio reinforcement when performing live. These condens-



er microphones feature supercardioid polar patterns for highly uniform off-axis frequency response, superior gain-before-feedback, and are capable of handling high sound pressure levels. The versatile gooseneck provides stable positioning, and can easily be unclipped and repositioned with only one hand. The gentle mounting system will not mar the finish of the instrument. The included MicroDot connector and more than 35 available DPA adapters (purchased separately) ensure compatibility with just about any wireless system. It can also be used as a standard 48V phantom powered microphone with the supplied XLR connector.

HEM	DESCRIPTION	PRICE
4099-GUITAR	. Guitar microphone with MicroDot connector	599.00
4099-SAX	. Sax microphone with MicroDot connector	579.00
4099-TRUMPET	. Trumpet microphone with MicroDot connector	579.00
4099-VIOLIN	. Violin microphone with MicroDot connector	599.00
MicroDot Adapters	•	
DAD6008	. For Sony WRT8020/860	93.00
DAD6010	. For Shure TA4F	87.00
DAD6019	. For Sony WRT805, Sennheiser Evolution/SK300	87.00
DAD6020	. For Telex TA4F	73.00
DAD6021	. For Lectrosonic TA5F	73.00
DAD6034	. For Sennheiser Evolution G2	80.00
1		



EARTHWORKS PIANOMIC™ SYSTEM This system meets piano recording needs for churches, performing arts centers and recording studios with high definition audio - whether the piano lid is up or down. It cannot be seen from outside the piano, needs no stands or mic booms, and allows virtually no leakage from sounds outside the piano. The touring version is collapsible and fits in an airline carrying case.

ITEM	DESCRIPTION	PRICE
PM40	. Omni (random-incidence), 48V, 9Hz-40kHz	2999.00
PM40T	. Touring version, collapsible, fits in smaller case	3199.00
PMVM1	. Leather pouch for PM40/PM40T electronics box	129.00

### SENNHEISER®

SENNHEISER E908B CLIP-ON CONDENSER MIC The e908b condenser mic has an exceptionally lively and clear sound, designed for brass instruments. Comes with a mounting clamp for quick, flexible set-up and optimal positioning with the long-necked, flexible boom. The e908d is designed for drums and percussion, and comes with a drumset clamp and integrated shock absorber. Includes MZA 900 P pre-amp (cable, phantom power and level check.)

ITEM	DESCRIPTION	PRICE
E908B	For brass	279.95
E908B-EW	Wireless version of E908B	199.95
E908D	For drums	279.95



SHURE BETA98 CONDENSER MINIATURE MICS High-performance mini-condenser mics for sound reinforcement and recording. Great for instruments or drums. The ultra-uniform pickup pattern provides high gainbefore-feedback and excellent rejection of unwanted noise. Other features include a frequency response of 20Hz-20kHz, an included preamplifier, integrated shockmount and windscreen.

U		
ITEM	DESCRIPTION	PRICE
BETA98H/C	. Clip-on instrument mic w/ preamp, 155dB max SPL	. 209.00
WB98H/C	. Wireless version of BETA98H/C, 10ft cable terminated	
	w/4-pin mini (TA4F), 156dB max SPL	. 134.65
BETA98A/C	. Instrument mic w/ preamp, RK282 for standard mic stands,	
	144dB max SPL	. 199.00
BETA98AD/C	. Drum mic w/ preamp, A98D drum mount, 144dB max SPL	. 229.00
BETA98AMP/C	. Drum mic w/ preamp, A75M universal mount, 153dB max SPL	. 269.00
A75M	. Universal mic mount w/ clip adapters (large and small)	86.45
A98D	. Clip-style mic mount	65.55














































































































AEA LARGE RIBBON MICROPHONES These Large Ribbon Geometry (LRG) mics have a wideband response from

20Hz-20kHz, low self-noise and high SPL capabilities. The R84 features a pure natural sound, figure-8 directional sensitivity and quick smooth transients. The A840 is the



active version of the R84 and requires less gain than passive ribbons. The R88 is a stereo mic with 2 ribbon motors that are oriented at 90°, has excellent off-axis frequency response and is specifically designed for recording orchestras and choirs. The R92 has reduced proximity bass boost and excellent wind-blast protection making it suitable for close recording (6-12"). The KU4 features a supercardioid pattern, reduced proximity effect, field-tech replaceable ribbon assembly, and smooth, highbandwidth frequency response.

ITEM	DESCRIPTION	PRICE
R84	General-purpose large ribbon mic, includes case, 165 max SPL	990.00
R84SLE	Silver Limited Edition version of R84, 165 dB max SPL	1102.50
A840	Active version of R84, 141 dB max SPL	1552.50
R84DJV	R84 variation optimized for close-up voice reproduction	1080.00
R88	Stereo large ribbon mic, includes case & 4 meter 5-pin female	
	XLR to 3-pin male XLR break-out cable, 165 dB max SPL	1705.50
R92	Large ribbon mic for close recording, includes case,	
	manual & 2 meter captive cable, 135 dB max SPL	810.00
KU4	Supercardioid ribbon mic, includes case, stand adapter,	
	manual & attached 1.5 meter cable, 140 dB max SPL	CALL
R84SC	Soft case for the R84 series	40.00
R84VC	Vertical storage and shipping case for R84 series	150.00
	Twin vertical storage and shipping case for R84 series	
TRP	2-channel ribbon mic preamp	

### AEA A440/R44 SERIES RIBBON MICROPHONES

The active A440 ribbon mic has a 126.5dB dynamic range, and a quiet noise level of 6dB SPL. At low frequency ranges, it delivers bass with effortless authority. It has a smooth and articulate midrange, and at the high end, transients are quick and detailed without hard edges. This hand-built mic features authentic RCA New Old Stock ribbon material, flat frequency response and holds an accurate figure-8 polar pattern down to 20Hz. The R44C is a handmade museum-quality replica of the 1936-38 RCA 44, which uses 1.8-micron thick ribbon mate-



rial originally manufactured by RCA. The R44CX is a high output (+6dB) version of the R44C. The R44CNE combines RCA Ltd's British engineering with the RCA 44's sound to reduce the mic's weight and hum sensitivity. Features satin aluminum, instead of chrome. All come with stand adapter, and vertical case for proper storage or shipping. R44C/X/NE models come hard-wired with 6ft XLR output cable.

ITEM	DESCRIPTION	PRICE
A440	Phantom powered ribbon mic, 20Hz-20kHz	CALL
R44C	Hand-crafted ribbon microphone (exact RCA44BX replica)	CALL
R44CX	High output (+6dB) version of the R44C	CALL
R44CNE	International edition of R44C	2790.00
TRP	2-channel ribbon mic preamp	868.50


# (AVANTONE)

### AVANTONE CR-14 DUAL RIBBON MICROPHONE

This retro-design bi-directional velocity ribbon mic is ideal for studio and home use. A dual-ribbon mic offers better sensitivity as well as a fuller, more natural sound than most single-ribbon mics. Includes a wooden box, suspension shockmount, and metal road case.

ITEM	DESCRIPTION	PRICE
CR-14	Dual-ribbon, figure-8 pattern,	30Hz-15kHz,
	145dB max SPL (.5% THD@1)	(Hz) 259.00





Class "A" discrete handmade electronics with the bold sound of a handmade aluminum ribbon. It's designed to be highly durable and delivers a focused mid-range, ultra-smooth top end and outstanding bass response. Includes custom mount, and cherrywood box.

ITEM	DESCRIPTION	PRICE
WOODPECKER	Active ribbon microphone, figure-8 polar pattern, 20Hz-20kHz	999.99



APEX RIBBON MICROPHONES These ribbon mics feature smooth, natural frequency responses, yet handle extremely fast transients accurately. The figure-8 pickup pattern has an extended sweet spot on the backside for accurate reproduction of a live room with fast transient response and stunning realism.

E
99
99
99

## (A) audio-technica always listening...

AUDIO-TECHNICA AT4080 & AT4081 RIBBON MICROPHONES These mics provide smooth and natural high-fidelity sound for both studio and live settings. A figure-8 polar pattern picks up sound equally from front and back. Both models feature dual ribbon construction for increased sensitivity, 150dB max SPL, and



APEX210

MicroLinear™ ribbon imprint, which protects the ribbons from lateral flexing and distortion, while the ultra-fine mesh guards against ribbon damage. The AT4080 offers acoustic baffle system and a large output transformer to provide low-frequency response and extended dynamic range. The AT4081's low-profile stick design maximizes placement options.

	· · · · · · · · · · · · · · · · · · ·	
ITEM	DESCRIPTION	PRICE
AT4080	Side address microphone, 20Hz-18kHz	. 999.00
AT4081	Active ribbon pencil microphone, 30Hz-18kHz	699.00

# beyerdynamic)))

### BEYERDYNAMIC M130 BI-DIRECTIONAL DOUBLE RIBBON MIC

This unique double-ribbon designed element has superb response with detailed sound reproduction. It has a constant figure eight pattern and smooth response throughout the frequency spectrum. It can produce a true summed stereo to mono image using Mid-Side Technique. Freq. response is 40Hz-18kHz.

ITEM	DESCRIPTION	PRICE
M130	. Bi-directional double ribbon mic	699.00

### BEYERDYNAMIC M160 HYPERCARDIOID DOUBLE RIBBON MIC

Dynamic double ribbon microphone featuring a hypercardioid polar pattern, the M160 is an outstanding microphone for all types of remote and in-studio voice reproduction. Recommended for studio miking of string instruments such as violins, violas, cellos and for pianos, saxophones as well as for hi-hat, and toms. In conjunction with the M130 ribbon microphone the M160 is ideal for stereo recordings in MS technique.

ITEM	DESCRIPTION	PRICE
M160	. 40Hz-18kHz, hypercardioid	699.00

BEYERDYNAMIC M260 RIBBON MICROPHONE This mic is great for vocals and capturing live instrument performances at studio recordings. Its flat frequency response and natural sonic profile make it a highly effective element of the digital recording process. The hypercardioid polar pattern provides an extremely high gain-before-feedback and elimination of lateral noise (maximum at 115°). The M260 is equipped with a built-in hi-pass-filter which compensates for proximity effect when the microphone is very close to an instrument. The microphone also features a high insensitivity towards magnetic stray fields and extreme temperatures. The rugged grille protects the microphone against accidental hits and kicks.

ITEM	DESCRIPTION	PRICE
M260	Hypercardioid dynamic ribbon microphone, 40Hz-18kHz	449.00





Follow us!



R122V

SF12

R121



**CLOUD MICROPHONES JRS-34** RIBBON MICS Handcrafted in the US, these mics combine the best of vintage and modern technologies to

create a high-quality ribbon microphone ideal for music and vocalists. The JRS-34 Active mic requires phantom power and has an output level compatible with virtually any modern preamp. The JRS-34 Passive, like other passive ribbon mics,

requires a high-gain preamp with over 60dB of gain. The Cloudlifter comes in a single and 2-channel version and uses transparent direct-



couple JFET circuitry to give passive mics active output levels up to 25dB of boost. Phantom powered from the secondary input, it's safe to use with ribbon mics, as the +48V current doesn't transfer through. Each mic includes a hand-crafted

Wooden bon.		
ITEM	DESCRIPTION	PRICE
JRS-34-ACTIVE	Active ribbon, figure-8 pattern,	
	20Hz->20kHz, brushed nickel finish	1699.00
JRS-34-PASSIVE	Passive ribbon version of the JRS34,	
	grey powdercoat finish/nickel screens	1399.00
CLOUDLIFTER-CL2	2-channel portable passive mic preamp	249.00
	1-channel portable passive mic preamp	




### **RIBBON** COLES **BI-DIRECTIONAL**

MICROPHONES The 4038 is a BBC Designed COLES ribbon mic which features excellent transient response and accurate, clear and natural reproduction. Features include a low-mass damped ribbon, extremely low distortion and hum-neutralizing shielding. The housing is uniquely

shaped to enhance acoustic performance. With a bold look, greater output, and a frequency response that is exceptionally flat, the 4040 represents the latest in magnet technology. The elements are gold-plated and internally shockmounted and it includes a universal stand mount and hard case.

ITEM	DESCRIPTION	PRICE
4038	Figure-8, 30Hz-15kHz	. 1316.25
4040	Figure-8, 30Hz-20kHz	. 1403.78

COLES 4050 STEREO RIBBON MICROPHONE Not only a stereo mic, the 4050 transforms from its stereo configuration into two completely separate mono mics. The mount has magnets that allow the two mono mics to connect together transforming it into a stereo mic. The 4050 was developed from the critically acclaimed Coles 4040 capsule which features extended frequency response and high output making it very versatile.







SONTRONICS RIBBON MICS The APOLLO is a Blumlein XY stereo mic with an open basket design,

allowing it to soak up every nuance and capture the ambience for a complete & silky smooth sound. One channel for mono recordings can be used as well. It includes a custom shockmount, a cable and velvet-lined ABS flightcase. The DELTA is ideal for recording guitar amps, saxophones, brass, woodwind, & stringed instruments. It comes with a custom shockmount and a rugged aluminum flightcase.

The SIGMA has punchy low-mid frequency responses and a smooth high frequency roll-off, producing very natural sound. It is ideal for vocals, flute, saxophone, acoustic guitar, and accordion but can also be used for drums overhead. Comes with custom shockmount and a velvet-lined aluminum case.

ITEM	DESCRIPTION	PRICE
APOLLO	X/Y stereo/figure-8 ribbon mic, 10Hz-20kHz, 48V phantom power	1699.00
DELTA	Figure-8 ribbon mic, 20Hz-15kHz, 48V phantom power	949.00
SIGMA	Figure-8 ribbon mic, 20Hz-20kHz, 48V phantom power	829.00



**PASSIVE** 

**ROYER RIBBON MICS** Smooth and clear with many of the attributes of condenser mics but with a wider dynamic range without pads and clipping. The frequency response is very flat and the panoramic soundfield is well balanced.

The figure-8 bi-directional pattern offers excellent rejection at the sides - the ribbon is lengthwise providing a side-address type microphone. The R-121 is compact & lightweight, but with high out-

put. The R101 bears an offset-ribbon transducer, a 2.5 micron ribbon, and is great for studio and live settings. The R-122 has a

48V phantom powered internal amplifier to provide 15dB more gain. The SF-12 offers 2 matched ribbon mics placed one above the other, each aimed  $45^{\circ}$  from the center in the classic Blumlein configuration. The SF-24 is an active version of the SF-12 and its output of 38dB is a full 14dB more sensitive than the SF-12.

"LIVE" models feature a thicker, more durable ribbon suitable for the rigors of live stage applications. All models except for the SF12 come solely in a nickel finish.

ITEM	DESCRIPTION	PRICE
R101	Mono passive ribbon microphone	799.00
R121	Mono ribbon microphone	1295.00
R121-LIVE	R121 with thicker ribbon	1295.00
R122	Mono active ribbon microphone	1750.00
R122-LIVE	R122 with thicker ribbon	1750.00
R122V	Vacuum tube version of R122	2795.00
SF12	Stereo ribbon microphone, matte black (nickel finish optiona	1) 2695.00
SF24	Stereo active ribbon microphone, matte black	CALL
SF-24V	Vacuum tube version of SF24	CALL
AT84	Shockmount	77.00
PS101	Metal popscreen	59.00
WS58	Foam windscreen for R121, R122	21.00
WS12	Furry windscreen for SF12 & SF24	135.00



### SE VR1 & VR2 VOODOO RIBBON MICS These mics achieve full frequency response using a


new mechanical device (patent pending), designed by Siwei Zou. The Voodoo's brings traditional ribbon sound to the project and commercial studio, but extends it to perform as well as most condensers do. The result is superbly

detailed and wonderfully open and natural sounding recordings of acoustic instruments and guitar cabs. The VR2 is an active version

ITEM	DESCRIPTION	PRICE
VOODOO-VR1	Ribbon microphone, figure-8, 20Hz-18kHz	699.00
V00D00-VR2	Active ribbon microphone, figure-8, 20Hz-18kHz	999.00

SE RNR1 RUPERT NEVE ACTIVE RIBBON MIC A solid-state mic built with a transformer-input, transformer-output design, using discrete Class "A" components and circuitry similar to that found in the Rupert Neve Designs 5088 mixer. It offers warm and silky lows and incredible depth and air to mid frequencies. Has a clarity and impact in high freissed.

quencies that revea	ais vitai narmonic information that is normally	mı
ITEM	DESCRIPTION	Ρ
RNR1	. Ribbon microphone, figure-8, 20Hz-25kHz,	
	101/ 1 1 1 1	100





Æ

SHURE RIBBON MICROPHONES Featuring Roswellite<sup>TM</sup> ribbon technology for superior resilience at extreme SPLs, these premium mics are crafted for studio and concert hall applications. The KSM313 offers a dual-voice design and bidirectional polar pattern. The KSM353 has a bidirectional polar pattern, features a custom ribbon motor assembly and double-shielded matched full-sized transformer for minimizing signal loss. Both offer 146dB SPL across 30Hz-15kHz frequency response, and 3-pin XLR.

TEM	DESCRIPTION	PRICE
KSM313	Dual-voice ribbon mic, black & red	1295.00
KSM353	Premier bi-directional ribbon mic, silver	2695.00




























































FULLCOMPASS.COM

Full Service: 800-356-5844

M-F: 9:00-5:30 CST



















ITFM































AKG BLUE LINE A modular mic system that offers flexibility and ease of use. Comprised of one preamplifier, 5 capsules, and many accessories. The capsules are

active with internal amplifiers which allows them to be mounted remotely from the preamp without degradation. Operates from phantom power (12-48V),



the preamp also has a 10dB pad and 75Hz roll-off filter switch.

ITEM	DESCRIPTION	PRICE
SE300B	Preamp unit	289.00
C391B	. Combo SE 300/CK91	539.00
CK91	. Cardioid capsule	199.00
CK92	. Omni capsule	199.00
CK93	. Hypercardioid capsule	199.00
CK94	. Figure-8 capsule	499.00
	. 10" shotgun capsule	

**AKG PERCEPTION CONDENSER MICROPHONES** These five mics feature true condenser capsules, 20Hz-20kHz frequency response, switchable 20dB pad for 135/155dB max SPL, switchable low-cut filter (except on 170), rugged die-cast chassis and goldplated 3-pin XLR outputs (except 820). The 220, 420 & 820 each include a shock mount and metal case.

DESCRIPTION

PERCEPTION120 Large .667" diaphragm cardioid condenser 99.00
PERCEPTION170 Small 1/2" diaphragm cardioid condenser,
no low-cut filter99.00
PERCEPTION220 Large 1" diaphragm cardioid condenser 179.00
PERCEPTION420 Dual-capsule, multi-pattern condenser
(cardioid, omni, figure-8)249.00
PERCEPTION820 9-pattern (cardioid, omni, figure-8, six
intermediate patterns), ECC 83 tube,
dual-capsule condenser, includes 7-pin
cable and remote control unit



The C214 is a cost-effective alternative to AKG's C414 series microphones, using the same 1" diaphragm in a single-capsule, cardioid-only design. Its dynamic range is up to 156dB SPL and features an integrated suspension to reduce mechanical noise, a 20dB attenuation pad, 13dB noise floor, and low cut switch. The double mesh, all-metal grille protects the capsule while ensuring high RF immunity. The all-metal diecast body and scratch-resistant finish also ensures protection.

ITEM	DESCRIPTION	PRICE
C214	.Large single capsule cardioid condenser microphone w/	shock
	mount, windscreen & metal carrying case	399.00
C214-ST	.Matched stereo pair of C214 mics w/shock mounts,	
	stand adapters, windscreens & metal carrying case	899.00

**AKG C414 STUDIO MICROPHONES** dual 1" diaphragms with flat 20Hz-20kHz merless output, all-metal shielded co powering, electronic switching of pic -12dB and -18dB pre-attenuation levels, at 40Hz, 80Hz and 160Hz. These version now have intermediate settings for 9 po as control Lock Mode and Peak Hold LEI in an all-metal road case with an H-85 external 2-stage pop-filter, and W414 Also available in factory-matched stereo pairs packaged with C414/XLS an H50 stereo bar instead of the external pop-filter.

These mics feature is response, transfor- onstruction, phantom ckup patterns, -6dB, and bass cut filters is of the C414 classic olar patterns, as well in the complete is shockmount, a PF80 external windscreen	主。
external windscreen.	24440

PRICE

ITEM	DESCRIPTION	PRICE
C414/XLS	Classic sonic character for beautifully detailed	
	pickup of any acoustic instrument, 9 patterns,	
	control Lock Mode and Peak Hold LED	999.00
C414/XLS-STEREO	Stereo XLS pair with H50 bar mount	2199.00
C414/XLII	Distinctive timbre especially for recording solo vocals	
	and solo instruments, 9 patterns, control Lock Mode	
	and Peak Hold LED	999.00
C414/XLII-STEREO	Stereo XLII pair with H50 bar mount	2199.00

AKG C1000S STUDIO CONDENSER A cardioid electret condenser microphone with an adapter for a hypercardioid pattern. Operates on either a 9V battery or 9 to 52V phantom power. Response is from 50Hz-20kHz with a 6dB roll off below 200Hz to compensate for presence boost in close-in use and reinforcement applications. Capable of 137dB sound pressure level. 1.3" diameter, 8.7" long, includes stand clamp.

	, ,,	•		19
ITEM		DESCRIPTION	PRICE	ı
C1000S		Cardioid microphone	199.00	14

#### **LOOKING FOR THESE BRANDS?**





VISIT FULLCOMPASS.COM OR CALL 800-356-5844 FOR MORE INFO



**AKG C451B MICROPHONE** It has an acoustically identical version of the legendary CK1 capsule that is permanently mounted. This combination can handle high output transients as well as subtle harmonics. Also included are switchable 75Hz & 150Hz 12dB per octave rolloff, & switchable -10 &

-20dB input pad. It is a single pattern (cardioid), & has frequency response of 20Hz-20kHz with 135dB SPL. Requires 12 to 48V phantom power. Kit comes with bag, windscreen and clip.

0.	•	
ITEM	DESCRIPTION	PRICE
C451B	. Cardioid condenser microphone	579.00
C451B-STEREO-PAIR.	. Stereo pair of C415B	. 1299.00

#### **(A)** audio-technica. always listening...

AUDIO-TECHNICA AE5100 CARDIOID INSTRUMENT For overheads, percussion, acoustic guitar, strings. Large diaphragm, 80Hz low cut filter switch, 10dB pad, AT8471 isolation clamp, requires phantom power.

		• •	•	•
ITEM	DESCRIPTION			PRICE
AE5100	Cardioid instrument m	ic, 20Hz-20kHz		279.00

AUDIO-TECHNICA ATM450 CARDIOID CONDENSER **INSTRUMENT MIC** This microphone's extended flat frequency response makes it ideal for high SPLs and for live and amplified acoustic instruments. Side-address stick design for endless placement options. Equipped with an 80Hz hi-pass filter and 10dB pad. Includes an isolation clamp.

ITEM	DESCRIPTION	PRICE
ATM450	Cardioid condenser instrument mic, 40Hz-20kHz, 152dB max SPL	. 249.00

AUDIO-TECHNICA AT2020 CARDIOID CONDENSER MIC A sideaddress studio condenser microphone featuring high SPL handling and wide dynamic range. Custom-engineered 16mm low-mass diaphragm provides extended frequency response and superior transient response. Cardioid polar pattern reduces pickup of sounds from the sides and rear, improving isolation of desired sound source. Pivoting, threaded stand mount attaches securely for easy and precise placement of the microphone.

	 •	•		•		_
ITEM	DESCRI	PTION				PRICE
AT2020	 Cardioid	condenser.	20Hz-20kHz.	144dB r	nax SPL	99.00

AUDIO-TECHNICA PRO37 SMALL DIAPHRAGM CARDIOID CONDENSER MIC A low-profile design enables optimal placement making this mic ideal for acoustic guitar, overheads, piano and group vocals. The low-mass element gives superb transient response and it also excels in high-SPL applications.

ITEM	DESCRIPTION	PRICE
PR037	Cardioid mic, 30Hz-15kHz, 141db max SPL	119.00

## AUDIO-TECHNICA AT4033/CL STUDIO MICROPHONE

Large diaphragm studio microphone with low noise transformerless electronics (17dB). 80Hz switched filter, smooth response to 20kHz, requires 48V phantom power and includes AT8449 spider type shockmount.

ITEM	DESCRIPTION	PRICE
AT4033/CL	Studio cardioid	399.00
AT8137	Windscreen	37.54







Follow us!

# Designed, Assembled & Tested by Audix... in the USA.



FULL COMPASS

PRO AUDIO | VIDEO | AV | LIGHTING
MUSICAL INSTRUMENTS

800-356-5844 FULLCOMPASS.COM Designing great microphones for over 25 years.



















































## (A) audio-technica. always listening...

AUDIO-TECHNICA AT2035/AT2050 Bundled together at a great price, the AT2035 condenser mic is equipped with a switchable 80Hz hi-pass filter and 10dB pad, and comes with a protective pouch and a custom shock mount. The ATH-M20 dynamic headphones features a low-profile, closed-back design, 40mm drivers (each with a neodymium

magnet structure), adjustable cushioned headband, gold-plated stereo 1/8" connector with strain relief and snap-on 1/4" adapter, 10' coiled cable with single-side exit.

ITEM	DESCRIPTION	PRICE
AT2035/ATHM20	Includes AT2035 cardioid condenser mic (20Hz-20kHz)	
	& ATH-M20 closed-back dynamic headphones (30Hz-20kHz)	151.32
AT2050	. Cardioid, omni, figure-8, 20Hz-20kHz,	
	149dB max SPL (mic only)	229.00

#### **AUDIO-TECHNICA 40 SERIES CONDENSER**

MICS High quality studio condenser microphones with turned brass housings and black chrome plating. Very flat response from 20Hz-20kHz, maximum SPL of 145dB, 48V phantom power and low-cut switch. The AT4041/SP is a matched pair of AT4041 condensers packaged with 2 AT8410A shockmounts



in a wooden box. The AT4021 and AT4022 have 5dB better signal to noise ratios and AT4051b & AT4053b are modular and support interchangeable capsules.

ITEM	DESCRIPTION	PRICE
AT4041	. Cardioid microphone	. 299.00
AT4041/SP	Studio pack with 2x AT4041 mics in a wooden box	499.00
AT4021	. Cardioid mic with –10dB pad	. 349.00
AT4022	Omnidirectional mic with -10dB pad	. 349.00
AT4051B	Cardioid mic, supports optional hypercardioid capsule	. 599.00
AT4053B	. Hypercardioid microphone, supports optional cardioid capsule.	. 599.00
AT4051B-EL	. Cardioid capsule	. 249.00
AT4053B-EL	. Hypercardioid capsule	. 249.00
AT8114	. Windscreen for AT813, AT814	8.66
AT8407	Replacement stand adapter (clothes-pin universal style)	15.26
AT8415	Shockmount	62 64

#### AUDIO-TECHNICA AT4040 STUDIO MICROPHONE

This single-pattern large-diaphragm microphone has an extremely low noise transformerless design, wide dynamic range, high SPL capability, and smooth natural sonic characteristics. It features 20Hz-20kHz response, an 80Hz rolloff, 10dB pad, 100-ohm impedance, and 133dB dynamic range. Requires 48V phantom power and includes AT8449 spider-type shockmount.



ITEM	DESCRIPTION	PRICE
AT4040	Studio cardioid microphone	299.00
AT4040/SP	. Studio pack with AT4040 and AT4041	
	condenser mics in wooden box	549.00

#### **AUDIO-TECHNICA AT4050 3-PATTERN STUDIO MICROPHONE**

Large diaphragm studio microphones with low noise transformless electronics (17dB). 80Hz switched filter, smooth response to 20kHz, requires 48V phantom power and includes AT8449 spider type shockmount

let phantom power and includes the the sphaer type shocking and			
ITEM	DESCRIPTION	PRICE	
AT4050	Multi-pattern condenser	699.00	
	Stereo condenser, cardioid & figure-8		
AT8137	Windscreen	37.54	



AUDIX SCX25-A An elegant design with patented capsule suspension system in an intricate machined brass ring which minimizes acoustic reflections and diffractions, delivering a pure open-air sound unlike other mics. A smooth uniform response of 20Hz-20kHz, Cardioid pattern, low 14dBA noise, 48-52V phantom power, 138dB Maximum SPL. Good for vocal and instrumental recording.

ITEM	DESCRIPTION	PRICE
SCX25-A	Cardioid microphone	695.00
SCX25A-MATCHED-P	AIR . Matched pair of SCX25A	1489.00
SCX25A-PS	Piano system – includes (2) SCX25/	A, (2) D-flex mounts,
	(2) 20' mic cables, and an aluminu	m flight case . 1589.00



AUDIX MICROS SERIES The smallest, fully integrated condenser on the market today with an internal preamplifier, detachable cable, low noise & high sensitivity. Perfect for live, recording, and installation applications. Micro mics do not need an external power supply and are immune to RF interference. The M1255B offers higher sensitivity for distance miking. They are available in cardioid, hypercardioid, omni or supercardioid capsule

configurations, and feature a 25' mini-XLR to XLR cable, stand adapter, hanging clip windscreen, & pouch, M1250B and M1255B models are also available in white

willuscreen, & pour	cii. W11230D alia W11233D filoacis are also avallable ili wilite.	
ITEM	DESCRIPTION	PRICE
M1250B	. Cardioid micro, 50Hz-19kHz, 150ohms, max SPL 140dB,	
	requires 18-52V phantom power, 10mV sensitivity, black	
M1250B-HC	. M1250B w/ hypercardioid capsule	419.00
	. M1250B w/ omnidirectional capsule	
M1250B-S	. M1250B w/ supercardioid mini-shotgun capsule	429.00
M1255B	. Cardioid mini, 50Hz-19kHz, 150ohms, max SPL 130dB,	
	requires 18-52V phantom power, extra 12dB sensitivity,	
	32mV sensitivity, black	409.00
M1255B-HC	. M1255B w/ hypercardioid capsule	429.00
	. M1255B w/ omnidirectional capsule	
M1255B-S	. M1255B w/ supercardioid mini-shotgun capsule	449.00
	. Cardioid mini, 40Hz-20kHz, 150ohms, max SPL 150dB,	
	requires 18-52V phantom power	399.00
M1280-HC	. M1280 w/ hypercardioid capsule	419.00
M1280B-0	. M1280 w/ omnidirectional capsule	399.00
	. M1280 w/ supercardioid mini-shotgun capsule	
Micro Series Acce		
SMT-MICRO	. Shockmounted stand adapter	24.95
	. Mini gooseneck for rim mounting Micros	
	. Mini-gooseneck w/drum tension lug clamp	
DOLLIII IIIIONO	inini 600001100K ii/ draini tonolon lag olaliip	20.00

**AUDIX MICROBOOM** The MicroBoom is a 24", 50" or 84" carbon fiber boom arm that attaches to any microphone stand. It has a diameter of less than .3" and is only 2.5oz. The upper end features a mini-XLR connector that securely holds the mic in place and also allows for easy access when changing out mics. It can be used either in a horizontal or vertical position, and is designed for use with any of the microphones in the Micros series.

micros series.		
ITEM	DESCRIPTION	PRICE
MICROBOOM-24	.24" carbon fiber boom and clip only (no mic)	.145.00
MICROBOOM-50	.50" carbon fiber boom and clip only (no mic)	.229.00
MICROBOOM-84	.84" carbon fiber boom and clip only (no mic)	.329.00
MB5050	MICROBOOM-50 w/M1250B cardioid mic,	
	clutch assembly, cable, RFI immunity	.499.00
MB5050-HC	Same as MB5050 with hypercardioid capsule	.549.00
MB5055	Same as MB5050 with high-output cardioid capsule	.549.00
MB5055-HC	Same as MB5050 with high-output hypercardioid capsule	.569.00
MB8450	.MICROBOOM-84 w/M1250B cardioid mic,	
	clutch assmebly, cable, RFI immunity	.599.00
MB8450-HC	Same as MB8450 with hypercardioid capsule	.649.00
MB8455	Same as MB8450 with high-output cardioid capsule	.649.00
MB8455-HC	Same as MB8450 with high-output hypercardioid capsule	.669.00
STAND-MB	.Heavy-duty pedestal base mic stand (max height 21")	29.95
MC-BOOM	.Clutch assembly for MicroBoom	19.95



ITEM	DESCRIPTION				PRICE
electronics	and capsule. 3-year warr	anty.			
Features p	recision machined brass	s housings,	low noise	electronics,	replaceable
rour time u	naijuoto, room anaijoto o	Jitinaro prog	5. 4 0. 0.	on ambient i	00

Omni condenser, 20Hz-20kHz





299.00

This specialized condenser mic is designed for use with realbehringer time analyzers in providing an accurate acoustic picture of a

room. The ruler-flat frequency response from 15Hz-20kHz and omnidirectional polar pattern delivers a clear, accurate reading of any room's unique sound characteristics. Includes carrying case, mic clip and stand adapter. Requires phantom power.

ITEM	DESCRIPTION	PRICE
ECM8000	Measurement mic, omni condenser, 15Hz-20kHz	54.99








#### **BLUE SPARK SOLID STATE CONDENSER MICROPHONE**

A cardioid solid-state condenser mic designed for professional quality recording. Features a custom-designed condenser capsule with Class-A discrete electronics resulting BAING LATYIAN UNIVERSAL ELECTRONICS in detailed and uncolored output. Ideal for recording vocals,

drums, guitars, pianos, brass, woodwinds, etc. A unique focus control provides two different usage modes; Normal mode for increased low frequency sensitivity and Focus mode for greater clarity and detail. Ships with a custom-designed pop filter, shockmount and wood case. Frequency response is 20Hz-20kHz, sensitivity rating is 28 mV/Pa, output impedance of 50ohms, a max SPL of 128dB and a S/N Ratio of 84dB. Requires +48VDC phantom power.

ITEM	DESCRIPTION	PRICE
SPARK	. Cardioid condenser microphone	. 199.99





AVANTONE CONDENSER MICS Avantone's C series condenser microphones offer true professional performance and meet or surpass the performance and specs of higher priced mics. The CK-1 and CK-6 are ideal for recording instruments and percussion while the CK-7 can be used for instruments or vocals. The CV-12 is intended for use with vocals while the CV-28 is designed for acoustic instruments. All bodies and capsule assemblies are made from precision-machined brass.

ITEM	DESCRIPTION	PRICE
FET Microph	nones	
CK-1	Small diaphragm FET condenser, pad & HPF, includes interchangeable capsules (cardioid, hypercardioid & omni), 25Hz-20kHz,	40.00
CK-6	padded wooden box & shockmount	
CK-7	.Large diaphragm multi-pattern (cardioid/omni/figure-8) FET condenser, pad & HPF, 20Hz-20kHz, wooden box & shockmount, metal road case 2	
Tube Microp	nhones	
CV-12	Large diaphragm 9-pattern tube condenser, pad & HPF, 25Hz-20kHz, wooden box, shockmount, metal road case	199.00
CV-28	Small diaphragm tube condenser w/interchangeable capsules (cardioid, omni, hypercardioid), pad & HPF, shockmount, proprietary power supply w/cables, wood box, aluminum case	149.00

## beyerdynamic)))

**BEYERDYNAMIC** MC910/930/950 DIAPHRAGM CONDENSER MICS These true condenser mics provide enormous versatility due to their neutral sound and accurate design. All models include a switchable 15dB pad for excellent high SPL performance, and switchable bass roll-off with 6dB/octave at 250Hz to compensates for proximity effects.

ITEM	DESCRIPTION	PRICE
MC910	. Omni-directional, 30Hz-20kHz.	599.00
MC930	. Cardioid, 40Hz-20kHz	599.00
MC930-STEREO-SET.	. Matched stereo pair of MC930.	1149.00
MC950	. Supercardioid, 40Hz-20kHz	599.00



#### BEYERDYNAMIC OPUS 53 SMALL DIAPHRAGM CONDENSER MIC A lightweight vet rugged cardioid mic with carbon fiber strength-

ened plastic casing. Its small and short design allows flexible and unobtrusive positioning. The frequency response has been optimized for universal miking of instruments. Perfect for drums, brass and woodwind instruments as well as guitars and other string instruments. A 30Hz-20kHz frequency range mic with a max SPL of 136dB (at 48V phantom power) and a S/N ratio of 64dB. Requires phantom power and comes with mic mount.

ITEM	DESCRIPTION	PRICE
OPUS53	. Small diaphragm cardioid condenser mic	129.00





phantom power.

ITEM

REACTOR

BLUE BABY BOTTLE It is all discreet Class "A" solid-state circuitry, with a hand-selected gold sputtered diaphragm. It is perfect for vocal, percussion or acoustic recordings. It boasts 20Hz-20kHz response, cardioid pattern, 133dB SPL, and a 128dB dynamic

range with 12dB output. Includes shockmount and pop filter.

ITFM DESCRIPTION PRICE BABY-BOTTLE. Cardioid, FET.. 399.99

BLUE BLUEBIRD The Bluebird is a large diaphragm cardioid condenser with Class-A discrete circuitry for low distortion and extremely low noise (7.5dB). Bluebird has been engineered to be as versatile as possible, with applications ranging from vocals to electric and acoustic guitars, close-miking of drums, drum overheads, percussion, piano, horns, strings, and any other application where crystal-clear sound quality and detail are of the utmost concern. The Bluebird Accessory Pak includes Blue's high-definition 22-AWG Blueberry mic cable, a specially designed shockmount - the BirdCage, and a metal mesh pop filter - the BirdNest.

ITEM	DESCRIPTION	PRI
BLUEBIRD	.Cardioid, 20Hz-20kHz, 50ohms, 138dB SPL	299.
BLUEBIRD-ACCESS-KIT	Includes mic cable, shockmount and pop filter	80.

BLUE REACTOR LARGE-DIAPHRAGM CONDENSER MIC A largediaphragm condenser mic with class-A discrete components and multiple pickup patterns. It features a proprietary preamp for noiseless live switching between cardioid, omni or figure-8 patterns. To facilitate use in multiple mic setups (mid/side, X-Y), its capsule head rotates 90° for perfect positioning in tight spaces and easy pattern adjustability. Its pattern selection is both intuitive and stylish, featuring LED backlighting on the pattern indicators and a magnifying element that compliments its design. Frequency response is 20Hz-20kHz, a sensitivity rating of 19.0mW/Pa at 1kHz, max SPL of 135dB, dynamic range of 128dB, S/N ratio of 88dB-A and on output impedance rating of 50ohms. Requires +48VDC

Multi-pattern, large-diaphragm condenser mic... BLUE DRAGONFLY A transformerless cardioid large-diaphragm Class

DESCRIPTION

"A" design with integrated elastic shock-mount. The sonic character is neutral, the capsule pivots for versatile positioning. 48V phantom power is required.

ITEM DESCRIPTION PRICE Cardioid...



PRICE

499.99











































electro-harmonix

VISIT FULLCOMPASS.COM OR CALL 800-356-5844 FOR MORE INFO



























































1200BP

2200BP

CAD GXL BLACK PEARL CONDENSER MICROPHONES These versatile condenser mics feature a lustrous black pearl chrome finish along with exceptional performance specs. All GXLBP mics include a shock mount or clip, vinyl pouch and polishing cloth.

ITEM	DESCRIPTION	PRICE
GXL1200BP	. Small diaphragm, cardioid, 30Hz-20kHz	79.99
GXL2200BP	. Large diaphragm, cardioid, 30Hz-20kHz	79.65
GXL3000BP	. Large diaphragm, cardioid/figure-8/omnidirectional,	
	35Hz-20kHz, high-pass filter & -10dB pad	139.99
GXL2200BPSP	. Studio pack w/ GXL2200BP, GXL1200BP,	
	MH110 studio headphones, EPF15A pop filter	199.99
GXL3000BPSP	. Studio pack w/ GXL3000BP, GXL1200BP,	
	MH110 studio headphones, EPF15A pop filter	249.99

CAD E70 MODULAR DUAL-CAPSULE CONDENSER MIC Includes 2 capsules: Omnidirectional for flat near field and ambience; and Cardioid for proximity boost and off-axis rejection. Features field-effect detection, transformerless drive, dual-frequency hi-pass filter, two-position pad, a max SPL of 145dB, and a sensitivity of -39dBV. Elastic shockmount, stand clamp and windscreen are included. 48V phantom power required.

ITEM	DESCRIPTION	PRICE
E70	Condenser mic, omni & cardioid capsules, 20Hz-20kHz	99.00

CAD E100S SUPERCARDIOID LARGE DIAPHRAGM CONDENSER MICROPHONE Now engineered and built in the USA, this mic has the lowest noise floor in its class (3.7 dBA). The bootstrapped, full differential Quadra-FET front end delivers high sensitivity and low distortion, and CAD's proprietary circuitry ensures the highest performance. The nickel-plated 1" capsule delivers accurate phasing on instruments, and a full rich vocal tone, accentuated by the extended low frequency response. Features include an

80Hz hi-	pass filter and a 10dB pad. 48V phantom power is required.	_
ITEM	DESCRIPTION	PRICE
E100S	Large diaphragm mic, 40Hz-18kHz, w/ woodgrain cherry case & shockmon	unt 599.00

# Earthworks

EARTHWORKS M30 MEASUREMENT MIC A cost-effective omni reference mic for acoustical measurements including speaker design, quality control, sound system setup/troubleshooting, room acoustics. It has a flat frequency response of 5Hz-30kHz, fast impulse response, exceptional polar characteristics, and a max of 142dB SPL. It meets or exceeds ANSI Type 1 and applicable IEC 61094 requirements. Requires 48V phantom power. Mic clip & wood case included.

ITEM	DESCRIPTION	PRICE
M30	Omni measurement mic, 5Hz-30kHz	649.00
M30-MATCHED-PAIR	Matched pair of M30s in wood box	
	(mic clips included)	1399.00

EARTHWORKS SR SERIES DIRECTIONAL MICS These microphones sound natural and have the ability to handle very high SPL transients with astounding detail. They are flat in frequency response and have only a mild bass proximity effect. They maintain a uniform frequency response as you approach the limits of a cardioid or hypercardioid pick up pattern, offering greater gain before feedback. The SR20 comes with screw-on windscreen. The SR25, SR30 and SR40 models are considered "High Definition" microphones due to frequency response extending beyond 25kHz.

ITEM	DESCRIPTION	PRICE
SR40	Cardioid mic, 30Hz-40kHz	999.00
SR40-MP	Matched pair of SR40	2099.00
SR30	Cardioid mic, 30Hz-30kHz	849.00
SR30-MP	Matched pair of SR30	1799.00
SR30/HC	Hypercardioid mic, 30Hz-30kHz	849.00
SR30/HC-MATCHED-PAIR	Matched pair of SR30/HC	1799.00
SR25	Cardioid mic, 50Hz-25kHz	599.00
SR25-MP	Matched pair of SR25	1299.00
	Cardinid vocal/instr_convertible mic	

#### **LOOKING FOR THESE BRANDS?**







3000BP

VISIT FULLCOMPASS.COM OR CALL 800-356-5844 FOR MORE INFO

# Earthworks

#### EARTHWORKS TIME COHERENT OMNI MICS

Time Coherent Response means these models are optimized to deliver time accurate performance across the spectrum of frequency response. They don't smear the



time domain as most microphones do. Impulse settling time is faster than any other microphone available which yields remarkable high frequency detail definition. They handle huge sound pressure levels and have no proximity effect or handling noise. The TC25, TC30, and QTC models are considered "High Definition" microphones due to frequency response extending beyond 25kHz.

ITEM		PRICE
QTC50	Omni with 3Hz-50kHz response	1399.00
QTC40	40kHz flat response, ideal for acoustic instrument recording.	999.00
QTC40MP	Matched pair of QTC40, cherry box	2199.00
QTC30	30kHz response for less critical apps	799.00
TC25	Omni for loud sources, 9Hz-25kHz	549.00
TC30	30kHz general purpose omni	769.00
TC20	20kHz, shorter version of TC30	479.00

LEWITT SMALL DIAPHRAGM CONDENSER MICROPHONES The LCT140 is a versatile, easy-to-use, compact 2/3" condenser mic with a pressure gradient transducer. Its lower-mass diaphragm delivers clear and natural sound, good for a wide

range of applications and features a 10dB/20db switchable preattenuation pads with 160dB max SPL and a bass cut filter slope. The LCT340 is a 1/2" externally polarized condenser mic designed for acoustic, percussion, and vocals with and interchangeable capsules for cardioid and omni-directional patterns. It has a 6/12/18db switchable preattenuation pads with an SPL of 155dB and a bass cut filter slope. Both models have LED displays, 124dB dynamic range, gold plated 3-pin XLR output connector, and include shockmount, windshield and leather bag.

ITEM	DESCRIPTION	PRICE
LCT140	. Electret condenser mic, cardioid, 30Hz-20kHz, black	. 229.00
LCT340	. Condenser mic, cardioid or omni-directional, 20Hz-20kHz	. 469.00

LEWITT RECORDING MICROPHONES The LCT 240 is a condenser mic with a cardioid pattern for effective sound source isolation and a 2/3" capsule. Great for live and studio apps. The LCT 540 has a 1" cardioid capsule suitable for lead vocals, instruments and more. Both mics feature 10dB/20dB switchable preattenuation pads, 160dB max SPL (163dB max SPL for the LCT540) and a bass cut filter slope. The LCT 640 features a 1" dual system capsule with cardioid, omni-directional, figure-8, broad-cardioid, super-cardioid options, 163dB max SPL, 1/12/18dB switchable preattenuation and bass cut filter slope. All models are immune to electromagnetic interference

with transformerless output stage and have key-lock, clipping history and automatic attenuation. Also feature noiseless push buttons for attenuation and HPF selection and have a frequency response of 20Hz-20kHz.

ITEM	DESCRIPTION	PRICE
LCT240	Condenser mic, cardioid	249.00
LCT540	Condenser mic, cardioid	599.00
LCT640	Condenser mic, multipattern	799.00





Follow us!



LCT640

# **GXL Black Pearl**



CAD Audio introduces a 10th anniversary tribute to the industry leading GXL line of Studio Mics. Engineered to the highest standards, the GXLBP studio microphone series feature a lustrous Black Pearl, Chrome finish.

Add distinctive style to your session and the warmth, edge and attitude your music deserves. GXL Black Pearl mics are available individually or as studio packs with included headphone and pop filter.

CAD Audio "Sound Your Best"

























































MIC-W MICROPHONES High-precision instruments for professional recording, broadcast and live music applications. A variety of omni or cardioid models offer a choice of flat ultra-definition extended frequency response or a tailored response with presence boost for vocal enhancement. Each microphone ships in a padded case, with individual frequency response plot, mounting clip and windscreen.

DESCRIPTION

	DESCRIPTION	INIOL
N SERIES		
N101	Large diaphragm omni-directional	l.
	Stainless steel housing and a	
	2.5-micron thick nickel diaphragm	1.
	10Hz-20kHz with 4-6dB soft boost	
	around 8kHz. 12dBA noise floor ar	
	140dB SPL peak	
N101 DAID	A matched pair of N101's	2220 00
N101	Large diaphragm cardioid pattern	
	with a pressure gradient capsule.	
	diaphragm and stainless steel ho	
	Great for spot miking live music a	nd in
	the studio. 6Hz-20kHz, soft boost	
	around 8kHz. Approx 130dB SPL	
	peak and 16dBA noise floor	1165.00
N151-PAIR	A matched pair of N151's	2435.00
N201	Omni-directional mic with 1/2" dia	. cap-
	sule. Suitable for most critical reco	
	apps. 20Hz-20kHz. Approx 135dB S	PL O
	peak and 20dBA noise floor	
N201-PAIR	A matched pair of N201's	
	Omni-directional reference mic wit	
	1/3" all-metal capsule. Linear freq	
	response of 20H-40kHz. Up to 160c	
	SPL peak and 20dB noise floor. God	
	drums, percussion and brass	Ju IUI
		000
11404	for accurate and clean sound	.855.00
N401		105 10
	frequency response of 10Hz-70kHz.	
	SPL peak. Great for ensembles, pian	
	drums or background vocals	
N401-PAIR	A matched pair of N401's	1940.00

NTU 1-1 AIN	A materieu pair of N401 31340.	UU
E SERIES		
E120	Cardioid mic with 24 Karat gold	
	diaphragm. 20Hz-20kHz with 4-6dB soft	
	rise around 8-10kHz. Great for precise	
	studio instrument recording270.	00
E216	Omni-directional mic with 1/2" polymer	
	diaphragm covered by a thin layer of gold	
	20Hz-20kHz with 20dBA noise floor and	
	approx. 135dB SPL195.	00
E418	Omni-directional mic with 1/4" E Series	;
	capsule, 20Hz-20kHz with 4-6dB	
	soft rise around 8-10kHz. Short impulse	•
	response and settling time for clear, ric	h
	sounds. Approx. 135dB SPL and	
	26dBA noise floor195.	00

Omni-directional mic with 26mm goldplated polymer diaphragm. 10Hz-20kHz with4-6dB soft boost around 8kHz. 140dB SPL peak and 12dBA noise floor . 1055.00 <u>Milab</u>

MILAB LARGE DIAPHRAGM CONDENSER MICS All models feature rectangular, large membrane, shock absorbing rubber-fitted capsules and gold-plated XLR connectors. The DC-96B cardioid provides a full-bodied and exceptionally clean sound with natural brightness. The DC-196 is a variable pattern condenser (cardioid, omni, figure-8) that features built-in pop protection, -12dB pre-attenuation and is transformerless. The VIP-50 is also transformerless and shares the same polar patterns as the DC-196 plus wide-cardioid and hypercardioid patterns. It also features 200/500Hz hi-pass filters and -10/-20dB pre-attenuation.

torno. It also reatares 200,000 mero and 10, 2005 pre attendation.		
ITEM	DESCRIPTION	PRICE
DC-96B	Cardioid pattern, 20Hz-20kHz	CALL
DC-196	Variable pattern (cardioid, omni, figure-8), 20Hz-20kHz	CALL
VIP50	Variable pattern (cardioid, omni, figure-8,	
	wide-cardioid, hypercardioid) 20Hz-20kHz	CALL



#### MILAB BDM-01 TRANSFORMERLESS CARDIOID CONDENSER MICROPHONE FOR BASS

**DRUMS** Built around a high-class VM-44 capsule and capable of handling 155dB without audible distortion, the BDM-01 has been designed for bass drums and other powerful sound sources. The high-end rubber-fitted condenser capsule provides superior attack and HF response, and the frequency curve has been tailored for a presence peak around 5KHz. The dynamic range, sensitivity and pop filters have also been optimized for the bass drum. Also features a 48V phantom power supply.

ITEM	DESCRIPTION	PRICE
BDM-01	Bass drum cardioid condenser mic, 20Hz-20kHz, 155dB SPL	CALL



MXL LARGE DIAPHRAGM CONDENSER STUDIO MICS Studio condenser microphones with both FET and tube circuitry available. FET models require 48V phantom power, while tube models include power supply.

circuitry availab	ile. FET inodels require 46v phantom power, while tube models include power supply.	
ITEM	DESCRIPTION	PRICE
MXL-770	Cardioid, 6-micron 20mm gold-sputtered diaphragm FET w/shockmount and case,	
	30Hz-20kHz, -10dB pad and bass roll off	99.95
MXI -2003	Cardioid transformerless condenser w/bass cut and -10dB pad switches. 20Hz-20kHz	
	MXL2003 & MXL603S (transformerless cardioid instrument mic),	. 170.00
	w/shockmounts, cables, windscreens in padded case	299 95
MXI -2006	Cardioid, true Class 'A' FET preamp w/balanced transformerless	. 200.00
MAC 2000	output, high-isolation shockmount and case, 30Hz-20kHz	109 95
MXI -2010	3-pattern (cardioid/Figure-8/omni) capsule, FET preamp w/bass	. 100.00
MAC 2010	roll-off switch, shockmount & windscreen, 30Hz-20kHz	179 95
MXI_CURE	Drum condenser cardioid mic. FET balanced output w/mic clip. 20Hz-20khz	
	Gold-plated cardioid condenser w/shockmount, leather case, windscreen, 20Hz-20kHz	
	Cardioid condenser, transformer balanced output, FET preamp, 20Hz-23kHz	
	Classic body Figure-8-patterned ribbon condenser w/wood case,	. 243.00
MAL N77	desktop stand, & 25ft XLR cable, 20Hz-18kHz	399 99
MXI -R77-I	Same as above, but w/custom Swedish Lundahl transformer	
	Figure-8 patterned ribbon condenser, purple & chrome finish	. 545.55
	w/shockmount, case, cleaning cloth, 20Hz-17kHz	99 99
MXI -TROPHY	Cardioid condenser w/side-tapped capsule & removable nameplate. 20Hz-20kHz	
	Cardioid mic w/balanced FET output stage, case, & clip, 20Hz-20kHz	
	Transformer-balanced cardioid mic w/solid-state preamp & gold grill, 30Hz-20kHz	
	Same as above but w/2 selectable 1" cardioid capsules (one bright, one warm) & -10dB pad switch.	
	X/Y stereo pattern condenser mic, w/gold-plated grill, 2 externally biased 22mm pressure	. 100.00
	gradient capsules, 10ft custom XLR cable, 20Hz-20kHz	219 95
MXL-V69-MOGAN		. 210.00
mixt 100 mount	Transformerless tube cardioid condenser w/shockmount, power supply, 15ft 7-pin cable.	
	15ft XLR cable, cleaning cloth, & case, 20Hz-18kHz	299 95
MXI -V69XM	Same as above, but w/transformer balanced output, 20Hz-18kHz	
	Low-noise transformer-balanced cardioid condenser with	. 000.00
MAC 101	FET preamp, w/pop filter & shockmount, 20Hz-20kHz	299 95
MXI -V88	Low-noise cardioid condenser w/balanced transformerless output, FET preamp,	. 200.00
	high-isolation shockmount & flight case, 20Hz-20kHz	152 60
MXI -V177	Low noise classic body cardioid condenser w/6-micron thick gold-sputtered diaphragm, 20Hz-20kHz	299 95
	Variable pattern tube condenser mic w/EF86 pentode tube	
	Tube condenser cardioid mic w/-10 dB pad, dedicated power supply	
GENEUIU	rabe condenses caratora fine m. to ab pau, acaicated poner suppry	. 555.00

G SERIES G106 ......



MXL SMALL DIAPHRAGM CONDENSER MICS These small diaphragm condenser mics are quiet, sensitive, rugged enough for the road and inexpensive. They are an excellent choice for drum overheads and for close recording of acoustic instruments. 48V phantom power required.

	2200	PRICE
	Stereo pair of transformerless cardioid instrument mics, 30Hz-20kHz, w/ MXL-41-603 shockmounts & case	165.20
	.Small diaphragm cardioid condenser, 30Hz-20kHz, w/ wooden case,	100.20
	mounting clip and omnidirectional capsule	
	.Small diaphragm instrument condenser, omni/cardioid capsules, 20Hz-20kHz	
MXL-41-603	.Replacement shockmount for MXL-603PAIR	38.95





#### **NEUMANN U87AI 3-PATTERN** MIC A legendary FET large diaphragm transformer coupled studio mic with

omni, cardioid and figure-8 patterns, 10dB pad and low cut filter.

ITEM	DESCRIPTION	PRICE
U87AI	Multi-pattern microphone,	
	no mount or case	.3199.95
U87AI/SET-Z	Microphone with shockmount,	
	cable and windscreen	.3399.95
EA87	Elastic suspension (with SET-Z)	355.45
WS87	Windscreen	48.02

NEUMANN TLM102 CARDIOID **CONDENSER MICROPHONE** This mic features a large-diaphragm cardioid capsule that handles a maximum sound pressure level of 144dB, which is good for recording amps, drums, and other loud instruments. Acoustic instruments will benefit from the TLM102's fast transient

response. The TLM102 also features a slight boost above 6kHz, making it ideal for voice/speech applications. Below 6kHz, the frequency response is linear, providing clear bass and little coloration. Features an elastic suspension in the capsule and an integrated pop screen. Ideal for a wide range of applications including home recording and broadcasting.

ITEM	DESCRIPTION	PRICE
TLM102	.Large diaphragm cardioid	
	condenser mic, black	699.95
TLM102-NICKEL	.As TLM102, nickel finish	699.95

#### **NEUMANN** TLM103/TLM103D LARGE DIAPHRAGM MICS These are large diaphragm cardioid mics with a transformerless output stage. Designed primarily for vocals, the TLM03 also excels on piano, percussion, and stringed instruments. The TLM103D is a digital version of the mic, designed for home recording and project studios. Its A/D converter receives the output signal directly from the capsule, ensuring that the signal has no coloration and superb transparency. Both mics require 48V phantom power and come with

an SG-1 swivel mount and wooden box.

ITEM	DESCRIPTION	PRICE
TLM103-BLACK.	.Cardioid mic, 20Hz-20kHz,	
	Max SPL for THD 0.5% -138dB,	
	w/swivel mount & case, black	1099.95
TLM103-NICKEL	.As above, but with nickel finish	1099.95
TLM103-D	.Digital version of TLM103, availa	able
	in black or nickel finish	1599.95
EA1-BLACK	.Elastic suspension mount, black	253.53
EA1-NICKEL	.Elastic suspension mount, nicke	1253.53
WS87	Windscreen	48.02



#### **NEUMANN KM180 SERIES** The KM180

series condensers offer the same transformerless circuitry

as the KM100s without the 10dB pad. Frequency response is 20Hz-20kHz. The KM183, KM184 and KM185 have SPL handling of 140dB, 138dB and 142dB respectively. 48V phantom power is required.

ITEM	DESCRIPTION	PRICE
KM183	Omni condenser mic	899.95
KM184	Cardioid condenser mic	849.95
KM185-SILVER.	Hypercardioid condenser mic	899.95
EA2124A	Optional suspension mount	279.01
WNS100	Replacement windscreen	26.07
WS100	Optional 90mm windscreen	28.03
SKM183-MT	Stereo mic pair-omni,	
	w/case, black	1699.95
SKM183-SILVER	.Stereo mic pair-omni, w/case.	1699.95
SKM184-MT	Stereo mic pair-cardioid,	
	w/case, black	1599.95
SKM184-NI	Stereo mic pair-cardioid,	
	w/case_nickel	1599 95



RØDE NT1-A CARDIOID MIC World's quietest microphone with an incredible 5dBA self noise figure. 48V phantom power, transformerless output,

137dB max. SPL, fixed cardioid pattern.

ITEM	DESCRIPTION	PRICE
NT1-A-COMPLETE	Anniversary edition, include:	S:
	shockmount, pop shield, 20	cable,
	dust cover, and DVD	229.00

# CONDENSER MICS The RØDE NT5 is

a true condenser microphone specifically designed for instrument recording. Its discrete size and design allows for effective and subtle positioning, which is crucial when close miking. NT5's are supplied as closely matched pairs in a custom carry case with two stand mounts and two windscreens. Requires 48V phantom power. Frequency response is 20Hz-20kHz, max SPL of 143dB,


dynamic range >128dB. Available in pairs, or as single mics. The new NT55 model is essentially the NT5 with a two stage hp (75Hz or 150Hz) filter and a two stage (-10dB/-20dB) pad, and includes a NT45-O omni capsule so that you have the option to operate cardioid or omni by swapping capsules.

ITEM	DESCRIPTION	PRICE
NT5	Studio condenser mic, pair	429.00
NT5-S	Single NT5 condenser mic	219.00
NT55	Mic w/ two stage hp filter, 2 sta	ige pad,
	and cardioid & omni capsules	369.00
WS5	Replacement windscreen for NT	519.99



#### **RØDE NT2A MULTI-PATTERN LARGE** DIAPHRAGM CONDENSER MIC The

successor to the very popular NT-2 studio condenser mic, the NT2A now has the internally shock mounted HF1 dual 1" capsule, the same as is used in the K2 microphone, and new electronics with extremely low 7dBA self-noise. It has a



ITEM	DESCRIPTION	PRICE
NT2A	Multi-pattern condenser .	399.00



SETS Microphones consist of a mic capsule and amplifier. The CMC 6 microphone

amplifier converts extremely high-imped-

ance signals from the attached capsule to

a very low-impedance signal suitable for

transmission via mic cable. It also features

SG20 stand clamps and B5 popscreens.

DESCRIPTION

CMC622G-SET....Includes CMC 6 amplifier, &

CMC621G-SET....Includes CMC 6 amplifier & MK21

cardioid capsule. CMC641G-SET....Includes CMC 6 amplifier &

ITEM

CMC64G-SET..

CMC65G-SET..

CMC68G-SET.

NEAR-FIELD-OMNI-ST

UNIVERSAL-OMNI-H-ST

UNIVERSAL-OMNI-S-ST

WIDE-CARDIOID-ST

OPEN-CARDIOID-ST

SUPERCARDIOID-ST

SWITCHABLE-PATTRN-ST

CARDIOID-ST..

a symmetrical Class "A" output stage, free of coupling

condensers or an output transformer. They are light-

weight, have extremely low distortion, and their very

low output impedance helps make them insensitive

to electrical interference. The CMC 6 works with both

12V and 48V phantom powering. Matte gray options

listed below but also available in nickel. All sets include

wide cardioid capsule...

MK22 open cardioid capsule

MK41 supercardioid capsule. CMC641CG-SET...Includes CMC 6 amplifier & MK41 supercardioid capsule, CUT 1 filter ..

.Includes CMC 6 amplifier &

MK5 omni/cardioid capsule.

.Includes CMC 6 amplifier &

Includes 2 CMC 6s, matched pair

Includes 2 CMC 6s, matched pair of MK22 open cardioids ...

.Includes 2 CMC 6s, matched pair

Includes 2 CMC 6s, matched pair of MK41 supercardioids .......

Includes 2 CMC 6s, matched pair of MK5 omni/cardioids......

of MK2 S omnis.....

of MK21 wide cardioids...

of MK4 cardioids......

of MK2 H omnis.....

MK8 figure-8 capsule..

of MK2 omnis...

..Includes CMC 6 amplifier & MK4





1796.00

1796.00

1698.00

.1918.00

..2552.00

2265.00

.2132.00

3465 00

.3465.00

MK41



MK8































ITEM	DESCRIPTION	PRICE
NT5	Studio condenser mic, pair	429.00
NT5-S	Single NT5 condenser mic	219.00
NT55	Mic w/ two stage hp filter, 2 stage	ge pad,
	and cardioid & omni capsules	369.00
WS5	Replacement windscreen for NT5	19.99

**FULLCOMPASS.COM** 

















































### SENNHEISER



SENNHEISER E614 DRUM OVERHEAD CONDENSER The e614 has a supercardioid pattern, with a neutral response and moderate sensitivity, which insures optimum isolation from other instruments on stage. Unobtrusive for precise placement and powered by external phantom power (P48), the e614 tolerates extremely high SPLs, precisely capturing cymbals and hi-hats better than other mics in its price range. 10-year warranty. Frequency response is 40Hz-20KHz.

ITEM	DESCRIPTION	PRICE
E614	. Supercardioid condenser	219.95

#### **SENNHEISER K6 MODULAR ELECTRET MIC SYSTEM This**

rugged system has separate capsules and powering modules that can be combined to produce a wide variety of microphones. A single module and a few capsules can provide the user with flexibility that would otherwise require investing in a number of individual microphones. It converts quickly from one type of microphone to another by simply threading together various system components. All capsules use back-electret technology for uncompromised quality. Output of all powering modules is balanced, low impedance (200ohms) and terminates in a standard 3-pin XLR connector.

K6 Powering Module "Universal" powering module for the system. Powered by a single 1.5V "AA" battery with a life of 150 hours, or phantom power (12-48V). On/off switch with LED indicator, bass rolloff switch (flat, -11dB).

ITEM	DESCRIPTION	PRICE
K6	. Powering module battery/phantom	249.95
	. Powering module phantom only	
Capsules for K6		
ME62	. Omni capsule	159.95
ME64	. Cardioid capsule	169.95
ME65	. Handheld capsule	229.95
	. 8.75" shotgun capsule	
ME66/K6-COMBO	. Short electret shotgun system	499.95
ME67	. 12.5" shotgun capsule	299.95
MKE2-60-GOLD	. Lapel capsule	329.95
MZSK6	. Camera adapter and shockmount	49.99
MZW66	. Foam windscreen for ME66	41.83

#### SENNHEISER MK4 LARGE DIAPHRAGM SIDE ADDRESS

MICROPHONE A large diaphragm side-address microphone with a cardioid pickup pattern and a nickel colored finish. It has a large 1" diaphragm precisely sputtered with 24-carat gold. It has a sturdy metal housing and the elastically mounted capsule suppresses handling noise. It has a max SPL level of 140dB and a low self-noise level of 10dB(A). It has a frequency response of 20Hz-20kHz, a sensitivity rating of 25mV/Pa and a dynamic range of 130dB. It requires +48V of phantom power.

ITEM	DESCRIPTION	PRICE
MK4	Large diaphragm side-address microphone.	299.95
MKW4	Windscreen for MK4	24.95
MXP40	Popscreen for MK4	COMING SOON!
MKS4	Shockmount for MK4	99 95

SENNHEISER MKH-SERIES RF-CONDENSER RF condenser microphones constitute a unique, sophisticated class of condenser microphones. They fulfill the very highest demands made on sound quality and versatility, and are renowned for their high quality, highly accurate sound reproduction, ruggedness, all-weather operation, wide frequency response and extremely low inherent self-noise. RF condenser microphones use a comparatively low RF voltage, modulated by the capacitance changes produced by the capsule diaphragm. Excellent low frequency response can be achieved even with small capsules. RF condenser microphones possess a genuine fully floating, balanced output without having to use an audio frequency transformer. 48V phantom power is required.

ITEM	DESCRIPTION	PRICE
MKH20-P48	Omni-directional	1199.95
MKH30-P48	Figure-8	1249.95
MKH40-P48	Cardioid	1199.95
MKH50-P48	Supercardioid	1199.95
MKH60-P48	Short shotgun, supercardioid	1499.95
MKH70-P48	Long shotgun, lobar	1749.95
MKH800-P48	Multi-pattern side address, 50kHz response	2999.95
MKH416P48U3	Short shotgun, hypercardioid	999.95
MKH418S	Stereo shotgun, M: supercardioid: S: figure-8	1649.95

## SHUR

SHURE KSM32 EMBOSSED SINGLE-DIAPHRAGM CONDENSER MICROPHONE For studio recording and live sound production. The KSM32 offers an extended frequency response of 20Hz-20kHz for an open, natural sound. The Class "A" transformerless preamp circuitry eliminates cross-over distortion for improved linearity across the full frequency range. An embossed, high-compliance, ultra-thin, gold-layered, low-



mass diaphragm provides extended low frequency response and excellent transient response. Other features include a 15dB pad switch, switchable low-frequency filter, integrated 3-stage pop protection, swivel mount and an internal shock mount for reduced handling noise

Toddeod Manania Moloci		
ITEM		PRICE
KSM32/UG	Studio condenser mic, charcoal finish, carrying case	499.00
KSM32/SL	Studio condenser mic, silver finish, shockmount,	
	aluminum case	549.00
A32SM	Elastic-suspension shockmount for the KSM32	136.28
A32SC	Locking aluminum carry case for the KSM32	107.59
A32WS	Windscreen for KSM series, black	11.40

#### SHURE KSM42 & KSM44A LARGE **CONDENSER MICROPHONES** Premium side-address mics offering a dual-diaphragm design with an active front, ultra thin (2.5 micron) 24-karat gold, low mass, 1" Mylar® diaphragm. The KSM42 is ideal for vocal applications with a tailored frequency response and extensive internal and exter-



nal pop filtering. The single-pattern design exhibits smooth proximity control & ultra-wide dynamic range. An internal shock mount reduces unwanted handling & stand noise. Prethos<sup>TM</sup> Advanced Preamplifier Technology exhibits extremely low self-noise with superior dynamic range, transient response & ultra-low distortion for transparent recording. The KSM42 includes ShureLock® shock mount, Popper Stopper™ magnetic pop filter, aluminum carrying case, & velveteen pouch. The KSM44A adds multiple polar pattern options (cardioid, omnidirectional, bidirectional) and a switchable 15dB pad. A 3-position switchable low-frequency filter helps reduce unwanted handling & stand noise. The KSM44A includes ShureLock® suspension shock mount, ShureLock® stand mount, carrying case, & velveteen pouch.

ITEM	DESCRIPTION	PRICE
KSM42/SG	Large dual-diaphragm side-address condenser vocal mic, cardioid	799.00
KSM44A/SL	Multi-pattern large dual-diaphragm side-address	999 00

SHURE KSM PROBE SERIES INSTRUMENT MICS These condenser microphones feature 20Hz-20kHz frequency response, a 3-position pad switch, a 3-position LF filter, and include a windscreen and carrying case. The KSM137 is a single pattern cardioid mic, while the KSM141 is a dual

pattern mic (omni and cardioid). Both mics require 48V phantom power.		
ITEM	DESCRIPTION	PRICE
KSM137/SL	. Cardioid condenser, windscreen, case,	
	champagne finish	299.00
KSM137/SL-STEREO	. Stereo matched pair, 2 foam windscreens,	
	A27M stereo mic adapter, case	665.00
KSM141/SL	. Dual-pattern condenser, windscreen, case,	
	champagne finish	399.00
KSM141/SL-STEREO.	. Stereo matched pair, 2 foam windscreens,	
	A27M stereo mic adapter, case	870.00



SHURE SM81 One of the world's great studio or live mics. Ruler-flat response 20Hz-20kHz ultra low self-noise. The ultimate in precise, detailed sound reproduction. Excellent for use with acoustic instruments, choirs, overhead cymbal applications. Build in 10dB attenuator and bass cut switch. Phantom power only.

ITEM	DESCRIPTION	PRICE
SM81LC	Condenser cardioid	349.00
A81WS	Optional multilayer windscreen	31.92
A53M	"Shock Stopper" isolation mount	33.25





### SHURE<sup>®</sup>

SHURE PG27LC & PG42LC SIDE ADDRESS CONDENSER MICROPHONES These mics feature a cardioid pickup pattern, large diaphragm capsules with switchable attenuators. The PG27LC is designed for use with instruments. It has a flat, neutral frequency response of 20Hz-20kHz as well as a high SPL rating of 124dB with pad off and 144dB with pad engaged. It ships with a stand adapter and zippered pouch. The PG42LC is designed for vocals and



PG42LC

PG27LC

features a voice-tailored frequency response of 20Hz-20kHz as well as an SPL rating of 130dB with pad off and 145dB with pad engaged. It also includes a switchable highpass filter and ships with a shockmount and carrying case. Both models have 3-pin XLR connectors.

ITEM	DESCRIPTION	PRICE
PG27LC	Side-address cardioid condenser instrument microphone,	
	20Hz-20kHz	149.00
PG42LC	Side-address cardioid condenser vocal microphone,	
	20Hz-20kHz	. 199.00

SHURE PG81 This condenser instrument microphone is the perfect choice for instrument recording in the home studio environment. Its condenser element provides high sensitivity and low self-noise, while its extended flat frequency response keeps instruments and samples sounding accurate. The PG81 operates on an internal AA battery or phantom power. Includes padded vinyl carrying case, swivel adapter and AA battery.

ITEM	DESCRIPTION	PRICE
PG81-XLR	. Cardioid microphone	129.00
A53M	. Shock stopper isolation mount	33.25

#### SHURE SM137 SMALL DIAPHRAGM CARDIOID CONDENSER

**MICROPHONE** A versatile, flat-response mic for both acoustic and high-volume performance applications. Useful for acoustic guitar, acoustic bass, strings, piano, woodwinds, and orchestral applications. Steel and brass construction with dark gray matte finish and stainless steel mesh grille. Frequency response 40Hz-16kHz.

ITEM	DESCRIPTION	PRICE
SM137LC	Cardioid condenser microphone	179.00

#### SHURE BETA 181 SIDE-ADDRESS INSTRUMENT MICROPHONES

This ultra-compact, small-diaphragm side-address condenser microphone is designed for discrete placement and gives great control in live and studio environments. Features interchangeable capsules for superior versatility. The small diaphragm design provides superior audio with consistent, textbook polar responses and is small enough to use in the tightest conditions. The compact side-address design features an innovative locking ring to provide secure connection between capsule and preamplifier. The 20Hz-20kHz frequency response is tailored for wide dynamic range applications for use in high SPL environments. Ships with stand adapter, windscreen and carrying case which securely protects up to 4 capsules.

	, ,	
ITEM	DESCRIPTION	PRICE
BETA181/C	Cardioid side-address microphone	499.00
BETA181/S	Supercardioid side-address microphone	499.00
BETA181/BI	Bi-directional side-address microphone	499.00
BETA181/0	Omnidirectional side-address microphone	499.00
RPM181/PRE	Preamp for Beta181 microphones	249.00
RPM181/C	Cardioid capsule only	249.00
RPM181/S	Supercardioid capsule only	249.00
RPM181/BI	Bidirectional capsule only	249.00
	Omidirectional capsule only	

SHURE SM94LC INSTRUMENT MICROPHONE A unidirectional electret condenser microphone tailored to the needs of professional musicians and sound engineers in both live performance and sound recording. It is equally at home in sound reinforcement systems or in sound studios and motion picture/ TV scoring stages. When used with the optional windscreen, the SM94 can be used by vocalists and speechmakers who desire a wide, flat response with minimum coloration. It runs on either an AA battery or phantom power. Other features include an internal shockmount, wide dynamic range of 119dB, a flat frequency response of 40Hz-16kHz and a uniform cardioid polar pattern.

ITEM	DESCRIPTION	PRICE
SM94LC	. Cardioid condenser microphone	. 162.92
	. Windscreen	

## **LOOKING FOR THESE BRANDS?**







SAMSON'

SONY



VISIT FULLCOMPASS.COM OR CALL 800-356-5844 FOR MORE INFO



SONTRONICS STUDIO MICS Capsules are handcrafted, using gold-sputtered Mylar film, and artificially aged to ensure stability and to give special characteristics. All models have low cut filter and —10dB pad. The HELIOS & OMEGA tube mics use dual-triode 12AX7/ECC83 tubes in their preamp. The SATURN offers omni, subcardioid, cardioid, hypercardioid, & figure-8 patterns, and hi-pass filter (75Hz/125Hz). The STC-1 features a 3-stage filter, and STC-2X has a 75Hz/150Hz filter switch. The SATURN, STC-1, & STC2X mics offer —10/—20dB pad switches. The ORPHEUS & STC-1 come in velvet-lined wooden case while the SATURN, STC-2, & STC-2X include an aluminum flightcase. The HELIOS & OMEGA come in a wooden box inside an aluminum flightcase.

arammam mgm	drammam manecase.			
ITEM	DESCRIPTION	PRICE		
HELIOS	Tube, 1.07" capsule, variable pattern from omni to figure-8,			
	power supply, cables	899.00		
OMEGA	Tube, 1.07" cardioid, shockmount, power supply, cables	789.00		
ORPHEUS	1.07" dual-diaphragm omni/cardioid/figure-8	639.00		
SATURN	5-pattern condenser (omni, cardioid, subcardioid,			
	hypercardioid, figure-8), -10/-20dB pad, shockmount	. 1199.00		
STC1	Cardioid condenser instrument mic10/-20dB pad.			
	mounting clip, windshield	179.00		
STC1-STEREO	Matched stereo pair of STC1 mics, mounting bar, clips, windshields.	499.00		
STC2	Cardioid large-diaphragm condenser, shockmount	359.00		
STC2X	Omni/cardioid condenser, -10/-20dB pad, shockmount	449.00		
	Pencil cardioid condenser, clip & foam windshield			
STC20	Large diaphragm cardioid condenser, mounting ring	249.00		
STC-OMNI-CAP	Omnidirectional capsule for STC1/STC1-STEREO			
	Hypercardioid capsule for STC1/STC1-STEREO			



VIOLET DESIGN BLACK KNIGHT LARGE DIAPHRAGM CARDIOID CONDENSER MIC This mic uses a

27mm capsule to produce a wide flat response with a slight presence bump at 3kHz. An integrated swivel-mount allows fast and handy positioning of the head for optimum instrument pick-up. Includes wood box, stand holder and users manual.

ITEM	DESCRIPTION	PRICE
BLACK-KNIGHT	. Cardioid condenser mic	580.95
BKS	. Spider-type shockmount	60.95
PSM	. Elastic shockmount	160.95
GSM-VIOLET-SILVER	. Compact vertical studio shockmount	210.95






































































































VIOLET DESIGN THE FINGER CARDIOID CONDENSER The Finger has a 1/2" diaphragm capsule and a unique body design incorporating an integrated, tapered reflector which reduces resonances, removes reflections and optimizes the microphone's cardioid polar pat-



tern. Integrated damping of the transducer reduces stand rumble, outside infrasonic interference and mechanical shocks. The optional and unique FRR Reflection Ring is a reflector disc which can be positioned at the head or anywhere along the body of the microphone to alter the polar pattern, frequency response and sensitivity

the interophone to diter the polar pattern, frequency response and sensitivity.		
ITEM	DESCRIPTION	PRICE
GOLD-FINGER	Matte black body with polished gold-plated hardware	. 500.95
BLACK-FINGER	Matte black body with polished nickel-plated hardware	. 500.95
FRR	Reflection ring ontion	60 95

#### **VIOLET DESIGN PEARL SERIES CARDIOID CONDENSER**

MICS These mics have a rear-ported spherical head and narrow tapered form reflector to reduce internal resonances and optimize the cardioid polar pattern. The Pearl Standard uses a medium single-diaphragm to provide a modern, airy and detailed sound while the Grand Pearl uses a large dual-diaphragm, providing the warm, classic sound usually associated with vintage studio microphones. Pearl Vocal is a handheld stage vocal mic, and has special shockmounting for reduced handling noise, a special mid-sized capsule designed for high gain before feedback with extended flat LF response and outstanding dynamic range. All models include wood box and stand clip.



6		
ITEM	DESCRIPTION	PRICE
PEARL-STANDARD	Medium single-diaphragm, cardioid instrument mic	544.80
GRAND-PEARL	Large dual-diaphragm, cardioid instrument mic	920.95
PEARL-VOCAL	Cardioid handheld vocal mic, black matte finish	900.95
RAV II 2-TA IUI V-M29	Shockmounting stand adapter	210 95

VIOLET DESIGN GLOBAL PRE A compact electrostatic mic preamp body for use with vintage German-made M-series interchangeable capsule heads, as well as B-series and VIN-series interchangeable capsule heads made by JZ in Latvia. The electronics are phantom powered, with a linear Class "A" discrete solid state transformerless design to provide extremely low selfnoise and distortion. The Global Pre provides a low-impedance, balanced output on a gold-plated 3-pin XLR. It comes in a wooden box and includes the GSM compact studio shockmount.

.... Elastic suspension shockmount .....



ITEM	DESCRIPTION	PRICE
GLOBAL-PRE	Preamp unit only, requires capsule (see below)	820.95
VIN12	Cardioid, bright, large-diaphragm capsule head,	
	similar sound to C12	. 1080.95
VIN26	Cardioid, medium bright, large-diaphragm capsule head	. 1080.95
VIN27	Cardioid, natural sounding, large-diaphragm capsule head	. 1080.95
VIN44	Figure-8, large-diaphragm capsule head	. 1080.95
VIN47	Cardioid, classic sounding, large-diaphragm capsule head,	
	similar sound to U47	. 1150.95
VIN55	Omni-directional, large-diaphragm capsule head	. 1080.95
VIN67	Cardioid, large-diaphragm capsule head,	
	similar sound to U67	. 1150.95
VIN89	Cardioid, medium-diaphragm capsule head,	
	similar sound to U89	. 1150.95

#### VIOLET DESIGN FLAMINGO JUNIOR CARDIOID CONDENSER MICS

The Flamingo Junior series are side-addressed studio microphones that use a single-diaphragm, cardioid electrostatic transducer which provides vintage tone with transparent highs, optimized vocal presence and fundamental low-frequency register with minimal proximity effect. An integrated capsule shockmount within the head and an included external compact studio shockmount reduce stand rumble and mechanical shocks. The custom-wound large humbucking audio transformer adds "analog warmth" to the sound. Comes with GSM stand mount and wooden box.



ITEM	DESCRIPTION	PRICE
FLAMINGO-JUNIOR	Cardioid condenser mic w/polished violet body	1150.95
FLAMINGO-JR-VINTAGE	Cardioid condenser mic w/matte black body	1150.95

#### VIOLET DESIGN AMETHYST CONDENSER STUDIO MICS

The Amethyst cardioid studio microphones use fully-discrete, phantom-powered Class "A" transformerless amplifiers. The Amethyst Standard uses a single diaphragm center-terminated capsule which provides modern, detailed sound with airy highs, medium vocal presence and accentuated low-end response. The Amethyst Vintage uses a dual-diaphragm, dual-backplate capsule which provides a classic, wide-spectrum, vintage microphone sound. Both models have a uni-directional cardioid polar



pattern with minimal proximity effect and are linear over the wide frontal incidence angle. They can be mounted directly on a standard microphone stand or in the optional ASM elastic shockmount. Comes in a wooden box.

ITEM	DESCRIPTION	PRICE
AMETHYST-STANDARD	.Single large diaphragm capsule, dark red	1520.95
AMETHYST-VINTAGE	.Dual large diaphragm capsule, grey/blue	. 1930.95
ASM	Optional elastic shockmount	160.95

**VIOLET DESIGN THE GARNET VACUUM TUBE MIC An electrostatic** multi-pattern studio mic with a vintage sound, warmed by vacuum tube circuitry and an output transformer. Features specially designed large dual-diaphragm transducer, and 9 different polar patterns. Its Class "A' fully-discrete internal vacuum tube preamp provides high output, low impedance and low distortion. A large humbucker, custom-wound audiotransformer balances the microphone's output, providing additional analog warmth to the sound. Soft starting, smart power supply and external elastic suspension shockmount are included.

ITEM	DESCRIPTION	PRICE
GARNET	. Electrostatic vacuum tube mic,	
	20Hz-20kHz, 9 different polar patterns	CALL

VIOLET DESIGN THE WEDGE This large dual-diaphragm cardioid condenser studio microphone has a warmer smooth tone with very high output and low noise. The fast transient response, crystal clear highs and loud SPL handling make it excellent for recording drums. The multi-layered wedge shaped brass mesh head design effectively reduces plosive sounds and breath, pop or wind noises. The internal solid state preamplifier is a Class "A" fully discrete transformerless circuit, and runs on 48V phantom power.



ITEM	DESCRIPTION	PRICE	
THE-WEDGE	Cardioid condenser studio mic, wooden box	990.95	
VSMD-BK	Elastic studio shockmount	130.95	4

#### VIOLET DESIGN THE GLOBE CARDIOID CONDENSER MICRO-

PHONE Globe features transformerless Class "A" discreet electronics, STANDAR internal shockmounts for both electronics and capsule, and a spherical and acoustically transparent head design. The Globe Standard has a classic wide-spectrum sound ideal for orchestral applications. The Globe Vintage uses a different dual-diaphragm capsule providing a sweet and warm, vin-

tage vocal micropho	one sound. Comes in a wooden box with shockmount.	
ITEM	DESCRIPTION	PRICE
GLOBE-STANDARD	Globe mic tuned for orchestral application,	
	with GSM shockmount	1919.00
GLOBE-VINTAGE	Globe mic tuned for classic vocal application,	
	with CCM abademount	2240 05

#### **VIOLET DESIGN FLAMINGO TUBE MICROPHONES**

These are side-addressed, cardioid, large dual diaphragm vacuum-tube studio microphones in 3 variations, with acoustically-transparent head construction and internal shockmounts. The 6267 vacuum tube preamplifier is a Class "A" fully-discrete circuit with massive heatsink, very high output, flat audio-response and ultra-low noise and distortion. The large custom-wound Permalloy humbucking audio transformer adds even more "analog warmth" to the sound with wide frequency response and minimum saturation. Comes with power supply, GSM stand mount, and wooden box.



ITEM	DESCRIPTION	PRICE
FLAMINGO-STANDARD	. Polished violet body w/classic wide-spectrum	
	vintage tube-mic sound and extended top end	CALL
FLAMINGO-VINTAGE	. Black matte body w/sweet, vintage, warm vocal	
	sound and high-frequency roll-off	CALL
FLAMINGO-ME	. Uses an ear-shaped capsule providing a unique,	
	resonance-free, warm and full vocal sound	CALL
VSM47FL	Optional spider-type elastic shockmount	. 420.95



Follow us!

















#### AKG PERCEPTION 120 USB MIC

- •2/3" diaphragm condenser mic with a low-mass diaphragm
- Integrated pop filter
- ·Switches for bass cut filter and attenuation
- Features a high-quality A-to-D converter (24-bit, 128x oversampling)
- Compatible with Windows XP, Windows Vista, Windows 7 and Mac OSX
- . Comes with tripod table stand, swivel mount and USB cable

**APEX** 

for ideal stereo imaging

MICROPHONE



**APEX APEX188 STEREO USB CONDENSER** 

• Dual XY axis cardioid pickup patterns

•Plugs in directly to any USB equipped

• Perfect mic for Podcasters, broadcast

•Full 20Hz-20kHz frequency response

•Dual 22mm cardioid diaphragm design

•24-bit/96kHz A to D converter:

16-bit/48kHz Resolution

applications, ENG and music applications

•USB connection cable & shockmount included

computer running Mac OSX or Windows XP



- •Ideal for multimedia applications or gaming
- ·Closed headphone with transparent blue ear caps
- ·Flexible headband for optimum fit
- Noise-canceling cardioid condenser microphone
- •USB converter controls volume •Ideal for gaming, multimedia, and VoIP
- Compatible with PC (Windows 98 Se, ME, 2000, XP, Vista) and Apple (MAC OS 9 and OS X)



SHOWN WITH

OPTIONAL SHOCKMOUNT



**BLUE YETI PRO MULTI-PATTERN/** STEREO USB/XLR **MICROPHONE** 

- •Multi-pattern USB/XLR mic
- Three custom condenser capsules for recording in cardioid, bidirectional, omnidirectional patterns or in stereo
- •Built-in 24-bit/192kHz analog-to-digital converter and headphone amplifier for zero-latency monitoring
- Simple controls for gain, mute, pattern selection and headphone volume

**BLUE ICICLE USB CONVERTER/** 

•XLR-input microphone preamp

**MIC PREAMP COMBO** 

•16-bit/44.1kHz resolution

Powers 48V phantom mics

Phantom power active light

•USB bus-powered, draws 200mA

Windows XP, Vista, and Mac OSX compatible

ICICLE.....USB converter & mic preamp .....

Analog level control

Requires no drivers

Includes 6ft, USB cable

**CAD U9 USB MINIMIC** 

•3.5mm headphone jack for playback

•Ideal for Podcasting, Skyping,

VoIP or recording music

Power LED indicator

•180° swivel and cardioid capsule allow for

precise placement and maximum sound quality

Compact USB cardioid

microphone

·Low-profile design

- 22kHz-192kHz sample rates, 15Hz-22kHz freq. response, 120dB max SPL, 4.5mV/Pa sensitivity
- •No drivers needed simply plug into a PC or Mac

YETI-PRO ...... Multi-pattern USB/stereo XLR mic........... 249.99














































#### BLUE SNOWBALL **CONDENSER USB**

•Condenser, pressure-gradient w/USB digital output

- •40Hz-18kHz frequency response
- •Includes desk stand and USB cable
- ·Windows XP, Vista, and Mac OSX compatible
- · Handles everything from soft vocals to loud garage bands - ideal for podcasting

	USB microphone, condenser	
INGER	Shockmount for Snowball microphone	59.99



- Unique 3-pattern switch
- (cardioid, cardioid w/-10dB pad, omni)
- •16-bit/44.1kHz sampling rate

- · Available in White, Brushed Metal or Gloss Black

SNOWBALLUSB microphone, conden	ser 99.99
RINGER Shockmount for Snowbal	l microphone 59.99



## CARDIOID CONDENSER MICROPHONE

- •USB digital output
- · Low-mass diaphragm
- Perfect for podcasting, voiceovers & home or field recording
- · Includes pivoting stand mount, tripod desk stand, USB cable & storage pouch





#### **BLUE SNOWFLAKE PORTABLE USB MIC**

- ·Professional-quality portable recording mic

SNOWFLAKE ...... Portable USB mic.....



AT2020-USB...... Cardioid USB mic, 20Hz-16kHz ......



#### **AUDIX USB-12 HIGH DEFINITION CONDENSER MIC**

- •Records directly into computer via USB port
- •Sleek, low-profile desktop design
- ·No additional preamp or interface needed •16-bit, 48kHz sampling rate
- •12mm high-resolution condenser capsule •Push-to-talk includes choice of "steady-on", or "momentary on"
- · Includes bass roll-off filter, & headphone jack for monitoring



... USB desktop mic, white.....



#### **BLUE YETI MULTI-PATTERN/** STEREO USB MIC

- •Multi-pattern USB mic
- •3 premium, 14mm tuned condenser capsules, allowing for recording in stereo or choice of three patterns: cardioid, omnidirectional, and bidirectional
- •THX Certified for exceptional sound and performance
- ·Built-in high quality analog-to-digital converter and headphone amplifier
- ·Simple controls for headphone volume, pattern selection, instant mute, and mic gain located directly on the mic
- ●No drivers needed simply plug into your PC or Mac









**FULLCOMPASS.COM** 



#### ASTATIC COMMERCIAL **CAD U7 USB TABLETOP** RECORDING MICROPHONE

- ·For speech/dictation, legal records, audio for slide presentations, laptop recording Frequency response tailored
- for speech Omni-directional pick-up pattern for 360° coverage
- •10' USB cable for flexible mic placement
- · Low-profile for unobtrusive recording Windows XP and Macintosh OSX compatible






Full Service: 800-356-5844

M-F: 9:00-5:30 CST

































































ACCESSORIES

















 Low noise analog mic preamp with XLR input

- Powers 48V phantom mics
- •USB bus-powered
- ·Zero latency headphone output
- •24-bit/96kHz conversion
- USB output connector

MAC/PC

low-noise analog front ends

to USB, 3-position gain control

MXL LARGE DIAPHRAGM

**CARDIOID USB MICS** 

Cardioid pickup patterns

and integrated pop filter

(pad)

MXL-USB.008.

·Heavy-duty wire mesh grille

20Hz-20kHz frequency response

•3-position switchable attenuator

•16-bit Delta Sigma A/D converter

with 44.1kHz and 48kHz sample rates

· Includes a travel case, desktop stand,

10' USB cable and applications guide

MXL-USB.006 ....... Cardioid, USB, silver...

MLX AC-404 USB-POWERED

INTERNET CONFERENCE MIC

programs like  $Skype^{TM}$ 

·Built-in custom circuitry

Automatic gain control

•6ft USB cable

·For use with internet conferencing

·Comes with leatherette zipper case

3-capsule boundary mic design with 180° coverage

·Built-in headphone/speaker monitoring jack

Cardioid, USB, 32mm capsule, black ..... 137.74



<b>P</b>
----------

MICPORT-PRO	USB	microphone	preamp.	149.95

MXL MIC MATE SERIES USB ADAPTERS FOR

No special drivers required, features fully-balanced

line-level sources from news line feeds, pro audio

gear, etc. 3 selectable levels (+10dB, +4dB, and -10dB)

to USB, supplies 48V phantom power, zero latency

with 3 selectable levels .. MICMATE....... Dynamic mic adapter/preamp w/USB ... 59.20
MICMATE-PRO......Mic adapter/preamp w/USB output...... 89.60

•Mic Mate line-level adapter allows you to adapt

Mic Mate adapter adapts any dynamic mic

•Mic Mate Pro adapts any condenser mic

monitoring, and has a 1/8" headphone jack

MICMATE-LINE-LEVEL .. USB line level adapter

RT-PRO	USB	microphone i	oreamo	 149.95	j



## *SAMSON*

RØDE

**MICROPHONE** 

•USB bus-powered

**RØDE PODCASTER USB** 

•40Hz-14kHz frequency response

•Windows and Mac compatible

Internal capsule shockmounting

•28mm dynamic neodymium capsule

•18-bit resolution, 8kHz to 48kHz sampling

·Tight cardioid pattern for superior off-axis sound rejection

•Includes microphone stand mount and a 40" USB cable

•3.5mm stereo headphone jack output with volume control

..... Studio mic arm with two axis swivel mount, holds up to 4.4lbs .....

Optional shockmount...

#### SAMSON METEOR USB STUDIO MIC •Large (25mm) diaphragm condenser

PODCASTER.....USB dynamic microphone..

- for rich audio recording
- ·Cardioid pickup pattern
- ·Smooth, flat frequency response of 20Hz-20kHz
- •CD quality, 16-bit, 44.1/48kHz resolution
- Durable chrome-plated body
- ·Plugs directly into any computer with a USB input, no drivers required
- Compatible with most computer-based DAW software
- •Stereo 1/8" headphone jack with volume control for no-latency monitoring
- Fold-back leg design provides optimal mic positioning

# SAMSON

#### SAMSON GO MIC USB CONDENSER MIC

- •Plug-and-play Mac and PC compatible
- •USB digital output
- No drivers required
- ·Custom compact design that clips to a laptop or sits on a desk
- · Headphone out for no latency monitoring
- Cardioid and omni-directional patterns
- •Sample rate of 44.1kHz/16-bit
- •20Hz-18kHz frequency response
- ·For recording music, podcasting, field recording, voice recognition software, iChat, VoIP and web casting
- Titanium finish

GO-MICUSB condenser microphone	GO-MIC	USB	condenser	microphone.		49.	.00
--------------------------------	--------	-----	-----------	-------------	--	-----	-----

#### SAMSON

#### SAMSON Q2U DYNAMIC HANDHELD MICROPHONE WITH XLR AND USB

- · High-quality dynamic handheld microphone with XLR and USB I/O
- •XLR output plugs directly into any console
- •Plugs directly into any computer with a USB input
- •3.5mm stereo headphone jack output with volume control for no-latency monitoring
- •On/off switch controls audio to XLR output
- •High-quality A/D converter with 16-bit/48kHz sampling rate Cardioid pickup pattern
- ·Compatible with any computer-based digital audio workstation
- •Includes mic clip, USB and XLR cables and Cakewalk® Music Creator



Q2U Handheld	microphone w/XLR &	USB outputs	60.00

#### SAMSON'

#### SAMSON USB CONDENSER **MICROPHONES**

- ·Plug the mic directly into a laptop for a fuss-free portable recording, without the need for external preamps or digital converters
- •High-quality A/D converter with 16-bit/48kHz sampling rate
- Compatible with Vista, WinXP, Mac OSX
- •C01U/CO3U ships with Sonar LE, USB cable, desktop stand

CO1U CO3U

·Pak versions ship with Sonar LE, desktop mic stand, mic clip, shockmount, USB cable, and aluminum case

CO1U-CONDENSER-MIC	USB mic, cardioid	. 99.00
C01U-PAK	Podcast/Recording pack w/C01U	149.00
CO3U-MULTI-MIC	USB mic, multi-pattern	149.00
C03U-PAK	Podcast/Recording pack w/C03U	199.00

#### SAMSON'

#### SAMSON G-TRACK USB MICROPHONE WITH STEREO INPUT

- · Large diaphragm USB studio condenser microphone with gain control
- ·Stereo input jack for instrument and line level signal with gain control
- Stereo headphone output for no latency monitoring with level control
- •3-position headphone switch for stereo, mono, computer monitoring
- •USB bus-powered and compliant
- ·Audio I/O cable, USB cables and desktop microphone stand included
- ·Bundled with Cakewalk's Sonar LE DAW software


GTRACK-USB-MIC .. USB microphone with stereo input .......... 149.00

PG27USB PG42USB

#### SHURE

#### SHURE PG SERIES USB SIDE ADDRESS CONDENSER **MICROPHONES**

- · Large diaphragm capsules
- •USB plug-and-play interconnect with 1/8" headphone jack for zero-latency monitoring, monitor mix control for blending mic and playback audio
- Cardioid pickup pattern
- •Integrated preamp with microphone gain control
- •Pad switch (15dB on the 42, 20dB on the 27)
- •USB-powered, 500mA maximum
- •20Hz-20kHz frequency response



#### SHURE

#### SHURE X2U XLR TO USB MIC ADAPTER

- Plug-and-play USB connectivity
- Compatible with Windows Vista Business, XP Pro/Home SP1 or later, 2000 Pro, and Mac OSX
- 10.1 or later, requires 64MB RAM or better •Includes 3m/9.8' USB cable,
- and padded zipper carrying pouch · Monitor mix control for blending mic wand playback audio
- · Headphone jack with volume control for monitoring with zero-latency
- •Integrated pre-amp provides +48V phantom power and mic gain signal control
- •16-bit up to 48kHz sample rate,
- 20Hz-20kHz +/- 1dB frequency response ·Peak signal LED indicator

X2U ......XLR-to-USB signal adapter w/headphone output ...... 99.00





















AC-404.......Web conferencing boundary mic, 40Hz-16kHz.......92.40

**AUDIO-TECHNICA BP4027 AND BP4029** M-S STEREO SHOTGUN MICS Designed for broadcasters, sound recordists and videographers, these phantom-powered models feature independent line-cardioid and figure-8 elements configured in an M-S (Mid-Side) arrangement.



Each provides a switch-selectable internal matrixing system offering a selection of wide and narrow stereo (L/R) output or M-S output. A switchable low frequency rolloff filter helps minimize the pickup of unwanted low frequency noise. The models differ from one another primarily in length (the BP4027 is 15 in. long and the BP4029 is 9 in. long); they both feature a lightweight rugged design and sleek black color scheme, ideal for on-camera use.

ITEM	DESCRIPTION	PRICE
BP4027	. 15" stereo shotgun microphone	. 771.36
BP4029	9" stereo shotgun microphone	. 700.12

AUDIO-TECHNICA AT2022 X/Y STEREO MIC A condenser microphone designed for stereo recording. Two unidirectional condenser capsules in an XY configuration pivot to allow for narrow (90°) or wide (120°) stereo operation. The capsules also fold flat for storage and transportation. Designed for general stereo recording and field sound capture, it provides the spatial impact and realism of a live sound field. Runs on one AA battery. A switchable low-frequency roll-off minimizes pickup of unwanted lowfrequency noise. It features a frequency response of 20Hz-20kH, a max SPL level of 122dB, 200-ohm impedance rating and a signal-tonoise ratio of 75dB, 1kHz @ 1Pa. It comes equipped with a stand clamp, AA battery, windscreen and .5 m cable that terminates in a 3.5 mm stereo plug.

ITEM	DESCRIPTION	PRICE
AT2022	X/Y stereo condenser mic, 20Hz-20kHz, 122dB	249.00



views and home recording. The coincident capsule configuration produces an XY stereo image in a small housing. Both models include a high-pass filter, while the BP4025 also adds a -10dB pad

meer, mme	and 21 1020 and adds a 1022 page	
ITEM	DESCRIPTION	PRICE
AT8022	X/Y stereo condenser microphone, battery or phantom powered,	
	20Hz-15kHz, includes 2 cables (dual 3-pin XLRM-type & 3.5mm TRS)	399.00
BP4025	X/Y stereo condenser microphone, phantom power only,	
	20Hz-17kHz, includes 1 cable (dual 3-pin XLRM-type)	649.00

#### **AUDIO-TECHNICA** ATR6250 **CONDENSER** VIDEO/RECORDING

MICROPHONE An extremely affordable, highquality stereo pickup in a single microphone. Its compact design is ideal for use with video cameras and portable audio recorders. Includes 3.5mm stereo female output connector, 3.5mm-



3.5mm stereo camera cable, 3.5mm stereo to 2x3.5mm mono recording cable, camera mount, interchangeable mic stand base, windscreen, two 3.5mm to 1/4" mono adapters and AA battery.

ITEM	DESCRIPTION	PRICE
ATR6250	Stereo condenser video microphone	43.29



#### **HOLOPHONE PORTAMIC 5.1 SURROUND** SOUND MIC An affordable, professional, por-

table surround microphone designed for both H€LOPHONE® audio and video applications. It features a multidirectional pick-up pattern, compact, low-profile body and captures discrete and instantaneous 5.1 channel audio. The PortaMic 5.1 has a 12dB pad, stereo output, plug and play capability, and includes an onboard Dolby PLII encoder. Powered by 9V battery.



DESCRIPTION PORTAMIC-5.1 ...... Surround sound microphone...



#### **RØDE SVM STEREO VIDEOMIC**

The X/Y configuration enables the SVM to capture the true ambience of the recording space, while still



offering a high level of rear rejection and low noise. The SVM offers 9V battery operation, an LED battery status indicator, a hi-pass filter switch, and a -10dB pad switch which allows for the mic to be used on most cameras with perfect level control. You can also use the SVM as a remote mic on a stand.

ITEM	DESCRIPTION	PRICE
STEREO-VIDEOMIC	Stereo video microphone	249.00

**RØDE NT4 SINGLE POINT STEREO MIC** The RØDE NT4 is a studio grade condenser microphone, but is perfect for location recording. It utilizes two 1/2" capsules in a 90°, XY arrangement. It comes with a case with a stand mount, windscreen and custom stereo cables, which include both XLR and mini-jack connectors. Requires 48V phantom power but can also use a 9V battery. Freq. response is 20Hz-20kHZ, max SPL of 143dB, dynamic range >128dB.

ITEM	DESCRIPTION	PRICE
NT4	. Single point stereo mic	. 529.00
WS4	Replacement windscreen for NT4	19.99



































PRICE

PRICE

# SHURE \* SHURE VP88 STEREO CONDENSER The VP88 incorporates a forward-facing car-

dioid mid-capsule, a perpendicular bidirectional side capsule and a built-in stereo matrix to provide wide, natural, uncolored response for optimal stereo imaging. Yet it's 100% mono compatible. Perfect for reinforcement, live music recording, drum overhead miking, and ambient studio miking. Frequency response 40Hz-20kHz. A88SM shockmount for stand mounting.

	DESCRIPTION	PRICE
VP88	Stereo condenser	697.32
A88SM	Shockmount for stand mounting	192.38
C110	25' extension cable	69.65
084=90G4046	Replacement swivel stand adapter	19.89
084=49A91	Replacement foam windscreen	32.75
084=95A2300	Replacement stereo mic cable	24.94



SONTRONICS **APOLLO** X/Y STEREO RIBBON MIC A Blumlein X/Y stereo ribbon microphone with an open bas-

ket design, allowing it to soak up every nuance of your recording and capturing the whole ambience for a truly complete sound. You can also use just one channel for mono recordings. Uses a unique shockmount that's extremely effective in providing isolation from transmitted noise. Includes shockmount, cable, and velvet-lined ABS flightcase. ITFM DESCRIPTION

X/Y stereo/figure-8, 20Hz-20kHz, requires phantom power 48V x2...... 1699.00 APOLLO



#### AVANTONE AVANTONE ELECTRONICS STEREO FET MIC The CK-40 condenser mic is designed for

versatility with group vocal, room, piano, or utility applications. It features twin large 35mm gold sputtered thin mylar diaphragms, three polar patterns (cardioid, omni, and figure 8), a –10dB attenuation switch, and a 80Hz high-pass filter switch. The mic includes a 5-pin mic cable that plugs into the provided 1x2 stereo splitter box, a custom shockmount, wind filter, and padded aluminum travel case.

ITEM	DESCRIPTION	PRICE
CK-40	Condenser mic, 20Hz-20kHz freq response, 48V phantom po	ver599.00



VIOLET DESIGN **STEREO FLAMINGO MICROPHONE** This

DESIGN unique stereo microphone uses two large diaphragm, true electrostatic JZ capsules with rotating spherical metal mesh heads that can be positioned according to its markers. It includes an integrated elastic studio suspension cradle with a swivel mount.

DESCRIPTION FLAMINGO-STEREO ... Stereo mic ..

















































AUDIO-TECHNICA AT SERIES SHOTGUN MICS The AT875 is a 6.9" long electret condenser operating from 11-52V phantom power with 127dB SPL. The AT897 is an 11" long shotgun ideal for camera-mounted use. The 14.5" AT8035 has an acceptance angle of 60° and the 18" AT8015, 40°. The AT897, AT8015 and AT8035 will operate over 3000 hours on a single AA cell or 11-52V of phantom power and have a switch to roll off low frequencies. All come with a windscreen, protective case, and mic clip.


ITEM	DESCRIPTION	PRICE
AT875R	. Short shotgun, 6.9" long, 90Hz-20kHz, phantom power only	215.19
AT897	. Short shotgun, 11", 20Hz-20kHz	254.89
AT8035	. Medium shotgun, 14.5" long, 40Hz-20kHz	399.00
AT8015	. Long shotgun, 18" long, 40Hz-20kHz	429.00
AT8405A	. Replacement stand adapter	9.98
	. Shockmount system (universal)	



#### (A) audio-technica always listening.

AUDIO-TECHNICA ATR6550 CONDENSER SHOTGUN MIC

Crisp & intelligible pickup - far away or up close. In its "Tele" range



ITEM	DESCRIPTION	PRICE
ATR6550	. 70Hz-18kHz, 3' long output cable with 3.5mm plug	64.92

## **≰**I∧ZDEN

#### AZDEN SGM SERIES SHOTGUN

MICS The SGM-PDII has an electret condenser and an 8.12" supercardioid barrel. The SGM-1X features an 11.8" supercardioid barrel, while the SGM-2X




features an 8.125" omni barrel with an extension that creates a 16" supercardioid. The SGM-1000 has a 12.2" supercardioid barrel and is phantom powered. The SGM-X has an 8.34" supercardioid barrel designed for use with mini DV cameras. All feature an integrated shockmount/shoe camera mount and windscreen.

ITEM	DESCRIPTION	PRICE
SGM-PDII	Supercardioid condenser, 80Hz-18kHz, phantom powered	199.00
SGM1X	Supercardioid condenser, switchable low cut filter, XLR out,	
	80Hz-18kHz	169.00
SGM2X	Omni with extension condenser, switchable low cut filter,	
	XLR out, 40Hz-20kHz	219.00
SGM1000	Supercardioid condenser, phantom powered,	
	switchable low cut filter, XLR out, 80Hz-20kHz	249.00
SGMX	For use with mini DV cameras, 3.5mm mini-jack, 80Hz-18kHz	119.00
SMH1	Shockmount shotgun mic holder	30.24

#### AZDEN SMX-10 STEREO SHOTGUN MIC

Record in stereo directly with this 7" long, dual unidirectional, electret-condenser mic. It is powered by a single "AAA" battery (not included) and features a built-in cable with a 3.5mm



WE SELL Rycote MICROPHONE ACCESSORIES SEE PAGE 454 WINDSHIELD-KIT
---



QUE AUDIO Q210 VIDEO SHOTGUN MIC KIT Designed to mount to professional, small video cameras where a shorter, compact shotgun mic is needed to stay out of the shot. Features supercardioid polar pattern for superior off-axis rejection, lightweight construction, full frequency response for targeted sound source, switchable 80Hz @ 12dB high pass filter, -36dB sensitivity and SPL -130dB. Can also be mounted to the Q Mini Boom Pole for "run and gun" boom applications. Package includes shockmount, shoe adapter with adjustable gimbal, 30cm curly cable (XLRF to right angle XLRM), WOMBAT fluffy windjammer and 1/4" to 3/8" thread converter. Requires 48V phantom power.

ITEM	DESCRIPTION		PRICE
Q210	 . Short shotgun	(210mm) mic kit	 . 329.00
OMB1	Q Mini Room P	Pole for shotgun mics	89 99



QUE AUDIO Q SNIPER SHOTGUN MIC KIT Includes a mini shotgun mic plus the Q Mini Boom Pole. Also includes a base for the boom pole, QAD2 passive 3.5mm to XLR adapter plug and 6.5ft cable. The Q Mini Boom Pole is made out of telescoping stainless steel outfitted with a ribbed rubber comfort grip for extremely lightweight and travel-friendly location booming. Measures 13.5" when collapsed and 57.5" fully extended w/out any attachments. Use the Q Sniper Kit anywhere a high quality, compact and lightweight mini shotgun microphone is needed (on/off camera run-and-gun, boom pole/location sound, desktop stand, ENG/Journalism, studio production). Although the mini-shotgun mic is extremely small and unobtrusive, the rejection properties are comparable to standard wide body shotgun mics. The mic is self-powered using (2) AG4 1.5V batteries (included) but can also be phantom powered (balanced/low-impedance) using the optional QAD3 XLR adapter (batteries remain in mic for parallel operation). The kit also includes shockmount, cold shoe mount with adjustable gimbal, rubber shock absorber, WOMBAT fluffy windjammer, and a TRS 3.5mm female to XLR male adapter.

ITEM	DESCRIPTION	PRICE
QSNIPER-KIT	Sniper mini shotgun mic kit w/mini boom pole	. 479.00
QAD3	Q compact thread (female) to 90° male XLR, requires 48V phantom power, balanced low impedance connection to digital recorders,	1
	standard or camera-mount mixers and pro video camcorders	34.99
QBA2	1.5V AG4 batteries, package of 10	15.90



ITFM

# Compact... Lightweight... Durable...

... and extremely travel friendly!

## Introducing...

#### The Q DSLR-VIDEO KIT

Mini Shotgun w/Windscreen Wombat (Fluffy Windjammer) Mini Shockmount Rubber Shock Absorber Cold Shoe w/Adjustable Gimbal 30cm Curly Cable 3.5mm Adapter Plug AG4 Batteries (2) Leatherette Carry Case

#### The Q SNIPER KIT

Mini Shotgun w/Windscreen Mini Boom Pole. Base (for Mini Boom Pole/desktop stand) Wombat (Fluffy Windjammer) Mini Shockmount Rubber Shock Absorber Cold Shoe w/Adjustable Gimbal 2 Meter Straight Cable 3.5mm Adapter Plug 3.5mm to XLR Adapter AG4 Batteries (2) Leatherette Carry Case



#### Complete Microphone Solutions

When our Australian design team released the Que Mini Shotgun, we knew we had a winner. To make such a small microphone to be so accurate with such a high quality of performance was a complex engineering feat.

So... we packaged it in two specific kits for use with HD camcorders and DSLR cameras, or for wherever a Mini Shotgun with superlative audio quality is needed.



From on-camera run-and-gun to booming location shoots. Anywhere a high quality, compact, lightweight mic is needed.

#### The Q COMPACT CONNECTION SYSTEM (QCCS)

Delivering rock solid twist-on connection capabilities opening up a wide variety of Q adapter options including all the popular wireless connectors and our QAD3 48V phantom powered balanced low impedance XLR plug.



Got full size rejection and throw, all the accessories, affordable price...

# The 210 Shot Gun Microphone

#### The Q 210 VIDEO SHOTGUN MICROPHONE KIT

210mm Shotgun w/windscreen Wombat (fluffy windjammer) Cold Shoe w/Adjustable Gimbal 30cm Curly Cable XLR to 90 degree male Leatherette Carry Case





### You've known our premium Da-Cappo Microphones... Now Introducing them as... The Q Performance Series



DA15 single ear headworn microphone with in-ear monitor bud





DA12 single ear water-resistant headworn microphone



800-356-5844 FULLCOMPASS.COM



Q the Talent - headworn mic for the budget conscience



DA04 lavalier micro microphone



Que Audio

















































MIC KIT Designed specifically for use with HD camcorders and DSLR cameras for high quality sound in a small, lightweight package. Great for onboard run-and-gun situations and wide body shotgun mic rejection applications. Self powered by (2) AG4 1.5V batteries (included) but can also be phantom powered (bal-

**QUE AUDIO QVIDEO-KIT** 

MINI DSLR SHOTGUN

anced/low impedance) using the QAD3 XLR adapter (sold separately). Features a hypercardioid polar pattern, high SPL capabilities, -36dB sensitivity and 100 hours of continuous use. Kit includes shockmount, cold shoe adapter with adjustable gimbal, rubber shock absorber (use with mini shockmount and cold shoe), 12" curly cable with Q compact threads, WOMBAT fluffy windjammer, DAADTRL Q compact thread to

1/8" TRS and Q	BA2 AG4 batteries (pair).	
ITEM	DESCRIPTION	PRICE
QVIDEO-KIT	4.92" mini DSLR shotgun mic with accessories	299.00
QAD3	Q compact thread (female) to 90° male XLR, requires 48V phanton	1
	power, balanced low impedance connection to digital recorders,	
	standard or camera-mount mixers and pro video camcorders	34.99
UCBL2	6.5ft compact thread (male) to compact thread (male)	
	straight black cable	
QAD2	1/8" (female) to XLR (male) straight passive adapter black	24.99
DAADTRL	1/8" for non-phantom powered connection to	



MXL FR SERIES SHOTGUN MICS Versatile mics for general video production, broadcast applications, interviews, and Foley work. The FR-304 comes with an AA battery and can be self-powered or via your video camera's power. All models include a windscreen, and a mic clip/stand adapter (except for FR-303).

ITEM DESC	RIPTION	• `	•	*	PRICE
FR-30010" p	nantom powered	supercardio	oid w/14mm	capsule,	
FET p	reamp, 50Hz-18F	кНz			148.40
FR-30116.5"	phantom powere	ed supercard	lioid w/14m	m capsule,	
FET p	reamp, 50Hz-201	кHz			184.80
FR-3036" sh	otgun mic w/buil	t-in XLR cal	ole, 50Hz-15	kHz	138.60
FR-30414.5"	shotgun mic w/	14mm capsi	ıle, FET prea	mp, 50Hz-20kHz	154.00

RØDE VIDEOMICS Røde's VideoMics are supercardioid condenser microphones with

integrated shockmounts designed to connect directly to consumer video cameras and DSLRs. They attach to any camera/camcorder with the standard hot-shoe

audio devices/recorders ...

mount. The mics feature 3.5mm stereo mini-jack output (dual mono), rugged ultra-lightweight ABS housing, and 9V battery power with up to 70 hours battery life. Pro version adds two step HPF (flat, 80Hz), three-position level control (-10dB, 0, +20dB), internal shockmount and includes DeadCat VMP furry wind shield.

ITEM		PRICE
VIDEOMIC	Shotgun mic, 9V powered	149.00
	Shotgun mic, 9V powered	
VXLR	Female mini to XLR-M adapter for VideoMic	9.99
	10' extension cable for VideoMic	
WSVM	Replacement wind screen for VideoMic	11.99

#### ALSO SEE SVM STEREO VIDEO MICROPHONE IN STEREO MIC SECTION.

RØDE NTG SERIES SHOTGUN MICS The NTG-1/ NTG-3 operate on 48V phantom, and the NTG-2 can operate from phantom or internal AA battery. NTG3 uses RF-bias technology and is almost completely resistant to



VIDEOMIC-PRO

moisture. It is designed to withstand adverse environmental conditions and has a high level of immunity to RFI. All come with clip mount and windscreen suitable for outdoor recording situations. The NTG-3 also includes a weather resistant aluminum storage cylinder. All mics include a zip pouch.

ITEM	DESCRIPTION	PRICE
NTG1	48V phantom only, 8.5"	249.00
NTG2	48V phantom or AA battery, 11"	269.00
	48V phantom only, moisture resistant 10"	
DEADCAT	Wind muff for NTG1/NTG2	39.00
WSVM	Replacement windscreen for NTG1/NTG2	11.99

#### **SENNHEISER®**

ITFM

MKF400

SENNHEISER MKE400 VIDEO CAMERA SHOTGUN MICROPHONE A rugged, professional and compact microphone for cameras with a lighting shoemount and external microphone input. It features an all-metal housing.



maximum side noise rejection, switchable sensitivity for long and short distances, single AAA battery operation, coiled cable, and integral shockmount. Includes a foam windscreen.

5.1" compact shotgun mic for video cameras.....

- Manua-Manua-Manua (1997)	
	MKH

SENNHEISER MKH SERIES SHOTGUN MICS Interference tube microphones with supercardioid/lobar (>2kHz) patterns with high directivity throughout the whole frequency range. Very lightweight with exceptionally low inherent self-noise and high sensitivity. MKH416 is a pressure gradient receiver with short interference tube. MKH60 and MKH70 include switchable roll-off filter and treble emphasis, along with switchable pre-attenuation.

ITEM	DESCRIPTION	PRICE
MKH60-P48	11.02" short shotgun, 50Hz-20kHz	1499.95
MKH70-P48	16.14" long shotgun, 50Hz-20kHz	1749.95
MKH416P48U3	9.84" short shotgun, 40Hz-20kHz	999.95

### SHURE

SHURE SM89 CONDENSER SHOTGUN MICROPHONE At a distance it discriminates dialogue or effects, even in noisy surroundings. A slight presence rise compensates for high-frequency losses. It has a dynamic range of 111dB and a frequency response of 60Hz-20kHz, switchable L.F. roll-off and uses 11-52V phantom power. Other features include suppressed side pickup with minimum comb filter effects, aircraft-grade materials, foam windscreen and durable carrying case.

ITEM	DESCRIPTION	PRICE
SM89	. Condenser shotgun microphone, hypercardioid, 20-5/8" long	658.76
A89SM	. Shockmount for SM89	133.95



#### SHURE VP82/VP89 MODULAR SHOTGUN MICS The VP89 and VP82 shotgun mics provide exceptional audio quality for broadcast/media production venues. The VP89 has 3 interchangeable capsules – long, medium and short. These are used when critical sound capture is required. The VP89L is ideal for sporting events/field recording as it targets sources of high volume over long distances. The

VP89M offers a wider target for higher ambience, suited

for audience response, talk shows and live concerts. The VP89S is perfect for camera mounting and features a wide pickup angle for high ambience. The VP82 is compact & lightweight, offering excellent off-axis rejection for sound capture and reinforcement in camera-mounted AV media productions. It includes an integrated preamp design for exceptional performance.

ITEM	DESCRIPTION	PRICE
VP89L	Long shotgun, w/RPM89L capsule	999.00
VP89M	Medium shotgun, w/RPM89M capsule	899.00
VP89S	Short Shotgun, w/RPM89S capsule	699.00
VP82	Non-modular shotgun mic for camera mount,	
	includes zipper pouch and windscreen	299.00
RPM89L	15.21" long capsule for VP89 systems C	OMING SOON!
RPM89M	9.41" medium capsule for VP89 systems C	OMING SOON!
RPM89S	6.41" short capsule for VP89 systemsC	OMING SOON!





















































#### AUDIO-TECHNICA AT8004L LONG-HANDLE OMNI-DIRECTIONAL DYNAMIC MICROPHONE

Ideal for interviews and sports broadcasting, with an extended-length handle (AT8004L) that provides ample room for a microphone flag. Provides natural reproduction of surrounding ambience. Rugged housing with hardened-steel grille stands up to field use, while internal shock mounting minimizes handling and cable noise. Includes stand clamp and protective pouch.

ITEM	DESCRIPTION	PRICE
AT8004L	Omni-directional, 80Hz-16kHz, extended handle, 9.43" long	102 72
AT8004		102./3
	5.93" long	91.20
AT8101	Optional windscreen for	
	AT8004/AT8004L	6.83

tures an omnidirectional polar pattern that provides

maximum ambient pickup. It gives a very smooth,

extended response on- and off-axis and has a low

sensitivity to popping and overload. Operates on

battery or phantom power. Stand clamp, windscreen,

.Omnidirectional condenser mic,

**AUDIO-TECHNICA AT8010 CONDENSER MICROPHONE** Ideal for interviews, group vocals,

or acoustic guitar, the AT8010 fea-

battery and soft pouch included.

beyerdynamic)))

DESCRIPTION

20Hz-20kHz...

ITEM

AT8010



300-BLACK...

ITEM

635A.

ence for authentic audio.

COLES 4104 COMMENTATOR'S RIBBON MIC The 4104 BBC Design ribbon COLES mic is designed for high-quality commentary speech recording even in noisy sur-

EV 635A DYNAMIC OMNI The Electro-Voice

635A has flat response for recording speech and

music for video. Will pick up both the desired sound and ambi-

DESCRIPTION

Omni, gray finish.. Omni, black finish...

Optional windscreen......

roundings. The 4104's noise cancellation provides for better than 30dB of discrimination between voice and background noise. Features include: figure-8 polar pattern, 60Hz-12kHz frequency response and distortion of less than 1% at 120dB SPL. The body housing is lightweight and robust with a stainless steel lip screen that controls talking distance for optimum pickup.

ITEM	DESCRIPTION	PRICE
4104B-XLR	. Commentator's ribbon mic	740.79
4104-HS	. 10-pack hygiene kit	42.90



MD42

MD46

EV RE50 DYNAMIC OMNI A shock isolated version of the

Electro-Voice 635A to reduce unwanted handling noise. Offers experienced and novice alike mechanical noise free audio. The "infield" mic of choice used by professionals.

ITEM	DESCRIPTION	PRICE
RE50-BLACK	Dynamic omni	287.00
RE50N/D-BLACK	Omni microphone	308.00
	Optional windscreen	5.05



PRICE

146 92

#### SENNHEISER

SENNHEISER ENG MICROPHONES High-quality microphones optimized for rough use in live reporting and broadcasting environments. The design of the mics helps block wind and noise. Mic bodies are refined steel with black finish. Does not include mic clip.

ITEM	DESCRIPTION	PRICE
MD42	Omni-directional dynamic mic, 40Hz-18kHz	199.95
MD46	Cardioid dynamic mic, 40Hz-18kHz	199.95
MZQ800	Mic clip	11.48



#### SHURE

SHURE SM63L This compact, lightweight handheld mic was designed for broadcast professionals who need an extra long interview mic that has very low handling noise. The omni-directional pattern ensures pickup of the subject and the rugged design and Shure's legendary quality make this a mic that every interviewer should have.

ITEM SM63L	DESCRIPTION .Omni-directional dynamic, champagne finish	PRICE 135.66
	. Omni-directional dynamic, black finish	
	.Short handle version	

SHURE VP-64 Shure's VP-64 is rugged and engineered to withstand nearly any kind of abuse. Its neodymium magnet structure maximizes signal to noise ratio and helps cut through background noise. Built-in pop/blast filter and

snockmounted capsule keeps wind and handling noise at a minimum.		
ITEM	DESCRIPTION	PRICE
VP64A	. Omni-directional dynamic microphone	71.97
Δ57F	Replacement stand adapter	7 98



**BEYERDYNAMIC M-58** This is an omni-directional high output moving coil or dynamic microphone that has significant reduced handling noise because of

its internal shock mounting. Its extended frequency

response puts it into a class by itself for the sole

purpose of announcing, interviewing, or ENG. The

rugged construction, non-reflective finish and slim

profile make it the perfect mic for on camera use. The smooth, natural response also makes it less susceptible to feedback where a PA is being used.


#### BEYERDYNAMIC MCE58 CONDENSER MIC

A highly accurate electret-condenser omni interview microphone with integrated shockmount and pop shield for in-field broadcasting. Powered by internal AA cells and provides a high-balanced output level for broadcast equipment.

ITEM	DESCRIPTION	PRICE
MCE58	Condenser mic	389.00

#### $SONY_{i}$

SONY F112 AND F115B INTERVIEW MICROPHONES High-quality handheld dynamic microphones designed for field production and newsgathering applications. These mics are equipped with a newly developed omni-directional microphone capsule for clear voice pick-up from all directions. The metal body is rugged with an ergonomic design for a stable



ITEM	DESCRIPTION	PRICE
F112	Omni-directional dynamic	CALL
F115B	Omni-directional dynamic, weather-resi	stantCALL

















































uses the same transducer as the C562BL. The C562CM has been designed specifically for permanent, "invisible" mounting in ceil-

ings, walls, tables, stage props, etc. The C562CM is a perfect tool for surveillance or live recording since a single microphone can cover an entire room. The supplied XLR phantom power adapter connects to the microphone cable through a miniature connector so installation holes can be smaller than the diameter of the phantom power adapter.

ITEM	DESCRIPTION	PRICE
C562CM	. Low-profile boundary mic, omni (hemispherical), 20Hz-20kHz	. 299.00



AUDIX M60 BOUNDARY MIC Features Micros technology with RF immunity, fully integrated preamp and is optimized for voice. Hemi-cardioid pattern for directional coverage, cable can be routed 90° to 180°, shock resistant and available in black, white or nickel.

ITEM	DESCRIPTION	PRICE
MAN	Roundary mic for vocal and other applications	490 00

#### (A) audio-technica always listening...

AUDIO-TECHNICA UNIPOINT BOUNDARY MICS UniPoint boundary condenser mics feature superior off-axis rejection and maximum gain-before-feedback, on- and off-axis response, 80Hz filter which reduces pickup of unwanted low-frequency ambient noise, and a heavy die-cast case with non-slip bottom pads. UniGuard® technology offers unsurpassed immunity from radio

frequency interference. PivotPoint® provides a unique rotating output connector that allows the cable to exit form either the back or the bottom of the microphone (except for U841A). The U891R, U891RW, and U891RC boundary mics are equipped with programmable switches and LED status indicators.

ITEM	DESCRIPTION	PRICE
U841A	. Omni-directional with battery or phantom power	. 222.62
U851A	. Cardioid with battery or phantom power	. 233.74
U851R	. Cardioid with phantom power only	. 184.78
U851RW	. Same as U851R with white finish	. 184.78
U891RX	. Cardioid with phantom power, touch-sensitive	
	3-position built-in switch	. 228.18
U891RWX	. Same as U891RX with white finish	. 228.18
U891RCX	. Same as U891RX with provision for local or remote switching	. 250.44

#### **AUDIO-TECHNICA PRO42/PRO44 CARDIOID CONDENSER BOUNDARY MICROPHONES**

Both these mics feature a low-profile design for limited visibility, half-cardioid polar pattern, wide-range condenser element with low-mass diaphragm, 25' cable, and self-contained electronics. The PRO 42 is miniature-sized for minimum visibility



The TRO 42 is initiature-sized for initinitially visibility.					
ITEM	DESCRIPTION	PRICE			
PR042	. Miniature boundary mic, 70Hz-14kHz,				
	25ft permanently-attached cable	92.97			
PR044	. Boundary mic, 70Hz-16kHz, 25ft detachable cable	. 99.79			



AUDIX M70 FLUSH MOUNT CEILING MIC An innovative flush mount condenser microphone designed for distance miking. Featuring a fully integrated preamp, extremely high sensitivity rating of 37 millivolts (@1k 37 mV/Pa), and a small footprint of only 3 inches in diameter. Applications include ceiling mount for videoconferencing, distance learning, hospital rooms, surveillance, and ambient room miking. The capsule is housed within a proprietary machined cradle that enables the microphone to be aimed and focused up to an angle of 45 degrees towards the source. Complete immunity from RF interference caused by cell phones and GSM devices. Terminates in a Phoenix connector and easy to install, requiring only a 2 inch drilled hole. Available in stock white or satin nickel finish.


NEW!

ITEM	DESCRIPTION	PRICE
M70	Flush mount ceiling mic, 2ft cable, phoenix connecter	490.00
JBM70	Metal safety junction box to house connecters and plenum ca	ble 19.50

## beyerdynamic))

#### BEYERDYNAMIC CLASSIS BOUNDARY INSTALLATION **MICROPHONES** These condenser boundary microphones are designed for flush mounting into tabletops or ceilings, and

applications such as teleconferencing, videoconferencing, recording or amplification of round table discussions - wherever the microphone needs to be as unobtrusive as possible.



ITEM	DESCRIPTION	PRICE
BM32-B	Half-cardioid, 50Hz-18kHz, black	100.37
BM32-SE	Same as BM32B but silver metallic	100.37
BM32-W	Same as BM32B but white	111.51
BM33-B	Half-spherical, 50Hz-20kHz, black	108.15
BM33-SE	Same as BM33B but silver metallic	108.15
BM33-W	Same as BM33B but white	108.15
BM34-B	Half-cardioid, 150Hz-18kHz w/bass roll-off filter, black	100.37
BM34-SE	Same as BM34B but silver metallic	100.37
BM34-W	Same as BM34B but white	100.37



#### CAD BOUNDARY MICS The

220VP and 2220VP are continuously variable polar pattern, buttonstyle, condenser boundary mics,

designed for surface installation. These mics are made to resist interference from cell phones and RF devices. The 80Hz, 12dB/octave high-pass filter removes unwanted low-frequency energy to improve intelligibility. The mics are terminated with a standard 3-pin XLRM-type connector recessed in the body of the mic. The 2220VP has remote polar control through a Digital Signal Processor (DSP).



	U	0	U			,	
ITEM	DESCRIPT	ON					PRICE
220VP	.Boundary i	nic, 90Hz	-17kHz	, 120ohms,	blac	k	239.00
220VPW	.As above b	ut white					239.00
2220VP	.Boundary i	nic, 90Hz	-17kHz	, 120ohms,	DSP	compatible, blac	k 499.00
2220VPW	.As above b	ut white					499.00

CAD 930VPL CONTINUOUSLY VARIABLE POLAR PATTERN **BOUNDARY MICROPHONE** A condenser boundary microphone with a programmable membrane switch, LED and logic interface. Resists interference from devices (cell phones, etc), and includes an integral 80Hz, 12dB/octave hi-pass filter. The dual outputconnector design allows the cable to exit the rear or the underside of the microphone. It comes with 30ft of detachable cable, terminated with a 3-pin XLRM-type connector, and features logic I/O functions for use with automatic mixers, teleconferencing systems and control systems.

ITEM	DESCRIPTION	PRICE
930VPL	Boundary mic, continuously variable-polar pattern, 40Hz-15kHz	299.00







PCC-160 Surface-mounted, supercardioid condenser mic intended for stage floors, lecterns, conference tables, and



news desks. Features excellent gain-before-feedback, room noise and rear sound rejection. Surface mounting results in a "half-supercardioid" polar pattern with increased directivity and sensitivity. The low profile and black finish make the PCC160 almost invisible in most applications. Phantom power only.

ITEM	DESCRIPTION	PRICE
PCC160	Supercardioid microphone, black	449.00

**CROWN PZM10 LOW PROFILE MICROPHONES** Features a cylindrical design for ceiling, wall or tabletop installations. Intelligibility is excellent, with low frequencies below the voice range rolled off to reduce the pickup of HVAC rumble. It has an XLR connector and is phantom powered. The PZM-10LL has line-level output featuring pigtail connectors and is powered by 12-14V DC (not phantom power).




ITEM	DESCRIPTION	PRICE
PZM10	Low profile mic, 80Hz-20kHz, -52dBm/Pa,	
	12-48V phantom powered	149.00
PZM10LL	Line level version, 100Hz- 20kHz, +8dBm/Pa,	
	12-14VDC powered	179.00

CROWN PZM-11 This low-cost microphone mounts on a standard wall plate, for surveillance and conference room applications. It resembles a light switch rather than a microphone. Electronics on the rear of the plate offer screw terminals, eliminating the need



for connectors. Powering is via 12-48V phantom power. The PZM-11LL features line-level output and is powered by 24VAC, 12-24VDC, or phantom power. The PZM-11LLWR is the weather-resistant version.

ITEM	DESCRIPTION	PRICE
PZM11	. Boundary mic, phantom required	. 109.00
PZM11LL	Line level boundary mic	. 139.00
	. Weather-resistant, line level boundary mic	





30D has integral XLR output connector, the PZM-6D has hard wire output. Both have flat or rising response switchable. Phantom power only.

ITEM	DESCRIPTION	PRICE
PZM30D	Boundary microphone, XLR output	349.00
PZM6D	Boundary microphone, hard-wired output	349.00

**CROWN PZM-185** An inexpensive version of the PZM-30 and PZM6 with XLR output, can be phantom or battery powered.

ITEM	DESCRIPTION	PRICE
PZM185	Microphone	199.00




IIEM	PRICE
SOUND-GRABBER-II	79.00



#### **SENNHEISER**

SENNHEISER E900 SERIES HALF-CARDIOID BOUNDARY

MICROPHONES Pre-polarized condenser microphones with a halfcardioid pickup pattern and internal preamp electronics in rugged low-profile housings. The e901 is especially well-suited for kick drum and grand piano. The e912 is designed for picking up speech, vocals



ITEM	DESCRIPTION	PRICE
E901	Boundary mic for kick drum or grand piano	239.95
E912	Boundary mic for speech and acoustic instruments, I	ok or wh 299.95

#### SHURE

#### SHURE BETA91A HALF-CARDIOID CONDENSER MIC

Designed for use with kick drums, as well as other low-frequency applications including piano. It features an updated microphone capsule, integrated preamp, XLR connection and a 20Hz-20kHz frequency response. The Beta 91A combines superior attack and punch for studio-quality sound, even at extremely high sound pressure levels (SPL). A 2-position contour switch maximizes attack and clarity depending on application; flat response for



natural sound, or low-mid scoop for a strong low-frequency punch with ample higher frequency attack. Requires no external mounting or accessories.

ITEM	DESCRIPTION	PRICE
BETA91A	Half-cardioid condenser kick-drum mic	239.00

#### SHURE MX391 MINIATURE CONDENSER BOUNDARY MICS


The low-profile design of the MX393 at half the size! The smooth, widefrequency response and high sensitivity are perfect for boardrooms, houses of worship and courtrooms. Other features include interchangeable capsules, dent-resistant steel grilles, mounting holes, bottom cable exit and attached 12' cable and preamp. Also available in a white finish.



ITEM	DESCRIPTION	PRICE
MX391/C	.Cardioid, detachable preamp w/XLR, requires phantom power	156.43
MX391/S	Supercardioid, detachable preamp w/XLR, requires phantom power	161.93
MX391/0	.Omni-directional, detachable preamp w/XLR, requires phantom power.	144.32

#### SHURE MICROFLEX BOUNDARY

MICS Perfect for altars, boardrooms and distance learning centers. Features programmable, silent membrane switches, logic inputs/outputs and LED indicators. Like all microflex



models, 3 interchangeable condenser cartridges are available. The MX393s feature a 10' tiny QG-to-XLR cable, a paint mask, skid-resistant feet and a keyhole slot for rigid mounting. The MX690 has an integrated wireless transmitter, programmable mute, bi-color status indicator, requires SLX4 or SLX4L receiver.

ITEM	DESCRIPTION	PRICE
	. Cardioid with XLR cable	197.18
MX393/S	. Super-cardioid with XLR cable	203.80
MX393/0	Omni-directional with XLR cable	186.17
MX690	Wireless boundary microphone cardioid condenser	451.07

SHURE MX395 LOW PROFILE BOUNDARY MICS Perfect for meeting rooms, these microphones deliver exceptional sound pickup while barely being noticed. Choose from a selection of colors and pickup patterns for customized table installations. They feature logic inputs for remote LED control, bi-color status indicators, a wide dynamic range and smooth frequency response, and are only 1.25" in diameter.



#### SHURE MX396 MULTI-ELEMENT BOUNDARY

MIC These mics come in 2-or 3-element configurations, combining the coverage of multiple microphones into one compact package. They feature end of table (300°), center of table (360°), or cross table (bi-directional) coverage patterns, individual control of each element, bi-color status indicator, programmable mute switch, back or bottom exit cable, logic input/output



for remote LED and mute control. The MX396C/Dual features a 0-180° dual element while the MX396C/TRI features a 90-0-90° tri-element adjustable to 120-120-120°.

ITEM	DESCRIPTION	PRICE
MX396/C-DUAL	Cardioid boundary dual-element	340.39
MX396/C-TR	Cardioid boundary tri-element	417.50
























































COMPUTER AV

LIGHTS

min ACCESSORIES







	out the manner of other elected comigan	ation
ITEM	DESCRIPTION	PRICE
CHM99-BLACK	Cardioid, 70Hz-18kHz, matte black	149.00
CHM99-WHITE	As above, except white	149.00





1600VF

fully integrated preamp designed with very high sensitivity for distance miking. Applications include ceiling mounted video conferencing, distance learning, hospital rooms, surveillance, and ambient room miking. It has complete immunity from RF interference caused by cell phones and GSM devices. Comes with a cardioid capsule and is also available with hypercardioid or shotgun capsules (call for specific models), allowing the mic the ability to be used in a wide variety of applications. The cable assembly is equipped with a Phoenix connector.

• •		
ITEM	DESCRIPTION	PRICE
M40W-6	6" mini cardioid condenser ceiling mic	375.00
M40W-12	12" mini cardioid condenser ceiling mic	375.00
JBM40	Metal safety junction box to house	4
	connectors and plenum rated cable	19 50



**CAD VARIABLE PATTERN CONDENSER** OVERHEAD MICS The continuously variable polar pattern of these mics can be changed with the remote control and allows

the user to precisely adjust the shape of the pick-up pattern for the best performance from a remote location. Utilizing a 2-conductor shielded cable between the mic head and the pattern box, the user can adjust the polar pattern in real time w/o changing capsules or mic positions. Both models include rackmountable remote box. The 2600VP and 2700VP are both controlled through a Digital Signal Processor (DSP).

		. ,
ITEM	DESCRIPTION	PRICE
1600VP	Hanging condenser mic, variable pattern, 40Hz-20kHz, w/ 30' cable	
	terminated to TA3F and XLR-M, steel hanger, remote box	. 499.00
1700VP	As above, but includes MB-1 mini boom in place of steel hanger	. 599.00
MB-1	Carbon fiber 56" mini boom, fits standard 5/8" thread mic post	84.68
2600VP	Hanging condenser mic, variable pattern, 40-200kHz, w/ 30' cable	
	terminated to TA3F and XLR-M, steel hanger, DSP compatible	. 499.00
2700VP	As above, but includes MB-1 mini boom w/ clutch rotation	
	in place of steel hanger DSP compatible	599 00



from the audience, musicians, and monitor speakers. The coverage pattern reduces the number of mics necessary to capture the whole choir. These tiny, lightweight mics are easy to replace, position and control. Supplied with windscreen, cable spool, stiffener for hanging and phantom-powered preamp.

TEM	DESCRIPTION			PRICE
M2HP4FF50B/ISOMAX-2.	Hypercardioid,	40Hz-18kHz, w/50'	cable, black	193.36
M2HP4FF50W/ISOMAX-2	Hypercardioid,	40Hz-18kHz, w/50'	cable, white	193.36

**EV RE92H HANGING CHOIR MICROPHONES Miniature** electret condenser microphones for applications where the mic needs to be suspended from above the sound source. Ideal for theatre, houses of worship, or anywhere a mic needs to be heard, not seen. Both include an in-line electronics module, 12dB/octave switchable hipass filter and 25' of cable. Both require 24-52V phantom powering.

ITEM	DESCRIPTION	PRICE
RE92H	Cardioid hanging mic, 40Hz-20kHz, 135dB SPL (1%THD), black	. 335.00
RE92HW	Cardioid hanging mic, 40Hz-20kHz, 135dB SPL (1%THD), white	. 335.00

#### SHURE

SHURE MICROFLEX OVERHEAD MICS These mini-condenser overhead mics are perfect for choirs and stages. Comes with in-line or plate-mount preamps, with choice of one interchangeable condender mic cartridge. Also includes: 4" gooseneck with 30' cable, snap fit windscreen. Available in black or white.

ITEM		PRICE
Models with	in-line preamps	
MX202B/C	Cardioid, black finish	160.52
MX202B/S	Supercardioid, black finish	166.18
MX202W/C	Cardioid, white finish	160.52
MX202W/S	Supercardioid, white finish	166.18
Models with	1-gang wall plate type preamp	
MX202BP/C	Cardioid, black finish	160.52
MX202BP/S	Supercardioid, black finish	166.18
MX202WP/C	Cardioid, white finish	160.52
	Supercardioid, white finish	



AUDIO-TECHNICA PRO45 PROPOINT HANGING MIC A widerange condenser cardioid hanging mic with a 25' cable terminated in an XLR connector. Phantom powering from 9-52V is required. Ideal for choirs and theatre. A foam windscreen and wire hanger are standard. Response from 70Hz-16kHz.

ITEM	DESCRIPTION	PRICE
PR045	Cardioid condenser microphone	99.79
AT8153	Replacement foam windscreen	7.62
AT8451	Replacement steel hanger	9.98

AUDIO-TECHNICA UNIPOINT HANGING MICS Cardioid condenser hanging mics featuring UniGuard<sup>TM</sup> technology and offering unsurpassed immunity from radio frequency interference. An 80Hz UniSteep® filter reduces pickup of low-frequency ambient noise. Interchangeable elements offer superior on- and off-axis response, resulting in truly exceptional sonic quality and a choice of angle of acceptance.

ITEM	DESCRIPTION	PRICE
U853A	. Cardioid, uses battery/phantom power	209.26
U853AU	. Same as U853A with 90° pickup pattern	242.65
U853AW	. Same as U853A with white finish	209.26
U853AWU	. Same as U853A with 90° pickup pattern, white	232.63
U853PM	. Cardioid, uses phantom with wall/ceiling plate	173.64
U853PMU	. Same as U853PM with 90° pickup pattern	195.90
U853PMW	. Same as U853PM with white finish	173.64
	. Same as U853PM with 90° pickup pattern, white	
	. Cardioid, uses phantom power	
	. Same as U853R with 90° pickup pattern	
U853RW	. Same as U853R with white finish	173.64
U853RWU	. Same as U853R with 90° pickup pattern, white	205.92
	. Cardioid element, 120° pickup pattern	
UE-H	. Hyper-cardioid element, 100° pickup pattern	73.69
	. Omni-directional element, 360° pickup pattern	
UE-UL	. UniLine element, 90° pickup pattern	103.41

AUDIX ADX 40 SERIES HANGING MICROPHONES A miniature condenser microphone for overhead hanging applications, with a smooth uniform response of 40Hz-20kHz for full rich sound. It is machined from solid brass and is available in non-reflective black or white, and in a cardioid or hypercardioid pick-up pattern. Has an attached 30' cable, and operates on 9-53V phantom power with the preamp module APS-910.

ITEM	DESCRIPTION	PRICE
ADX40	Hanging cardioid mic, black	209.00
ADX40W	Hanging cardioid mic, white	219.00
ADX40-HC	Hanging hypercardioid mic, black	219.00
ADX40W-HC	Hanging hypercardioid mic, white	239.00
	Dhanton nouser prooms modulo	

.... Phantom power preamp module.. AUDIX M1255 MICRO SERIES HIGH-OUTPUT HANGING MICS

A miniature condenser mic with an integrated preamp and detachable cable. With unmatched high-output and extremely low-noise electronics, it's the perfect choice for choir, ceiling and recording from a distance. It has great RFI immunity and natural hi-pass filter frequency response of 80Hz-20kHz. Available in black or white as well as a choice of pick up patterns.

ITEM	DESCRIPTION	PRICE
M1255B	High-output hanging cardioid mic, black finish	409.00
M1255BW	Cardioid mic, white finish	429.00
M1255B-HC	Hypercardioid mic, black finish	429.00
M1255BW-HC	Hypercardioid mic, white finish	449.00
M1255B-0	Omni-directional mic, black finish	409.00
M1255BW-0	Omni-directional mic, white finish	429.00
M1255B-S	Supercardioid (mini-shotgun) mic, black finish	449.00
MC-HANGER	Hanging clin transparent	19 95









#### **AKG 99ER SERIES GOOSENECK MICROPHONES**

These goosenecks come with only one flexible section. a rigid connection between gooseneck and capsule and a 3-pin standard XLR connector. The metal grill is joined

permanently to the gooseneck, and the contacts inside are soldered. This protects the condenser capsule against mechanical stress and electromagnetic interference, and ensures maximum reliability and excellent audio. You can choose between 12" or 20" long goosenecks, with either a cardioid or hypercardioid polar pattern.

ITEM	DESCRIPTION	PRICE
CGN99C/S	. 12" cardioid gooseneck, 70Hz-18kHz	. 149.00
CGN99C/L	. 20" cardioid gooseneck, 70Hz-18kHz	. 149.00
CGN99H/S	. 12" hypercardioid, 50Hz-19kHz	. 149.00
CGN99H/L	. 20" hypercardioid, 50Hz-19kHz	. 149.00



CAD GOOSENECK MIC The Astatic 920B is a low-noise, cardioid, condenser gooseneck mic that provides natural, artic-

ulate and transparent sound. The cardioid polar pattern minimizes feedback when used close to sound reinforcement speaker and monitors Has durable matte-black non-reflective paint. Foam windscreen included.

ITEM	DESCRIPTION	PRICE
920B	Cardioid gooseneck mic, 150Hz-20kHz, 20-7/16" long	129.00
GSM1	Shockmount for 920B	. 52.52
FM-1A	Flange w/3-pin XLRF stem mount	. 20.37
	Locking flange mount w/3-pin XLRF	









































## ${\mathbin{igspace}}$ audio-technica ${\mathbin{f .}}$

always listening...

AUDIO-TECHNICA PROPOINT GOOSENECK MICS All models operate only from 9-52V of phantom power. Four models in two different lengths and two mounting styles. The PRO47 has a 5/8" thread mount and a 9' cable terminated with an XLR connector.

ITEM	DESCRIPTION	PRICE
PR047T	12.4" thread mount	124.73
PR047TL	15.8" thread mount	124.73
PR049Q	13" quick XLR mount	112.26
PR049QL	16.4" quick XLR mount	112.26
	Replacement foam windscreen	

AUDIO-TECHNICA UNIPOINT GOOSENECK MICS Cardioid condenser gooseneck mics with UniGuard<sup>TM</sup> technology (except U855QL/ U859QL). Unsurpassed immunity from radio frequency interference, and 80Hz UniSteep® filter that reduces pickup of unwanted low-frequency ambient noise. New interchangeable elements (hypercardioid, cardioid, omnidirectional and super-directional UniLine® line cardioid) offer an angle of acceptance from 90° through 360° and superior on- and off-axis response for exceptional sonic quality. A 2-stage foam windscreen yields outstanding resistance to plosives and other breath noises. The U855QL is a cardioid talk-back, paging & dispatch cardioid dynamic gooseneck mic. Interchangeable elements are for U857 mics only.

ITEM	DESCRIPTION PRICE
U855QL	. 17.64" cardioid, XLR mount, w/o UniGuard™ 85.71
	. 16.58" cardioid, 5/8" mount, uses phantom
	or battery power, includes power module,
	windscreen, flange and pass-through adapter 238.19
U857AU	. 16.81" UniLine® line-cardioid, 5/8" mount,
	uses phantom or battery power, includes power
	module, windscreen, flange, pass-through adapter270.47
118570	. 14.47" cardioid, XLR mount,
00074	includes foam windscreen and shockmount 197.03
1185701	As above but 18.94"
	. 19.17" UniLine® line-cardioid, XLR mount,
	includes foam windscreen and shockmount 224.84
118570111	As above but 23.74"
	. 16.58" cardioid, 5/8" mount,
	includes power module, foam windscreen,
	flange and pass-through adapter201.46
II857RII	. 16.81" UniLin® line-cardioid, 5/8" mount,
	includes power module, foam windscreen,
	flange and pass-through adapter233.74
II857RI II	As above but 21.38"
	. 18.90" cardioid, XLR mount, phantom only,
	w/o UniGuard™, includes windscreen140.25
IIF-C	Cardioid element, 120° pickup pattern73.69
	Hypercardioid element, 100° pickup pattern
	Omnidirectional element, 360° pickup pattern73.69
	UniLine® element, 90° pickup pattern103.41
JL	. c E C.

AUDIO-TECHNICA AT808G SUBCARDIOID DYNAMIC CONSOLE MICROPHONE A quality talk-back microphone for entertainment, commercial and industrial applications which features a versatile gooseneck for unlimited positioning. Custom-tailored frequency response ensures excellent intelligibility in environments with excessive ambient noise.

ITEM	DESCRIPTION	PRICE
AT808G	Dynamic, subcardioid, 200Hz-5kHz, 3-pin XLR	130.31

#### CAD VARIABLE PATTERN GOOSNECK MICS

The 1800VP is a continuously-variable pattern condenser 18" gooseneck mic system with a remote polar control which allows the user to precisely adjust the shape of the pick-up pattern from a remote location. A 2-conductor shielded cable (max length 2000') connects the mic head and the pattern control box. The mic is designed to resist interference from cell phones and other communication devices. The 2800VP has the same features but has remote polar control through a Digital Signal Processor (DSP). Both mics are terminated with a TA3F type connector and XLRM-type connector.

ITEM	DESCRIPTION	PRICE
1800VP	18" gooseneck, 40Hz-20kHz, includes remote polar control box.	. 549.00
2800VP	18" gooseneck, 40Hz-20kHz, DSP compatible,	
	includes 30' shielded cable	. 549.00

#### COUNTRYMAN ISOMAX 4 RF GOOSENECK MICS

The lowest noise podium mic features improved RF rejection of interference from cell phones, wireless devices, and active noise cancellation to eliminate mechanical noise from either touching

the mic or the surface it is attached to. The base is a standard XLR male connector, the output is balanced transformerless, a minimum of 9VDC phantom power is required. The matte black extension tube may be bent repeatedly.

ITEM	DESCRIPTION	PRICE
M4HP5RF18EB/ISOMAX	<b>1-4</b> 18" Isomax 4RF mic, hypercardioid,	
	70Hz-18kHz, black	289.10
M4HP5RF24EB	24" Isomax 4RF mic, hypercardioid,	
	70Hz-18kHz, black	289.10
M4CP5RF18EB/ISOMAX	<b>I-4</b> 18" Isomax 4RF mic, cardioid,	
	70Hz-18kHz, black	289.10
M4CP5RF24EB/ISOMAX	<b>I-4</b> 24" Isomax 4RF mic, cardioid,	
	70Hz-18kHz, black	289.10
A4STAND	Isomax 4RF stand clip	20.73
A4CDM	Isomax 4RF desk mount	20.73
A4WSB	Replacement windscreen, black	13.03

# **Earthworks**

**EARTHWORKS FLEX SERIES PODIUM MICROPHONES These** offer exceptional intelligibility, impressive impulse response, diaphragm settling time and sound quality that is not usually available in podium microphones. Their patented cardioid and hypercardioid pick-up pattern and smooth off-axis response allows an orator to move up to 90° off-axis and still be heard with exceptional intelligibility and with more gain before feedback. The flexible neck allows adjustment of microphone positioning with no handling noise. Flex Mics are intended for podium use, but they can also be used as choir or orchestra mics (when hung) and for vocals, piano, acoustic instruments and even drums. They are flat from 50Hz-20kHz within + 2dB at 6" and will handle up to 145dB SPL.

ITEM DESC	CRIPTION	PRICE
FM72027" (	cardioid	499.00
FMR72027" (	cardioid w/rigid center and flex on both ends	559.00
FM720/HC27"	hypercardioid	499.00
FMR720/HC27"	hypercardioid w/rigid center and flex on both ends	559.00
FM50019" (	cardioid	499.00
FMR50019" (	cardioid w/rigid center and flex on both ends	549.00
FM500/HC19"	hypercardioid	499.00
FMR500/HC19"	hypercardioid w/rigid center and flex on both ends	549.00
FM36013"	cardioid	499.00
FM360HC13"	hypercardioid	499.00



















































**EV POLARCHOICE GOOSENECK PODIUM MIC Easily** select from 4 polar pattern choices (omni, cardioid, supercardioid & hypercardioid). Available in 12- or 18-inch lengths,

and XLR, flange mount, or PolarChoice Plus which features a push button on top of the mount and status LED.

ITEM	DESCRIPTION	PRICE
PC12/FL	12" multi-pattern gooseneck mic, flushmount	356.00
PC12/XLR	12" multi-pattern gooseneck mic, XLR-mount	336.00
PC18/FL	18" multi-pattern gooseneck mic, flushmount	356.00
PC18/XLR	18" multi-pattern gooseneck mic, XLR-mount	336.00
PC-PLUS-12	12" multi-pattern w/base switch & LED	402.00
PC-PLUS-18	18" multi-pattern w/base switch & LED	402.00

EV RE90P ARCHITECTURAL PODIUM MIC The RE90P is an unobtrusive podium microphone designed to pickup sounds distant or near. Dual gooseneck points allow for quick and reliable microphone positioning. Available in 12" or 18" length.

ITEM	DESCRIPTION	PRICE
RE90P-12	12" length, cardioid	282.00
RE90P-18	18" length, cardioid	282.00
CPSM	Shockmount hardware	33.00

POLAR CHOICE SATELLITE WIRELESS PODIUM MICROPHONE The PolarChoice Satellite brings the benefits of wireless to the podium. It is a freestanding gooseneck style microphone, firmly anchored in place by its base. This low-profile foundation hides PolarChoice Satellite's most powerful feature - space for a wireless transmitter. Turn the base over to reveal the specially designed compartment for housing a required Electro-Voice bodypack transmitter (sold separately). Connect the microphone to the bodypack, set up the wireless channel, and place the PC Satellite anywhere an easy-to-use microphone is required. It features switchable polar patterns, mute switch, and is available in 3 length options.

ITEM	DESCRIPTION	PRICE
PC-SATELLITE-5	5" wireless condenser gooseneck mic, 50Hz-20kHz	.529.00
PC-SATELLITE-12	12" wireless condenser gooseneck mic, 50Hz-20kHz	.529.00
PC-SATELLITE-18	18" wireless condenser gooseneck mic, 50Hz-20kHz	. 529.00
BPU-2-71887X1	RE2 series UHF bodypack transmitter, A-band	. 199.00
RE2-71883X1	RE2 series UHF receiver, A-band	.299.00

#### **SAMSON**

SAMSON CM SERIES GOOSENECK MICS These mics feature miniature cardioid condenser elements, XLR-M connectors at their base, onboard high-pass filter at 100Hz, a dual-stage, rippled windscreen, and they function on 9-52V phantom power. They include a FMS1standard flange mount for installation, and a WS15 windscreen.

ITEM	DESCRIPTION	PRICE
CM15P	15" cardioid condenser, 60Hz-16kHz, 127	7dB SPL, black89.00
CM20P	20" cardioid condenser, 60Hz-16kHz, 127	7dB SPL. black99.00

## SHURE

SHURE 515SB-G18X All metal impact resistant screen/grille provides extra ruggedness. Momentary push to talk switch makes this the standard gooseneck microphone for the fast-food industry and applications such as supermarkets, etc. Includes 18" gooseneck/ flange mount.

ITEM	DESCRIPTION		PRICE
515BSM	. With cable, push-to-talk	switch, low	
	impedance, for handheld	l use	101.74
515SB-GX	. With push-to-talk switch	, low	
	impedance, gooseneck n	ot included	64.44
515SB-G18X	. 18-inch gooseneck, pus	h-to-talk	
	switch, low impedance, v	with A13HD flange	79.13
515SB-G18XF	. 18-inch gooseneck, push	ı-to-talk	
	switch, low impedance, v	with A12 flange	75.74
515SDX	. Dual-impedance, switch	selectable,	
	for handheld use, no cab	ıle	48.61
Δ1WS	Foam windscreen (gray)		6.33

SHURE MX405/MX410/MX415 MINIATURE GOOSENECK MICS

These models are available in 5", 10" or 15" desktop, mounted base, wired, or wireless versions, with interchangeable capsule options. Desktop models have a programmable mute switch. CommShield<sup>TM</sup> technology ensures the MX models to be highly resistant to intense nearby radio signals. The MX890 desktop base allows you to interface these mics with compatible Shure SLX wireless systems.

ITEM	DESCRIPTION	PRICE
MX405/C	5" cardioid, bi-color indicator, w/surface mount preamp	. 223.83
MX405/S	5" supercardioid, bi-color indicator, w/surface mount preamp	. 229.49
MX405R/N	5", no cartridge, light ring indicator, w/surface mount preamp	. 186.54
MX405LP/C	5" cardioid, bi-color indicator, less preamp	. 167.31
MX405LP/S	5" supercardioid, bi-color indicator, less preamp	. 172.97
MX405RLP/N	5", no cartridge, light ring indicator, less preamp	. 130.00
MX410/C	10" cardioid, bi-color indicator, w/surface mount preamp	. 223.83
MX410/S	10" supercardioid, bi-color indicator, w/surface mount preamp	. 229.49
MX410R/N	10", no cartridge, light ring indicator, w/surface mount preamp	. 186.54
MX410LP/C	10" cardioid, bi-color indicator, less preamp	. 167.31
MX410LP/S	10" supercardioid, bi-color status indicator, less preamp	. 172.97
MX410RLP/N	10", no cartridge, light ring indicator, less preamp	. 130.00
MX415/C	15" cardioid gooseneck, includes surface mount preamp,	
	bi-color status indicator	. 235.13
MX415/S	15" supercardioid gooseneck, includes surface mount preamp,	
	bi-color status indicator	. 240.79
	15" cardioid gooseneck, less preamp, bi-color status indicator	. 178.61
MX415LP/S	15" supercardioid gooseneck, less preamp,	
	bi-color status indicator	. 184.27
MX415R/N	15" no mic cartridge, gooseneck,	
	includes surface mount preamp, light ring	
	15" no mic cartridge, gooseneck, less preamp, light ring	
	Desktop base for MX405 & MX410 models	
	Wireless desktop base, compatible with SLX series	
	Surface mount preamp for MX405 & MX410 models	
	UHF bodypack option for MX890 base only (specify band)	
SLX4	UHF receiver option for MX890 base only (specify band)	. 380.00

SHURE MICROFLEX GOOSENECK MICROPHONES Ideal for lectern, pulpits and conference tables. These mini-condenser gooseneck mics offer a variety of heights and mounting styles, high sensitivity and wide frequency range. The new D versions include a desktop base with built in programmable switching capability. Other features include: interchangeable cardioid, supercardioid and omnidirectional mic cartridges, a rigid center tube for easy positioning and transformerless output for maximum immunity to electromagnetic hum and RF interference even over long cable runs.

ITEM	DESCRIPTION	PRICE
Models with XLR a	t bottom, no cable	
MX412/C	. 12" cardioid	178.61
	. 12" super cardioid	
	. 12" supercardioid with switch and LED	
MX418/C	. 18" cardioid	178.61
MX418/S	. 18" supercardioid	184.27
Models with 10ft.	cable	
MX412D/C	. 12" cardioid, desktop base	237.40
MX412D/S	. 12" supercardioid, desktop base	243.05
MX412SE/C	. 12" cardioid, side exit cable	191.06
MX412SE/S	. 12" supercardioid with side exit cable	196.70
A412MWS	Locking metal windscreen	17.91
A400SM	Shockmount systems	22.61
RK100PK	In-line preamp	113.38
RK412WS	Snap-fit windscreen (4-pack)	18.53
A412B	Desktop microphone base	63.37
R183	Omni replacement cartridge	32.54
R184	Supercardioid replacement cartridge	52.57
R185	Cardioid replacement cartridge	45.06

SHURE 503BG DYNAMIC GOOSENECK MIC Developed for computer voice recognition applications, this microphone offers excellent voice fidelity while reducing background noise. Also useful in other close-talking applications such as paging and talkback. It has a low-impedance, moving coil transducer with an integral humbucking coil and attached 2-conductor shielded cable with built-in strain relief. It has a frequency response of 100Hz-7kHz with constant output voltage over the voice spectrum when used close to the sound source. It has a black finish and mounts to a gooseneck (not included), a fixed pipe or a microphone stand using a standard 5/8"-27 thread.

ITEM	DESCRIPTION	PRICE
503BG	Cardioid dynamic mic, for gooseneck mounting	84.78
G27B	27" gooseneck, black	19.79
G18	18" gooseneck, chrome	16.00





Follow us!



Combining sleek, low profile aesthetics and a comprehensive selection, Microflex® microphones include the highest standard of quality and efficiency for installed audio applications. Developed primarily for AV conferencing installations, these models were designed with your needs in mind:

- · Wired and Wireless functionality for unprecedented placement flexibility
- · Low profile button, gooseneck and boundary models to fit any room aesthetic
- CommShield® Technology for RF Filtering against GSM devices
- · Legendary Shure performance and reliability

Look to Microflex for your next microphone installation, with the confidence of the superior sound quality, reliability and durability you only get from Shure.





SHURE

LEGENDARY
PERFORMANCE\*\*

© 2011 Shure Incorporated

















































**BOGEN DDU250 DYNAMIC DESKTOP MICROPHONE** Compact desktop microphone with gooseneck. Excellent speech and intelligibility to cut through the noisy backgrounds of live situations and large gatherings. Features a push-to-talk switch, push-to-lock switch, hard-wired 10ft cable (5-conductor), and wire-mesh wind filter. Table stand with on/off switch.

ITEM DESCRIPTION PRICE DDU250 Cardioid, 100Hz-12kHz

BOGEN MBS1000A DESKTOP PAGING MICROPHONE This dualimpedance desktop microphone uses a simple push-to-talk bar (lockable) or lift-to-talk operation (defeatable) for activating the microphone and any external equipment. Features 7ft of 4-conductor shielded cable, an

an impedance sele	ector switch, and 4 molded non-skid feet.	
ITEM	DESCRIPTION	PRICE
MBS1000A	Cardioid mic, dynamic, 45Hz-15kHz	137.20

#### SHURE

SHURE 104C INDOOR/OUTDOOR COMMUNICATION MICROPHONE A small, pressure actuated, diaphragmtype, carbon microphone that fits comfortably in the hand. Features include a heavy-duty PTT switch, a high impact ARMO-DUR case, and a long life, rubber-jacketed coil cord cable and frequency response of 300Hz – 4kHz specifically

for voice communications. Recommended for all types of outdoor/indoor communication activity, such as mobile and fixed station use, police, fire, utility, forestry and transportation services, industrial applications, and public address.

ITEM	DESCRIPTION	PRICE
104C	. Indoor/outdoor communication microphone	67.83

SHURE 596LB OMNI HANDHELD DYNAMIC PUSH-TALK MIC

A compact, handheld low-impedance communications mic with a 200Hz-5kHz frequency response. An economical mic compatible with many popular paging amplifier inputs and its tailored frequency response provides clear, intelligible operation. Fits comfortably in the palm of the hand and has a long-life push-to-talk switch, and a durable coiled cable (5ft) for years of reliable performance.

ITEM	DESCRIPTION	PRICE
596LB	. Omnidirectional handheld push-talk mic	39.56

SHURE 514B HANDHELD MIC W/ SWITCH A low impedance, dynamic, handheld microphone designed for paging and public address systems. It offers clear, natural voice response and high intelligibility. It connects to microphone inputs rated at 19-300ohms. It can be used in applications that require long cable lengths, or where severe hum conditions are present. The 514B microphone is provided with a 4-conductor (2 shielded) coiled cable and a "Million-Cycle" leaf-type switch. It fits comfortably in the hand and is not affected by heat or humidity. The exclusive ARMO-DUR case resists mechanical shocks and vibration, and is impervious to oil, fumes, salt spray, ultraviolet radiation, and corrosion. It has a frequency response of 100Hz-6kHz and an output level of -36.5dB.

ITEM	DESCRIPTION	PRICE
514B	. Handheld microphone w/switch	56.52

SHURE 577B HANDHELD DYNAMIC MICROPHONE Designed for communications and paging applications that require highly intelligible, low noise output. The 577B represents a significant improvement over most microphones with anti-noise features. Shaped frequency response, directionality, and distant sound discrimination contribute to total noise reduction. A mounting bracket is supplied to provide convenient hang-up when the microphone is not in use. It has a frequency response of 100Hz-5kHz, and an output level of -66dBV/Pa (0.5mV). Other features include a rugged ARMO-DUR case, leaf-type push-to-talk switch, and a non-detachable 6ft Triple-Flex cable.

ITEM	DESCRIPTION	PRICE
577B	Handheld microphone w/push-to-talk switch	101.74
R98B	Replacement cartridge for 577B	80.99

#### SHURE

SHURE 450-II PAGING DISPATCH MIC Designed for high-speed intelligibility and reliable paging and dispatching. Features an omnidirectional pattern, low to high impedance switch, press to talk switch, sturdy high impact base, and an external relay or control circuit. Its frequency response of 200Hz-5kHz is tailored for optimum speech intelligibility. Includes case and 7ft cable.

ITEM	DESCRIPTION	PRICE
450-II	Desktop paging microphone, omnidirectional	101.74

SHURE 522 DESKTOP MICROPHONE Designed for radio communications, paging, and dispatching systems, this dynamic base station mic features a cardioid pattern that suppresses background noise. It also reduces feedback in public address paging applications, includes a press to talk switch, and external relay or control unit. Dual impedance (19 to 300 ohms or High). Frequency response 60Hz-11kHz. Sturdy high impact base. Includes case and 7' cable.

ITEM	DESCRIPTION	PRICE
522	Desktop paging microphone, cardioid	. 101.74

SHURE 527 SERIES HANDHELD MICROPHONES Extremely reliable dynamic microphones well suited for Ham radio, mobile FM transmission, and top quality paging systems. Omni-directional pattern, neoprene jacketed cord, million cycle leaf switch.

ITEM	DESCRIPTION	PRICE
527B	Low impedance 300Hz-5kHz response	62.17
527C	Built in amplifier – up to 100ft	
	unshielded cable, 300Hz-5kHz response	65.56

SHURE 550L OMNI-DIRECTIONAL DESKTOP MIC Get all the features and stay in budget! Tailored for natural intelligible voice response with a non-locking, million cycle plus leaf type, long-life PTT switch, this mic features a frequency response of 50Hz-6kHz, has a 220-ohm impedance, a recommended load of 1000ohms, and comes with a 2.1m (7ft), 4-conductor, 2-shielded coiled cord.

ITEM	DESCRIPTION	PRICE
550L	Omni desktop mic	63.24



#### PM660U DESKTOP PA/PAGING MICROPHONE

Ideal for use in restaurants, warehouses, transportation terminals, dispatch centers, or entertainment facilities. It features a cardioid pick-up pattern, 600 ohm balanced output, 8.2', four conductor cable with stripped wire ends. Conductors are shielded and are dedicated for the microphone signal. The other two unshielded conductors connect to an auxiliary, normally-open switch contact, used to acti-

vate external muting, priority or relay control circuits. The auxiliary switch contact is closed by using the push-to-talk bar, which also turns on the microphone by opening a second set of contacts that normally short the mic element. A locking lever is provided to keep the push-to-talk bar in the "on" position when the microphone must be kept open for an extended period.

ITEM	DESCRIPTION	PRICE
PM660U	. Paging mic, dynamic cardioid w/push-to-talk bar,	
	100Hz-10kHz	. 117.00

#### PM222U NOISE-CANCELLING PAGING MICROPHONE

The PM-222U is a noise-cancelling paging microphone designed for hand held applications with a push-to-talk switch that locks on for continued use. It has a 6.5" pig-tail cord with external control contacts and conductors as well as a mounting sleeve for wall mount storage. Includes mounting sleeve for wall-mounting. Unit carries a 5-year manufacturer's warranty.

ITEM	DESCRIPTION	PRICE
PM222U	Paging microphone w/lock-on push-to-talk switch, 100Hz-10kHz	52.50





#### A DESIGNS REDDI TUBE DIRECT

-BOX Ideal for basses, guitars, synths, and electronic instruments that require a direct box for recording. Features

include: vacuum tube design, level control, ground lift, Neutrik Combo input connectors, XLR outputs, zero feedback loop, custom wound output transformers, a 6NI-P tube, and a 1/4" through jack. It has a frequency response of 10Hz-60kHz.



ITEM	DESCRIPTION	PRICE
REDDI	Tube direct box	715 00

### ARTcessories\*

ART DI BOXES These all convert high-impedance inputs to 600-ohm balanced outputs and feature 1/4" TRS/XLR combo inputs, XLR outputs, switchable ground lift, and aluminum case. The X series are active and can be phantom or 9V battery powered, and DUAL-2 include switchable input attenuation (-30dB). The Z series are a passive transformer design, and feature switchable input attenuation (-20dB, -40dB), low pass filter and phase invert.



ITEM	DESCRIPTION	PRICE
X-DIRECT	. Single-channel active direct box	40.00
Z-DIRECT	. Single-channel passive direct box	25.00
DUAL-X-DIRECT	. Dual-channel active direct box	55.00
DUAL-Z-DIRECT	. Dual-channel passive direct box	40.00

AVALON 🕕 DESIGN

AVALON DESIGN **U**5 **INSTRUMENT DI** The U5 includes a variable gain Class "A" preamplifier, six passive EO curves, a high-cut switch, headphone



monitor amp and uses twin DC coupled Class "A" output amplifiers for direct to tape/ disc recording. Switched 3dB steps, a maximum gain of +30dB, 3,000,000-ohm unbalanced input, +24dBu unbalanced-400W speaker input, 2 x XLR outputs-+30dBu DC coupled, balanced 600ohms.

ITEM	DESCRIPTION	PRICE
U5	. Mono-instrument DI	585.00





BEHRINGER DI BOXES The DI100 allows direct connection of amplifier outputs with ratings of up to 3,000W, and features internal battery shut-off when phantom power is connected. The DI20 converts 2 unbalanced 1/4" inputs into 2 balanced XLR outputs. The DI400P/600P are single-channel transformer-coupled passive DI boxes with switchable ground lift.

ITEM	DESCRIPTION	PRICE
DI100-ULTRA-DI	. Direct box	33.99
D120	. 2-channel direct box/splitter, powered by	
	9V battery or 48V phantom power	21.99
DI400P-ULTRA-DI	. Passive DI w/ground lift switch	26.99
DI600P-ULTRA-DI	. Passive DI w/switchable 30dB pad and 7.5kHz filter	33.99

**BEHRINGER** DI4000/ DI800 ULTRA-DI PRO **DIRECT BOXES** Your choice of either four or eight



professional DI channels in one rack space. An XLR and a 1/4" TRS input, and a balanced output XLR and 1/4" TRS output per channel. Up to 40dB of switchable attenuation and up to 20dB of gain. Allows direct connection to speaker outputs at up to 3000W. Includes phase reverse and ground lift switches.

ITEM	DESCRIPTION	PRICE
DI4000-ULTRA-DI-PRO	Four DI channels in 1RU	
D1800-ULTRA-D1	Eight DI channels in1RU	

BSS AR133 An active direct box that has switchable input attenuation capable of handling a wide-range of output levels from the output of guitar pickups, to normal line level signals, to the output of amplifiers. Sounds outstanding on



acoustic guitar and bass guitar pickups, suitable whenever it is critical to match levels and impedances, sources needing isolation, or with long cable runs.

ITEM	DESCRIPTION	PRICE
AR133	Active direct box	156.18

**COUNTRYMAN DIRECT & STEREO DIRECT BOXES** Connect guitar pickups, contact mics or electric instru-

ments to a recording or PA console without loss of level or increased distortion. Has recessed connectors and switches, battery or phantom power, internal pad for speaker bridging, true ground isolation, RF filtered. Both models have a rugged DT85S



extra thick aluminum housing material and are virtually indestructible and static free. The DT10 adds lights to monitor battery or phantom power performance.

ITEM	DESCRIPTION	PRICE
DT85	FET direct box, 20Hz-20kHz, ground lift switch,	
	pickup/speaker switch	153.04
DT85S	Same as above w/2 channels	253.29
DT10	DI with battery and phantom LED indicators,	
	10Hz-50kHz, -15dB/-30dB pad, ground lift	191.73
DT10S	Same as above w/2 channels	352.69

DBX DB12 & DB10 DIRECT BOXES

Utilizes custom metal-shielded audio poucrs transformers, high-quality Neutrik connectors, and low-noise circuitry to preserve the sonic integrity and true characteristics of the signal source. Both boxes include a pad switch that accommodates instrument, line and even speaker level signals. Includes polarity invert and ground lift.

ITEM	DESCRIPTION	PRICE
DB12	. Active DI box	99.95
DB10	. Passive DI box	79.95







KLARK TEKNIK DN100 ACTIVE DIRECT BOX This features a high impedance, transformer isolated input, XLR plus twin 1/4" jack input connectors, and a low impedance, active, balanced XLR output. It utilizes 48V phantom power, has a switchable 30dB input pad & a switchable 15dB output attenuator.

ITEM	DESCRIPTION	PRICE
DN100	Active direct box	209.00



LA AUDIO DI BOX & DUAL TRANSFORMER BALANCING INTERFACE The DI2 is a single-channel active DI which can be powered via 2 internal 9V batteries or phantom power. The unit also features input link facility, unbalanced & balanced outputs capable of long cable runs without level loss, switchable input and output levels, and a ground lift switch. The DBT-PLUS is a dual-channel unit with high-quality balancing transformers. Comes with XLR connectors and a ground lift switch.

ITEM	DESCRIPTION	PRICE
	1-channel active DI box 2-channel 600-ohm transformer balancing interface	
	<u> </u>	











































































































RADIAL ENGINEERING DIRECT BOXES No-compromise DI's used by professionals for both studio and live applications. Using ultra-high quality/low distortion components they achieve transparency and a clear signal with amazing frequency response. Available in several configurations to meet your specific requirements. All boxes feature heavy-duty 14-gauge steel boxes, XLR or XLR/1/4" TRS & unbalanced connectors and a 3-year warranty.

ITEM	DESCRIPTION	PRICE
J33	Combo phono preamp & direct box	199.99
J48-MK2	Transformerless DI, 15dB pad, 48V phantom power,	
	ground lift, mix-merge, 10Hz-40kHz	199.99
JDX	Guitar amp DI, feed amp head to mixer/recorder,	
	ground lift, polarity switch	199.99
JDV-MK3	Passive DI, polarity reverse, ground lift, pad,	
	mix/merge, Jensen JT-DB-EPC xformer, 10Hz-80kHz	399.99
JDI-MK3	Passive DI, ground lift, Jensen xformer, 10Hz-80kHz	199.99
JDI-DUPLEX.	Stereo version of the JDI	349.99
JD6	6-channel rackmount version of the JDI	899.99
JD7	Jensen transformer guitar level distribution to feed up to	
	7 amps simultaneously, with push button selection, and	
	halanced I/O for record/playback of existing tracks	1099 99

ITEM	DESCRIPTION	PRICE
JPC	2-channel active/transformer DI with 1/8", 1/4" and RCA	
	inputs to interface with computers/consumer audio gear	199.99
PRODI	Mono transformer-coupled passive DI	99.99
PROD2	Stereo transformer-coupled passive DI	149.99
TWIN-ISO	2-channel line-level isolation box with Jensen transformers,	
	15dB pad and separate ground lifts	259.99
JS2	Mic splitter, 1 in, 3 out	219.99
JS3	As JS-2 w/input, thru and 2 transformer isolated outputs	
J-RAK	Chassis (2RU) for up to 8 DIs, drivers, or splitters	149.99
	Active direct box, compact design	
PROAV1	Single-channel AV DI box, 1/4"-1/8"-RCA-XLR inputs	119.99
PROAV2	Passive stereo multimedia DI with RCA, 3.5mm, XLR, 1/4" conn	169.99
PROD8	Passive 8-channel DI, Radial trasformers, 1RU	799.99





LITTLE LABS RED EYE PASSIVE DIRECT BOX/RE-AMP BOX A direct box and re-amping tool featuring a high quality buffered direct box input (phantom power required via XLR in) or passive direct box inputs; both with earth lift and phase reverse capabilities. Compare the direct and re-amped signals with a single button. It is expandable for daisy chaining to other Red Eyes to feed multiple amps or pedals. (2) 1/4" instrument inputs (1 active, 1 passive), XLR in, XLR out and (1) 1/4" re-amp output.

	•	•	
ITEM		DESCRIPTION	PRICE
RED-EYE-31	D	Passive direct box/re-amp box w/ phantom power	269.00



PEAVEY ADI-C & ADI-Q ACTIVE DIRECT **INTERFACES** Both direct interface units feature an active 1/4" unbalanced high-impedance input, local amplifier output, balanced XLR mic level output, 1/4" unbalanced thru output, ground lift switch, source select switch (pre/post processing) and requires phantom power or an optional external 15VDC

requires phantom power of an optional external 10126.			
ITEM	DESCRIPTION	PRICE	
ADI-C	DI with compressor - soft-knee compressor, soft-knee noise gate	51.29	
ADI-Q	DI with EQ — bass control (shelving), mid sweep EQ control,		
	high EQ control	51.29	
3004300	Power supply, 15V DC	13.66	

<b></b>



impedance balanced mic signals that are ready for use with your mixing console. DESCRIPTION ITEM PRICE IGATE ... Line level to balanced mic signal rackmount audio interface, 1RU...

PRO CO CB-1 DIRECT BOX Affordable and versatile. Features 1/4" HI-Z input and loop-through output, a LO-Z output and a ground-lift switch. Packaged in a durable 16 gauge steel box.

ITEM	DESCRIPTION	PRICE
CB1	Passive direct box	47.45

PRO CO INTERFACE BOXES DB-1 DIRECT BOX 1/4" phone jack input, 1/4" phone jack parallel output. SPKR/INST switch (-20dB pad). FILTER/FLAT switch (six dB/octave low pass), XLR male isolated output with GND/LIFT switch.

ITEM	DESCRIPTION	PRICE
DB1	. Passive direct box	78.56

PRO CO DB-2 STEREO DIRECT BOX This low noise direct box has a high dynamic range and features two 1/4" inputs with parallel 1/4" outputs, a -30dB pad for each input, and 2 XLR male balanced outputs with a ground lift switch. Suitable for any high impedance instrument, it uses two DBT-1 transformers and MU metal cans for optimal RF/ EMF rejection. When using a single input, this direct box will act as a transformer-isolated split that provides 2 balanced outputs from a single in.

ITEM	DESCRIPTION	PRICE
DB-2	. Stereo direct box	 148.92





Follow us!

# Ground Control.

The one and only direct box with phantom power controlled ground lift.

## 900 Series

Instrument Direct Box with Phantom Lift

The new standard for Live Sound! The ground lift can be controlled remotely using +48V phantom power from the console.

Input: ¼ Inch TS Thru: ¼ Inch TS Output: Balanced XLFI

Switching: 20dB Input Pad, XLR Ground Lift Featuring Phantom

Lift

\*Available with Jensen Transformers





### 700 Series

#### A / V Direct Box

The perfect DI for MP3 Players, Laptops, DJ Mixers and a wide range of audio equipment.

Input: 1/2 Inch Stereo, Dual RCA and Dual 1/4 Inch TS

Thru: Dual RCA

Output: Balanced XLR

Switching: 20dB Input Pad, XLR Ground Lift

\*All Stereo inputs are summed to mono on the XLR output;

Available with Jensen Transformers



# 800 Series

#### Instrument Direct Box

Ideal for converting the outputs of musical instruments to balanced, mic level signals that can be connected to audio consoles and mic preamps.

Input: 1/4 Inch TS

Thru: Two 1/4 Inch TS

Output: Balanced XLR

Switching: 20dB Input Pad, XLR Ground Lift.

\*Available with Jensen Transformers







800-356-5844 FULLCOMPASS.COM



















































ROLLS DB25 MATCHBOX The DB25 is a transformer balanced, passive direct box. It features a ground lift switch for hum elimination, and an attenuator switch for padding the

input signal by 20dB, or 40dB. Padding the input signal provides a way to connect the DB25 to a line-level signal, even a speaker level signal and connecting it to a balanced line or mic input on a mixer. The two 1/4" inputs are paralleled for guitarists to "passthrough" their input signal to a tuner, pre amp, etc.

ITEM	DESCRIPTION	PRICE
DB25-B	. Matchbox, polarity + pin 2 hot (XLR),	
	freqency response 50Hz-15kHz ±3dB	23.63



SM PRO AUDIO Q-DI **4 CHANNEL DIRECT BOX/LINE** MIXER Compact with SM Pro's



E-Series circuit design, this unit offers high-quality audio and robust connectors for all inputs and outputs. This 4 channel DI Box and line mixer offers master volume control, 1 RCA stereo line out, 4 XLR balanced outs, and a headphone amp. Each channel features earth lift, 20dB pad, volume control, and pan control.

ITEM	DESCRIPTION	PRICE
SMP-QDI-1	. 4-channel DI box, 4-channel mixer	99.99

#### Switchcraft








SWITCHCRAFT DIRECT BOXES These boxes convert the output of high impedance line level audio devices and musical instruments to low impedance, balanced and isolated mic level signals that can be connected to audio consoles, mic pres, effects processors, and other equipment with 3-pin XLR inputs. The SC700 and SC700CT feature RCA inputs and are designed for use with sources like MP3 players and turntables. The SC800 and SC800CT are designed for use with instruments. The SC900 and SC900CT are also for instrument use and feature Phantom Lift technology which allows the ground lift function to be operated remotely using +48V phantom power from the console. All models feature throughputs, high quality I/O jacks, -20dB pad, and Pin 1 ground lift. Built by hand in the USA.

ITEM		PRICE
SC700	A/V direct box w/Jensen transformer	182.25
SC700CT	A/V direct box w/custom transformer	114.75
SC800	Instrument DI box w/Jensen transformer	182.25
SC800CT	Instrument DI box w/custom transformer	114.75
SC900	Instrument DI box, Jensen transformer, phantom lift	225.45
SC900CT	Instrument DI box, w/custom transformer, phantom lift	155.25

#### whirlwind





ton to safely sum stereo feeds to a single channel. The "FILTER/OFF" button engages a filter that emulates the frequency response of a microphone placed in front of a 12" speaker. The "PAD" button engages 15dB pad for reducing hot input levels. Also includes reverse phase and ground lift buttons. THD @ 1kHz: less than 0.001%

ITEM	DESCRIPTION	PRICE
DIRECT-JT	Passive direct box in aluminum housing	169.88

#### whirlwind

WHIRLWIND PODMIX PODDI DIRECT BOXES The podMIX is a passive mixer & direct box that combines a mic source with a stereo line level



audio source for connection to a single channel input of a sound system. It accepts stereo line inputs via 1/8" stereo jack or dual RCA phone jacks and sums them with a mic signal into a single balanced XLR mono output. Works with dynamic & condenser mics and passes phantom power from the output to the mic input. The podDI accepts stereo inputs and sums them into a single balanced XLR mono output. A variable attenuator on each input allows level matching between left & right inputs, making the podDI a passive mixer in split track audio applications. Signal input is via 1/8" stereo TRS jack or color coded RCA phono jacks, and features a balanced male XLR output. Also be used as a single input DI box. Both feature a ground lift switch for eliminating hum & buzz.

ITEM	DESCRIPTION	PRICE
PODMIX	Mic/Line passive mixer and direct box	127.07
PODDI	Single input/output summing direct box	73.41

WHIRLWIND DIRECTOR/MULTI-DIRECTOR A premium Direct Box that converts a line, instrument or speaker level signal to a low impedance mic level. The input is Hi-Z bridging. Features include a

30dB pad switch for selecting line/instrument or speaker level, a switchable low pass roll-off filter to eliminate amplifier noise, and a ground lift switch on the Lo-Z output. Utilizes the TRHL-M transformer.

ITEM	DESCRIPTION	PRICE
DIRECTOR	Direct box	65.34
MULTIDIRECTOR	4 Director DI's in 1RU package	259.59

WHIRLWIND EDB1 An economy direct box offering rugged construction while maintaining exceptional sound quality. 1/4" in and through jacks, pad switch, and ground lift. Input impedance: 20k Ohms output impedance: 150ohms.



WHIRLWIND HOT BOX This top-of-the-line DI is an active direct box that operates from battery or phantom power. The Hot Box provides super-clean front-end circuitry that delivers the widest frequency response that you'll find in any direct box. There is a ground-lift switch, useful for eliminating ground-loop hum problems even with Phantom Power,

Direct box .....

and a switch that allows you to switch between instrument, line, or amplifier inputs. DESCRIPTION ...... Active direct box.

WHIRLWIND IMP2 An economical Direct Box that converts a line or instrument level unbalanced signal to a low impedance balanced signal. The input is Hi-Z bridging and the output is provided with a ground lift switch. Utilizes the TRHL transformer.

HOTBOX-QUAD....... 1RU 4-channel active DI......

ITEM	DESCRIPTION	PRICE
IMP2	Direct box	 43.55

WHIRLWIND PCDI The PCDI is designed to interface your unbalanced stereo line sources with professional balanced low impedance equipment. Features 2 separate DI's, Inputs; 1-3.5mm (1/8") mini TRS stereo jack or 2 sets of color coded RCA in/thru. Output; color coded XLRs. Also features a ground lift and a 20dB pad. Perfect for interfacing with the outputs of CD players, computer sound cards, tape decks, etc.



ITEM	DESCRIPTION	PRICE
PCDI	Dual-direct box	. 134.93







With over 35 years of rock solid, touring grade, audio interface, Whirlwind Music is proud to partner with Full Compass. It's just another way we can keep you connected and serve you better.

#### THE ORANGE BOX PHASER

The swirling, edgy phaser that started it all! This hand wired classic features select resistors paired with hand-matched components to achieve the same smooth and warm modulation as the original.

#### THE GOLD BOX DISTORTION

This classic hand wired tank of a box delivers a wide range of sonic distortion from a subtle, warm, tubedriven tone to a spot light, searing hot overdrive, with that vintage sustain and classic tone that defined a generation of guitar distortion.

#### THE RED DOX COMPARISON

The Red Box compressor is a true classic and can be heard in almost every great rock recording of the '70s and '80s. It's known best for its crisp percussive attack when applied to a clean guitar, as well as its lush, rich sustain when soloing. From ultra clean, chicken pickin' to the thickest sustain on the grid, the Red Box is an absolute cornerstone for your arsenal.

#### WHIRLWIND DIRECT BOXES

For decades Whirlwind has been providing the cleanest direct baxes in the industry, housed in an indestructible shell and hand-built with only the finest components. You can count on Whirlwind to perform time and time again, show after show, recording after recording.

#### MEDUSA SERIES STAGE SNAKES

Whirlwind's Medusa Series Snakes have been the touring standard worldwide for decades. They're still made here at our Rochester NY factory.

#### LEADER ELITE INSTRUMENT GABLE

We've taken premium low capacitance guitar cable, surrounded it with heavy duty striped cloth braid (available in several colors) and capped it all off with a special gold plated Elite version of our famous Leader plug. Like all whirtwind cables we back it up with a LIFETIME WARRANTY!



DIRECT-IT





DIRECTOR


























































ART S8 8-CHANNEL MIC SPLITTERS Splits 8 mic signals into 16 (8 direct XLR outs, 8 transformer-balanced XLR outs). Direct outputs pass phantom power from the main mixer to the mics. Includes a groundlift switch on each isolated output and an attenuator pad switch on each input.

ITEM	DESCRIPTION	PRICE
S8-ART	. 2-way 8-channel mic splitter, 16 XLR outs	. 239.00



ART S8-3-WAY 8-CHANNEL MIC SPLITTER An 8-channel 3-way mic splitter suitable for recording, broadcast, or live sound scenarios where microphone and XLR balanced line level input signals need to go to multiple locations. Each channel has 1 XLR input; 1 direct XLR output with 2 additional transformer isolated XLR outputs for a total of 3 balanced outputs from each mic input signal.

ITEM	DESCRIPTION	PRICE
S8-3-WAY	3-way 8-channel mic splitter	279.00

#### ART AV DIRECT AUDIO/VIDEO DIRECT BOX


It's the ideal input solution for any application where iPods, laptop computers, consumer DVD players, consumer HiFi equipment or video machines have to be connected to a single XLR microphone level input. This audio/video direct box features a transformer-isolated XLR microphone

level ouput, 20Hz-20kHz response, stereo RCA, 1/8" and 1/4" TRS line level inputs, 1/4" pressure clip speaker level inputs, variable level control, switchable 4.8kHz high cut filter, ground lift and a balanced 150ohms output.

ITEM	DESCRIPTION	PRICE
AVDIBOX	Audio/video direct box	55.00

#### ARTcessories<sup>®</sup>

ART SPLITCOM PRO MIC SPLITTER/ COMBINER Used to split or combine balanced low impedance microphone signals. It provides 1 direct-coupled output and 1 isolated output from a single microphone,



			-	
ITEM	DESCRIPTION			PRICE
SPLITCOM-PRO	Mic splitter/com	nbiner		. 35.00

#### (<u>()</u> audio-technica always listening...




MIC PROCESSORS UniTools are 24-48 volt phantom powered microphone accessories that pass the phantom power on to the mic. The rugged steel housings can be mounted anywhere in-line either near the mixer or the mice

anywhere m-mie, e	ther hear the mixer of the mic.	
ITEM	DESCRIPTION	PRICE
AT8681	UniMix 2 to 1 mic combiner with balance control	I 60.69
AT8684	UniMute Switch operated 57dB attenuator	60.69

## AUDIO-TECHNICA AT8801 PHANTOM POWER

**SUPPLY** The AT8801 is a line-powered device that provides 48V phantom power for a single microphone. This highly regulated power supply provides a constant voltage source, even with a heavily loaded input. The regulator IC is internally protected to prevent overheating even if shorted. The rugged



ITEM	DESCRIPTION	PRICE
AT8801	. 1-channel 48V phantom power supply	62.48

## Hosa



ATTENUATOR This switchable inline XLR input attenuator is great for steppingdown input level to a mixer when the level is too high. You can choose 20, 30, or 40dB of signal reduction, for a wide range of uses on stage and in the studio.

ITEM	DESCRIPTION	PRICE
ATT448	Inline attenuator	23.25



LA AUDIO MIC SPLITTERS These mic splitters are designed to work with one set of microphones and offer multiple feeds with little signal degradation. They require little recalibration after being integrated into existing systems. Both the 12-channel and 4-channel versions have 4 independently transformer-buffered outputs, pad switching for line level signals, phantom power switching, a phantom presence LED and can be configured for press box applications. The 4-channel version has an internal power supply. The 12-channel unit requires the use of an external power supply (MS1224PS) which bears a channel monitoring circuit. The power supply's headphone monitor circuit features a protection system that amplifies low background levels and limits high signal levels. On the 1224 you can also configure how the inputs and outputs appear on the front and back of the unit.

ITEM	DESCRIPTION	PRICE
MS424	4-channel 1:4 unity gain active mic splitter	1050.95
MS424X	Transformer-balanced version of the MS424	1850.95
MS1224	12-channel 1:4 unity gain active mic splitter	2500.95
MS1224PS	Power supply for MS1224	790.95
MS1224PS-B	Backup power supply for MS1224	790.95

#### ₩ PRO CO

PRO CO UTILITY MICROPHONE **MUTING BOXES** These problem solvers help in a variety of situations. Check out the Full Compass website for more detailed specs. The "Cough Drop" provides noiseless

instantaneous muting for those "emergency" situations. The "Short Stop" is for temporarily muting a dynamic or condenser mic by pressing and holding the switch. Releasing the switch resumes the signal. The "Sign Off" works the same way except that you don't need to hold the









switch down to mute. You push once to mute, again to resume the signal. The "Power Mute" combines the functions of the "Short Stop" and the "Sign Off" into one unit. The "Panic Button" is for when you actually need to switch your signal from front of house, to an alternate location (backstage to request a different guitar, etc.)

ITEM	DESCRIPTION	PRICE
COUGHDROP-SHORTSTOP	Shortstop momentary muting switch	63.69
COUGHDROP-SIGNOFF	Sign-off latching muting switch	63.69
COUGHDROP-PANICBUTTN	Panic button A/B switch	127.41
COUGHDROP-POWERMUTE	"Shortstop" and "Sign-off" in one unit	114.66

PRO CO AUDIO VISUAL INTERFACE BOXES 1/4" phone, RCA phono and 3.5mm mini-jack inputs (all parallel). HIGH/LOW switch (-20dB pad). 1/4" phone jack line output. XLR male isolated mic-level output with GND/LIFT switch.

		100
ITEM	DESCRIPTION	PRICE
AV1A	. Mobile interface box	102.88
AVP-1STS	. A/V interface w/ steel wallplate/mountable	83.12
AVP-1VSTS	. A/V interface w/ volume control	104.34

PRO CO MS-2/MS-3 MIC SPLITTERS Female XLR input, XLR male 1-direct & 1-isolated (w/ground lift) output (MS-2), or 1-direct & 2-isolated (w/ground lift) outputs (MS-3), both use the Pro Co MBT-1 transformer.

ITEM	DESCRIPTION	PRICE
MS2	1x2 mic splitter	70.83
MS3	1x3 mic splitter	86.28





Follow us!

## whirlwind

WHIRLWIND SPLIT 6 Use this handy box when you need to split a line level signal up to 6 times. Features 1 female XLR input wired to 6 male XLR outputs. Note: It is not recommended that the SPLIT 6 be used to split a microphone level signal to more than two outputs.

DESCRIPTION ITEM SPLIT6 .Line-level signal splitter.





MS42A

#### WHIRLWIND IMP COMBINER 2-TO-1 MIC COMBINER

This versatile box combines 2 microphone signals into 1 signal, and is built with the premium TRSP-2 transformer for optimum durability. Features a phase reverse switch which flips the polarity of Input #2.

ITEM	DESCRIPTION	PRICE
IMP-COMBINER	. Mic combiner	95.54

### (A) PRO CO

PRO CO MS42A/MS43A RACKMOUNT MIC SPLITTERS These split mic signals for 2 or 3 mixers. 4-female XLR mic inputs, 2 outputs (MS42A) or 3 outputs (MS43A), 1 direct & 1 or 2 isolated (w/ground lift) XLR outputs.



ITEM . 4x2 rackmount splitter. MS42A MS43A ... 4x3 rackmount splitter. 282.30

#### **PRO** CO SPORTS **ANNOUNCER**

SWITCHES These rugged, desktop push-totalk mic switches are designed specifically for sports event announcers but equally suitable for any application where a desktop push-totalk device is required. Offers clean reliable performance with any balanced or floating

low-impedance (150-ohm nominal) mic or signal source. Designed for either condenser or dynamic mics. XLRF input and XLRM outputs standard. SAS3 has (1) XLRF mic input





on the gooseneck as a direct connect and an additional XLRF input on the back (both inputs run parallel and controlled by switch.)

ITEM	DESCRIPTION	PRICE
SAS1	Push-to-talk switch, (1) XLRF in, (1) XLRM out,	
	magnetically shielded	183.84
SAS2	Push-to-talk switch with 6" gooseneck (mic and adapter not	
	included), (1) XLRF in, (1) XLRM out, magnetically shielded	239.22
SAS3	Push-to-talk switch with 6" gooseneck XLRF in,	
	(1) XLRF in, (1) XLRM out, magnetically shielded	270.46



#### **RADIAL ENGINEERING MIC ACCESSORIES**

ITEM	DESCRIPTION	PRICE
JS2	Jensen transformer mic splitter w/XLR input, thru,	
	and isolated monitor output +4th output w/ground lift	219.99
8CX	Mic splitter, 8 channels on frame mount for install,	
	radial transformers	699.99
HOTSHOTABI	Dual-to-single XLR source selector	79.99
HOTSHOTABO	Single-to-dual XLR source selector	79.99
DM1-HOTSHOT	Passive mic mute and signal redirector,	
	momentary switch w/ground lift	79.99



#### **ROLLS PB224 PHANTOM POWER SUPPLY** Perfect for any

condenser microphone, the PB224 powers even the high-current draw microphones. The unit features a rock solid 48 volts of clean phantom power. It can

operate from two internal 9V batteries or from the Rolls PS27S AC adapter.

ITEM	DESCRIPTION	PRICE
PB224	2-channel phantom power supply	81.00
	. AC adapter	

#### SABINE

#### SABINE PHANTOM MIC RIDER PRO SERIES FOR

GOOSENECK OR PODIUM MICS Now you can leave your mics unattended knowing the Phantom will take care of feedback, gain and clarity for you. Series 3 provides Infrared Gate only (turns the mic on/off automatically). Series 2 adds automatic gain control, Proximity Effect Control (controls excess bass as you get closer to the mic), and Plosive Control (controls loud pops from some consonants).

ITEM	DESCRIPTION	PRICE
PMR-GP3-12	Phantom Mic Rider Pro Series 3	
	(for 12" gooseneck & podium mics)	. 112.97
PMR-GP3-18	Phantom Mic Rider Pro Series 3	
	(for 18" gooseneck & podium mics)	.112.97
PMR-GP3-C	Phantom Mic Rider Pro Series 3, custom cable length	.120.97
PMR-GP2-12	Phantom Mic Rider Pro Series 2	
	(for 12" gooseneck & podium mics)	. 136.97
PMR-GP2-18	Phantom Mic Rider Pro Series 2	
	(for 18" gooseneck & podium mics)	. 136.97
PMR-GP2-C	Phantom Mic Rider Pro Series 2, custom cable length	. 144.97



SHURE	PROBLEM SOLVERS	
ITEM	DESCRIPTION	PRICE
A15AS	Switchable mic attenuator, (15,20,25dB), passes	
	phantom, requires use of balanced signals	45.60
A15BT	Bridging transformer, in-line XLR-F to XLR-M,	
	33 kilo-ohm primary, 600- or 750-ohm secondary	51.30
A15HP	High pass filter, in-line XLR-F to XLR-M, roll off of 12dB	
	below 100Hz, requires use of balanced signals	54.15
A15LA	Line adapter, converts balanced line level signals to mic level	
	(50dB attenuation), in-line XLR-F to XLR-M configuration	41.33
A15PRS	Switchable phase reverser, requires balanced signals, XLR-F to	KLR-M 71.25
A15RF	RF Filter, XLR in/out, passes phantom power	49.88
A15TG	Tone generator, 700Hz mic level signal, XLR-M output	143.90
A85F	Transformer, Low Z, XLR-F to High Z 1/4" phone plug, may be used in	reverse 18.75
A95U	Transformer, Low Z, XLR-M to High Z Amphenol MC1M	
	with 1/4" jack adapter, may be used in reverse	46.88
A95UF	Same as A95U but with XLR-F low impedance connector	46.88
A96F	Transformer, Low Z XLR-F to medium impedance mini plug	
	on attached 2' cable	61.99
A120S	In-line on/off switch (no connectors, requires soldering)	26.79

#### Switchcraft

SWITCHCRAFT RMAS1 SINGLE CHANNEL MIC

SPLITTER Passive 3-way transformer isolated mic splitter with female XLR input, XLR male 1-direct & 2-isolated, with ground lifte AndR and The direct out passes phantom nowe

gr	Juliu IIIts, "40ub	au. The un ect out pass	ses phantom power.
ITE	M	DESCRIPTION	PRICE
RM	IAS1	1X3 mic splitter	160.00





















GOOSENECK

































