

DP4[®] and DP4-B
METAL-POLYMER SELF-LUBRICATING
LEAD FREE BEARING SOLUTIONS



The Tribological Solution Provider for Industrial Progress, Regardless of Shape or Material

GGB helps create a world of motion with minimal frictional loss through plain bearing and surface engineering technologies. With R&D, testing and production facilities in the United States, Germany, France, Brazil, Slovakia and China, GGB partners with customers worldwide on customized tribological design solutions that are efficient and environmentally sustainable. GGB's engineers bring their expertise and passion for tribology to a wide range of industries, including automotive, aerospace and industrial manufacturing. To learn more about tribology for surface engineering from GGB, visit www.ggbearings.com.

GGB is an Enpro company (NYSE: NPO).

Our products are used in tens of thousands of critical applications every day on our planet. It is always our goal to provide superior, high-quality solutions for our customers' needs, no matter where those demands take our products. From space vehicles to golf carts and virtually everything in between; we offer the industry's most extensive range of high performance, maintenance-free bearing solutions for a multitude of applications:

- [Aerospace](#)
- [Railway](#)
- [Recreation](#)
- [Energy](#)
- [Agricultural](#)
- [Industrial](#)
- [Construction](#)
- [Fluid Power](#)
- [Automotive](#)
- [Primary Metals](#)
- [Oil & Gas](#)
- [Medical](#)

The GGB Advantage



LOWER SYSTEM COST

GGB bearings reduce shaft costs by eliminating the need for hardening and machining grease paths. Their compact, one-piece construction provides space and weight savings and simplifies assembly.



LOW-FRICTION, HIGH WEAR RESISTANCE

Low coefficients of friction eliminate the need for lubrication, while providing smooth operation, reducing wear and extending service life. Low-friction also eliminates the effects of stick-slip or “stiction” during start up.



MAINTENANCE-FREE

GGB bearings are self-lubricating, making them ideal for applications requiring long bearing life without continuous maintenance, as well as operating conditions with inadequate or no lubrication.



ENVIRONMENTAL

Greaseless, lead-free GGB bearings comply with increasingly stringent environmental regulations such as the EU RoHS directive restricting the use of hazardous substances in certain types of electrical and electronic equipment.



CUSTOMER SUPPORT

GGB's flexible production platform and extensive supply network assure quick turnaround and timely deliveries. In addition, we offer local applications engineering and technical support.

The Highest Standards in Quality



SAFETY

Our deep-rooted culture of safety places a relentless focus on creating a secure, healthy work environment for all. As one of our core values, safety is essential for us to achieve our goal of having the safest employees in the industry.



EXCELLENCE

Our world-class manufacturing plants in the United States, Brazil, China, Germany, France, and Slovakia are certified in quality and excellence according to ISO 9001, IATF 16949, ISO 14001, OHSAS 18001, and AS9100D/EN9100. This allows us to access the industry's best practices while aligning our management system with global standards.

For a complete listing of our certifications, please visit our website:

<https://www.ggbearings.com/en/certificates>



RESPECT

Our teams work together with mutual respect regardless of background, nationality, or function, embracing the diversity of people and learning from one another - after all, with respect comes both individual and group growth.

GGB - Who We Are

AT GGB, WE AREN'T AFRAID TO TAKE RISKS FOR OUR CUSTOMERS.

We are passionate about the work we do and believe that same passion contributes to the level of innovation that can enhance human potential. We take pride in working closely with customers in the early stage of a design to think broadly and boldly, and to expand beyond traditional surface engineered solutions. We offer reliable partnerships based on trust, compassion, determination, collaboration and respect.

As the tribological leader, GGB helps create a world of motion with minimal frictional loss through plain bearing and surface engineering technologies. Thanks to our global footprint and wealth of specific applications expertise, our capabilities are virtually limitless. We work to push the boundaries of possibility, inspiring customers across all markets to partner - and innovate - alongside us.



Table of Contents

| | | | |
|---|-----------|--|-----------|
| 1 Introduction | 7 | 5 Lubrication | 25 |
| 1.1 Characteristics and Advantages | 7 | 5.1 Lubricants | 25 |
| 1.2 Applications | 8 | 5.2 Tribology | 25 |
| 2 Structure and Composition | 9 | Hydrodynamic Lubrication | 25 |
| 2.1 Basic Forms | 9 | Mixed Film Lubrication | 26 |
| Standard Components | 9 | Boundary Lubrication | 26 |
| Non-Standard Components | 9 | 5.3 Characteristics of Lubricated Bearings | 27 |
| 3 Properties | 10 | 5.4 Design Guidance | 28 |
| 3.1 Physical and Mechanical Properties | 10 | 5.5 Clearances for Lubricated Operation | 29 |
| 3.2 Chemical Resistance | 10 | 5.6 Grooving for Lubricated Operation | 29 |
| 3.3 Frictional Properties | 11 | 5.7 Mating Surface Finish for Lubricated Operation | 29 |
| Effect of Temperature for Unlubricated Applications | 11 | 5.8 Grease Lubrication | 29 |
| 4 Bearing Performance | 12 | 6 Bearing Assembly | 30 |
| 4.1 McPherson Strut Applications | 12 | Dimensions and Tolerances | 30 |
| Wear and Friction Properties | 12 | 6.1 Allowance for Thermal Expansion | 30 |
| McPherson Strut Test Rig | 12 | 6.2 Tolerances for Minimum Clearance | 30 |
| Cavitation Erosion Resistance | 14 | Burnishing | 31 |
| Flow Erosion Resistance | 15 | 6.3 Counterface Design | 31 |
| 4.2 Hydraulic Applications | 16 | 6.4 Installation | 32 |
| GGB Jupiter Test Rig | 16 | Fitting of Cylindrical Bushes | 32 |
| 4.3 Dry Wear Performance | 17 | Fitting of Flanged Bushes | 32 |
| Design Factors | 17 | Insertion Forces | 32 |
| Specific Load p | 17 | Alignment | 33 |
| Sliding Speed U | 18 | Sealing | 33 |
| Continuous Rotation | 18 | 6.5 Axial Location | 33 |
| Oscillating Movement | 18 | Fitting of Thrust Washers | 33 |
| pU Factor | 19 | Slideways | 34 |
| Application Factors | 19 | 7 Modification | 35 |
| Temperature | 19 | 7.1 Cutting and Machining | 35 |
| Mating Surface | 20 | Drilling Oil Holes | 35 |
| Bearing Size | 20 | Cutting Strip Material | 35 |
| Bore Burnishing | 21 | 7.2 Electroplating | 35 |
| Type of Load | 21 | DP4® Components | 35 |
| 4.4 Calculation of Bearing Service Life | 22 | | |
| Specific Load p | 22 | | |
| High Load Factor a_E | 22 | | |
| Modified pU Factor | 22 | | |
| Estimation of Bearing Life L_H | 23 | | |
| Bore Burnishing | 23 | | |
| Slideways | 23 | | |
| 4.5 Worked Examples | 24 | | |

Table of Contents

| | |
|--|-----------|
| 8 Standard Products | 36 |
| 8.1 DP4® Cylindrical Bushes | 36 |
| 8.2 DP4® Flanged Bushes | 42 |
| 8.3 DP4® Thrust Washers | 44 |
| 8.4 DP4® Flanged Washers | 45 |
| 8.5 DP4® Strip | 46 |
| 8.6 DP4-B Cylindrical Bushes | 47 |
| 8.7 DP4-B Flanged Bushes | 50 |
| 8.8 DP4-B Strip | 51 |
| 9 Test Methods | 52 |
| 9.1 Measurement of Wrapped Bushes | 52 |
| Test A of ISO 3547 Part 2 | 52 |
| Test B (alternatively to Test A) | 52 |
| Test C | 52 |
| Measurement of Wall Thickness (alternatively to Test C) | 52 |
| Test D | 52 |
| 10 Data Sheet for Bearing Design | 53 |
| Formula Symbols and Designations | 54 |
| Product Information | 55 |

1 Introduction

The purpose of this handbook is to provide comprehensive technical information on the characteristics of DP4® and DP4-B bearings.

The information given permits designers to establish the correct size of bearing required and the expected life and performance.

In addition, your local sales representative is available to assist you with your design. Complete information on the range of DP4® standard stock products is given together with details of other DP4® products.

GGB is continually refining and extending its experimental and theoretical knowledge and, therefore, when using this brochure it is always worth-while to contact GGB should additional information be required.

As it is impossible to cover all conditions of operation which arise in practice, customers are advised to carry out prototype testing wherever possible.

1.1 CHARACTERISTICS AND ADVANTAGES

The DP4® and DP4-B materials offer the following characteristics:

- Good frictional properties with negligible stick-slip
- High static and dynamic load capacity
- Suitable for rotating, oscillating, reciprocating and sliding movements
- Compact size and low weight
- Prefinished that requires no machining after assembly
- Possibility to burnish for reduced operating clearance
- No water absorption and therefore dimensionally stable
- Suitable for a wide operating temperature range from -200 to +280 °C
- DP4-B with bronze backing for increased corrosion resistance
- Lead free in compliance with European RoHS 2002/95/EC, 2002/96/EC and EVL 2000/53/EC directives (see page 55)

In particular, depending on the dry running conditions, DP4® and DP4-B materials present the following performance advantages:

Dry conditions

- Good friction and wear performance under light duty conditions
- Particularly suitable for intermittent oscillating and reciprocating movements
- Maintenance free as no external lubrication required
- Seizure resistant.

Lubricated conditions

- Good wear and friction performance over a wide range of load, speed and temperature conditions
- High wear resistance in boundary operating conditions
- High resistance of bearing surface under fluid cavitation and flow erosion conditions
- Suitable for operation in diverse fluids (oil, fuel, solvents, refrigerants, water).

1 Introduction

1.2 APPLICATIONS

Given the performance characteristics in both dry and lubricated operating conditions, DP4® and DP4-B bearing materials are extensively used in a wide range of automotive and industrial applications, such as:

Automotive

Braking systems, clutches, gearbox and transmissions, hinges - door bonnet and boot, convertible roof tops, pedal systems, pumps - axial, radial, gear and vane, seat mechanisms, steering systems, struts and shock absorbers, wiper systems.

Industrial

Aerospace, agricultural, construction equipment, food and beverage, marine, material handling, office equipment, packaging equipment, pneumatic and hydraulic cylinders, railroad and tramways, textile machinery, valves.



2 Structure and Composition

DP4[®] / DP4-B

DP4[®] is a composite bearing material. It consists of a steel DP4[®] / bronze DP4-B backing to which is bonded a porous sinter bronze interlayer which is overlaid and impregnated with Polytetrafluoroethylene (PTFE) containing a mixture of inorganic fillers and special polymer fibres. The steel DP4[®] / bronze DP4-B backing provides mechanical strength and the bronze sinter layer provides a strong mechanical bond for the filled bearing lining.




Fig.1: DP4 microsection




Fig.2: DP4-B microsection

2.1 BASIC FORMS

Standard Components

These products are manufactured to International, National or GGB standards. The following components are standard stock products:

- Cylindrical Bushes
- Flanged Bushes
- Thrust Washers
- Flanged Washers
- Strip Material



Fig.3: Standard stock products

Non-standard Components

These products are manufactured to customer's requirements and include for example:

- Modified Standard Components
- Half Bearings
- Flat Components
- Deep Drawn Parts
- Pressings
- Stampings



Fig.4: Non-standard components

3 Properties

3.1 PHYSICAL AND MECHANICAL PROPERTIES

| BEARING PROPERTIES | | SYMBOL | UNIT | VALUE | | COMMENTS |
|---|---------------------|---------------|-------------|-------|-------|---|
| | | | | DP4® | DP4-B | |
| PHYSICAL PROPERTIES | | | | | | |
| Coefficient of linear thermal expansion | parallel to surface | α_1 | $10^{-6}/K$ | 11 | 18 | |
| | normal to service | α_2 | | 30 | 36 | |
| Operating temperature | | T_{max} | °C | +280 | +280 | |
| | | T_{min} | | -200 | -200 | |
| MECHANICAL PROPERTIES | | | | | | |
| Compressive yield strength | | σ_c | MPa | 350 | 300 | measured on disc Ø 25 mm x 2.45 mm thick |
| Maximum load | static | $p_{sta.max}$ | MPa | 250 | 140 | |
| | dynamic | $p_{dyn.max}$ | | 140 | 140 | |

Table 1: Physical and mechanical properties of DP4 and DP4-B

3.2 CHEMICAL PROPERTIES

The following table provides an indication of the chemical resistance of DP4® and DP4-B to various chemical media. It is recommended that the chemical resistance is confirmed by testing if possible.

| CHEMICAL | % | °C | DP4® | DP4-B | CHEMICAL | °C | DP4® | DP4-B |
|---------------------|----|----|------|-------|-----------------------------|----|------|-------|
| STRONG ACIDS | | | | | SOLVENTS | | | |
| Hydrochloric Acid | 5 | 20 | - | - | Acetone | 20 | + | + |
| Nitric Acid | 5 | 20 | - | - | Carbon Tetrachloride | 20 | + | + |
| Sulfuric Acid | 5 | 20 | - | - | LUBRICANTS AND FUELS | | | |
| WEAK ACIDS | | | | | Paraffin | 20 | + | + |
| Acetic Acid | 5 | 20 | - | o | Gasolene | 20 | + | + |
| Formic Acid | 5 | 20 | - | o | Kerosene | 20 | + | + |
| BASES | | | | | Diesel Fuel | 20 | + | + |
| Ammonia | 10 | 20 | o | - | Mineral Oil | 70 | + | + |
| Sodium Hydroxide | 5 | 20 | o | o | HFA-ISO46 High Water Fluid | 70 | + | + |
| | | | | | HFC-Water-Glycol | 70 | + | + |
| | | | | | HFD-Phosphate Ester | 70 | + | + |
| | | | | | Water | 20 | o | + |
| | | | | | Sea Water | 20 | - | o |

Table 2: Chemical Resistance of DP4 and DP4-B

- + **Satisfactory:** Corrosion damage is unlikely to occur
- o **Acceptable:** Some corrosion damage may occur but this will not be sufficient to impair either the structural integrity or the tribological performance of the material
- **Unsatisfactory:** Corrosion damage will occur and is likely to affect either the structural integrity and/or the tribological performance of the material

3.3 FRICTIONAL PROPERTIES

DP4® bearings show negligible 'stick-slip' and provide smooth sliding between adjacent surfaces. The coefficient of friction of DP4® depends upon:



- The specific load p [MPa]
- The sliding speed U [m/s]
- The roughness of the mating running surface Ra [μm]
- The bearing temperature T [$^{\circ}\text{C}$].

A typical relationship is shown in Fig. 5, which can be used as a guide to establish the actual friction under clean, dry conditions after running in. Exact values may vary by $\pm 20\%$ depending on operating conditions. Before running in, the friction may be up to 50 % higher.

After progressively longer periods of dwell under load (e.g. hours or days) the static coefficient of friction on the first movement may be between 1.5 and 3 times greater, particularly before running in.

Effect of Temperature for Unlubricated Applications

The coefficient of friction of DP4® varies with temperature. Typical values are shown in Fig. 6 for temperatures up to 250 $^{\circ}\text{C}$. Friction increases at bearing temperatures below 0 $^{\circ}\text{C}$. Where frictional characteristics are critical to a design they should be established by prototype testing.



4 Bearing Performance

4.1 MCPHERSON STRUT APPLICATIONS

DP4® has been developed to provide improved wear, erosion resistance and reduced friction in McPherson strut piston rod guide bush applications under the most demanding of operating conditions.

In the following sections, the performance of DP4® is compared with that of the material used in the majority of this type of application.

Wear and friction properties

The wear and frictional performance of DP4® has been evaluated in the piston rod guide bush application of a McPherson strut shock absorber using the test rig shown in Fig. 7. The test conditions are designed to simulate the operational duty of the test strut in service and differ in detail according to the strut manufacturer. The test conditions used are given in Table 3 and Table 4.

McPherson strut test rig




Fig. 7: Principle of the strut test rig

| STRUT WEAR - TEST CONDITIONS | |
|------------------------------|-----------|
| Waveform | Sine |
| Frequency | 2.5 Hz |
| Side load | 890 N |
| Test duration | 100 hours |
| Stroke | 100 mm |
| Mean diametral clearance | 0.06 mm |
| Lubricant | TEX 0358 |
| Foot valve temperature | 70 °C |

Table 3: McPherson strut wear test conditions

STRUT FRICTION - TEST CONDITIONS

| | |
|--------------------------|----------|
| Waveform | Sine |
| Frequency | 0.1 Hz |
| Side load | 600 N |
| Stroke | 70 mm |
| Mean diametral clearance | 0.06 mm |
| Lubricant | TEX 0358 |
| Foot valve temperature | ambient |

Table 4: McPherson strut friction test conditions

The relative wear and frictional performance of DP4® tested under these conditions are shown in Figures 8 - 10. Actual results for the wear rate and friction are not quoted because these depend strongly on the actual test conditions and design of the strut under test. The relative performance plots shown thus provide the best indication as to the benefits offered by DP4® in this class of application.




Fig. 8: Relative wear resistance




Fig. 9: Relative static friction coefficient




Fig. 10: Relative dynamic friction coefficient

4 Bearing Performance

Cavitation Erosion Resistance

Under certain operating conditions, the PTFE lining of the McPherson strut piston rod guide bush can suffer erosion damage, due to cavitation and flow erosion effects from the oil film within the bearing. The test rig shown in Fig. 11 is designed to reproduce the cavitation erosion damage to the bearing lining of the test specimen.

The test conditions are given in Table 5.




Fig. 11: Principle of the cavitation erosion test rig

CAVITATION EROSION - TEST CONDITIONS

| | |
|---------------|------------|
| Amplitude | 0.015 mm |
| Frequency | 20 kHz |
| Separation | 1 mm |
| Test duration | 30 minutes |
| Lubricant | TEX 0358 |
| Temperature | ambient |

Table 5: Cavitation erosion test conditions

The relative resistance to cavitation damage of DP4® as evaluated on this test rig is shown in Fig. 12.




Fig. 12: Relative resistance to cavitation erosion

Flow Erosion Resistance

The test rig shown in Fig. 13 is designed to reproduce flow erosion damage to the bearing lining of the test specimen.

The test conditions are given in Table 6.




Fig. 13: Principle of the flow erosion test rig

FLOW EROSION - TEST CONDITIONS

| | |
|----------------------|-----------------------------|
| Bearing diameter | 20 mm |
| Bearing length | 15 mm |
| Diametral clearing | 0.11 mm |
| Pressure | 13.8 MPa |
| Flow rate | 5 l/min |
| Test duration | 20 hours |
| Shaft surface finish | 0.15 $\mu\text{m} \pm 0.05$ |
| Temperature | ambient |

Table 6: Flow erosion test conditions

The relative resistance to flow erosion damage of DP4® as evaluated on this test rig is shown in Fig. 14.




Fig. 14: Relative resistance to flow erosion

4 Bearing Performance

4.2 HYDRAULIC APPLICATIONS

DP4 also shows excellent wear and frictional performance in a wide range of oil lubricated hydraulic applications. The wear resistance of DP4 under steady load oil immersed boundary lubrication conditions has been evaluated using the test rig shown in Fig. 15. The test conditions are given in Table 7.

GGB Jupiter Test Rig




Fig. 15: Principle of the GGB Jupiter test rig

LUBRICATED WEAR - TEST CONDITIONS

| | |
|-------------------------|-------------------------|
| Bearing diameter | 20 mm |
| Bearing length | 15 mm |
| Mean diametral clearing | 0.10 mm |
| Speed | 0.11 m/s |
| Lubricant | ISO VG 46 hydraulic oil |

Table 7: Lubricated wear test conditions

The relative pU limits with boundary lubrication of DP4® and the material used in many high performance hydraulic pump applications as determined from these tests are shown in Fig. 16. The limiting pU depends upon the actual operating conditions and hence the relative performance only is given for guidance.




Fig. 16: Relative pU limits

4.3 DRY WEAR PERFORMANCE

Design Factors

The main parameters when determining the size or calculating the service life for a DP4® bearing are:

- Specific load limit p_{lim}
- Mating surface material
- pU Factor
- Temperature T
- Mating surface roughness Ra
- Other environmental factors e.g. housing design, dirt, lubrication.

The following calculation can be used to estimate the bearing service life of DP4® under dry running conditions.

Specific Load p

For the purpose of assessing bearing performance the specific load p is defined as the working load divided by the projected area of the bearing and is expressed in MPa.

Cylindrical Bush

$$(4.3.1) \quad p = \frac{F}{D_i \cdot B} \quad [\text{MPa}]$$

Thrust Washer

$$(4.3.2) \quad p = \frac{4F}{\pi \cdot (D_o^2 - D_i^2)} \quad [\text{MPa}]$$

Flanged Bush (Axial Loading)

$$(4.3.3) \quad p = \frac{F}{0,04 \cdot (D_{fl}^2 - D_i^2)} \quad [\text{MPa}]$$

Slideway

$$(4.3.4) \quad p = \frac{F}{L \cdot W} \quad [\text{MPa}]$$

Specific Load Limit p_{lim}

The maximum load which can be applied to a DP4® bearing can be expressed in terms of the Specific Load Limit, which depends on the type of the loading. It is highest under steady loads. Conditions of dynamic load or oscillating movement which produce fatigue stress in the bearing result in a reduction in the permissible Specific Load Limit.

In general the specific load on a DP4® bearing should not exceed the Specific Load Limits given in Table 8.

The values of Specific Load Limit specified in Table 8 assume good alignment between the bearing and mating surface (Fig. 35, page 33).




Fig. 17: Projected Area

4 Bearing Performance

Maximum Specific Load p_{lim}

| TYPE OF LOADING / p_{lim} [MPa] | | | | | | | | | | |
|--|------|------|------|------|------|--------|--------|--------|--------|--------|
| Steady load - rotating movement p_{lim} 140 | | | | | | | | | | |
| Steady load - oscillating movement | | | | | | | | | | |
| p_{lim} | 140 | 140 | 115 | 95 | 85 | 80 | 60 | 44 | 30 | 20 |
| Number of movement cycles Q | 1000 | 2000 | 4000 | 6000 | 8000 | 10^4 | 10^5 | 10^6 | 10^7 | 10^8 |
| Dynamic load - rotating or oscillating movement | | | | | | | | | | |
| p_{lim} | 60 | 60 | 50 | 46 | 42 | 40 | 30 | 22 | 15 | 10 |
| Number of load cycles Q | 1000 | 2000 | 4000 | 6000 | 8000 | 10^4 | 10^5 | 10^6 | 10^7 | 10^8 |

Table 8: Maximum specific load p_{lim}

Permanent deformation of the DP4® bearing lining may occur for specific loads above 140 MPa unless with slow intermittent movements. Under these conditions, it is recommended to contact GGB for further information.

The permissible maximum load on a thrust washer is higher than that on the flange of a flanged bush, and under conditions of high axial loads a thrust washer should be specified.

Sliding Speed U

Speeds in excess of 2.5 m/s sometimes lead to overheating, and a running in procedure may be beneficial. This could consist of a series of short runs progressively increasing in duration from an initial run of a few seconds.

Continuous Rotation

Cylindrical Bush

$$(4.3.5) \quad U = \frac{D_i \cdot \pi \cdot N}{60 \cdot 10^3} \quad [\text{m/s}]$$

Thrust Washer

$$(4.3.6) \quad U = \frac{D_o + D_i}{2} \cdot \pi \cdot N \quad [\text{m/s}]$$

Oscillating Movement

Cylindrical Bush

$$(4.3.7) \quad U = \frac{D_i \cdot \pi}{60 \cdot 10^3} \cdot \frac{4\varphi \cdot N_{osz}}{360} \quad [\text{m/s}]$$

Thrust Washer

$$(4.3.8) \quad U = \frac{D_o + D_i}{2} \cdot \pi \cdot \frac{4\varphi \cdot N_{osz}}{360} \quad [\text{m/s}]$$




Figure 18: Oscillating cycle φ

pU Factor

The useful operating life of a DP4® bearing is governed by the pU factor, the product of the specific load p [MPa] and the sliding speed U [m/s].

For thrust washers and flanged bush thrust faces the rubbing velocity at the mean diameter is used.

pU factors up to 1.0 MPa x m/s can be accommodated for short periods, whilst for continuous rating, pU factors up to 0.5 MPa x m/s can be used, depending upon the operating life required.

| | DU | UNIT |
|-----------------|-----|-----------|
| p | 140 | MPa |
| U | 2.5 | m/s |
| pU continuous | 0.5 | MPa · m/s |
| pU intermittent | 1.0 | MPa · m/s |

Table 9: Typical data p, U and pU

Calculation of pU Factor

$$(4.3.9) \quad pU = p \cdot U \quad [\text{MPa} \cdot \text{m/s}]$$

Applicaton Factors

The following factors influence the bearing performance of DP4® and must be considered in calculating the required dimension or estimating the bearing life for a particular application.

Temperature

The useful life of a DP4® bearing depends upon the operating temperature.

Under dry running conditions frictional heat is generated at the rubbing surface of the bearing dependent on the pU condition. For a given pU factor the operating temperature of the bearing depends upon the temperature of the surrounding environment, the heat dissipation properties of the housing and the mating surface. Intermittent operation affects the heat dissipation from the assembly and hence the operating temperature of the bearing.

The effect of temperature on the operating life of DP4® bearings is indicated by the factor a_T shown in Table 10.

| MODE OF OPERATION | NATURE OF HOUSING | TEMPERATURE OF BEARING ENVIRONMENT T_{amb} [°C] AND TEMPERATURE APPLICATION FACTOR a_T | | | | | |
|--|--|---|-----|-----|-----|-----|-----|
| | | [°C] 25 | 60 | 100 | 150 | 200 | 280 |
| Dry continuous operation | Average heat dissipating qualities | 1.0 | 0.8 | 0.6 | 0.4 | 0.2 | 0.1 |
| Dry continuous operation | Light pressings or isolated housing with poor heat dissipating qualities | 0.5 | 0.4 | 0.3 | 0.2 | 0.1 | - |
| Dry continuous operation | Non-metallic housings with bad heat dissipating qualities | 0.3 | 0.3 | 0.2 | 0.1 | - | - |
| Dry intermittent operation (duration less than 2 min, followed by a longer dwell period) | Average heat dissipating qualities | 2.0 | 1.6 | 1.2 | 0.8 | 0.4 | 0.2 |

Table 10: Temperature application factor a_T

4 Bearing Performance

Mating Surface

The effect of the mating surface material type on the operating life of DP4® bearings is indicated by the mating surface factor a_M and the life correction constant a_L shown in Table 11.

| MATERIAL | a_M | a_L |
|--|-------|-------|
| Steel and Cast Iron | | |
| Carbon Steel | 1 | 400 |
| Carbon Manganese Steel | 1 | 400 |
| Alloy Steel | 1 | 400 |
| Case Hardened Steel | 1 | 400 |
| Nitrided Steel | 1 | 400 |
| Salt bath nitrocarburised | 1 | 400 |
| Stainless Steel (7-10 % Ni, 17-20 % Cr) | 2 | 400 |
| Cast Iron ($0.3 \pm 0.1 \mu\text{m } R_a$) | 1 | 400 |

Table 11: Mating surface factor a_M and life correction constant a_L

Note:

The factor values given assume a mating surface finish of $R_a = 0.4 \pm 0.1 \mu\text{m}$.

- A ground surface is preferred to fine turned
- Surfaces should be cleaned of abrasive particles after polishing
- Cast iron surfaces should be ground to $R_a = 0.3 \pm 0.1 \mu\text{m}$
- The grinding cut should be in the same direction as the bearing motion relative to the shaft

Bearing Size

The running clearance of a DP4® bearing increases with bearing diameter resulting in a proportionally smaller contact area between the shaft and bearing. This reduction in contact area has the effect of increasing the actual unit load and hence pU factor. The bearing size factor (Fig. 20) is used in the design calculations to allow for this effect.




Figure 19: Contact area between bearing and shaft




Fig. 20: Bearing size factor a_B

Bore Burnishing

Burnishing or machining the bore of a DP4® bearing results in a reduction in the wear performance. The application factor a_C given in table 12 is used in the design calculations to allow for this effect. Machining DP4® is not recommended.

| DEGREE OF SIZING | APPLICATION FACTOR a_C | |
|--|--------------------------|-----|
| BURNISHING | | |
| Excess of burnishing tool diameter over mean bore size | 0.025 mm | 0.8 |
| | 0.038 mm | 0.6 |
| | 0.050 mm | 0.3 |

Table 12: Bore burnishing or machining application factor a_C

Type of Load

The type of load is considered in formula (4.4.9) page 23 and (4.4.10) page 23.




Fig. 21: Steady load, bush stationary, shaft rotating




Fig. 22: Rotating load, shaft stationary, bush rotating

4 Bearing Performance

4.4 CALCULATION OF BEARING SERVICE LIFE

Where the size of a bearing is governed largely by the space available the following calculation can be used to determine whether its useful life will satisfy the requirements. If the calculated life is inadequate, a larger bearing should be considered.

Specific Load p

Bushes

$$(4.4.1) \quad p = \frac{F}{D_i \cdot B} \quad [\text{MPa}]$$

Flanged bushes

$$(4.4.2) \quad p = \frac{F}{0.04 \cdot (D_f^2 - D_i^2)} \quad [\text{MPa}]$$

Thrust washers

$$(4.4.3) \quad p = \frac{4F}{p \cdot (D_o^2 - D_i^2)} \quad [\text{MPa}]$$

High load factor a_E

$$(4.4.4) \quad a_E = \frac{p_{lim} - p}{p_{lim}} \quad [-]$$

p_{lim} see Table 8, Page 18

If a_E is negative then the bearing is overloaded. Increase the bearing diameter and/or length.

Modified pU Factor

Bushes

$$(4.4.5) \quad pU = \frac{5.25 \cdot 10^{-5} F \cdot N}{a_E \cdot B \cdot a_T \cdot a_M \cdot a_B} \quad [\text{MPa} \cdot \text{m/s}]$$

Flanged bushes

$$(4.4.6) \quad pU = \frac{6.5 \cdot 10^{-4} F \cdot N}{a_E \cdot (D_f - D_i) \cdot a_T \cdot a_M \cdot a_B} \quad [\text{MPa} \cdot \text{m/s}]$$

Thrust washers

$$(4.4.7) \quad pU = \frac{3.34 \cdot 10^{-5} F \cdot N}{a_E \cdot (D_o - D_i) \cdot a_T \cdot a_M \cdot a_B} \quad [\text{MPa} \cdot \text{m/s}]$$

For oscillating movement, calculate the average rotational speed.

$$(4.4.8) \quad N = \frac{4\phi \cdot N_{osz}}{360} \quad [1/\text{min}]$$




Figure 23: Oscillating cycle ϕ



Estimation of Bearing Life L_H

Bushes (Steady load)

$$(4.4.9) \quad L_H = \frac{265}{pU} - a_L \quad [h]$$

Bushes (Rotating load)

$$(4.4.10) \quad L_H = \frac{530}{pU} - a_L \quad [h]$$

Flanged Bushes (Axial load)

$$(4.4.11) \quad L_H = \frac{175}{pU} - a_L \quad [h]$$

Thrust Washers

$$(4.4.12) \quad L_H = \frac{175}{pU} - a_L \quad [h]$$

Bore Burnishing

If the DP4® bush is bore burnished then this must be allowed for in estimating the bearing life by the application factor a_C (Table 12, page 21).

Estimated Bearing Life

$$(4.4.13) \quad L_H = L_H \cdot a_C \quad [h]$$

For Oscillating Movements or Dynamic Loads

$$(4.4.14) \quad Z_T = L_H \cdot N_{osc} \cdot 60 \quad [\text{cycles}]$$

for oscillating movements

Calculate estimated number of cycles Z_T

Check that Z_T is less than total number of cycles Q for the operating specific load p (Table 8, page 18)

$$(4.4.15) \quad Z_T = L_H \cdot C \cdot 60 \quad [\text{cycles}]$$

for dynamic loads

If $Z_T < Q$, L_H will be limited by wear after Z_T cycles.

If $Z_T > Q$, L_H will be limited by fatigue after Z_T cycles.

Slideways

Specific Load Factor

$$(4.4.16) \quad a_{E1} = A - \frac{F}{p_{lim}} \quad [-]$$

If negative the bearing is overloaded and the bearing area should be increased.

Speed Temperature and Material Application Factors

$$(4.4.17) \quad a_{E2} = \frac{280 \cdot a_T \cdot a_M}{F \cdot U} \quad [-]$$

Relative Contact Area Factor

$$(4.4.18) \quad a_{E3} = \frac{A}{A_M} \quad [-]$$

Estimated Bearing Life

$$(4.4.19) \quad L_H = a_{E1} \cdot a_{E2} \cdot a_{E3} - a_L \quad [h]$$

Note:

Estimated bearing lives greater than 4000 h are subject to error due to inaccuracies in the extrapolation of test data.

4 Bearing Performance

4.5 WORKED EXAMPLES

Cylindrical Bush

| Given: | | | |
|--------------|------------------------------------|--|-----------------------|
| Load Details | Steady Load Continuous Rotation | Inside Diameter D_i | 40 mm 30 mm |
| Shaft | Steel Unlubricated at 25°C | Bearing Load F Rotational Speed N | 5.000 N 25 · 1/min |

| Calculation Constants and Application Factors | | |
|---|---------|---------------------|
| Specific Load Limit p_{lim} | 140 MPa | (Table 8, page 18) |
| Temperature Application Factor a_T | 1.0 | (Table 10, page 19) |
| Material Application Factor a_M | 1.0 | (Table 11, page 20) |
| Bearing Size Factor a_B | 0.85 | (Fig. 20, page 21) |
| Life Correction Constant a_L | 400 | (Table 11, page 20) |

| Calculation | Ref | Value |
|--|--------------------|--|
| Specific Load p [MPa] | (4.4.1) Page 22 | $p = \frac{F}{D_i \cdot B} = \frac{5.000}{40 \cdot 30} = 4.17$ |
| Sliding Speed U [m/s] | (4.3.5) Page 18 | $U = \frac{D_i \cdot \pi \cdot N}{60 \cdot 10^3} = \frac{40 \cdot 3.14 \cdot 25}{60 \cdot 10^3} = 0.052$ |
| High Load Factor a_E [-] must be > 0 | (4.4.4) Page 22 | $a_E = \frac{p_{lim} - p}{p_{lim}} = \frac{140 - 4.17}{140} = 0.97$ |
| Modified pU Factor [MPa · m/s] | (4.4.5) Page 22 | $pU = \frac{5.25 \cdot 10^{-5} F \cdot N}{a_E \cdot B \cdot a_T \cdot a_M \cdot a_B} = 0.27$ |
| Life L_H [h] | (4.4.9) Page 23 | $L_H = \frac{265}{pU} - a_L = \frac{265}{0.27} - 400 = 581$ |

Flanged Bush

| Given: | | | |
|--------------|-----------------------------------|--|--------------------|
| Load Details | Axial Load Continuous Rotation | Flange Outside $\varnothing D_f$ | 23 mm 15 mm |
| Shaft | Steel Unlubricated at 25°C | Bearing Load F Rotational Speed N | 250 N 5 · 1/min |

| Calculation Constants and Application Factors | | |
|---|---------|---------------------|
| Specific Load Limit p_{lim} | 140 MPa | (Table 8, page 18) |
| Temperature Application Factor a_T | 1.0 | (Table 10, page 19) |
| Material Application Factor a_M | 1.0 | (Table 11, page 20) |
| Bearing Size Factor a_B | 1.0 | (Fig. 20, page 21) |
| Life Correction Constant a_L | 400 | (Table 11, page 20) |

| Calculation | Ref | Value |
|--|---------------------|--|
| Specific Load p [N/mm ²] | (4.4.2) Page 22 | $p = \frac{250}{0.04 \cdot (23^2 - 15^2)} = 20.55$ |
| Sliding Speed U [m/s] | (4.3.6) Page 18 | $U = \frac{(23 + 15)}{60 \cdot 10^3} \cdot 3.14 \cdot 5 = 0.005$ |
| High Load Factor a_E [-] must be > 0 | (4.4.4) Page 22 | $a_E = \frac{p_{lim} - p}{p_{lim}} = \frac{140 - 20.55}{140} = 0.853$ |
| Modified pU Factor [N/mm ² · m/s] | (4.4.6) Page 22 | $pU = \frac{6.5 \cdot 10^{-4} \cdot 250 \cdot 5}{0.853 \cdot (23 - 15) \cdot 1 \cdot 1 \cdot 1} = 0.119$ |
| Life L_H [h] | (3.8.11) Page 21 | $L_H = \frac{175}{pU} - a_L = \frac{175}{0.119} - 400 = 1071$ |

Thrust Washer

| Given: | | | |
|--------------|-----------------------------------|--|-----------------------|
| Load Details | Axial Load Continuous Rotation | Outside Diameter D_o | 62 mm 38 mm |
| Shaft | Steel Unlubricated at 25°C | Bearing Load F Rotational Speed N | 6.500 N 10 · 1/min |

| Calculation Constants and Application Factors | | |
|---|---------|---------------------|
| Specific Load Limit p_{lim} | 140 MPa | (Table 8, page 18) |
| Temperature Application Factor a_T | 1.0 | (Table 10, page 19) |
| Material Application Factor a_M | 1.0 | (Table 11, page 20) |
| Bearing Size Factor a_B | 0.85 | (Fig. 20, page 21) |
| Life Correction Constant a_L | 400 | (Table 11, page 20) |

| Calculation | Ref | Value |
|--|---------------------|--|
| Specific Load p [N/mm ²] | (4.4.3) Page 22 | $p = \frac{4 \cdot 6.500}{3.14 \cdot (62^2 - 38^2)} = 3.45$ |
| Sliding Speed U [m/s] | (4.3.6) Page 18 | $U = \frac{(62 + 38)}{60 \cdot 10^3} \cdot 3.14 \cdot 10 = 0.026$ |
| High Load Factor a_E [-] must be > 0 | (4.4.4) Page 22 | $a_E = \frac{p_{lim} - p}{p_{lim}} = \frac{140 - 3.45}{140} = 0.975$ |
| Modified pU Factor [MPa · m/s] | (4.4.7) Page 22 | $pU = \frac{3.34 \cdot 10^{-5} \cdot 6.500 \cdot 10}{0.975 \cdot (62 - 38) \cdot 1 \cdot 1 \cdot 0.85} = 0.11$ |
| Life L_H [h] | (4.4.12) Page 23 | $L_H = \frac{175}{pU} - a_L = \frac{175}{0.11} - 400 = 1191$ |

5 Lubrication

DP4® provides excellent performance in lubricated applications. The following sections describe the basics of lubrication and provide guidance on the application of DP4® in such environments.

5.1 LUBRICANTS

DP4® can be used with most fluids including:

- water
- lubricating oils
- engine oil
- turbine oil
- hydraulic fluid
- solvent
- refrigerants

In general, the fluid will be acceptable if it does not chemically attack the PTFE/lead overlay or the porous

bronze interlayer. Where there is doubt about the suitability of a fluid, a simple test is to submerge a sample of DP4® material in the fluid for two to or three weeks at 15-20 °C above the operating temperature.

The following will usually indicate that the fluid is not suitable for use with DP4®:

- A significant change in the thickness of the DP4® material,
- a visible change in the bearing surface other than some discolouration or staining,
- a visible change in the microstructure of the bronze interlayer.

5.2 TRIBOLOGY

There are three modes of lubricated bearing operation which relate to the thickness of the developed lubricant film between the bearing and the mating surface.

- Hydrodynamic lubrication
- Mixed film lubrication
- Boundary lubrication

These three modes of operation depend upon:

- Bearing dimensions
- Clearance
- Load
- Speed
- Lubricant Viscosity
- Lubricant Flow

Hydrodynamic lubrication

Characterised by:

- Complete separation of the shaft from the bearing by the lubricant film
- Very low friction and no wear of the bearing or shaft since there is no contact.
- Coefficients of friction of 0,001 to 0,01

Hydrodynamic conditions occur when:

$$(5.2.1) \quad p \leq \frac{U \cdot \eta}{7.5} \cdot \frac{B}{D_i} \quad [\text{MPa}]$$




Figure 24: Hydrodynamic lubrication

5 Lubrication

Mixed Film Lubrication

Characterised by:

- Combination of hydrodynamic and boundary lubrication.
- Part of the load is carried by localised areas of self pressurised lubricant and the remainder supported by boundary lubrication.
- Friction and wear depend upon the degree of hydrodynamic support developed.

- DP4® provides low friction and high wear resistance to support the boundary lubricated element of the load.




Figure 25: Mixed film lubrication

Boundary Lubrication

Characterised by:

- Rubbing of the shaft against the bearing with virtually no lubricant separating the two surfaces.
- Bearing material selection is critical to performance
- Shaft wear is likely due to contact between bearing and shaft.
- The excellent self lubricating properties of DP4® material minimises wear under these conditions.

- The dynamic coefficient of friction with DP4® is typically 0.05 to 0.3 under boundary lubrication conditions.
- The static coefficient of friction with DP4® is typically slightly above the dynamic coefficient of friction under boundary lubrication conditions.




Figure 26: Boundary lubrication

5.3 CHARACTERISTICS OF LUBRICATED DP4® BEARINGS

DP4® is particularly effective in the most demanding of lubricated applications where full hydrodynamic operation cannot be maintained, for example:

– High load conditions

In highly loaded applications operating under boundary or mixed film conditions DP4® shows excellent wear resistance and low friction.

– Start up and shut down under load

With insufficient speed to generate a hydrodynamic film the bearing will operate under boundary or mixed film conditions. DP4® minimises wear and requires less start up torque than conventional metallic bearings.

– Sparse lubrication

Many applications require the bearing to operate with less than the ideal lubricant supply, typically with splash or mist lubrication only. DP4® requires significantly less lubricant than conventional metallic bearings.

– Non lubricating fluids

DP4® operates satisfactorily in low viscosity and non lubricating fluids such as water and some process fluids.

Note the following however:

If a DP4 bearing is required to run dry after running in water under non hydrodynamic conditions then the wear resistance will be substantially reduced due to an increased amount of bedding in wear.

Fig. 27, page 28 shows the three lubrication regimes discussed above plotted on a graph of sliding speed vs the ratio of specific load to lubricant viscosity.

– Using the formula in Section 4:

- Calculate the specific load p ,
- calculate the shaft surface speed U .

– Using the viscosity temperature relationships presented in Table 13:

- Determine the viscosity in centipoise of the lubricant.

Note:

Viscosity is a function of operating temperature. If the operating temperature of the fluid is unknown, a provisional temperature of 25 °C above ambient can be used.

| Temperature [°C] | VISCOSITY η [cP] | | | | | | | | | | | | | | |
|------------------|-----------------------|------|------|------|------|------|------|------|------|------|------|-----|-----|-----|-----|
| | 0 | 10 | 20 | 30 | 40 | 50 | 60 | 70 | 80 | 90 | 100 | 110 | 120 | 130 | 140 |
| Lubricant | | | | | | | | | | | | | | | |
| ISO VG 32 | 310 | 146 | 77 | 44 | 27 | 18 | 13 | 9.3 | 7.0 | 5.5 | 4.4 | 3.6 | 3.0 | 2.5 | 2.2 |
| ISO VG 46 | 570 | 247 | 121 | 67 | 40 | 25 | 17 | 12 | 9.0 | 6.9 | 5.4 | 4.4 | 3.6 | 3.0 | 2.6 |
| ISO VG 68 | 940 | 395 | 190 | 102 | 59 | 37 | 24 | 17 | 12 | 9.3 | 7.2 | 5.8 | 4.7 | 3.9 | 3.3 |
| ISO VG 100 | 2110 | 780 | 335 | 164 | 89 | 52 | 33 | 22 | 15 | 11.3 | 8.6 | 6.7 | 5.3 | 4.3 | 3.6 |
| ISO VG 150 | 3600 | 1290 | 540 | 255 | 134 | 77 | 48 | 31 | 21 | 15 | 11 | 8.8 | 7.0 | 5.6 | 4.6 |
| Diesel oil | 4.6 | 4.0 | 3.4 | 3.0 | 2.6 | 2.3 | 2.0 | 1.7 | 1.4 | 1.1 | 0.95 | | | | |
| Petrol | 0.6 | 0.56 | 0.52 | 0.48 | 0.44 | 0.40 | 0.36 | 0.33 | 0.31 | | | | | | |
| Kerosene | 2.0 | 1.7 | 1.5 | 1.3 | 1.1 | 0.95 | 0.85 | 0.75 | 0.65 | 0.60 | 0.55 | | | | |
| Water | 1.79 | 1.30 | 1.0 | 0.84 | 0.69 | 0.55 | 0.48 | 0.41 | 0.34 | 0.32 | 0.28 | | | | |

Table 13: Dynamic viscosity

5 Lubrication

5.4 DESIGN GUIDANCE




Fig. 27: Design guide for lubricated application

Explanation to figure 27

Area 1

The bearing will operate with boundary lubrication and pU factor will be the major determinant of bearing life. The DP4® bearing performance can be calculated using the method given in section 4, although the result will probably underestimate the bearing life

Area 2

The bearing will operate with mixed film lubrication and the pU factor is no longer a significant parameter in determining the bearing life. The DP4® bearing performance will depend upon the nature of the fluid and the actual service conditions.

Area 3

The bearing will operate with hydrodynamic lubrication. The bearing wear will be determined only by the cleanliness of the lubricant and the frequency of start up and shut down.

Area 4

These are the most demanding operating conditions. The bearing is operated under either high speed or high bearing load to viscosity ratio, or a combination of both. These conditions may cause:

- excessive operating temperature and/or
- high wear rate.

The bearing performance may be improved by adding one or more grooves to the bearing and a shaft surface finish $<0.05 \mu\text{m } R_a$.

5.5 CLEARANCES FOR LUBRICATED OPERATION

The recommended shaft and housing diameters given for standard DP4® bushes will provide sufficient clearance for applications operating with boundary lubrication.

For bearings operating with mixed film or hydrodynamic lubrication it may be necessary to improve the fluid flow through the bearing by reducing the recommended shaft diameter by approximately 0.1 %, particularly when the shaft surface speed exceeds 2.5 m/s.

5.6 GROOVING FOR LUBRICATED OPERATION

In demanding applications an axial oil groove will improve the performance of DP4®. Figure 28 shows the recommended form and location of a single groove with respect to the applied load and the bearing split. GGB can manufacture special DP4® bearings with embossed or milled grooves on request.

5.7 MATING SURFACE FINISH FOR LUBRICATED OPERATION

- $R_a \leq 0.4 \pm 0.1 \mu\text{m}$ boundary lubrication
- $R_a = 0.1 - 0.2 \mu\text{m}$ mixed film or hydrodynamic conditions
- $R_a \leq 0.05 \mu\text{m}$ for the most demanding operating conditions

5.8 GREASE LUBRICATION

DP4® is not generally recommended for use with grease lubrication. In particular the following must be avoided:

- Dynamic loads - which can result in erosion of the PTFE/lead bearing surface.
- Greases with EP additives or fillers such as graphite or MoS_2 which can cause rapid wear of DP4®.

Under grease lubrication, improved performance can be obtained by the use of other GGB metal polymer bearing materials, for example, DX®, DX®10, DS, HI-EX®.

Please contact your local sales representative or consult: <https://www.ggbearings.com> for more details.




Fig. 28: Location of oil holes and grooves

6 Bearing Assembly

Dimensions and Tolerances

DP4® bushes are prefinished and excluding very exceptional circumstances, must not be broached, machined or otherwise modified in the bore. It is essential that the correct running clearance is used and that both the diameter of the shaft and the bore of the housing are finished to the limits given in the tables. Under dry running conditions any increase in the clearances given will result in a proportional reduction in performance.

If the bearing housing is unusually flexible the bush will not close in by the calculated amount and the running clearance will be more than the optimum. In these circumstances the housing should be bored slightly undersize or the journal diameter increased, the correct size being determined by experiment.

Where free running is essential, or where light loads (less than 0.1 MPa) prevail and the available torque is low, increased clearance is required and it is recommended that the shaft size quoted in the table be reduced by 0.025 mm.

6.1 ALLOWANCE FOR THERMAL EXPANSION

For operation in high temperature environments the clearance should be increased by the amounts indicated by figure 29 to compensate for the inward thermal expansion of the bearing lining.




Fig. 29: Increase in diametral clearance

If the housing is non-ferrous then the bore should be reduced by the amounts given in Table 14, in order to give an increased interference fit to the bush, with a similar reduction in the journal diameter additional to that indicated by figure 29.

| HOUSING MATERIAL | REDUCTION IN HOUSING DIAMETER PER 100°C RISE | REDUCTION IN SHAFT DIAMETER PER 100°C RISE |
|---------------------|--|--|
| Aluminium alloys | 0.1 % | 0.1 % + values from Fig. 29 |
| Copper base alloys | 0.05 % | 0.05 % + values from Fig. 29 |
| Steel and cast iron | – | values from Fig. 29 |
| Zinc base alloys | 0.15 % | 0.15 % + values from Fig. 29 |

Table 14: Allowance for high temperature

6.2 TOLERANCES FOR MINIMUM CLEARANCE

Where it is required to keep the variation of assembled clearance to a minimum, closer tolerances can be specified towards the upper end of the journal tolerance and the lower end of the housing tolerance. If housings to H6 tolerance are used, then the journals should be finished to the following limits. The sizes in Table 16 give the following nominal clearance range.

| D_i | D_j |
|-----------------|------------------|
| > 5 mm < 25 mm | -0.019 to -0.029 |
| > 25 mm < 50 mm | -0.021 to -0.035 |

Table 15: Shaft tolerances for use with H6 housings

| D_i | D_j |
|-------|----------------|
| 10 mm | 0.009 to 0.080 |
| 50 mm | 0.011 to 0.134 |

Table 16: Clearance vs bearing diameter

Burnishing

The burnishing or fine boring of the bore of an assembled DP4® bush in order to achieve a smaller clearance tolerance is only permissible if a substantial reduction in performance is acceptable. Fig. 24 shows a recommended burnishing tool for the sizing of DP4® bushes.

The coining section of the burnishing tool should be case hardened (case depth 0.6 - 1.2 mm, HRC 60±2) and polished with diamond paste ($R_z \approx 1 \mu\text{m}$). A TiN type surface treatment increases the wear resistance of the burnishing tool and when absent gives a visual indication of burnishing tool wear.

Note: Ball burnishing of DP4® bushes is not recommended.

The values given in Table 17 indicate the dimensions of the burnishing tool required to give specific increases in the bearing bore diameter.

Exact values must be determined by test.

The reduction in bearing performance as a result of burnishing is allowed for in the bearing life calculation by the application factor a_c (Table 12, page 21). The impact of burnishing on the bearing and assembly should be validated by trials.




Fig. 30: Burnishing tool

| ASSEMBLED BUSH INSIDE Ø | REQUIRED BUSH INSIDE Ø | REQUIRED BURNISHING TOOL Ø D_c |
|----------------------------|---------------------------|-------------------------------------|
| $D_{i,a}$ | $D_{i,a} + 0.025$ | $D_{i,a} + 0.06$ |
| $D_{i,a}$ | $D_{i,a} + 0.038$ | $D_{i,a} + 0.08$ |
| $D_{i,a}$ | $D_{i,a} + 0.050$ | $D_{i,a} + 0.1$ |

Table 17: Burnishing tool tolerances

6.3 COUNTERFACE DESIGN

The suitability of mating surface materials and recommendations of mating surface finish for use with DP4® are discussed in detail on page 20.

DP4® is normally used in conjunction with ferrous journals and thrust faces, but in damp or corrosive surroundings, particularly without the protection of oil or grease, stainless steel, hard chromium plated mild steel, or hard anodised aluminium is recommended. When plated mating surfaces are specified the plating should possess adequate strength and adhesion, particularly if the bearing is to operate with high fluctuating loads.

The shaft or thrust collar used in conjunction with the DP4® bush or thrust washer must extend beyond the bearing surface in order to avoid cutting into it. The mating surface must also be free from grooves or flats, the end of the shaft should be given a lead-in chamfer and all sharp edges or projections which may damage the soft overlay of the DP4® must be removed.




Fig. 31: Counterface Design

6 Bearing Assembly

6.4 INSTALLATION

Fitting of Cylindrical Bushes




Fig. 32: Fitting of cylindrical bushes

Fitting of Flanged Bushes




Fig. 33: Fitting of flanged bushes

Insertion Forces




Fig. 34: Maximum Insertion Force F_i

Alignment

Accurate alignment is an important consideration for all bearing assemblies, but is particularly so for dry bearings because there is no lubricant to spread the load. With DP4® bearings misalignment over the length of a bush (or pair of bushes), or over the diameter of a thrust washer should not exceed 0.020 mm as illustrated in Fig. 35.




Fig. 35: Alignment

Sealing

While DP4® can tolerate the ingress of some contaminant materials into the bearing without loss of performance, where there is the possibility of highly abrasive material entering the bearing, a suitable sealing arrangement, as illustrated in Fig. 36 should be provided.




Fig. 36: Recommended sealing arrangements

6.5 AXIAL LOCATION

Where axial location is necessary, it is advisable to fit DP4® thrust washers in conjunction with DP4® bushes, even when the axial loads are low.

Fitting of thrust washers

DP4® thrust washers should be located in a recess as shown in Fig. 37. For the recess diameter the tolerance class [D10] is recommended. The recess depth is given in the product tables, page 44 and following. If a recess is not possible one of the following methods may be used:

- Two dowel pins
- Two screws
- Adhesive
- Soldering (temperature < 320 °C).

6 Bearing Assembly

Important Note

- Ensure the washer ID does not touch the shaft after assembly
- Ensure that the washer is mounted with the steel backing to the housing
- Dowel pins should be recessed 0.25 mm below the bearing surface
- Screws should be countersunk 0.25 mm below the bearing surface
- DP4® must not be heated above 320 °C
- Contact adhesive manufacturers for guidance selection of suitable adhesives
- Protect the bearing surface to prevent contact with adhesive




Fig. 37: Installation of Thrust-Washer

Grooves for Wear Debris Removal

Tests with thrust washers have demonstrated that for optimum dry wear performance at specific loads in excess of 35 MPa, four wear debris removal grooves should be machined in the bearing surface as shown in Fig. 38.

Grooves in bushes have not been found to be beneficial in this respect.




Fig. 38: Debris removal grooves

Slideways

DP4® strip material for use as slideway bearings should be installed using one of the following methods:

- Countersunk screws
- Adhesives
- Mechanical location as shown in Fig. 39




Fig. 39: Mechanical location of DU slideplates

7 Modification

7.1 CUTTING AND MACHINING

The modification of DP4® bearing components requires no special procedures. In general it is more satisfactory to perform machining or drilling operations from the PTFE side in order to avoid burrs. When cutting is done from the steel side, the minimum cutting pressure should be used and care taken to ensure that any steel or bronze particles protruding into the remaining bearing material, and all burrs, are removed.

Drilling Oil Holes

Bushes should be adequately supported during the drilling operation to ensure that no distortion is caused by the drilling pressure.

Cutting Strip Material

DP4® strip material may be cut to size by any one of the following methods.

Care must be taken to protect the bearing surface from damage and to ensure that no deformation of the strip occurs:

- Using side and face cutter, or slitting saw, with the strip held flat and securely on a horizontal milling machine.

- Cropping
- Guillotine (For widths less than 90 mm only)
- Water-jet cutting
- Laser cutting (see Health Warning)

7.2 ELECTROPLATING

DP4® Components

In order to provide some protection in mildly corrosive environments the steel back and end faces of standard range DP4® bearings are tin flashed.

DP4® can be electroplated with most of the conventional electroplating metals including the following:


- zinc ISO 2081
- nickel ISO 1456
- hard chromium ISO 1456

For the harder materials if the specified plating thickness exceeds approximately 5 µm then the housing diameter should be increased by twice the plating thickness in order to maintain the correct assembled bearing bore size.

Where electrolytic attack is possible tests should be conducted to ensure that all the materials in the bearing environment are mutually compatible.

8 Standard Products

8.1 DP4® CYLINDRICAL BUSHES



Dimensions and Tolerances according to ISO 3547 and GGB-Specifications

Outside C_0 and Inside C_i Chamfers

| WALL THICKNESS S_3 | C_0 (a) | | C_i (b) | WALL THICKNESS S_3 | C_0 (a) | | C_i (b) |
|-------------------------|---------------|---------------|--------------|-------------------------|---------------|---------------|--------------|
| | MACHINED | ROLLED | | | MACHINED | ROLLED | |
| 0.75 | 0.5 ± 0.3 | 0.5 ± 0.3 | -0.1 to -0.4 | 2 | 1.2 ± 0.4 | 1.0 ± 0.4 | -0.1 to -0.7 |
| 1 | 0.6 ± 0.4 | 0.6 ± 0.4 | -0.1 to -0.5 | 2.5 | 1.8 ± 0.6 | 1.2 ± 0.4 | -0.2 to -1.0 |
| 1.5 | 0.6 ± 0.4 | 0.6 ± 0.4 | -0.1 to -0.7 | | | | |

(a) = chamfer C_0 machined or rolled at the opinion of the manufacturer

(b) = C_i can be a radius or a chamfer in accordance with ISO 13715

| PART NO. | NOMINAL DIAMETER | | WALL THICKNESS S_3 max. min. | WIDTH B max. min. | SHAFT Ø D_j [h6, f7, h8] max. min. | HOUSING Ø D_H [H6, H7] max. min. | BUSH Ø $D_{i,a}$ ASSEMBLY IN H6/H7 HOUSING max. min. | CLEARANCE C_D max. min. | | | |
|----------|------------------|-------|---|----------------------------|---|---|--|------------------------------------|-------|-------|-------|
| | D_i | D_0 | | | | | | | | | |
| 0203DP4 | 2 | 3.5 | 0.750 0.730 | 3.25 | 2.000 | 3.508 | 2.048 | 0.054 0.000 | | | |
| 0205DP4 | | | | 2.75 | | | | | | | |
| 0303DP4 | 3 | 4.5 | | 5.25 | | | | | 3.000 | 4.508 | 3.048 |
| 0305DP4 | | | | 4.75 | | | | | | | |
| 0306DP4 | | | | 6.25 | | | | | | | |
| 0403DP4 | | | | 5.75 | | | | | | | |
| 0404DP4 | 4 | 5.5 | | 3.25 | 4.000 | 5.508 | 4.048 | | | | |
| 0404DP4 | | | | 2.75 | | | | | | | |
| 0406DP4 | | | | 4.25 | | | | | | | |
| 0410DP4 | | | | 3.75 | | | | | | | |
| 0505DP4 | 5 | 7 | | 6.25 | 4.990 | 7.015 | 5.055 | | | | |
| 0508DP4 | | | | 5.75 | | | | | | | |
| 0510DP4 | | | 10.25 | | | | | | | | |
| 0604DP4 | | | 9.75 | | | | | | | | |
| 0606DP4 | 6 | 8 | 4.25 | 5.990 | 8.015 | 6.055 | | | | | |
| 0606DP4 | | | 3.75 | | | | | | | | |
| 0608DP4 | | | 6.25 | | | | | | | | |
| 0610DP4 | | | 5.75 | | | | | | | | |
| 0705DP4 | 7 | 9 | 8.25 | 6.987 | 9.015 | 7.055 | | | | | |
| 0705DP4 | | | 7.75 | | | | | | | | |
| 0710DP4 | | | 10.25 | | | | | | | | |
| | | | 9.75 | 6.972 | 9.000 | 6.990 | 0.083 0.003 | | | | |

All dimensions in mm

| PART NO. | NOMINAL DIAMETER | | WALL THICKNESS S ₃ max. min. | WIDTH B max. min. | SHAFT Ø D _J [h6, f7, h8] max. min. | HOUSING Ø D _H [H6, H7] max. min. | BUSH Ø D _{i,a} ASSEMBLY IN H6/H7 HOUSING max. min. | CLEARANCE C _D max. min. |
|----------|------------------|------------------|--|----------------------------|--|--|---|---|
| | D _i | D _O | | | | | | |
| 0806DP4 | 8 | 10 | 1.005 0.980 | 6.25 | 7.987 7.972 | 10.015 10.000 | 8.055 7.990 | 0.083 0.003 |
| 0808DP4 | | | | 5.75 | | | | |
| 0810DP4 | | | | 8.25 | | | | |
| 0812DP4 | | | | 7.75 | | | | |
| 1006DP4 | | | | 10.25 | | | | |
| 1008DP4 | 9.75 | 9.987 9.972 | | 12.018 12.000 | 10.058 9.990 | 0.086 0.003 | | |
| 1010DP4 | 12.25 | | | | | | | |
| 1012DP4 | 11.75 | | | | | | | |
| 1015DP4 | 6.25 | | | | | | | |
| 1020DP4 | 5.75 | | | | | | | |
| 1208DP4 | 12 | 14 | | 8.25 | 11.984 11.966 | 14.018 14.000 | 12.058 11.990 | 0.092 0.006 |
| 1210DP4 | | | | 7.75 | | | | |
| 1212DP4 | | | | 10.25 | | | | |
| 1215DP4 | | | | 9.75 | | | | |
| 1220DP4 | | | | 12.25 | | | | |
| 1225DP4 | 11.75 | 12.984 12.966 | | 15.018 15.000 | 13.058 12.990 | 0.092 0.006 | | |
| 1310DP4 | 15.25 | | | | | | | |
| 1320DP4 | 14.75 | | | | | | | |
| 1405DP4 | 20.25 | | | | | | | |
| 1410DP4 | 19.75 | | | | | | | |
| 1412DP4 | 5.25 | 13.984 13.966 | 16.018 16.000 | 14.058 13.990 | 0.092 0.006 | | | |
| 1415DP4 | 4.75 | | | | | | | |
| 1420DP4 | 10.25 | | | | | | | |
| 1425DP4 | 9.75 | | | | | | | |
| 1510DP4 | 12.25 | | | | | 14.984 14.966 | 17.018 17.000 | 15.058 14.990 |
| 1512DP4 | 11.75 | | | | | | | |
| 1515DP4 | 15.25 | | | | | | | |
| 1520DP4 | 14.75 | | | | | | | |
| 1525DP4 | 20.25 | | | | | | | |
| 1610DP4 | 16 | 18 | 10.25 | 15.984 15.966 | 18.018 18.000 | 16.058 15.990 | 0.092 0.006 | |
| 1612DP4 | | | 9.75 | | | | | |
| 1615DP4 | | | 12.25 | | | | | |
| 1620DP4 | | | 11.75 | | | | | |
| 1625DP4 | | | 15.25 | | | | | |
| 1720DP4 | 17 | 19 | 20.25 | 16.984 16.966 | 19.021 19.000 | 17.061 16.990 | 0.095 0.006 | |
| | | | 19.75 | | | | | |

All dimensions in mm

8 Standard Products

| PART NO. | NOMINAL DIAMETER | | WALL THICKNESS S ₃ max. min. | WIDTH B max. min. | SHAFT Ø D _J [h6, f7, h8] max. min. | HOUSING Ø D _H [H6, H7] max. min. | BUSH Ø D _{i,a} ASSEMBLY IN H6/H7 HOUSING max. min. | CLEARANCE C _D max. min. |
|----------|------------------|----------------|--|----------------------------|--|--|---|---|
| | D _i | D _O | | | | | | |
| 1810DP4 | 18 | 20 | 1.005 0.980 | 10.25 | 17.984 17.966 | 20.021 20.000 | 18.061 17.990 | 0.095 0.006 |
| 1815DP4 | | | | 9.75 | | | | |
| 1820DP4 | | | | 15.25 | | | | |
| 1825DP4 | | | | 14.75 | | | | |
| | | | | 20.25 | | | | |
| | 19.75 | | | | | | | |
| | 25.25 | | | | | | | |
| | 24.75 | | | | | | | |
| 2010DP4 | 20 | 23 | 1.505 1.475 | 10.25 | 19.980 19.959 | 23.021 23.000 | 20.071 19.990 | 0.112 0.010 |
| 2015DP4 | | | | 9.75 | | | | |
| 2020DP4 | | | | 15.25 | | | | |
| 2025DP4 | | | | 14.75 | | | | |
| | | | | 20.25 | | | | |
| | 19.75 | | | | | | | |
| | 25.25 | | | | | | | |
| | 24.75 | | | | | | | |
| 2030DP4 | 22 | 25 | 1.505 1.475 | 30.25 | 21.980 21.959 | 25.021 25.000 | 22.071 21.990 | 0.112 0.010 |
| 2215DP4 | | | | 29.75 | | | | |
| 2220DP4 | | | | 15.25 | | | | |
| 2225DP4 | | | | 14.75 | | | | |
| | | | | 20.25 | | | | |
| | 19.75 | | | | | | | |
| | 25.25 | | | | | | | |
| | 24.75 | | | | | | | |
| 2230DP4 | 24 | 27 | 1.505 1.475 | 30.25 | 23.980 23.959 | 27.021 27.000 | 24.071 23.990 | 0.112 0.010 |
| 2415DP4 | | | | 29.75 | | | | |
| 2420DP4 | | | | 15.25 | | | | |
| 2425DP4 | | | | 14.75 | | | | |
| | | | | 20.25 | | | | |
| | 19.75 | | | | | | | |
| | 25.25 | | | | | | | |
| | 24.75 | | | | | | | |
| 2430DP4 | 25 | 28 | 1.505 1.475 | 30.25 | 24.980 24.959 | 28.021 28.000 | 25.071 24.990 | 0.112 0.010 |
| 2515DP4 | | | | 29.75 | | | | |
| 2520DP4 | | | | 15.25 | | | | |
| 2525DP4 | | | | 14.75 | | | | |
| | | | | 20.25 | | | | |
| | 19.75 | | | | | | | |
| | 25.25 | | | | | | | |
| | 24.75 | | | | | | | |
| 2530DP4 | 28 | 32 | 2.005 1.970 | 30.25 | 27.980 27.959 | 32.025 32.000 | 28.085 27.990 | 0.126 0.010 |
| 2550DP4 | | | | 29.75 | | | | |
| 2815DP4 | | | | 50.25 | | | | |
| 2820DP4 | | | | 49.75 | | | | |
| | | | | 15.25 | | | | |
| | 14.75 | | | | | | | |
| | 20.25 | | | | | | | |
| | 19.75 | | | | | | | |
| | 25.25 | | | | | | | |
| | 24.75 | | | | | | | |
| 2830DP4 | 30 | 34 | 2.005 1.970 | 30.25 | 29.980 29.959 | 34.025 34.000 | 30.085 29.990 | 0.126 0.010 |
| 3010DP4 | | | | 29.75 | | | | |
| 3015DP4 | | | | 10.25 | | | | |
| 3020DP4 | | | | 9.75 | | | | |
| | | | | 15.25 | | | | |
| | 14.75 | | | | | | | |
| | 20.25 | | | | | | | |
| | 19.75 | | | | | | | |
| | 25.25 | | | | | | | |
| | 24.75 | | | | | | | |
| 3030DP4 | 32 | 36 | 2.005 1.970 | 30.25 | 31.975 31.950 | 36.025 36.000 | 32.085 31.990 | 0.135 0.015 |
| 3040DP4 | | | | 29.75 | | | | |
| 3040DP4 | | | | 40.25 | | | | |
| | | | | 39.75 | | | | |
| | | | | 20.25 | | | | |
| | 19.75 | | | | | | | |
| 3220DP4 | 32 | 36 | 2.005 1.970 | 30.25 | 31.975 31.950 | 36.025 36.000 | 32.085 31.990 | 0.135 0.015 |
| 3230DP4 | | | | 29.75 | | | | |
| 3240DP4 | | | | 40.25 | | | | |
| | | | | 39.75 | | | | |

All dimensions in mm

| PART NO. | NOMINAL DIAMETER | | WALL THICKNESS S ₃ max. min. | WIDTH B max. min. | SHAFT Ø D _J [h6, f7, h8] max. min. | HOUSING Ø D _H [H6, H7] max. min. | BUSH Ø D _{i,a} ASSEMBLY IN H6/H7 HOUSING max. min. | CLEARANCE C _D max. min. | | | |
|----------|------------------|----------------|--|----------------------------|--|--|---|---|------------------|------------------|------------------|
| | D _i | D _O | | | | | | | | | |
| 3520DP4 | 35 | 39 | 2.005 1.970 | 20.25 | 34.975 34.950 | 39.025 39.000 | 35.085 34.990 | 0.135 0.015 | | | |
| 3530DP4 | | | | 19.75 | | | | | | | |
| 3535DP4 | | | | 30.25 | | | | | | | |
| 3540DP4 | | | | 29.75 | | | | | | | |
| 3550DP4 | | | | 35.25 | | | | | | | |
| 3720DP4 | 37 | 41 | | 34.75 | | | | | 36.975 | 41.025 | 37.085 |
| 4020DP4 | 40 | 44 | | 19.75 | | | | | 39.975 39.950 | 44.025 44.000 | 40.085 39.990 |
| 4030DP4 | | | | 20.25 | | | | | | | |
| 4040DP4 | | | | 30.25 | | | | | | | |
| 4050DP4 | | | | 29.75 | | | | | | | |
| 4520DP4 | | | 40.25 | | | | | | | | |
| 4530DP4 | 45 | 50 | 39.75 | 44.975 44.950 | 50.025 50.000 | 45.105 44.990 | | | | | |
| 4540DP4 | | | 40.25 | | | | | | | | |
| 4545DP4 | | | 39.75 | | | | | | | | |
| 4550DP4 | | | 45.25 | | | | | | | | |
| 5020DP4 | | | 44.75 | | | | | | | | |
| 5030DP4 | 50 | 55 | 49.75 | 49.975 49.950 | 55.030 55.000 | 50.110 49.990 | | | | | |
| 5040DP4 | | | 19.75 | | | | | | | | |
| 5050DP4 | | | 30.25 | | | | | | | | |
| 5060DP4 | | | 29.75 | | | | | | | | |
| 5520DP4 | | | 40.25 | | | | | | | | |
| 5525DP4 | 55 | 60 | 24.75 | 54.970 54.940 | 60.030 60.000 | 55.110 54.990 | | | | | |
| 5530DP4 | | | 20.25 | | | | | | | | |
| 5540DP4 | | | 19.75 | | | | | | | | |
| 5550DP4 | | | 25.25 | | | | | | | | |
| 5555DP4 | | | 29.75 | | | | | | | | |
| 5560DP4 | 30.25 | | | | | | | | | | |
| 6020DP4 | 60 | 65 | 59.75 | 59.970 59.940 | 65.030 65.000 | 60.110 59.990 | | | | | |
| 6030DP4 | | | 20.25 | | | | | | | | |
| 6040DP4 | | | 19.75 | | | | | | | | |
| 6050DP4 | | | 30.25 | | | | | | | | |
| 6060DP4 | | | 29.75 | | | | | | | | |
| 6070DP4 | | | 40.25 | | | | | | | | |
| | | | 39.75 | | | | | | | | |

All dimensions in mm

8 Standard Products

| PART NO. | NOMINAL DIAMETER | | WALL THICKNESS S ₃ max. min. | WIDTH B max. min. | SHAFT Ø D _J [h6, f7, h8] max. min. | HOUSING Ø D _H [H6, H7] max. min. | BUSH Ø D _{i,a} ASSEMBLY IN H6/H7 HOUSING max. min. | CLEARANCE C _D max. min. | | | |
|-----------|------------------|------------------|--|----------------------------|--|--|---|---|--------------------|--------------------|--------------------|
| | D _i | D _O | | | | | | | | | |
| 6530DP4 | 65 | 70 | 2.505 2.460 | 30.25 | f7 | 70.030 70.000 | 65.110 64.990 | 0.170 0.020 | | | |
| 6550DP4 | | | | 29.75 | | | | | 64.970 64.940 | | |
| 6570DP4 | | | | 50.25 49.75 | | | | | | | |
| 7040DP4 | 70.25 69.75 | 69.970 69.940 | | | | | | | | | |
| 7050DP4 | 40.25 39.75 | | | | | | | | | | |
| 7070DP4 | 50.25 49.75 | | | | | | | | | | |
| 7560DP4 | 75 | 80 | | 60.25 | 74.970 74.940 | 80.030 80.000 | 75.110 74.990 | | | | |
| 7580DP4 | | | | 59.75 | | | | | | | |
| 8040DP4 | | | | 80.25 79.75 | | | | | | | |
| 8060DP4 | 80 | 85 | | 40.50 | h8 | 85.035 85.000 | 80.155 80.020 | | 0.209 0.020 | | |
| 8080DP4 | | | | 39.50 | | | | | | | |
| 80100DP4 | | | | 60.50 59.50 | | | | | | | |
| 8530DP4 | | | 80.50 79.50 | | | | | | | | |
| 8560DP4 | 85 | 90 | 100.50 99.50 | 85.000 84.946 | | | | 90.035 90.000 | | 85.155 85.020 | |
| 85100DP4 | | | 30.50 29.50 | | | | | | | | |
| 9060DP4 | | | 60.50 59.50 | | | | | | | | |
| 90100DP4 | 90 | 95 | 100.50 99.50 | 90.000 89.946 | | | | 95.035 95.000 | | 90.155 90.020 | |
| 9560DP4 | | | 60.50 59.50 | | | | | | | | |
| 95100DP4 | | | 100.50 99.50 | | | | | | | | |
| 10050DP4 | 100 | 105 | 50.50 49.50 | h8 | | | | 100.000 99.946 | | 105.035 105.000 | 100.155 100.020 |
| 10060DP4 | | | 60.50 59.50 | | | | | | | | |
| 100115DP4 | | | 115.50 114.50 | | | | | | | | |
| 10560DP4 | 105 | 110 | 60.50 59.50 | | 105.000 104.946 | 110.035 110.000 | 105.155 105.020 | | | | |
| 105115DP4 | | | 115.50 114.50 | | | | | | | | |
| 11060DP4 | | | 60.50 59.50 | | | | | | | | |
| 110115DP4 | 110 | 115 | 115.50 114.50 | | 110.000 109.946 | 115.035 115.000 | 110.155 110.020 | | | | |
| 11550DP4 | | | 50.50 49.50 | | | | | | | | |
| 11570DP4 | | | 70.50 69.50 | | | | | | | | |
| 12050DP4 | 120 | 125 | 50.50 49.50 | | h8 | 120.000 119.946 | 125.040 125.000 | | 120.210 120.070 | | |
| 12060DP4 | | | 60.50 59.50 | | | | | | | | |
| 120100DP4 | | | 100.50 99.50 | | | | | | | | |
| 125100DP4 | 125 | 130 | 100.50 99.50 | 125.000 124.937 | | | | 130.040 130.000 | | 125.210 125.070 | |
| 13060DP4 | | | 60.50 59.50 | | | | | | | | |
| 130100DP4 | | | 100.50 99.50 | | | | | | | | |


All dimensions in mm

| PART NO. | NOMINAL DIAMETER | | WALL THICKNESS S ₃ max. min. | WIDTH B max. min. | SHAFT Ø D _J [h6, f7, h8] max. min. | HOUSING Ø D _H [H6, H7] max. min. | BUSH Ø D _{i,a} ASSEMBLY IN H6/H7 HOUSING max. min. | CLEARANCE C _D max. min. | | | |
|-----------|------------------|----------------|--|----------------------------|--|--|---|---|----------------|---------|---------|
| | D _i | D _O | | | | | | | | | |
| 13560DP4 | 135 | 140 | 2.465 2.415 | 60.50 | 135.000 | 140.040 | 135.210 | 0.273 0.070 | | | |
| 13580DP4 | | | | 59.50 | | | | | 134.937 | 135.070 | |
| 14060DP4 | 140 | 145 | | 60.50 | 140.000 | 145.040 | 140.210 | | | | |
| 140100DP4 | | | | 59.50 | | | | | 139.937 | 140.070 | |
| 15060DP4 | 150 | 155 | | 60.50 | 150.000 | 155.040 | 150.210 | | | | |
| 15080DP4 | | | | 59.50 | | | | | 149.937 | 150.070 | |
| 150100DP4 | | | | 80.50 | | | | | 160.000 | 165.040 | 160.210 |
| 16080DP4 | | | | 79.50 | | | | | | | |
| 160100DP4 | 160 | 165 | | 100.50 | 159.937 | 165.040 | 160.070 | | | | |
| 180100DP4 | | | | 99.50 | | | | | 185.046 | 180.216 | |
| 200100DP4 | 180 | 185 | | 100.50 99.50 | 180.000 | 185.046 | 180.216 | | 0.279 0.070 | | |
| 210100DP4 | 200 | 205 | | | 179.937 | 185.000 | 180.070 | | | | |
| 220100DP4 | 210 | 215 | | | 200.000 | 205.046 | 200.216 | | 0.288 0.070 | | |
| | | | | | 199.928 | 205.000 | 200.070 | | | | |
| 250100DP4 | 220 | 225 | | | 210.000 | 215.046 | 210.216 | | 0.294 0.070 | | |
| | | | | | 209.928 | 215.000 | 210.070 | | | | |
| 300100DP4 | 250 | 255 | 220.000 | | 225.046 | 220.216 | 0.303 0.070 | | | | |
| | | | 219.928 | | 225.000 | 220.070 | | | | | |
| 300100DP4 | 300 | 305 | 250.000 | 255.052 | 250.222 | 0.303 0.070 | | | | | |
| | | | 249.928 | 255.000 | 250.070 | | | | | | |
| | | | | 300.000 | 305.052 | 300.222 | | | | | |
| | | | | 299.919 | 305.000 | 300.070 | | | | | |

All dimensions in mm

8 Standard Products

8.2 DP4® FLANGED BUSHES



Dimensions and Tolerances according to ISO 3547 and GGB-Specifications

Outside C_o and Inside C_i Chamfers

| WALL THICKNESS S ₃ | C _o (a) | | C _i (b) | WALL THICKNESS S ₃ | C _o (a) | | C _i (b) |
|----------------------------------|--------------------|-----------|--------------------|----------------------------------|--------------------|-----------|--------------------|
| | MACHINED | ROLLED | | | MACHINED | ROLLED | |
| 0.75 | 0.5 ± 0.3 | 0.5 ± 0.3 | -0.1 to -0.4 | 2 | 1.2 ± 0.4 | 1.0 ± 0.4 | -0.1 to -0.7 |
| 1 | 0.6 ± 0.4 | 0.6 ± 0.4 | -0.1 to -0.5 | 2.5 | 1.8 ± 0.6 | 1.2 ± 0.4 | -0.2 to -1.0 |
| 1.5 | 0.6 ± 0.4 | 0.6 ± 0.4 | -0.1 to -0.7 | | | | |

(a) = chamfer C_o machined or rolled at the opinion of the manufacturer

(b) = C_i can be a radius or a chamfer in accordance with ISO 13715

| PART NO. | NOMINAL DIAMETER | | WALL THICKNESS S ₃ max. min. | FLANGE THICKN. S _f max. min. | FLANGE Ø D _f max. min. | WIDTH B max. min. | SHAFT Ø D _J [h6, f7, h8] | | HOUSING Ø D _H [H6, H7] | | BUSH Ø D _{i,a} ASSEMBLY IN H6/H7 HOUSING max. min. | CLEARANCE C _D max. min. |
|-----------|------------------|----------------|--|--|--------------------------------------|----------------------|-------------------------------------|------------------|-----------------------------------|----------------|---|---------------------------------------|
| | D _i | D _o | | | | | max. min. | max. min. | max. min. | max. min. | | |
| BB0304DP4 | 3 | 4.5 | 0.750 0.730 | 0.80 0.70 | 7.50 6.50 | 4.25 3.75 | h6 | 3.000 2.994 | H6 | 4.508 4.500 | 3.048 3.000 | 0.054 0.000 |
| BB0404DP4 | 4 | 5.5 | | | 9.50 8.50 | 4.25 3.75 | | 4.000 3.992 | | 5.508 4.500 | 4.048 4.000 | 0.056 0.000 |
| BB0505DP4 | 5 | 7 | 1.005 0.980 | 1.05 0.80 | 10.50 9.50 | 5.25 4.75 | f7 | 4.990 4.978 | H7 | 7.015 7.000 | 5.055 4.990 | 0.077 0.000 |
| BB0604DP4 | 6 | 8 | | | 12.50 11.50 | 4.25 3.75 | | 5.990 5.978 | | 8.015 8.000 | 6.055 5.990 | 0.077 0.000 |
| BB0806DP4 | | | 8 | 10 | 15.50 14.50 | 5.75 5.25 | 7.987 7.972 | 10.015 10.000 | 8.055 7.990 | 0.083 0.003 | | |
| BB0808DP4 | 7.75 | | | | | | | | | | | |
| BB0810DP4 | 10 | 12 | 18.50 17.50 | 7.25 6.75 | 9.987 9.972 | 12.018 12.000 | 10.058 9.990 | 0.086 0.003 | | | | |
| BB1007DP4 | | | | 9.25 | | | | | | | | |
| BB1009DP4 | 10 | 12 | 18.50 17.50 | 9.25 | 11.984 11.966 | 14.018 14.000 | 12.058 11.990 | 0.092 0.006 | | | | |
| BB1012DP4 | | | | 8.75 | | | | | | | | |
| BB1017DP4 | 10 | 12 | 18.50 17.50 | 12.25 11.75 | 13.984 13.966 | 16.018 16.000 | 14.058 13.990 | 0.092 0.006 | | | | |
| BB1207DP4 | | | | 17.25 16.75 | | | | | | | | |
| BB1209DP4 | 12 | 14 | 20.50 19.50 | 7.25 6.75 | 11.984 11.966 | 14.018 14.000 | 12.058 11.990 | 0.092 0.006 | | | | |
| BB1212DP4 | | | | 9.25 | | | | | | | | |
| BB1217DP4 | 12 | 14 | 20.50 19.50 | 8.75 | 13.984 13.966 | 16.018 16.000 | 14.058 13.990 | 0.092 0.006 | | | | |
| BB1412DP4 | | | | 12.25 11.75 | | | | | | | | |
| BB1417DP4 | 14 | 16 | 22.50 21.50 | 17.25 16.75 | 13.984 13.966 | 16.018 16.000 | 14.058 13.990 | 0.092 0.006 | | | | |
| BB1417DP4 | | | | 12.25 11.75 | | | | | | | | |



All dimensions in mm

| PART NO. | NOMINAL DIAMETER | | WALL THICK- NESS S_3 | FLANGE THICKN. S_n | FLANGE Ø D_n | WIDTH B | SHAFT Ø D_j [h6, f7, h8] | HOUSING Ø D_H [H6, H7] | BUSH Ø $D_{i,a}$ ASSEMBLY IN HG/H7 HOUSING | CLEARANCE C_D | | | | | | |
|-----------|------------------|-------|---------------------------|-------------------------|-------------------|----------------|-------------------------------|-----------------------------|--|--------------------|------------------|------------------|------------------|------------------|------------------|------------------|
| | D_i | D_o | | | | | | | | | max. min. | max. min. | max. min. | max. min. | max. min. | max. min. |
| BB1509DP4 | 15 | 17 | 1.005 0.980 | 1.05 0.80 | 23.50 22.50 | 9.25 | 14.984 14.966 | 17.018 17.000 | 15.058 14.990 | 0.092 0.006 | | | | | | |
| BB1512DP4 | | | | | | 8.75 | | | | | | | | | | |
| BB1517DP4 | | | | | | 12.25 11.75 | | | | | | | | | | |
| BB1612DP4 | 16 | 18 | | | 24.50 23.50 | 12.25 11.75 | 15.984 15.966 | 18.018 18.000 | | | 16.058 15.990 | | | | | |
| BB1617DP4 | | | | | | 17.25 16.75 | | | | | | | | | | |
| BB1812DP4 | 18 | 20 | | | 1.505 1.475 | 1.60 1.30 | 26.50 25.50 | 12.25 11.75 | | | 17.984 17.966 | 20.021 20.000 | 18.061 17.990 | 0.095 0.006 | | |
| BB1817DP4 | | | 17.25 16.75 | | | | | | | | | | | | | |
| BB1822DP4 | | | 22.25 21.75 | | | | | | | | | | | | | |
| BB2012DP4 | 20 | 23 | 1.505 1.475 | 1.60 1.30 | | | 30.50 29.50 | 11.75 11.25 | 19.980 19.959 | 23.021 23.000 | 20.071 19.990 | 0.112 0.010 | | | | |
| BB2017DP4 | | | | | | | | 16.75 16.25 | | | | | | | | |
| BB2022DP4 | | | | | | | | 21.75 21.25 | | | | | | | | |
| BB2512DP4 | 25 | 28 | | | | | 1.505 1.475 | 1.60 1.30 | 35.50 34.50 | 11.75 11.25 | | | 24.980 24.959 | 28.021 28.000 | 25.071 24.990 | 0.126 0.010 |
| BB2517DP4 | | | | | | | | | | 16.75 16.25 | | | | | | |
| BB2522DP4 | | | | | | | | | | 21.75 21.25 | | | | | | |
| BB3016DP4 | 30 | 34 | 2.005 1.970 | 2.10 1.80 | | | | | 42.50 41.50 | 16.25 15.75 | 29.980 29.959 | 34.025 34.000 | 30.085 29.990 | 0.135 0.015 | | |
| BB3026DP4 | | | | | | | | | | 26.25 25.75 | | | | | | |
| BB3516DP4 | 35 | 39 | | | | | | | 2.005 1.970 | 2.10 1.80 | 47.50 46.50 | 16.25 15.75 | 34.975 34.950 | | 39.025 39.000 | 35.085 34.990 |
| BB3526DP4 | | | | | 26.25 25.75 | | | | | | | | | | | |
| BB4016DP4 | 40 | 44 | | | 2.505 2.460 | 2.60 2.30 | | | | | 53.50 52.50 | 16.25 15.75 | 39.975 39.950 | | 44.025 44.000 | 40.085 39.990 |
| BB4026DP4 | | | | | | | | | | | | 26.25 25.75 | | | | |
| BB4516DP4 | 45 | 50 | 2.505 2.460 | 2.60 2.30 | | | | | | | 58.50 57.50 | 16.25 15.75 | 44.975 44.950 | 50.025 50.000 | 45.105 44.990 | 0.155 0.015 |
| BB4526DP4 | | | | | | | | | | | | 26.25 25.75 | | | | |

All dimensions in mm

8 Standard Products

8.3 DP4® THRUST WASHERS





Dimensions and Tolerances according to ISO 3547 and GGB-Specifications

| PART NO. | INSIDE DIAMETER D_i | | OUTSIDE DIAMETER D_o | | THICKNESS S_T max. min. | DOWEL HOLE $\emptyset d_p$ max. min. | | RECESS DEPTH H_a max. min. |
|----------|--------------------------|-------|---------------------------|-------|------------------------------------|---|-------------------------------------|---------------------------------------|
| | max. | min. | max. | min. | | $\emptyset d_p$ max. min. | PCD $\emptyset d_p$ max. min. | |
| WC08DP4 | 10.25 | 10.00 | 20.00 | 19.75 | 1.50 1.45 | No Hole | No Hole | 1.20 0.95 |
| WC10DP4 | 12.25 | 12.00 | 24.00 | 23.75 | | 1.875 1.625 | 18.12 17.88 | |
| WC12DP4 | 14.25 | 14.00 | 26.00 | 25.75 | | 2.375 2.125 | 20.12 19.88 | |
| WC14DP4 | 16.25 | 16.00 | 30.00 | 29.75 | | | 22.12 21.88 | |
| WC16DP4 | 18.25 | 18.00 | 32.00 | 31.75 | | 3.375 3.125 | 25.12 24.88 | |
| WC18DP4 | 20.25 | 20.00 | 36.00 | 35.75 | | | 28.12 27.88 | |
| WC20DP4 | 22.25 | 22.00 | 38.00 | 37.75 | | 4.375 4.125 | 30.12 29.88 | |
| WC22DP4 | 24.25 | 24.00 | 42.00 | 41.75 | | | 33.12 32.88 | |
| WC24DP4 | 26.25 | 26.00 | 44.00 | 43.75 | | 61.12 60.88 | 35.12 34.88 | |
| WC25DP4 | 28.25 | 28.00 | 48.00 | 47.75 | | | 38.12 37.88 | |
| WC30DP4 | 32.25 | 32.00 | 54.00 | 53.75 | | 2.00 1.95 | 43.12 42.88 | |
| WC35DP4 | 38.25 | 38.00 | 62.00 | 61.75 | | | 50.12 49.88 | |
| WC40DP4 | 42.25 | 42.00 | 66.00 | 65.75 | | 76.12 75.88 | 54.12 53.88 | |
| WC45DP4 | 48.25 | 48.00 | 74.00 | 73.75 | | | 61.12 60.88 | |
| WC50DP4 | 52.25 | 52.00 | 78.00 | 77.75 | 1.70 1.45 | 65.12 64.88 | | |
| WC60DP4 | 62.25 | 62.00 | 90.00 | 89.75 | | 76.12 75.88 | | |

All dimensions in mm

8.4 DP4® FLANGED WASHERS






Dimensions and Tolerances according to ISO 3547 and GGB-Specifications

| PART NO. | INSIDE DIAMETER D_i | | OUTSIDE DIAMETER D_o | | FLANGE ϕ D_n | | LOCATION ϕ d_p | |
|----------|--------------------------|------|---------------------------|------|------------------------|------|--------------------------|------|
| | max. | min. | max. | min. | max. | min. | max. | min. |
| BS40DP4 | 40.7 | | 75.0 | | 44.00 | | 65.0 | |
| | 40.2 | | 74.5 | | 43.90 | | 64.5 | |
| BS50DP4 | 51.5 | | 85.0 | | 55.00 | | 75.0 | |
| | 51.0 | | 84.5 | | 54.88 | | 74.5 | |
| BS60DP4 | 61.5 | | 95.0 | | 65.00 | | 85.0 | |
| | 61.0 | | 94.5 | | 64.88 | | 84.5 | |
| BS70DP4 | 71.5 | | 110.0 | | 75.00 | | 100.0 | |
| | 71.0 | | 109.5 | | 74.88 | | 99.5 | |
| BS80DP4 | 81.5 | | 120.0 | | 85.00 | | 110.0 | |
| | 81.0 | | 119.5 | | 84.86 | | 109.5 | |
| BS90DP4 | 91.5 | | 130.0 | | 95.00 | | 120.0 | |
| | 91.0 | | 129.5 | | 94.86 | | 119.5 | |
| BS100DP4 | 101.5 | | 140.0 | | 105.00 | | 130.0 | |
| | 101.0 | | 139.5 | | 104.86 | | 129.5 | |

All dimensions in mm

8 Standard Products

8.5 DP4® STRIP





| PART NO. | LENGTH L max. min. | TOTAL WIDTH W | USABLE WIDTH $W_{U \min}$ | THICKNESS S_s max. min. |
|-----------|--------------------------|---------------|------------------------------|---------------------------------|
| S07190DP4 | 503 500 | 200 | 190 | 0.74 |
| S10190DP4 | | | | 0.70 |
| S15190DP4 | | | | 1.01 |
| S20190DP4 | | | | 0.97 |
| | | | | 1.52 |
| | | | | 1.48 |
| S25240DP4 | 254 | 240 | 2.46 | |
| | | | 2.42 | |

All dimensions in mm

8 Standard Products

8.6 DP4-B CYLINDRICAL BUSHES



Dimensions and Tolerances according to ISO 3547 and GGB-Specifications

Outside C_o and Inside C_i Chamfers

| WALL THICKNESS S_3 | C_o (a) | | C_i (b) |
|-------------------------|---------------|---------------|--------------|
| | MACHINED | ROLLED | |
| 0.75 | 0.5 ± 0.3 | 0.5 ± 0.3 | -0.1 to -0.4 |
| 1 | 0.6 ± 0.4 | 0.6 ± 0.4 | -0.1 to -0.5 |
| 1.5 | 0.6 ± 0.4 | 0.6 ± 0.4 | -0.1 to -0.7 |

| WALL THICKNESS S_3 | C_o (a) | | C_i (b) |
|-------------------------|---------------|---------------|--------------|
| | MACHINED | ROLLED | |
| 2 | 1.2 ± 0.4 | 1.0 ± 0.4 | -0.1 to -0.7 |
| 2.5 | 1.8 ± 0.6 | 1.2 ± 0.4 | -0.2 to -1.0 |

(a) = chamfer C_o machined or rolled at the opinion of the manufacturer

(b) = C_i can be a radius or a chamfer in accordance with ISO 13715

| PART NO. | NOMINAL DIAMETER | | WALL THICKNESS S_3 max. min. | WIDTH B max. min. | SHAFT \emptyset D_j [h6, f7, h8] | HOUSING \emptyset D_H [H6, H7] | BUSH $\emptyset D_{i,a}$ ASSEMBLY IN H6/H7 HOUSING max. min. | CLEARANCE C_D max. min. | |
|----------|------------------|--------|---|----------------------------|---|---------------------------------------|--|------------------------------------|----------------|
| | D_i | D_o | | | | | | | |
| 0203DP4B | 2 | 3.5 | 0.750 0.730 | 3.25 | h6 | H6 | 2.048 2.000 | 0.054 0.000 | |
| 0205DP4B | | | | 2.75 | | | | | 1.994 |
| 0306DP4B | 5.25 | 3.000 | | | | | | | |
| 0404DP4B | 4.75 | 2.994 | | | | | | | |
| 0406DP4B | 6.25 | 4.508 | | | | | | | |
| 0406DP4B | 5.75 | 4.500 | | | | | | | |
| 0505DP4B | 4 | 5.5 | | 1.005 0.980 | 4.25 | f7 | H7 | 3.048 3.000 | 0.056 0.000 |
| 0406DP4B | | | | | 3.75 | | | | |
| 0510DP4B | 6.25 | 5.508 | | | | | | | |
| 0510DP4B | 5.75 | 5.500 | | | | | | | |
| 0606DP4B | 8.25 | 7.015 | | | | | | | |
| 0606DP4B | 7.75 | 7.000 | | | | | | | |
| 0608DP4B | 6 | 8 | 1.005 0.980 | | 8.25 | f7 | H7 | 5.055 4.990 | 0.077 0.000 |
| 0610DP4B | | | | | 7.75 | | | | |
| 0610DP4B | 7.25 | 8.015 | | | | | | | |
| 0610DP4B | 10.25 | 8.000 | | | | | | | |
| 0610DP4B | 9.75 | 10.015 | | | | | | | |
| 0610DP4B | 9.75 | 10.000 | | | | | | | |
| 0808DP4B | 8 | 10 | | 1.005 0.980 | 8.25 | f7 | H7 | 6.055 5.990 | 0.083 0.003 |
| 0810DP4B | | | | | 7.75 | | | | |
| 0810DP4B | 10.25 | 7.972 | | | | | | | |
| 0812DP4B | 9.75 | 10.015 | | | | | | | |
| 0812DP4B | 12.25 | 8.055 | | | | | | | |
| 0812DP4B | 11.75 | 7.990 | | | | | | | |
| 1010DP4B | 10 | 12 | 1.005 0.980 | | 10.25 | f7 | H7 | 10.058 9.990 | 0.086 0.003 |
| 1010DP4B | | | | | 9.75 | | | | |
| 1015DP4B | 15.25 | 12.018 | | | | | | | |
| 1015DP4B | 14.75 | 12.000 | | | | | | | |
| 1208DP4B | 8.25 | 12.018 | | | | | | | |
| 1208DP4B | 7.75 | 12.000 | | | | | | | |
| 1210DP4B | 12 | 14 | | 1.005 0.980 | 10.25 | f7 | H7 | 12.058 11.990 | 0.092 0.006 |
| 1210DP4B | | | | | 9.75 | | | | |
| 1212DP4B | 12.25 | 14.018 | | | | | | | |
| 1212DP4B | 11.75 | 14.000 | | | | | | | |
| 1215DP4B | 15.25 | 12.058 | | | | | | | |
| 1215DP4B | 14.75 | 11.990 | | | | | | | |

All dimensions in mm

8 Standard Products

| PART NO. | NOMINAL DIAMETER | | WALL THICKNESS S ₃ max. min. | WIDTH B max. min. | SHAFT Ø D _J [h6, f7, h8] max. min. | HOUSING Ø D _H [H6, H7] max. min. | BUSH Ø D _{i,a} ASSEMBLY IN H6/H7 HOUSING max. min. | CLEARANCE C _D max. min. | | | |
|----------|------------------|----------------|--|----------------------------|--|--|---|---|----------------|------------------|----------------|
| | D _i | D _O | | | | | | | | | |
| 1410DP4B | 14 | 16 | 1.005 0.980 | 10.25 | 13.984 13.966 | 16.018 16.000 | 14.058 13.990 | 0.092 0.006 | | | |
| 1415DP4B | | | | 9.75 | | | | | | | |
| 1420DP4B | | | | 15.25 | | | | | | | |
| 1515DP4B | 14.75 | | | | | | | | | | |
| 1525DP4B | 20.25 | | | | | | | | | | |
| 1615DP4B | 19.75 | | | | | | | | | | |
| 1625DP4B | 15.25 | 15 | | 1.005 0.980 | 14.75 | 14.984 14.966 | 17.018 17.000 | | 0.092 0.006 | | |
| 1820DP4B | 14.75 | | | | | | | | | | |
| 1825DP4B | 25.25 | | | | | | | | | | |
| 2015DP4B | 24.75 | 16 | | | 1.005 0.980 | 15.25 | 15.984 15.966 | | | 18.018 18.000 | 0.092 0.006 |
| 2020DP4B | 14.75 | | | | | | | | | | |
| 2025DP4B | 25.25 | | | | | | | | | | |
| 2030DP4B | 24.75 | 18 | 1.005 0.980 | 20.25 | | 17.984 17.966 | 20.021 20.000 | 0.095 0.006 | | | |
| 2215DP4B | 19.75 | | | | | | | | | | |
| 2220DP4B | 25.25 | | | | | | | | | | |
| 2225DP4B | 24.75 | 20 | | 1.505 1.475 | 15.25 | 19.980 19.959 | 23.021 23.000 | | 0.112 0.010 | | |
| 2515DP4B | 14.75 | | | | | | | | | | |
| 2525DP4B | 20.25 | | | | | | | | | | |
| 2830DP4B | 19.75 | 22 | 1.505 1.475 | | 20.25 | 21.980 21.959 | 25.021 25.000 | 0.112 0.010 | | | |
| 3020DP4B | 14.75 | | | | | | | | | | |
| 3030DP4B | 25.25 | | | | | | | | | | |
| 3040DP4B | 24.75 | 25 | | 2.005 1.970 | 15.25 | 24.980 24.959 | 28.021 28.000 | | 0.126 0.010 | | |
| 3520DP4B | 14.75 | | | | | | | | | | |
| 3530DP4B | 20.25 | | | | | | | | | | |
| 4030DP4B | 19.75 | 28 | 2.005 1.970 | | 30.25 | 27.980 27.959 | 32.025 32.000 | 0.135 0.015 | | | |
| 4050DP4B | 29.75 | | | | | | | | | | |
| 4530DP4B | 29.75 | | | | | | | | | | |
| 4550DP4B | 20.25 | 30 | | 2.005 1.970 | 20.25 | 29.980 29.959 | 34.025 34.000 | | 0.135 0.015 | | |
| 5040DP4B | 19.75 | | | | | | | | | | |
| 5060DP4B | 30.25 | | | | | | | | | | |
| 5540DP4B | 29.75 | 35 | 2.505 2.460 | | 30.25 | 34.975 34.950 | 39.025 39.000 | 0.155 0.015 | | | |
| 6040DP4B | 19.75 | | | | | | | | | | |
| 6050DP4B | 40.25 | | | | | | | | | | |
| 6060DP4B | 39.75 | 40 | | 2.505 2.460 | 30.25 | 39.975 39.950 | 44.025 44.000 | | 0.160 0.015 | | |
| 6070DP4B | 29.75 | | | | | | | | | | |
| | 50.25 | | | | | | | | | | |
| | 49.75 | 45 | 2.505 2.460 | | 40.25 | 44.975 44.950 | 50.025 50.000 | 0.170 0.020 | | | |
| | 29.75 | | | | | | | | | | |
| | 50.25 | | | | | | | | | | |
| | 49.75 | 50 | | 2.505 2.460 | 60.25 | 49.975 49.950 | 55.030 55.000 | | 0.170 0.020 | | |
| | 59.75 | | | | | | | | | | |
| | 59.75 | | | | | | | | | | |
| | 70.25 | 55 | 2.505 2.460 | | 40.25 | 54.970 54.940 | 60.030 60.000 | 0.170 0.020 | | | |
| | 39.75 | | | | | | | | | | |
| | 40.25 | | | | | | | | | | |
| | 39.75 | 60 | | 2.505 2.460 | 50.25 | 59.970 59.940 | 65.030 65.000 | | 0.170 0.020 | | |
| | 49.75 | | | | | | | | | | |
| | 60.25 | | | | | | | | | | |
| | 59.75 | 60 | 2.505 2.460 | | 70.25 | 59.970 59.940 | 65.030 65.000 | 0.170 0.020 | | | |
| | 69.75 | | | | | | | | | | |
| | 69.75 | | | | | | | | | | |

All dimensions in mm


GGBEARINGS.COM

| PART NO. | NOMINAL DIAMETER | | WALL THICKNESS S ₃ max. min. | WIDTH B max. min. | SHAFT Ø D _J [h6, f7, h8] | HOUSING Ø D _H [H6, H7] | BUSH Ø D _{i,a} ASSEMBLY IN H6/H7 HOUSING max. min. | CLEARANCE C _D max. min. | | | |
|------------|------------------|----------------|--|----------------------------|--|--------------------------------------|---|---|------------------|------------------|------------------|
| | D _i | D _O | | | | | | | | | |
| 6570DP4B | 65 | 70 | 2.505 2.460 | 70.25 69.75 | f7 | 70.030 70.000 | 65.110 64.990 | 0.170 0.020 | | | |
| 7050DP4B | 70 | 75 | | 50.25 49.75 | | | | | 64.970 64.940 | | |
| 7070DP4B | | | | 70.25 69.75 | | | | | 69.970 69.940 | | |
| 7580DP4B | 75 | 80 | | 80.25 79.75 | | | | | 74.970 74.940 | 75.030 75.000 | 70.110 69.990 |
| 8060DP4B | 80 | 85 | 2.490 2.440 | 60.50 59.50 | h8 | 80.000 79.946 | 85.035 85.000 | 0.201 0.020 | | | |
| 80100DP4B | | | | 100.50 99.50 | | | | | H7 | | |
| 85100DP4B | 85 | 90 | | 100.50 99.50 | | | | | | 85.000 84.946 | 90.035 90.000 |
| 9060DP4B | 90 | 95 | | 60.50 59.50 | | | | | 90.000 89.946 | 95.035 95.000 | 90.155 90.020 |
| 90100DP4B | | | 100.50 99.50 | | | | | | | | |
| 95100DP4B | 95 | 100 | 100.50 99.50 | 95.000 94.946 | 100.035 100.000 | 95.155 95.020 | 0.209 0.020 | | | | |
| 10060DP4B | 100 | 105 | 60.50 59.50 | 100.000 99.946 | 105.035 105.000 | 100.155 100.020 | | | | | |
| 100115DP4B | | | 115.50 114.50 | | | | | | | | |
| 105115DP4B | 105 | 110 | 115.50 114.50 | 105.000 104.946 | 110.035 110.000 | 105.155 105.020 | | | | | |
| 110115DP4B | 110 | 115 | 115.50 114.50 | 110.000 109.946 | 115.035 115.000 | 115.155 115.020 | | | | | |

All dimensions in mm

8 Standard Products

8.7 DP4-B FLANGED BUSHES



Dimensions and Tolerances according to ISO 3547 and GGB-Specifications

Outside C_o and Inside C_i Chamfers

| WALL THICKNESS S_3 | C_o (a) | | C_i (b) | WALL THICKNESS S_3 | C_o (a) | | C_i (b) |
|-------------------------|---------------|---------------|--------------|-------------------------|---------------|---------------|--------------|
| | MACHINED | ROLLED | | | MACHINED | ROLLED | |
| 0.75 | 0.5 ± 0.3 | 0.5 ± 0.3 | -0.1 to -0.4 | 2 | 1.2 ± 0.4 | 1.0 ± 0.4 | -0.1 to -0.7 |
| 1 | 0.6 ± 0.4 | 0.6 ± 0.4 | -0.1 to -0.5 | 2.5 | 1.8 ± 0.6 | 1.2 ± 0.4 | -0.2 to -1.0 |
| 1.5 | 0.6 ± 0.4 | 0.6 ± 0.4 | -0.1 to -0.7 | | | | |

(a) = chamfer C_o machined or rolled at the opinion of the manufacturer

(b) = C_i can be a radius or a chamfer in accordance with ISO 13715



| PART NO. | NOMINAL DIAMETER | | WALL THICKNESS S_3 | FLANGE THICKN. S_H | FLANGE \varnothing D_H | WIDTH B | SHAFT \varnothing D_j [h6, f7, h8] | | HOUSING \varnothing D_H [H6, H7] | | BUSH \varnothing $D_{i,a}$ ASSEMBLY IN H6/H7 HOUSING | CLEARANCE C_D |
|------------|------------------|-------|----------------------|----------------------|----------------------------|----------------|--|------------------|--------------------------------------|------------------|--|-----------------|
| | D_i | D_o | | | | | max. min. | max. min. | max. min. | max. min. | | |
| BB0304DP4B | 3 | 4.5 | 0.750 0.730 | 0.80 0.70 | 7.50 6.50 | 4.25 3.75 | h6 | 3.000 2.994 | H6 | 4.508 4.500 | 3.048 3.000 | 0.054 0.000 |
| BB0404DP4B | 4 | 5.5 | | | 9.50 8.50 | 4.25 3.75 | | 4.000 3.992 | | 5.508 4.500 | 4.048 4.000 | 0.056 0.000 |
| BB0505DP4B | 5 | 7 | 1.005 0.980 | 1.05 0.80 | 10.50 9.50 | 5.25 4.75 | f7 | 4.990 4.978 | H7 | 7.015 7.000 | 5.055 4.990 | 0.077 0.000 |
| BB0604DP4B | 6 | 8 | | | 12.50 11.50 | 4.25 3.75 | | 5.990 5.978 | | 8.015 8.000 | 6.055 5.990 | 0.077 0.000 |
| BB0608DP4B | | | | | 15.50 14.50 | 5.75 5.25 | | 7.987 7.972 | | 10.015 10.000 | 8.055 7.990 | 0.083 0.003 |
| BB0806DP4B | 8 | 10 | | | 18.50 17.50 | 7.25 6.75 | | 9.987 9.972 | | 12.018 12.000 | 10.058 9.990 | 0.086 0.003 |
| BB1007DP4B | | | | | 20.50 19.50 | 9.25 8.75 | | 11.984 11.966 | | 14.018 14.000 | 12.058 11.990 | 0.092 0.006 |
| BB1012DP4B | 10 | 12 | | | 22.50 21.50 | 12.25 11.75 | | 13.984 13.966 | | 16.018 16.000 | 14.058 13.990 | |
| BB1207DP4B | | | | | 12 | 14 | | 23.50 22.50 | | 12.25 11.75 | 14.984 14.966 | |
| BB1209DP4B | 14 | 16 | | | | | | 24.50 23.50 | | 12.25 11.75 | 15.984 15.966 | |
| BB1417DP4B | | | | | 15 | 17 | | 25.50 22.50 | | 17.25 16.75 | | |
| BB1512DP4B | 16 | 18 | | | | | | 24.50 23.50 | | 17.25 16.75 | | |
| BB1517DP4B | | | | | | | | | | | | |
| BB1612DP4B | | | | | | | | | | | | |
| BB1617DP4B | | | | | | | | | | | | |

All dimensions in mm

| PART NO. | NOMINAL DIAMETER | | WALL THICKNESS S_3 max. min. | FLANGE THICKN. S_{fl} max. min. | FLANGE Ø D_{fl} max. min. | WIDTH B max. min. | SHAFT Ø D_j [h6, f7, h8] max. min. | HOUSING Ø D_H [H6, H7] max. min. | BUSH Ø $D_{i,a}$ ASSEMBLY IN H6/H7 HOUSING max. min. | CLEARANCE C_D max. min. |
|------------|------------------|-------|--------------------------------------|---|-----------------------------------|-------------------------|--|--|---|---------------------------------|
| | D_i | D_o | | | | | | | | |
| BB1812DP4B | 18 | 20 | 1.005 | 1.05 | 26.50 | 12.25 | 17.984 | 20.021 | 18.061 | 0.095 |
| BB1822DP4B | | | 0.980 | 0.80 | 25.50 | 11.75 | | | | |
| BB2012DP4B | 20 | 23 | 1.505 | 1.60 | 30.50 | 11.75 | 19.980 | 23.021 | 20.071 | 0.112 |
| BB2017DP4B | | | | | 29.50 | 11.25 | | | | |
| BB2512DP4B | 25 | 28 | 1.475 | 1.30 | 35.50 | 11.75 | 24.980 | 28.021 | 25.071 | 0.126 |
| BB2522DP4B | | | | | 34.50 | 11.25 | | | | |
| BB3016DP4B | 30 | 34 | 2.005 | 2.10 | 42.50 | 16.25 | 29.980 | 34.025 | 30.085 | 0.135 |
| BB3026DP4B | | | | | 41.50 | 15.75 | | | | |
| BB3526DP4B | 35 | 39 | 1.970 | 1.80 | 47.50 | 26.25 | 34.975 | 39.025 | 35.085 | 0.135 |
| BB4026DP4B | 40 | 44 | | | 46.50 | 25.75 | 34.950 | 39.000 | 34.990 | 35.000 |
| BB4526DP4B | 45 | 50 | 2.505 | 2.60 | 53.50 | 26.25 | 39.975 | 44.025 | 40.085 | 0.135 |
| | | | | | 52.50 | 25.75 | 39.950 | 44.000 | 39.990 | 0.015 |
| | | | 2.460 | 2.30 | 58.50 | 26.25 | 44.975 | 50.025 | 45.105 | 0.155 |
| | | | | | 57.50 | 25.75 | 44.950 | 50.000 | 44.990 | 0.015 |

All dimensions in mm

8.8 DP4-B STRIP



| PART NO. | LENGTH L max. min. | TOTAL WIDTH W | USABLE WIDTH $W_{U \min}$ | THICKNESS S_s max. min. |
|------------|--------------------------|---------------|---------------------------|---------------------------------|
| S07085DP4B | 503 500 | 95 | 85 | 0.74 |
| S10180DP4B | | | | 0.70 |
| S15180DP4B | | 195 | 180 | 1.01 |
| S20180DP4B | | | | 0.97 |
| S25180DP4B | | | | 1.52 |
| | | | | 1.48 |
| | | | | 1.98 |
| | | | | 1.94 |
| | | | | 2.46 |
| | | | | 2.42 |

All dimensions in mm

9 TEST METHODS

9.1 MEASUREMENT OF WRAPPED BUSHES

It is not possible to accurately measure the external and internal diameters of a wrapped bush in the free condition. In its free state a wrapped bush will not be perfectly cylindrical and the butt joint may be open. When correctly installed in a housing the butt joint will be tightly closed and the bush will conform to the housing. For this reason the external diameter and internal diameter of a wrapped bush can only be checked with special gauges and test equipment.

The checking methods are defined in ISO 3547 Parts 1 to 7.

Test A of ISO 3547 Part 2

Checking the external diameter in a test machine with checking blocks and adjusting mandrel.

| TEST A OF ISO 3547 PART 2 ON 2015DP4® | |
|---|---------------------|
| Checking block and setting mandrel $d_{ch,1}$ | 23.062 mm |
| Test force F_{ch} | 4500 N |
| Limits for Δz | 0 and -0.065 mm |
| Bush Outside diameter D_o | 23.035 to 23.075 mm |

Table 18 : Test A of ISO 3547 Part 2




Fig.34 : Test A, data for drawing

Test B (alternatively to Test A)

Check external diameter with GO and NO GO ring gauges.

Test C

Checking the internal diameter of a bush pressed into a ring gauge, which nominal diameter corresponds to the dimension specified in table 6 of ISO 3547 Part 2 (Example $D_i = 20$ mm).

Measurement of Wall Thickness (alternatively to Test C)

The wall thickness is measured at one, two or three positions axially according to the bearing dimensions.




Fig.35 : Test C, data for drawing

| B [mm] | X [mm] | MEASUREMENT POSITION |
|---------------|-----------|----------------------|
| ≤ 15 | B/2 | 1 |
| $>15 \leq 50$ | 4 | 2 |
| $>50 \leq 90$ | 6 and B/2 | 3 |
| >90 | 8 and B/2 | 3 |

Table 19 : Measurement position




Fig.36 : Test C, measurement position

Test D

Check external diameter by precision measuring tape.

10 Bearing Application Data Sheet

Please complete the form below and share it with your GGB sales engineer or send it to: usa@ggbearings.com

DATA FOR BEARING DESIGN CALCULATION

Application: _____

Project/No.: _____ Quantity: _____ New Design Existing Design

Steady load Rotating load Rotational movement Oscillating movement Linear movement

DIMENSIONS [MM]

| | |
|-------------------------|----------|
| Inside diameter | D_i |
| Outside diameter | D_o |
| Length | B |
| Flange Diameter | D_{fl} |
| Flange thickness | B_{fl} |
| Wall thickness | S_T |
| Length of slideplate | L |
| Width of slideplate | W |
| Thickness of slideplate | S_s |


LOAD

Static load
 Dynamic load

| | |
|---------------|-----|
| Axial load F | [N] |
| Radial load F | [N] |

MOVEMENT

| | |
|---------------------|------------|
| Rotational speed | N [1/min] |
| Speed | U [m/s] |
| Length of stroke | L_s [mm] |
| Frequency of stroke | [1/min] |
| Oscillating cycle | ϕ [°] |



| | |
|----------------|-------------------|
| Osc. frequency | N_{osz} [1/min] |
|----------------|-------------------|

MATING SURFACE

| | |
|----------------|---------|
| Material | |
| Hardness | HB/HRC |
| Surface finish | Ra [μm] |

CUSTOMER INFORMATION

Company _____
 Street _____
 City / State / Province / Post Code _____
 Telephone _____ Fax _____
 Name _____
 Email Address _____ Date _____

FITS & TOLERANCES

| | |
|-----------------|-------|
| Shaft | D_j |
| Bearing housing | D_H |

OPERATING ENVIRONMENT

| | |
|--------------------------|---------------|
| Ambient temperature | T_{amb} [°] |
| Bearing housing material | |

Housing with good heating transfer properties
 Light pressing or insulated housing with poor heat transfer properties
 Non metal housing with poor heat transfer properties
 Alternate operation in water and dry

LUBRICATION

Dry
 Continuous lubrication
 Process fluid lubrication
 Initial lubrication only
 Hydrodynamic conditions

| | |
|-------------------|---------------|
| Process fluid | |
| Lubricant | |
| Dynamic viscosity | η [mPas] |

SERVICE HOURS PER DAY


| | |
|------------------------|--|
| Continuous operation | |
| Intermittent operation | |
| Operating time | |
| Days per year | |

SERVICE LIFE


| | |
|-----------------------|-----------|
| Required service life | L_H [h] |
|-----------------------|-----------|

BEARING TYPE


Cylindrical bush




Flanged bush



Thrust washer



Slideplate



Special parts (sketch)

FORMULA SYMBOLS AND DESIGNATIONS

| SYMBOL | UNIT | DESIGNATION |
|------------------|-----------------|---|
| A | mm ² | Surface area of DU® bearing |
| A _M | mm ² | Surface area of mating surface in contact with DU® bearing (slideway) |
| a _B | - | Bearing size factor |
| a _C | - | Application factor for bore burnishing or machining |
| a _E | - | High load factor |
| a _{E1} | - | Specific load factor (slideways) |
| a _{E2} | - | Speed, temperature and material factor (slideways) |
| a _{E3} | - | Relative contact area factor (slideways) |
| a _L | - | Life correction constant |
| a _M | - | Mating surface material factor |
| a _T | - | Temperature application factor |
| B | mm | Nominal bush length |
| C | 1/min | Dynamic load frequency |
| C _D | mm | Installed diametrical clearance |
| C _i | mm | ID chamfer length |
| C _o | mm | OD chamfer length |
| C _T | - | Total number of dynamic load cycles |
| D _C | mm | Diameter of burnishing tool |
| D _{fl} | mm | Nominal bush flange OD |
| D _H | mm | Housing Diameter |
| D _i | mm | Nominal bush and thrust washer ID |
| D _{i,a} | mm | Bush ID when assembled in housing |
| D _J | mm | Shaft diameter |
| D _{Nth} | nvt | Max. thermal neutron dose |
| D _o | mm | Nominal bush and thrust washer OD |
| D _γ | Gy | Max. Gamma radiation dose |
| d _D | mm | Dowel hole diameter |
| d _L | mm | Oil hole diameter |
| d _p | mm | Pitch circle diameter for dowel hole |
| F | N | Bearing load |
| F _{ch} | N | Test force |
| F _i | N | Insertion force |
| f | - | Coefficient of friction |

| SYMBOL | UNIT | DESIGNATION |
|----------------------|---------------------|---|
| H _a | mm | Depth of housing recess (e.g. for thrust washers) |
| H _d | mm | Diameter of housing recess (e.g. for thrust washers) |
| L | mm | Strip length |
| L _H | h | Bearing service life |
| L _S | mm | Length of stroke (slideway) |
| N | 1/min | Rotational speed |
| N _{osz} | 1/min | Oscillating movement frequency |
| p | MPa | Specific load |
| p _{lim} | MPa | Specific load limit |
| p _{sta,max} | MPa | Maximum static load |
| p _{dyn,max} | MPa | Maximum dynamic load |
| Q | - | Permissible number of cycles |
| R _a | μm | Surface roughness (DIN 4768, ISO/DIN 4287/1) |
| R _{OB} | Ω | Electrical resistance |
| s ₃ | mm | Bush wall thickness |
| s _{fl} | mm | Flange thickness |
| s _S | mm | Strip thickness |
| s _T | mm | Thrust washer thickness |
| T | °C | Temperature |
| T _{amb} | °C | Ambient temperature |
| T _{max} | °C | Maximum temperature |
| T _{min} | °C | Minimum temperature |
| U | m/s | Sliding speed |
| W | mm | Strip width |
| W _{U min} | mm | Minimum usable strip width |
| Z _T | - | Total number of cycles |
| α ₁ | 1/10 ⁶ K | Coefficient of linear thermal expansion parallel to surface |
| α ₂ | 1/10 ⁶ K | Coefficient of linear thermal expansion normal to surface |
| σ _c | MPa | Compressive yield strength |
| λ | W/mK | Thermal conductivity |
| φ | ° | Angular displacement |
| η | cP | Dynamic viscosity |

Product Information

GGB assures the products described in this document have no manufacturing errors or material deficiencies.

The details set out in this document are registered to assist in assessing material suitability for intended use. They have been developed from our own investigations as well as generally accessible publications. They do not represent any assurance for the properties themselves.

Unless expressly declared in writing, GGB gives no warranty that the products described are suited for any particular purpose or specific operating circumstances. GGB accepts no liability for any losses, damages, or costs however they may arise through direct or indirect use of these products.

GGB's sales and delivery terms and conditions, included as an integral part of quotations, stock and price lists, apply absolutely to all business conducted by GGB. Copies can be made available on request.

Products are subject to continual development. GGB retains the right to make specification amendments or improvements to technical data without prior announcement. Edition 2021 (this edition replaces earlier editions which hereby lose their validity).

STATEMENT REGARDING LEAD CONTENT IN GGB PRODUCTS & EU DIRECTIVE COMPLIANCE

GGB is committed to adhering to all U.S., European, and international standards and regulations with regard to lead content. We have established internal processes that monitor any changes to existing standards and regulations, and we work collaboratively with customers and distributors to ensure all requirements are strictly followed. This includes RoHS and REACH guidelines.

GGB makes it a top priority to operate in an environmentally conscious and safe manner. We follow numerous industry best practices and are committed to meeting or exceeding a variety of internationally recognized standards for emissions control and workplace safety.

Each of our global locations has management systems in place that adhere to IATF 16949, ISO 9001, ISO 14001, OHSAS 18001, and AS9100D/EN9100 quality regulations.

All of our certificates can be found here: <https://www.ggbearings.com/en/certificates>. A detailed explanation of our commitment to REACH and RoHS directives can be found at <https://www.ggbearings.com/en/who-we-are/quality-and-environment>



THE TRIBOLOGICAL SOLUTION PROVIDER FOR INDUSTRIAL
PROGRESS, REGARDLESS OF SHAPE OR MATERIAL



GGB NORTH AMERICA

700 Mid Atlantic Parkway | Thorofare, New Jersey, 08086 USA

Tel: +1-856-848-3200

<https://www.ggbearings.com/en>



HB104ENG11-21USA