Crestron Flex Advanced Tabletop Medium Room Video Conference System with Lenovo® M920Q ThinkSmart™ Edition Tiny for Microsoft Teams® Rooms



- Tabletop video conferencing solution for a Microsoft Teams® Rooms environment
- Present, call, conference, and collaborate using your own device's UC conference platform (BYOD) or the native Microsoft Teams® Rooms platform
- Native Microsoft Teams® Rooms touch screen UI provides a consistent, simple user experience with one-touch meeting joins
- Complete kit contains a Crestron Flex tabletop conference device, collaboration camera, UC bracket assembly, power supply, and cables — just add a display and mount
- Easy to specify and install no custom design, programming, or software installation required
- Direct connection option between UC Engine and Crestron Flex tabletop conference device for simple installation and configuration
- Network management and provisioning, system alerts, and Crestron Flex tabletop conference device pairing to the system's UC Engine through the XiO Cloud® service
- Premium-level support with Crestron Flex Care (optional)
- Enterprise-grade security connects and communicates securely over any enterprise or SMB network
- Supports single or dual video displays (not included)

The UC-MX50-T-L Crestron Flex advanced tabletop conferencing system provides a medium room video conference solution for use with Microsoft Teams® Rooms software. It supports single or dual video displays¹ (not included) and features a Crestron Flex tabletop conference device, collaboration camera, UC bracket assembly, power supply, and cables.

Native Microsoft Teams® Rooms Experience

The UC-MX50-T-L system brings the full Microsoft Teams Rooms UC experience to any meeting space in an enterprise or SMB facility, whether implementing a cloud based Microsoft Teams Rooms deployment, on-premises Skype® for Business software, or a hybrid of the two.

Intuitive User Interface with Impressive Audio

With a large 7 in. HD color touch screen and an integrated AEC-enabled USB speakerphone that affords full-duplex wideband audio performance, the Crestron Flex Tabletop Conference device (CCS-UC-1-X-T-V) provides a superior conferencing and collaboration experience for meeting rooms, huddle spaces, and executive offices. The conference device also offers optional control of room lighting, shades, thermostats, and other equipment.²

Simplified Deployment

The UC Bracket Assembly provides preassembled components on one ready-to-mount bracket to simplify installation. The assembly can be mounted on a wall, or it can be attached to the rear of the display device. Crestron's direct connection method further simplifies installation with a single connection from the Crestron Flex tabletop conference device to the UC Bracket Assembly.³

High-Definition Video Conferencing

The included collaboration camera (CCS-CAM-USB-F-400) features an ultra wide-angle 150° diagonal field of view to capture an entire conference room in Full HD 1080p video resolution. High precision aspherical optics, 12 MP CMOS sensor, and advanced video processing ensure a clear video image free from light or noise artifacts. Genius Framing digital autozoom detects the people in the room and frames them for an optimal view.

Crestron Control System Integration

The UC-MX50-T-L integrates with a Crestron control system to enable touch screen control of room lighting, motorized window shades, climate control, AV, and other amenities.²

Bring Your Own Device (BYOD)

Conference room visitors can connect their laptop to the Crestron Flex system to use their own UC conference platform. The system's built-in content ingest device switches to the connected laptop's UC platform and returns to the native platform when disconnected.



Crestron Flex Advanced Tabletop Medium Room Video Conference System with Lenovo® M920Q ThinkSmart™ Edition Tiny for Microsoft Teams® Rooms

Enterprise-Grade Security

Crestron Flex is an enterprise-grade solution, engineered in partnership with Microsoft to integrate seamlessly into any Microsoft Teams Rooms or Skype® for Business software deployment. Crestron Flex is ideally equipped for mass deployment throughout any sized corporate, university, medical, military, or government facility.

Easy Provisioning and Device Management

The XiO Cloud service is an IoT cloud based provisioning service (available separately) that enables installers and IT managers to easily deploy and manage thousands of devices. The XiO Cloud service provides system alerts, network management and provisioning, and the pairing of a control device to the system's UC Engine. System updates are controlled by Windows® software update.

Visit www.crestron.com/xiocloud for additional information.

Premium-Level Support

Crestron Flex Care is an optional subscription service that automatically renews annually, providing 24/7 live remote technical support, an extended five year warranty on Crestron® hardware, expedited advance replacements, and a discounted rate for on-site support.

Visit www.crestron.com/flexcare for additional information.

Dual Control Option

A TS- or TSW-70 series 10.1 in. touch screen may be added to the solution as an additional control point for the Microsoft Teams Rooms environment.^{2, 3}

Deployment Resources

View the <u>Crestron Flex Pre-Deployment Checklist</u> to help plan your Crestron Flex installation.

Specifications

Included Components

CCS-UC-1-X-T-V

Crestron Flex tabletop conferencing device:

- PW-2420RU: Universal power supply and power cord
- Cable, CAT5e, RJ-45-to-RJ-45, 12 ft (3.66 m);
- Cable management hardware

UC-BRKT-260-P-T-L-ASSY

UC Bracket Assembly comprised of:

- UC Engine: Lenovo® M920Q ThinkSmart™ Edition Tiny with Microsoft Teams video
- ADPT-USB-ENET: USBto-Ethernet Adapter
- HD-CONV-USB-260: HDMI® over CAT5 to USB 3.0 converter for content ingest
- Mounting hardware

CCS-CAM-USB-F-400 CBL-4K-DP-HD-6

Collaboration Camera
DisplayPort™ to HDMI Cable,
6 ft (1.8 m)

CBL-CAT5E-7

Ethernet LAN cable for UC Engine, RJ-45-to-RJ-45, black,

7 ft (2.1 m)

CBL-HD-6

HDMI Interface Cable, 6 ft

(1.8 m)

CBL-HD-THIN-HS-6

Thin HDMI cable for connecting display device, Type A male-to-male, 6 ft

(1.8 m)

CBL-USB-A-BMICRO-6

USB Cable, USB Type A Male to Micro-B Male cable, 6 ft

(1.8 m)

CBL-USBC-USBA-6

USB 3.0 Cable, Right angle USB-C® to A, 6 ft (1.8 m)

DM-CBL-ULTRA-PC-20

(2) Ethernet LAN cable, CAT6a, RJ-45-to-RJ-45, blue,

20 ft (6.1 m)

UC-CAM-WMK

Wall Mount Kit for Crestron®

Cameras

Crestron Flex tabletop conferencing device

Touch Screen 7 in. (178 mm) diagonal capacitive

multi-touch TFT active matrix color LCD,

1280 x 800 pixels

UI Microsoft Teams Rooms UI plus optional

Crestron room control Ul²

Mic Mute Symbol and (2) Capacitive buttons with bi-color LEDs, either button toggles between mute and

Light Bar unmute



Crestron Flex Advanced Tabletop Medium Room Video Conference System with Lenovo® M920Q ThinkSmart™ Edition Tiny for Microsoft Teams® Rooms

AEC Limes Audio TrueVoice® acoustic echo

cancellation, automatic mic mixing, automatic gain control, and dynamic noise reduction, full-duplex IEEE 1329 Type 1

compliant

Speaker Full range speaker;

Amplifier Power: 11 W;

95 dB SPL at 0.5 m maximum output; Frequency Response: 90 Hz to 22 kHz

Microphones 360° quad mic array;

Pickup Range (typical): 20 ft (6 m) Supports two mic pods, model CCS-UCA-MIC (sold separately)

Microphones
Occupancy

Extension

Sensor

6 ft (1.83 m) PIR range in front of touch

screer

Ethernet 100 Mbps, auto-switching, autonegotiating,

autodiscovery, full/half duplex, DHCP, TCP/IP, UDP/IP, CIP, SSL, TLS, SSH, SFTP (SSH File Transfer Protocol), SRTP, IEEE 802.1X, Active Directory authentication, digest access authentication, password login, XiO Cloud service, Microsoft Intune®

client

USB 2.0 micro Type B device port, supports

UAC for audio interface to UC Engine (cable

ncluded)

Power 24VDC via external 100-240VAC, 50/60 Hz

power pack, model PW-2420RU

NOTE: The CCS-UC-1-X-T-V cannot be powered by Power over Ethernet or PoE+.

Dimensions Height: 4.11 in. (104 mm)

Width: 8.92 in. (227 mm) Depth: 12.74 in. (324 mm)

Weight 5.5 lb (2.5 kg)

Camera

Image Sensor 12 Megapixel 1/2.3 CMOS sensor

Lens High precision, ultra wide angle, six

element aspherical glass lens

Field of View 150° diagonal, 120° horizontal, 90° vertical

Aperture f/2.8

Autozoom Genius Framing automatic lossless digital

zoom intelligently frames around people

in the room

Connectivity Plug-and-play USB 3.1 **Resolution/FPS** HD 1080p @ 30 fps

Dimensions Height: 1.40 in. (36 mm)

Width: 1.60 in. (41 mm) Depth: 2.82 in. (72 mm)

Weight 4.2 oz (120 g)

UC Bracket Assembly

UC Engine Lenovo M920Q ThinkSmart Edition Tiny,

Intel Core® processor with Windows® 10 IoT Edition OS and 100/1000 Mbps Ethernet

connectivity

UC Client Microsoft Teams Rooms with Skype® for

Business software functionality

Management XiO Cloud Service

Client

Content Ingest HDMI input via CAT5 to USB 3.0 converter

(model HD-CONV-USB-260)

Display Output Single or dual display support

Display Output 1080p

Resolution

Power UC Engine: 135 W via external 100-240VAC,

50/60 Hz adapter (included);

HD-CONV-USB-260: 24VDC via external 100-240VAC, 50/60 Hz power pack

(included)

Construction Metal mounting bracket, black,

preassembled with UC Engine and CAT5 to

USB 3.0 content ingest device

(HD-CONV-USB-260)

Mounting Surface wall mount behind the display

device, or attach to the rear of the display device via the bolts attaching the display to

a VESA® compliant display mount;

Bracket includes mounting holes on both side edges, spaced 100, 200, and 300 mm vertically, to allow for attachment to either

side of the display mounting plate

Dimensions Height: 15.00 in. (381 mm)

Width: 14.50 in. (368 mm) Depth: 1.90 in. (48 mm)

Weight 6.64 lb (3 kg)

Crestron Flex Advanced Tabletop Medium Room Video Conference System with Lenovo® M920Q ThinkSmart™ Edition Tiny for Microsoft Teams® Rooms

Model

UC-MX50-T-L

Crestron Flex Advanced Tabletop Medium Room Video Conference System with Lenovo® M920Q ThinkSmart™ Edition Tiny for Microsoft Teams® Rooms

Available Accessories

For a list of available accessories, visit the <u>UC-MX50-T-L</u> product page.

Notes:

- Display must support "Wake on Sync" and "Sleep on No Sync" functionality. Consult the display manufacturer's specifications or internal settings of the specific display.
- Room control capability (lighting, shades, thermostats, etc.) requires
 additional equipment and commissioning to be provided by a Crestron
 authorized integrator and/or programmer. Additional costs may apply.
- 3. Only one control device may be connected via direct connection method.

This product may be purchased from select authorized Crestron dealers and distributors. To find a dealer or distributor, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/How-To-Buy/Find-a-Representative or by calling 855-263-8754.

This product is covered under the Crestron standard limited warranty. Refer to www.crestron.com/warranty for full details.

The specific patents that cover Crestron products are listed online at patents.crestron.com.

Certain Crestron products contain open source software. For specific information, please visit www.crestron.com/opensource.

Crestron, the Crestron logo, and XiO Cloud are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. TrueVoice is either a trademark or registered trademark of Google Inc. in the United States and/or other countries. HDMI is either a trademark or registered trademark of HDMI Licensing LLC in the United States and/or other countries. Intel Core is either a trademark or registered trademark of Intel Corporation in the United States or other countries. Lenovo and ThinkSmart are either trademarks or registered trademarks of Lenovo in the United States and/or other countries. Active Directory, Microsoft Intune, Microsoft Teams, Skype, and Windows are either trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. USB-C is either a trademark or registered trademark of USB Implementers Forum, Inc. in the United States and/or other countries. DisplayPort and VESA are either trademarks or registered trademarks of Video Electronics Standards Association in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography.

Specifications are subject to change without notice.


©2021 Crestron Electronics, Inc.


Rev 06/16/21




Crestron Flex Advanced Tabletop Medium Room Video Conference System with Lenovo® M920Q ThinkSmart™ Edition Tiny for Microsoft Teams® Rooms


Crestron Flex Tabletop Conference Device (CCS-UC-1-X-T-V)











Crestron Flex Advanced Tabletop Medium Room Video Conference System with Lenovo® M920Q ThinkSmart™ Edition Tiny for Microsoft Teams® Rooms

UC Bracket Assembly (UC-BRKT-260-P-T-L-ASSY)

