AP98894F

Power Cord Kit (6 ea), C19 to C20 (90 degree), 1.2m







Overview

Presentation	Low profile cord designed to eliminate space interference when accessing removable hot swap blade modules.
Lead time	Usually in Stock

General

Provided Equipment	Left-angle jumper cords Right-angle jumper cords

Physical

2.01 in (5.1 cm)	
24.02 in (61 cm)	
2.16 lb(US) (0.98 kg)	
4.49 in (11.4 cm)	
	24.02 in (61 cm) 2.16 lb(US) (0.98 kg)

Input

Plug standard	IEC 60320 C20
Input current limits	16 A

Output

Number of power socket outlets	1 IEC 60320 C19

Environmental

Ambient Air Temperature for Operation	23140 °F (-560 °C)	
Relative Humidity	595 %	
Operating altitude	010000 ft	
Ambient Air Temperature for Storage	-13149 °F (-2565 °C)	
Storage Relative Humidity	595 %	
Storage altitude	050000 ft (0.0015240.00 m)	

Ordering and shipping details

Category	11309 - APC RESALE PRODUCTS
GTIN	00731304261995
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	No
Country of origin	US

Packing Units

Package 1 Height	4.02 in (10.2 cm)	
Package 1 width	8.50 in (21.6 cm)	
Package 1 Length	5.98 in (15.2 cm)	

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Compliant EEU RoHS Declaration
Lead free	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	☑ End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
	_ years . epair or . epair