



Overview

Lead time	Usually in Stock
-----------	------------------



General

Provided Equipment	Mounting Hardware Rack Mounting brackets Serial configuration cable
--------------------	---

Physical

Cable length	8 ft (2.44 m)
Color	Black
Depth	9.29 in (23.6 cm)
Height	3.46 in (8.8 cm)
Product Weight	13.96 lb(US) (6.33 kg)
Width	17.01 in (43.2 cm)

Input

Input Frequency	50/60 Hz
Line Rated Current	24 A
Plug standard	NEMA L5-30P
Max line current	30 A
Input current limits	30 A
Load Capacity	2880 VA
Nominal Input Voltage	120 V

Output

Max current draw	30 A
Number of power socket outlets	16 NEMA 5-20R
Protection Type	Circuit breaker
Output voltage	120 V

Conformance

Standards	EN 55022 Class A FCC Part 15 class A
-----------	---

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environmental

Ambient Air Temperature for Operation	23...113 °F (-5...45 °C)
Relative Humidity	5...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
Storage Relative Humidity	5...95 %
Storage altitude	0...50000 ft (0.00...15240.00 m)

Ordering and shipping details

GTIN	00731304333524
Package weight(Lbs)	19.44 lb(US) (8.82 kg)

Packing Units

Package 1 Height	8.27 in (21 cm)
Package 1 width	22.99 in (58.4 cm)
Package 1 Length	14.02 in (35.6 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Lead free	Yes
Mercury free	Yes
RoHS exemption information	Yes
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------