



Overview

Presentation	Provides early detection of water in your data room or critical computing area.
Lead time	Usually in Stock

General

Provided Equipment	Installation guide
--------------------	--------------------

Physical

Color	Orange
Depth	6.34 in (16.1 cm)
Height	2.76 in (7 cm)
Product Weight	0.97 lb(US) (0.44 kg)
Width	6.73 in (17.1 cm)

Environmental

Ambient Air Temperature for Operation	32...131 °F (0...55 °C)
Operating altitude	0...10000 ft
Relative Humidity	0...95 %
Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)
Storage Relative Humidity	0...95 %

Ordering and shipping details

GTIN	00731304209416
Package weight(Lbs)	1.15 lb(US) (0.52 kg)

Packing Units

Package 1 Height	2.80 in (7.1 cm)
Package 1 width	9.21 in (23.4 cm)
Package 1 Length	6.42 in (16.3 cm)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Lead free	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------