

HIKTEHRAN

نماینده مجاز فروش محصولات هایک ویژن



آدرس فروشگاه

تهران ، خیابان جمهوری پاساژ امجد طبقه همکف پلاک 28






شماره تماس











09906500074-66765968-66765923










ایمیل










Info@Hikvisiontehran.com




CONTACT US
HIKVISIONTEHRAN.COM



Turbo HD Camera - DVR			
Items	Description	User Price	
Turbo HD - 1MP			
1	DS-2CE16C0T-IRP 1.0 Megapixel high-performance CMOS - Analog HD output, up to 720P resolution - True Day/Night - Up to 20m IR distance - Video Frame Rate: 720p@25fps/720p@30fps - Min. Illumination : 0.01 Lux - IP66 weatherproof - DNR, Smart IR	IRR 3,730,000	
2	DS-2CE56C0T-IRP 1.0 Megapixel high-performance CMOS - Analog HD output, up to 720P resolution - True Day/Night - Up to 20m IR distance - Video Frame Rate: 720p@25fps/720p@30fps - Min. Illumination : 0.01 Lux - IP66 weatherproof - DNR, Smart IR	IRR 3,800,000	
3	DS-2CE56C0T-IRPF 1.0 Megapixel high-performance CMOS - Analog HD output, up to 720P resolution - True Day/Night - Up to 20m IR distance - Video Frame Rate: 720p@25fps/720p@30fps - Min. Illumination : 0.01 Lux - IP66 weatherproof - DNR, Smart IR - Switchable TVI/AHD/CVI/CVBS	IRR 4,070,000	
Turbo HD - 2MP			
5	DS-2CE16D0T-IF 2 MP high performance CMOS - 1920 x 1080 resolution - 2.8 mm, 3.6 mm fixed lens - Up to 20 m IR distance - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP66 weatherproof - True Day/Night, Smart IR	IRR 4,540,000	
6	DS-2CE56D0T-IPF 2 MP high performance CMOS - 1920 x 1080 resolution - 2.8 mm, 3.6 mm fixed lens - Up to 20 m IR distance - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - True Day/Night, Smart IR	IRR 3,680,000	









7	DS-2CE16D0T-IR	2 MP high performance CMOS - 1920 × 1080 resolution - 2.8 mm, 3.6 mm fixed lens - Up to 20 m IR distance - IP66 weatherproof - True Day/Night, Smart IR - Material Metal	IRR 5,440,000	
8	DS-2CE56D0T-IR	2 MP high performance CMOS - 1920 × 1080 resolution - 2.8 mm, 3.6 mm fixed lens - Up to 20 m IR distance - IP66 weatherproof - True Day/Night, Smart IR	IRR 5,280,000	
9	DS-2CE56D0T-IRM	2 MP high performance CMOS - 1920 × 1080 resolution - 2.8 mm, 3.6 mm fixed lens - Up to 20 m IR distance - IP66 weatherproof - True Day/Night, Smart IR - Material Metal	IRR 5,445,000	
10	DS-2CE16D0T-IT1	,2 MP CMOS Sensor, 2 pcs EXIR LEDs, 20m IR, Outdoor EXIR Bullet, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, IP66, 3.6/6mm Lens - IP66 weatherproof	تماس	
11	DS-2CE16D0T-IT3	2 MP CMOS Sensor, 2 pcs EXIR LEDs, 40m IR, Outdoor EXIR Bullet, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, IP66, 3.6/6/8/12/16mm Lens - IP66 weatherproof	IRR 7,640,000	
12	DS-2CE56D0T-IT1	2 MP CMOS Sensor, 2 pcs EXIR LEDs, 20m IR, Outdoor EXIR Eyeball, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, IP66, 3.6/6mm Lens - IP66 weatherproof	تماس	
13	DS-2CE16D0T-VFIR3F	2 MP high performance CMOS - 1920 × 1080 resolution - 2.8 mm, 3.6 mm fixed lens - Up to 40 m IR distance - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP66 weatherproof - True Day/Night, Smart IR - Lens 2.8 - 12 mm @ F1.4	IRR 12,250,000	
14	DS-2CE56D0T-VFIR3F	2 MP high performance CMOS - 1920 × 1080 resolution - 2.8 mm, 3.6 mm fixed lens - Up to 40 m IR distance - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP66 weatherproof - True Day/Night, Smart IR - Lens 2.8 - 12 mm @ F1.4	IRR 12,250,000	
15	Turbo HD - 2MP built-in PoC			
16	DS-2CE16D0T-IRE	2M HD1080p CMOS Sensor , EXIR, 20m IR, Outdoor EXIR Eyeball, ICR, 12 VDC & built-in PoC , Smart IR DNR, OSD Menu, IP66, 2.8/3.6/6mm Lens	IRR 6,650,000	
17	DS-2CE16D0T-IT1E	2M HD1080p CMOS Sensor , EXIR, 20m IR, Outdoor EXIR Eyeball, ICR, 12 VDC & built-in PoC , Smart IR DNR, OSD Menu. IP66, 2.8/3.6/6mm Lens	تماس	









18	DS-2CE56D0T-IT1E	2M HD1080p CMOS Sensor , EXIR, 20m IR, Outdoor EXIR Eyeball, ICR, 12 VDC & built-in PoC , Smart IR DNR, OSD Menu, IP66, 2.8/3.6/6mm Lens	IRR 7,990,000	
19	DS-2CE56D0T-IT3E	2M HD1080p CMOS Sensor , EXIR, 40m IR, Outdoor EXIR Eyeball, ICR, 12 VDC & built-in PoC , Smart IR DNR, OSD Menu, IP66, 2.8/3.6/6mm Lens	تماس	
20	DS-2CE16D0T-VFIR3E	2M HD1080p CMOS Sensor , EXIR, 40m IR, Outdoor EXIR Eyeball, ICR, 12 VDC & built-in PoC , Smart IR DNR, OSD Menu , IP66 - Lens 2.8 - 12 mm @ F1.4	تماس	
21	DS-2CE56D0T-VFIR3E	2M HD1080p CMOS Sensor , EXIR, 40m IR, Outdoor EXIR Eyeball, ICR, 12 VDC & built-in PoC , Smart IR DNR, OSD Menu IP66 - Lens 2.8 - 12 mm @ F1.4	تماس	
22	Turbo HD - 2MP built-in PoC - Starlight Value Series			
23	DS-2CE16D8T-ITE	2.0 megapixel high-performance CMOS, EXIR 2.0, smart IR, up to 20 m IR distance, Outdoor EXIR Bullet, ICR, Ultra Low-Light 0.005 Lux/F1.2 , 12 VDC/ built-in PoC , Smart IR, 3D DNR , OSD Menu, 120 dB True WDR , IP67, 2.8/3.6/6mm Lens	IRR 10,300,000	
24	DS-2CE56D8T-ITME	2.0 megapixel high-performance CMOS, EXIR 2.0, smart IR, up to 20 m IR distance, Outdoor EXIR Bullet, ICR, Ultra Low-Light 0.005 Lux/F1.2 , 12 VDC/ built-in PoC , Smart IR, 3D DNR , OSD Menu, 120 dB True WDR , IP67, 2.8/3.6/6mm Lens	IRR 10,080,000	
25	DS-2CE16D8T-IT3E	2.0 megapixel high-performance CMOS, EXIR 2.0, smart IR, up to 40 m IR distance, Outdoor EXIR Bullet, ICR, Ultra Low-Light 0.005 Lux/F1.2 , 12 VDC/ built-in PoC , Smart IR, 3D DNR , OSD Menu, 120 dB True WDR , IP67 , 2.8/3.6/6mm Lens	تماس	
26	DS-2CE16D8T-IT3ZE	2.0 megapixel high-performance CMOS, EXIR 2.0, smart IR, up to 40 m IR distance, Outdoor EXIR Bullet, ICR, Ultra Low-Light 0.005 Lux/F1.2 , 12 VDC/ built-in PoC , Smart IR, 3D DNR , OSD Menu, 120 dB True WDR , 2.8 mm to 12 mm motorized vari-focal lens - IP67	IRR 17,600,000	
27	DS-2CE56D8T-IT1E	2.0 megapixel high-performance CMOS, EXIR 2.0, smart IR, up to 20 m IR distance, Outdoor EXIR Bullet, ICR, Ultra Low-Light 0.005 Lux/F1.2 , 12 VDC/ built-in PoC , Smart IR, 3D DNR , OSD Menu, 120 dB True WDR , IP67, 2.8/3.6/6mm Lens	IRR 10,590,000	










28	DS-2CE38D8T-PIR	2.0 megapixel progressive scan CMOS - Ultra-Low Light PIR Cube Camera - Color: 0.005 Lux @ (F1.2, AGC ON), 0 Lux with IR - 2.8 mm, 3.6 mm fixed focal lens - Backlight Compensation: WDR/BLC/OFF - Motion Detection: 4 programmable motion areas	تماس	
29	Turbo HD - 3MP			
30	DS-2CE16F1T-IT	3 Megapixel high-performance CMOS - Analog HD output, up to 3MP resolution - 2.8mm, 3.6mm, 6mm lens - True Day/Night - OSD menu, DNR, Smart IR - EXIR technology, up to 20m IR distance - IP66 weatherproof	IRR 6,800,000	
31	DS-2CE56F1T-ITM	3 Megapixel high-performance CMOS - Analog HD output, up to 3MP resolution - 2.8mm, 3.6mm, 6mm lens - True Day/Night - OSD menu, DNR, Smart IR - EXIR technology, up to 20m IR distance - IP66 weatherproof	IRR 6,800,000	
32	DS-2CE16F1T-IT1	3 Megapixel high-performance CMOS - Analog HD output, up to 3MP resolution - 2.8mm, 3.6mm, 6mm lens - True Day/Night - OSD menu, DNR, Smart IR - EXIR technology, up to 20m IR distance - IP66 weatherproof	تماس	
33	DS-2CE16F1T-IT3	3 Megapixel high-performance CMOS - Analog HD output, up to 3MP resolution - 2.8mm, 3.6mm, 6mm lens - True Day/Night - OSD menu, DNR, Smart IR - EXIR technology, up to 40m IR distance - IP66 weatherproof	تماس	
34	DS-2CE16F1T-IT5	3 Megapixel high-performance CMOS - Analog HD output, up to 3MP resolution - 2.8mm, 3.6mm, 6mm lens - True Day/Night - OSD menu, DNR, Smart IR - EXIR technology, up to 80m IR distance - IP66 weatherproof	تماس	
35	DS-2CE56F1T-IT1	3 Megapixel high-performance CMOS - Analog HD output, up to 3MP resolution - 2.8mm, 3.6mm, 6mm lens - True Day/Night - OSD menu, DNR, Smart IR - EXIR technology, up to 20m IR distance - IP66 weatherproof	IRR 7,150,000	
36	DS-2CE56F1T-IT3	3 Megapixel high-performance CMOS - Analog HD output, up to 3MP resolution - 2.8mm, 3.6mm, 6mm lens - True Day/Night - OSD menu, DNR, Smart IR - EXIR technology, up to 40m IR distance - IP66 weatherproof	IRR 8,030,000	
37	DS-2CE16F7T-IT3Z	3 Megapixel high-performance CMOS - Analog HD output, up to 3MP resolution - 2.8-12mm motorized varifocal lens - True Day/Night - OSD menu, DNR, Smart IR - True WDR , up to 120dB - EXIR technology, up to 40m IR distance - IP66 weatherproof	تماس	









38	DS-2CE56F7T-IT3Z	3 Megapixel high-performance CMOS - Analog HD output, up to 3MP resolution - 2.8-12mm motorized vari-focal lens - True Day/Night - OSD menu, DNR, Smart IR - True WDR , up to 120dB - EXIR technology, up to 40m IR distance - IP66 weatherproof	IRR 20,160,000	
39	Turbo HD - 5MP			
40	DS-2CE16H0T-ITF	5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 20 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	IRR 8,560,000	
41	DS-2CE16H0T-IT1F	5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 20 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	IRR 9,340,000	
42	DS-2CE16H0T-IT3F	5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	IRR 10,080,000	
43	DS-2CE16H0T-IT5F	5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 80 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	تماس	
44	DS-2CE16H0T-IT3ZF	5 MP high performance COMS - 2560 × 1944 resolution - 2.7 mm to 13.5 mm motorized vari-focal lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	IRR 17,390,000	
45	DS-2CE56H0T-ITMF	5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	تماس	
46	DS-2CE56H0T-IT1F	5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	IRR 9,580,000	
47	DS-2CE56H0T-IT3F	5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	IRR 9,850,000	

48	DS-2CE56H0T-IT3ZF	5 MP high performance COMS - 2560 x 1944 resolution - 2.7 mm to 13.5 mm motorized vari-focal lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	IRR 17,140,000	
49 Turbo HD - 5MP - built-in PoC				
50	DS-2CE16H1T-ITE	5 MP high-performance CMOS - 2560 x 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed focal lens - EXIR 2.0, smart IR, up to 20 m IR distance - OSD menu, DNR, DWDR - IP67- PoC.af - Up the coax	IRR 9,150,000	

51	DS-2CE16H1T-IT1E	5 MP high-performance CMOS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed focal lens - EXIR 2.0, smart IR, up to 20 m IR distance - OSD menu, DNR, DWDR - IP67- PoC.af - Up the coax	IRR 9,980,000	
52	DS-2CE16H1T-IT3E	5 MP high-performance CMOS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed focal lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, DNR, DWDR - IP67- PoC.af - Up the coax	IRR 10,780,000	
53	DS-2CE16H1T-IT5E	5 MP high-performance CMOS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed focal lens - EXIR 2.0, smart IR, up to 80 m IR distance - OSD menu, DNR, DWDR - IP67- PoC.af	تماس	
54	DS-2CE16H1T-IT3ZE	5 MP high-performance CMOS - 2560 × 1944 resolution - 2.8 mm to 12 mm motorized vari-focal lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, DNR, DWDR - IP67 - PoC.at	IRR 18,600,000	
55	DS-2CE56H1T-ITME	5 MP high-performance CMOS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed focal lens - EXIR 2.0, smart IR, up to 20 m IR distance - OSD menu, DNR, DWDR - IP67- PoC.af	IRR 9,150,000	
56	DS-2CE56H1T-IT1E	5 MP high-performance CMOS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed focal lens - EXIR 2.0, smart IR, up to 20 m IR distance - OSD menu, DNR, DWDR - IP67- PoC.af	IRR 12,100,000	
57	DS-2CE56H1T-IT3E	5 MP high-performance CMOS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed focal lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, DNR, DWDR - IP67- PoC.af	IRR 10,500,000	
58	DS-2CE56H1T-IT3ZE	5 MP high-performance CMOS - 2560 × 1944 resolution - 2.8 mm to 12 mm motorized vari-focal lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, DNR, DWDR - IP67 - PoC.at	تماس	
59	DS-2CC52H1T-FITS	5MP IR Fisheye Camera, 5 Megapixel high-performance CMOS, Analog HD output, up to 5MP resolution, 0.01Lux @ (F1.2,AGC ON), 0 Lux with IR, IR cut filter with auto switch, OSD menu, Built-in microphone, 1-ch audio output	تماس	
60	TURBO HD 5MP (TURBO HD 5.0) PIR Series			

61	DS-2CE11H0T-PIRL	5 MP high performance CMOS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm fixed focal lens - PIR detection, visual alarm - EXIR 2.0, smart IR, up to 20 m IR distance - IP67 - Up the coax (HIKVISION-C) - 0.01 Lux@(F1.2, AGC ON), 0 Lux with IR	تماس	
62	DS-2CE12H0T-PIRL	5 MP high performance CMOS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm fixed focal lens - PIR detection, visual alarm - EXIR 2.0, smart IR, up to 20 m IR distance - IP67 - Up the coax (HIKVISION-C) - 0.01 Lux@(F1.2, AGC ON), 0 Lux with IR	تماس	
63	DS-2CE71H0T-PIRL	5 MP high performance CMOS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm fixed focal lens - PIR detection, visual alarm - EXIR 2.0, smart IR, up to 20 m IR distance - IP67 - Up the coax (HIKVISION-C) - 0.01 Lux@(F1.2, AGC ON), 0 Lux with IR	IRR 8,700,000	
64	Turbo HD - 8MP			
65	DS-2CE78U8T-IT3	4K Ultra-Low Light Turret Camera - 8.29 Megapixel high-performance CMOS - Ultra-low light - 3840 × 2160 resolution - 2.8 mm, 3.6 mm, 6 mm fixed focal lens - 120 dB true WDR, 3D DNR - EXIR 2.0, smart IR, up to 60m IR distance - IP67	IRR 28,720,000	
66	DS-2CE18U8T-IT3	4K Ultra-Low Light Bullet Camera - 8.29 Megapixel high-performance CMOS - Ultra-low light - 3840 × 2160 resolution - 2.8 mm, 3.6 mm, 6 mm fixed focal lens - 120 dB true WDR, 3D DNR - EXIR 2.0, smart IR, up to 60m IR distance - IP67	IRR 30,240,000	
67	Turbo HD PTZ Camera			
68	DS-2AE5223TI-A (24VAC)	1/3" CMOS, 1920x1080:30fps, TVI & CVBS dual output - 3D DNR, ICR, Color: 0.05lux/F1.4, B/W:0.005lux/F1.4, Optical Zoom:23x, Focus:4.0-92mm, Digital Zoom:16X, Pan range:360° endless; Tilt range: -15°~90°(Auto Flip), Pan Speed: 0.1° - 400°/s, Tilt Speed: 0.1° -120°/s, Up the Coax, 150m IR	تماس	
69	DS-2AE7230TI-A (24VAC)	High performance 1/3" CMOS - Max. image resolution: 1920 × 1080 - Min. illumination: Color: 0.05Lux @ (F1.6,AGC ON); B/W: 0.005Lux @ (F1.6, AGC ON); 0 Lux with IR - 30x optical zoom, focal length 4-120mm - 16x digital zoom - 120m IR distance - IR cut filter - 3D DNR, Digital WDR, BLC - TVI and CVBS dual output	تماس	
70	Turbo HD DVR 720P / 1080p lite			
71	DS-7208HGHI-F1	<u>Analog video input</u> 8-ch - <u>Encoding resolution</u> 1080p lite/HD 720p lite/WD1/4CIF/VGA/CIF - <u>Video compression</u> H.264+/H.264 - Full channel recording at up to 1080p lite resolution - <u>Frame rate</u> : 1080p lite/HD 720p lite/WD1/4CIF/VGA@12fps; CIF@25fps (P)/30fps (N) - <u>IP video input</u> 2-ch (up to 10-ch) Up to 2 MP resolution - Support H.264+/H.264 IP cameras - <u>Audio input</u> 1-ch - <u>HDMI output</u> 1-ch, 1920 × 1080/60Hz - <u>Capacity</u> 1 SATA interface Up to 6 TB capacity	IRR 19,050,000	

72	DS-7216HGHI-K1	<p>Analog video input 16-ch - Encoding resolution 1080p lite/720p/VGA/WD1/4CIF/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 1080p lite resolution - Frame rate: 1080p lite/720p lite/WD1/4CIF/VGA@15fps; CIF@25fps (P)/30fps (N) - IP video input : 2-ch (up to 18-ch) Up to 5 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output 1-ch, 1920 x 1080/60Hz - Audio input 1-ch, RCA - Capacity 1 SATA interface Up to 10 TB capacity</p>	IRR 23,540,000	
73	Turbo HD DVR 1080p / 3MP / 4MP lite			
74	DS-7204HQHI-K1	<p>Analog video input 4-ch - Encoding resolution 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - Frame rate: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - IP video input : 2-ch (up to 6-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output 1-ch, 1920 x 1080/60Hz - Audio input 1-ch, RCA - Capacity 1 SATA interface Up to 10 TB capacity</p>	IRR 16,130,000	
75	DS-7108HQHI-K1	<p>Analog video input 8-ch - Encoding resolution 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - Frame rate: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - IP video input : 4-ch (up to 12-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output 1-ch, 1920 x 1080/60Hz - Audio input 1-ch, RCA - Capacity 1 SATA interface Up to 6 TB capacity</p>	IRR 22,726,000	
76	DS-7208HQHI-K1/Eco	<p>Analog video input 8-ch - Encoding resolution 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - Frame rate: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - IP video input : 4-ch (up to 12-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output 1-ch, 1920 x 1080/60Hz - Audio input 1-ch, RCA - Capacity 1 SATA interface Up to 10 TB capacity - ECO CASE</p>	IRR 22,800,000	
77	DS-7208HQHI-K1	<p>Analog video input 8-ch - Encoding resolution 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - Frame rate: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - IP video input : 4-ch (up to 12-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output 1-ch, 1920 x 1080/60Hz - Audio input 1-ch, RCA - Capacity 1 SATA interface Up to 10 TB capacity</p>	IRR 24,330,000	
78	DS-7116HQHI-K1	<p>Analog video input 16-ch - Encoding resolution 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - Frame rate: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - IP video input : 8ch (up to 24-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output : 1-ch, 4K (3840 x 2160)/30Hz - Audio input 1-ch, RCA - Capacity 1 SATA interface Up to 6 TB capacity</p>	IRR 35,590,000	
79	7216HQHI-K1-Eco	<p>Analog video input 16-ch - Encoding resolution 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - Frame rate: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - IP video input : 8ch (up to 24-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output : 1-ch, 4K (3840 x 2160)/30Hz - Audio input 1-ch, RCA - Capacity 1 SATA interface Up to 10 TB capacity - ECO CASE</p>	تماس	
80	DS-7216HQHI-K1	<p>Analog video input 16-ch - Encoding resolution 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - Frame rate: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - IP video input : 8ch (up to 24-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output : 1-ch, 4K (3840 x 2160)/30Hz - Audio input 1-ch, RCA - Capacity 1 SATA interface Up to 10 TB capacity</p>	IRR 41,740,000	
81	DS-7216HQHI-K2	<p>Analog video input 16-ch - Encoding resolution 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - Frame rate: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - IP video input : 8ch (up to 24-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output : 1-ch, 4K (3840 x 2160)/30Hz - Audio input 1-ch, RCA - Capacity 2 SATA interface Up to 10 TB capacity for each disk</p>	IRR 46,200,000	

82	DS-7224HQHI-K2	<u>Analog video input</u> 24-ch - <u>Encoding resolution</u> 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - <u>Frame rate</u> : 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - <u>IP video input</u> : 8ch (up to 32-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> : 1-ch, 4K (3840 x 2160)/30Hz - <u>Audio input</u> 1-ch, RCA - <u>Capacity</u> 2 SATA interface Up to 10 TB capacity for each disk	تماس	
83	DS-7232HQHI-K2	<u>Analog video input</u> 24-ch - <u>Encoding resolution</u> 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - <u>Frame rate</u> : 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - <u>IP video input</u> : 8ch (up to 40-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> : 1-ch, 4K (3840 x 2160)/30Hz - <u>Audio input</u> 1-ch, RCA - <u>Capacity</u> 2 SATA interface Up to 10 TB capacity for each disk	IRR 80,390,000	
84	Turbo HD DVR 1080p / 3MP / 4MP / 5MP / 8MP lite			
85	DS-7204HUHI-K1	<u>Analog video input</u> 4-ch - <u>Encoding resolution</u> 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - 8 MP@8 fps is only available for channel 1 of DS-7204HUHI-K1 - <u>Frame rate</u> : 8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - <u>IP video input</u> : 4-ch (up to 8-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 1920 x 1080/60Hz - <u>Audio input</u> 4-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity	IRR 26,550,000	
86	DS-7208HUHI-K1	<u>Analog video input</u> 8-ch - <u>Encoding resolution</u> 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - <u>Frame rate</u> : 8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - <u>IP video input</u> : 8-ch (up to 16-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 4K (3840 x 2160)/30Hz - <u>Audio input</u> 4-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity	تماس	
87	DS-7216HUHI-K2	<u>Analog video input</u> 16-ch - <u>Encoding resolution</u> 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - <u>Frame rate</u> : 8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - <u>IP video input</u> : 16-ch (up to 32-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 4K (3840 x 2160)/30Hz - <u>Audio input</u> 4-ch, RCA - <u>Capacity</u> 2 SATA interface Up to 10 TB capacity for each disk	IRR 73,990,000	
88	Turbo HD DVR 1080p / 3MP / 4MP / 5MP / 8MP lite (Built in PoC Series)			
89	DS-7204HUHI-K1/P	<u>Analog video input</u> 4-ch - <u>Encoding resolution</u> 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - 8 MP@8 fps is only available for channel 1 of DS-7204HUHI-K1 - <u>Frame rate</u> : 8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - <u>IP video input</u> : 4-ch (up to 8-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch 2K (2560 x 1440)/60Hz - <u>Audio input</u> 4-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity - Provide power supply to PoC cameras over coaxial cable	IRR 28,510,000	
90	DS-7208HUHI-K2/P	<u>Analog video input</u> 8-ch - <u>Encoding resolution</u> 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - <u>Frame rate</u> : 8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - <u>IP video input</u> : 8-ch (up to 12-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 4K (3840 x 2160)/30Hz - <u>Audio input</u> 4-ch, RCA - <u>Capacity</u> 2 SATA interface Up to 10 TB capacity for each disk - Provide power supply to PoC cameras over coaxial cable	IRR 53,190,000	
91	Turbo HD DVR 1080p / 3MP / 4MP / 5MP / 8MP			
92	DS-7204HTHI-K1	<u>Analog video input</u> 4-ch - <u>Encoding resolution</u> 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 8 MP resolution - <u>Frame rate</u> : 8 MP@15 fps, 5 MP@20 fps, 3 MP@18 fps 4 MP/1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - <u>IP video input</u> : 4-ch (up to 8-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 4K (3840 x 2160)/30Hz - <u>Audio input</u> 4-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity	IRR 30,240,000	







93











DS-7208HTHI-K2











Analog video input 8-ch - Encoding resolution 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Frame rate: 8 MP@15 fps, 5 MP@20 fps, 3 MP@18 fps 4 MP/1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - IP video input : 8-ch (up to 16-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output 1-ch, 4K (3840 x 2160)/30Hz - Audio input 4-ch, RCA - Capacity 2 SATA interface Up to 10 TB capacity for each disk











IRR 58,790,000






















Network Camera - NVR			
Items	Description	User Price	
Lite Mini Bullet Series			
1	DS-2CD1023G0E-I 2.0 MP IR Network Bullet Camera -1/2.8" progressive scan CMOS - Max. Frame Rate: 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720 - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP67 - Dual stream - Digital WDR (Wide Dynamic Range) - ECO CASE	IRR 14,100,000	
2	DS-2CD1023G0-I 2.0 MP IR Network Bullet Camera -1/2.8" progressive scan CMOS - Max. Frame Rate: 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720 - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP67 - Dual stream - Digital WDR (Wide Dynamic Range)	IRR 14,650,000	
3	DS-2CD1031-I 1/3" progressive scan CMOS- Up to 3.0 megapixel- 2.8mm/4mm/6mm fixed focal lens Up to 30 m IR range- Dual stream- Digital WDR (Wide Dynamic Range) 3D DNR (Digital Noise Reduction) - PoE (Power over Ethernet) - IP67	تماس	
4	DS-2CD1043G0-I 4.0 MP IR Network Bullet Camera, 1/3" progressive scan CMOS , 3D DNR (Digital Noise Reduction), 2560 × 1440@20fps - Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264 , IP67, Dual stream, Digital WDR (Wide Dynamic Range)	IRR 20,500,000	
5	DS-2CD1053G0-I 5.0 MP IR Network Bullet Camera, 1/3" progressive scan CMOS , 3D DNR (Digital Noise Reduction), 2560 × 1920@12.5fps - Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264 , IP67, Dual stream, True 120db WDR	IRR 21,800,000	
Lite Dome Series			
7	DS-2CD1123G0E-I 2MP dome Exir, fixed lens 2.8mm, white color-1/2.8" progressive scan CMOS - 3D DNR (Digital Noise Reduction) - 1920 × 1080@30fps - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP67, IK10 - Digital WDR (Wide Dynamic Range) - ECO CASE	IRR 15,400,000	










8	DS-2CD1123G0-I	2MP dome Exir, fixed lens 2.8mm,white color-1/2.8" progressive scan CMOS - 3D DNR (Digital Noise Reduction) - 1920 x 1080@30fps - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP67, IK10 - Digital WDR (Wide Dynamic Range)	IRR 15,680,000	
9	DS-2CD1323G0E-I	1/2.8" progressive scan CMOS - 1920 x 1080@30fps - 2.8 mm/4 mm/6 mm fixed lens - H.264+, H.264 - Dual stream - Digital WDR (Wide Dynamic Range) - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - PoE (Power over Ethernet) - IP67 - ECO CASE	تماس	
10	DS-2CD1323G0-I	1/2.8" progressive scan CMOS - 1920 x 1080@30fps - 2.8 mm/4 mm/6 mm fixed lens - H.265+, H.265, H.264+, H.264 - Dual stream - Digital WDR (Wide Dynamic Range) - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - PoE (Power over Ethernet) - IP67	IRR 14,850,000	
11	DS-2CD1131-I	1/3" progressive scan CMOS- Up to 3.0 megapixel- 2.8 mm/4 mm/6 mm fixed focal lens Up to 30 m IR rang-Dual stream- Digital WDR (Wide Dynamic Range)- 3D DNR (Digital Noise Reduction) - PoE (Power over Ethernet) - IP67, Ik10	تماس	
12	DS-2CD1143G0-I	4.0 MP IR Network Dome Camera, 1/3" progressive scan CMOS - 3D DNR (Digital Noise Reduction), 2560 x 1440@20fps - Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens ,PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264 - IP67, IK10, Dual stream, Digital WDR (Wide Dynamic Range)	IRR 21,080,000	
13	Mini Bullet Series			
14	DS-2CD2020F-I	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (6mm optional), H.264/MJPEG, dual-stream, IP66, DWDR, 3D DNR, BLC, Support on-board storage (SD card not included), IR range: up to 30m	تماس	
15	DS-2CD2023G0-I	2 MP IR Fixed Bullet Network Camera - 1/3" Progressive Scan CMOS - 1920 x 1080@30fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 22,870,000	
16	DS-2CD2043G0-I	4 MP IR Fixed Bullet Network Camera - 1/3" Progressive Scan CMOS - 2560 x 1440@30fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 26,120,000	
17	DS-2CD2052-I	1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920: 20fps, 4mm/F2.0 lens (6mm optional), H.264+/H.264/MJPEG, 3 streams,IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 30m	IRR 25,680,000	
18	DS-2CD2063G0-I	6 MP IR Fixed Bullet Network Camera - 1/2.9" Progressive Scan CMOS - 3072 x 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	تماس	











19	DS-2CD2083G0-I	8 MP IR Fixed Bullet Network Camera - 1/2.5" Progressive Scan CMOS - 3840 x 2160 @15 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI/HLC - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	تماس	
20	Dome Series			
21	DS-2CD2120F-I	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (2.8mm, 6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 30m, Support on-board storage (SD card not included), Support Mobile Monitoring via EZVIZ P2P	تماس	
22	DS-2CD2120F-IS	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (2.8mm, 6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 30m, Support on-board storage (SD card not included), Support Mobile Monitoring via EZVIZ P2P -S: Audio/Alarm IO connectors	IRR 22,000,000	
23	DS-2CD2123G0-IS	2 MP IR Fixed Dome Network Camera - 1/2.8" Progressive Scan CMOS - 1920 x1080@30fps - 2.8/4/6/8mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 Lux @ (F2.0, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI/HLC - IP67 - IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128GB S: Audio/Alarm IO connectors	IRR 24,670,000	
24	DS-2CD2143G0-IS	4 MP IR Fixed Dome Network Camera - 1/3" Progressive Scan CMOS, 2688 x1520@30fps, 2.8/4/6/8mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams -120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67- IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB S: Audio/Alarm IO connectors	IRR 26,730,000	
25	DS-2CD2152F-IS	1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920: 20fps, 4mm/F2.0 lens (6mm optional), H.264+/H.264/MJPEG, 3 streams, IP67, IK10, DC12V & PoE, DWDR, 3D DNR, BLC, support on-board storage up to 128GB(SD card not included), 3-axis adjustment, IR range: up to 30m, Vandal-proof -housing, HIK-Connect cloud service - S: Audio/Alarm IO connectors	IRR 27,000,000	
26	DS-2CD2163G0-IS	6 MP IR Fixed Dome Network Camera - 1/2.9" Progressive Scan CMOS - 3072 x 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - S: Audio/Alarm IO connectors	IRR 31,870,000	
27	DS-2CD2183G0-IS	8 MP IR Fixed Dome Network Camera - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.5" Progressive Scan CMOS - 3840 x 2160 @15 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection -120dB WDR - S: Audio/Alarm IO connectors	IRR 37,520,000	
28	Bullet Series			
29	DS-2CD2T35FWD-I8	Up to 3 megapixel high resolution-Max. 2048 x 1536 @30fps - 2.8 mm/4mm/6mm/8 mm/12mm fixed lens,- optional - Ultra-low light-265, H.265+, H.264+, H.264- 120dB Wide Dynamic Range - 3D Digital Noise Reduction 12 VDC & PoE (802.3af) - IR range: 50m, 80m, optional- Support on board storage, up to 128 GB - IP67	تماس	
30	DS-2CD2T43G0-I5	1/3" Progressive Scan CMOS,2688 x1520@30fps,2.8/4/6/8mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR, H.265+, H.265, H.264+, H.264,Three streams,120dB WDR,2 Behavior analyses, and face detection,BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB-up to 50m IR range	IRR 29,140,000	











31	DS-2CD2T52-I5	1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920:20fps, 4mm/F1.4 lens (6mm optional), H.264+/H.264/MJPEG, 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, HIK-Connect cloud service, 2pcs EXIR LEDs, up to 50m IR range	تماس	
32	DS-2CD2T63G0-I5	6 MP IR Fixed Bullet Network Camera - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.9" Progressive Scan CMOS - 3072 x 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR	تماس	
33	DS-2CD2T63G0-I8	6 MP IR Fixed Bullet Network Camera - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.9" Progressive Scan CMOS - 3072 x 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - up to 80m IR range	IRR 35,470,000	
34	DS-2CD2T83G0-I5	8 MP IR Fixed Bullet Network Camera - 1/2.5" Progressive Scan CMOS -3840 x 2160 @15 fps 2.8/4/6/8 mm fixed lens □ Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 G	تماس	
35	DS-2CD2T83G0-I8	8 MP IR Fixed Bullet Network Camera - 1/2.5" Progressive Scan CMOS -3840 x 2160 @15 fps 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 G-up to 80m IR range	IRR 42,150,000	
36	Exir Dome Series			
37	DS-2CD2322WD-I	Up to 2 megapixel high resolution - Full HD1080p video - Dual stream - 2.8mm/4mm/6mm fixed lens - 120dB Wide Dynamic Range - 3D Digital Noise Reduction - Backlight Compensation - DC12V & PoE - Support H.264+ - High performance EXIR LED - Up to 30m IR range - IP67 weather proof protection - 3-axis adjustment - Mobile Monitoring via EZVIZ P2P or Hik-Connect	IRR 22,930,000	
38	DS-2CD2342FWD-I	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, EXIR range: up to 30m	تماس	
39	DS-2CD2352-I	1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920:20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264+/H.264/MJPEG, 3 streams, IP67, DC12V & PoE, DWDR, 3D DNR, BLC, EXIR range: up to 30m	تماس	
40	Mini Dome Series			
41	DS-2CD2523G0-IS	1/2.7" Progressive Scan CMOS - 1920 x 1080@30fps - H.265+/H.265/H.264+/H.264/MJPEG - IR: up to 10 m 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR - Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR -S: Built-in MIC, audio/alarm IO	تماس	
42	DS-2CD2542FWD-IS	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F2.0 lens (2.8mm, 6mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 10m, support on-board storage up to 128GB(SD card not included), HIK-Connect cloud service-S: Built-in MIC, audio/alarm IO	IRR 35,100,000	













43	DS-2CD2543G0-IS	1/3" Progressive Scan CMOS - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 lux @(F1.6, AGC ON), 0 lux with IR - 2688 x 1520@30fps - IR: up to 10 m - H.265+/H.265/H.264+/H.264/MJPEG - 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR -S: Built-in MIC, audio/alarm IO	تماس	
44	DS-2CD2563G0-IS	1/3" Progressive Scan CMOS - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 lux @(F1.6, AGC ON), 0 lux with IR - 3072 x 2048@20fps - IR: up to 10 m - H.265+/H.265/H.264+/H.264/MJPEG - 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR -S: Built-in MIC, audio/alarm IO	تماس	
45	Lite Bullet Vari-Facal Motorized Series			
46	DS-2CD1623G0-I	2MP Bullet Network camera - 2.8-12mm varifocal lens - EXIR - 1/2.8" progressive scan CMOS - BLC/3D DNR/ROI1920 x 1080@30fps - Up to 30 m IR range - IP67 - Digital WDR - H.265+, H.265, H.264+, H.264Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 30,000,000	
47	DS-2CD1623G0-IZ	2MP Bullet Network camera - 2.8-12mm varifocal lens - EXIR - 1/2.8" progressive scan CMOS - BLC/3D DNR/ROI1920 x 1080@30fps - Up to 30 m IR range - IP67 - Digital WDR - H.265+, H.265, H.264+, H.264Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Z:Motorized VF lens	IRR 33,410,000	
48	DS-2CD1643G0-I	4 MP EXIR VF Bullet Network Camera, 1/3" progressive scan CMOS - BLC/3D DNR/ROI - 2560 x 1440@20fps ,Up to 30 m IR range, 2.8 mm to 12 mm varifocal lens - IP67- H.265+, H.265, H.264+, H.264 - 120dB True WDR - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON) - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 35,980,000	
49	Lite Dome Vari-Facal Series			
50	DS-2CD1723G0-I	2 MP VF Dome Network camera - 1/2.8" progressive scan CMOS - 3D DNR (Digital Noise Reduction) - 1920 x 1080@30fps - Up to 30 m IR range - 2.8 mm to 12 mm manual vari-focal lens - PoE (Power over Ethernet) - IP67, IK10 - H.265+, H.265, H.264+, H.264 - Dual stream - Digital WDR	IRR 29,400,000	
51	DS-2CD1743G0-I	4 MP VF Network Dome Camera, 1/3" progressive scan CMOS - 3D DNR (Digital Noise Reduction), 2560 x 1440@20fps - Up to 30 m IR range, 2.8 mm to 12 mm manual vari-focal lens, PoE (Power over Ethernet) - IP67, H.265+, H.265, H.264+, H.264, Dual stream, 120 dB True WDR	IRR 32,380,000	
52	Bullet Vari-Facal Motorized Series			
53	DS-2CD2620F-I	2 MP IR VF Bullet Network Camera - 1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Support Mobile Monitoring via EZVIZ P2P	تماس	
54	DS-2CD2632F-I	3 MP IR VF Bullet Network Camera - 1/3" Progressive CMOS, ICR, 0lux with IR, 2048x1536:25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/MJPEG/H.264+ , dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Support Mobile Monitoring via EZVIZ P2P	IRR 34,950,000	
55	DS-2CD2643G0-IZS	4 MP IR VF Bullet Network Camera - 1/3" Progressive Scan CMOS - 2688 x1520@30fps - 2.8 to 12 mm varifocal lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with I - H.265+, H.265, H.264+, H.264 - Three streams - IR Range up to 50m - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Z:Motorized VF lens	IRR 53,970,000	














56	DS-2CD2663FG0-IZS	6 MP IR VF Bullet Network Camera - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.9" Progressive Scan CMOS - 3072 × 2048@20 fps -2.8 to 12 mm varifocal lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - IR Range up to 50m - 120dB WDR - 2 Behavior analyses, and face detection - Z:Motorized VF lens	تماس	
57	DS-2CD2683G0-IZS	8 MP(4K) IR Vari-focal Bullet Network Camera - 1/2.5" Progressive Scan CMOS - 3840 ×2160@15fps - 2.8 to 12 mm varifocal lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - IR Range up to 50m - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI • IP67, IK10 - Z:Motorized VF lens	تماس	
58	Dome Vari-Facal Motorized Series			
59	DS-2CD2720F-I	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Vandal-proof, Support Mobile Monitoring via EZVIZ P2P	IRR 26,500,000	
60	DS-2CD2720F-IZ	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Vandal-proof, Support Mobile Monitoring via EZVIZ P2P - Z: Motorized VF lens	IRR 33,000,000	
61	DS-2CD2723G0-IZS	2MP IR Motorized NETWORK DOME CAMERA 1/2.8 " 2MP progressive scan CMOS Up to 1920 × 1080 resolution (25 fps) 2.8~12 mm Motorized lens , 0 lux IR on Max IR distance: 30 meters H.265+,H.265,H.264+,H.264,MJPEG video compression 3DDNR,BLC, WDR(120dB),ROI,VCA,Micro SD (Up to 128 GB), Reset Button 1 Audio I/O , 1 Alarm I/O PoE, DC12V, IP67,IK10,3 axis adjustment Onvif support - Z: Motorized VF lens	تماس	
62	DS-2CD2743G0-IZS	4 MP IR VF Dome Network Camera - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Max IR distance: 30 meters - 3-Axis adjustment - 1/3" Progressive Scan CMOS - 2560 × 1440@30fps - 2.8 to 12 mm Varifocal lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams - 120dB WDR - 2 behavior analyses, and face detection - Digital Noise Reduction 3D DNR - Z: Motorized VF lens	IRR 53,970,000	
63	DS-2CD2763G0-IZS	6 MP IR Vari-focal Dome Network Camera - 1/2.9" Progressive Scan CMOS - 3072 ×2048@20fps - 2.8 to 12 mm varifocal lens - Max IR distance: 30 meters - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Z: Motorized VF lens	تماس	
64	DS-2CD2783G0-IZS	8 MP(4K) IR Vari-focal Dome Network Camera - 1/2.5" Progressive Scan CMOS - 3840 ×2160@15fps - Max IR distance: 30 meters - 2.8 to 12 mm varifocal lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - 120dB WDR - 2 Behavior analyses, and face detectio - BLC/3D DNR/ROI - IP67 - IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Z: Motorized VF lens	تماس	
65	Fish Eye Series			
66	DS-2CD2942F-IS	Color: 0.01lux @(F1.2, AGC ON), 0.018lux @(F1.6, AGC ON), 0 lux with IR - 2560 × 1440 -1.6mm, F1.6 Angle of view: 186°(horizontal), 106°(vertical) -H.264/MJPEG - 50Hz: 12.5fps(2560 × 1440), 25fps(1920 × 1080, 1280 × 720) 60Hz: 15fps(2560 × 1440) - 30fps(1920 × 1080, 1280 × 720) -8 meters - 12 VDC ± 10%, PoE (802.3af)	تماس	










67	DS-2CD2955FWD-IS	5 MP Network Fisheye Camera, Up to 5 megapixel high resolution, 2560 × 1920 @30fps, H.265, H.265+, H.264+, H.264, Support 14 display modes, FOV: horizontal FOV 180°, vertical FOV 180°, Dual video streams, DC12V & PoE (802.3af), Digital Noise Reduction, Support on-board storage, up to 128 GB, Up to 8m IR range, -S: Audio/Alarm IO	IRR 64,710,000	
68	Cube Smart Series			
69	DS-2CD2420F-IW	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (2.8mm, 6mm optional), H.264/MJPEG, dual-stream, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 10m, Support on-board card slot (SD card not included), Support Mobile Monitoring via EZVIZ P2P -W: Built-in Wi-Fi with WPS	تماس	
70	DS-2CD2423G0-IW	1/2.7" Progressive Scan CMOS - 1920 × 1080@30fps - IR: 10 m - PIR: 10m - H.265, H.265+ 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR - Wi-Fi (Optional) - Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 lux @ (F2.0, AGC ON), 0 lux with IR -W: Built-in Wi-Fi with WPS	IRR 20,560,000	
71	DS-2CD2442FWD-IW	1/3" Progressive CMOS, ICR, 0.01lux/F1.2, 2688x1520:20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR range: up to 10m, support on-board storage up to 128GB (SD card not included), -W: Built-in Wi-Fi with WPS	تماس	
72	DS-2CD2443G0-IW	1/3" Progressive Scan CMOS - 2688 × 1520@30fps - IR: 10 m - PIR: 10m - 120dB WDR - Video Compression: H.265+/H.265/H.264+/H.264/MJPEG - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - Lens 2.8 mm, horizontal FOV: 98°, vertical FOV: 55° -W: Built-in Wi-Fi with WPS	IRR 25,440,000	
73	Pin Hole Series			
74	DS-2CD2D14WD	1 MP Pin Hole Camera - 1/4" Progressive CMOS, Electronic Day/night, Color: 0.01lux/F1.2, B/W: 0.001lux/F1.2, 1280x720: 25fps(P)/30fps(N), 3.6mm/F1.2 lens, H.264/MJPEG, dual-stream, DC12V, 100dB WDR, 3D DNR, BLC, Support Mobile Monitoring via EZVIZ P2P	ناموجود	
75	Hologen Series			
76	DS-2CD2E20F-W	1/3" Progressive CMOS, Day/night, 0.1lux/F1.2, 1920x1080:25fps(P)/30fps(N), 4mm lens (2.8/6mm optional), H.264/MJPEG, dual-stream, DC12V & PoE, DWDR, 3D DNR, BLC, Support on-board storage up to 64GB (SD card not included), Support Mobile Monitoring via EZVIZ P2P, Color Lens Cover optional - (Black, Silver, Golden) -W: Built-in Wi-Fi	ناموجود	
77	2Q Smart Series			
78	DS-2CD2Q10FD-IW	1 MP CMOS PT Camera - 1/4" Progressive Scan CMOS - Up to 1.0 megapixel resolution - Support motorized Pan & Tilt - Digital WDR - 3D DNR - IR range approx. 10 meters - Support Wi-Fi, support WPS configuration with one touch (-W) - Two-way audio - Built-in microphone and speaker - Support 128G on-board storage - 5V DC±10% - Pan & Tilt Control Pan: 0° - 355°, Tilt: -20° - 90	IRR 18,090,000	
79	DS-2CV2Q21FD-IW	2 MP CMOS PT Camera - 1/2.8" Progressive CMOS, ICR, 0lux with IR, 1920x1080: 25fps(P)/30fps(N), 2.8mm lens, H.264/MJPEG, dual-stream, 3D DNR, 5m IR, PT function (Pan: 0° - 355°; Tilt: -10° - 90°), support on-board storage up to 128GB, HIK-Connect cloud service, Built-in microphone and speaker, support two-way audio. Built-in Wi-Fi, 12VDC power supply - Default: No SD card included. - 32GB-T: Include 16GB sd card.	ناموجود	
80	2U Smart Series			








81	DS-2CV2U21FD-IW	2.0 MP Network Cube Camera - 1/2.8" Progressive CMOS, ICR, 0lux with IR, 1920x1080: 25fps(P)/30fps(N), 2.8mm lens,H.264/MJPEG, dual-stream, 3D DNR, 5m IR, support on-board storage up to 128GB, HIK-Connect cloud service, Build-in microphone and speaker, support two-way audio. Built-in Wi-Fi, 12VDC power supply - 32GB-T: Include 32GB sd card.	IRR 12,420,000	
82	Mini PTZ Series			
83	DS-2CD2F52F-IS	5MP CMOS ICR Infrared Network Dome Camera - 1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920: 20fps,2048x1536: 25fps(P)/ 30fps(N), 4mm/F2.0 lens (2.8/6mm lens optional), H.264+/H.264/MJPEG, 3 streams, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 10m, Support on-board storage up to 128GB(SD card not included), Pan: 0°~180°, Tilt: 0°~75°, HIK-Connect cloud service -S: Audio/Alarm IO	IRR 32,450,000	
84	IP PTZ Camera			
85	DS-2DE4A220IW-DE	1/2.8" Progressive Scan CMOS, Up to 1920 x 1080 resolution 20x Optical Zoom, 16x Digital Zoom, WDR, 3D DNR, HLC, Smart IR Up to 50 m IR distance, 12 VDC & PoE+ (802.3at, class4), Support H.265 video compression	تماس	
86	DS-2DE4220IW-DE	2MP 20x Network IR Speed Dome - 1/3" CMOS sensor, H.264 codec, Color: 0.02lux/F1.5, B/W:0.02lux/F1.5, Optical Zoom:20x, Focus:4.7-94.0mm, Digital Zoom:16X, Pan range:360° endless; Tilt range: -15°~90°(Auto Flip), Pan Speed: 0.1° - 80°/s, Tilt Speed: 0.1° - 80°/s, 100m IR Distance, POE&12VDC	تماس	
87	DS-2DE4225IW-DE	2MP 25x Network IR Speed Dome - 1/2.8" progressive scan CMOSUp to 1920 x 1080@30fps resolution- Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON)0 Lux with IR25x optical zoom Focal Length 4.8 mm to 120 mm - 16x digital zoom - WDR, HLC, BLC, 3D DNR, Defog, EIS, Regional Exposure, Regional Focus - Up to 100 m IR distance - 12 VDC & PoE+ (802.3 at, class4) Support H.265+/H.265 video compression	IRR 92,260,000	
88	DS-2DE5220IW-AE	2MP 20X Network IR PTZ Dome Camera - 1/3" CMOS, 3D DNR, ICR, Color: 0.02lux/F1.5, B/W:0.02lux/F1.5, Optical Zoom:20x, Focus:4.7-94.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan range:360° endless; Tilt range: -15°~90°(Auto Flip), Pan Speed: 0.1° -400°/s, Tilt Speed: 0.1° -200°/s - 150m IR Distance - Hi-PoE&24VAC	IRR 147,400,000	
89	DS-2DE5230W-AE	2MP 30x Network IR Speed Dome - 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom 30x, Focus:4.3-129.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -250°/s, Tilt Speed: 0.1° -150°/s	تماس	
90	DS-2DE7184-AE	2MP 20x Network IR Speed Dome - 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:20x, Focus: 4.7-94.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -120°/s, 100m IR Distance, Hi-PoE&24VAC	IRR 96,100,000	
91	DS-2DE7220IW-AE	22MP 20x Network IR Speed Dome - 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:20x, Focus: 4.7-94.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -120°/s, 150m IR Distance, Hi-PoE&24VAC	تماس	
92	DS-2DE7230IW-AE	2MP 30x Network IR Speed Dome - 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:30x, Focus:4.3-129.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -120°/s, 150m IR Distance, Hi-PoE&24VAC	تماس	











93	DS-2DE7232IW-AE	2MP 32x Network IR Speed Dome, Up to 1920 x 1080@60fps resolution,Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON),B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR,32x optical zoom, 16x digital zoom, WDR, HLC, BLC, 3D DNR, Defog,EIS,Regional Exposure, Regional Focus,Up to 150 m IR distance,24 VAC & Hi-PoE,Support H.265+/H.265 video compression	IRR 166,800,000	
94	DS-2DE7320IW-AE	3MP 20x Network IR Speed Dome - 1/2.8" Progressive Scan CMOS - 2048 x 1536@30fps Resolution - 20x optical zoom, 16x digital zoom - WDR - 3D Positioning - 24VAC & Hi-PoE - Up to 150m IR distance	تماس	
95	DS-2DE7330IW-AE	3MP 30x Network IR Speed Dome - 1/2.8" Progressive Scan CMOS - 2048 x 1536@30fps Resolution - 30x optical zoom, 16x digital zoom - WDR - 3D Positioning - 24VAC & Hi-PoE - Up to 150m IR distance	تماس	
96	DS-2DE7420IW-AE	4MP 20x Network IR Speed Dome - 1/1.9" progressive scan CMOS,Up to 2560 x 1440 resolution,20x Optical Zoom, 16x Digital Zoom,Defog, EIS, 3D DNR, BLC, HLC, Digital WDR,IR distance up to 150 m,24 VAC & Hi-PoE,Support H.265+/H.265 video compression	تماس	
97	DS-2DE7430IW-AE	4MP 30x Network IR Speed Dome - 1/1.9" progressive scan CMOS,Up to 2560 x 1440 resolution,30x Optical Zoom, 16x Digital Zoom,Defog, EIS, 3D DNR, BLC, HLC, Digital WDR,IR distance up to 150 m,24 VAC & Hi-PoE,Support H.265+/H.265 video compression	تماس	
98	DS-2DE7530IW-AE	5MP 30x Network IR Speed Dome - 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:20x, Focus: 4.7-94.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -120°/s, 150m IR Distance, Hi-PoE&24VAC	تماس	
99	PanoVu Mini Series IR Network PTZ Camera			
100	DS-2PT3326IZ-DE3(2.8-12mm)	Panoramic Camera:1/2.8" progressive scan CMOS,3-ch1920 x 1080@30fps resolution,Min. illumination: Color: 0.05 Lux @(F2.0, AGC ON),B/W: 0.01 Lux @(F2.0, AGC ON),0 Lux with IR, Support H.265 video compression, Horizontal FOV: 128.5° x 3 PTZ Camera:1/2.8" progressive scan CMOS,Up to 1920 x 1080@30fps resolution,Min. illumination:Color: 0.05 Lux @(F2.0, AGC ON), B/W: 0.01 Lux @(F2.0, AGC ON), 0 Lux with IR Support H.265 video compression,4x optical zoom, 8x digital zoom	IRR 94,000,000	
101	NVR-Monitor			
102	DS-7600NI-E1/A	Advertising files import and preview,The output resolution of LCD is up to 1080P, Third party network cameras supported,Up to 8-ch synchronous playback at 720P resolution,Up to 8 network cameras can be connected,Smart search and smart playback 1TB HDD WD10JUCT pre-installed	IRR 109,000,000	
103	NVR 4 Channel			
104	DS-7104NI-Q1/M	IP video input : 4-ch Up to 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 12,020,000	
105	DS-7104NI-Q1/4P/M	IP video input : 4-ch / 4-ch POE Up to 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 19,850,000	










106	DS-7604NI-E1	IP video input : 4-ch Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity	تماس	
107	DS-7604NI-E1/4P	IP video input : 4-ch / 4-ch POE Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity	تماس	
108	DS-7604NI-Q1	IP video input : 4-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 18,550,000	
109	DS-7604NI-Q1/4P	IP video input : 4-ch / 4-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 26,500,000	
110	DS-7604NI-K1	IP video input : 4-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	تماس	
111	DS-7604NI-K1/4P	IP video input : 4-ch - 4-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	تماس	
112	NVR 8 Channel			
113	DS-7108NI-Q1/M	IP video input :8-ch Up to 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 60 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 15,110,000	
114	DS-7108NI-Q1/8P/M	IP video input :8-ch / 8-ch POE Up to 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 60 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 28,860,000	
115	DS-7608NI-E2	IP video input :8-ch Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	IRR 27,000,000	
116	DS-7608NI-E2/8P	IP video input :8-ch / 8-ch POE Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	تماس	
117	DS-7608NI-Q1	IP video input : 8-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 22,350,000	
118	DS-7608NI-Q1/8P	IP video input : 8-ch / 8-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	تماس	











119	DS-7608NI-Q2	IP video input : 8-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	تماس	
120	DS-7608NI-K1	IP video input : 8-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 22,990,000	
121	DS-7608NI-K2/8P	IP video input : 8-ch / 8-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	تماس	
122	NVR 16 Channel			
123	DS-7616NI-E2	IP video input :16-ch Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	تماس	
124	DS-7616NI-E2/8P	IP video input :16-ch / 8-ch POE Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	تماس	
125	DS-7616NI-E2/16P	IP video input :16-ch / 16-ch POE Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	تماس	
126	DS-7616NI-Q1	IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 26,960,000	
127	DS-7616NI-Q2	IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	IRR 28,210,000	
128	DS-7616NI-Q2/16P	IP video input : 16-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	IRR 57,460,000	
129	DS-7616NI-K2	IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	IRR 31,350,000	
130	DS-7616NI-K2/16P	IP video input : 16-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	تماس	
131	DS-7716NI-E4	IP video input :16-ch Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	تماس	
132	DS-7716NI-E4/16P	IP video input :16-ch / 16-ch POE Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	تماس	









133	DS-7716NI-Q4	IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 60,330,000	
134	DS-7716NI-K4	IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 67,320,000	
135	DS-7716NI-K4/16P	IP video input : 16-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	تماس	
136	NVR 32 Channel			
137	DS-7732NI-E4	IP video input :32-ch Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	تماس	
138	DS-7732NI-E4/16P	IP video input :32-ch / 16-ch POE Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 104,500,000	
139	DS-7732NI-Q4	IP video input : 32-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 200 Mbps - HDMI output : 1920 x 1080/60Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 74,430,000	
140	DS-7732NI-Q4/16P	IP video input : 32-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 200 Mbps - HDMI output : 1920 x 1080/60Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 107,850,000	
141	DS-7732NI-K4	IP video input : 32-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 256 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 89,030,000	
142	DS-7732NI-K4/16P	IP video input : 32-ch - 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 256 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	تماس	

Accessories				
Items	Description	User Price		
Switches				
1	DS-3E0105P-E L2, Unmanaged, 4 100M PoE port, 1 100M uplink port, 802.3af/at, PoE power budget 58W	IRR 8,625,000		
2	DS-3E0109P-E L2, Unmanaged, 8 100M PoE port, 1 100M uplink port, 802.3af/at, PoE power budget 123W	IRR 21,970,000		
3	DS-3E0318P-E L2, Unmanaged, 16 100M PoE port, 2 1000M combo port, 802.3af/at, PoE power budget 230W	IRR 50,270,000		
4	DS-3E0326P-E L2, Unmanaged, 24 100M PoE port, 2 1000M combo port, 802.3af/at, PoE power budget 370W	تماس		
5	DS-3E1310P-E L2, Web managed, 8 100M PoE port, 2 1000M combo port, 802.3af/at, PoE power budget 123W	IRR 23,230,000		
6	DS-3E1318P-E 802.3af/at PoE standard 8-core power supply technology, reducing the power circuit loss,Data monitor and control for the important ports, EXTEND mode available to extend the network cable transmission distance to 250 meters Buffer optimization to guarantee the video data transmission,VLAN configurable Port trunk, multicast and port mirroring,WEB management,Store-and-forward switching IEEE802.3, IEEE802.3u and IEEE802.3x network standards available MTBF (Mean Time Between Failure) ≥ 100,000 hours All-metal enclosed construction Table-mounted and rack-mounted design for convenient installation	تماس		
Cables				
8	DS-1LN6-UE-W UTP / CAT.6 / Indoor PVC / 23AWG, Full 305m, OFC / 0.530mm, CM Rating, Default Color: BLUE. TEST FLUKE	IRR 28,450,000		

9	DS-1LN6-UU	UTP / CAT.6 / Indoor PVC / 23AWG Full 305m OFC / 0.565mm CM Rating Default Color: Orange	IRR 31,310,000	
10	Brackets			
11	DS-1602ZJ	Wall mount , Hik white , Aluminum alloy , 97×182×305mm Suitable for:-DS-2DE/AE4xxx-DS-2DE/AE5xxx-DS-2DE/AE7xxx-DS-2DF8xxx-DS-2DF6xxx-DS-2DF7xxx-DS-2DF5xxx	IRR 4,150,000	
12	DS-1602ZJ-pole	Vertical pole mount, Hik white , Aluminum alloy , 117×194×310mm , Suitable for:DS-2DE/AE5xxx-DS-2DE/AE7xxx-DS-2DF8xxx--DS-2DF6xxx-DS-2DF7xxx-DS-2DF5xxx	ناموجود	
13	DS-1605ZJ	Wall Mount bracket Parameters: Wall mounting bracket-Colour: Hik White-Feature: Suitable for speed dome cameras Dimensions: Ø171.7 x 158 x 228.6mm	ناموجود	
14	DS-1661ZJ	Pendent Mounting Bracket In/Outdoor,-Color: -Hik white-Material: -Aluminum alloy-Dimensin: - 116.5×200mm-Weight: -600g	IRR 4,560,000	
15	DS-1662ZJ	Pendant mount , Hik white , Aluminum alloy , Φ116.5×500mm Suitable for:-DS-2DE/AE4xxx-DS-2DE/AE5xxx-DS-2DE/AE7xxx-DS-2DF8xxx-DS-2DF6xxx-DS-2DF7xxx-DS-2DF5xxx	IRR 5,210,000	
16	DS-1663ZJ	Ceiling mount , Hik white , Aluminum alloy , Φ116.5×57mm-Suitable for:-DS-2DE/AE4xxx-DS-2DE/AE5xxx-DS-2DE/AE7xxx-DS-2DF8xxx-DS-2DF6xxx-DS-2DF7xxx-DS-2DF5xxx	ناموجود	
17	DS-1693ZJ	Wall mount , Hik white , steel , 190×200×500mm , 5700g Suitable for PTZ positioner	ناموجود	
18	DS-1681ZJ	Ceiling mount , Hik white , Aluminum alloy -Suitable for:-DS-2DE/AE4xxx-DS-2DE/AE5xxx-DS-2DE/AE7xxx-DS-2DF8xxx-DS-2DF6xxx-DS-2DF7xxx-DS-2DF5xxx	IRR 1,520,000	
19	DS-1273ZJ-135B	Wall mount , White , Aluminum alloy , with junction box , Φ135×182×120mm Suitable for: DS-2CD27xx	Call	

20	Keyboard			
21	DS-1100KI	Network Keyboard, 7" TFT touch screen, up to 256 units of DVR/Network Cameras/Speed Dome management, 1-ch HD 1080p video steam decoding, USB 2.0 interface for video backup	ناموجود	
22	DS-1005KI	network Keyboard, USB interface, support Hikvision VMS, NVR, DVR	ناموجود	
23	Tester			
24	IPC-4300H	IPC-4300 IP camera tester 4.3 inch capacitive touch screen / ONVIF/ Hikvision, Dahua, etc more than 40 IP camera brands test /IP Camera view /12 V/2A power output / 5V 2A power bank / PoE power supply / HDMI output / WIFI	ناموجود	
25	DS-TT-X41T-tester	TurboHD (HD-TVI 2.0), HDMI 1.0, VGA, and CVBS Inputs - 7" TFT active matrix LCD monitor - TurboHD: Up to 720p @ 25/30/50/60 fps, 1080p @ 25/30 fps	IRR 84,680,000	
26	Access Control			
27	DS-K2804	Four-door Access Controller, Accessible Card Reader: 4 Wiegand readers; Input interface: Door Magneticx4, Door Switchx4, Case Inputx4; Output interface: Door Switch Relayx4, Alarm Relayx4; Uplink Communication Interface: TCP/IP Network Interface; Storage with 10,000 cards information and 50,000 access control events	Call	
28	DS-K1100 Series Card Reade			
29	DS-K1101MK	Mifare 1 card, with keypad, Supports RS485 and Wiegand(W26/W34) protocol, Tamper-proof alarm, Dust-proof, IP 64, Applied for 120 Gang Box Only	Call	
30	DS-K1102M	Mifare 1 card, Supports RS485 and Wiegand(W26/W34) protocol, Tamper-proof alarm, Dust-proof, IP 64, Applied for 86 &120 Gang Box	Call	
31	DS-K1102MK	Mifare 1 card, with keypad, Supports RS485 and Wiegand(W26/W34) protocol, Tamper-proof alarm, Dust-proof, IP 64, Applied for 86 & 120 Gang Box	Call	
32	DS-K1104M	Mifare 1 card, Supports RS485 and Wiegand(W26/W34) protocol, Tamper-proof alarm, Dust-proof, Vandal Proof, IP 65, Applied for 86 & 120 Gang Box	Call	

33	DS-K1801M	Mifare 1 card, with keypad, Supports Wiegand(W26/W34) protocol, Dust-proof, IP 65	Call	
34	DS-K1801MK	Mifare 1 card, with keypad, Supports Wiegand(W26/W34) protocol, Dust-proof, IP 65	Call	
35	Card Sender			
36	DS-K1F100-D8E	Plug-and-play USB with no-driver technology, Supports various card types (Mifare card, and EM card)	Call	
37	Pro Magnetic Lock			
38	DS-K4T100	Electric Bolt, Polished and Brushed Stainless Steel, Support Thrust of 800kg; Working Current: 900mA(Startup Current), 100mA (Standby), DC12V	Call	
39	DS-K4H250S	Single-door Magnetic Lock, supports static linear thrust of 250kg, Working Current: DC12V(500 mA) / 24VAC(250 mA)	Call	
40	DS-K4H250D	Double-door Magnetic Lock, supports static linear thrust of 2 x 250kg, Working Current: 12V/500mAx2 24V/250mAx2	Call	
41	Eco Magnetic Lock			
42	DS-K4H188S	Single-door Magnetic Lock, supports static linear thrust of 188kg, Working Current: DC12V(500 mA) / 24VAC(250 mA)	Call	
43	Pro Bracket for Magnetic Lock			
44	DS-K4T100-U2	Upper and lower U-bracket of Electric Bolt, for Using with DS-K4T100	Call	
45	DS-K4H250-LZ	LZ-Bracket of Magnetic Lock, for DS-K4H250S/D	Call	
46	DS-K4H250-U	U-Bracket of Magnetic Lock, for DS-K4H250S/D	Call	
47	Eco Bracket for Magnetic Lock			

48	DS-K4H188-LZ	LZ-Bracket of Magnetic Lock, for DS-K4H188S/D	Call	
49	Door release button			
50	DS-K7P01	aluminum alloy panel, metal button, Dimension(LxWxH): 86x86x20mm(3.39x3.39x0.79")	Call	
51	DS-K1T8 Series			
52	DS-K1T803MF	LCD Display Standalone Access Control Terminal, Support Access Control and Time Attendance Function, Optical Fingerprint Module, 3,000 Fingerprints Capacity, Support Wi-Fi & TCP-IP, Stand-alone Operation, Multiple Authentication: Card(EM or Mifare-1 Card), Fingerprint, etc	Call	
53	DS-K1T200 Series			
54	DS-K1T200MF-C	2.8 inch LCD-TFT Screen IP-based Fingerprint Access Control Terminal, Built-in Mifare card reading module and 2 Megapixels camera, Max. 9500 fingerprints, Max. 100,000 cards No.and Max. 300,000 access control events records, TCP/IP, WIFI, RS-485, Wiegand Protocol communication supported, 17 Keys keyboard and doorbell, DC 12V/1A	Call	
55	DS-K1T105 Series			
56	DS-K1T105M-C	2.8 inch LCD-TFT Screen Standalone Access Control Terminal, Built-in Mifare card (EM card) reading module, 2 Megapixels camera, Max. 100,000 cards No., and Max. 300,000 access control events records, TCP/IP, WIFI, RS-485, Wiegand Protocol communication supported, 17 Keys keyboard and doorbell, DC 12V/1A	Call	
57	DS-K1T801M	Standalone Access Control Terminal, Built-in Mifare card reading module, Max. 3,000 cards No., TCP/IP, 12 Keys keyboard and doorbell, DC 12V/1A	Call	
58	DS-K1T802M	LCD Display Screen Standalone Access Control Terminal, Built-in Mifare card reading module, Max. 3,000 cards No., and Max. 10,000 access control events records, TCP/IP, 12 Keys keyboard and doorbell, DC 12V/1A	Call	
59	Card			
60	S50+TK4100	EM + Mifare	Call	
61	Adapters			
62	Power Adapter	12V/1A	IRR 440,000	



HIKTEHRAN

نماینده مجاز فروش محصولات هایک ویژن

آدرس فروشگاه

تهران ، خیابان جمهوری پاساژ امجد طبقه همکف پلاک 28

شماره تماس








09906500074-66765968-66765923

ایمیل










Info@Hikvisiontehran.com









CONTACT US
HIKVISIONTEHRAN.COM

Hilook-DVR				
Items	Description	User Price		
1	THC-B120-P	2 MP high-performance CMOS-1920 × 1080 resolution- 2.8 mm, fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-Switchable TVI/AHD/CVI/CVBS- IP66	IRR 4,700,000	
2	THC-B120-M	2 MP high-performance CMOS-1920 × 1080 resolution- 2.8 mm, fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-Switchable TVI/AHD/CVI/CVBS- IP66-METAL	IRR 5,300,000	
3	THC-B140-P	4 MP high-performance CMOS-2560 × 1440 resolution- 2.8 mm fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- -DWDR-BLC-IP66	IRR 4,900,000	
4	THC-B140-M	4MP high-performance CMOS - 2560 × 1440 resolution- 2.8 mm- fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) -DWDR-IP 66-BLC-Full Metal	IRR 6,500,000	
5	THC-B220	2 MP high-performance CMOS-1920 × 1080 resolution- 2.8 mm fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 40 m IR distance-Switchable TVI/AHD/CVI/CVBS- IP66	IRR 5,500,000	
6	THC-B220-M	2MP CMOS Sensor, 40m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR,DWDR- OSD Menu, IP66, 2.8/3.6/6mm Lens, Support HD-TVI/AHD/CVI/CVBS video output-Full Metal	IRR 6,900,000	
7	THC-B240	4MP high-performance CMOS - 2560 × 1440 resolution- 2.8 mm- fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 40 m IR distance- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) -DWDR-BLC-IP 66	IRR 6,500,000	

8	THC-B240-M	4MP CMOS Sensor, EXIR Bullet, 40m IR, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR-DWDR, OSD Menu, IP66, 2.8/3.6/6mm Lens,Support HD-TVI/AHD/CVI/CVBS video output-Full Metal	IRR 8,300,000	
9	THC-T120-PC	2 MP high-performance CMOS- 1920 x 1080 resolution-2.8 mm, fixed focal lens-Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC	IRR 3,950,000	
10	THC-T120	2 MP high-performance CMOS- 1920 x 1080 resolution-2.8 mm, fixed focal lens-Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC	IRR 4,300,000	
11	THC-T120-M	2 MP high-performance CMOS- 1920 x 1080 resolution-2.8 mm, fixed focal lens-Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC-METAL	IRR 5,410,000	
12	THC-T140-P	4 MP high-performance CMOS-2560 x 1440 resolution-2.8 mm, Fixed focal lens-Day/Night switch-EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)DWDR-BLC-IP66	IRR 4,700,000	
13	THC-T140	4 MP high-performance CMOS-2560 x 1440 resolution-2.8 mm, Fixed focal lens-Day/Night switch-EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)DWDR-BLC-IP66	IRR 5,300,000	
14	THC-T140-M	4 MP high-performance CMOS-2560 x 1440 resolution-2.8 mm, Fixed focal lens-Day/Night switch-EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)DWDR-BLC-IP66-METAL	IRR 6,400,000	
15	THC-T220-P	2 MP high-performance CMOS-1920 x 1080 resolution-2.8 mm, fixed focal lens-Day/Night switch-EXIR 2.0, smart IR, up to 40 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC	IRR 4,150,000	
16	THC-T220-M	2 MP high-performance CMOS-1920 x 1080 resolution-2.8 mm, fixed focal lens-Day/Night switch-EXIR 2.0, smart IR, up to 40 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC-METAL	IRR 6,150,000	
17	THC-T240-P	4 MP high-performance CMOS-2560 x 1440 resolution-2.8 mm fixed focal lens-Day/Night switch- EXIR 2.0, smart IR, up to 40 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- DWDR-BLC-IP66	IRR 5,900,000	
18	THC-T240-M	4 MP high-performance CMOS-2560 x 1440 resolution-2.8 mm fixed focal lens-Day/Night switch- EXIR 2.0, smart IR, up to 40 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- DWDR-BLC-IP66-METAL	IRR 7,519,050	
19	Vari-Focal Series			

20	THC-B320-VF	2MP CMOS Sensor, 40m IR , Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR,, DWDR- DNR, OSD Menu, IP66, 2.8-12mm Vari Focal Lens , Support HD-TVI/AHD/CVI/CVBS video output-Front cover: Metal-Main body: Plastic-Bracket: Metal	IRR 9,850,000	
21	THC-B340-VF	4MP CMOS Sensor - 2.8-12mm Vari Focal Lens , EXIR Bullet, 40m IR , ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR,DWDR, OSD Menu, IP66 , Support HD-TVI/AHD/CVI/CVBS video output-Front cover: Metal-Main body: Plastic-Bracket: Metal	IRR 12,400,000	
22	THC-D320-VF	2MP CMOS Sensor, 40m IR , EXIR Dome, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, DWDR- OSD Menu, IP66, 2.8-12mm Vari Focal Lens --support HD-TVI/AHD/CVI/CVBS video output-,IK10-Full Metal	IRR 9,130,000	
23	THC-D340-VF	4MP CMOS Sensor, EXIR Dome, 40m IR , ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR,DWDR- OSD Menu, IP66, 2.8-12mm Vari Focal Lens ,IK10, Support HD-TVI/AHD/CVI/CVBS video output-Full Metal	IRR 10,500,000	
24	THC-T320 VF	2MP CMOS Sensor, 40m IR , EXIR Eyeball, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, DWDR- OSD Menu, IP66, 2.8-12mm Vari Focal Lens , Support HD-TVI/AHD/CVI/CVBS video output-Cover&Base:Plastic- Eyeball: Metal	IRR 8,700,000	
25	THC-T340-VF	4MP CMOS Sensor, EXIR Eyeball, 40m IR , ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR,DWDR- OSD Menu, IP66, 2.8-12mm Vari Focal Lens , Support HD-TVI/AHD/CVI/CVBS video output-Cover&Base:Plastic-Eyeball: Metal	IRR 9,850,000	
26	Turbo HD PTZ Camera			
27	PTZ-T4225I-D	1/2.8" HD progressive scan CMOS 1920 x 1080 resolution 25x optical zoom, 16x digital zoom 120 dB true WDR (Wide Dynamic Range) Up to 100 m IR distance 3D intelligent positioning Switchable TVI/AHD/CVI/CVBS video outputs	تماس	
28	PTZ-T4215I-D	1/2.8" HD progressive scan CMOS 1920 x 1080 resolution 5x optical zoom, 16x digital zoom 120 dB true WDR (Wide Dynamic Range) Up to 100 m IR distance 3D intelligent positioning Switchable TVI/AHD/CVI/CVBS video outputs	تماس	
29	PTZ-T5225I-A	1/2.8" HD progressive scan CMOS 1920 x 1080 resolution 25x optical zoom DWDR (Digital Wide Dynamic Range) Up to 150 m IR distance 3D intelligent positioning Switchable turbo HD and CVBS outputs	تماس	
30	DVR 4 Channel			

31	DVR-204G-F1	Recording Capability HD1080p Lite 4-ch -HD-TVI/AHD/CVI/CVBS video & 1-ch audio input,- 1-ch Up to 960P resolution), 1 SATA (6TB)interface, HD1080p Lite @ 25 fps/ch, 260 1U case--HDMI output HD1080p-Metal	IRR 9,500,000	
32	DVR-204Q-F1	Recording Capability 3MP 4-ch -HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, 1-ch IP video input(up to HD1080p resolution), 1 SATA(6TB) interface, CH 1: 3MP @ 12 fps, CH 2-4:1920x1080P: 12 fps/ch, 260 1U case-HDMI outputHD1080p-Metal	IRR 10,800,000	
33	DVR-204Q-K1	H265+ compression saving up to 50% on bandwidth and storage. Recording 2MP@15FPS on 1080P or @25FPS on 1080PLite (3MP@15FPS on channel 1) Support self-adaptive HDTV/HDCVI/AHD/CVBS signal input.Add up to 2 x 6MP IP cameras.HDMI output at 1920 x 1080 resolution Up to 4-ch synchronous playback at 1080p resolution playback at up to 256X speed.	IRR 12,000,000	
34	DVR-204U-F1	Recording Capability 5MP/3MP 4-ch -HD-TVI/AHD/CVI/CVBS video & 1-ch audio input,- 2-ch IP video input(up to 6MP resolution), 1 SATA (6 TB)- interface,5MP@12fps,4MP@15fps,3MP@18fps,1080p/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N), 315 1U case-HDMI output HD1080p-Metal	IRR 17,200,000	
35	DVR-204U-K1	Self-adaptive HDTV/HDCVI/AHD/CVBS signal input I Up to 8/16-ch 8 MP IP cameras input for DVR-204/208U-K1 I 8 MP/5 MP/4 MP HDTV video input and live view for DVR-208U-K1, and 5MP/4 MP for DVR-204U-K1 I Defogging function enabled for the supported analog cameras I Long distance transmission over UTP and coaxial cable: max. 800m for 1080p and 1200m for 720p HDTV signal	IRR 18,500,000	
36	DVR 8 Channel			
37	DVR-208G-F1	Recording Capability HD1080p Lite 8-ch- HD-TVI/AHD/CVI/CVBS video & 1-ch audio input,-2-ch Up to 960P resolution), 1 SATA(6TB) interface, HD1080p Lite @ 12 fps/ch, 260 1U case--HDMI output HD1080p-Metal	IRR 11,088,000	
38	DVR-208Q-F1	Recording Capability 3MP 8-ch- HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, -2-ch IP video input(up to HD1080p resolution), 1 SATA(6TB) interface, CH 1 & 2: 3MP @ 12 fps, CH 3 - 8:1920x1080P: 12 fps/ch, 260 1U case-HDMI output HD1080p-Metal	IRR 21,000,000	
39	DVR-208Q-K1	Connectable to turbo HD, AHD, HDCVI and analog cameras. 2-ch 1080p IP cameras input. Long distance transmission over UTP and coaxial cable One key enable H.264+ compression. Up to 3 MP resolution for recording of the first 2 channels. Supports real-time 1080p lite. Simultaneous HDMI/VGA output at up to 1920 x 1080 resolution. One SATA interface (up to 6TB capacity per HDD).	IRR 23,500,000	
40	DVR-208U-F1	Recording Capability 5MP/3MP 8-ch -HD-TVI/AHD/CVI/CVBS video & 1-ch audio input- 4-ch IP video input(up to 6MP resolution), 1 SATA(6 TB) interface,5MP@12fps,4MP@15fps,3MP@18fps,1080p/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N), 315 1U case-HDMI output 4K-Metal	IRR 32,000,000	

41	DVR-208U-K1	8 Channel DVR,Support HD-TVI, AHD, HD-CVI and analog cameras Supports 4 x IP Camera,1080P resolution real-time recording 8MP recording @ 8fps,VGA output at up to 1920 x 1080P resolution HDMI output at up to 4K (3840 x 2160) resolution,Supports h.265+ Support up to 8-ch synchronous playback,Internet & Smart Phone compatible	IRR 35,000,000	
42	Digital Video Recorder			
43	DVR-216G-F1	Recording Capability HD1080p Lite 16-ch -HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, -2-ch Up to 960P resolution, 1 SATA (6TB)interface, HD1080p Lite @ 12 fps/ch, 260 1U case- HDMI output HD1080p-Metal	IRR 20,800,000	
44	DVR-216Q-F1	Recording Capability 3MP 16-ch HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, -2-ch IP video input(up to HD1080p resolution), 1 SATA (6TB)- interface, CH 1 - 4: 3MP @ 12 fps, CH 5 - 16:1920x1080P: 12 fps/ch, 260 1U case- HDMI output 1ch 4K-Metal	IRR 32,000,000	
45	DVR-216Q-K1	One-key enable H.265+ compression Self adaptive: TVI Turbo HD, AHD, HD-CVI & analog inputs Accepts 16 BNC analog video inputs Up to 8ch IP video input (6MP) Max 24ch: 16 HD and 8 IP Long distance transmission over UTP & coaxial cable Supports real-time 1080P lite	IRR 35,000,000	
46	DVR-216U-F2	Recording Capability 5MP/3MP 16-ch -HD-TVI/AHD/CVI/CVBS video & 1-ch audio input,- 8-ch IP video input(up to 6MP resolution), 2 SATA (6 TB)- interface,5MP@12fps,4MP@15fps,3MP@18fps,1080p/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N), 380 1U case- HDMI output 1ch 4K-Metal-	IRR 62,850,000	
47	DVR-216U-K2	DVR 16 Channels HD 8 Megapixel,Interfaces input: 16 video / 1 Audio, (Support (TVI - AHD - CVI - CVBS,HDMI, VGA Outputs, 2 USB Support H.265+ compression, 2SATA up to 8TB capacity per HDD,Up to 8-ch,6MP IP cameras input, Up to 8 MP resolution for recording	IRR 67,000,000	

HIKTEHRAN

نماینده مجاز فروش محصولات هایک ویژن

آدرس فروشگاه

تهران ، خیابان جمهوری پاساژ امجد طبقه همکف پلاک 28

شماره تماس

09906500074-66765968-66765923

ایمیل








Info@Hikvisiontehran.com










CONTACT US








HIKVISIONTEHRAN.COM












Hilook-NVR



Items	Description	User Price	
1	IPC-B120 1/2.8" progressive scan CMOS-1920 x 1080@30fps -2.8 mm fixed lens- H.264+, H.264- Color: 0.01 Lux @(F1.2, AGC ON), 0.028 Lux @(F2.0, AGC ON)-BLC/3D DNR-IP67-Digital WDR	IRR 9,882,180	
2	IPC-B120H 2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H265/H.264+&H.264, 3D DNR, -2.8/4/6mm fixed lensBLC, DC12V & PoE,-up to 30m IR-Support mobile monitoring via Hik-Connec *power supply no included-DWDR-Front Cover: Metal-Back Cover & Bracket: Plastic-IP67	IRR 12,500,000	
3	IPC-B140H 4MP- 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, 3D DNR, BLC, DWDR- DC12V & PoE,2.8/4/6mm fixed lens, Support mobile monitoring via Hik-up to 30m IR, Connec *power supply no included-Front Cover: Metal Back Cover & Bracket: Plastic-IP67	IRR 14,800,000	
4	IPC-B220 1/2.8" progressive scan CMOS - Up to 2.0 megapixel high resolution-H264- 4 mm Lens-Up to 30 m IR distance-Dual stream-DWDR-3D DNR (Digital Noise Reduction)-BLC-IP67- Mobile monitoring via mobile application	IRR 11,000,000	
5	IPC-B220-D 1/2.8" progressive scan CMOS - Up to 2.0 megapixel high resolution-H264- 4 mm Lens-Up to 30 m IR distance-Dual stream-DWDR-3D DNR (Digital Noise Reduction)-BLC-IP67- Mobile monitoring via mobile application- D model only support 12VDC power supply	IRR 9,800,000	
6	IPC-T120 2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N),DWDR - H.264+&H.264-,2.8/4/6mm fixed lens- BLC, - DC12V & PoE ,-up to 10m IR- Support mobile monitoring via Hik-Connect *power supply no included-Eyeball:Plastic-Cover: Plastic-Indoor-ip67	IRR 10,500,000	
7	IPC-T120-D 1/2.8" progressive scan CMOS-Up to 2.0 megapixel -2.8 mm fixed focal lens-H264+ - 10 m IR range-Dual stream-DWDR-3D DNR (Digital Noise Reduction)- Mobile monitoring via mobile application-IP 67- D model only support 12VDC power supply	IRR 9,800,000	

8	IPC-T220-H	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H265/H.264+&H.264, 3D DNRDWDR, BLC, DC12V & PoE,-up to 30m IR-Support mobile monitoring via HikConnec *power supply no included2.8/4/6mm fixed lens-Eyeball: MetalCover: Plastic-IP67	IRR 11,000,000	
9	IPC-T240H	4MP-1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, up to 30m IR- 3D DNR-DWDR, BLC, DC12V & PoE-2.8/4/6mm fixed lens,--Support mobile monitoring via Hik-Connec *power supply no included-Eyeball: Metal-Cover: Plastic- IP67	IRR 14,300,000	
10	IPC-D120	1/2.8" progressive scan CMOS-2 MP-1920 x 1080@30fps-2.8mm fixed lens-H.264+, H.264-Color: 0.01 Lux @(F1.2, AGC ON), 0.028 Lux @(F2.0, AGC ON)-BLC/3D DNR-IP67-Digital WDR- IK 10	IRR 10,500,000	
11	IPC-D120H	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H265/H.264+&H.264, 3D DNR,--2.8/4/6mm fixed lens- BLC, DC12V & PoE,DWDR- Support mobile monitoring via Hik-Connect *power supply no included-up to 30m IR-Base: Metal-Cover: Plastic-IP67, IK10	IRR 13,000,000	
12	IPC-D140H	4.0 MP IR NetworkDome Camera,1/3" progressive scan CMOS, 3D DNR (Digital Noise Reduction), 2560 x 1440@20fps □ Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens,PoE (Power over Ethernet),H.265+, H.265, H.264+, H.264 □ IP67, IK10, Dual stream, 120 dB WDR.	IRR 14,300,000	
13	Vari-Focal Series			
14	IPC-B620H-V	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N),H.265+/H265/H.264+&H.264, 3D DNR ,DWDR- BLC, DC12V & PoE, TF card slot,up to 30m IR-Support mobile monitoring via Hik-Connect *power supply no included-2.8~12mm vari-focal lens-Body&Bracket: Metal-SunShield: Plastic-IP67	IRR 22,500,000	
15	IPC-B620H-Z	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N),H.265+/H265/H.264+&H.264, 3D DNR, BLC, -up to 30m IR-DC12V & PoE, -DWDR- TF card slot,-Support mobile monitoring via Hik-Connect *power supply no included-2.8~12mm motorized vari-focal lens-Body&Bracket: Metal-SunShield: Plastic-IP67	IRR 21,000,000	
16	IPC-B640H-V	4MP- 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, 3D DNR, BLC,up to 30m IR- DC12V & PoE, TF card slot, WDR- Support mobile monitoring via Hik-Connect *power supply no included-2.8~12mm vari-focal lens-Body&Bracket: Metal-SunShield: Plastic--IP67	IRR 26,000,000	
17	IPC-B640H-Z	4MP- 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, 3D DNR, BLC,up to 30m IR- DC12V & PoE, TF card slot,-WDR- Support mobile monitoring via Hik-Connect *power supply no included-2.8~12mm motorized vari-focal lens-Body&Bracket: Metal-SunShield: Plastic-IP67	IRR 28,500,000	

18	IPC-T620-Z	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.264+&H.264, 3D DNR, BLC,-WDR- up to 30m IR-DC12V & PoE,Support mobile monitoring via Hik-Connect *power supply no included2.8~12mm VF lens-Eyeball: MetalCover: Plastic-IP67	تماس	
19	IPC-D620H-V	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H265/H.264+&H.264,DWDR- 3D DNR, BLC,2.8~12mm varifocal lens - DC12V & PoE, TF card slot,-up to 30m IR - Support mobile monitoring via Hik-Connect *power supply no included -Full Metal-IP67, IK10	IRR 19,600,000	
20	IPC-D620H-Z	1/2.8" progressive scan CMOS-2 MP-1920 x 1080@30fps- 2.8 mm to 12 mm manual/motorized (with -Z) vari-focal lens- H.265+, H.265, H.264+, H.264-Dual stream-DWDR -3D DNR (Digital Noise Reduction)-Up to 30 m IR range-PoE (Power over Ethernet)- IP67, IK10	IRR 21,000,000	
21	IPC-D640H-V	4MP-1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264,WDR, 3D DNR, BLC,up to 30m IR - DC12V & PoE, TF card slot-- 2.8~12mm vari-focal lens - Support mobile monitoring via Hik-Connect *power supply no included - Full Metal-IP67, IK10	IRR 26,209,260	
22	IPC-D640H-Z	4MP-1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264,WDR, 3D DNR, BLC,up to 30m IR - DC12V & PoE, TF card slot-- 2.8~12mm vari-focal lens - Support mobile monitoring via Hik-Connect *power supply no included - Full Metal-IP67, IK10	IRR 23,000,000	
23	PanoVu Mini Series IR Network PTZ Camera			
24	PTZ-P332ZI-DE3	System Functions I 3-ch panoramic images in different directions and 1-ch close-up image I PTZ linkageI Up to 10 m IR radius Panoramic CameraI Three 1/2.8" progressive scan CMOSI 3-ch 1920 x 1080@30fps resolutionI Horizontal FOV: 128.5° x 3 PTZ CameraI 1/2.8" progressive scan CMOSI Up to 1920 x 1080@30fps resolutionI 4x optical zoom, 8x digital zoom	تماس	
25	IP PTZ Camera			
26	PTZ-N2204I-DE3	1/2.8" progressive scan CMOS .Up to 1920 x 1080@30fps resolution Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR 4x optical zoom, 16x digital zoom 20 dB WDR, 3D DNR, HLC, EIS, Regional Exposure, Regional Focus 2 VDC & PoE Up to 20 m IR distance IK10, IP66 Support H.265+/H.265 video compression	تماس	

27	PTZ-N2404I-DE3	<p>1/3" progressive scan CMOS .Up to 2560 × 1440@25fps resolution Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR 15x optical zoom, 16x digital zoom 120 dB WDR, 3D DNR, HLC, EIS, Regional Exposure, Regional Focus 2 VDC & PoE .Up to 20 m IR distance. K10, IP66 Support H.265+/H.265 video compression</p>	تماس	
28	PTZ-N4215-DE3	<p>1/2.8" progressive scan CMOS Up to 1920 × 1080 resolution Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR 15x optical zoom, 16x digital zoom 120dB WDR, 3D DNR, HLC, BLC 12 VDC & PoE+ (802.3at, class4) Support H.265+/H.265 video compression Up to 24 programmable privacy masks Support ROI</p>	تماس	
29	PTZ-N4215I-DE	<p>1/2.8" progressive scan CMOS Up to 1920 × 1080 resolution Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR Up to 100 m IR distance 15x optical zoom, 16x digital zoom 120dB WDR, 3D DNR, HLC, BLC, Smart IR 12 VDC & PoE+ (802.3at, class4) Support H.265+/H.265 video compression Up to 24 programmable privacy masks Support ROI</p>	تماس	
30	PTZ-N4225I-DE	<p>1/2.8" progressive scan CMOS Up to 1920 × 1080 resolution Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR Up to 100 m IR distance 25x optical zoom, 16x digital zoom 120dB WDR, 3D DNR, HLC, BLC, Smart IR 12 VDC & PoE+ (802.3at, class4) Support H.265+/H.265 video compression Up to 24 programmable privacy masks Support ROI</p>	تماس	
31	PTZ-N5225I-AE	<p>1/2.8" progressive scan CMOS Up to 1920 × 1080 resolution Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR Up to 150 m IR distance 25x optical zoom, 16x digital zoom 120dB WDR, 3D DNR, HLC, BLC, Smart IR 24 VAC & PoE+ (802.3at, class4) Support H.265+/H.265 video compression Up to 24 programmable privacy masks Support ROI Support smart detection</p>	تماس	
32	Network Video Recorder			
33	NVR-104-B	<p>Full channel recording at up to 4 MP resolution-40Mbps Bit Rate Input Max (up to 4-ch IP video),Output Bandwidth 40Mbps- H.264, 1 SATA interface 6TB, mini 1U case(Plastic)-HDMI Output 1, up to 1080P-Decoding Capability- 2-ch@ 4MP-4-ch@1080p</p>	IRR 8,910,000	

34	NVR-104-B/4P	Full channel recording at up to 4 MP resolution-40Mbps Bit Rate Input Max (up to 4-ch IP video),Output Bandwidth 40Mbps- H.264, 1 SATA interface 6TB , 4 independent PoE network interfaces, mini 1U case(Plastic)-HDMI Output 1, up to 1080P-Decoding Capability-4-ch 1080P,or 2-ch 4MP	تماس	
35	NVR-108-B	Full channel recording at up to 4 MP resolution-60Mbps Bit Rate Input -Max (up to 8-ch IP video),,Output Bandwidth 40Mbps- H.264, 1 SATA interface 6TB, mini 1U case(Plastic)-HDMI Output 1, up to 1080P-Decoding Capability-2-ch@4 MP, 4-ch@1080p	IRR 11,330,000	
36	NVR-108-B/8P	Full channel recording at up to 4 MP resolution-60Mbps Bit Rate Input Max (up to 8-ch IP video),Output Bandwidth 40Mbps- H.264, 1 SATA interface 6TB ,8 independent PoE network interfaces, mini 1U case(Plastic)-HDMI Output 1, up to 1080P-Decoding Capability-4-ch 1080P,or 2-ch 4MP	IRR 21,500,000	
37	NVR-104MH-C	Recording at up to 8 MP resolution40Mbps Bit Rate -Input Max (up to 4-ch IP video UP to 8MP), Output Bandwidth 80Mbps- H.265-, 1 SATA (6TB)interface, standalone 1U 315 case(Metal)-HDMI Output 1CH 4K, --Decoding Capability 1-ch @ 8 MP / 4-ch @ 1080p	IRR 13,530,000	
38	NVR-104MH-C/4P	Recording at up to 8 MP resolution-40Mbps Bit Rate Input- Max (up to 4-ch IP video UP to 8 MP) ,Output Bandwidth 80Mbps- H.265-, 1SATA(6TB) interface, 4 independent PoE network interfaces, 1U 315 case(Metal)-HDMI Output 1ch 4k-Decoding Capability 1-ch @ 8 MP 4-ch @ 1080P	IRR 25,100,000	
39	NVR-108MH-C	Recording at up to 8 MP resolution-80Mbps Bit Rate Input- Max (up to 8-ch IP video UP to 8 MP),Output Bandwidth 80Mbps- H.265, 1 SATA interface(6TB), standalone 1U 315 case(Metal)-HDMI Output 1CH 4K,Decoding Capability: -1-ch @ 8 MP / 4-ch @ 1080p	IRR 17,100,000	
40	NVR-108M-C/8P	Recording at up to 8 MP resolution-80Mbps Bit Rate Input- Max (up to 8-ch IP video UP tp 8mp),Output Bandwidth 80Mbps-, H.265, 1 SATA interface(6 TB),8 independent PoE network interfaces, standalone 1U 315 case(Metal)--HDMI Output 1ch 4k, - Decoding Capability:1-ch @ 8 MP / 4-ch @ 1080p	IRR 34,600,000	
41	NVR-108M-D/8P	IP video input 8ch, Incoming bandwidth 60 Mbps Outgoing,bandwidth 60 Mbps, Recording resolution 4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF, H.265+/H.265/ H.264+/H.264, 1 SATA interface,Capacity Up to 6TB capacity for each disk,	IRR 32,000,000	
42	NVR-116MH-C	Recording at up to 8 MP resolution-160Mbps Bit Rate Input- Max (up to 16-ch IP video UP to 8MP),Output Bandwidth 80Mbps-, H.265, 1 SATA interface(6TB), standalone 1U 315 case(Metal)-HDMI Output 1CH 4K, Decoding Capability: 1-ch @ 8 MP / 4-ch @ 1080p	IRR 20,500,000	

43	NVR-216MH-C	Recording at up to 8 MP resolution-160Mbps Bit Rate Input Max (up to 16-ch IP video),Output Bandwidth 80Mbps, - H.265-2,SATA up to 6TB per HDD interface, standalone 1U 385 case(Metal)-HDMI Output1 ch 4k -Decoding Capability: 1-ch @ 8 MP / 4-ch @ 1080p	IRR 24,750,000	
44	NVR-216MH-C/16P	Recording at up to 8 MP resolution-160Mbps Bit Rate Input Max (up to 16-ch IP video)Output Bandwidth 80Mbps, H.265, 2 SATA(up to 6TB per HDD) interface,16 independent PoE network interfaces, standalone 1U 385 case(Metal)-HDMI Output1 ch 4k,-Decoding Capability 1-ch @ 8 MP / 4-ch @ 1080p	IRR 48,500,000	

HOME - Bussiness		
Items	Description	User Price
Modem Router		
1	X6200-EU Linksys X6200 ADSL2+ Modem; 802.11a/b/g/n/ac; Dual Band; Max 433Mbps + 300Mbps; 4 x 10/100/1000 Ports; 1 x USB Port; MIMO2x2; Internal Antennas	IRR 12,400,000
2	XAC1200-EK Linksys XAC1200 ADSL2+ Modem; 802.11a/b/g/n/ac; Dual Band; Max 867Mbps + 300Mbps; 4 x 10/100/1000 Ports; 1 x USB Port; MIMO2x2; Internal Antennas	IRR 18,230,000
3	XAC1900-EK Linksys XAC1900 ADSL2+ Modem; 802.11a/b/g/n/ac; Dual Band; Max 1300Mbps + 600Mbps; 4 x 10/100/1000 Ports; 2 x USB Ports; MIMO3x3; External Antennas	IRR 28,260,000
Wireless Router E-series		
5	E900-EE Linksys E900 Wireless-N Router; 802.11b/g/n; Single Band; Max 300Mbps; 4 x 10/100 Ports; No USB; MIMO2x2; Internal Antennas	IRR 2,990,000
6	E1200-M2 Linksys E1200 Wireless-N Router; 802.11b/g/n; Single Band; Max 300Mbps; 4 x 10/100 Ports; No USB; MIMO2x2; Internal Antennas	IRR 4,490,000
7	E1700-EK Linksys E1700 Wireless-N Router; 802.11b/g/n; Single Band; Max 300Mbps; 4 x 10/100/1000 Ports; No USB; MIMO2x2; External Antennas	IRR 5,430,000
8	E2500-M2 Linksys E2500 Wireless-N Router; 802.11a/b/g/n; Dual Band; Max 300Mbps; 4 x 10/100/100 Ports; 1xUSB; MIMO2x2; Internal Antennas	IRR 6,550,000
Wireless Router EA-series		
9		

10	EA2750-M2	Linksys EA2750 Wireless-N Router; 802.11a/b/g/n; Dual Band Concurrent; Max 300Mbps + 300Mbps; 4x10/100/1000 Ports; 1xUSB; MIMO2x2; External Antennas	IRR 9,170,000
11	EA6100-EK	Linksys EA6100 Wireless-AC Router; 802.11a/b/g/n/ac; Dual Band Concurrent; Max 867Mbps + 300Mbps; 4x10/100 Ports; 1xUSB; MIMO2x2; External Antennas	IRR 9,260,000
12	EA6350-EK	Linksys EA6350 Wireless-AC Router; 802.11a/b/g/n/ac; Dual Band Concurrent; Max 867Mbps + 300Mbps; 4x10/100/1000 Ports; 1xUSB; MIMO2x2; External Antennas	IRR 15,350,000
13	EA6900-M2	Linksys EA6900 Wireless-AC Router; 802.11a/b/g/n/ac; Dual Band Concurrent; Max 1300Mbps + 600Mbps; 4x10/100/1000 Ports; 2xUSB; MIMO3x3; External Antennas	IRR 21,930,000
14	EA7500-EU	Linksys EA7500 Wireless-AC Router; 802.11a/b/g/n/ac; Dual Band Concurrent; Max 1300Mbps + 600Mbps; 4x10/100/1000 Ports; 2xUSB; MU-MIMO3x3; External Antennas	IRR 25,270,000
15	EA8500-EU	Linksys EA8500 Wireless-AC Router; 802.11a/b/g/n/ac; Dual Band Concurrent; Max 1733Mbps + 800Mbps; 4x10/100/1000 Ports; 2xUSB; MU-MIMO4x4; External Antennas	IRR 32,760,000
16	EA9500-EU	Linksys EA9500 Wireless-AC Router; 802.11a/b/g/n/ac; Dual Band Concurrent; Max 2166Mbps + 1000Mbps; 8x10/100/1000 Ports; 2xUSB; MU-MIMO4x4; External Antennas	IRR 53,360,000
17	Wireless Router WRT-series		
18	WRT1900ACS-EU	Linksys WRT1900ACS Wireless-AC Router; 802.11a/b/g/n/ac; Dual Band Concurrent; Max 1300Mbps + 600Mbps; 4x10/100/1000 Ports; 2xUSB; MU-MIMO4x4; External Antennas	IRR 22,280,000
19	WRT1200AC-EU	Linksys WRT1200AC Wireless-AC Router; 802.11a/b/g/n/ac; Dual Band Concurrent; Max 867Mbps + 300Mbps; 4x10/100/1000 Ports; 2xUSB; MIMO2x2; External Antennas	IRR 17,780,000
20	WRT3200ACM-EU	Linksys WRT3200ACS Wireless-AC Router; 802.11a/b/g/n/ac; Dual Band Concurrent; Max 2600Mbps + 600Mbps; 4x10/100/1000 Ports; 2xUSB; MU-MIMO4x4; External Antennas	IRR 35,560,000
21	WRT32X-EU	LINKSYS WRT32X WIFI ROUTER,AC3200 DUAL-BAND WI-FI GAMING ROUTER WITH KILLER PRIORITIZATION ENGINE; 4 Gigabit ports; 4 detach Antenna; 2 USB Ports	IRR 39,320,000
22	USB Adapter		
23	AE1200-EE	Linksys AE1200 Wireless-N USB Adapter; Single Band; Max 300Mbps	IRR 2,430,000
24	AE2500-EE	Linksys AE2500 Wireless-N USB Adapter; Dual Band; Max 300Mbps	IRR 3,900,000

25	AE6000-EE	Linksys AE6000 Wireless-AC USB Adapter; Dual Band; Max 433Mbps	IRR 3,900,000
26	WUSB6100M-EU	Linksys WUSB6100M Wireless-AC USB Adapter; Dual Band; Max 433Mbps	IRR 6,550,000
27	WUSB6300-EK	Linksys WUSB6300 Wireless-AC USB Adapter; Dual Band; Max 867Mbps	IRR 5,990,000
28	USB3GIG-EJ	Linksys USB 3.0 Gigabit Ethernet Adapter	IRR 2,990,000
29	Range Extender		
30	RE3000W-EK	Linksys RE3000W Range Extender; Single Band; 802.11b/g/n; Max 300Mbps; 1x10/100 Port	IRR 5,270,000
31	RE4100W-EU	Linksys RE4100W Range Extender; Dual Band; 802.11a/b/g/n; Max 300Mbps; 1x10/100 Port	IRR 6,360,000
32	RE6300-EU	Linksys RE6300 Range Extender; Dual Band; 802.11a/b/g/n/ac; Max 433Mbps; 1x10/100/1000 Port	IRR 9,300,000
33	RE6400-EU	Linksys RE6400 Range Extender; Dual Band; 802.11a/b/g/n/ac; Max 867Mbps; 1x10/100/1000 Port	IRR 9,730,000
34	RE6500-EU	Linksys RE6500 Range Extender; Dual Band; 802.11a/b/g/n/ac; Max 867Mbps; 4x10/100/1000 Port; Audio Jack; Desktop	IRR 12,540,000
35	RE6700-EG	Linksys RE6700 Range Extender; Dual Band; 802.11a/b/g/n/ac; Max 867Mbps; 1x10/100/1000 Port; Audio Jack; Power Out	IRR 13,480,000
36	Switches (HOME)		
37	SE2500-EU	Linksys SE2500 Gigabit Switch; 5x10/100/1000 Ports; Plastic Case; Desktop; Power Saving	IRR 4,120,000
38	SE2800-EU	Linksys SE2800 Gigabit Switch; 8x10/100/1000 Ports; Plastic Case; Desktop; Power Saving	IRR 5,782,000
39	SE4008	Linksys SE4008 Gigabit Switch; 8x10/100/1000 Ports; Plastic Case; Desktop; Power Saving; Stacks over WRT1900AC	IRR 6,550,000
40	Switches (Business)		
41	LGS105-EU	5-Ports Auto-Sensing; Unmanaged; Gigabit; Metal Case; Desktop or Wall Mount; Fanless; Power Saving; Adapter Included	IRR 4,100,000

42	LGS108-EU	8-Ports Auto-Sensing; Unmanaged; Gigabit; Metal Case; Desktop or Wall Mount; Fanless; Power Saving; Adapter Included	IRR 4,900,000
43	LGS116-EU	16-Ports Auto-Sensing; Unmanaged; Gigabit; Metal Case; Desktop; Wall Mount; Fanless; Power Saving; Adapter Included	IRR 15,110,000
44	LGS124-EU	24-Ports Gigabit ,Unmanaged, QOS, Metal, RackMount; 24x10/100/1000 Ports	IRR 21,520,000
45	LGS308-EU	8-Ports Gigabit; Smart, Advanced QOS, TFTP Upgrade, Port Mirroring (up to 4 Ports), Metal, Wallmount, RMON, VLAN 802.1Q	IRR 9,770,000
46	LGS318-EU	18-Ports Gigabit 2 Combo Ports (RJ45 + SFP) , Advanced QOS, TFTP Upgrade, Port Mirroring (up to 4 Ports), Metal, Rackmount, RMON, VLAN 802.1Q	IRR 22,590,000
47	LGS326-EU	26-Ports Gigabit, 2 Combo Ports (RJ45 + SFP) Enhanced QOS, TFTP Upgrade, Port Mirroring (up to 4 Ports), Metal, Rackmount, RMON	IRR 27,060,000
48	LGS528-EU	28-Ports Gigabit , Layer 3 Static Routing, 28Ports , 2 Combo Ports (RJ45 + SFP) Advanced QOS, TFTP Upgrade, Port Mirroring , Metal, Rackmount, RMON.VLAN 802.1Q, Auto Voice VLAN, IGMP Snooping, HOL blocking pervation, Storm Control, SNMP V1-V2c, Copper FE/GE Ports, Total System Ports: 28GE-	IRR 43,760,000
49	LGS552-EU	52-Ports Gigabit , Layer 3 Static Routing, 2 Combo Ports (RJ45 + SFP), 2 X 10GB uplink Ethernet SFP+, advanced QOS, TFTP Upgrade, Port Mirroring , Metal, Rackmount, RMON.VLAN 802.1Q, Auto Voice VLAN, IGMP Snooping, HOL blocking pervation, Storm Control, SNMP V1-V2c, Copper FE/GE Ports, Total System Ports:	IRR 78,150,000
50	Switches POE		
51	LGS108P-EU	8-Ports Gigabit ,Unmanaged, 4 Ports POE, 50W, QOS, Metal,Wall Mount	IRR 13,020,000
52	LGS116P-EU	Gigabit ,Unmanaged, 16-Port (8POE), 80W, QOS, Metal, Wall Mount	IRR 21,160,000
53	LGS124P-EU	Gigabit, Unmanaged, 24-Port (12POE), 120W, QOS, Metal, RackMount	IRR 32,810,000
54	LGS308P-EU	8-Ports Gigabit ,Smart, 8Port POE 802.3af & 802.3at, 72W, Advances QOS, TFTP Upgrade, Port Mirroring (up to 4 Ports), Metal, Wallmount, RMON, VLAN 802.1Q	IRR 18,310,000
55	LGS318P-EU	Gigabit ,Smart, 18-Ports (16POE) 802.3af & 802.3at, 125W, 2 Combo Ports (RJ45 + SFP) Enhanced QOS, TFTP Upgrade, Port Mirroring (up to 4 Ports), Metal, Rackmount, RMON.VLAN 802.1Q	IRR 46,650,000
56	LGS326P-EU	Gigabit ,Smart, 26-Ports (24POE) 802.3af & 802.3at, 192W, 2 Combo Ports (RJ45 + SFP) Enhanced QOS, TFTP Upgrade, Port Mirroring (up to 4 Ports), Metal, Rackmount, RMON	IRR 65,000,000

57	LGS326MP-EU	Gigabit ,Smart, 26-Ports (24POE) 802.3af & 802.3at, 384W, 2 Combo Ports (RJ45 + SFP) Enhanced QOS, TFTP Upgrade, Port Mirroring (up to 4 Ports), Metal, Rackmount, RMON	IRR 68,800,000
58	LGS528P-EU	28-Ports Gigabit , Layer 3 Static Routing, 24Ports POE 192W Budget, 2 Combo Ports (RJ45 + SFP),, advanced QOS, TFTP Upgrade, Port Mirroring , Metal, Rackmount, RMON.VLAN 802.1Q, Auto Voice VLAN, IGMP Snooping, HOL blocking pervation, Storm Control, SNMP V1-V2c, Copper FE/GE Ports, Total System Ports: 28GE	IRR 71,070,000
59	LGS552P-EU	Gigabit , Layer 3 Static Routing, 52-Ports (48 POE) 375W, 2 Combo Ports (RJ45 + SFP), 2 X 10GB uplink Ethernet SFP+, advanced QOS, TFTP Upgrade, Port Mirroring , Metal, Rackmount, RMON.VLAN 802.1Q, Auto Voice VLAN, IGMP Snooping, HOL blocking pervation, Storm Control, SNMP V1-V2c, Copper FE/GE Ports, Total System Ports: 52GE	IRR 117,230,000
60	Access Point		
61	LAPN300-EU	Single Band; 802.11n; Max 300Mbps; Bridge; Schedule; VLAN; PoE or Adapter; Desktop/Ceiling/Wall; Rate Limit; 1*GigaEthernet; MIMO2x2	IRR 12,010,000
62	LAPN600-EU	Dual Band; 802.11n; Max 300 + 300Mbps; Bridge; Schedule; VLAN; PoE or Adapter; Desktop/Ceiling/Wall; Rate Limit; 1*GigaEthernet; MIMO2x2	IRR 18,850,000
63	LAPAC1200-EU	Dual Band; 802.11ac; Max 867 + 300Mbps; Bridge; Schedule; VLAN; PoE or Adapter; Desktop/Ceiling/Wall; Rate Limit; 1*GigaEthernet; MIMO2x2	IRR 23,250,000
64	LAPAC1750-EU	Dual Band; 802.11ac; Max 1300 + 450Mbps; Bridge; Schedule; VLAN; PoE or Adapter; Desktop/Ceiling/Wall; Rate Limit; 1*GigaEthernet; MIMO 3x3	IRR 31,650,000
65	LAPAC1750 PRO-EU	Dual Band; 802.11ac; Max 1300 + 450Mbps; Bridge; Schedule; VLAN; PoE or Adapter; Desktop/Ceiling/Wall; Rate Limit; 2*GigaEthernet; MIMO 3x3; High Gain Antenna	IRR 49,040,000
66	LAPAC2600-EU	Linksys Business Dual-Band Access Point AC2600	IRR 52,750,000
67	WAP300N-EE	Dual Band; 802.11n;Max 300Mbps;Bridge; Adapter only; Desktop;1*Fast Ethernet ; MIMO 2*2	IRR 5,610,000
68	WHW0302-ME new	LINKSYS VELOP	IRR 50,880,000
69	WAP750AC	Linksys WAP750AC AC750 Wi-Fi Access Point	IRR 8,930,000
70	VPN Router		
71	LRT214-EU	Linksys VPN Router; Site-to-Site VPN; Remote-Access VPN; Router; Firewall; 4x10/100/1000 Ports; 1xWAN Port; Metal Case	IRR 19,140,000

72	LRT224-EU	Linksys VPN Router; Site-to-Site VPN; Remote-Access VPN; Router; Firewall; 4x10/100/1000 Ports; 2xWAN Port; Metal Case; Load Balance; Smart Backup; Aggregate WAN1 + WAN2	IRR 19,930,000
73	Poe Injector		
74	LACPI30-EU	Linksys PoE Injector; 802.3af and 802.3at; 30Watts; Gigabit Ethernet; Wall Mount	IRR 5,470,000