# **HP DesignJet HD Pro 44-in MFP**



High-definition graphics 44-in MFP for technical and graphics applications—fast and secure



## PRECISE—Excellent reproduction with CCD technology

- Reproduce colors with excellent accuracy with CCD technology that enables highquality color scanning/copying.
- Efficiently handle complex images with an advanced five-camera system that captures detail in high precision.
- Scan maps, orthophotos, and technical drawings—even if old and damaged—with CCD technology for great results.
- Create large-format color and black-andwhite scans up to 42-in (1067-mm)) wide on thick<sup>1</sup>, rigid media.

### FAST—HD scanner designed to streamline workflows

- Scan fast—up to 6 inches (152 mm) per second in color and 13 inches (330 mm) per second in black-and-white.
- Accelerate workflows. Save scans as PDF, TIFF, JPEG, or DWF files. Do batch scanning. Create multipage PDFs.
- Scan to email, USB, network—or print with the HP DesignJet Z6dr 44-in PostScript® Printer with V-Trimmer.
- Work comfortably with a 15.6-in (396-mm) color touchscreen.

### SECURE—Protect your work and vour information

- Protect printers/data from unauthorized access with HP Secure Boot, whitelisting, 500 GB encrypted hard disk.
- Protect documents, preserve confidentiality with authentication solutions like PIN printing, card readers.<sup>2</sup>
- Secure your printer with HP JetAdvantage Security Manager; manage your fleet remotely with HP Web Jetadmin.
- Reliable color—HP Professional PANTONE® color emulation, embedded Adobe® PostScript®, Adobe® PDF Print Engine.

# For more information, please visit hp.com/go/DesignJetHDProMFP

Dynamic security enabled printer. Only intended to be used with cartridges using an HP original chip. Cartridges using a non-HP chip may not work, and those that work today may not work in the future. More at: hp.com/go/learnaboutsupplies

<sup>&</sup>lt;sup>1</sup> Up to 0.6-in (15-mm) thickness.

<sup>&</sup>lt;sup>2</sup> Card reader functionality enabled through optional third-party solutions.

#### **Technical specifications**

Print		Printer with V-Trimmer  916 ft²/hr (85.1 m²/hr) on plain media	
	Color images	Normal: 1.1 min/page² on A1/D or up to 310 ft²/hr¹ (28.8 m²/hr¹) on	
	Cotor images	coated media	
	Print resolution	Best: $3.2 \min/page^2$ on A1/D or up to $108 \text{ ft}^2/hr^1$ ( $10 \text{ m}^2/hr^1$ ) on glossy media. Up to $2400 \times 1200$ optimized dpi	
	Margins (top x bottom		
	x left x right) Ink types	Sheet: 0.2 x 0.67 x 0.2 x 0.2 in (5 x 17 x 5 x 5 mm)  Pigment-based	
	Ink cartridges	6 (cyan, magenta, yellow, matte black, photo black, chromatic red)	
	Ink drop	7/3 pl dual-drop weight (M, C, PK); 6 pl single-drop weight (Y, CR, MK)	
Media	Handling	Two automatic roll feeds, smart roll-switching, top sheet feed, media output bin, automatic horizontal cutter and vertical trimmer (cuts all HP Z-series printer-qualified media, including most canvas)	
	Size	Rolls: 11 to 44 in (279 to 1118 mm) Sheets: 8.3 x 11 to 44 x 66 in (210 x 279 to 1118 x 1676 mm) Standard sheets: A, B, C, D, E (A4, A3, A2, A1, A0)	
	Thickness	Up to 31.5 mil (0.8 mm)	
Applications	Banners, Exhibition and event graphics, Light boxes - film, Maps, Orthophotos, Point of sale display, Posters		
Memory	128 GB (virtual)4; 500 GB self-encrypting hard disk		
Connectivity	Interfaces	Ethernet, Fast Ethernet, Gigabit Ethernet, 10/100/1000Base-T Ethernet (802.3, 802.3u, 802.3ab); USB Type-A host port	
	Print languages (standard)	Adobe PostScript 3, Adobe PDF 1.7, TIFF, JPEG, CALS G4, HP-GL/2, HP-RTL	
Acoustic	Sound pressure	45 dB(A) (operating); 33 dB(A) (idle); <16 dB(A) (sleep)	
	Sound power	6.3 B(A) (operating); 5.1 B(A) (idle); <3.4 B(A) (sleep)	
Power	Consumption	$^{<}$ 100 W (printing); $^{<}$ 32 W (ready); $^{<}$ 0.3 W ( $^{<}$ 6.5 W with embedded Digital Front End) (sleep); 0.1 W (off)	
	Requirements	Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max	
Certification	Safety	USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Singapore (PSB); China (CCC); Argentina (IRAM); India (BIS)	
	Electromagnetic	Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI), Korea (KCC), South Africa (SABS)	
	Environmental	ENERGY STAR; ErP; WEEE; RoHS (EU, China, Korea, India); REACH; EPEAT Silver	
HP HD Pro 42	in Scanner (CCD scan to		
Scan and	Scan speed	Color: up to 6 in/sec (15 cm/sec) Grayscale: up to 13 in/sec (33 cm/sec)	
Scan and			
Scan and	Scan speed Enhanced resolution Optical resolution	Grayscale: up to 13 in/sec (33 cm/sec) 9600 dpi 1200 dpi	
Scan and	Scan speed Enhanced resolution Optical resolution Maximum scan width	Grayscale: up to 13 in/sec (33 cm/sec) 9600 dpi 1200 dpi 42 in (1067 mm)	
Scan and copy	Enhanced resolution Optical resolution Maximum scan width Scan input modes	Grayscale: up to 13 in/sec (33 cm/sec) 9600 dpi 1200 dpi 42 in (1067 mm) File, email, USB, HDD, network folder, FTP, print	
Scan and copy	Scan speed Enhanced resolution Optical resolution Maximum scan width	Grayscale: up to 13 in/sec (33 cm/sec) 9600 dpi 1200 dpi 42 in (1067 mm) File, email, USB, HDD, network folder, FTP, print	
Scan and copy Media	Scan speed  Enhanced resolution Optical resolution Maximum scan width Scan input modes Handling  Thickness	Grayscale: up to 13 in/sec (33 cm/sec) 9600 dpi 1200 dpi 42 in (1067 mm) File, email, USB, HDD, network folder, FTP, print Straight-through scan paper path for sheet and cardboard originals, adjustable paper pressure for very thin media. Face-down, front entry, rear exit, rewind to front, use document return guide for front-return. Automatic high adjustment of scanner bridge for thick originals up to 15 mm (0.6 in) thickness.  Up to 0.6 in (15 mm)	
Scan and copy  Media	Scan speed  Enhanced resolution Optical resolution Maximum scan width Scan input modes Handling  Thickness Scanner	Grayscale: up to 13 in/sec (33 cm/sec) 9600 dpi 1200 dpi 1200 dpi 12 in (1067 mm) File, email, USB, HDD, network folder, FTP, print Straight-through scan paper path for sheet and cardboard originals, adjustable paper pressure for very thin media. Face-down, front entry, rear exit, rewind to front, use document return guide for front-return. Automatic high adjustment of scanner bridge for thick originals up to 15 mm (0.6 in) thickness. Up to 0.6 in (15 mm) 4 GB memory, 500 GB hard disk	
Scan and copy  Media  Memory  Connectivity	Scan speed Enhanced resolution Optical resolution Maximum scan width Scan input modes Handling Thickness Scanner Interfaces (standard)	Grayscale: up to 13 in/sec (33 cm/sec) 9600 dpi 1200 dpi 1210 (1067 mm) File, email, USB, HDD, network folder, FTP, print Straight-through scan paper path for sheet and cardboard originals, adjustable paper pressure for very thin media. Face-down, front entry, rear exit, rewind to front, use document return guide for front-return. Automatic high adjustment of scanner bridge for thick originals up to 15 mm (0.6 in) thickness. Up to 0.6 in (15 mm) 4 GB memory, 500 GB hard disk Dual Gigabit Ethernet (1000Base-T), Hi-Speed USB 3.0 certified	
Scan and copy  Media  Memory  Connectivity	Scan speed Enhanced resolution Optical resolution Maximum scan width Scan input modes Handling Thickness Scanner Interfaces (standard) Sound pressure	Grayscale: up to 13 in/sec (33 cm/sec) 9600 dpi 1200 dpi 1200 dpi 12 in (1067 mm) File, email, USB, HDD, network folder, FTP, print Straight-through scan paper path for sheet and cardboard originals, adjustable paper pressure for very thin media. Face-down, front entry, rear exit, rewind to front, use document return guide for front-return. Automatic high adjustment of scanner bridge for thick originals up to 15 mm (0.6 in) thickness. Up to 0.6 in (15 mm) 4 GB memory, 500 GB hard disk Dual Gigabit Ethernet (1000Base-T), Hi-Speed USB 3.0 certified 48 dB(A) (scanning); <22 dB(A) (ready); <22 dB(A) (sleep)	
Scan and copy  Media  Memory Connectivity Acoustic	Scan speed  Enhanced resolution Optical resolution Maximum scan width Scan input modes Handling  Thickness Scanner Interfaces (standard) Sound pressure Sound power	Grayscale: up to 13 in/sec (33 cm/sec) 9600 dpi 1200 dpi 42 in (1067 mm) File, email, USB, HDD, network folder, FTP, print Straight-through scan paper path for sheet and cardboard originals, adjustable paper pressure for very thin media. Face-down, front entry, rear exit, rewind to front, use document return guide for front-return. Automatic high adjustment of scanner bridge for thick originals up to 15 mm (0.6 in) thickness. Up to 0.6 in (15 mm) 4 GB memory, 500 GB hard disk Dual Gigabit Ethernet (1000Base-T), Hi-Speed USB 3.0 certified 48 dB(A) (scanning); <22 dB(A) (ready); <22 dB(A) (sleep) 6.4 B(A) (scanning); <3.9 B(A) (ready); <3.9 B(A) (sleep)	
Scan and Copy  Media  Memory Connectivity Acoustic	Scan speed  Enhanced resolution Optical resolution Maximum scan width Scan input modes Handling  Thickness Scanner Interfaces (standard) Sound pressure Sound power Consumption	Grayscale: up to 13 in/sec (33 cm/sec) 9600 dpi 1200 dpi 1200 dpi 12 in (1067 mm) File, email, USB, HDD, network folder, FTP, print Straight-through scan paper path for sheet and cardboard originals, adjustable paper pressure for very thin media. Face-down, front entry, rear exit, rewind to front, use document return guide for front-return. Automatic high adjustment of scanner bridge for thick originals up to 15 mm (0.6 in) thickness. Up to 0.6 in (15 mm) 4 GB memory, 500 GB hard disk Dual Gigabit Ethernet (1000Base-T), Hi-Speed USB 3.0 certified 48 dB(A) (scanning); <22 dB(A) (ready); <22 dB(A) (sleep) 6.4 B(A) (scanning); <3.9 B(A) (ready); <3.9 B(A) (sleep) 90 watts (scanning); 80 watts (ready); <3 watts (sleep)	
Scan and Copy  Media  Memory Connectivity Acoustic  Power	Scan speed  Enhanced resolution Optical resolution Maximum scan width Scan input modes Handling  Thickness Scanner Interfaces (standard) Sound pressure Sound power	Grayscale: up to 13 in/sec (33 cm/sec) 9600 dpi 1200 dpi 42 in (1067 mm) File, email, USB, HDD, network folder, FTP, print File, email, USB, HDD, network folder, FTP, print Straight-through scan paper path for sheet and cardboard originals, adjustable paper pressure for very thin media. Face-down, front entry, rear exit, rewind to front, use document return guide for front-return. Automatic high adjustment of scanner bridge for thick originals up to 15 mm (0.6 in) thickness. Up to 0.6 in (15 mm) 4 GB memory, 500 GB hard disk Dual Gigabit Ethernet (1000Base-T), Hi-Speed USB 3.0 certified 48 dB(A) (scanning); <22 dB(A) (ready); <22 dB(A) (sleep) 9.0 watts (scanning); <3.9 B(A) (ready); <3.9 B(A) (sleep) 90 watts (scanning); 80 watts (ready); <3 watts (sleep) 10 yet voltage (auto ranging): 100-240 V (±10%), 50/60 Hz, 5 A max USA and Canada (UL certified), EU (UVD and EN 60950-1 compliant), Russia	
Scan and copy  Media  Memory Connectivity Acoustic  Power	Scan speed  Enhanced resolution Optical resolution Maximum scan width Scan input modes Handling  Thickness Scanner Interfaces (standard) Sound pressure Sound power Consumption Requirements	Grayscale: up to 13 in/sec (33 cm/sec) 9600 dpi 1200 dpi 42 in (1067 mm) File, email, USB, HDD, network folder, FTP, print Straight-through scan paper path for sheet and cardboard originals, adjustable paper pressure for very thin media. Face-down, front entry, rear exit, rewind to front, use document return guide for front-return. Automatic high adjustment of scanner bridge for thick originals up to 15 mm (0.6 in) thickness. Up to 0.6 in (15 mm) 4 GB memory, 500 GB hard disk Dual Gigabit Ethernet (1000Base-T), Hi-Speed USB 3.0 certified 48 dB(A) (scanning); <22 dB(A) (ready); <22 dB(A) (sleep) 6.4 B(A) (scanning); <3.9 B(A) (ready); <3 watts (sleep) 10 watts (scanning); <3.9 watts (ready); <3 watts (sleep) 10 mput voltage (auto ranging): 100-240 V (±10%), 50/60 Hz, 5 A max USA and Canada (UL certified), EU (UVD and EN 60950-1 compliant), Russia (EAC), Singapore (PSB), China (CCC), Argentina (IRAM), Mexico (NYCE), Korea (KC), Canada (ICES), Australia (ACMA), New Zealand (RSM), China (CCC), Japan	
Scan and Copy  Media  Memory Connectivity Acoustic  Power	Scan speed  Enhanced resolution Optical resolution Maximum scan width Scan input modes Handling  Thickness Scanner Interfaces (standard) Sound pressure Sound power Consumption Requirements Safety	Grayscale: up to 13 in/sec (33 cm/sec) 9600 dpi 1200 dpi 1200 dpi 12 in (1067 mm) File, email, USB, HDD, network folder, FTP, print Straight-through scan paper path for sheet and cardboard originals, adjustable paper pressure for very thin media. Face-down, front entry, rear exit, rewind to front, use document return guide for front-return. Automatic high adjustment of scanner bridge for thick originals up to 15 mm (0.6 in) thickness. Up to 0.6 in (15 mm) 4 GB memory, 500 GB hard disk Dual Gigabit Ethernet (1000Base-T), Hi-Speed USB 3.0 certified 48 dB(A) (scanning); <22 dB(A) (ready); <22 dB(A) (sleep) 90 watts (scanning); <3.9 B(A) (ready); <3.9 B(A) (sleep) 90 watts (scanning); 80 watts (ready); <3 watts (sleep) Input voltage (auto ranging): 100-240 V (±10%), 50/60 Hz, 5 A max USA and Canada (UL certified), EU (LVD and EN 60950-1 compliant), Russia (EAC), Singapore (PSB), China (CCC), Argentina (IRAM), Mexico (NYCE), Korea (KCC Compliance for Class A ITE products: EU (EMC Directive), USA (FCC Rules), Canada (ICES), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI), Korea (MSIP), Taiwan (BSM)), Russia (EAC)	
Media  Memory Connectivity Acoustic Power Certification	Scan speed  Enhanced resolution Optical resolution Maximum scan width Scan input modes Handling  Thickness Scanner Interfaces (standard) Sound pressure Sound power Consumption Requirements Safety  Electromagnetic	Grayscale: up to 13 in/sec (33 cm/sec) 9600 dpi 1200 dpi 42 in (1067 mm) File, email, USB, HDD, network folder, FTP, print Straight-through scan paper path for sheet and cardboard originals, adjustable paper pressure for very thin media. Face-down, front entry, rear exit, rewind to front, use document return guide for front-return. Automatic high adjustment of scanner bridge for thick originals up to 15 mm (0.6 in) thickness. Up to 0.6 in (15 mm) 4 GB memory, 500 GB hard disk Dual Gigabit Ethernet (1000Base-T), Hi-Speed USB 3.0 certified 48 dB(A) (scanning); <22 dB(A) (ready); <22 dB(A) (sleep) 6.4 B(A) (scanning); <3.9 B(A) (ready); <3 watts (sleep) 10 watts (scanning); <3.9 watts (ready); <3 watts (sleep) 10 mput voltage (auto ranging): 100-240 V (±10%), 50/60 Hz, 5 A max USA and Canada (UL certified), EU (UVD and EN 60950-1 compliant), Russia (EAC), Singapore (PSB), China (CCC), Argentina (IRAM), Mexico (NYCE), Korea (KC), Canada (ICES), Australia (ACMA), New Zealand (RSM), China (CCC), Japan	
Media  Memory Connectivity Acoustic Power Certification  Other Details Dimensions	Scan speed  Enhanced resolution Optical resolution Maximum scan width Scan input modes Handling  Thickness Scanner Interfaces (standard) Sound pressure Sound power Consumption Requirements Safety  Electromagnetic	Grayscale: up to 13 in/sec (33 cm/sec) 9600 dpi 1200 dpi 1200 dpi 12 in (1067 mm) File, email, USB, HDD, network folder, FTP, print Straight-through scan paper path for sheet and cardboard originals, adjustable paper pressure for very thin media. Face-down, front entry, rear exit, rewind to front, use document return guide for front-return. Automatic high adjustment of scanner bridge for thick originals up to 15 mm (0.6 in) thickness. Up to 0.6 in (15 mm) 4 GB memory, 500 GB hard disk Dual Gigabit Ethernet (1000Base-T), Hi-Speed USB 3.0 certified 48 dB(A) (scanning); <22 dB(A) (ready); <22 dB(A) (sleep) 90 watts (scanning); <3.9 B(A) (ready); <3.9 B(A) (sleep) 90 watts (scanning); 80 watts (ready); <3 watts (sleep) Input voltage (auto ranging): 100-240 V (±10%), 50/60 Hz, 5 A max USA and Canada (UL certified), EU (LVD and EN 60950-1 compliant), Russia (EAC), Singapore (PSB), China (CCC), Argentina (IRAM), Mexico (NYCE), Korea (KCC Compliance for Class A ITE products: EU (EMC Directive), USA (FCC Rules), Canada (ICES), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI), Korea (MSIP), Taiwan (BSM)), Russia (EAC)	
Media  Memory Connectivity Acoustic Power Certification  Other Details Dimensions (w x d x h)	Scan speed  Enhanced resolution Optical resolution Maximum scan width Scan input modes Handling  Thickness Scanner Interfaces (standard) Sound pressure Sound power Consumption Requirements Safety  Electromagnetic  MFP Shipping	Grayscale: up to 13 in/sec (33 cm/sec) 9600 dpi 1200 dpi 121 in (1067 mm) File, email, USB, HDD, network folder, FTP, print Straight-through scan paper path for sheet and cardboard originals, adjustable paper pressure for very thin media. Face-down, front entry, rear exit, rewind to front, use document return guide for front-return. Automatic high adjustment of scanner bridge for thick originals up to 15 mm (0.6 in) thickness. Up to 0.6 in (15 mm) 4 GB memory, 500 GB hard disk Dual Gigabit Ethernet (1000Base-T), Hi-Speed USB 3.0 certified 48 dB(A) (scanning); <22 dB(A) (ready); <22 dB(A) (sleep) 6.4 B(A) (scanning); <22 dB(A) (ready); <3.9 B(A) (sleep) 90 watts (scanning); 80 watts (ready); <3 watts (sleep) Input voltage (auto ranging): 100-240 V (±10%), 50/60 Hz, 5 A max USA and Canada (UL certified), EU (LVD and EN 60950-1 compliant), Russia (EAC), Singapore (PSB), China (CCC), Argentina (RANM), Mexico (NYCE), Korea (KC) canada (ICES), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI), Korea (MSIP), Taiwan (BSMI), Russia (EAC) ENERGY STAR, WEEE, ROHS (EU, China, Korea, India), REACH, EPEAT Bronze 69.6 x 44.9 x 59.1 in (1770 x 1140 x 1500 mm) 76.0 x 27.9, 57.1 in (1930 x 710 x 1450 mm)	
Media  Memory Connectivity Acoustic  Power  Certification  Other Details Dimensions (w x d x h)	Scan speed Enhanced resolution Optical resolution Maximum scan width Scan input modes Handling  Thickness Scanner Interfaces (standard) Sound pressure Sound power Consumption Requirements Safety Electromagnetic Environmental  MFP Shipping MFP	Grayscale: up to 13 in/sec (33 cm/sec) 9600 dpi 1200 dpi 121 in (1067 mm) File, email, USB, HDD, network folder, FTP, print Straight-through scan paper path for sheet and cardboard originals, adjustable paper pressure for very thin media. Face-down, front entry, rear exit, rewind to front, use document return guide for front-return. Automatic high adjustment of scanner bridge for thick originals up to 15 mm (0.6 in) thickness. Up to 0.6 in (15 mm) 4 GB memory, 500 GB hard disk Dual Gigabit Ethernet (1000Base-T), Hi-Speed USB 3.0 certified 48 dB(A) (scanning); <22 dB(A) (ready); <22 dB(A) (sleep) 90 watts (scanning); <3.9 B(A) (ready); <3.9 B(A) (sleep) 90 watts (scanning); 80 watts (ready); <3 watts (sleep) Input voltage (auto ranging): 100-240 V (±10%), 50/60 Hz, 5 A max USA and Canada (UL certified), EU (LVD and EN 60950-1 compliant), Russia (EAC), Singapore (PSB), China (CCC), Argentina (IRAM), Mexico (NYCE), Korea (KC Compliance for Class A ITE products: EU (EMC Directive), USA (FCC Rules), Canada (ICES), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCC), Korea (MSIP), Taiwan (BSM)), Russia (EAC) ENERGY STAR, WEEE, RoHS (EU, China, Korea, India), REACH, EPEAT Bronze	
Media  Memory Connectivity Acoustic  Power  Certification  Other Details Dimensions (w x d x h) Weight What's in	Scan speed  Enhanced resolution Optical resolution Maximum scan width Scan input modes Handling  Thickness Scanner Interfaces (standard) Sound pressure Sound power Consumption Requirements Safety Electromagnetic  Environmental  MFP Shipping MFP Shipping Printer: HP Design Jet Zicartridges, printer sea Head	Grayscale: up to 13 in/sec (33 cm/sec) 9600 dpi 1200 dpi 12 in (1067 mm) File, email, USB, HDD, network folder, FTP, print Straight-through scan paper path for sheet and cardboard originals, adjustable paper pressure for very thin media. Face-down, front entry, rear exit, rewind to front, use document return guide for front-return. Automatic high adjustment of scanner bridge for thick originals up to 15 mm (0.6 in) thickness. Up to 0.6 in (15 mm) 4 GB memory, 500 GB hard disk Dual Gigabit Ethernet (1000Base-T), Hi-Speed USB 3.0 certified 48 dB(A) (scanning); <22 dB(A) (ready); <22 dB(A) (sleep) 6.4 B(A) (scanning); <22 dB(A) (ready); <3 watts (sleep) 10 watts (scanning); 80 watts (ready); <3 watts (sleep) 11 uput voltage (auto ranging): 100-240 V (±10%), 50/60 Hz, 5 A max USA and Canada (UL certified), EU (LVD and EN 60950-1 compliant), Russia (EAC), Singapore (PSB), China (CCC), Argentina (RAM), Mexico (NVCE), Korea (KC) Canada (ICES), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI), Korea (MSIP), Taiwan (BSMI), Russia (EAC) ENERGY STAR, WEEE, ROHS (EU, China, Korea, India), REACH, EPEAT Bronze 69.6 x 44.9 x 59.1 in (1770 x 1140 x 1500 mm) 76.0 x 27.9, 57.1 in (1930 x 710 x 1450 mm) 346 lb (157 kg) 445.3 lb (202 kg) 66r 44-in PostScript Printer with V-Trimmer, printheads, introductory ink	
Media  Memory Connectivity Acoustic  Power  Certification  Other Details Dimensions (w x d x h) Weight What's in the box	Scan speed  Enhanced resolution Optical resolution Maximum scan width Scan input modes Handling  Thickness Scanner Interfaces (standard) Sound pressure Sound power Consumption Requirements Safety  Electromagnetic  Environmental  MFP Shipping MFP Shipping Printer: HP DesignJet Z cartridges, printer stand power cord; Scanner: H media guides, setup po power cord; Scanner: H media guides, setup po power cord; Scanner: H media guides, setup po power cord; Scanner: H	Grayscale: up to 13 in/sec (33 cm/sec) 9600 dpi 1200 dpi 12 in (1067 mm) File, email, USB, HDD, network folder, FTP, print Straight-through scan paper path for sheet and cardboard originals, adjustable paper pressure for very thin media. Face-down, front entry, rear exit, rewind to front, use document return guide for front-return. Automatic high adjustment of scanner bridge for thick originals up to 15 mm (0.6 in) thickness. Up to 0.6 in (15 mm) 4 GB memory, 500 GB hard disk Dual Gigabit Ethernet (1000Base-T), Hi-Speed USB 3.0 certified 48 dB(A) (scanning); <22 dB(A) (ready); <22 dB(A) (sleep) 6.4 B(A) (scanning); <3.9 B(A) (ready); <3 matts (sleep) 10 muts (scanning); <3.9 B(A) (ready); <3 matts (sleep) 10 muts (scanning); <3.9 B(A) (ready); <3 matts (sleep) 10 mut voltage (auto ranging): 100-240 V (±10%), 50/60 Hz, 5 A max USA and Canada (UL certified), EU (LVD and EN 60950-1 compliant), Russia (EAC), Singapore (PSB), China (CCC), Argentina (IRAM), Mexico (NYCE), Korea (KC, Canada (ICES), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCC), Korea (MSIP), Taiwan (BSMI), Russia (EAC) ENERGY STAR, WEEE, ROHS (EU, China, Korea, India), REACH, EPEAT Bronze 69.6 x 44.9 x 59.1 in (1770 x 1140 x 1500 mm) 76.0 x 27.9, 57.1 in (1930 x 710 x 1450 mm) 346 lb (157 kg) 6dr 44-in PostScript Printer with V-Trimmer, printheads, introductory ink d and media bin, spindle, 3-in core adapter, quick reference guide, setup poster	
Media  Memory Connectivity Acoustic  Power  Certification  Other Details Dimensions (w x d x h) Weight What's in the box	Scan speed  Enhanced resolution Optical resolution Maximum scan width Scan input modes Handling  Thickness Scanner Interfaces (standard) Sound pressure Sound power Consumption Requirements Safety  Electromagnetic  Environmental  MFP Shipping MFP Shipping Printer: HP DesignJet Z cartridges, printer stand power cord; Scanner: H media guides, setup po power cord; Scanner: H media guides, setup po power cord; Scanner: H media guides, setup po power cord; Scanner: H	Grayscale: up to 13 in/sec (33 cm/sec) 9600 dpi 1200 dpi 42 in (1067 mm) File, email, USB, HDD, network folder, FTP, print Straight-through scan paper path for sheet and cardboard originals, adjustable paper pressure for very thin media. Face-down, front entry, rear exit, rewind to front, use document return guide for front-return. Automatic high adjustment of scanner bridge for thick originals up to 15 mm (0.6 in) thickness. Up to 0.6 in (15 mm) 4 GB memory, 500 GB hard disk Dual Gigabit Ethernet (1000Base-T), Hi-Speed USB 3.0 certified 48 dB(A) (scanning); <22 dB(A) (ready); <22 dB(A) (sleep) 9.4 dB(A) (scanning); <3.9 B(A) (ready); <3.9 B(A) (sleep) 90 watts (scanning); <3.9 B(A) (ready); <3.9 watts (sleep) 10 untual (scanning); <3.9 B(A) (ready); <3.9 watts (sleep) 90 watts (scanning); <3.9 b(A) (ready); <3.9 watts (sleep) 90 watts (scanning); <3.9 b(A) (ready); <3.9 watts (sleep) 90 watts (scanning); <3.9 b(A) (ready); <3.9 watts (sleep) 90 watts (scanning); <3.9 b(A) (ready); <3.9 watts (sleep) 90 watts (sleep) 90 watts (scanning); >3.9 b(A) (ready); <3.9 watts (sleep) 90	

### Ordering information

Product	2QX51A	HP DesignJet HD Pro 44-in MFP
Accessories	CN538A	HP USB 3.0 to Gigabit LAN Adapter
	N7P47A	HP Jetdirect 640n Print Server
	Q6709A	HP DesignJet 44-in Spindle
	1QF38A	HP DesignJet 44-in Take-up Reel
Original HP	F9J86A	HP 744 Photo Black and Cyan DesignJet Printhead
printheads	F9J87A	HP 744 Magenta and Yellow DesignJet Printhead
	F9J88A	HP 744 Matte Black and Chromatic Red DesignJet Printhead
Original HP	P2V81A	HP 746 300-ml Chromatic Red DesignJet Ink Cartridge
ink cartridges	P2V80A	HP 746 300-ml Cyan DesignJet Ink Cartridge
	P2V78A	HP 746 300-ml Magenta DesignJet Ink Cartridge
	P2V83A	HP 746 300-ml Matte Black DesignJet Ink Cartridge
	P2V82A	HP 746 300-ml Photo Black DesignJet Ink Cartridge
	P2V79A	HP 746 300-ml Yellow DesignJet Ink Cartridge
Original HP large format printing materials	Q6581A	HP Universal Instant-dry Satin Photo Paper (FSC® certified) <sup>5</sup> 42 in x 100 ft (1067 mm x 30.5 m)
materiats	E4J57A	HP Artist Matte Canvas 44 in x 50 ft (1118 mm x 15.2 m)
	C6569C	HP Heavyweight Coated Paper (FSC® certified) <sup>5</sup> 🍪 42 in x 100 ft (1067 mm x 30.5 m)
	CH025A	HP Everyday Matte Polypropylene, 2 Pack 🛟 42 in x 100 ft (1067 mm x 30.5 m)
	CG460B	HP Premium Matte Photo Paper (FSC® certified)⁵ 🏰 42 in x 100 ft (1067 mm x 30.5 m)
	CG460B	HP Premium Matte Photo Paper (FSC® certified) <sup>s</sup> 🛟 36 in x 100 ft (914 mm x 30.5 m)
Service and Support	U9ZE2E	HP 3 year Next Business Day plus Defective Media Retention Support
	U9ZE4E	HP 5 year Next Business Day plus Defective Media Retention Support
	U9ZE5PE	HP 1 year Post Warranty, Next Business Day plus Defective Media Retention Support
	H4518E	HP Network Installation Service with Network Setup

HP DesignJet Support Services offer solutions for business critical environments — installation, extended support and maintenance, as well as variety of value added services. For more information, please visit  $\underline{\mathsf{hp.com/go/DesignJetsupport}}.$ 

Use Original HP inks printheads, and HP large format printing materials, to experience consistent high quality and reliable performance that enable less downtime. These critical components are designed and engineered together as an optimized printing system, and Original HP inks are designed to maximize the life of HP printheads. Protect your HP printer investment by using Original HP inks for full HP warranty protection. For more information, visit hp.com/go/OriginalHPinks.

- Maximum rate of output for color image 100% color coverage. Printed in Economode, on HP Bright White Inkjet Paper (bond), maximum roll size, with Original HP Vivid Photo Inks.

  Mechanical printing time with Original HP Vivid Photo Inks.
- Except self-adhesive vinyls and non-cuttable medias.
- Based on 4 GB RAM.
- BMG trademark license code FSC®-C115319, see fs.corg. HP trademark license code FSC®-C017543, see fs.corg. Not all FSC®-certified products are available in all regions.

  Recyclable HP papers can be recycled through commonly available recycling programs, or according to region-
- specific practices, or can be returned through the HP Large Format Media take-back program. Recycling programs may not exist in your area. See HPLFMedia.com/hp/ecosolutions for details.

### **Eco Highlights**

- ENERGY STAR® certified¹, EPEAT® Silver registered as environmentally preferable product²
- Breakthrough color consistency can help reduce unnecessary reprints
- Printer made from 30% post-consumer recycled plastic; free HP printing supplies recycling<sup>3</sup>
- FSC®-certified papers<sup>4</sup>, range of recyclable HP media with a take-back program<sup>5</sup>
- <sup>1</sup> ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency.
- <sup>2</sup> EPEAT® registered where applicable. EPEAT registration varies by country. See epeat.net for registration status by country.
- <sup>3</sup> Program availability varies. Please check hp.com/recycle for details.
- 4 BMG trademark license code FSC®-C11539, see fs.corg. HP trademark license code FSC®-C017543, see fs.corg. Not all FSC®-certified products are available in all regions.
- 5 HP Large Format Media take-back program availability varies. Some recyclable HP papers can be recycled through commonly available recycling programs. Recycling programs may not exist in your  $area.\,See\, \underline{\text{HPLFMedia.com/hp/ecosolutions}}\,for\, details.$

Please recycle large-format printing hardware and printing supplies. Find out how at our website

hp.com/ecosolutions



















