UHD Commercial TV with Essential Smart Function

The UT640S series is specifically designed for diverse business environments. By providing compatibility with AV Control systems and DPM (Display Power Management) as well as its smart connectivity, simple user-friendly interface, and UHD picture quality, the UT640S series enhances ease of use while facilitating communications between businesses and their target audiences.



Simple Content Management



Higher Visibility



Better Usability





Embedded Content & Group Management

The embedded Content and Group Management System allows you to edit and play content, schedule playlists and groups, and control signage via remote control, mouse and mobile phone without the use of separate PC or software. This makes content management much easier and more user-friendly.

SuperSign Control

SuperSign Control is the basic control software, and it can manage up to 100 displays through a single account and server. Power, volume, and scheduling can be remotely adjusted, and firmware updates are supported.

USB Data Cloning

USB data cloning increases efficiency in managing multiple displays for optimal operation since users don't have to set up each display one by one. Once users copy data to a USB device in one display, it can be easily distributed to the other displays through a USB plug-in.







 $[\]ensuremath{^{\star}}$ These images are provided for illustrative purposes, and the actual GUI may differ.

^{*} All displays must be connected to the same network.

Real-Time Remote Monitoring

Malfunctions or errors can be easily handled through real-time remote care. When an error occurs, notifications can be sent through the SNMP (Simple Network Management Protocol) protocol.

WOL (Wake-on-LAN)

WOL (Wake-on-LAN) enables users to send a message throughout the network to power on displays.



True Color, Immersive View

The UT640S series is large enough to enhance the visibility of content and captivate viewers. The IPS panel provides a wide range of viewing angles so that content can be clearly seen, regardless of the viewer's position. Each pixel in the IPS panel reproduces true-to-life colors without distorting images.



Perfect Picture Quality and Color

Enjoy Full HD content in 4K ULTRA HD quality, optimized by the 4K Upscaler. The 4K upscaler automatically upgrades Full HD content to ULTRA HD through several upscaling processes so that images look crisp and clear in any viewing situation. This LG TV can also express intense highlights, vivid colors, and deep black hues on the screen through HDR10.




Compatibility with AV Control Systems

The UT640S series has been certified Crestron Connected®, proving that it has a higher level of compatibility with professional AV controls. This results in seamless integration and automated control*, boosting business management efficiency.


DPM (Display Power Management)

From now on, you can configure the DPM (Display Power Management) function by setting it to On. When there is no signal, the TV enters DPM mode to manage power more efficiently.










^{*} Dimensions & Jack Panels (Read/Side) may differ from the above image, so please contact LG sales team to verify before ordering.


* The UT640S series basically have a two-pole stand, but it is able to detach the stand from the body, per service environment (can be used as a wall-mount unit).

CONNECTIVITY Commercial TV | UT640S Series (EU/CIS)


75"



65" | 60" | 55" | 49" | 43"



70"



^{*} Dimensions & Jack Panels (Read/Side) may differ from the above image, so please contact LG sales team to verify before ordering.

* The UT640S series basically have a two-pole stand, but it is able to detach the stand from the body, per service environment (can be used as a wall-mount unit).

UT640S	series (EU/CIS)	75UT640S	70UT640S	65UT640S	60UT640S	55UT640S	49UT640S	43UT640S
DESIGN	Stand Type	2 Pole (No-Stand available)	2 Pole (No-Stand available)	2 Pole (No-Stand available)	2 Pole (No-Stand available)	2 Pole (No-Stand available)	2 Pole (No-Stand available)	2 Pole (No-Stand available)
	Front Color	Dark Meteo Titan	Ceramic Black	Ceramic Black	Ceramic Black	Ceramic Black	Ceramic Black	Ceramic Black
DISPLAY	Inch	75	70	65	60	55	49	43
	Resolution	3,840 X 2,160 (UHD)	3,840 X 2,160 (UHD)	3,840 X 2,160 (UHD)	3,840 X 2,160 (UHD)	3,840 X 2,160 (UHD)	3,840 X 2,160 (UHD)	3,840 X 2,160 (UHD)
	Brightness (cd/m²)	350	350	400	350	400	400	300
BROADCASTING SYSTEM	TV Reception	DVB-T2 / C / S2	DVB-T2 / C / S2	DVB-T2 / C / S2	DVB-T2 / C / S2	DVB-T2 / C / S2	DVB-T2 / C / S2	DVB-T2 / C / S2
VIDEO	HDR (10 Pro / HLG)	Yes / Yes	Yes / Yes	Yes / Yes	Yes / Yes	Yes / Yes	Yes / Yes	Yes / Yes
AUDIO	Audio Output	10W + 10W	10W + 10W	10W + 10W	10W + 10W	10W + 10W	10W + 10W	10W + 10W
	Speaker System	2.0 ch	2.0 ch	2.0 ch	2.0 ch	2.0 ch	2.0 ch	2.0 ch
	DOLBY ATMOS	-	-	-	-	-	-	-
	One Touch Sound Tuning	-	-	-	-	-	-	-
	LG Sound Sync	Bluetooth required	Bluetooth required	Bluetooth required	Bluetooth required	Bluetooth required	Bluetooth required	Bluetooth required
SUPERSIGN SW COMPABILITY	Content Management Software (SuperSign CMS), Control and Monitoring Software (Control/Control+), Simple Editor							
SIGNAGE FEATURE	Crestron Connected® (Network Based Control), DPM (Digital Power Management), Time Scheduler, RTC (Real Time Clock), NTP sync timer, BEACON, Embedded CM (Contents Manager), Embedded GM (Group Manager)							
SMART FEATURE	webOS 4.5, Smart Home (Launcher Bar), Web Browser, Pre-loaded App (YouTube only), Soft AP, Wi-Fi (802.11ac, Built-in type), Screen Share (Miracast), DIAL, Bluetooth Audio Playback, LG Sound Sync/Bluetooth, Mobile Connection Overlay							
HOSPITALITY FEATURE	Hotel Mode (Installer Menu), Lock Mode (Limited), Welcome Screen (Splash Image), Insert Image, One Channel Map, IP Channel Manager, External Speaker Out (Int/Ext Variable/Fixed, 3.5mm, Stereo, Single ended Type (GND, L+, R+), 2W with 80), RJP (Remote Jack Pack) Compatibility (LG/Teleadapt (RS232C), Teleadapt/Guestlink (HDMI CEC)), Auto Off/Sleep Timer, Smart Energy Saving, Motion Eye Care							
MAINTENANCE FEATURE	USB Cloning, WOL, SNMP, Diagnostics (Self Diagnostics (USB)), SI Compatible (TVLink Tuner), Simplink (HDMI-CEC (1.4)), IR Out (RS-232C, HDMI), Multi IR Code							
JACK INTERFACE	Set Side HDMI in 2 (2.0), USB (2.0), CI Slot							
	Set Rear HDMI In (HDCP (2.0)), CI Slot, RF In 2, Digital Audio Out (Optical), RS-232C (D-Sub 9pin (Control & Service)), RJ45 (Ethernet), External Speaker Out (3.5mm phone jack) 2 (Spk-out 1, 4W (Stereo, R: 2.0W, L: 2.0W, BO) Vol. Control 1), Debug (Phone Jack Type (Ext. SPK Volume Control Share))							
DIMENSIONS (UNIT : mm / kg)	VESA	600 x 400	600 x 400	300 x 300	300 x 300	300 x 300	300 x 300	200 x 200
	W x H x D / Weight (with stand)	1,693 x 1,048 x 345 / 35.4	1,578 x 984 x 299 / 31.4	1,463 x 914 x 269 / 21.6	1,368 x 862 x 269 / 19.8	1,244 x 786 x 231 / 14.5	1,110 x 709 x 231 / 11.3	973 x 623 x 216 / 8.1
	W x H(H') x D / Weight (without stand)	1,693 x 978 x 88.8 / 34.6	1,578 x 913 x 91.1 / 30.7	1,463 x 850 x 87.8 / 21.4	1,368 x 796 x 89.1 / 19.4	1,244 x 726 x 87.1 / 14.3	1,110 x 650 x 81.1 / 11.1	973 x 572 x 85.0 / 8.0
		1,823 x 1,116 x 231 / 45.7	1,705 x 1,075 x 228 / 39.7	1,600 x 970 x 190 / 28.4	1,492 x 880 x 190 / 25.5	1,360 x 835 x 175 / 19.5	1,193 x 770 x 158 / 13.4	1,060 x 660 x 152 / 10.2
	W x H x D / Weight (Shipping)	1,023 X 1,110 X 231 / 43.7						
	WxHxD/Weight (Shipping) Voltage, Hz	100 - 240V, 50/60 Hz	100 - 240V, 50/60 Hz	100 ~ 240V, 50/60 Hz	100 ~ 240V, 50/60 Hz	100 ~ 240V, 50/60 Hz	100 ~ 240V, 50/60 Hz	100 ~ 240V, 50/60 Hz
POWER (UNIT : WATTS)			100 ~ 240V, 50/60 Hz	100 ~ 240V, 50/60 Hz 182.6 W	100 ~ 240V, 50/60 Hz 182.1 W	100 ~ 240V, 50/60 Hz 145 W	100 ~ 240V, 50/60 Hz	100 ~ 240V, 50/60 Hz 99.1 W

 $^{^{\}star}$ Specifications are subject to change without notice, so please contact LG sales team to verify before ordering.





