

Mini Needle Valves

6,000 psi



* MRC & MRS Series pressure rating at 6,000 psi.

Not recommended for over 4,000 psi due to difficult turning of round handle.

* MTC & MTS Series pressure rating at 6,000 psi.

Dimensions

SIZE	CARBON PART #	STAINLESS PART #	A	B	C	D	E
1/4" M x 1/4" F	MRC2M2F	MRS2M2F	1.85"	0.47"	1.97"	1.02"	0.75"
1/4" M x 1/4" M	MRC2M2M	MRS2M2M	1.85"	0.47"	1.97"	1.02"	0.75"
1/4" F x 1/4" F	MRC2F2F	MRS2F2F	1.85"	0.47"	1.97"	1.02"	0.75"

Dimensions

SIZE	CARBON PART #	STAINLESS PART #	A	B	C	D	E
1/4" M x 1/4" F	MTC2M2F	MTS2M2F	2.28"	0.87"	2.28"	1.81"	0.75"
1/4" M x 1/4" M	MTC2M2M	MTS2M2M	2.28"	0.87"	2.28"	1.81"	0.75"
1/4" F x 1/4" F	MTC2F2F	MTS2F2F	2.28"	0.87"	2.28"	1.81"	0.75"

Materials

PART	CARBON	316 STAINLESS
1 HANDLE	CARBON STEEL	304 STAINLESS
2 STEM	304 STAINLESS	316 STAINLESS
3 BONNET	CARBON STEEL	316 STAINLESS
4 BODY	CARBON STEEL	316 STAINLESS
5 SEAT	DELRIN SOFT	DELRIN SOFT

Materials

PART	CARBON	316 STAINLESS
1 HANDLE	CARBON STEEL	304 STAINLESS
2 STEM	304 STAINLESS	316 STAINLESS
3 BONNET	CARBON STEEL	316 STAINLESS
4 BODY	CARBON STEEL	316 STAINLESS
5 SEAT	HARD SEAT	HARD SEAT

