## 2 Port USB to RS232 Serial DB9 Adapter Cable

*StarTech ID: ICUSB232C2*

The StarTech.com ICUSB232C2 2 port USB to DB9 RS232 Serial Adapter Cable lets you connect up to two DB9 RS232 serial devices simultaneously to your Mac or PC laptop or desktop computer through a USB port, as though the computer offered an onboard DB9M connector.

A cost-effective solution that bridges the compatibility gap between modern computers and legacy serial peripherals.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

### Applications

- Perfect for IT Administrators looking to add legacy functionality to newer notebooks, PCs and servers that lack an integrated RS232 port
- Connect, monitor and control industrial/automotive sensors and equipment
- Connect bar code scanners, receipt printers and other point of sale devices
- Connect a satellite receiver, serial modem, or PDA with serial sync
- Connect and program LED and Digital signage boards with serial communication ports

**Features**

- USB to 2 Port Straight-Through RS232 Serial Adapter
- Easy Plug-and-Play installation
- Bus powered, no external power adapter required
- Fully compliant with USB 1.1 specifications

**Technical Specifications**

| | |
|---|---|
| Warranty | 2 Years |
| Bus Type | USB 2.0 |
| Chipset ID | Prolific - PL-2303 |
| Interface | Serial |
| Port Style | Cable Adapter |
| Ports | 2 |
| FIFO | 192 Bytes |
| Maximum Data Transfer Rate | 230Kbps |
| Serial Protocol | RS-232 |
| Connector Type(s) | 1 - USB A (4 pin) Male |
| Connector Type(s) | 2 - DB-9 (9 pin; D-Sub) Male |
| OS Compatibility | Windows® 7 (32/64bit), Vista (32/64), XP (32/64), 2000, ME, 98SE, CE 4.2, 5.2<br>Windows Server® 2012, 2008 R2, 2003<br>Mac OS® 10.x (Tested up to 10.10)<br>Linux 2.4.x – 3.9.x |
| System and Cable Requirements | 1 USB 1.1 (or above) port |
| Cable Length | 1 ft [0.3 m] |
| Color | Black |
| Enclosure Type | Plastic |
| Product Length | 12.2 in [310 mm] |
| Product Weight | 4.1 oz [115 g] |
| Humidity | 0~65% RH |
| Operating Temperature | 0°C to 60°C (32°F to 140°F) |
| Storage Temperature | -20°C to 80°C (-4°F to 176°F) |
| Shipping (Package) Weight | 0.3 lb [0.1 kg] |
| Included in Package | 1 - 2 Port USB to RS232 Serial Cable |

**Certifications, Reports and Compatibility**