

PULSAFEEDER[®]

METERING PUMPS AND CONTROL SYSTEMS

Product List Schedule

Effective 1/15/08



PULSAFEEDER

27101 Airport Road, Punta Gorda, FL 33982
Phone: 941-575-3800 Fax: 941-575-4085
800-333-6677 800-456-4085
www.pulsafeeder.com www.pulsatron.com

IDEX FLUID & METERING

Agriculture
Chemical Processing
Fuels & Energy
Sanitary
Water

TABLE OF CONTENTS

Important Information

When Placing An Order.....	3
Feature Selection Guide	4
Model Selection Guide.....	5-11

PULSAtron Electronic Metering Pumps

Series MP	12-13
Series E Plus	14-15
Series HV	16-17
Series E	18-19
Series E-DC	20-21
Series D	22-23
Series A Plus	24-25
Series C Plus	26-27
Series C	28-29

PULSAtron PLUS Electronic Metering Pumps with Integrated Controller

Series CW	30-31
Series CL.....	32-33
Series WT	34-35
Series ET.....	36-37
Series T7	38-39

Electronic Metering Pump Accessories

KOPkits.....	40-41
Suction/Discharge Valves	42
Parts	43-45

OMNI Mechanical Diaphragm Pumps

Model Selection	46-48
Accessories and KOPkits.....	49

Chem-Tech Pumps

Peristaltic:	
Series CTP and Parts	50-51
Mechanical Diaphragm:	
Prime Performance	52
Series 100, 100D, 150, 150D, 200 and Parts	53-56
Series 250 and Parts	57
Series 300 and Parts	58-59
Piston:	
Series 400	60
Series 500 and Parts	61-62

Mec-O-Matic Pumps

Diaphragm:	
Stingray 100, 200 and Parts	63-64
T-2000 and Parts	65
Peristaltic:	
Dolphin Series and Related Parts	65
VSP Series and Parts	66
2400T, 2400T Plus, 2400T-DC and Parts	67

<u>Policies and Procedures</u>	68-69
---	-------

<u>Terms and Conditions</u>	70
--	----

DUE TO CONTINUOUS IMPROVEMENT OF OUR PRODUCTS, WE RESERVE THE RIGHT TO UPDATE THE INFORMATION CONTAINED IN THIS CATALOG WITHOUT NOTICE.

IMPORTANT INFORMATION

WHEN PLACING AN ORDER

- 1) Fax, mail or telephone orders directly to the Customer Service Department:

Pulsafeeder Incorporated—A Unit of IDEX Corporation
Standard Product Operations Main Office & Manufacturing Facility
27101 Airport Road, Punta Gorda, Florida, USA 33982-2462 E-Mail: pulsaspo.cs@idexcorp.com
Telephone: 800-333-6677 or 941-575-3800 Fax: 800-456-4085 or 941-575-4085
www.pulsatron.com

- 2) Please have the following information available when placing an order:

Account Name	Special Tags or Marks (if needed)
Billing Zip Code	Item(s) Being Ordered
Purchase Order Number	Quantity of Each Item
Ship To Address	

- 3) Orders are immediately entered into the computer upon receipt. Our ability to change in house orders is limited. Please be certain your orders are complete when placed.
- 4) For assistance or to order a "special" pump model not available in the price schedule, please contact our Technical Support Department.
- 5) Orders are assigned standard lead times based on the size of the order and the time required to manufacture the particular products. Requests to expedite orders may be routed through our Customer Service Department.
- 6) Repairs and returns are coordinated through our Customer Service Department. All orders returned must have factory authorization and are subject to a 25% restocking charge.

- 7) Other Locations:

PULSAFEEDER (Knight UK Limited)

15 Brunel Centre Newton Road
Crawley, West Sussex, England, RH10 9YU
Tel: +44 80022102210
Fax: +44 80044104410

Far East (Office Only)

Room 3403, South Tower, Hong Kong Plaza
No 283 Huai Hai Zhong Road
Shanghai 200021, China
Tel: 86-2163906367
Fax: 86-2163863338

Latin America (Office Only)

Hegel 153-602, Colonia Polanco,
11560 Mexico, D.F., Mexico
Tel: 52-555-255-1357
Fax: 52-555-255-1356

IDEX India Private Ltd.

202 Matharu Arcade
32, Subhash Road, Vile Parie (East),
Mumbai-400 057, India
Tel: 91-22-66976631
Fax: 91-22-66976633

- Prices are subject to change without notice and are effective when order is accepted and acknowledged at point of shipment.
- When ordering, specify your P.O. number, model number, quantity, price, shipping and/or billing address and order date.
- **Standard terms are NET 30 days from date of invoice for approved accounts on open account.**
- **WE ACCEPT VISA AND MASTERCARD.**
- **TWO PERCENT DISCOUNT AVAILABLE FOR PAYMENT WITHIN 10 DAYS OF INVOICE DATE FOR ACCOUNTS THAT ARE CURRENT.**
- **PAYMENT BY CREDIT CARD WILL NOT RECEIVE AN ADDITIONAL DISCOUNT.**
- All prices are F.O.B. Punta Gorda, FL or factory warehouse location.
- Custom product sales are final.
- Charges for export documentation apply.
- Expediting fees may apply.
- Fees for changes to or cancellation of orders may apply.
- **Minimum factory order of \$50.**
- Possession of price schedule does not guarantee right to purchase direct from factory.

Pulsafeeder offers one of the most flexible electronic metering pumps in the world. The product can be configured to meet a large variety of applications and needs. The next few pages will guide you in structuring a complete and correct model number.

The first step in selecting the right model for your application is to select the correct Series. Each Series offers a variety of features that distinguish it from other Series. Within each Series are selections of models that offer different flow/pressure envelopes to choose from.

The following descriptions will help you understand the different features and then the chart at the bottom of the page will let you select the appropriate models that have the features you need.

4-20mA	Control the pump stroke frequency based on a current input signal from an external device. At 4mA input, the pump will not stroke. At 20mA input, the pump will stroke 100%
20-4mA	Same as 4-20 except that at 20mA input, the pump will not stroke and at 4mA input, the pump strokes at 100%.
External Pace / Water Meter	Allows the pump stroke to be controlled by an external dry contact closure, such as is provided by a Water Meter. For each closure, the pump will stroke one time. Some models provide the ability to multiply or divide the pulses.
Stop Function	A dry contact input that will stop the pump on closure and allow the pump to operate when open.
Touch Pad	Electronic 'touch pad' control with internationally recognized symbols.
Digital Display	Pump parameters are displayed on an LCD or LED type display.
Signal Relay	Provides a 24V DC signal output from the pump based on user specified conditions.
Power Relay	Provides AC power output from the pump based on user specified conditions.
Alarm Display	Flashing display or LED indicator that will display an alarm condition on the front panel of the pump.
Timed Sequences	Ability to pre-program operation for repetitive metering.
Programmable Timer	Timer that can be programmed with up to 8 on/off cycles per day during a 7-day week.
Hall Effect	Hall Effect Water Meter input.
Conductivity Control	Includes a conductivity controller built into the pump.
Bleed Relay	Separate relay used to control a solenoid that will "Bleed" a cooling tower as part of a control system.
Timer Control	User defined timer functions that control when the pump will operate. Used in Cooling Tower control systems.
Flow Control	Optional Flow Switch turns pump on when flow is active.

Series	Flow Capacity		Pressure		Turn Down Ratio	4-20 mA	20-4 mA	External Pace And Stop Function	External Pace Or Stop Function	Touch Pad	Digital Display	Signal/Power Relay	Alarm Signals	Timed Sequences	Programmable Timer	Hall Effect Input	Conductivity Control	Bleed Relay	Timer Control	Flow Control	
	GPH	LPH	PSIG	BAR																	
MP	0.13 to 21	0.50 to 79.5	20 to 300	1.3 to 21	1000:1	S	S	S		S	S	S	S	S							
E Plus	0.13 to 25	0.50 to 94.6	30 to 300	2.0 to 21	100:1	O		O													
HV	0.50 to 10	1.9 to 37.9	80 to 100	5.6 to 17	100:1	O															
E	0.13 to 25	0.50 to 94.6	20 to 300	1.3 to 21	100:1																
E-DC	0.25 to 1.85	0.90 to 7.0	100 to 150	7 to 10	100:1																
D	0.25 to 2	0.90 to 7.6	50 to 250	3.3 to 17	100:1			S		S	S										S
A Plus	0.25 to 2	0.90 to 7.6	50 to 250	3.3 to 17	100:1				O												
C Plus	0.25 to 1.25	0.90 to 4.7	80	5.6	100:1				O												
C	0.25 to 1.25	0.90 to 4.7	80	5.6	10:1				O												
CW	0.25 to 1.25	0.90 to 4.7	100 to 150	7 to 10	100:1			S		S	S					S	S	S	S	S	S
CL	0.25 to 1.25	0.90 to 4.7	100 to 150	7 to 10	100:1					S	S						S	S	S	S	S
WT	0.25 to 1.25	0.90 to 4.7	100 to 150	7 to 10	100:1			S		S	S					S		S			S
ET	0.21 to 2	0.80 to 79.5	20 to 250	1.3 to 17	100:1			S						S							
T7	0.50 to 2	1.9 to 7.6	100	7	10:1										S						


S = Standard Features O = Optional Features

Once you have selected the appropriate Series, you must configure the model so that it is built with the features you desire. The Configuration Guide associated with each Series will present the most popular selections. Select one code from each category to build up a complete model string.


To help you better understand the model string, in the following pages, we will explain what each of the digits represent and provide you some additional charts to help you select options not found in the Configuration Guides.

Model Selection:

The first four digits represent the Series and Flow/Pressure Selection.



The first digit will always start with the letter 'L'.




Digits 3 & 4 represent the Flow/Pressure Code.

All PULSAtron models begin with this letter. The second letter designates the Series (e.g. Series MP, Series E+, Series A+, etc.). Each series has a different set of features that are available in terms of control and flow/pressure capacity. The next two digits represent the flow/pressure capacity of the pump.

This code represents the specific flow/pressure rating for the model and can be found in the specification for each Series.

Series Code Designator	
Series MP	M
Series E Plus	P
Series HV	V
Series E	E
Series E-DC	S
Series D	F
Series A Plus	B
Series C Plus	D
Series C & T7	C
Series CW	W
Series CL	L
Series WT	Q
Series ET	T



Digits 5 & 6 represent the Controls and Electrical selections.

These selections are explained for each model in the Configuration Guide.

Selecting the Wet-End Code & Connection Type:

Digits 7-10 in the string represent the wet-end code. It is the group of four digits set apart by the dash lines.

LB02SA-PTC1



These four digits represent your wet-end code and connection type.

The four digits in the wet-end code represent the Head Material, Seats & O-Rings, Ball Material and Connection type. Using the above example, the code breaks down as follows:

- P** - Head Material, including fittings. In this example, the P represents GFPPPL.
- T** - Seat & O-Ring Material. In this example, the T represents TFE.
- C** - Types of Balls used in the valves. In this example, the C represents Ceramic.
- 1** - Connection type. In this example, the 1 represents tubing connections for 3/8" OD tubing.

In the configuration Guide, we have listed the most popular Wet-End codes. If you don't find the materials or connection selection to meet your needs, refer to the following selection guides to configure the proper Wet-End Code.

Selecting the Wet-End Code:

The wet-end code represents the materials of construction that will be in contact with the chemical you are pumping. It is critical that the materials selected are compatible. If you do not find the wet-end code to meet your application in the configuration guides, you can use the Wet-End Code Selection Guide to determine the correct Head Material, Seats & O-Rings and Balls. If you do not know what materials are compatible with the chemicals you are pumping, refer to the chemical compatibility chart below. We have identified the proper wet-end code for the chemicals in the list. If your chemical is not found in the list, please contact your chemical supplier or visit www.pulsatron.com for a complete listing.

PULSAtron Wet-End Code Selection Guide	
Head & Fittings	
A	= 316 Stainless Steel (All models except H8)
K	= PVDF (Kynar) (not available for H8 models)
P	= GFPPPL (Polypropylene)
V	= PVC (Poly Vinyl Chloride) (for models rated < 150 psi excluding K7, H7, H8)
W	= PVC (for models > 150 psi and K7, H7, H8)
Seats	
H	= Hypalon (150 psi max.)
T	= TFE (not available with TFE ball over 150 psi)
V	= Viton (150 psi max.)
Balls	
C	= Ceramic
H	= Alloy C (Hastelloy)
S	= 316 Stainless Steel
T	= TFE (not available with TFE seat over 150 psi)

Chemical Compatibility Chart	
Chemical	Liquid End Code
ACETIC ACID, 5 - 10%	PHC
ALUMINUM SULFATE	VHC
AMMONIA, 10%	PHC
BROMINE	KTC
CALCIUM HYPOCHLORITE	VVC
CITRIC ACID, 10 - 20%	PHC
DEAE - Steamline Treatment	ATS
ETHYLENE GLYCOL	PTC
FERRIC CHLORIDE	VTC
FERRIC SULFATE	PTC
FLUOSILICIC ACID	PTT
HYDROCHLORIC ACID, 0 - 37%	PTC
HYDROCHLORIC ACID, 37 - 100%	KTT
HYDROFLUOSILICIC ACID, 20%	PTT
HYDROGEN PEROXIDE, 0 - 30%	VVC
LACTIC ACID	PTC
NITRIC ACID, 0 - 20%	PVC
PHOSPHORIC ACID, 0 - 100%	KTC
POTASSIUM CHLORIDE	PTC
POTASSIUM PERMANGANATE	PTC
SODIUM BI-CARBONATE	PTC
SODIUM BI-SULFATE	PTC
SODIUM BI-SULFITE	PTC
SODIUM CARBONATE	PTC
SODIUM HYDROXIDE, 0 - 50%	PHC
SODIUM HYPOCHLORITE	VVC
SODIUM NITRATE	PTC
SODIUM SILICATE	PHC
SODIUM SULFATE	PHC
SODIUM SULFIDE	PHC
SULFURIC ACID, 0 - 10%	PTC
SULFURIC ACID, 10 - 75%	PTC
SULFURIC ACID, 95 - 100%	KTC

This is an abbreviated version using most common chemicals. Refer to the Chemical Resistance Guide (EMP-030) for a more detailed listing.

Selecting the Connection Code:

Selecting the proper connection code is probably the most difficult part of choosing a PULSAtron pump. Because of the flexibility built into this product line to meet a large variety of applications, the connection codes are determined by a lot more factors than just the size of the tubing. Connection code is probably the wrong name for this selection because you are selecting more than just the tubing size. This code also determines the type of valves used in the pump. The valve type is determined by factors such as flow rate of the pump, ball type selected and viscosity of the fluid you will be pumping.

Flow Rate:

The pump you select is rated to pump a certain number of gallons per hour (GPH). When selecting the connection code, please note the GPH limitations and select a connection that fits within the parameters of the pump model that you selected.

Ball Type:

If the material selected for the balls used in the check valves is TFE, you will probably need to use a spring-loaded connection. This is due to the fact that the weight of the balls will not allow them to seat properly without the spring. See the connection chart for a list of spring loaded connection types.

Viscosity:

Viscosity of the fluid you are pumping impacts the connection. The higher viscosity fluids (>3000 cps) require larger connection types and spring-loaded valves. Medium viscosity fluids (1000 to 3000 cps) can be pumped without the spring-loaded valves but you must use SS balls with these connections in order for the balls to seat properly in the valve.

Connection Codes							
Code	Connect Type	Suction	Discharge	Spring	GPH Flow Limitations	Viscosity	Other Factors
2	Piping	.25" FNPT	.25" FNPT		0 - 1.88	< 3000 cps	No Bleed Valve
4	Piping	.25" FNPT	.25" FNPT		1.63 - 10	< 3000 cps	No Bleed Valve
6	Piping	.25" FNPT	.25" FNPT	Yes	Up to 10	> 3000 cps	No Bleed Valve
8	Piping	.50" FNPT	.50" FNPT	Yes	Up to 25	> 3000 cps	No Bleed Valve
C	Piping	.50" FNPT	.50" FNPT		25	< 3000 cps	No Bleed Valve
G	Piping	.25" FNPT	.25" FNPT	Yes	0 - 1.88	< 3000 cps	No Bleed Valve
1	Tubing	.25" x .38"	.25" x .38"		0 - 1.88	< 3000 cps	
3	Tubing	.38" x .50"	.38" x .50"		1.63 - 10	< 3000 cps	
5	Tubing	.50" x .75"	.38" x .50"	Yes	Up to 10	> 3000 cps	
7	Tubing	.50" x .75"	.50" FNPT	Yes	Up to 25	> 3000 cps	No Bleed Valve
9	Tubing	.19" x .31"	.25" x .38"	Yes	0 - 1.88	< 3000 cps	Degas Head/No Bleed Valve
A	Tubing	.38" x .50"	.38" x .50"		0 - 1.88	< 3000 cps	
B	Tubing	.50" x .75"	.50" x .75"		25	< 3000 cps	No Bleed Valve
D	Tubing	.25" x .38"	.25" x .38"	Yes	0 - 1.88	< 3000 cps	
E	Tubing	.38" x .50"	.38" x .50"	Yes	0 - 1.88	< 3000 cps	
F	Tubing	.38" x .50"	.38" x .50"	Yes	1.63 - 10	< 3000 cps	
H	Tubing	.25" x .38"	.25" x .38"		1.63 - 10	< 3000 cps	
J	Tubing	.19" x .31"	.25" x .38"		0 - 1.04	< 3000 cps	
K	Tubing	.50" x .75"	.50" x .75"	Yes	1.88 - 25 (<50 psi)	> 3000 cps	No Bleed Valve
Metric Connections					LPH Flow Limitations		
M	Piping	G 1/2 A	G 1/2 A		6.15 - 37.85	< 3000 cps	No Bleed Valve
R	Piping	G 1/2 A	G 1/2 A		0 - 7.10	< 3000 cps	No Bleed Valve
N	Tubing	4 x 10 mm	4 x 10 mm		0 - 7.10	< 3000 cps	
P	Tubing	4 x 6 mm	4 x 6 mm		0 - 3.94	< 3000 cps	
Q	Tubing	10 x 14 mm	10 x 14 mm		6.15 - 37.85	< 3000 cps	
S	Tubing	6 x 10 mm	6 x 10 mm		> 18.93	< 3000 cps	
T	Tubing	6 x 10 mm	6 x 10 mm		0 - 7.10	< 3000 cps	Degas Head/No Bleed Valve
U	Tubing	6 x 10 mm	6 x 10 mm		0 - 7.10	< 3000 cps	
V	Tubing	12 x 19 mm	12 x 19 mm		> 29.96	< 3000 cps	No Bleed Valve
W	Tubing	10 x 16 mm	10 x 16 mm		6.15 - 37.85	< 3000 cps	
Y	Tubing	6 x 12 mm	6 x 12 mm		0 - 7.10	< 3000 cps	

Pumps ranging from 0.25 gph (0.9 lph) to 0.90 gph (3.4 lph) with the stainless steel ball option ("S" in the 9th digit of the model number) must select a connection code with a spring.


- Pumps less than or equal to .25 gph (0.9 lph) require a connection code with a spring and must use a ceramic ball in place of stainless steel.
- Stainless steel head assemblies are only available in piping connections.

Sensor/Flow Options (Models D, CL, CW & WT Only):

The Series D, CL, CW and WT have optional features that are covered by two additional digits in the Model Selection.

Series D:

LF02SA-PTC1-1A




Flow Switch Option
Electronic Connection Option

These selections are explained for each model in the Configuration Guide.

Series CL, CW & WT:

LW02SA-PTC1-2A



Flow Switch/Assembly Option
Sensor Option

These selections are explained for each model in the Configuration Guide.

Suffix Code:

LW02SA-PTC1-XXX

 ← Suffix Code

The last three digits of the model string are referred to as the Suffix Code. It is through the suffix code that the pump can be customized with optional features or customer specific features, e.g. private labeling. If your company has specific features that will be ordered on every pump, contact customer service with a description of what you want customized. We will then assign a unique suffix code that can be used as the last three digits in the model string when you place an order.

CZXXX = CE Approval

This suffix code tells us that you require CE Approval on the pump you are ordering. This suffix code is five digits and can be used in conjunction with other suffix codes by replacing the XXX after the CZ with another suffix code. For instance, if you require CE Approval and a Five Function Valve (shown below), the suffix code would be CZ500.

Standard Suffix Code Descriptions:

On the following pages are additional features that can be added to your PULSAtron pump through the use of the Suffix Code. Anytime you order a pump with one of these codes, it will be configured with that option.

130 = PVDF Tubing


This suffix code will replace the standard pump tubing with PVDF Tubing.

500 = Five Function Valve

The five function valve is easily installed, no tools required. The valve operates with all PULSAtron models up to 240 GPD. The five function valve is packed with features that increase safety, enhance performance and generally improves the convenience of operation.

FEATURES

- Pressure Relief – Allows for relief of excessive pressure in discharge line to protect connections and tubing.
- Back Pressure – Maintains output reproducibility and allows metering into atmospheric discharge.
- Anti-Siphon – Prevents siphoning through the pump when point of injection is lower than the pump or into the suction line of another pump. Rated at total vacuum.
- Air Bleed – Used during priming to manually remove air from the pump head.
- Discharge Drain – Depressurize pump discharge line without loosening tubing or fittings. Protects the operator from chemical exposure.



SPECIFICATIONS

Material Of Construction:

Valve Body	Glass-filled Polypropylene (GFPPPL) Polyvinylidene Flouride (PVDF)
Diaphragm	TFE faced Hypalon
O-Rings	TFE
Hardware	18-8 Stainless Steel (Recessed)

Maximum Operating Pressure:

300 PSI/21 BAR (except PVC)

Maximum Flow:

10 GPH (37.85 LPH)

Maximum Viscosity:

1000 CPS

Pressure Relief

Settings:	275 PSI (17 BAR) - red
(nominal cracking pressure)	175 PSI (12 BAR) - green
	125 PSI (8.6 BAR) - blue
	50 PSI (2.8 BAR) - black (PVC only)

Note: Pressure relief will occur at no more than 50% above maximum rating of pump.

OPERATION

The functions are selected by setting two dual position selector knobs. The label on the back panel of the valve identifies each function with selector knob positions.


The five function valve is compatible with most PULSAtron pumps. Connected to the existing discharge valve the five function valve is capable of handling a large output flow as well as viscous liquids. A return port located on the side body provides flow of chemical back to the solution tank when in the air bleed or drain discharge mode.

520 = DG/5FV Five Function Valve with De-Gas

With the DG/5FV you don't have to give up the accuracy and control of a solenoid metering pump in order to pump gaseous solutions. Available in a variety of materials and popular sizes, the DG/5FV is ready to tackle most applications. Not only does the DG/5FV provide degassing, it is packed with features that increase safety, enhance performance and generally improves the convenience of operation.

FEATURES

- De-Gas – Bypass gasses and fluid during normal pump operation. Allows for the constant removal of gases that would otherwise “air bind” the pump.
- Back Pressure – Maintains output reproducibility and allows metering into atmospheric discharge.
- Anti-Siphon – Prevents siphoning through the pump when point of injection is lower than the pump or into the suction line of another pump. Rated at total vacuum.
- Air Bleed – Used during priming to manually remove air from the pump head.
- Discharge Drain – Depressurize pump discharge line without loosening tubing or fittings. Protects the operator from chemical exposure.



SPECIFICATIONS

Material Of Construction:

Valve Body	Polyvinylidene Flouride (PVDF)
Diaphragm	TFE faced Hypalon
O-Rings	Viton or Hypalon
Hardware	18-8 Stainless Steel (Recessed)

Maximum Flow: 10 GPH (37.85 LPH)

Minimum Flow: 3 GPD (.47LPH)

Maximum Viscosity: 1000 CPS

MAX Pressure Ratings: Up to 250 psi (17 BAR)

Note: Degas/bypass volume is adjustable, typically 1-10% of pump output.

Connections: 1/4" (0.635 cm) Male NPT
 1/2" (1.27 cm) OD tubing
 3/8" (0.95 cm) OD tubing

All ports (input, output & bypass) on the selected valve will be the same.

OPERATION

The functions are selected by setting two dual position selector knobs. The label on the back panel of the DG/5FV identifies each function with selector knob positions.


The DG/5FV is compatible with most PULSAtron pumps. Connected to the existing discharge valve the GG/5FV is capable of handling a large output flow as well as viscous liquids. A return port located on the side body provides flow of chemical back to the solution tank when in the degas, air bleed or drain discharge mode.

ITS = Integrated Tank System

The ITS System is a completely integrated tank system constructed of high density UV resistant polyethylene (PE) with a 15 gallon capacity. This tank system is translucent with 5 gallon increments and the tank's low level indicator allows visual monitoring of chemicals without opening the tank. The tight fitting child-proof lid keeps the chemical free of contaminants and protects the surrounding area from chemical fumes.

The ITS System also allows for easy access to the liquid end and control panel of the mounted pump.

A system consists of a chemical tank with lid and bulkhead fittings; a liquid level indicator float assembly; and feeder mounting hardware.



ITS Tank not available on LM, LP, LT, and LE: H4, H5, H6, H7, J7, H8, K7 models) If you require a different type or size tank, please refer to our accessory price book.

PULSAtron® Series MP

Key Features

- **Automatic Control**, 4-20mA and 20-4mA current signals can be ratioed from 100% to 2% of incoming signal.
- **Manual Control** allows for a combined 1000:1 turndown resulting in accurate metering for critical applications.
- **Relay Output** for computer interface or AC power allows for external control.
- **Six-button Touch Pad Control** with internationally recognized symbols for simplified programming.
- **Simple Prompts** in plain language allow for easy-to-understand instructions for programming. **Available in three languages.**
- **Alarm Signals** for signal loss, full count, circuit failure, pulse overflow and pulse rate high. Liquid low level indicator capability is standard.
- **Timed Sequences** can be set for selected intervals and rate for repetitive metering.
- **Pulse Signals** can be multiplied or divided by 1 to 999 allowing for pumps to handle peak requirements.
- **LCD**, 16 character dot matrix backlit multi-lingual display allows for easy reading and user-friendly programming.
- **Extended Two Year Warranty** on electronic circuit board for trouble free service.



Pressure and Flow Rate Capacity

MODEL	LМК2	LMB2	LMA2	LMD3	LMB3	LMA3	LМК3	LMF4	LMD4	LMB4	LMH4	LMG4	LMF4	LMK5	LMH5	LMH6	LMK7	LMH7	LMH8	
Capacity nominal	GPH	0.13	0.21	0.25	0.50	0.50	0.60	0.85	0.90	1.00	1.70	1.75	1.85	2.50	3.15	5.00	8.00	10.00	21.00	
(max.)	GPD	3	5	6	12	12	14	20	22	24	41	42	44	60	76	120	192	240	504	
Pressure (max.)	LPH	0.5	0.8	0.9	1.9	1.9	1.9	2.3	3.2	3.4	3.8	6.4	6.6	7.0	9.5	11.9	18.9	30.3	37.9	
	PSIG	300	250	150	250	150	100	100	250	150	100	250	150	100	150	150	100	50	35	
	BAR	21	17	10	17	10	7	7	17	10	7	17	10	7	10	10	7	3.3	2.4	
Connections:	Tubing	1/4" ID X 3/8" OD 3/8" ID X 1/2" OD 3/16" ID X 5/16" OD											3/8" ID X 1/2" OD 1/2" ID X 3/4" OD (LPH8 ONLY)							
	Piping	1/4" FNPT											1/4" FNPT 1/2" FNPT							
Reproducibility	+/- 2% at maximum capacity																			
Viscosity Max CPS	For viscosity up to 3000 CPS, select connection size 3, 4, B or C with 316SS ball material. Flow rate will determine connection/ball size. Greater than 3000 CPS require spring loaded ball checks. See Selection Guide for proper connection.																			
Controls	6-Station Membrane Switch																			
Status Display	16-Position LCD Dot Matrix Backlight																			
LED Indicator Lights, Panel Mount	Power On - Green, Pulsing - Green Flashing, Stop - Red																			
Stroke Frequency	125 Strokes Per Minute (SPM) maximum																			
External Stroke Frequency Control (Automatic)	4-20 mADC, 20-4 mADC External Pacing																			
Output Relay (Signal Level Option)	24 VDC, 10 mA																			
Output Relay (Power Option)	250 VAC, 50/60 HZ, 0.5A																			
Stroke Frequency Turn-Down Ratio	100:1																			
Stroke Length Turn-Down Ratio	10:1																			
Power Input	115 VAC/50-60 HZ/1 ph 230 VAC/50-60 HZ/1 ph																			
Average Current	1.0 Amps @ 115 VAC, 0.5 Amps @ 230 VAC																			
Peak Input Power	300 Watts																			
Average Input Power	130 Watts																			

PULSAtron Series MP Selection Guide

LM _ _

MODELS:	K2	= 0.13 gph / 3 gpd (0.5 lph) max pres.: 300 PSI (21 BAR)
	B2	= 0.21 gph / 5 gpd (0.8 lph) max pres.: 250 PSI (17 BAR)
	D3	= 0.50 gph / 12 gpd (1.9 lph) max pres.: 250 PSI (17 BAR)
	F4	= 0.85 gph / 20 gpd (3.2 lph) max pres.: 250 PSI (17 BAR)
	H4	= 1.70 gph / 41 gpd (6.4 lph) max pres.: 250 PSI (17 BAR)
	A2	= 0.25 gph / 6 gpd (0.9 lph) max pres.: 150 PSI (10 BAR)
	B3	= 0.50 gph / 12 gpd (1.9 lph) max pres.: 150 PSI (10 BAR)
	D4	= 0.90 gph / 22 gpd (3.4 lph) max pres.: 150 PSI (10 BAR)
	G4	= 1.75 gph / 42 gpd (6.6 lph) max pres.: 150 PSI (10 BAR)
	K5	= 2.50 gph / 60 gpd (9.5 lph) max pres.: 150 PSI (10 BAR)
	H5	= 3.15 gph / 76 gpd (11.9 lph) max pres.: 150 PSI (10 BAR)
	A3	= 0.50 gph / 12 gpd (1.9 lph) max pres.: 100 PSI (7 BAR)
	K3	= 0.60 gph / 14 gpd (2.3 lph) max pres.: 100 PSI (7 BAR)
	B4	= 1.00 gph / 24 gpd (3.8 lph) max pres.: 100 PSI (7 BAR)
	E4	= 1.85 gph / 44 gpd (7.0 lph) max pres.: 100 PSI (7 BAR)
	H6	= 5.00 gph / 120 gpd (18.9 lph) max pres.: 100 PSI (7 BAR)
	K7	= 8.00 gph / 192 gpd (30.3 lph) max pres.: 50 PSI (3.3 BAR)
	H7	= 10.0 gph / 240 gpd (37.9 lph) max pres.: 35 PSI (2.4 BAR)
	H8	= 21.0 gph / 504 gpd (79.5 lph) max pres.: 20 PSI (1.3 BAR)

CONTROLS:	T	= Signal Level Output Relay
	K	= Power Level Output Relay

ELECTRICAL:	A	= 115 Volt / 50-60Hz
	1	= 115 Volt / 50-60Hz (without agency approvals)
	B	= 230 Volt / 50-60Hz / 1ph with 6' (1.8m) 3-wire US Plug
	2	= 230 Volt / 50-60Hz (without agency approvals)

LIQUID END MATERIALS:	PTC	= GFFPL / TFE / Ceramic
	KTC	= PVDF / TFE / Ceramic (not available on H8)
Pump Head & Fittings/Seats & O-rings/Balls	VHC	= PVC / Hypalon / Ceramic (not available on H7, H8, K7)
	VTC	= PVC / TFE / Ceramic (models <= 150 psi excluding H7, H8, K7)
	WTC	= PVC / TFE / Ceramic (models > 150 psi and H7, H8, K7)
	VVC	= PVC / PVC / Ceramic (not available on H8)
	ATS	= 316 S.S. / TFE / 316 S.S. (must use FNPT piping connection) (not available on H8)

See page 6 for additional liquid end materials.

CONNECTION SIZES:	1	= Tubing .25" I.D. x .38" O.D. / .25" Ball, 0 - 1.88 GPH
	3	= Tubing .38" I.D. x .50" O.D. / .38" Ball, 1.63 - 10 GPH
	9	= Degas Head: (S) 5/16", (D) 3/8", 0-1.83 GPH
	J	= Tubing, Suc: .19" I.D. x .31" O.D.; Dis: .25" I.D. x .38" O.D.; .19 Ball; 0 - 1.04 GPH
	METRIC:	
	M	= G 1/2 A Threads, .38" Ball, 6.15 - 37.85 LPH
	R	= G 1/2 A Threads, .25" Ball, 0 - 7.10 LPH
	Y	= 6 x 12mm, .25" Ball, 0 - 7.10 LPH


Please Refer to page 7 for additional connection sizes. All pumps with tubing connections come with the following items (except for LMH8, LPH8, LEH8, HV series pumps and pumps >150PSI in PVC): 4' Suction, 4' Return, 8' discharge tubing, footvalve/strainer

SUFFIX CODES:	XXX	= No Additional Options
	130	= PVDF Tubing
	500	= Five Function Valve
	520	= Five Function Degas Valve
	ITS	= 15 gal. ITS Tank System (ITS Tank not available on LM, LP, LT, and LE: H4, H5, H6, H7, H8, K7 models)
	CZXXX	= CE Approval (5 digits used for this suffix code)

See pages 9, 10 & 11 for additional information and specs.

A completed model number should look like 'LMB3TA-PTC1-XXX'

Dimensions



Series MP Dimensions (inches)

Model No.	A	B	B1	C	C1	D	E	Shpg Wt	Model No.	A	B	B1	C	C1	D	E	Shpg Wt
LMA2	5.4	10.3	-	10.8	-	7.5	8.9	13	LMH4	6.2	10.9	-	11.2	-	8.2	9.5	21
LMA3	5.4	10.6	-	10.7	-	7.5	9.2	13	LMH5	6.2	11.3	-	11.2	-	8.2	9.9	21
LMB2	5.4	10.3	-	10.8	-	7.5	8.9	13	LMH6	6.2	11.3	-	11.2	-	8.2	9.9	21
LMB3	5.4	10.6	-	10.7	-	7.5	9.2	13	LMH7	6.1	11.7	-	11.2	-	8.2	10.3	21
LMB4	5.4	10.6	-	10.7	-	7.5	9.2	13	LMH8*	6.1	-	10.9	-	10.6	8.2	-	25
LMD3	5.4	10.6	-	11.2	-	7.5	9.2	15	LMK2	5.4	10.3	-	10.8	-	7.5	8.9	13
LMD4	5.4	10.6	-	11.2	-	7.5	9.2	15	LMK3	5.4	10.6	-	10.7	-	7.5	9.2	13
LME4	5.4	10.6	-	11.2	-	7.5	9.2	15	LMK5	5.4	10.9	-	11.7	-	7.5	9.5	18
LMF4	5.4	10.6	-	11.7	-	7.5	9.2	18	LMK7	6.1	11.7	-	11.2	-	8.2	10.3	21
LMG4	5.4	10.6	-	11.7	-	7.5	9.2	18									

NOTE: Inches X 2.54 = cm / * the LMH8 is designed without a bleed valve available

PULSAtron® Series E PLUS

Key Features

- **Automatic Control**, available with 4-20 mA DC direct or external pacing, with stop function.
- **Manual Control** by on-line adjustable stroke rate and stroke length.
- **Agency approved** for demanding **OUTDOOR** and indoor applications.
- **Auto-Off-Manual** switch.
- **Highly Reliable** timing circuit.
- **Circuit Protection** against voltage and current upsets.
- **Panel Mounted Fuse.**
- **Solenoid Protection** by thermal overload with auto re-set.
- **Water Resistant**, for outdoor and indoor applications.
- **Indicator Lights**, panel mounted.
- **Guided Ball Check Valve Systems**, to reduce back flow and enhance outstanding priming characteristics.
- **Safe & Easy Priming** with durable leak-free **bleed valve assembly** (standard).



Pressure and Flow Rate Capacity

MODEL	LPK2	LPB2	LPA2	LPD3	LPB3	LPA3	LPK3	LPF4	LPD4	LPB4	LPH4	LPG4	LPE4	LPK5	LPH5	LPH6	LPK7	LPH7	LPH8	
Capacity nominal	0.13	0.21	0.25	0.5	0.50	0.50	0.60	0.85	0.90	1.00	1.70	1.75	1.85	2.50	3.15	5.00	8.00	10.00	25.00	
GPD	3	5	6	12	12	12	14	20	22	24	41	42	44	60	76	120	192	240	600	
(max.)	LPH	0.5	0.8	0.9	1.9	1.9	1.9	2.3	3.2	3.4	3.8	6.4	6.6	7	9.5	11.9	18.9	30.3	37.9	94.6
Pressure (max.)	PSIG	300	250	150	250	150	100	100	250	150	100	250	150	100	150	150	100	50	35	30
	BAR	21	17	10	17	10	7	7	17	10	7	17	10	7	10	10	7	3.3	2.4	2
Connections:	Tubing	1/4" ID X 3/8" OD 3/8" ID X 1/2" OD 3/16" ID X 5/16" OD											3/8" ID X 1/2" OD 1/2" ID X 3/4" OD (LPH8 ONLY)							
	Piping	1/4" FNPT											1/4" FNPT 1/2" FNPT							
Reproducibility	+/- 2% at maximum capacity																			
Viscosity Max CPS	For viscosity up to 3000 CPS, select connection size 3, 4, B or C with 316SS ball material. Flow rate will determine connection/ball size. Greater than 3000 CPS require spring loaded ball checks. See Selection Guide for proper connection.																			
Stroke Frequency	125 Strokes Per Minute (SPM) maximum																			
Stroke Frequency	10:1																			
Stroke Length Turn-	10:1																			
Power Input	115 VAC/50-60 HZ/1 ph 230 VAC/50-60 HZ/1 ph																			
Average Current	1.0 Amps @ 115 VAC, 0.5 Amps @ 230 VAC																			
Peak Input Power	300 Watts																			
Average Input Power	130 Watts																			

PULSAtron Series E Plus Selection Guide

LP _ _ - - - - -

MODELS:	K2	= 0.13 gph / 3 gpd (0.5 lph) max pres.: 300 PSI (21 BAR)
	B2	= 0.21 gph / 5 gpd (0.8 lph) max pres.: 250 PSI (17 BAR)
	D3	= 0.50 gph / 12 gpd (1.9 lph) max pres.: 250 PSI (17 BAR)
	F4	= 0.85 gph / 20 gpd (3.2 lph) max pres.: 250 PSI (17 BAR)
	H4	= 1.70 gph / 41 gpd (6.4 lph) max pres.: 250 PSI (17 BAR)
	A2	= 0.25 gph / 6 gpd (0.9 lph) max pres.: 150 PSI (10 BAR)
	B3	= 0.50 gph / 12 gpd (1.9 lph) max pres.: 150 PSI (10 BAR)
	D4	= 0.90 gph / 22 gpd (3.4 lph) max pres.: 150 PSI (10 BAR)
	G4	= 1.75 gph / 42 gpd (6.6 lph) max pres.: 150 PSI (10 BAR)
	K5	= 2.50 gph / 60 gpd (9.5 lph) max pres.: 150 PSI (10 BAR)
	H5	= 3.15 gph / 76 gpd (11.9 lph) max pres.: 150 PSI (10 BAR)
	A3	= 0.50 gph / 12 gpd (1.9 lph) max pres.: 100 PSI (7 BAR)
	K3	= 0.60 gph / 14 gpd (2.3 lph) max pres.: 100 PSI (7 BAR)
	B4	= 1.00 gph / 24 gpd (3.8 lph) max pres.: 100 PSI (7 BAR)
	E4	= 1.85 gph / 44 gpd (7.0 lph) max pres.: 100 PSI (7 BAR)
	H6	= 5.00 gph / 120 gpd (18.9 lph) max pres.: 100 PSI (7 BAR)
	K7	= 8.00 gph / 192 gpd (30.3 lph) max pres.: 50 PSI (3.3 BAR)
	H7	= 10.0 gph / 240 gpd (37.9 lph) max pres.: 35 PSI (5.6 BAR)
	H8	= 25.0 gph / 600 gpd (94.6 lph) max pres.: 30 PSI (2 BAR)

CONTROLS:	S	= Manual On/Off
	M	= 4-20mADC Direct, w/ Stop
	E	= External/Remote Pacing, w/ Stop

ELECTRICAL:	A	= 115 Volt / 50-60Hz
	1	= 115 Volt / 50-60Hz (without agency approvals)
	B	= 230 Volt / 50-60Hz / 1ph with 6' (1.8m) 3-wire US Plug
	2	= 230 Volt / 50-60Hz (without agency approvals)

LIQUID END MATERIALS:	PTC	= GFPP / TFE / Ceramic
	PTT	= GFPP / TFE / TFE
Pump Head & Fittings/Seats & O-rings/Balls	KTC	= PVDF / TFE / Ceramic (not available on H8)
	VHC	= PVC / Hypalon / Ceramic (not available on H7, H8, K7)
	VTC	= PVC / TFE / Ceramic (models <= 150 psi excluding H7, H8, K7)
	WTC	= PVC / TFE / Ceramic (models > 150 psi and H7, H8, K7)
	ATS	= 316 S.S. / TFE / 316 S.S. (must use FNPT piping connection) (not available on H8)

See page 6 for additional liquid end materials.

CONNECTION SIZES:	1	= Tubing .25" I.D. x .38" O.D. / .25" Ball, 0 - 1.88 GPH
	3	= Tubing .38" I.D. x .50" O.D. / .38" Ball, 1.63 - 10 GPH
	4	= Piping .25" FNPT / .38" Ball, 1.63 - 10 GPH
	B	= Tubing .50" I.D. x .75" O.D. / .50" Ball, 20.83 GPH only
	METRIC:	
	M	= G 1/2 A Threads, .38" Ball, 6.15 - 37.85 LPH
	R	= G 1/2 A Threads, .25" Ball, 0 - 7.10 LPH
	Y	= 6 x 12mm, .25" Ball, 0 - 7.10 LPH


Please Refer to page 7 for additional connection sizes. All pumps with tubing connections come with the following items (except for LMH8, LPH8, LEH8, HV series pumps and pumps >150PSI in PVC): 4' Suction, 4' Return, 8' discharge tubing, footvalve/strainer

SUFFIX CODES:	XXX	= No Additional Options
	130	= PVDF Tubing
	500	= Five Function Valve
	520	= Five Function Degas Valve
	ITS	= 15 gal. ITS Tank System (ITS Tank not available on LM, LP, LT, and LE: H4, H5, H6, H7, H8, K7 models)
	CZXXX	= CE Approval (5 digits used for this suffix code)

See pages 9, 10 & 11 for additional information and specs.

A completed model number should look like 'LPB3SA-PTC1-XXX'

Dimensions



Series E Plus Dimensions (inches)

Model No	A	B	B1	C	C1	D	E	Shpg Wt	Model No	A	B	B1	C	C1	D	E	Shpg Wt
LPA2	5.4	10.3	-	10.8	-	7.5	8.9	13	LPH4	6.2	10.9	-	11.2	-	8.2	9.5	21
LPA3	5.4	10.6	-	10.7	-	7.5	9.2	13	LPH5	6.2	11.3	-	11.2	-	8.2	9.9	21
LPB2	5.4	10.3	-	10.8	-	7.5	8.9	13	LPH6	6.2	11.3	-	11.9	-	8.2	9.9	21
LPB3	5.4	10.6	-	10.7	-	7.5	9.2	13	LPH7	6.1	11.7	-	11.9	-	8.2	10.3	21
LPB4	5.4	10.6	-	10.7	-	7.5	9.2	13	LPH8*	6.1	-	10.9	-	11.3	8.2	-	26
LPD3	5.4	10.6	-	11.2	-	7.5	9.2	15	LPK2	5.4	10.3	-	10.8	-	7.5	8.9	13
LPD4	5.4	10.6	-	11.2	-	7.5	9.2	15	LPK3	5.4	10.6	-	10.7	-	7.5	9.2	13
LPE4	5.4	10.6	-	11.2	-	7.5	9.2	15	LPK5	5.4	10.9	-	11.7	-	7.5	9.5	18
LPF4	5.4	10.6	-	11.7	-	7.5	9.2	18	LPK7	6.1	11.7	-	11.2	-	8.2	10.3	21
LPG4	5.4	10.6	-	11.7	-	7.5	9.2	18									

NOTE: Inches X 2.54 = cm /* the LPH8 is designed without a bleed valve available

PULSAtron® Series HV

Key Features

- **Automatic Control**, available with 4-20 mA DC direct or external pacing, with stop function.
- **Manual Control** by on-line adjustable stroke rate and stroke length.
- **Agency approved** for demanding **OUTDOOR** and indoor applications.
- **Auto-Off-Manual** switch.
- **Highly Reliable** timing circuit.
- **Circuit Protection** against voltage and current upsets.
- **Panel Mounted Fuse.**
- **Solenoid Protection** by thermal overload with auto re-set.
- **Water Resistant**, for outdoor and indoor applications.
- **Indicator Lights**, panel mounted.
- **Guided Ball Check Valve Systems**, to reduce back flow and enhance outstanding priming characteristics.
- **Viscosities to 20,000 CPS.**



Pressure and Flow Rate Capacity

MODEL	LVB3	LVF4	LVG4	LVG5	LVH7
Capacity nominal	GPH 0.50	1.00	2.00	4.00	10.00
(max.)	GPD 12	24	48	96	240
	LPH 1.9	3.8	7.6	15.1	37.9
Pressure (max.)	PSIG 150	150	110	110	80
	BAR 10	10	7	7	5.6
Connections: Tubing	(S) .50" I.D. X .75" O.D. .38" I.D. X .50" OD (LVB3 & F4 only) (S & D) .50" I.D. X .75" O.D. (LVG4, G5 & H7 only)				
Reproducibility	+/- 2% at maximum capacity				
Viscosity Max CPS	20,000 CPS				
Stroke Frequency	125 Strokes Per Minute (SPM) maximum				
Stroke Frequency	10:1				
Stroke Length Turn-	10:1				
Power Input	115 VAC/50-60 HZ/1 ph 230 VAC/50-60 HZ/1 ph				
Average Current	1.0 Amps @ 115 VAC, 0.5 Amps @ 230 VAC				
Peak Input Power	300 Watts				
Average Input Power	130 Watts				

PULSAtron Series HV Selection Guide

MODELS:	B3	= 0.50 gph / 12 gpd (1.9 lph) max pres.: 150 PSI (10 BAR)
	F4	= 1.00 gph / 24 gpd (3.8 lph) max pres.: 150 PSI (10 BAR)
	G4	= 2.00 gph / 48 gpd (7.6 lph) max pres.: 110 PSI (7 BAR)
	G5	= 4.00 gph / 96 gpd (15.1 lph) max pres.: 110 PSI (7 BAR)
	H7	= 10.0 gph / 240 gpd (37.9 lph) max pres.: 80 PSI (5.6 BAR)

CONTROLS:	S	= Manual On/Off
	M	= 4-20mADC Direct, w/ Stop
	E	= External/Remote Pacing, w/ Stop

ELECTRICAL:	A	= 115 Volt / 50-60Hz
	1	= 115 Volt / 50-60Hz (without agency approvals)
	B	= 230 Volt / 50-60Hz / 1ph with 6' (1.8m) 3-wire US Plug
	2	= 230 Volt / 50-60Hz (without agency approvals)

LIQUID END MATERIALS: Pump Head & Fittings/Seats & O-rings/Balls	WTS	= PVC / TFE / 316 Stainless Steel - LVH4 & H7 only
	VTT	= PVC / TFE / TFE - LVB3 & F4 only
	VTS	= PVC / TFE / 316 Stainless Steel - LVG5 & G4 No other liquid end materials available.

CONNECTION SIZES:	5	= Tubing (S) .50" I.D. x .75" O.D. / .38" I.D. x .50" O.D. - LVB3 & F4 only
	K	= Tubing .50" I.D. x .75" o.d. - LVH4, G4, G5 & H7 only


No other connection sizes available. Pumps come with 4' suction tubing and 8' discharge tubing. No bleed valve

SUFFIX	XXX	= No Additional Options
CODES	CZXXX	= CE Approval (5 digits used for this suffix code)

See pages 9, 10 & 11 for additional information and specs.

A completed model number should look like 'LVB3SA-VTT5-XXX'

Dimensions



Series HV Dimensions (inches)					
Model No.	A	B	C	D	Shipping Weight
LVB3	5.4	9.3	9.5	7.5	13
LVF4	5.4	10.8	10.8	7.5	18
LVG4	5.4	9.5	10.6	7.5	18
LVG5	5.4	10.8	10.8	7.5	18
LVH7	6.1	11.5	11	8.2	25

NOTE: Inches X 2.54 = cm

PULSAtron® Series E

Key Features

- **Manual Control** by on-line adjustable stroke rate and stroke length.
- **Agency approved** for demanding **OUTDOOR** and indoor applications.
- **Highly Reliable** timing circuit.
- **Water Resistant** excellent for **OUTDOOR** and indoor applications.
- **Internally Dampened To Reduce Noise**, very acceptable for household installations.
- **Guided Ball Check Valve Systems**, to reduce back flow and enhance outstanding priming characteristics.
- **Premium Standard Wetted Component Materials**.
- **Few Moving Parts** and **Wall Mountable**.
- **Safe & Easy Priming** with durable leak-free **bleed valve assembly** (standard).



Pressure and Flow Rate Capacity

MODEL	LEK2	LE12	LE02	LE33	LE13	LE03	LEK3	LEF4	LE34	LE14	LEH4	LEG4	LE44	LEK5	LEH5	LEH6	LEK7	LEH7	LEJ7	LEH8	
Capacity nominal (max.)	GPH	0.13	0.21	0.25	0.50	0.50	0.50	0.60	0.85	0.90	1.00	1.70	1.75	1.85	2.50	3.15	5.00	8.00	10.00	10.00	25.00
	GPD	3	5	6	12	12	12	14	20	22	24	41	42	44	60	76	120	192	240	240	600
	LPH	0.5	0.8	0.9	1.9	1.9	1.9	2.3	3.2	3.4	3.8	6.4	6.6	7	9.5	11.9	18.9	30.3	37.9	37.9	94.6
Pressure (max.)	PSIG	300	250	150	250	150	100	100	250	150	100	250	150	100	150	150	100	50	35	80	30
	BAR	21	17	10	17	10	7	7	17	10	7	17	10	7	10	10	7	3.3	2.4	5.5	2
Connections:	Tubing	1/4" ID X 3/8" OD 3/8" ID X 1/2" OD 3/16" ID X 5/16" OD											3/8" ID X 1/2" OD 1/2" ID X 3/4" OD (LPH8 ONLY)								
	Piping	1/4" FNPT											1/4" FNPT 1/2" FNPT								
Reproducibility	+/- 3% at maximum capacity																				
Viscosity Max CPS	For viscosity up to 3000 CPS, select connection size 3, 4, B or C with 316SS ball material. Flow rate will determine connection/ball size. Greater than 3000 CPS require spring loaded ball checks. See Selection Guide for proper connection.																				
Stroke Frequency	125 Strokes Per Minute (SPM) maximum																				
Stroke Frequency	10:1																				
Stroke Length Turn-	10:1																				
Power Input	115 VAC/50-60 HZ/1 ph																				
	230 VAC/50-60 HZ/1 ph																				
Average Current	1.0 Amps @ 115 VAC, 0.5 Amps @ 230 VAC																				
Peak Input Power	300 Watts																				
Average Input Power	130 Watts																				

PULSAtron Series E Selection Guide

MODELS:		
K2	= 0.13 gph / 3 gpd (0.5 lph)	max pres.: 300 PSI (21 BAR)
12	= 0.21 gph / 5 gpd (0.8 lph)	max pres.: 250 PSI (17 BAR)
33	= 0.50 gph / 12 gpd (1.9 lph)	max pres.: 250 PSI (17 BAR)
F4	= 0.85 gph / 20 gpd (3.2 lph)	max pres.: 250 PSI (17 BAR)
H4	= 1.70 gph / 41 gpd (6.4 lph)	max pres.: 250 PSI (17 BAR)
02	= 0.25 gph / 6 gpd (0.9 lph)	max pres.: 150 PSI (10 BAR)
13	= 0.50 gph / 12 gpd (1.9 lph)	max pres.: 150 PSI (10 BAR)
34	= 0.90 gph / 22 gpd (3.4 lph)	max pres.: 150 PSI (10 BAR)
G4	= 1.75 gph / 42 gpd (6.6 lph)	max pres.: 150 PSI (10 BAR)
K5	= 2.50 gph / 60 gpd (9.5 lph)	max pres.: 150 PSI (10 BAR)
H5	= 3.15 gph / 76 gpd (11.9 lph)	max pres.: 150 PSI (10 BAR)
03	= 0.50 gph / 12 gpd (1.9 lph)	max pres.: 100 PSI (7 BAR)
K3	= 0.60 gph / 14 gpd (2.3 lph)	max pres.: 100 PSI (7 BAR)
14	= 1.00 gph / 24 gpd (3.8 lph)	max pres.: 100 PSI (7 BAR)
44	= 1.85 gph / 44 gpd (7.0 lph)	max pres.: 100 PSI (7 BAR)
H6	= 5.00 gph / 120 gpd (18.9 lph)	max pres.: 100 PSI (7 BAR)
K7	= 8.00 gph / 192 gpd (30.3 lph)	max pres.: 50 PSI (3.3 BAR)
H7	= 10.0 gph / 240 gpd (37.9 lph)	max pres.: 35 PSI (2.4 BAR)
J7	= 10.0 gph / 240 gpd (37.9 lph)	max pres.: 80 PSI (5.5 BAR)
H8	= 25.0 gph / 600 gpd (94.6 lph)	max pres.: 30 PSI (2 BAR)

CONTROLS: S = No Options Available

ELECTRICAL:		
A	= 115 Volt / 50-60Hz	
1	= 115 Volt / 50-60Hz (without agency approvals)	
B	= 230 Volt / 50-60Hz / 1ph with 6' (1.8m) 3-wire US Plug	
2	= 230 Volt / 50-60Hz (without agency approvals)	

LIQUID END MATERIALS:		
PHC	= GFPP / Hypalon / Ceramic	
PTC	= GFPP / TFE / Ceramic	
KTC	= PVDF / TFE / Ceramic (not available on J7 or H8)	
VHC	= PVC / Hypalon / Ceramic (not available on H7, H8, K7)	
VTC	= PVC / TFE / Ceramic (models <= 150 psi excluding H7, H8, K7)	
WTC	= PVC / TFE / Ceramic (models > 150 psi and H7, H8, K7)	
ATS	= 316 S.S. / TFE / 316 S.S. (must use FNPT piping connection) (not available on J7 or H8)	

See page 6 for additional liquid end materials.

CONNECTION SIZES:		
1	= Tubing .25" I.D. x .38" O.D. / .25" Ball, 0 - 1.88 GPH	
3	= Tubing .38" I.D. x .50" O.D. / .38" Ball, 1.63 - 10 GPH	
METRIC:		
M	= G 1/2 A Threads, .38" Ball, 6.15 - 37.85 LPH	
P	= 4 x 6mm, .25" Ball, 0 - 3.94 LPH	


Please Refer to page 7 for additional connection sizes. All pumps with tubing connections come with the following items (except for LMH8, LPH8, LEH8, HV series pumps and pumps >150PSI in PVC): 4' Suction, 4' Return, 8' discharge tubing, footvalve/strainer

SUFFIX CODES:		
XXX	= No Additional Options	
130	= PVDF Tubing	
500	= Five Function Valve	
520	= Five Function Degas Valve	
ITS	= 15 gal. ITS Tank System (ITS Tank not available on LM, LP, LT, and LE: H4, H5, H6, H7, H8, K7 models)	
CZXXX	= CE Approval (5 digits used for this suffix code)	

See pages 9, 10 & 11 for additional information and specs.

A completed model number should look like 'LE33SA-PTC1-XXX'

Dimensions



Series E Dimensions (inches)

Model No.	A	B	B1	C	C1	D	E	Shpg Wt	Model No.	A	B	B1	C	C1	D	E	Shpg Wt
LE02	5	9.6	-	9.5	-	6.4	8.2	7	LEH4	6.2	10.9	-	11.2	-	8.2	9.5	18
LE03	5	9.8	-	9.5	-	6.4	8.4	7	LEH5	6.2	11.3	-	11.2	-	8.2	9.9	18
LE12	5	9.6	-	9.5	-	6.4	8.2	7	LEH6	6.2	11.3	-	11.2	-	8.2	9.9	18
LE13	5	9.8	-	9.5	-	6.4	8.4	7	LEH7	6.1	11.7	-	11.2	-	8.2	10.3	18
LE14	5	9.8	-	9.5	-	6.4	8.4	7	LEH8*	6.1	-	10.9	-	10.6	8.2	-	23
LE33	5.4	10.6	-	11.2	-	7.5	9.2	12	LEK2	5.4	10.3	-	10.8	-	7.5	8.9	10
LE34	5.4	10.6	-	11.2	-	7.5	9.2	12	LEK3	5.4	10.6	-	10.7	-	7.5	9.2	10
LE44	5.4	10.6	-	11.2	-	7.5	9.2	12	LEK5	5.4	10.9	-	11.7	-	7.5	9.5	15
LEF4	5.4	10.6	-	11.7	-	7.5	9.2	15	LEK7	6.1	11.7	-	11.2	-	8.2	10.3	18
LEG4	5.4	10.6	-	11.7	-	7.5	9.2	15	LEJ7	6.1	10.0	-	10.7	-	-	-	18

NOTE: Inches X 2.54 = cm

* the LEH8 is designed without a bleed valve available

PULSAtron® Series E-DC

Key Features

- **Powered by 12 Volt DC..**
- **Manual Control** by on-line adjustable stroke rate and stroke length.
- **Agency approved** for demanding **OUTDOOR** and indoor applications.
- **Highly Reliable** timing circuit.
- **Water Resistant** excellent for **OUTDOOR** and indoor applications.
- **Internally Dampened To Reduce Noise**, very acceptable for household installations.
- **Guided Ball Check Valve Systems**, to reduce back flow and enhance outstanding priming characteristics.
- **Premium Standard Wetted Component Materials.**
- **Few Moving Parts** and **Wall Mountable.**
- **Safe & Easy Priming** with durable leak-free **bleed valve assembly** (standard).



Pressure and Flow Rate Capacity

MODEL		LS02	LS13	LS14	LS44
Capacity nominal (max.)	GPH	0.25	0.50	1.00	1.85
	GPD	6	12	24	44
	LPH	0.9	1.9	3.8	7.0
Pressure (max.)	PSIG	150	150	100	100
	BAR	10	10	7	7
Connections:	Tubing	1/4" ID X 3/8" OD 3/8" ID X 1/2" OD			
	Piping	1/4" FNPT			
Reproducibility		+/- 3% at maximum capacity			
Viscosity Max CPS	LS02, 13	300 CPS			
	LS14, 44	1000 CPS			
Stroke Frequency		125 Strokes Per Minute (SPM) maximum			
Stroke Frequency Turn-Down Ratio		10:1			
Stroke Length Turn-Down Ratio		10:1			
Power Input		12.6 VDC Nominal Range 11.8 - 14.0 VDC			
Average Current Draw	LS02, 13, 14	4.0 Amps			
	LS44	8.0 Amps			
Peak Input Power	LS02, 13, 14	138.6 Watts			
	LS44	189 Watts			
Average Input Power @ max SPM	LS02, 13, 14	50.4 Watts			
	LS44	100.8 Watts			

PULSAtron Series E-DC Selection Guide

MODELS:	02	= 0.25 gph / 6 gpd (0.9 lph) max pres.: 150 PSI (10 BAR)
	13	= 0.50 gph / 12 gpd (1.9 lph) max pres.: 150 PSI (10 BAR)
	14	= 1.00 gph / 24 gpd (3.8 lph) max pres.: 100 PSI (7 BAR)
	44	= 1.85 gph / 44 gpd (7.0 lph) max pres.: 100 PSI (7 BAR)

CONTROLS: S = No Options Available

ELECTRICAL: 4 = 12V DC

LIQUID END MATERIALS:	PHC	= GFPP / Hypalon / Ceramic
	PTC	= GFPP / TFE / Ceramic
Pump Head & Fittings/Seats & O-rings/Balls	PVC	= GFPP / Viton / Ceramic
	VTC	= PVC / TFE / Ceramic

See page 6 for additional liquid end materials.

CONNECTION SIZES:	1	= Tubing .25" I.D. x .38" O.D. / .25" Ball, 0 - 1.88 GPH
	J	= Tubing (S) .19" I.D. x .31" O.D.; (D) .25" I.D. x .38" O.D.; 19" Ball, 0 - 1.04 GPH
	METRIC:	
	M	= G 1/2 A Threads, .38" Ball, 6.15 - 37.85 LPH
	R	= G 1/2 A Threads, .25" Ball, 0 - 7.10 LPH


Please Refer to page 7 for additional connection sizes. All pumps with tubing connections come with the following items (except for LMH8, LPH8, LEH8, HV series pumps and pumps >150PSI in PVC): 4' Suction, 4' Return, 8' discharge tubing, footvalve/strainer

SUFFIX CODES:	XXX	= No Additional Options
	130	= PVDF Tubing
	500	= Five Function Valve
	520	= Five Function Degas Valve
	ITS	= 15 gal. ITS Tank System (ITS Tank not available on LM, LP, LT, and LE: H4, H5, H6, H7, H8, K7 models)
	CZXXX	= CE Approval (5 digits used for this suffix code)

See pages 9, 10 & 11 for additional information and specs.

A completed model number should look like 'LS02S4-PTC1-XXX'

Dimensions



Series E-DC Dimensions (inches)						
Model No.	A	B	C	D	E	Shipping Weight
LS02	5.0	9.6	9.6	6.5	8.2	10
LS13	5.0	9.9	9.5	6.5	8.5	10
LS14	5.0	9.9	9.5	6.5	8.5	10
LS44	5.0	10.6	11.4	7.5	9.2	15

NOTE: Inches X 2.54 = cm

PULSAtron® Series D

Key Features

- **Completely Digital.** The Series D is easy to set-up with scrolling menus that appear on the easy to read 16 digit LCD backlit display.
- **Flow Control Option.** Create a flow control system. Pump will stop if you lose flow.
- **Hall Effect water meter input.**
- **Four-button Touch Pad Control** with internationally recognized symbols for simplified programming.
- **Water Resistant** excellent for **OUTDOOR** and indoor applications.
- **Internally Dampened To Reduce Noise**, very acceptable for household installations.
- **Guided Ball Check Valve Systems**, to reduce back flow and enhance outstanding priming characteristics.
- **Safe & Easy Priming** with durable leak-free **bleed valve assembly** (standard).

OPTIONS

Add a flow switch to the Series D to create a Flow Control System. Available in 3/4" and 1" for easy installation in most systems.



Pressure and Flow Rate Capacity

MODEL	LF02	LFC3	LF03	LF04	LF64	LFC4	
Capacity	GPH	0.25	0.42	0.50	1.00	1.25	2.00
	nominal	6	10	12	24	30	48
	(max.)	LPH	1.6	0.9	1.9	3.8	4.7
Pressure	PSIG	150	250	150	100	100	50
	(max.)	BAR	10	17	10	7	7
Connections:	Tubing	1/4" ID X 3/8" OD 3/8" ID X 1/2" OD 3/16" ID X 5/16" OD					
	Piping	1/4" FNPT					
Reproducibility	+/- 3% at maximum capacity						
Viscosity Max CPS	1000						
Stroke Frequency	125 Strokes Per Minute (SPM) maximum						
Stroke Frequency	100:1						
Status Display	16-Position LCD Dot Matrix Backlight						
Power Input	115 VAC/50-60 HZ/1 ph 230 VAC/50-60 HZ/1 ph						
Average Current	0.6 Amps @ 115 VAC, 0.3 Amps @ 230 VAC						
Peak Input Power	130 Watts						
Average Input Power	50 Watts						

PULSAtron Series D Selection Guide

MODELS:	C3 = 0.42 gph / 10 gpd (1.6 lph) max pres.: 250 PSI (17 BAR)
	02 = 0.25 gph / 6 gpd (0.9 lph) max pres.: 150 PSI (10 BAR)
	03 = 0.50 gph / 12 gpd (1.9 lph) max pres.: 150 PSI (10 BAR)
	04 = 1.00 gph / 24 gpd (3.8 lph) max pres.: 100 PSI (7 BAR)
	64 = 1.25 gph / 30 gpd (4.7 lph) max pres.: 100 PSI (7 BAR)
	C4 = 2.00 gph / 48 gpd (7.6 lph) max pres.: 50 PSI (3.3 BAR)

CONTROLS: **S** = No Options Available

ELECTRICAL:	A = 115 Volt / 50-60Hz
	1 = 115 Volt / 50-60Hz (without agency approvals)
	B = 230 Volt / 50-60Hz / 1ph with 6' (1.8m) 3-wire US Plug
	2 = 230 Volt / 50-60Hz (without agency approvals)

LIQUID END MATERIALS:	PHC = GFPPL / Hypalon / Ceramic
Pump Head & Fittings/Seats & O-rings/Balls	PTC = GFPPL / TFE / Ceramic
	PVC = GFPPL / Viton / Ceramic
	KTC = PVDF / TFE / Ceramic
	VHC = PVC / Hypalon / Ceramic
	VTC = PVC / TFE / Ceramic (models <= 150 psi)
	WTC = PVC / TFE / Ceramic (models > 150 psi)

See page 6 for additional liquid end materials.

CONNECTION SIZES:	1 = Tubing .25" I.D. x .38" O.D. / .25" Ball, 0 - 1.88 GPH
	3 = Tubing .38" I.D. x .50" O.D. / .38" Ball, 1.63 - 10 GPH
	9 = Degas Head: (S) 5/16", (D) 3/8", 0-1.83 GPH
	J = Tubing, Suc: .19" I.D. x .31" O.D.; Dis: .25" I.D. x .38" O.D.; .19 Ball; 0 - 1.04 GPH
	METRIC:
	R = G 1/2 A Threads, .25" Ball, 0 - 7.10 LPH
	Y = 6 x 12mm, .25" Ball, 0 - 7.10 LPH

Please Refer to page 7 for additional connection sizes. All pumps with tubing connections come with the following items (except for LMH8, LPH8, LEH8, HV series pumps and pumps >150PSI in PVC): 4' Suction, 4' Return, 8' discharge tubing, footvalve/strainer

CONNECTION ELECTRONIC OPTIONS:	X = Liquid Tight Connector for Hardwiring Options
	1 = Water Tight DIN Connector with Sealing Cap


FLOW:	X = No Flow
	A = Flow Switch 3/4" with 8.5 ft. cable
	B = Flow Switch 3/4" with 25 ft. cable
	C = Flow Switch 1" with 8.5 ft. cable
	D = Flow Switch 1" with 25 ft. cable
	E = 25 ft. - 22g, four conductor cable

SUFFIX CODES:	XXX = No Additional Options
	130 = PVDF Tubing
	500 = Five Function Valve
	520 = Five Function Degas Valve
	ITS = 15 gal. ITS Tank System (ITS Tank not available on LM, LP, LT, and LE: H4, H5, H6, H7, H8, K7 models)
	CZXXX = CE Approval (5 digits used for this suffix code)

See pages 9, 10 & 11 for additional information and specs.

A completed model number should look like 'LF03SA-PTC1-XA-XXX'

Dimensions



Series D Dimensions (inches)						
Model No.	A	B	C	D	E	Shipping Weight
LF02	5.0	9.6	9.5	6.5	8.2	10
LFC3	5.0	9.9	9.5	6.5	8.5	10
LF03	5.0	9.9	9.5	6.5	8.5	10
LF04	5.0	9.9	9.5	6.5	8.5	10
LF64	5.0	9.9	9.5	6.5	8.5	10
LFC4	5.0	9.9	9.5	6.5	8.5	10

NOTE: Inches X 2.54 = cm

PULSAtron® Series A PLUS

Key Features

- **Manual Control** by on-line adjustable stroke rate and stroke length.
- **Agency approved** for demanding **OUTDOOR** and indoor applications.
- **Highly Reliable** timing circuit.
- **Water Resistant** excellent for **OUTDOOR** and indoor applications.
- **Internally Dampened To Reduce Noise**, very acceptable for household installations.
- **Guided Ball Check Valve Systems**, to reduce back flow and enhance outstanding priming characteristics.
- **Premium Standard Wetted Component Materials**.
- **Few Moving Parts** and **Wall Mountable**.
- **Safe & Easy Priming** with durable leak-free **bleed valve assembly** (standard).
- **Optional Control**: External pace with auto/manual selection.



Pressure and Flow Rate Capacity

MODEL	LBC2	LB02	LBC3	LB03	LB04	LB64	LBC4
Capacity	GPH 0.25	0.25	0.42	0.50	1.00	1.25	2.00
nominal	GPD 6	6	10	12	24	30	48
	(max.) LPH 0.9	0.9	1.6	1.9	3.8	4.7	7.6
Pressure	PSIG 250	150	250	150	100	100	50
	(max.) BAR 17	10	17	10	7	7	3.3
Connections:	Tubing	1/4" ID X 3/8" OD 3/8" ID X 1/2" OD 3/16" ID X 5/16" OD					
	Piping	1/4" FNPT					
Reproducibility	+/- 3% at maximum capacity						
Viscosity Max CPS	1000						
Stroke Frequency	125 Strokes Per Minute (SPM) maximum						
Stroke Frequency	10:1						
Stroke Length Turn-	10:1						
Power Input	115 VAC/50-60 HZ/1 ph 230 VAC/50-60 HZ/1 ph						
Average Current	0.6 Amps @ 115 VAC, 0.3 Amps @ 230 VAC						
Peak Input Power	130 Watts						
Average Input Power	50 Watts						

PULSAtron Series A Plus Selection Guide

LB__ - - - - -

MODELS:	C2	= 0.25 gph / 6 gpd (0.9 lph) max pres.: 250 PSI (17 BAR)
	C3	= 0.42 gph / 10 gpd (1.6 lph) max pres.: 250 PSI (17 BAR)
	02	= 0.25 gph / 6 gpd (0.9 lph) max pres.: 150 PSI (10 BAR)
	03	= 0.50 gph / 12 gpd (1.9 lph) max pres.: 150 PSI (10 BAR)
	04	= 1.00 gph / 24 gpd (3.8 lph) max pres.: 100 PSI (7 BAR)
	64	= 1.25 gph / 30 gpd (4.7 lph) max pres.: 100 PSI (7 BAR)
	C4	= 2.00 gph / 48 gpd (7.6 lph) max pres.: 50 PSI (3.3 BAR)

CONTROLS:	S	= Manual
	E	= External Pacing w/ Auto/Manual Switch
	G	= External Pacing w/ Prime Button
	P	= Stop Function Option

ELECTRICAL:	A	= 115 Volt / 50-60Hz
	1	= 115 Volt / 50-60Hz (without agency approvals)
	B	= 230 Volt / 50-60Hz / 1ph with 6' (1.8m) 3-wire US Plug
	2	= 230 Volt / 50-60Hz (without agency approvals)

LIQUID END MATERIALS: Pump Head & Fittings/Seats & O-rings/Balls	PHC	= GFPP / Hypalon / Ceramic
	PTC	= GFPP / TFE / Ceramic
	PVC	= GFPP / Viton / Ceramic
	KTC	= PVDF / TFE / Ceramic
	VHC	= PVC / Hypalon / Ceramic
	VTC	= PVC / TFE / Ceramic (models <= 150 psi)
	WTC	= PVC / TFE / Ceramic (models > 150 psi)

See page 6 for additional liquid end materials.

CONNECTION SIZES:	1	= Tubing .25" I.D. x .38" O.D. / .25" Ball, 0 - 1.88 GPH
	3	= Tubing .38" I.D. x .50" O.D. / .38" Ball, 1.63 - 10 GPH
	9	= Degas Head: (S) 5/16", (D) 3/8", 0-1.83 GPH
	J	= Tubing, Suc: .19" I.D. x .31" O.D.; Dis: .25" I.D. x .38" O.D.; .19 Ball; 0 - 1.04 GPH
	METRIC:	
	R	= G 1/2 A Threads, .25" Ball, 0 - 7.10 LPH
	Y	= 6 x 12mm, .25" Ball, 0 - 7.10 LPH


Please Refer to page 7 for additional connection sizes. All pumps with tubing connections come with the following items (except for LMH8, LPH8, LEH8, HV series pumps and pumps >150PSI in PVC): 4' Suction, 4' Return, 8' discharge tubing, footvalve/strainer

SUFFIX CODES:	XXX	= No Additional Options
	130	= PVDF Tubing
	500	= Five Function Valve
	520	= Five Function Degas Valve
	ITS	= 15 gal. ITS Tank System (ITS Tank not available on LM, LP, LT, and LE: H4, H5, H6, H7, H8, K7 models)
	CZXXX	= CE Approval (5 digits used for this suffix code)

See pages 9, 10 & 11 for additional information and specs.

A completed model number should look like 'LB03SA-PTC1-XXX'

Dimensions



Series A PLUS Dimensions (inches)						
Model No.	A	B	C	D	E	Shipping Weight
LB02	5.0	9.6	9.5	6.5	8.2	10
LBC2	5.0	9.9	9.5	6.5	8.5	10
LBC3	5.0	9.9	9.5	6.5	8.5	10
LB03	5.0	9.9	9.5	6.5	8.5	10
LB04	5.0	9.9	9.5	6.5	8.5	10
LB64	5.0	9.9	9.5	6.5	8.5	10
LBC4	5.0	9.9	9.5	6.5	8.5	10

NOTE: Inches X 2.54 = cm

PULSAtron® Series C PLUS

Key Features

- **Manual Control** by on-line adjustable stroke rate and stroke length.
- **Agency approved** for demanding **OUTDOOR** and indoor applications.
- **Highly Reliable** timing circuit.
- **Water Resistant** excellent for **OUTDOOR** and indoor applications.
- **Internally Dampened To Reduce Noise**, very acceptable for household installations.
- **Guided Ball Check Valve Systems**, to reduce back flow and enhance outstanding priming characteristics.
- **Premium Standard Wetted Component Materials**.
- **Few Moving Parts** and **Wall Mountable**.
- **Safe & Easy Priming** with durable leak-free **bleed valve assembly** (standard).
- **Optional Control**: External pace with auto/manual selection.



Pressure and Flow Rate Capacity

MODEL	LD02	LD03	LD04	LD54	
Capacity nominal (max.)	GPH	0.25	0.50	1.00	1.25
	GPD	6	12	24	30
	LPH	0.9	1.9	3.8	4.7
Pressure (max.)	PSIG	80	80	80	80
	BAR	5.6	5.6	5.6	5.6
Connections:	Tubing	1/4" ID X 3/8" OD 3/8" ID X 1/2" OD 3/16" ID X 5/16" OD			
	Piping	1/4" FNPT			
Reproducibility	+/- 3% at maximum capacity				
Viscosity Max CPS	1000 CPS				
Stroke Frequency	125 Strokes Per Minute (SPM) maximum				
Stroke Frequency	10:1				
Stroke Length Turn-	10:1				
Power Input	115 VAC/50-60 HZ/1 ph 230 VAC/50-60 HZ/1 ph				
Average Current	0.6 Amps @ 115 VAC, 0.3 Amps @ 230 VAC				
Peak Input Power	130 Watts				
Average Input Power	50 Watts				

PULSAtron Series C Plus Selection Guide

MODELS:	02	= 0.25 gph / 6 gpd (0.9 lph) max pres.: 80 PSI (5.6 BAR)
	03	= 0.50 gph / 12 gpd (1.9 lph) max pres.: 80 PSI (5.6 BAR)
	04	= 1.00 gph / 24 gpd (3.8 lph) max pres.: 80 PSI (5.6 BAR)
	54	= 1.25 gph / 30 gpd (4.7 lph) max pres.: 80 PSI (5.6 BAR)

CONTROLS:	S	= Manual
	E	= External Pacing w/ Auto/Manual Switch
	G	= External Pacing w/ Prime Button
	P	= Stop Function Option

ELECTRICAL:	A	= 115 Volt / 50-60Hz
	1	= 115 Volt / 50-60Hz (without agency approvals)
	B	= 230 Volt / 50-60Hz / 1ph with 6' (1.8m) 3-wire US Plug
	2	= 230 Volt / 50-60Hz (without agency approvals)

LIQUID END MATERIALS:	PHC	= GFPP / Hypalon / Ceramic
	PTC	= GFPP / TFE / Ceramic
	KTC	= PVDF / TFE / Ceramic
	VHC	= PVC / Hypalon / Ceramic
	VTC	= PVC / TFE / Ceramic

See page 6 for additional liquid end materials.

CONNECTION SIZES:	1	= Tubing .25" I.D. x .38" O.D. / .25" Ball, 0 - 1.88 GPH
	A	= Tubing .38" I.D. x .50" O.D. / .25" Ball, 0 - 1.88 GPH
	J	= Tubing, Suc: .19" I.D. x .31" O.D.; Dis: .25" I.D. x .38" O.D.; .19 Ball; 0 - 1.04 GPH
	METRIC:	
	R	= G 1/2 A Threads, .25" Ball, 0 - 7.10 LPH
	Y	= 6 x 12mm, .25" Ball, 0 - 7.10 LPH


Please Refer to page 7 for additional connection sizes. All pumps with tubing connections come with the following items (except for LMH8, LPH8, LEH8, HV series pumps and pumps >150PSI in PVC): 4' Suction, 4' Return, 8' discharge tubing, footvalve/strainer

SUFFIX CODES:	XXX	= No Additional Options
	130	= PVDF Tubing
	500	= Five Function Valve
	520	= Five Function Degas Valve
	ITS	= 15 gal. ITS Tank System (ITS Tank not available on LM, LP, LT, and LE: H4, H5, H6, H7, H8, K7 models)
	CZXXX	= CE Approval (5 digits used for this suffix code)

See pages 9, 10 & 11 for additional information and specs.

A completed model number should look like 'LD03SA-PTC1-XXX'

Dimensions



Series C PLUS Dimensions (inches)						
Model No.	A	B	C	D	E	Shipping Weight
LD02	5.0	9.6	9.5	6.5	8.2	10
LD03	5.0	9.9	9.5	6.5	8.5	10
LD04	5.0	9.9	9.5	6.5	8.5	10
LD54	5.0	9.9	9.5	6.5	8.5	10

NOTE: Inches X 2.54 = cm

PULSAtron® Series C

Key Features

- **Automatic Control** by external pacing with prime switch (optional).
- **Manual Control** by on-line adjustable stroke length (fixed stroke rate).
- **Liquid Low Level Option** available to prevent loss of prime.
- **Agency approved** for demanding **OUTDOOR** and indoor applications.
- **Highly Reliable** timing circuit.
- **Water Resistant** excellent for **OUTDOOR** and indoor applications.
- **Internally Dampened To Reduce Noise**, very acceptable for household installations.
- **Guided Ball Check Valve Systems**, to reduce back flow and enhance outstanding priming characteristics.
- **Premium Standard Wetted Component Materials**.
- **Few Moving Parts** and **Wall Mountable**.
- **Safe & Easy Priming** with durable leak-free **bleed valve assembly** (standard).



Pressure and Flow Rate Capacity

MODEL		LC02	LC03	LC04	LC54
Capacity nominal (max.)	GPH	0.25	0.50	1.00	1.25
	GPD	6	12	24	30
	LPH	0.9	1.9	3.8	4.7
Pressure (max.)	PSIG	80	80	80	80
	BAR	5.6	5.6	5.6	5.6
Connections:	Tubing	1/4" ID X 3/8" OD 3/8" ID X 1/2" OD 3/16" ID X 5/16" OD			
	Piping	1/4" FNPT			
Reproducibility	+/- 3% at maximum capacity				
Viscosity Max CPS	1000 CPS				
Stroke Frequency	125 Strokes Per Minute (SPM) maximum				
Stroke Length Turn-	5:1				
Power Input	115 VAC/50-60 HZ/1 ph				
	230 VAC/50-60 HZ/1 ph				
Average Current	0.6 Amps @ 115 VAC, 0.3 Amps @ 230 VAC				
Peak Input Power	130 Watts				
Average Input Power	50 Watts				

PULSAtron Series C Selection Guide

MODELS:	02	= 0.25 gph / 6 gpd (0.9 lph) max pres.: 80 PSI (5.6 BAR)
	03	= 0.50 gph / 12 gpd (1.9 lph) max pres.: 80 PSI (5.6 BAR)
	04	= 1.00 gph / 24 gpd (3.8 lph) max pres.: 80 PSI (5.6 BAR)
	54	= 1.25 gph / 30 gpd (4.7 lph) max pres.: 80 PSI (5.6 BAR)

CONTROLS:	S	= Manual
	E	= External Pacing w/ Auto/Manual Switch
	G	= External Pacing w/ Prime Button
	P	= Stop Function Option

ELECTRICAL:	A	= 115 Volt / 50-60Hz
	1	= 115 Volt / 50-60Hz (without agency approvals)
	B	= 230 Volt / 50-60Hz / 1ph with 6' (1.8m) 3-wire US Plug
	2	= 230 Volt / 50-60Hz (without agency approvals)

LIQUID END MATERIALS:	PHC	= GFPP / Hypalon / Ceramic
	PTC	= GFPP / TFE / Ceramic
	VHC	= PVC / Hypalon / Ceramic
	VTC	= PVC / TFE / Ceramic
	VVC	= PVC / Viton / Ceramic

See page 6 for additional liquid end materials.

CONNECTION SIZES:	1	= Tubing .25" I.D. x .38" O.D. / .25" Ball, 0 - 1.88 GPH
	A	= Tubing .38" I.D. x .50" O.D. / .25" Ball, 0 - 1.88 GPH
	J	= Tubing, Suc: .19" I.D. x .31" O.D.; Dis: .25" I.D. x .38" O.D.; .19 Ball; 0 - 1.04 GPH
	METRIC:	
	P	= 4 x 6mm, .25" Ball, 0 - 3.94 LPH
U	= 6 x 10mm, .25" Ball, 0 - 7.10 LPH	


Please Refer to page 7 for additional connection sizes. All pumps with tubing connections come with the following items (except for LMH8, LPH8, LEH8, HV series pumps and pumps >150PSI in PVC): 4' Suction, 4' Return, 8' discharge tubing, footvalve/strainer

SUFFIX CODES:	XXX	= No Additional Options
	130	= PVDF Tubing
	500	= Five Function Valve
	520	= Five Function Degas Valve
	ITS	= 15 gal. ITS Tank System (ITS Tank not available on LM, LP, LT, and LE: H4, H5, H6, H7, H8, K7 models)
	CZXXX	= CE Approval (5 digits used for this suffix code)

See pages 9, 10 & 11 for additional information and specs.

A completed model number should look like 'LC03SA-PTC1-XXX'

Dimensions



Series C Dimensions (inches)						
Model No.	A	B	C	D	E	Shipping Weight
LC02	5.0	9.6	9.5	6.5	8.2	10
LC03	5.0	9.9	9.5	6.5	8.5	10
LC04	5.0	9.9	9.5	6.5	8.5	10
LC54	5.0	9.9	9.5	6.5	8.5	10

NOTE: Inches X 2.54 = cm

PULSAtron® PLUS Series CW

Conductivity Control with Water Meter Feed

The Series CW was designed to control conductivity and feed inhibitor in an open-air cooling tower. Chemical feed is initiated and controlled by input from a water meter. The Series CW combines everything you need to control conductivity and feed inhibitor into one unique, compact package to create a simple and cost effective metering and control system.

Principal of Operation

The Series CW includes a solenoid actuated metering pump, conductivity sensor, bleed relay and a dry contact input for water meter control. At set-up, the operator sets the conductivity set point, differential (or dead-band), the pump stroke frequency and run time. When conductivity reaches the set point, the system activates the bleed relay.

As make-up water passes through the water meter, it generates a series of pulses based on the volume of flow. The pump counts the pulses until the total reaches the Count set point. The pump runs at the frequency and run-time specified at set-up and the count is reset.



Features

- 120VAC or 250VAC @ 50/60 HZ, 5A max
- 4-electrode conductivity input
- 0-6000 mS/cm \pm 1%, temperature compensated
- Relay rated to 5A at 240VAC
- Isolated dry contact flow switch input
- Isolated dry contact water meter input
- 4 Digit LED, 9 key membrane keypad
- Single-button function keys
- Set, Differential, Calibration, Pulse Timer, and Count functions
- Stroke rate adjusts 0-100% in 1% increments, turndown ratio 100:1

Pressure and Flow Rate Capacity

MODEL	LW02	LW03	LW04	LW64	
Capacity	GPH	0.25	0.50	1.00	1.25
	GPD	6	12	24	30
	LPH	0.9	1.9	3.8	4.7
Pressure	PSIG	150	150	100	100
	BAR	10	10	7	7

PULSAtron Series CW Selection Guide

MODELS:	02	= 0.25 gph / 6 gpd (0.9 lph) max pres.: 150 PSI (10 BAR)
	03	= 0.50 gph / 12 gpd (1.9 lph) max pres.: 150 PSI (10 BAR)
	04	= 1.00 gph / 24 gpd (3.8 lph) max pres.: 100 PSI (7 BAR)
	64	= 1.25 gph / 30 gpd (4.7 lph) max pres.: 100 PSI (7 BAR)

CONTROLS:	R	= Rising Set Point (standard)
	F	= Falling Set Point

ELECTRICAL:	A	= 115 Volt / 50-60Hz
	1	= 115 Volt / 50-60Hz (without agency approvals)
	B	= 230 Volt / 50-60Hz / 1ph with 6' (1.8m) 3-wire US Plug
	2	= 230 Volt / 50-60Hz (without agency approvals)

LIQUID END MATERIALS:	PHC	= GFPP / Hypalon / Ceramic
	PTC	= GFPP / TFE / Ceramic
Pump Head & Fittings/Seats & O-rings/Balls	PVC	= GFPP / Viton / Ceramic
	KTC	= PVDF / TFE / Ceramic
	VHC	= PVC / Hypalon / Ceramic
	VTC	= PVC / TFE / Ceramic

See page 6 for additional liquid end materials.

CONNECTION SIZES:	1	= Tubing .25" I.D. x .38" O.D. / .25" Ball, 0 - 1.88 GPH
	9	= Degas Head: (S) 5/16", (D) 3/8", 0-1.83 GPH
	J	= Tubing, Suc: .19" I.D. x .31" O.D.; Dis: .25" I.D. x .38" O.D.; .19 Ball; 0 - 1.04 GPH
	METRIC:	
	R	= G 1/2 A Threads, .25" Ball, 0 - 7.10 LPH
	Y	= 6 x 12mm, .25" Ball, 0 - 7.10 LPH

Please Refer to page 7 for additional connection sizes. All pumps with tubing connections come with the following items (except for LMH8, LPH8, LEH8, HV series pumps and pumps >150PSI in PVC): 4' Suction, 4' Return, 8' discharge tubing, footvalve/strainer

SENSOR:	2	= Stainless Steel with 8.5 ft. cable
	3	= Stainless Steel with 25 ft. cable
	4	= Carbon Graphite with 8.5 ft. cable
	5	= Carbon Graphite with 25 ft. cable


FLOW:	X	= No Flow
	A	= Flow Switch 3/4" with 8.5 ft. cable and 3" nipple
	B	= Flow Switch 3/4" with 25 ft. cable and 3" nipple
	C	= Flow Assembly with 8.5 ft. cable
	E	= Flow Assembly with 25 ft. cable

SUFFIX CODES:	XXX	= No Additional Options
	130	= PVDF Tubing
	500	= Five Function Valve
	520	= Five Function Degas Valve
	CZXXX	= CE Approval (5 digits used for this suffix code)

See pages 9, 10 & 11 for additional information and specs.

A completed model number should look like 'LW03SA-PTC1-2A-XXX'

Dimensions



Series CW Dimensions (inches)						
Model No.	A	B	C	D	E	Shipping Weight (lbs.)
LW02	5.0	9.6	9.5	6.5	8.2	13
LW03	5.0	9.9	9.5	6.5	8.5	13
LW04	5.0	9.9	9.5	6.5	8.5	13
LW64	5.0	9.9	9.5	6.5	8.5	13

NOTE: Inches X 2.54 = cm

PULSAtron® PLUS Series CL

Conductivity Control with Limit Timer

The Series CL was designed to control conductivity and feed inhibitor in an open-air cooling tower. The Series CL combines everything you need to control conductivity and feed inhibitor into one unique, compact package to create a simple and cost effective metering and control system.

Principle of Operation

The Series CL includes a conductivity sensor, bleed relay and a user programmable limit timer. When conductivity reaches the user specified level, the system activates the bleed relay and begins pumping inhibitor. The 'feed & bleed' cycle will continue until the conductivity returns to the desired level.

The programmable limit timer allows the user to specify a maximum pumping time for the feed cycle. If the limit time expires before the conductivity level returns to the set range, the pump stops feeding while the bleed continues. Once the conductivity level is reached and the system stops bleeding, the feed limit timer is automatically reset for the next bleed cycle.



Features

- 120VAC or 250VAC @ 50/60 HZ, 5A max
- 4-electrode conductivity input
- 0-6000 mS/cm \pm 1%, temperature compensated
- Relay rated to 5A at 240VAC
- Isolated dry contact flow switch input
- 4 Digit LED, 9 key membrane keypad
- Single-button function keys
- Set, Differential, Calibration, Pulse Timer, and Count functions
- Stroke rate adjusts 0-100% in 1% increments, turndown ratio 100:1

Pressure and Flow Rate Capacity

MODEL		LL02	LL03	LL04	LL64
Capacity	GPH	0.25	0.50	1.00	1.25
	nominal				
	GPD	6	12	24	30
(max.)	LPH	0.9	1.9	3.8	4.7
	Pressure				
PSIG	150	150	100	100	
(max.)	BAR	10	10	7	7

PULSAtron Series CL Selection Guide

MODELS:	02	= 0.25 gph / 6 gpd (0.9 lph) max pres.: 150 PSI (10 BAR)
	03	= 0.50 gph / 12 gpd (1.9 lph) max pres.: 150 PSI (10 BAR)
	04	= 1.00 gph / 24 gpd (3.8 lph) max pres.: 100 PSI (7 BAR)
	64	= 1.25 gph / 30 gpd (4.7 lph) max pres.: 100 PSI (7 BAR)

CONTROLS:	R	= Rising Set Point (standard)
	F	= Falling Set Point

ELECTRICAL:	A	= 115 Volt / 50-60Hz
	1	= 115 Volt / 50-60Hz (without agency approvals)
	B	= 230 Volt / 50-60Hz / 1ph with 6' (1.8m) 3-wire US Plug
	2	= 230 Volt / 50-60Hz (without agency approvals)

LIQUID END MATERIALS: Pump Head & Fittings/Seats & O-rings/Balls	PHC	= GFPPL / Hypalon / Ceramic
	PTC	= GFPPL / TFE / Ceramic
	PVC	= GFPPL / Viton / Ceramic
	KTC	= PVDF / TFE / Ceramic
	VHC	= PVC / Hypalon / Ceramic
	VTC	= PVC / TFE / Ceramic

See page 6 for additional liquid end materials.

CONNECTION SIZES:	1	= Tubing .25" I.D. x .38" O.D. / .25" Ball, 0 - 1.88 GPH
	9	= Degas Head: (S) 5/16", (D) 3/8", 0-1.83 GPH
	J	= Tubing, Suc: .19" I.D. x .31" O.D.; Dis: .25" I.D. x .38" O.D.,; .19 Ball; 0 - 1.04 GPH
	METRIC:	
	R	= G 1/2 A Threads, .25" Ball, 0 - 7.10 LPH
	Y	= 6 x 12mm, .25" Ball, 0 - 7.10 LPH

Please Refer to page 7 for additional connection sizes. All pumps with tubing connections come with the following items (except for LMH8, LPH8, LEH8, HV series pumps and pumps >150PSI in PVC): 4' Suction, 4' Return, 8' discharge tubing, footvalve/strainer

SENSOR:	2	= Stainless Steel with 8.5 ft. cable
	3	= Stainless Steel with 25 ft. cable
	4	= Carbon Graphite with 8.5 ft. cable
	5	= Carbon Graphite with 25 ft. cable


FLOW:	X	= No Flow
	A	= Flow Switch 3/4" with 8.5 ft. cable and 3" nipple
	B	= Flow Switch 3/4" with 25 ft. cable and 3" nipple
	C	= Flow Assembly with 8.5 ft. cable
	E	= Flow Assembly with 25 ft. cable

SUFFIX CODES:	XXX	= No Additional Options
	130	= PVDF Tubing
	500	= Five Function Valve
	520	= Five Function Degas Valve
	CZXXX	= CE Approval (5 digits used for this suffix code)

See pages 9, 10 & 11 for additional information and specs.

A completed model number should look like 'LLO3RA-PTC1-2A-XXX'

Dimensions



Series CL Dimensions (inches)						
Model No.	A	B	C	D	E	Shipping Weight (lbs.)
LL02	5.0	9.6	9.5	6.5	8.2	13
LL03	5.0	9.9	9.5	6.5	8.5	13
LL04	5.0	9.9	9.5	6.5	8.5	13
LL64	5.0	9.9	9.5	6.5	8.5	13

NOTE: Inches X 2.54 = cm

PULSAtron® PLUS Series WT

Water Meter Feed & Bleed Control

The Series WT was designed to control the feed and bleed cycle in an open-air cooling tower. The feed and bleed cycle is initiated and controlled by input from a water meter. The Series WT combines everything you need to bleed off the tower and feed inhibitor into one unique, compact package to create a simple and cost effective metering and control system.

Principal of Operation

The Series WT includes a water meter input with programmable pulse timers that control the feed and bleed relays. When the water level in the cooling tower drops, the make-up water is turned on creating flow through the water meter. As make-up water passes through the water meter, it generates a series of pulses based on the volume of flow.

The Series WT has two pulse counters with independent set points that monitors output of the water meter. One controls the pump and one controls the bleed relay. When the count exceeds the set point, the counter is reset and the control function is activated for the run-time specified at set-up.

Features

- 120VAC or 250VAC @ 50/60 HZ, 5A max
- Relay rated to 5A at 240VAC
- Isolated dry contact flow switch input
- Isolated dry contact water meter input
- 4 Digit LED, 9 key membrane keypad
- Single-button function keys
- Pump and bleed timers, pump and bleed counters
- Stroke rate adjusts 0-100% in 1% increments, turndown ratio 100:1



Pressure and Flow Rate Capacity

MODEL	LQ02	LQ03	LQ04	LQ64		
Capacity	GPH	0.25	0.50	1.00	1.25	
	nominal	GPD	6	12	24	30
	(max.)	LPH	0.9	1.9	3.8	4.7
Pressure	PSIG	150	150	100	100	
	(max.)	BAR	10	10	7	7

PULSAtron Series WT Selection Guide

MODELS:	02	= 0.25 gph / 6 gpd (0.9 lph) max pres.: 150 PSI (10 BAR)
	03	= 0.50 gph / 12 gpd (1.9 lph) max pres.: 150 PSI (10 BAR)
	04	= 1.00 gph / 24 gpd (3.8 lph) max pres.: 100 PSI (7 BAR)
	64	= 1.25 gph / 30 gpd (4.7 lph) max pres.: 100 PSI (7 BAR)

CONTROLS: X = No options Available

ELECTRICAL:	A	= 115 Volt / 50-60Hz
	1	= 115 Volt / 50-60Hz (without agency approvals)
	B	= 230 Volt / 50-60Hz / 1ph with 6' (1.8m) 3-wire US Plug
	2	= 230 Volt / 50-60Hz (without agency approvals)

LIQUID END MATERIALS:	PHC	= GFPPL / Hypalon / Ceramic
	PTC	= GFPPL / TFE / Ceramic
Pump Head & Fittings/Seats & O-rings/Balls	PVC	= GFPPL / Viton / Ceramic
	KTC	= PVDF / TFE / Ceramic
	VHC	= PVC / Hypalon / Ceramic
	VTC	= PVC / TFE / Ceramic

See page 6 for additional liquid end materials.

CONNECTION SIZES:	1	= Tubing .25" I.D. x .38" O.D. / .25" Ball, 0 - 1.88 GPH
	9	= Degas Head: (S) 5/16", (D) 3/8", 0-1.83 GPH
	J	= Tubing, Suc: .19" I.D. x .31" O.D.; Dis: .25" I.D. x .38" O.D.; .19 Ball; 0 - 1.04 GPH
	METRIC:	
	R	= G 1/2 A Threads, .25" Ball, 0 - 7.10 LPH
	Y	= 6 x 12mm, .25" Ball, 0 - 7.10 LPH

Please Refer to page 7 for additional connection sizes. All pumps with tubing connections come with the following items (except for LMH8, LPH8, LEH8, HV series pumps and pumps >150PSI in PVC): 4' Suction, 4' Return, 8' discharge tubing, footvalve/strainer

SENSOR: X = No Options Available


FLOW:	X	= No Flow
	A	= Flow Switch 3/4" with 8.5 ft. cable and 3" nipple
	B	= Flow Switch 3/4" with 25 ft. cable and 3" nipple
	C	= Flow Assembly with 8.5 ft. cable
	E	= Flow Assembly with 25 ft. cable

SUFFIX CODES:	XXX	= No Additional Options
	130	= PVDF Tubing
	500	= Five Function Valve
	520	= Five Function Degas Valve
	CZXXX	= CE Approval (5 digits used for this suffix code)

See pages 9, 10 & 11 for additional information and specs.

A completed model number should look like 'LQ03XA-PTC1-XA-XXX'

Dimensions



Series WT Dimensions (inches)						
Model No.	A	B	C	D	E	Shipping Weight (lbs.)
LQ02	5.0	9.6	9.5	6.5	8.2	13
LQ03	5.0	9.9	9.5	6.5	8.5	13
LQ04	5.0	9.9	9.5	6.5	8.5	13
LQ64	5.0	9.9	9.5	6.5	8.5	13

Note: Inches x 2.54 = cm

PULSAtron® PLUS Series ET

Feed Control with Water Meter Input

The Series ET was designed to feed chemical in response to a water meter input. Typical applications include inhibitor feed for an open air-cooling tower. The Series ET provides everything you need in one unique, compact package to create a simple and cost effective metering system.

Principal of Operation

The Series ET counts pulses from a water meter. When the count exceeds a set value (either 1 or 10), the pump starts. The pump will continue to run for an adjustable time period. There are two time ranges – either 2 to 200 seconds or 12 seconds to 20 minutes. The setting is made by selecting a time base value (200 seconds or 20 minutes) and then setting the time base percentage from 1 to 100%.

Other control features include a standby mode, continuous 'ON' mode and the ability to adjust the stroke length from 0 – 100%.

The pump includes both input and output water meter connections at the front panel. The output connection provides an isolated dry contact output of the water meter contact to operate additional pumps or timers off the same water meter.



Features

- Isolated from Earth Ground
- 120VAC or 250VAC @ 50/60 HZ, 5A max
- Isolated Dry Contact (Water Meter)
- Isolated Dry Contact (Water Meter)
- Mode Select Knob, Stroke Length, Stroke Rate
- Standby, On, 200 sec/count, 200 sec/10 count, 20 min/count and 20 min/10 count
- Stroke rate and stroke length adjust 0-100% in 1% increments. Frequency turndown ratio 100:1.
- Agency approved for demanding **OUTDOOR** and indoor applications

Pressure and Flow Rate Capacity

MODEL	LTB2	LTA2	LTB3	LTA3	LTF4	LTD4	LTB4	LTH4	LTG4	LTE4	LTH5	LTH6	LTH7	LTH8	
Capacity nominal (max.)	GPH	0.21	0.25	0.50	0.50	0.85	0.90	1.00	1.70	1.75	1.85	3.15	5.00	10.00	21
	GPD	5	6	12	12	20	22	24	41	42	44	76	120	240	504
	LPH	0.8	0.9	1.9	1.9	3.2	3.4	3.8	6.4	6.6	7.0	11.9	18.9	37.9	79.5
Pressure (max.)	PSIG	250	150	150	100	250	150	100	250	150	100	150	100	35	20
	BAR	17	10	10	7	17	10	7	17	10	7	10	7	2.4	1.3

PULSAtron Series ET Selection Guide

MODELS:	B2 = 0.21 gph / 5 gpd (0.8 lph) max pres.: 250 PSI (17 BAR)
	F4 = 0.85 gph / 20 gpd (3.2 lph) max pres.: 250 PSI (17 BAR)
	H4 = 1.70 gph / 41 gpd (6.4 lph) max pres.: 250 PSI (17 BAR)
	A2 = 0.25 gph / 6 gpd (0.9 lph) max pres.: 150 PSI (10 BAR)
	B3 = 0.50 gph / 12 gpd (1.9 lph) max pres.: 150 PSI (10 BAR)
	D4 = 0.90 gph / 22 gpd (3.4 lph) max pres.: 150 PSI (10 BAR)
	G4 = 1.75 gph / 42 gpd (6.6 lph) max pres.: 150 PSI (10 BAR)
	H5 = 3.15 gph / 76 gpd (11.9 lph) max pres.: 150 PSI (10 BAR)
	A3 = 0.50 gph / 12 gpd (1.9 lph) max pres.: 100 PSI (7 BAR)
	B4 = 1.00 gph / 24 gpd (3.8 lph) max pres.: 100 PSI (7 BAR)
	E4 = 1.85 gph / 44 gpd (7.0 lph) max pres.: 100 PSI (7 BAR)
	H6 = 5.00 gph / 120 gpd (18.9 lph) max pres.: 100 PSI (7 BAR)
	H7 = 10.0 gph / 240 gpd (37.9 lph) max pres.: 35 PSI (2.4 BAR)
	H8 = 21.0 gph / 504 gpd (79.5 lph) max pres.: 20 PSI (1.3 BAR)

CONTROLS: S = Manual On/Off

ELECTRICAL:	A = 115 Volt / 50-60Hz
	1 = 115 Volt / 50-60Hz (without agency approvals)
	B = 230 Volt / 50-60Hz / 1ph with 6' (1.8m) 3-wire US Plug
	2 = 230 Volt / 50-60Hz (without agency approvals)

LIQUID END MATERIALS:	PTC = GFPP / TFE / Ceramic
	PTT = GFPP / TFE / TFE
Pump Head & Fittings/Seats & O-rings/Balls	KTC = PVDF / TFE / Ceramic
	VHC = PVC / Hypalon / Ceramic
	VTC = PVC / TFE / Ceramic (models <= 150 psi excluding H7, H8, K7)
	WTC = PVC / TFE / Ceramic (models > 150 psi and H7, H8, K7)
	ATS = 316 S.S. / TFE / 316 S.S. (must use FNPT piping connection)

See page 6 for additional liquid end materials.

CONNECTION SIZES:	1 = Tubing .25" I.D. x .38" O.D. / .25" Ball, 0 - 1.88 GPH
	3 = Tubing .38" I.D. x .50" O.D. / .38" Ball, 1.63 - 10 GPH
	4 = Piping .25" FNPT / .38" Ball, 1.63 - 10 GPH
	B = Tubing .50" I.D. x .75" O.D. / .50" Ball, 20.83 GPH only
	METRIC:
	M = G 1/2 A Threads, .38" Ball, 6.15 - 37.85 LPH
	R = G 1/2 A Threads, .25" Ball, 0 - 7.10 LPH
	Y = 6 x 12mm, .25" Ball, 0 - 7.10 LPH


Please Refer to page 7 for additional connection sizes. All pumps with tubing connections come with the following items (except for LMH8, LPH8, LEH8, HV series pumps and pumps >150PSI in PVC): 4' Suction, 4' Return, 8' discharge tubing, footvalve/strainer

SUFFIX CODES:	XXX = No Additional Options
	130 = PVDF Tubing
	500 = Five Function Valve
	520 = Five Function Degas Valve
	ITS = 15 gal. ITS Tank System (ITS Tank not available on LM, LP, LT, and LE: H4, H5, H6, H7, H8, K7 models)
	CZXXX = CE Approval (5 digits used for this suffix code)

See pages 9, 10 & 11 for additional information and specs.

A completed model number should look like 'LTA3SA-PTC1-XXX'

Dimensions



Series ET Dimensions (inches)

Model No.	A	B	B1	C	C1	D	E	Shipping Weight
LTA2	5.4	10.3	-	10.8	-	7.5	8.9	13
LTA3	5.4	10.6	-	10.7	-	7.5	9.2	13
LTB2	5.4	10.3	-	10.8	-	7.5	8.9	13
LTB3	5.4	10.6	-	10.7	-	7.5	9.2	13
LTB4	5.4	10.6	-	10.7	-	7.5	9.2	13
LTD4	5.4	10.6	-	11.2	-	7.5	9.2	15
LTE4	5.4	10.6	-	11.2	-	7.5	9.2	15
LTF4	5.4	10.6	-	11.7	-	7.5	9.2	18
LTG4	5.4	10.6	-	11.7	-	7.5	9.2	18
LTH4	6.1	10.9	-	11.2	-	8.2	9.5	21
LTH5	6.1	11.3	-	11.2	-	8.2	9.9	21
LTH6	6.1	11.3	-	11.2	-	8.2	9.9	21
LTH7	6.1	11.7	-	11.2	-	8.2	10.3	21
LTH8 *	6.1	-	10.9	-	10.6	8.2	-	25

NOTE: Inches X 2.54 = cm

* the LPH8 is designed without a bleed valve available

PULSAtron® PLUS Series T7

Feed Control with 7 Day Timer

The Series T7 was designed to feed chemical products on a timed schedule. Typical applications include the feed of biocides in open-air cooling towers. The feed cycle is initiated and controlled by the programmable timer. The Series T7 provides everything you need in one unique, compact package to create a simple and cost effective metering system for timed applications.

Principal of Operation

The Series T7 is controlled by a 7-day programmable timer. The timer is programmable in 1-minute increments with up to 8 on/off cycles per day. Each timed event can be set to run any day of the week on a 7-day cycle.

Other control features include a standby mode, continuous 'ON' mode and the ability to adjust the stroke length from 0 – 100%.



Features

- Isolated from Earth Ground
- 120VAC or 250VAC @ 50/60 HZ, 5A max
- Mode Select Knob, Stroke Length, Stroke Rate
- 12, 22, 30 & 44 GPD @ 100 psi – 7 bar
- Stroke length adjust 0-100% in 1% increments. Turn down ratio 10:1



Pressure and Flow Rate Capacity

MODEL	LC13BA	LC14BA	LC64BA	LC44BA		
Capacity	GPH	0.50	1.00	1.25	2.00	
	nominal	GPD	12	24	30	48
	(max.)	LPH	1.9	3.8	4.7	7.6
Pressure	PSIG	100	100	100	50	
	(max.)	BAR	7	7	7	3.3



7-Day Timer

Solid-state 7-day electronic timer for easy adjustment of metering schedules and feed rates. Manual control allows for easy priming and start-up. The timer is programmable in 1 minute increments, with up to 8 events per day.

PULSAtron Series T7 Selection Guide

MODELS:	13	= 0.50 gph / 12 gpd (1.9 lph) max pres.: 100 PSI (7 BAR)
	14	= 1.00 gph / 24 gpd (3.8 lph) max pres.: 100 PSI (7 BAR)
	64	= 1.25 gph / 30 gpd (4.7 lph) max pres.: 100 PSI (7 BAR)
	44	= 2.00 gph / 48 gpd (7.6 lph) max pres.: 50 PSI (3.3 BAR)

CONTROLS: **B** = No Options Available

ELECTRICAL:	A	= 115 Volt / 50-60Hz
	1	= 115 Volt / 50-60Hz (without agency approvals)
	B	= 230 Volt / 50-60Hz / 1ph with 6' (1.8m) 3-wire US Plug
	2	= 230 Volt / 50-60Hz (without agency approvals)

LIQUID END MATERIALS:	PHC	= GFPPL / Hypalon / Ceramic
	PTC	= GFPPL / TFE / Ceramic
	KTC	= PVDF / TFE / Ceramic
	VHC	= PVC / Hypalon / Ceramic
	VTC	= PVC / TFE / Ceramic

See page 6 for additional liquid end materials.

CONNECTION SIZES:	1	= Tubing .25" I.D. x .38" O.D. / .25" Ball, 0 - 1.88 GPH
	9	= Degas Head: (S) 5/16", (D) 3/8", 0-1.83 GPH
	J	= Tubing, Suc: .19" I.D. x .31" O.D.; Dis: .25" I.D. x .38" O.D.; .19 Ball; 0 - 1.04 GPH
	METRIC:	
	Y	= 6 x 12mm, .25" Ball, 0 - 7.10 LPH
	T	= 6 x 10mm, Degassing (Note: has 10mm suction), 0 - 7.10 LP


Please Refer to page 7 for additional connection sizes. All pumps with tubing connections come with the following items (except for LMH8, LPH8, LEH8, HV series pumps and pumps >150PSI in PVC): 4' Suction, 4' Return, 8' discharge tubing, footvalve/strainer

SUFFIX CODES:	XXX	= No Additional Options
	130	= PVDF Tubing
	500	= Five Function Valve
	520	= Five Function Degas Valve
	ITS	= 15 gal. ITS Tank System (ITS Tank not available on LM, LP, LT, and LE: H4, H5, H6, H7, H8, K7 models)
	CZXXX	= CE Approval (5 digits used for this suffix code)

See pages 9, 10 & 11 for additional information and specs.

A completed model number should look like 'LC13BA-PTC1-XXX'

Dimensions



Series T7 Dimensions (inches)						
Model No.	A	B	C	D	E	Shipping Weight
LC13BA	5.0	9.6	9.5	6.5	8.2	10
LC14BA	5.0	9.9	9.5	6.5	8.5	10
LC64BA	5.0	9.9	9.5	6.5	8.5	10
LC44BA	5.4	10.6	11.3	7.4	9.2	11.8

NOTE: Inches X 2.54 = cm

PULSAtron® KOPkits

Selecting a KOPkit:

All KOPkit model strings begin with the letter K. The remainder of the string can be determined by knowing your pump model.

When you select your KOPkit, you will need to build the model number based on the pump model string that you purchased. The two pieces of information you need are the head size and the wet-end code, which is part of the model string of the pump.

The pump head size is the fourth digit in the pump model number.

LB02SA-PTC1-XXX

The 2 represents your pump head size.

Digits 7-20 in the pump model string represent the wet-end code. It is the group of four digits set apart by the dash lines.

LB02SA-PTC1-XXX

These four digits represent your wet-end code.

In the following selection guide, you will break down your wet-end code into the four parts to get your total price for the KOPkit. The four digits in the wet-end code represent the Head Material, Seats & O-Rings, Ball Material and Connection Type. Using the above example, the code breaks down as follows:

P - Head Material, including fittings. In this example, the P represents GPPPL.

T - Seat & O-Ring Material. In this example, the T represents Teflon.

C - Types of Balls used in the valves. In this example, the C represents Ceramic.

1 - Connection type. In this example, the 1 represents tubing connections for 3/8" OD tubing.

The completed KOPkit number for the above example is:

K2PTC1

Note: If you do not find your connection size in the following selection guide, please consult the factory for accurate pricing. Our philosophy with the PULSAtron product line is to make it as flexible as our customers need it to be.

PULSAtron KOPkit Selection Guid

K_

HEAD SIZE

2 =
3 =
4 =
5 =
6 =
7 =
8 =

The digits 2-8 following the K represents the pump head size. This is represented by the fourth digit in the pump model string.

HEAD MATERIALS

A = 316 Stainless Steel
K = PVDF (Kynar)
P = GFPPPL (Polypropylene)
V = PVC (Poly Vinyl Chloride) (models <= 150 psi excluding H7, H8, K7)
W = PVC (models > 150 psi and H7, H8, K7)

SEATS/O-RINGS

H = Hypalon
V = Viton
T = TFE

BALLS

T = TFE
C = Ceramic
S = 316 Stainless Steel
H = Alloy C (Hastelloy)

CONNECTION TYPE

Type	Suction	Discharge	Spring
1 = Tubing	.25" x .38"	.25" x .38"	
2 = Piping	.25" FNPT	.25" FNPT	
3 = Tubing	.38" x .50"	.38" x .50"	
4 = Piping	.25" FNPT	.25" FNPT	
5 = Tubing	.50" x .75"	.38" x .50"	Yes
6 = Piping	.25" FNPT	.25" FNPT	Yes
7 = Tubing	.50" x .75"	.50" FNPT	Yes
8 = Piping	.50" FNPT	.50" FNPT	Yes
9 = Tubing	.19" x .31"	.25" x .38"	Yes Degas
A = Tubing	.38" x .50"	.38" x .50"	
B = Tubing	.50" x .75"	.50" x .75"	
C = Piping	.50" FNPT	.50" FNPT	
D = Tubing	.25" x .38"	.25" x .38"	Yes
E = Tubing	.38" x .50"	.38" x .50"	Yes
F = Tubing	.38" x .50"	.38" x .50"	Yes
G = Piping	.25" FNPT	.25" FNPT	Yes
J = Tubing	.19" x .31"	.25" x .38"	
K = Tubing	.50" x .75"	.50" x .75"	Yes
M = Piping	G 1/2 A	G 1/2 A	
N = Tubing	4 x 10 mm	4 x 10 mm	
P = Tubing	4 x 6 mm	4 x 6 mm	
Q = Tubing	10 x 14 mm	10 x 14 mm	
R = Piping	G 1/2 A	G 1/2 A	
S = Tubing	6 x 10 mm	6 x 10 mm	
T = Tubing	6 x 10 mm	6 x 10 mm	Degas
U = Tubing	6 x 10 mm	6 x 10 mm	
V = Tubing	12 x 19 mm	12 x 19 mm	
W = Tubing	10 x 16 mm	10 x 16 mm	
Y = Tubing	6 x 12 mm	6 x 12 mm	

Suction/Discharge Valve Selection Guide

L3

VALVE TYPE: 101 = Suction Valve
201 = Discharge Valve

SEATS: H = Hypalon
V = Viton
T = TFE

BALLS: T = TFE
C = Ceramic
S = 316 Stainless Steel
H = Alloy C (Hastelloy)

CONNECTION TYPE:

- 1 = Double Balls when TFE seats selected
- 2 = Double Balls when TFE seats selected
- 3 = Double Balls when TFE seats selected
- 4 = Double Balls when TFE seats selected
- 5 = Available for Discharge Only (L3101)
- 6 =
- 7 = Available for Suction Only (L3201)
- 8 =
- A =
- B =
- C =
- D = Spring Loaded with SS Balls
- E = Spring Loaded with SS Balls
- F = Spring Loaded with SS Balls
- G = Spring Loaded with SS Balls
- J =
- K =
- M =
- N =
- P =
- Q =
- R =
- S =
- U =
- V =
- W =
- Y =

MATERIALS OF CONSTRUCTION: FPP = Glass Filled Polypropylene
PVC = Poly Vinyl Chloride
PVD = Kynar
316 = 316 Stainless Steel

DRIVE END COMPONENTS

Item No.	Part No.	Description	
55	L2000200-080	SHAFT, ADJ FEMALE .080	SG #1
56	L2000300-PBT	SHAFT, ADJ MALE	G #2,3
56	L2000400-PBT	SHAFT, ADJ MALE	SG #1
59	L1500100-EPB	O-RING, HSG #1/CONT PNL	
59	L1500300-NTR	O-RING, HSG #2/CONT PNL	
59	L1500500-NTR	O-RING, HSG #3/CONT PNL	
61	L9900600-000	CONNECTOR, LIQUID TIGHT	
61	L9900700-000	CONNECTOR, STRAIN RELIEF	
62	L9700300-000	CORD, POWER, SERIES C, E	125V
62	L9700400-000	CORD, POWER, SERIES C, E	230V
62	L9701200-000	CORD, POWER, SERIES E PLUS	125V
62	L9701300-000	CORD, POWER, SERIES E PLUS	230V
63	L9700700-250	CIRCUIT BREAKER, SERIES MP	
63	L9707300-000	FUSE 2 AMP, SERIES E, E PLUS	
63	L9706900-000	BOARD MNT'D FUSE, SERIES A+, C+, C, E	
64	L9800200-188	CNTRL PNL SCREW	
65	L1500800-NTR	GROMMET, STROKE LENGTH	
66	L1900800-000	KNOB, STROKE RATE/SWITCH	
70	L9700500-000	LOCKING TAB	
71	L1900100-FPP	KNOB, STROKE LENGTH	
71	L1900300-FPP	KNOB, STROKE LENGTH	
72	L9800200-188	KNOB MOUNTING SCREW	
76	L1500900-NTR	GROMMET STROKE LENGTH	
81	L5000801-115	CNTRL PANEL ASSY, A-B-D-E SIZE SLDS, 115V	
81	L5000801-230	CNTRL PANEL ASSY, A-B-D-E SIZE SLDS, 230V	
81	L5000901-115	CNTRL PANEL ASSY, EXT/STOP, A-B-D-E SIZE SLDS, 115V	
81	L5000901-230	CNTRL PANEL ASSY, EXT/STOP, A-B-D-E SIZE SLDS, 230V	
81	L5001001-115	CNTRL PANEL ASSY, 4-20MA/STOP, A-B-D-E SIZE SLDS, 115V	
81	L5001001-230	CNTRL PANEL ASSY, 4-20MA/STOP, A-B-D-E SIZE SLDS, 230V	
81	L5000301-230	CNTRL PANEL ASSY, F-G SIZE SLDS, 230V	
81	L5001301-115	CNTRL PANEL ASSY, H SIZE SLD	115V
81	L5001301-230	CNTRL PANEL ASSY, H SIZE SLD	230V
81	L5028500-115	CNTRL PANEL ASSY, LEH8	115V
81	L5028500-230	CNTRL PANEL ASSY, LEH8	230V
81	L5028201-115	CNTRL PANEL ASSY, LVH7, LP/LVH8	115V
81	L5028200-230	CNTRL PANEL ASSY, LVH7, LP/LVH8	230V
81	L5001401-115	CNTRL PANEL ASSY, EXT/STOP, H SIZE SLD, 115V	
81	L5001401-230	CNTRL PANEL ASSY, EXT/STOP, H SIZE SLD, 230V	
81	L5028301-115	CNTRL PANEL ASSY, EXT/STOP, LVH7, LP/LVH8	115V
81	L5028300-230	CNTRL PANEL ASSY, EXT/STOP, LVH7, LP/LVH8	230V
81	L5001501-115	CNTRL PANEL ASSY, 4-20MA/STOP, H SIZE SLD, 115V	
81	L5001501-230	CNTRL PANEL ASSY, 4-20MA/STOP, H SIZE SLD, 230V	
81	L5028401-115	CNTRL PANEL ASSY, 4-20MA/STOP, LVH7, LP/LVH8	115V
81	L5028401-230	CNTRL PANEL ASSY, 4-20MA/STOP, LVH7, LP/LVH8	230V
81	L5000100-012	CNTRL PANEL ASSY, E-DC SIZE 01, 13, 14	
81	L5000200-012	CNTRL PANEL ASSY, E-DC SIZE 44	
81	L5000100-115	CNTRL PANEL ASSY, SERIES E 0-1/SIZE SLD	115V
81	L5000100-230	CNTRL PANEL ASSY, SERIES E 0-1/SIZE SLD	230V
81	L5000200-115	CNTRL PANEL ASSY, 3-4 SIZE SLDS	115V
81	L5000200-230	CNTRL PANEL ASSY, 3-4 ZISE SLDS	230V
81	L5002900-115	CNTRL PANEL ASSY SIN-FUNC 0-SIZE SLD, 115V SERIES C	
81	L5002900-230	CNTRL PANEL ASSY SIN-FUNC 0-SIZE SLD, 230V SERIES C	
81	L5003000-115	CNTRL PANEL ASSY SIN-FUNC 5-SIZE SLD, 115V SERIES C	
81	L5003000-230	CNTRL PANEL ASSY SIN-FUNC 5-SIZE SLD, 230V SERIES C	
81	L5011000-115	CNTRL PANEL ASSY EXT PACE SIZE 54, SERIES C	115V
81	L5013000-115	CNTRL PANEL ASSY EXT PACE SIZE 54, SERIES C	115V
81	L5003014-115	CNTRL PANEL ASSY, EXT/STOP K5	115V
81	L5003015-115	CNTRL PANEL ASSY, 4-20MA/STOP K2	115V

DRIVE END COMPONENTS

Item No.	Part No.	Description	
81	L5003016-115	CNTRL PANEL ASSY, 4-20MA/STOP LPK5	115V
81	L5003701-115	CNTRL PANEL ASSY, STD K SIZE SLD	115V
81	L5003701-230	CNTRL PANEL ASSY, STD K SIZE SLD	230V
81	L5003801-115	CNTRL PANEL ASSY, EXT/STOP K SIZE SLD	115V
81	L5003801-230	CNTRL PANEL ASSY, EXT/STOP K SIZE SLD	230V
81	L5003903-115	CNTRL PANEL ASSY, 4-20MA/STOP K7	115V
81	L5003903-230	CNTRL PANEL ASSY, 4-20MA/STOP K7	230V
81	L5004100-115	CNTRL PANEL ASSY, SIN-FUNC SIZE 54, 115V SERIES C PLUS	
81	L5004100-230	CNTRL PANEL ASSY, SIN-FUNC SIZE 54, 230V SERIES C PLUS	
81	L5010800-230	CNTRL PANEL ASSY EXT PACE SIZE 02, 03, 04, C3, C4 SERIES A+/C+	230V
81	L5010900-230	CNTRL PANEL ASSY EXT PACE SIZE 54, 64 SERIES A+/C+	230V
81	L5005200-115	CNTRL PANEL ASSY, SIZE 02, 03, 04, C3, C4 SERIES A+/C+	115V
81	L5005300-230	CNTRL PANEL ASSY, SIZE 02, 03, 04, C3, C4 SERIES A+/C+	230V
81	L5004800-115	CNTRL PANEL ASSY, SIZE 54, 64 SERIES A+/C+	115V
81	L5004900-230	CNTRL PANEL ASSY, SIZE 54, 64 SERIES A+/C+	230V
81	L5007501-115	CNTRL PNL ASSY LMK2 SIGNAL RELAY	115V
81	L5007301-115	CNTRL PNL ASSY LM A,B,C,D,E,K3 SIGNAL RELAY	115V
81	L5007501-230	CNTRL PNL ASSY LMK2 SIGNAL RELAY	230V
81	L5007301-230	CNTRL PNL ASSY LM A,B,C,D,E,K3 SIGNAL RELAY	230V
81	L5007601-115	CNTRL PNL ASSY LMK2 POWER RELAY	115V
81	L5007401-115	CNTRL PNL ASSY LM A,B,C,D,E,K3 POWER RELAY	115V
81	L5007601-230	CNTRL PNL ASSY LMK2 POWER RELAY	230V
81	L5007401-230	CNTRL PNL ASSY LM A,B,C,D,E,K3 POWER RELAY	230V
81	L5007701-115	CNTRL PNL ASSY LMK5 SIGNAL RELAY	115V
81	L5007101-115	CNTRL PNL ASSY LM F, G SIGNAL RELAY	115V
81	L5007701-230	CNTRL PNL ASSY LMK5 SIGNAL RELAY	230V
81	L5007101-230	CNTRL PNL ASSY LM F, G SIGNAL RELAY	230V
81	L5007801-115	CNTRL PNL ASSY LMK5 POWER RELAY	115V
81	L5007201-115	CNTRL PNL ASSY LM F, G POWER RELAY	115V
81	L5007801-230	CNTRL PNL ASSY LMK5 POWER RELAY	230V
81	L5007201-230	CNTRL PNL ASSY LM F, G POWER RELAY	230V
81	L5007901-115	CNTRL PNL ASSY LMK7 SIGNAL RELAY	115V
81	L5006901-115	CNTRL PNL ASSY LM H SIGNAL RELAY	115V
81	L5007901-230	CNTRL PNL ASSY LMK7 SIGNAL RELAY	230V
81	L5006901-230	CNTRL PNL ASSY LM H SIGNAL RELAY	230V
81	L5008001-115	CNTRL PNL ASSY LMK7 POWER RELAY	115V
81	L5007001-115	CNTRL PNL ASSY H POWER RELAY	115V
81	L5008001-230	CNTRL PNL ASSY LMK7 POWER RELAY	230V
81	L5007001-230	CNTRL PNL ASSY H POWER RELAY	230V
88	L9804000-000	GROUND LUG NUT	
89	L9800500-STL	GROUND LUG BOLT	
92	L9700800-000	BREAKER COVER	
	L9700200-000	CORD, SIGNAL, 10 FT	
	L9700201-000	CORD, SIGNAL, 20 FT	
	L9700800-000	PROTECTIVE BOOT, CKT BRKER	

BLEED VALVE ASSEMBLIES

Item No.	Part No.	Description	OD
11	L3300H01-FPP	FPP/HYP	3/8"
11	L3300H01-PVC	PVC/HYP	3/8"
11	L3300H03-FPP	FPP/HYP	1/2"
11	L3300H03-PVC	PVC/HYP	1/2"
11	L3300T01-FPP	FPP/TFE	3/8"
11	L3300T01-PVC	PVC/TFE	3/8"
11	L3300T01-PVD	PVD/TFE	3/8"
11	L3300T03-FPP	FPP/TFE	1/2"
11	L3300T03-PVC	PVC/TFE	1/2"
11	L3300T03-PVD	PVD/TFE	1/2"
11	L3300V01-FPP	FPP/VTN	3/8"
11	L3300V01-PVC	PVC/VTN	3/8"
11	L3300V01-PVD	PVD/VTN	3/8"
11	L3300V03-FPP	FPP/VTN	1/2"
11	L3300V03-PVC	PVC/VTN	1/2"
11	L3300V03-PVD	PVD/VTN	1/2"

FOOT VALVE / STRAINER ASSEMBLIES

Item No.	Part No.	Description	ID X OD
12	J40117	FPP/HYP/C	3/8" X 1/2"
12	J40203	FPP/HYP/316	3/8" X 1/2"
12	J40123	FPP/HYP/TFE	3/8" X 1/2"
12	J60509	FPP/VTN/C	3/8" X 1/2"
12	J40141	FPP/VTN/316	3/8" X 1/2"
12	J40125	FPP/VTN/TFE	3/8" X 1/2"
12	J40212	FPP/FTF/C	3/8" X 1/2"
12	J40175	FPP/FTF/316	3/8" X 1/2"
12	J40171	FPP/FTF/TFE	3/8" X 1/2"
12	J60728	PVD/FTF/C	3/8" X 1/2"
12	J60729	PVD/HYP/C	3/8" X 1/2"
12	J60730	PVD/VTN/C	3/8" X 1/2"
12	J40116	FPP/HYP/C	1/4" X 3/8"
12	J40156	FPP/HYP/316	1/4" X 3/8"
12	J40122	FPP/HYP/TFE	1/4" X 3/8"
12	J60524	FPP/VTN/C	1/4" X 3/8"
12	J40158	FPP/VTN/316	1/4" X 3/8"
12	J40124	FPP/VTN/TFE	1/4" X 3/8"
12	J40211	FPP/FTF/C	1/4" X 3/8"
12	J40170	FPP/FTF/316	1/4" X 3/8"
12	J40169	FPP/FTF/TFE	1/4" X 3/8"
12	J60716	PVD/FTF/C	1/4" X 3/8"
12	J60717	PVD/HYP/C	1/4" X 3/8"
12	J60718	PVD/VTN/C	1/4" X 3/8"
12	J40095	316	.25 NPT
12	J40195	FPP/HYP/C	.25 NPT
12	J40187	FPP/VTN/C	.25 NPT
12	J40179	FPP/FTF/C	.25 NPT
12	J60503	FPP	.50 NPT
12	J60561	FPP	1/2 X 3/4"
12	J60564	FPP/FTF/C	3/16 X 5/16"
12	J60712	PVD/FTF/C	3/16 X 5/16"

STAINLESS STEEL VALVE REPAIR KITS

Part No.	Description
L9904200-316	VALVE REPAIR KIT - ATS2
L9904600-316	VALVE REPAIR KIT - ATS4
L9904700-316	VALVE REPAIR KIT - ATS6
L9904800-316	VALVE REPAIR KIT - ATS8
L9904900-316	VALVE REPAIR KIT - ATSG

TUBING

Part No.	Description	FT
00007	SUCT, 3/8 OD, CLEAR PVC	FT
00008	DISCH, 1/2 OD, WHITE PE	FT
00009	DISCH, 1/2 OD, BLACK PE	FT
00010	DISCH, 3/8 OD, WHITE PE	FT
00011	DISCH, 3/8 OD, BLACK PE	FT
J00012	DISCH, 1/2 OD, HI PRES, WHITE	FT
00013	DISCH, 1/2 OD, HI PRES, BLACK	FT
J00022	DISCH, 3/8 OD, HI PRES, WHITE	FT
J00023	SUCT, 1/2 OD, CLEAR PVC	FT
J00024	DISCH, 3/8 OD, HI PRES, BLACK	FT
J00032	SUCT/DISCH, 3/4 OD, CLEAR PVC	FT
L9902900-000	PVDF TUBING, 3/8 OD	FT
L9903000-000	PVDF TUBING, 1/2 OD	FT
L9904300-PEB	SUCT, 5/16 OD, PE BLACK	FT
L9904300-PEW	SUCT, 5/16 OD, PE WHITE	FT
L9904300-PVC	SUCT, 5/16 OD, CLEAR PVC	FT
L9904300-PVD	SUCT, 5/16 OD, PVDF WHITE	FT
L9904500-PEW	DISCH, 1/2 X 5/8, PE WHITE	FT
19913200-BRD	PVC CLEAR BRAIDED, 3/4 OD	FT

INJECTION BACK PRESS VALVE ASSEMBLIES

Item No.	Part No.	Description	ID X OD
13	J41767	FPP/HYP/C	3/8" X 1/2"
13	J41863	FPP/HYP/316	3/8" X 1/2"
13	J41773	FPP/HYP/TFE	3/8" X 1/2"
13	41716	FPP/VTN/C	3/8" X 1/2"
13	J41882	FPP/VTN/316	3/8" X 1/2"
13	J41775	FPP/VTN/TFE	3/8" X 1/2"
13	J41872	FPP/FTF/C	3/8" X 1/2"
13	J41879	FPP/FTF/316	3/8" X 1/2"
13	J41875	FPP/FTF/TFE	3/8" X 1/2"
13	J41694	PVC/HYP/C	3/8" X 1/2"
13	41698	PVC/HYP/C 6"	3/8" X 1/2"
13	J41702	PP/VTN/C 6"	3/8" X 1/2"
13	J41865	PVC/HYP/316	3/8" X 1/2"
13	J41759	PVC/HYP/TFE	3/8" X 1/2"
13	J41714	PVC/VTN/C	3/8" X 1/2"
13	J41095	PVC/VTN/316	3/8" X 1/2"
13	J41761	PVC/VTN/TFE	3/8" X 1/2"
13	J41873	PVC/FTF/C	3/8" X 1/2"
13	J41881	PVC/FTF/316	3/8" X 1/2"
13	J41877	PVC/FTF/TFE	3/8" X 1/2"
13	J61073	PVD/FTF/TFE	3/8" X 1/2"
13	J61021	PVD/FTF/C	3/8" X 1/2"
13	J41766	FPP/HYP/C	1/4" X 3/8"
13	J41862	FPP/HYP/316	1/4" X 3/8"
13	J41772	FPP/HYP/TFE	1/4" X 3/8"
13	41715	FPP/VTN/C	1/4" X 3/8"
13	41701	FPP/VTN/C 6"	1/4" X 3/8"
13	J41866	FPP/VTN/316	1/4" X 3/8"
13	J41774	FPP/VTN/TFE	1/4" X 3/8"
13	J61098	FPP/FTF/C	1/4" X 3/8"
13	J41878	FPP/FTF/316	1/4" X 3/8"
13	J41874	FPP/FTF/TFE	1/4" X 3/8"
13	41693	PVC/HYP/C	1/4" X 3/8"
13	41705	PVC/HYP/C 6"	1/4" X 3/8"
13	J41864	PVC/HYP/316	1/4" X 3/8"
13	J41758	PVC/HYP/TFE	1/4" X 3/8"
13	41713	PVC/VTN/C	1/4" X 3/8"
13	J41867	PVC/VTN/316	1/4" X 3/8"
13	41760	PVC/VTN/TFE	1/4" X 3/8"
13	J41996	PVC/FTF/C	1/4" X 3/8"
13	J41880	PVC/FTF/316	1/4" X 3/8"
13	J41876	PVC/FTF/TFE	1/4" X 3/8"
13	J61020	PVD/FTF/C	1/4" X 3/8"
13	J61026	PVD/FTF/TFE	1/4" X 3/8"
13	J41911	FPP/HYP/C	.25 NPT
13	J41901	FPP/VTN/C	.25 NPT
13	J41944	FPP/FTF/C	.25 NPT
13	J41904	PVC/HYP/C	.25 NPT
13	J41858	PVC/VTN/C	.25 NPT
13	J41908	PVC/FTF/C	.25 NPT
13	J61015	PVD/FTF/C	.25 NPT
13	J61025	316/FTF/316	.25 NPT
13	J41969	PVC/HYP/C	1/2 X 3/4"
13	J61149-10P	FPP/FTF/C	1/2 X 3/4"
13	J61152-10P	FPP/HYP/C	1/2 X 3/4"
13	J61160-10P	FPP/FTF/C	.50 NPT
13	J61157-10P	PVC/FTF/C	.50 NPT
13	J61156-10P	PVC/TFE/S	.50 NPT

OTHER

Part No.	Description
26858	BULKHEAD FITTING - PP 1/2"
26859	BULKHEAD FITTING - PVC 1/2"
26860	BULKHEAD FITTING - PVC 3/8"
26867	BULKHEAD FITTING - PP 3/8"
L9905000-FPP	J CONVERSION KIT (FPP/TFE/C)
L9905000-PVC	J CONVERSION KIT (PVC/TFE/C)
L9905000-PVD	J CONVERSION KIT (PVD/TFE/C)
L9905100-FPP	J CONVERSION KIT (FPP/TFE/C)
L9905100-PVC	J CONVERSION KIT (PVC/TFE/C)
L9905100-PVD	J CONVERSION KIT (PVD/TFE/C)
L9906901-000	CONV. KIT (.75" VVC9) DEGAS HEAD
L9907001-000	CONV. KIT (1.00" VVC9) DEGAS HEAD
L9907101-000	CONV. KIT (1.25" VVC9) DEGAS HEAD

OMNI Mechanical Pump

OMNI mechanical metering pumps and controllers are the economical standard for a reliable chemical feed pump with virtually no maintenance. For high technology in a simple to understand package at an economical price, add an MPC (metering pump controller) to the OMNI pump to take advantage of complete system integration between metering pump and process. The OMNI offers the following user friendly benefits

- **Oil Free** - Greased for life, no oil to buy or change
- **Compact and Lightweight** - Saves space and easy handling
- **Controller Ready** - Add an MPC when automatic pump control is required
- **Simple Design** - Easy to install and operate
- **Highly Efficient** - Quiet and cool, standard fan cooled motor design
- **Guided Ball Check Valve Systems**, to reduce back flow and enhance outstanding priming characteristics.
- **Premium Standard Wetted Component Materials.**
- **Few Moving Parts** and **Wall Mountable.**
- **Liquid End Materials-** PVDF & 316 SS



MPC NO MOTOR OPTION	
Minimal MPC Motor Requirements:	
HP/KW	Defined on order (Pump Dependent)
Voltage	230V nominal
Base Freq	50 or 60Hz (by Mfgr's Motor design)
Type	TEFC
Phases	3 phase
Poles	4 poles, 1500 rpm (50 hz) or 1,800 rpm (60hz) synchronous speed
SF	>=1.05
Turn Down	Minimum 3:1 constant torque
Insulation	Class F or better
Inverter Duty	Not Required

Performance & Selection Table

MODEL		DC2A	DC2B	DC2C	DC3A	DC3B	DC3C	DC4A	DC4B	DC4C	DC4D	DC5A	DC5B	DC5C	DC5D	DC6C	DC6D
Capacity	GPH	7	14	24	15.9	30	56	21	40	65	82.8 ¹	33.1	66.8	108	138.0 ¹	212	266
60 hz & MPC	LPH	26.5	53	90.8	60.2	113.5	211.9	79.5	151.4	246	313.5 ¹	125.3	252.8	408.8	522.3 ¹	266	1008
Capacity	GPH	5.8	11.7	20	13.7	27	46.4	17.4	34.9	52	66.6	27.9	55.9	88	115	177	222
50 hz	LPH	22.1	44.1	75.7	51.8	102.3	175.6	66	132.1	196.8	252	105.6	211.5	333.1	435.3	670	840
Pressure	PSIG	150			75			150			90			45			
(max.)	BAR	10.3			5.1			10.3			6.2			3.1			
SPM @	1725	44	88	150	44	88	150	58	117	175	223 ¹	58	117	175	223 ¹	175	223 ¹
	1425	37	73	125	37	73	125	48	97	145	186	49	98	146	186	146	186
HP/kW Required		0.25 / 0.18						0.5 / 0.37									
Connection Size		1/4" (F)NPT		1/2" (F)NPT OR (F)BSPT						1" (F)NPT OR (F)BSPT				1 1/2" (F)NPT, ANSI 1 1/2" & DIN 40 FLANGE			

¹This selection uses a high stroking rate, use with caution.

Must have at least 25 psig discharge pressure and water-like viscosity.

OMNI DC2 thru DC6 Selection Guide

DC _ _

MODELS:	2A = PVDF - 7.0 GPH (27 LPH)@60hz & MPC or 5.8 GPH (22 LPH)@50hz
	2A = 316SS - 7.0 GPH (27 LPH)@60hz & MPC or 5.8 GPH (22 LPH)@50hz
	2B = PVDF - 14 GPH (53 LPH)@60hz & MPC or 12 GPH (44 LPH)@50hz
	2B = 316SS - 14 GPH (53 LPH)@60hz & MPC or 12 GPH (44 LPH)@50hz
	2C = PVDF - 24 GPH (91 LPH)@60hz & MPC or 20 GPH (76 LPH)@50hz
	2C = 316SS - 24 GPH (91 LPH)@60hz & MPC or 20 GPH (76 LPH)@50hz
	3B = PVDF - 30 GPH (114 LPH)@60hz & MPC or 27 GPH (102 LPH)@50hz
	3B = 316SS - 30 GPH (114 LPH)@60hz & MPC or 27 GPH (102 LPH)@50hz
	3C = PVDF - 56 GPH (212 LPH)@60hz & MPC or 46 GPH (176 LPH)@50hz
	3C = 316SS - 56 GPH (212 LPH)@60hz & MPC or 46 GPH (176 LPH)@50hz
	4B = PVDF - 40 GPH (151 LPH)@60hz & MPC or 35 GPH (132 LPH)@50hz
	4B = 316SS - 40 GPH (151 LPH)@60hz & MPC or 35 GPH (132 LPH)@50hz
	4C = PVDF - 65 GPH (246 LPH)@60hz & MPC or 52 GPH (197 LPH)@50hz
	4C = 316SS - 65 GPH (246 LPH)@60hz & MPC or 52 GPH (197 LPH)@50hz
	4D = PVDF - 83' GPH (314' LPH)@60hz & MPC or 67 GPH (252 LPH)@50hz
	4D = 316SS - 83' GPH (314' LPH)@60hz & MPC or 67 GPH (252 LPH)@50hz
	5C = PVC - 108 GPH (409 LPH)@60hz & MPC or 88 GPH (333 LPH)@50hz
	5C = PVDF - 108 GPH (409 LPH)@60hz & MPC or 88 GPH (333 LPH)@50hz
	5C = 316SS - 108 GPH (408.8 LPH)@60hz & MPC or 88 GPH (333 LPH)@50hz
	5D = PVC - 138' GPH (522' LPH)@60hz & MPC or 115 GPH (435 LPH)@50hz
	5D = PVDF - 138' GPH (522' LPH)@60hz & MPC or 115 GPH (435 LPH)@50hz
	5D = 316SS - 138' GPH (522' LPH)@60hz & MPC or 115 GPH (435 LPH)@50hz
	6C = PP - 212 GPH (804 LPH)@60hz & MPC or 177 GPH (670 LPH)@50hz
	6C = PVDF ² - 212 GPH (804 LPH)@60hz & MPC or 177 GPH (670 LPH)@50hz
	6C = 316SS - 212 GPH (804 LPH)@60hz & MPC or 177.0 GPH (670 LPH)@50hz
	6D = PP - 266' GPH (1008' LPH)@60hz & MPC or 222 GPH (840 LPH)@50hz
	6D = PVDF ² - 266' GPH (1008' LPH)@60hz & MPC or 222 GPH (840 LPH)@50hz
	6D = 316SS - 266' GPH (1008' LPH)@60hz & MPC or 222 GPH (840 LPH)@50hz

¹Caution: This pump has a high stroke rate & needs at least 25 psig back pressure and water-like viscosity.

²These pumps are subject to export restrictions

MOTOR:	1 = IEC 71 B14 Frame, 1PH 115/230V, 0.37kW (1/2HP), TEFC, Motor [50/60hz]*
	2 = 56C Frame, 1PH 115/230V, 0.37kW (1/2HP), TEFC, MOTOR (60hz)
	3 = IEC 71 B14 Frame, 3PH 220/380V (&460V), 0.37kW (1/2HP), TEFC, Motor [50/60hz]*
	4 = 56C Frame, 3PH 220/380V (&460V), 0.37kW (1/2HP), TEFC, MOTOR (60hz)
	5 = MPC with 56C frame motor - price included in MPC price
	6 = MPC NO MOTOR with 56C frame [Always @ 60 hz!] (price subtracted from MPC)
	7 = MPC with 71 frame motor - price included in MPC price
	8 = MPC NO MOTOR with 71 frame [Always @ 60 hz!] (price subtracted from MPC)
	X = NO MOTOR - 56C frame
	Y = NO MOTOR - IEC 71 B14 frame

* In the Americas, lead time is 8 weeks for any pump with these motors.

WET END MATERIALS:	P = PP Liquid End - PTFE Diaphragm and PTFE O-rings - Ceramic Ball Valves *
	F = PVDF Liquid End - PTFE Diaphragm and PTFE O-rings - Ceramic Ball Valve
	A = 316SS Liquid End - PTFE Diaphragm and PTFE O-rings - 316SS Ball Valves

* Model DC5 have PVC reagent heads with PP valves.

CONNECTION TYPE	P = NPT
	B = Din ISO 228/1 (BSPT) (Not available on DC2 pumps)

Optional MPC Controller

CONTROL:	BLANK = No MPC Controller
	M = MPC Controller

CONTROLLER INPUT VOLTAGE	BLANK = NO MPC CONTROLLER
	1 = 110-115V 50/60Hz ETL (UL & CSA) - Single Phase Only
	2 = 220-230V 50/60Hz CE & ETL (UL & CSA) - Single Phase Only

Contact factory for additional motor options. MPC output is 60Hz even if the input voltage is 50Hz - Select pump based on 60Hz

EXTENDED REMOTE CABLE:	BLANK = NO MPC CONTROLLER
	X = PUMP MOUNTED KEYPAD with standard 1.5m (4.5 feet) of cable
	C = EXTENDED REMOTE CABLE, KEYPAD MOUNTED OFF THE PUMP *

NOTE: * The MPC remote can be located up to 1000 feet (305m) away from the pump. Order extra cable by adding the line item part number NP530147-000 per foot to the order. The price is USD\$1.50 list/foot and will be shipped loose as a line item for field installation. Example: If 62 ft of cable is needed, order 62 pieces of NP530147-000. MPC - PANEL MOUNT: The MPC remote is already a NEMA 4X (IP56) rated enclosure. Instead of integrating this into a control panel, we suggest mounting the remote ""as is"" on the outside of a panel or next to a panel on the wall. The bracket for wall or panel mounting is the same bracket that comes as standard on the pump. There is no chassis mount available.

LANGUAGE (MPC will be shipped in language chosen)	BLANK = NO MPC CONTROLLER
	E = English
	F = French
	S = Spanish
	G = German

OMNI Mechanical Pump

OMNI DC7 Series Selection Guide		DC7_	-	-	-
MODELS	7C = PP - 380 GPH (1440 LPH)@60hz & MPC or 317 GPH (1220 LPH)@50hz 7C = PVDF ² - 380 GPH (1440 LPH)@60hz & MPC or 317 GPH (1220 LPH)@50hz 7D = PP - 476 ¹ GPH (1800 ¹ LPH)@60hz & MPC or 396 GPH (1500 LPH)@50hz 7D = PVDF ² - 476 ¹ GPH (1800 ¹ LPH)@60hz & MPC or 396 GPH (1500 LPH)@50hz Duplex Models 7J = PP - 761 GPH (2800 LPH)@60hz & MPC or 634 GPH (2400 LPH)@50hz 7J = PVDF ² - 761 GPH (2800 LPH)@60hz & MPC or 634 GPH (2400 LPH)@50hz 7K = PP - 951 ¹ GPH (3600 ¹ LPH)@60hz & MPC or 793 GPH (3000 LPH)@50hz 7K = PVDF ² - 951 ¹ GPH (3600 ¹ LPH)@60hz & MPC or 793 GPH (3000 LPH)@50hz				
Caution: This pump has a high stroke rate & needs at least 25 psig back pressure and water-like viscosity.					
²These pumps are subject to export restrictions.					
MOTORS	1 = 90 IEC FRAME 2 = 100 IEC FRAME 3 = 56C FRAME 4 = 145TC FRAME				
WET END MATERIALS:	P = PP Liquid End - PTFE Diaphragm and PTFE O-rings - Ceramic Ball Valves F = PVDF Liquid End - PTFE Diaphragm and PTFE O-rings - Ceramic Ball Valve				
	X = No Motor Purchased (Pump will come with Main Assy and Motor Frame Kit) M = Motor Purchased (as line item) (Pump will come completely assembled)				

OMNI DC7 Series Selection Guide		EP	C	B	-
MODELS	EP = MPC VECTOR				
ENCLOSURE	C = NEMA 4X (IP56)				
RATINGS	B = 2 HP (1.5kW) 208-240 VAC, 1 Phase, 50/60 Hz				
LANGUAGE	X = English A = German B = French C = Spanish				
A completed model number should look like "EPCBX"					

Motor Selection							
Part Number	Power (hp / kW)	Volts	Phase	Hz	RPM	Frame	Enclosure
MD496	1.5 / 1.1	208-230 / 460	3	60	1725	NEMA 56C	TEFC
W773127-001 **	2 / 1.5 (DC7 Duplex)			60		NEMA 145TC	
NP500622-000	1.5 / 1.1			60		NEMA 56C	
NP500619-000	1.5 / 1.1	220 / 380	3	50/60	1425 / 1725	IEC 90	TEFC
NP500624-000 **	2 / 1.5 (DC7 Duplex)			0			
NP500621-000	1.5 / 1.1			940 / 1140			

** Compatible with MPC Vector motor requirements

Performance & Selection Table

MODEL	DC7C	DC7D	DC7J	DC7K
Capacity GPH	380	476	761	951
60 hz & MPC LPH	1440	1800	2880	3600
Capacity GPH	317	396	634	2400
50 hz LPH	1200	1500	2400	3000
Pressure PSIG	60			
(max.) BAR	4.1			
SPM @ 1725	175	223	175	223
1425	146	186	146	186
HP/kW Required	1.5 / 1.1		2 / 1.5	
Connection Size				

OMNI Mechanical Pump

Common Pump Accessories - Omni & Others

Component	Size	Material	Part No.
Pressure Relief Valves	1/2"	PVC/TFE	NA100001-PVC
	1/2"	PVDF/TFE	NA100001-PVD
	1/2"	SS/TFE	NA100001-316
	1"	PVC/TFE	NA100002-PVC
	1"	KYN/TFE	NA100002-PVD
	1"	SS/TFE	NA100002-316
	1.5"	PVC/TFE	NA100003-PVC
	1.5"	KYN/TFE	NA100003-PVD
Back Pressure Valves	1/2"	PVC/TFE	NA200001-PVC
	1/2"	PVDF/TFE	NA200001-PVD
	1/2"	SS/TFE	NA200001-316
	1"	PVC/TFE	NA200002-PVC
	1"	KYN/TFE	NA200002-PVD
	1"	SS/TFE	NA200002-316
	1.5"	PVC/TFE	NA200003-PVC
Pulsation Dampener	3/8"	PVC/TFE 4 CU IN	NA600001-PVC
	3/8"	PVC/TFE 10 CU IN	NA600001-PVD
	3/4"	PVC/TFE 36 CU IN	NA600001-316
	3/8"	PVD/TFE 4 CU IN	NA600002-PVC
	3/8"	PVD/TFE 10 CU IN	NA600002-PVD
	3/4"	PVD/TFE 36 CU IN	NA600002-316
	3/8"	SS/TFE 4 CU IN	NA600003-PVC
	3/8"	SS/TFE 10 CU IN	NA600003-PVD
	3/4"	SS/TFE 36 CU IN	NA600003-316
Gauge Isolator w/ 200PSI Gauge	1/4"	CPVC/TFE	NA500001-CPVC
	1/4"	PVDF/TFE	NA500001-PVD
	1/4"	316SS/TFE	NA500001-316
Calibration Column	1/2"	PVC 100mL	NA300001-PVC
	1/2"	PVC 200mL	NA300002-PVC
	3/4"	PVC 500mL	NA300003-PVC
	3/4"	PVC 1000mL	NA300004-PVC
	1"	PVC 2000mL	NA300005-PVC
	1"	PVC 4000mL	NA300006-PVC
	2"	PVC 10,000mL	NA300007-PVC
	2"	PVC 20,000mL	NA300008-PVC
	1/2"	Glass/PVD 100mL	NA300009-PVD
	1/2"	Glass/PVD 200mL	NA300010-PVD
	3/4"	Glass/PVD 500mL	NA300011-PVD
	3/4"	Glass/PVD 1000mL	NA300012-PVD
	1"	Glass/PVD 2000mL	NA300013-PVD
	1"	Glass/PVD 4000mL	NA300014-PVD
	1/2"	Glass/SS 100mL	NA300015-316
	1/2"	Glass/SS 200mL	NA300016-316
	3/4"	Glass/SS 500mL	NA300017-316
	3/4"	Glass/SS 1000mL	NA300018-316
1"	Glass/SS 2000mL	NA300019-316	
1"	Glass/SS 4000mL	NA300020-316	
Y Strainer	1/2"	PVC	NA400001-PVC
	1/2"	CPVC	NA400001-CPVC
	1/2"	PVD	NA400001-PVD
	1"	PVC	NA400002-PVC
	1"	CPVC	NA400002-CPVC
	1"	PVD	NA400002-PVD

OMNI KOPkit Selection Guide

KOPkit Number	Pump Model	Wetted Material	Connection Type
NLK020FP	DC2	PVDF	NPT
NLK040FP	DC3 or DC4	PVDF	NPT
NLK040FB	DC3 or DC4	PVDF	BSPT
NLK050FP	DC5	PVDF	NPT
NLK050FB	DC5	PVDF	BSPT
NLK060FP	DC6	PVDF	NPT
NLK060FB	DC6	PVDF	BSPT
NLK070FX	DC7	PVDF	N/A
NLK050PP	DC5	PP	NPT
NLK050PB	DC5	PP	BSPT
NLK060PP	DC6	PP	NPT
NLK060PB	DC6	PP	BSPT
NLK070PX	DC7	PP	N/A
NLK020AP	DC2	316SS	NPT
NLK040AP	DC3 or DC4	316SS	NPT
NLK040AB	DC3 or DC4	316SS	BSPT
NLK050AP	DC5	316SS	NPT
NLK050AB	DC5	316SS	BSPT
NLK060AP	DC6	316SS	NPT
NLK060AB	DC6	316SS	BSPT

CHEM-TECH Series CTP Peristaltic

Series CTP Peristaltic Pump Selection Guide

		CTP	---	---	---	PAP1	XXXXX
MODELS:	<p>Series CTP-A Simplex - Percentage Timer</p> <p>A2H = 3.5 gpd (0.55 lph) max pres.: 125 PSI (8.6 BAR)</p> <p>A2L = 3.5 gpd (0.55 lph) max pres.: 80 PSI (5.5 BAR)</p> <p>A3H = 8.0 gpd (1.26 lph) max pres.: 110 PSI (7.6 BAR)</p> <p>A3L = 8.0 gpd (1.26 lph) max pres.: 70 PSI (4.8 BAR)</p> <p>A4H = 13.0 gpd (2.05 lph) max pres.: 100PSI (6.9 BAR)</p> <p>A4L = 13.0 gpd (2.05 lph) max pres.: 50 PSI (3.4 BAR)</p> <p>A6L = 30.0 gpd (4.73 lph) max pres.: 40 PSI (2.8 BAR)</p> <p>A6H = 30.0 gpd (4.73 lph) max pres.: 80 PSI (5.5 BAR)</p> <p>Series CTP-A Duplex *</p> <p>B2L = 7.0 gpd (1.10 lph) max pres.: 80 PSI (5.5 BAR)</p> <p>B3L = 16.0 gpd (2.52 lph) max pres.: 70 PSI (4.8 BAR)</p> <p>B4L = 26.0 gpd (4.10 lph) max pres.: 50 PSI (3.4 BAR)</p> <p>B6L = 60.0 gpd (9.46 lph) max pres.: 40 PSI (2.8 BAR)</p> <p>Series CTP-AE Simplex - 100% Fixed Rate</p> <p>A2H = 3.5 gpd (0.55 lph) max pres.: 125 PSI (8.6 BAR)</p> <p>A2L = 3.5 gpd (0.55 lph) max pres.: 80 PSI (5.5 BAR)</p> <p>A3H = 8.0 gpd (1.26 lph) max pres.: 110 PSI (7.6 BAR)</p> <p>A3L = 8.0 gpd (1.26 lph) max pres.: 70 PSI (4.8 BAR)</p> <p>A4H = 13.0 gpd (2.05 lph) max pres.: 100PSI (6.9 BAR)</p> <p>A4L = 13.0 gpd (2.05 lph) max pres.: 50 PSI (3.4 BAR)</p> <p>A6L = 30.0 gpd (4.73 lph) max pres.: 40 PSI (2.8 BAR)</p> <p>A6H = 30.0 gpd (4.73 lph) max pres.: 80 PSI (5.5 BAR)</p> <p>Series CTP-AE Duplex *</p> <p>B2L = 7.0 gpd (1.10 lph) max pres.: 80 PSI (5.5 BAR)</p> <p>B3L = 16.0 gpd (2.52 lph) max pres.: 70 PSI (4.8 BAR)</p> <p>B4L = 26.0 gpd (4.10 lph) max pres.: 50 PSI (3.4 BAR)</p> <p>B6L = 60.0 gpd (9.46 lph) max pres.: 40 PSI (2.8 BAR)</p> <p>Series CTP-D Simplex - Variable Speed</p> <p>D2H = 7.0 gpd (1.10 lph) max pres.: 125 PSI (8.6 BAR)</p> <p>D3H = 16.0 gpd (2.52 lph) max pres.: 110 PSI (7.6 BAR)</p> <p>D4H = 26.0 gpd (4.10 lph) max pres.: 100 PSI (6.9 BAR)</p> <p>D6H = 60.0 gpd (9.46 lph) max pres.: 80 PSI (5.5 BAR)</p> <p>Series CTP-D Duplex *</p> <p>E2H = 14.0 gpd (2.20 lph) max pres.: 125 PSI (8.6 BAR)</p> <p>E3H = 32.0 gpd (5.04 lph) max pres.: 110 PSI (7.6 BAR)</p> <p>E4H = 52.0 gpd (8.20 lph) max pres.: 100 PSI (6.9 BAR)</p> <p>E6H = 120.0 gpd (18.92 lph) max pres.: 80 PSI (5.5 BAR)</p>						
CONTROLS:	<p>S = Standard for CTP-A / CTP-D</p> <p>E = Standard for CTP-AE</p> <p>T = 7 Day Mechanical Timer (2 hr. increments) with Series CTP-A</p> <p>R = 7 Day Mechanical Timer (2 hr. increments) with Series CTP-AE</p> <p>D = 7 Day - 8 Event Electronic Timer (1 min. increments) with Series CTP-A / CTP-D</p> <p>C = 7 Day - 8 Event Electronic Timer (1 min. increments) with Series CTP-AE</p>						
ELECTRICAL:	<p>A = 115 Volt, 60 Hz with grounded U.S. plug (Standard)</p> <p>1 = 115 Volt, 60 Hz (for CTP-D only)</p> <p>B = 230 Volt, 60 Hz with grounded U.S. plug</p> <p>R = 230 Volt, 50 Hz with grounded European right angle plug</p> <p>S = 230 Volt, 50 Hz with grounded European straight plug</p> <p>T = 230 Volt, 50 Hz with Swiss plug</p> <p>U = 230 Volt, 50 Hz with Australian Plug</p> <p>3 = 230 Volt, 50 Hz with European power cord and no plug</p>						
NOTE: 230 volt 50 Hz is rated at 5/6 of the stated flow rate.							
LIQUID END MATERIALS:	PAP1 = PVC Head and Fittings/ Norprene Tubing						
SUFFIX CODES:	XXXXX = No Options Available						
A completed model should look like "CTPD2HS1-PAP1-XXX"							

Notes: * Standard duplex models are of like pressure and flow rate.

PARTS

<u>Part Number</u>	<u>Description</u>
KOPkits	
NCKA2HPAP1	KOPkit CTP A2HPAP1
NCKA2LPAP1	KOPkit CTP A2LPAP1
NCKA2FPAP1	KOPkit CTP A2FPAP1
NCKA3HPAP1	KOPkit CTP A3HPAP1
NCKA3LPAP1	KOPkit CTP A3LPAP1
NCKA3FPAP1	KOPkit CTP A3FPAP1
NCKA4HPAP1	KOPkit CTP A4HPAP1
NCKA4LPAP1	KOPkit CTP A4LPAP1
NCKA4FPAP1	KOPkit CTP A4FPAP1
NCKA6HPAP1	KOPkit CTP A6HPAP1
NCKA6LPAP1	KOPkit CTP A6LPAP1

TUBE KITS

NC90XX2HPA-XXXXX	Kit, Tube Assy	2HPA
NC90XX2LPA-XXXXX	Kit, Tube Assy	2LPA
NC90XX3HPA-XXXXX	Kit, Tube Assy	3HPA
NC90XX3LPA-XXXXX	Kit, Tube Assy	3LPA
NC90XX4HPA-XXXXX	Kit, Tube Assy	4HPA
NC90XX4LPA-XXXXX	Kit, Tube Assy	4LPA
NC90XX4FPA-XXXXX	Kit, Tube Assy	4FP1
NC90XX6HPA-XXXXX	Kit, Tube Assy	6HPA
NC90XX6LPA-XXXXX	Kit, Tube Assy	6LPA

ACCESSORIES ASSEMBLY

NC84XXXXPA-XXXXX	Access. Kit, PVC/VTN, .25N
------------------	----------------------------

ROTOR ASSEMBLY

NC82XX2HP1-XXXXX	Rotor Assy, .785, PRC, O/S
NC82XX3HP1-XXXXX	Rotor Assy, .785, PRC, O/S
NC82XX4HP1-XXXXX	Rotor Assy, .785, PRC, O/S
NC82XX6HP1-XXXXX	Rotor Assy, .785, PRC, O/S
NC82XX2LP1-XXXXX	Rotor Assy, .785, PRC, O/S
NC82XX3LP1-XXXXX	Rotor Assy, .785, PRC, O/S
NC82XX4LP1-XXXXX	Rotor Assy, .785, PRC, O/S
NC82XX6LP1-XXXXX	Rotor Assy, .785, PRC, O/S
NC82XX2FP1-XXXXX	Rotor Assy, .785, PRC, O/S
NC82XX3FP1-XXXXX	Rotor Assy, .785, PRC, O/S
NC82XX4FP1-XXXXX	Rotor Assy, .785, PRC, O/S

HEAD / ROTOR KITS

NC91XA2HP1-XXXXX	Kit, Head / Rotor Assy	A2HP1
NC91XA2LP1-XXXXX	Kit, Head / Rotor Assy	A2LP1

<u>Part Number</u>	<u>Description</u>	
HEAD / ROTOR KITS		
NC91XA2FP1-XXXXX	Kit, Head / Rotor Assy	A2FP1
NC91XA3HP1-XXXXX	Kit, Head / Rotor Assy	A3HP1
NC91XA3LP1-XXXXX	Kit, Head / Rotor Assy	A3LP1
NC91XA3FP1-XXXXX	Kit, Head / Rotor Assy	A3FP1
NC91XA4HP1-XXXXX	Kit, Head / Rotor Assy	A4HP1
NC91XA4LP1-XXXXX	Kit, Head / Rotor Assy	A4LP1
NC91XA6HP1-XXXXX	Kit, Head / Rotor Assy	A6HP1
NC91XA6LP1-XXXXX	Kit, Head / Rotor Assy	A6LP1

PARTS

* NC010003-115	Motor, Gear Assy, 115/50-60HZ
* NC010003-230	Motor, Gear Assy, 230/50-60HZ
NC010004-000	Motor, Gear Assy, CTP-D
NC050002-000	Cover, Pump Housing
NC050005-000	Housing Assy, CTP Std
NC050005-002	Hsing Assy, 100% Fixed Rate
NC050005-003	Hsing Assy, 100% Fixed Timer
NC070006-230	Circuit Board AC 230V
NC110001-PVC	Injection Valve Body, .25 NPT
NC110002-PVC	Coupling Nut, .25 NPT
NC110016-000	Sleeve, .25 OD Tube
NC110018-PVC	Inj. Valve Body Assy, .25 NPT
NC110020-PVC	Fit, 1/4" NPT, Close Nip Special
NC150003-NTR	Grommet, Motor Shaft
NC150005-000	Seal, Toggle Switch
NC170003-000	Label, AC Panel
NC170004-000	Label, Earth Ground
NC170005-000	Label, AC Panel On/Off
NC190000-000	Knob, #10 Thumb Screw
NC960002-000	Switch, Toggle On/Off
NC960003-000	Locking Ring, Toggle Switch
NC960004-000	Timer, 7-Day/24-Hr, 220V/50Hz
NC970027-000	Fuse, 3.15 Amp
J60552	Strainer Assembly w/o Valve
J61554	Kit, Flapper Valve with Inj.
D2568	Valve Flapper

* Motors listed are for simplex pumps manufactured after April, 2004. For duplex pumps or pumps manufactured before April, 2004 please contact factory

CHEM-TECH Prime Performance

The Chem-Tech Prime Performance pump is available in 15, 24 and 30 GPD at 100 PSI. Selecting the proper pump is easy! Just refer to selection charts one through four to select the proper output, voltage, liquid end materials, etc Fill in the model number with the correct codes as you go, taking note of the base and adder prices

PRIME PERFORMANCE Selection Guide		X	X	A		
MODELS:	015 = 15 gpd (2.34 lph) max pres.: 100 PSI (7 BAR) 024 = 24 gpd (3.78 lph) max pres.: 100 PSI (7 BAR) 030 = 30 gpd (4.72 lph) max pres.: 100 PSI (7 BAR) 068 = 68 gpd (10.72 lph) max pres.: 60 PSI (4.2 BAR) 100 = 100 gpd (15.75 lph) max pres.: 60 PSI (4.2 BAR)					
ELECTRICAL:	A = 115V, 60 Hz B = 230V, 50 Hz (not available in 2120) C = 230V, 60 Hz					
LIQUID END MATERIALS: Head, Fittings/ Diaph., Seats/ Balls	BAA = PVC / Hypalon / Ceramic BBA = PVC / Viton / Ceramic					
CONNECTION SIZES:	6 = Tubing .38" PE BLK Suction / .38" PE BLK Discharge / .38" PE BLK Return 8 = Tubing .38" PVC Suction / .38" PE Discharge / .38" PVC Return 7 = Tubing .50" PE BLK Suction / .50" PE BLK Discharge / .50" PE BLK Return 9 = Tubing .50" PVC Suction / .50" PE Discharge / .50" PVC Return					
SUFFIX CODES:	XXX = Standard 001 = Current Interrupter 15T = 15 gal tank w/ bulkhead for vent, level wand, safety cap & fasteners 35T = 35 gal tank w/ bulkhead for vent and fasteners					
A complete model should look like "X024-XA-BBA9XXX"						

Pumps come with foot valve/strainer/weight, 4' of suction tubing, 4' of return tubing, 8' of discharge tubing, and injection/back pressure valve assembly.

KOPkits

PRIME PERFORMANCE KOPkit Selection Guide		KX100	A	
PRODUCT DESIGNATOR:	KX100 = Chem-Tech Kopkit			
LIQUID END MATERIALS: Head, Diaph., Seats & Balls	BAA = PVC / Hypalon / Ceramic BBA = PVC / Viton / Ceramic			
CONNECTION :	6 = Tubing .38" Suction / Discharge / Return 8 = Tubing .38" Suction / Discharge / Return 7 = Tubing .50" Suction / Discharge / Return 9 = Tubing .50" Suction / Discharge / Return			

CHEM-TECH Series 100,150,100D, 150D, 200

Selecting the proper Chem-Tech pump is easy! Just refer to selection charts one through five to select the proper output, voltage, liquid end materials, etc. Fill in the model number with the correct codes as you go, taking note of the base and adder prices.

Note: Standard Features do not add to the pump price.

Chem-Tech Series 100, 150, 100D, 150D, 200 Selection G	
MODELS:	Series 100 X003 = 3 gpd (0.47 lph) max pres.: 100 PSI (7 BAR) X007 = 7 gpd (1.00 lph) max pres.: 100 PSI (7 BAR) X015 = 15 gpd (2.34 lph) max pres.: 100 PSI (7 BAR) X024 = 24 gpd (3.78 lph) max pres.: 100 PSI (7 BAR) X030 = 30 gpd (4.72 lph) max pres.: 100 PSI (7 BAR) Series 150 X068 = 68 gpd (10.71 lph) max pres.: 60 PSI (4 BAR) X100 = 100 gpd (15.76 lph) max pres.: 60 PSI (4 BAR) Series 200 X210 = 10 gpd (1.5 lph) max pres.: 150 PSI (10 BAR) X215 = 15 gpd (2.34 lph) max pres.: 150 PSI (10 BAR) X220 = 20 gpd (3.15 lph) max pres.: 150 PSI (10 BAR) X230 = 30 gpd (4.72 lph) max pres.: 125 PSI (9 BAR) X240 = 40 gpd (6.31 lph) max pres.: 125 PSI (9 BAR) X260 = 60 gpd (9.46 lph) max pres.: 125 PSI (9 BAR) X280 = 80 gpd (12.6 lph) max pres.: 100 PSI (7 BAR) 2100 = 100 gpd (15.76 lph) max pres.: 100 PSI (7 BAR) 2120 = 120 gpd (18.91 lph) max pres.: 80 PSI (6 BAR)
ELECTRICAL:	XA = 115V, 60 Hz XB = 230V, 50 Hz (not available in 2120) XC = 230V, 60 Hz XD = 115V, 50/60 Hz, T.E.F.C. (X200 only) XL = 230V, 50/60 Hz, T.E.F.C. (X200 only)
LIQUID END MATERIALS: Pump Head & Fittings/Seats & O-rings/Balls	AAA = SAN/PVC / Hypalon / Ceramic AAB = SAN/PVC / Hypalon / TFE ABA = SAN/PVC / Viton / Ceramic ABB = SAN/PVC / Viton / TFE ACA = SAN/PVC / Tef/Viton / Ceramic AHA = SAN/PVC / Tef/Hypalon / Ceramic BAA = PVC / Hypalon / Ceramic BAB = PVC / Hypalon / TFE BBA = PVC / Viton / Ceramic BBB = PVC / Viton / TFE BHA = PVC / Tef/Hyp / Ceramic DAA = PP / Hypalon / Ceramic DAB = PP / Hypalon / TFE DBA = PP / Viton / Ceramic DBB = PP / Viton / TFE GFA = PVC / TFE / Ceramic (dbl) GFB = PVC / TFE / TFE (dbl) EFC = 316 / TFE / 316 (dbl)
CONNECTION SIZES:	A = Tubing .44" PVC Suction / .50" PE Discharge C = Tubing .38" PVC Suction / .38" PE Discharge F = Tubing .44" PVC Suction / .50" PE BLK Discharge S = Tubing .38" PVC Suction / .38" PE BLK Discharge X w/ 316 = .25" FNPT Suction / .25" FNPT Discharge
SUFFIX CODES:	XXX = Standard 001 = Current Interrupter 500* = Five Function Valve 520* = Five Function Degas Valve ITS = 15 gal ITS Tank System
* Not available in SS. Adder price is per head.	
A completed model number should look like "X015-XA-BAAAXX"	

CHEM-TECH Series 100D and 150D

Note: Standard Features do not add to the pump price.

Remember that liquid end adders must be doubled for duplex pump models.

Chem-Tech Series 100D and 150D Duplex Selection Guide		1	---	---	---	---
MODELS:	Series 100D Duplex Pump 144 = 4.0 gpd (0.63 lph) / 4.0 gpd (0.63 lph) max pres.: 50 PSI (3.5 BAR) 145 = 5.0 gpd (0.79 lph) / 4.0 gpd (0.63 lph) max pres.: 50 PSI (3.5 BAR) 155 = 5.0 gpd (0.79 lph) / 5.0 gpd (0.79 lph) max pres.: 50 PSI (3.5 BAR) 244 = 6.5 gpd (1.03 lph) / 6.5 gpd (1.03 lph) max pres.: 75 PSI (5.25 BAR) 245 = 7.5 gpd (1.18 lph) / 6.5 gpd (1.03 lph) max pres.: 75 PSI (5.25 BAR) 255 = 7.5 gpd (1.18 lph) / 7.5 gpd (1.18 lph) max pres.: 75 PSI (5.25 BAR) 264 = 12.0 gpd (1.89 lph) / 8.0 gpd (1.26 lph) max pres.: 60 PSI (4.2 BAR) 265 = 12.0 gpd (1.89 lph) / 9.0 gpd (1.43 lph) max pres.: 60 PSI (4.2 BAR) 344 = 14.0 gpd (2.21 lph) / 14.0 gpd (2.21 lph) max pres.: 75 PSI (5.25 BAR) 345 = 18.0 gpd (2.84 lph) / 14.0 gpd (2.21 lph) max pres.: 75 PSI (5.25 BAR) 355 = 18.0 gpd (2.84 lph) / 18.0 gpd (2.84 lph) max pres.: 75 PSI (5.25 BAR) 364 = 25.0 gpd (3.94 lph) / 15.0 gpd (2.37 lph) max pres.: 60 PSI (4.2 BAR) 365 = 25.0 gpd (3.94 lph) / 19.0 gpd (3.0 lph) max pres.: 60 PSI (4.2 BAR) 444 = 30.0 gpd (4.73 lph) / 30.0 gpd (4.73 lph) max pres.: 75 PSI (5.25 BAR) 445 = 30.0 gpd (4.73 lph) / 33.0 gpd (5.20 lph) max pres.: 75 PSI (5.25 BAR) Series 150D 455 = 33.0 gpd (5.20 lph) / 33.0 gpd (5.20 lph) max pres.: 75 PSI (5.25 BAR) 464 = 69.0 gpd (10.88 lph) / 32.0 gpd (5.05 lph) max pres.: 60 PSI (4.2 BAR) 465 = 69.0 gpd (10.88 lph) / 24.0 gpd (5.53 lph) max pres.: 60 PSI (4.2 BAR) 466 = 69.0 gpd (10.88 lph) / 69.0 gpd (10.88 lph) max pres.: 60 PSI (4.2 BAR)					
ELECTRICAL:	XA = 115V, 60 Hz XB = 230V, 50 Hz (not available in 2120) XC = 230V, 60 Hz XD = 115V, 50/60 Hz, T.E.F.C. (X200 only) XL = 230V, 50/60 Hz, T.E.F.C. (X200 only)					
LIQUID END MATERIALS: Pump Head & Fittings/Seats & O-rings/Balls	AAA = SAN/PVC / Hypalon / Ceramic AAB = SAN/PVC / Hypalon / TFE ABA = SAN/PVC / Viton / Ceramic ABB = SAN/PVC / Viton / TFE ACA = SAN/PVC / Tef/Hyp / Ceramic AHA = SAN/PVC / Tef/Viton / Ceramic BAA = PVC / Hypalon / Ceramic BAB = PVC / Hypalon / TFE BBA = PVC / Viton / Ceramic BBB = PVC / Viton / TFE BHA = PVC / Tef/Hyp / Ceramic DAA = PP / Hypalon / Ceramic DAB = PP / Hypalon / TFE DBA = PP / Viton / Ceramic DBB = PP / Viton / TFE GFA = PVC / TFE / Ceramic (dbl) GFB = PVC / TFE / TFE (dbl) EFC = 316 / TFE / 316 (dbl)					
CONNECTION SIZES:	A = Tubing .44" PVC Suction / .50" PE Discharge C = Tubing .38" PVC Suction / .38" PE Discharge F = Tubing .44" PVC Suction / .50" PE BLK Discharge S = Tubing .38" PVC Suction / .38" PE BLK Discharge X w/ 316 = .25" FNPT Suction / .25" FNPT Discharge					
SUFFIX CODES:	XXX = Standard 001 = Current Interrupter 500* = Five Function Valve 520* = Five Function Degas Valve ITS = 15 gal ITS Tank System					
* Not available in SS. Adder price is per head.						
A completed model number should look like "1445-XA-BAAAXX"						

STANDARD ACCESSORIES

Series 100/150/100D/150D/200: Pumps with tubing connections come with foot valve/strainer/weight, 4' of suction tubing, bleed valve, 4' of return tubing, 8' of discharge tubing, and injection/back pressure valve assembly.

Any pumps with piping connections come with strainer and injection valve only.

CHEM-TECH

Chem-Tech KOPkit Selection Guide

KX100

PRODUCT DESIGNATOR: KX100 = Chem-Tech Kopkit

LIQUID END MATERIALS: Head, Diaph., Seats & Balls		
AAA	= SAN/PVC / Hypalon / Ceramic	
AAB	= SAN/PVC / Hypalon / TFE	
ABA	= SAN/PVC / Viton / Ceramic	
ABB	= SAN/PVC / Hypalon / TFE	
ACA	= SAN/PVC / Tef/Hyp / Ceramic	
AHA	= SAN/PVC / Tef/Viton / Ceramic	
BAA	= PVC / Hypalon / Ceramic	
BAB	= PVC / Hypalon / TFE	
BBA	= PVC / Viton / Ceramic	
BBB	= PVC / Viton / TFE	
BHA	= PVC / Tef/Hyp / Ceramic	
DAA	= PP / Hypalon / Ceramic	
DAB	= PP / Hypalon / TFE	
DBA	= PP / Viton / Ceramic	
DBB	= PP / Hypalon / TFE	
GFA	= PVC / TFE / Ceramic (dbl)	
GFB	= PVC / TFE / TFE (dbl)	
EFC	= 316 / TFE / 316 (dbl)	

CONNECTION :		
A	= Tubing .44" PVC Suction / .50" PE Discharge	
C	= Tubing .38" PVC Suction / .38" PE Discharge	
F	= Tubing .44" PVC Suction / .50" PE BLK Discharge	
S	= Tubing .38" PVC Suction / .38" PE BLK Discharge	
X w/ 316	= .25" FNPT Suction / .25" FNPT Discharge	

SERIES 100, 150, 100D, 150D AND 200 PARTS PRICE SCHEDULE

PART # DESCRIPTION

00006	- Suction Tubing - per foot 7/16" OD
00007	- Suction Tubing - per foot 3/8"
00008	- Discharge Tubing - per foot 1/2" OD
00009	- Discharge Tubing - per foot 1/2" Black
00010	- Discharge Tubing - per foot 3/8"
00011	- Discharge Tubing - per foot 3/8" Black
20038	- 1/2" NPT Connection - PVC - fits Suction side of Pump Head and Back Ck. Vlv. Assy. (per connection)
20039	- 1/2" NPT Connection - PVC - fits Discharge side of Pump Head and Strainer Assy. (per connection)
J20560	- Ball Check (ceramic)
21829	- Drive Bracket Assy. S100
21960	- Bronze Bushing (right)
21961	- Bronze Bushing (left)
21962	- Bronze Bushing (center)
21971	- Diaphragm Shaft Bushing
22255	- Cam Bearing Assy. S100 - 3, 7, 15, 30 GPD
22256	- Cam Bearing Assy. S100 - 24 GPD
22257	- Cam Bearing Assy. S150 - 68, 100 GPD
23700	- Shaft Collar - .38 Small
23701	- Shaft Collar - .38 Large
J24269	- Oil (quart)
24450	- Current Interrupter - S100 - 115V
24452	- Current Interrupter - S200 - 115V
24453	- Current Interrupter/Plug Receptacle S200 - 115V
24454	- Current Interrupter/Plug Receptacle/Bottom Plate (Standard) 115V
24481	- Current Interrupter - S100 - 230V
24482	- Current Interrupter - S200 - 230V
24820	- Cord Assy. - 115V, 60 Hz
24821	- Cord - 230V, 50 or 60 Hz
J24960	- Coupling Nut, PVC 1/2" (Standard)
24961	- Coupling Nut, PP 1/2"
24963	- Coupling Nut, PVC 3/8"
25180	- Motor Cover
25704	- Diaphragm, Hypalon
25706	- Diaphragm, Viton
25707	- Diaphragm, PTFE Coated
J26780	- Injection Fitting, PVC 3/8"
26781	- Injection Fitting, PVC 1/2"
26858	- Bulkhead Fitting (PP-1/2")
26867	- Bulkhead Fitting (PP-3/8")
J26907	- Bulkhead Fitting (PVC-1/2")
J26908	- Bulkhead Fitting (PVC-3/8")

PART # DESCRIPTION

J26909	- Bulkhead Fitting (PVC-5/16")
J26910	- Bulkhead Fitting without strainer (PVC-3/8")
J26905	- Bulkhead Fitting for ITS (PVC-1/4")
J27903	- Gasket, TFE
27911	- Gasket
28210	- Gear Housing Assembly #210
28211	- Gear Housing Assembly #215
28212	- Gear Housing Assembly #220
28213	- Gear Housing Assembly #230
28214	- Gear Housing Assembly #240
28215	- Gear Housing Assembly #260
28216	- Gear Housing Assembly #280
28217	- Gear Housing Assembly #2-100
28218	- Gear Housing Assembly #2-120
28521	- Grommet
28800	- Head, SAN
J28801	- Head, PVC
28803	- Head, Polypropylene
28896	- Head Assy, (SST-TFE-SST-1/4" S/D)
28897	- Head Assy, (PVC-VT-C-1/2" S/D)
28899	- Head Assy, (PP-VT-C-1/2" S/D)
28902	- Head Assy, (PVC-VT-C-3/8" S/D)
28903	- Head Assy, (SAN-HYP-C-1/2" S/D)
28904	- Head Assy, (SAN-HYP-C-3/8" S/D)
29020	- Head Assy, (PVC-VT-C-1/2" S - 3/8" D)
29036	- Head Assy, (PP-VT-C-3/8" D)
29230	- Motor Housing
29232	- Pump Housing (Duplex)
29313	- Main Housing 10, 15, 20, 30, 40, 60, 100 GPD
29314	- Main Housing 120 GPD only
30460	- Output Adjustment Knob
30467	- Output Adj Knob Asm S150
30468	- Output Adj Knob Asm S100
J30496	- Housing - S100 - 3, 7, 15, 30 GPD
J30497	- Housing - S100 - 24 GPD
J30498	- Housing - S150, 68, 100 GPD
J30503	- Motor - 115V, 60 Hz, S200
J30504	- Motor - 230V, 50 Hz, S200
J30505	- Motor - 230V, 60 Hz, S200
J30507	- Kit, Bleed, Valve, PVC/HPY/ 3/8
J30509	- Kit, Bleed, Valve, PVC/VTN/ 3/8
J30510	- Kit, Bleed, Valve, PVC/TFE/ 3/8
J30511	- Kit, Bleed, Valve, FPP/HYP/ 3/8
J30513	- Kit, Bleed, Valve, FPP/VTN/ 3/8

SERIES 100, 150, 100D, 150D AND 200 PARTS PRICE SCHEDULE

PART #	DESCRIPTION	PART #	DESCRIPTION
J30514	- Kit, Bleed, Valve, FPP/TFE/ 3/8	41588	- Anti-Siphon Valve (PVC-VT-1/2")
J30515	- Kit, Bleed, Valve, PVC/HPY/ 1/2	41624	- Anti-Siphon Valve (PVC-HY-1/2") (Standard)
J30517	- Kit, Bleed, Valve, PVC/VTN/ 1/2	41657	- Back Check Valve Assy (PVC-HY-C-3/8")
J30518	- Kit, Bleed, Valve, PVC/TFE/ 1/2	J41658	- Back Check Valve Assy (PVC-HY-C-1/2")
J30519	- Kit, Bleed, Valve, FPP/HYP/ 1/2	41659	- Back Check Valve Assy (PP-VT-C-1/2")
L3300V03-FPP	- Kit, Bleed, Valve, FPP/VTN/ 1/2	41661	- Back Check Valve Assy (PVC-VT-C-1/2")
J30522	- Kit, Bleed, Valve, FPP/TFE/ 1/2	41665	- Anti-Scale Injector (PVC-HY-1/2")
31081	- Locking Lever - S100, 215, 230, 260	41666	- Double Ball Ck Vlv Cart Assy (PVC-3/8") Suct
31082	- Locking Lever 20, 40, GPD S200	J41667	- Double Ball Ck Vlv Cart Assy (PVC-1/2") Suct
31083	- Locking Lever - S150, 280, 2-100, 2-120	41668	- Double Ball Ck Vlv Cart Assy (PVC-3/8") Disch
32520	- Motor - 7 SPM, 115V, 60 Hz, 003	J41669	- Double Ball Ck Vlv Cart Assy (PVC-1/2") Disch
32521	- Motor - 13 SPM, 115V, 60 Hz, 007	J41694	- Back Check Valve Assy (PVC-HYP-C-1/2")
32522	- Motor - 25 SPM, 115V, 60 Hz, 015	41695	- Back Check Valve Assy (PVC-VT-C-3/8")
32523	- Motor - 51 SPM, 115V, 60 Hz, 024/030/068	41696	- Back Check Valve Assy (PP-VT-C-3/8")
32524	- Motor - 7 SPM, 230V, 60 Hz, 003	41705	- 6" Ck Vlv Inj Assy (PVC-HY-C-3/8")
32525	- Motor - 13 SPM, 230V, 60 Hz, 007	41707	- 6" Ck Vlv Inj Assy (PVC-VT-C-3/8")
32526	- Motor - 25 SPM, 230V, 60 Hz, 015	41708	- 6" Ck Vlv Inj Assy (PVC-VT-C-1/2")
32527	- Motor - 51 SPM, 230V, 60 Hz, 024/030/068	41709	- 6" Ck Vlv Inj Assy (PP-VT-C-3/8")
32528	- Motor - 7 SPM, 230V, 50 Hz, 003	41710	- 6" Ck Vlv Inj Assy (PP-VT-C-1/2")
32529	- Motor - 13 SPM, 230V, 50 Hz, 007	41720	- Anti-Siphon Valve (PVC-HY-1/2" NPT)
32530	- Motor - 25 SPM, 230V, 50 Hz, 015	41786	- Anti-Siphon Valve (PVC-VT-1/2" NPT)
32531	- Motor - 51 SPM, 230V, 50 Hz, 024/030/068	41795	- Back Check Valve Assy (PVC-HY-C-1/2" x 1/2" NPT)
32532	- Motor - 70 SPM, 115V, 60 Hz, 100	J42020	- Head Bolt Washer SS .20 x .38
32533	- Motor - 70 SPM, 230V, 50 Hz, 100	J42030	- Fiber Washer
32535	- Motor - 70 SPM, 230V, 60 Hz, 100	42031	- Washer, Fiber
J34380	- Backing Plate	J60030	- Head Assy (SAN-HY-C-3/8" D)
34385	- Blue Bottom Housing Plate	J61222	- Kit, 5 Function Valve incl L380DT03-PVC for Series 100/200
34405	- Plate, Motor Cover	J61271	- Kit, 5 Function Valve incl L380FT03-PVC for Series 200
34423	- Back Plate	J61539	- Kit, 5 Function Valve incl L380DT02-PVC for Series 100/200
34532	- Oil Filler Plug w/Cap	J61506	- Kit, Oil Drain Plug (includes J37002 & J42030)
J37073	- Screw Motor Cover	J61503	- Kit, S200 Back Plate Screws (5 - J37017, 5 - J42030)
37080	- Output Adjust Screw 10, 20, 40 GPD	J61504	- Kit, S200 Motor Cover Hdwe (2 - J37002, 2 - J42030)
37081	- Output Adjust Screw 15, 30, 60 GPD	J61505	- Kit, S100 Motor Cover Hdwe (4 - J37032, 2 - J37073)
37083	- Output Adjust Screw 80, 100, 120 GPD	J61506	- Kit, S100 Cam Bearing Set Screw (2 - 37047)
37088	- Output Adj Screw - S150	J61507	- Kit, S100 Motor Mount Hdwe (3 - 37049)
37089	- Output Adj Screw - S100	J61508	- Kit, S200 Main Housing Screw
37300	- Oil Seal		(2 - 37021, 2 - J42083, 2 - 42031)
J37440	- Valve Seat, Hypalon	J61509	- Kit, S200 Shaft Coupling Motor (1 - 24966, 1 - 37060)
J37442	- Valve Seat, Viton	J61510	- Kit, S200 Shaft Coupling Gear (1 - 24967, 1 - 37061)
37886	- Diaphragm Shaft	J61511	- Kit, Screw Motor Cover (2 - J37073)
38080	- Locking Sleeve	J61512	- Kit, Valve Seats Hypalon (4 - J37440)
38980	- Diaphragm Return Spring	J61513	- Kit, Ball Checks (4 - J20560)
38981	- Coupling Spring	J61515	- Kit, Valve Seats Viton (4 - J37442)
38984	- Valve Spring - top - light	J61516	- Kit, Head Mounting Bolts (4 - J37005, 4 - J42020)
J38985	- Valve Spring	J61518	- Kit, Gasket TFE (4 - J27903)
J60717	- Foot Valve & Strainer Assy (PVD-Hyp-C-3/8")	L9906700-000	- Sinker
J60729	- Foot Valve & Strainer Assy (PVD-Hyp-C-1/2")		
J60718	- Foot Valve & Strainer Assy (PVD-VT-C-3/8")		
J60730	- Foot Valve & Strainer Assy (PVD-VT-C-1/2")		
J41540	- Valve Housing Discharge, PVC 1/2"		
41541	- Valve Housing Discharge, PP 1/2"		
41543	- Valve Housing Discharge, PVC 3/8"		
41544	- Valve Housing Discharge, PP 3/8"		
J41548	- Valve Housing Suction, PVC 1/2"		
J41834	- Valve Housing Suction, PP 1/2"		
41551	- Valve Housing Suction, PVC 3/8"		
J41835	- Valve Housing Suction, PP 3/8"		

SPECIAL ADAPTERS

20013 - Pressure Relief Valve Adapter

STAINLESS STEEL PUMP ACCESSORIES

28896 - 316 SS Head Assy - Double Check Vlv
(TFE, SS) 1/4" FPT Conn

J41656 - 316 SS Double Back Ck Vlv Assembly
(TFE, SS) 1/4" FPT Conn

J40095 - 316 SS Strainer Assy 1/4" FPT Conn

J41640 - 316 SS Suction Valve 1/4" FPT

J41641 - 316 SS Discharge Valve 1/4" FPT

CHEM-TECH Series 250

Selecting the proper Chem-Tech pump is easy! Just refer to selection charts one through five to select the proper output, voltage, liquid end materials, etc. Fill in the model number with the correct codes as you go, taking note of the base and adder prices.

Chem-Tech Series 250 Selection Guide		X25	-	---	-	---	Q	-	XXX
MODELS:	3 = 76.8 gpd (12.11 lph) max pres.: 225 PSI (15.52 BAR) 4 = 108 gpd (17.03 lph) max pres.: 160 PSI (11.03 BAR)								
ELECTRICAL:	XD = 115V, 50/60 Hz, T.E.F.C. XL = 230V, 50/60 Hz, T.E.F.C.								
LIQUID END MATERIALS:	GFA = PVC / TFE (dbl) / Ceramic								
CONNECTION SIZES:	Q = 44" PVC Suction / .50" PP Discharge								
SUFFIX CODES:	XXX = Standard								
A complete model should look like "X253-XD-GFAQXXX"									

IMPORTANT NOTES:

1. KOPkits are not available for this model.
2. Shipping weight is 21 lbs.

STANDARD ACCESSORIES:

Models with tubing connections come with a footvalve/strainer/weight, 4' of suction tubing, 8' of discharge tubing, and an injection valve.

Models with piping connections come with a strainer and an injection valve.

SERIES 250 PARTS PRICE SCHEDULE

PART #	DESCRIPTION	PART #	DESCRIPTION
00006	- Suction Tubing (per foot) 7/16" OD	29230	- Motor Cover / 253 - 254
J00012	- Polypropylene Tubing, 1/2" OD - Discharge (per foot)	29313	- Pump Housing
00013	- Polypropylene Tubing, 1/2" OD-Discharge (per ft) - Black	30460	- Output Adjustment Knob
J20560	- Ball Check, Ceramic	31084	- Locking Lever
23705	- Collar - Model 253	32545	- Motor, 115/230V, 50/60 Hz, TEFC
23706	- Collar - Model 254	34532	- Oil Filler Plug with Cap
J24269	- Oil (quart)	37084	- Adjustment Screw
24820	- Cord Assembly, 115V, 60Hz	37886	- Diaphragm Shaft
24821	- Cord, 230V, 50-60 Hz	J41658	- Back Check Valve Assy (PVC-HY-C-1/2")
J24960	- Coupling Nut - PVC 1/2"	J41667	- Double Ball Check Valve Cart Assy (PVC 1/2") Suction
25681	- Diaphragm Assembly - Model 253	41668	- Double Ball Check Valve Cart Assy (PVC 3/8") Disch
25682	- Diaphragm Assembly - Model 254	J41669	- Double Ball Check Valve Cart Assy (PVC 1/2") Disch
J27903	- Gasket, TFE	J42020	- Bolt Washer (4 required) SS
28220	- Gear Housing Assembly - Model 253/254	J60729	- Foot Valve & Strainer Assy (PVD-HY-C-1/2")
J28815	- Pump Head, PVC - Model 253	J61272	- Kit, 5 Function Valve incl L380KT03-PVC for Series X253
28816	- Pump Head, PVC - Model 254	J61516	- Kit, Head Mounting Bolts (4 - J37005, 4 - J42020)
J28919	- Head Assembly, PVC - Model 253 - 1/2"	J61518	- Kit, Gasket TFE (4 - J27930)
28920	- Head Assembly, PVC - Model 254 - 1/2"		

CHEM-TECH Series 300

Selecting the proper Chem-Tech pump is easy! Just refer to selection charts one through five to select the proper output, voltage, liquid end materials, etc. Fill in the model number with the correct codes as you go, taking note of the base and adder prices.

Note: Standard Features do not add to the pump price.

Remember that liquid end adders must be multiplied by the number of pump heads.

PLEASE ADD A CRATING FEE OF \$50.00 NET PER PUMP WHEN SHIPPING AIR OR OCEAN FREIGHT.

Chem-Tech Series 300 Selection Guide	
MODELS:	X310 = SIMPLEX 500 gpd (78.83 lph) max pres.: 150 PSI (10 BAR) X320 = DUPLEX 100 gpd (157.71 lph) max pres.: 150 PSI (10 BAR) X330 = TRIPLEX 1500 gpd (236.54 lph) max pres.: 150 PSI (10 BAR) X340 = QUADRAPLEX 2000 gpd (315.42 lph) max pres.: 150 PSI (10 BAR) 313D = SIMPLEX 210 gpd (33.08 lph) max pres.: 150 PSI (10 BAR) 316D = SIMPLEX 430 gpd (67.79 lph) max pres.: 150 PSI (10 BAR) 323D = DUPLEX 420 gpd (66.21 lph) max pres.: 150 PSI (10 BAR) 326D = DUPLEX 860 gpd (135.63 lph) max pres.: 150 PSI (10 BAR)
ELECTRICAL:	Series 300 Direct Drive Motor (models ending in D, i.e. 316D) XT = 115/230V, 50/60 Hz, T.E.F.C. Series 300 Motors (models beginning with an X, i.e. X320) XA = 115V, 60 Hz, single phase, open XB = 230V, 50 Hz, single phase, open XC = 230V, 60 Hz, single phase, open XD = 115V, 60 Hz, single phase, T.E.F.C. XG = 220/440V, 50/60 Hz, 3 phase, open XH = 220/440V, 60 Hz, 3 phase, T.E.F.C. XI = 220/440V, 50/60 Hz, 3 phase, Explosion Proof XJ = 115V, 60 Hz, single phase, Explosion Proof XK = 115V, 50/60 Hz, 1/3 HP, TENV DC motor & SCR Controller, 4- (X310 & X320 only) XN = 220/440V, 50 Hz, 3 phase, T.E.F.C. XX = No motor
LIQUID END MATERIALS: Pump Head & Fittings/Seats & O-rings/Balls	AHA = SAN/PVC / Hypalon / Ceramic AHB = SAN/PVC / Hypalon / Ceramic ACA = SAN/PVC / Viton / TFE ACB = SAN/PVC / Viton / Ceramic BHA = PVC / Hypalon / Ceramic BHB = PVC / Hypalon / TFE BCA = PVC / Viton / Ceramic BCB = PVC / Viton / TFE DHA = PP / Hypalon / Ceramic DHB = PP / Hypalon / TFE DCA = PP / Viton / Ceramic DCB = PP / Viton / TFE EFC = 304 / 304 / 316
* Diaphragms are all PTFE faced.	
CONNECTION SIZES:	A = Tubing .44" PVC Suction / .50" PE Discharge X w/ PVC = Tubing .38" PVC Suction / .38" PE Discharge X w/ 316 = Tubing .44" PVC Suction / .50" PE BLK Discharge
SUFFIX CODES:	XXX = Standard
A completed model number should look like "X330-XD-AHAAXX"	

IMPORTANT NOTE: KOPkits not available for this model.

STANDARD ACCESSORIES:

Models with tubing connections come with a foot valve/strainer/weight, 4' of suction tubing, 8' of discharge tubing, and an injection valve.

Models with piping connections come with a strainer and an injection valve.

SERIES 300 PARTS PRICE SCHEDULE

PART #	DESCRIPTION
00006	- Suction Tubing (per foot) 7/16" OD - PVC
00008	- Discharge Tubing Polyethylene (per foot) 1/2" OD
J20560	- Ball Check (Ceramic)
20700	- Base-Simplex
20843	- Drive Bearing
20844	- Main Shaft Bearing
20980	- V-Belt
21407	- Head Bolt, 1/4" - 20 x 2,2, Stainless Steel
21409	- Head Bolt, 1/4" - 20 x 10,5, Stainless Steel
21821	- Bracket
22253	- Cam
23702	- Locking Collar
J23723	- Collar, Suction Swivel Assy
J24960	- Coupling Nut, PVC 1/2" (Standard)
25712	- Diaphragm, PTFE Coated
J26780	- Injection Fitting
J27903	- Gasket, TFE
27906	- Gasket, Viton
28661	- Belt Guard
28805	- Head, Acrylic
J28814	- Head, PVC
28809	- SST Head 304
28813	- Polypropylene Head
28939	- Head Assembly, Acrylic (SAN-HY-C) 1/2"
28940	- Head Assembly, PVC (PVC-HY-C)
29074	- Polypropylene Head Assy
29107	- SST Head Assy 304
29237	- Housing Back Plate
29238	- Pump, Housing Simplex
29297	- Pump Housing, Assembly w/Fitting & Tubing (SAN-HY-C)
J30120	- Reducer Input Shaft Key
30121	- Main Shaft Key
30461	- Output Adjusting Knob
32590	- Motor (Standard) 1/3 hp, 115V, 60Hz ODP
32970	- Adjusting Screw Lock Nut
33081	- O Ring Seal - Hypalon
33761	- Output Indicator Pin
35220	- Pulley (4-step) - Motor
35221	- Pulley (4-step) - Reducer
J35918	- Speed Reducer 60:1
J36395	- Cam Bearing Locking ring
J37440	- Valve Seat, Hypalon
J37442	- Valve Seat, Viton
37447	- Valve Seat, Viton
37887	- Main Shaft
37888	- Output Adjusting Shaft
37889	- Diaphragm Shaft
38982	- Diaphragm Return Spring
38983	- Valve Spring
39180	- Sprocket - Motor
39181	- Sprocket - Reducer
40087	- Strainer Assembly - PP - HY - C - 1/2"
J41548	- Valve Housing PVC 1/2"
41565	- Valve Housing Discharge PVC
41566	- Valve Housing Suction PVC
41568	- Valve Seat, Suction - PVC
41637	- Back Check Valve Assembly (PVC - HY - C - 1/2")
41638	- Back Check Valve Assy (PVC - HY - C - 1/2")
41677	- Valve Seat Suction Assembly
J61519	- Kit, Gasket Hypalon (2 - 27905)
J61520	- Kit, Valve Seat Hypalon (2 - 37446)
J61521	- Kit, Acorn Nut Set (10 - 32960, 10 - 42022)
J61522	- Kit, Output Indicator (2 - 37030, 1 - 34381)
J61523	- Kit, Coupling Chain (1 - 24976, 1 - 33765, 1 - 36400)
J61526	- Kit, Valve Components (2 - 37446, 2 - 27905, 2 - L1000500-ALA)
J61527	- Kit, Suction Swivel Base (1 - 20705, 1 - 37040)
J61528	- Kit, Head Bolt 2,2" (2 - 21407, 2 - 32960, 2 - 42022)
L1000500-ALA	- Ball Check - Ceramic

CHEM-TECH Series 400

Selecting the proper Chem-Tech pump is easy! Just refer to selection charts one through five to select the proper output, voltage, liquid end materials, etc. Fill in the model number with the correct codes as you go, taking note of the base and adder prices.

Note: Standard Features do not add to the pump price.

Remember that liquid end adders must be multiplied by the number of pump heads.

PLEASE ADD A CRATING FEE OF \$50.00 NET PER PUMP WHEN SHIPPING AIR OR OCEAN FREIGHT.

Chem-Tech Series 400 Selection Guide			X	---	---	---	---	XXX
MODELS:	Piston Diameter							
405 = Simplex	1/4"	0.5 gph (1.89 lph) max pres.: 800 PSI (55.17 BAR)						
406 = Duplex	1/4"	1.0 gph (3.76 lph) max pres.: 800 PSI (55.17 BAR)						
409 = Simplex	3/8"	0.81 gph (3.06 lph) max pres.: 800 PSI (55.17 BAR)						
410 = Duplex	3/8"	1.72 gph (6.50 lph) max pres.: 800 PSI (55.17 BAR)						
413 = Simplex	1/4"	1.0 gph (3.78 lph) max pres.: 800 PSI (55.17 BAR)						
414 = Duplex	1/4"	2.00 gph (7.56 lph) max pres.: 800 PSI (55.17 BAR)						
417 = Simplex	3/8"	1.62 gph (6.12 lph) max pres.: 800 PSI (55.17 BAR)						
418 = Duplex	3/8"	3.24 gph (12.25 lph) max pres.: 800 PSI (55.17 BAR)						
425 = Simplex	1/2"	1.65 gph (6.24 lph) max pres.: 800 PSI (55.17 BAR)						
426 = Duplex	1/2"	3.3 gph (12.47 lph) max pres.: 800 PSI (55.17 BAR)						
429 = Simplex	5/8"	3.10 gph (11.72 lph) max pres.: 800 PSI (55.17 BAR)						
430 = Duplex	5/8"	6.2 gph (23.44 lph) max pres.: 800 PSI (55.17 BAR)						
433 = Simplex	1/2"	3.3 gph (12.47 lph) max pres.: 800 PSI (55.17 BAR)						
434 = Duplex	1/2"	6.6 gph (24.95 lph) max pres.: 800 PSI (55.17 BAR)						
437 = Simplex	5/8"	6.6 gph (24.95 lph) max pres.: 800 PSI (55.17 BAR)						
438 = Duplex	5/8"	12.4 gph (46.87 lph) max pres.: 800 PSI (55.17 BAR)						
441 = Simplex	1"	8.5 gph (32.13 lph) max pres.: 300 PSI (20.69 BAR)						
442 = Duplex	1"	17.0 gph (64.25 lph) max pres.: 300 PSI (20.69 BAR)						
445 = Simplex	1"	17.0 gph (64.25 lph) max pres.: 300 PSI (20.69 BAR)						
446 = Duplex	1"	34.0 gph (128.52 lph) max pres.: 300 PSI (20.69 BAR)						
ELECTRICAL:	XT = 115/230 V, 50/60 Hz, T.E.F.C.							
LIQUID END MATERIALS:	Based on Piston Diameter							
	<1"							
Pump Head & Fittings/ Packing & Balls	EFA = 303 SS / TFE / Ceramic							
	EFC = 303 SS / TFE / 316 SS							
	=1"							
	EFC = 304 SS / TFE / 316 SS							
	EFB = 304 SS / TFE / TFE							
CONNECTION SIZES:	X =	< 1"	1/2" FNPT Suction / 1/2" FNPT Discharge					
	X =	≥ 1"	1/4" FNPT Suction / 1/4" FNPT Discharge					
SUFFIX CODES:	XXX = Standard							
A completed model should look like "X413-XT-EFAXXXX"								

CHEM-TECH Series 500

Selecting the proper Chem-Tech pump is easy! Just refer to selection charts one through five to select the proper output, voltage, liquid end materials, etc. Fill in the model number with the correct codes as you go, taking note of the base and adder prices.

Note: Standard Features do not add to the pump price.

Remember that liquid end adders must be multiplied by the number of pump heads.

PLEASE ADD A CRATING FEE OF \$50.00 NET PER PUMP WHEN SHIPPING AIR OR OCEAN FREIGHT.

Chem-Tech Series 500 Selection Guide		X	---	---	---	X	XXX
MODELS:	Piston Diameter						
541 = Simplex	1" 6.97 gph (26.38 lph) max pres.: 500 PSI (34.48 BAR)						
542 = Duplex	1" 13.95 gph (52.76 lph) max pres.: 500 PSI (34.48 BAR)						
545 = Simplex	1" 13.7 gph (51.85 lph) max pres.: 500 PSI (34.48 BAR)						
546 = Duplex	1" 27.41 gph (103.71 lph) max pres.: 500 PSI (34.48 BAR)						
548 = Simplex	1" 27.65 gph (104.65 lph) max pres.: 500 PSI (34.48 BAR)						
572 = Duplex	1" 55.30 gph (209.31 lph) max pres.: 500 PSI (34.48 BAR)						
551 = Simplex	1 1/4" 10.89 gph (41.24 lph) max pres.: 300 PSI (20.69 BAR)						
552 = Duplex	1 1/4" 21.78 gph (82.48 lph) max pres.: 300 PSI (20.69 BAR)						
553 = Simplex	1 1/4" 21.41 gph (81.06 lph) max pres.: 300 PSI (20.69 BAR)						
554 = Duplex	1 1/4" 42.82 gph (162.12 lph) max pres.: 300 PSI (20.69 BAR)						
559 = Simplex	1 1/4" 43.20 gph (163.54 lph) max pres.: 300 PSI (20.69 BAR)						
560 = Duplex	1 1/4" 86.40 gph (327.08 lph) max pres.: 300 PSI (20.69 BAR)						
561 = Simplex	1 1/2" 15.69 gph (59.38 lph) max pres.: 200 PSI (13.79 BAR)						
562 = Duplex	1 1/2" 31.38 gph (118.77 lph) max pres.: 200 PSI (13.79 BAR)						
563 = Simplex	1 1/2" 30.83 gph (116.69 lph) max pres.: 200 PSI (13.79 BAR)						
564 = Duplex	1 1/2" 61.66 gph (233.38 lph) max pres.: 200 PSI (13.79 BAR)						
569 = Simplex	1 1/2" 62.21 gph (235.46 lph) max pres.: 200 PSI (13.79 BAR)						
570 = Duplex	1 1/2" 124.42 gph (470.93 lph) max pres.: 200 PSI (13.79 BAR)						
ELECTRICAL:							
XA	= 115V, 60 Hz, single phase, open						
XB	= 230V, 50 Hz, single phase, open						
XC	= 230V, 60 Hz, single phase, open						
XD	= 115V, 60 Hz, single phase, T.E.F.C.						
XG	= 220/440V, 50/60 Hz, 3 phase, open						
XH	= 220/440V, 60 Hz, 3 phase, T.E.F.C.						
XI	= 220/440V, 50/60 Hz, 3 phase, Explosion Proof						
XJ	= 115V, 60 Hz, single phase, Explosion Proof						
XN	= 220/440V, 50 Hz, 3 phase, T.E.F.C.						
LIQUID END MATERIALS:	Based on Piston Diameter						
	=1"						
Pump Head & Fittings/ Packing & Balls	EFC = 304 SS / TFE / 316 SS						
	EFB = 304 SS / TFE / TFE						
	=1 1/4"						
	EFC = 304 SS / TFE / 316 SS						
	EFB = 304 SS / TFE / TFE						
	=1 1/2"						
	EFC = 304 SS / TFE / 316 SS						
	EFB = 304 SS / TFE / TFE						
CONNECTION SIZES:							
X	= < 1" 1/2" FNPT Suction / 1/2" FNPT Discharge						
X	= ≥ 1" 1/4" FNPT Suction / 1/4" FNPT Discharge						
SUFFIX CODES:	XXX = Standard						
A completed model number should look like "X545-XJ-EFCXXX"							

SERIES 400 and SERIES 500 PARTS

SERIES 400 PARTS

PART #	DESCRIPTION
J20723	- Pump Base (Simplex)
20703	- Pump Base (Duplex)
20845	- Main bearing (closed)
21965	- Main Shaft Motor Bushing
21964	- Outboard Bearing
26810	- Grease Relief Fitting
26811	- Grease Fitting
28200	- Gear/Shaft Assy - 30RPM, 115V OPD Simp
28202	- Gear/Shaft Assy - 60 RPM, 115V OPD Simp
29246	- Housing Set Assy S400 Simplex & Duplex
29249	- Housing Set Assy S400 Duplex
30125	- Main Shaft Key
32632	- Motor Assy w/Shaft 60 RPM 115V ODP-Simp
32634	- Motor Assy w/Shaft 30 RPM 115V ODP-Dup
32645	- Motor Assy w/Shaft 60 RPM 115V ODP-Dup
32646	- Motor Assy w/Shaft 30 RPM 115V ODP-Simp
32648	- Shaft Assy, Coupled
J32749	- MTR, 30 RPM 115/230V TEFC
J32750	- MTR, 60 RPM 115/230V TEFC
J32943	- Mounting Nut (4 req)
32971	- Adjustment Screw Lock Nut
33764	- Slide Pin
36396	- Main Shaft Locking Ring
J37054	- Set Screw 1/4" - 20 x 3/4"
37090	- Adjustment Screw
37305	- PVC Seal (2 req)
37891	- Main Shaft (Duplex)
38221	- Slide (Simplex / Duplex)
38224	- Slide Arm Assembly (Simplex)
38225	- Slide Arm Assembly (Duplex)
38988	- Valve Spring (2 req)
41672	- Discharge Check Valve Assy 1/4" FPT
41674	- Suction Check Valve Assy 1/4" FPT
J61530	- Kit, Main Shaft (Simp, TEFC) (1 - 37899, 3 - D4844-31)
J61531	- Kit, Main Bearing Cam (1 - 22263, 1 - 33771)
J61532	- Kit, Housing Set Hdwe (2 - 21407, 2 - 21406, 2 - 42022, 2 - 42035, 4 - 32942)
L1000400-ALA	- Ceramic Ball 1/4" (2 req)
L1000500-ALA	- Ceramic Ball 3/8" (2 req)
A-PISTON HEAD ASSEMBLY	
28925	- 5/8" Bore CRS
28929	- 5/8" Bore Stainless Steel
28930	- 1/2" Bore Stainless Steel
28931	- 3/8" Bore Stainless Steel
28932	- 1/4" Bore Stainless Steel
B-PISTON	
34180	- 1/4" Diameter 303 SS
34182	- 3/8" Diameter 303 SS
34184	- 1/2" Diameter 303 SS
34186	- 5/8" Diameter 303 SS
C-PACKING NUT	
32972	- 1/4" Bore
32973	- 3/8" Bore
32974	- 1/2" Bore
32975	- 5/8" Bore
D-PACKING SET	
33420	- 1/4" Bore (Neoprene - Standard)
33421	- 3/8" Bore (Neoprene - Standard)
33422	- 1/2" Bore (Neoprene - Standard)
33423	- 5/8" Bore (Neoprene - Standard)
33427	- 1/4" Bore (TFE - Optional)
33428	- 3/8" Bore (TFE - Optional)
33429	- 1/2" Bore (TFE - Optional)
33430	- 5/8" Bore (TFE - Optional)
E-GREASE GLAND	
28380	- 1/4" Bore
28380	- 3/8" Bore
28381	- 1/2" Bore
28381	- 5/8" Bore

PART #	DESCRIPTION
F-PUMP HEAD	
28821	- 1/4" Bore Stainless Steel S-Series
28823	- 3/8" Bore Stainless Steel S-Series
28825	- 1/2" Bore Stainless Steel S-Series
28826	- 5/8" Bore CRS
28827	- 5/8" Bore Stainless Steel S-Series
J24960	- Coupling Nut (2 req)
J41667	- Double Ball Check Valve Cartridge (Suction)
J41669	- Double Ball Check Valve Cartridge (Discharge)

SERIES 500 PARTS

20579	- SS Ball 7/16" (2 req)
20580	- SS Ball 11/16" (2 req)
20704	- S500 Base (Simplex or Duplex)
21970	- Bronze Bushing
25004	- Delrin Motor Coupling Assy
29290	- Housing Set Assy 115 SPM Simplex-Duplex
29291	- Housing Set Assy 115 SPM Duplex
29247	- Housing Set Assy S500 Simplex-Duplex
29248	- Housing Set Assy S500 Duplex
32590	- Motor 1/3" HP 56 FR, 115V, Open
33082	- O-Ring, Head Cap, VT-1,859 x ,139
33083	- O-Ring, Head Cap, VT-2,359 x ,139
33767	- Pin - Suction Check Valve
J35913	- Speed Reducer, 115 SPM
J35916	- Speed Reducer, 57 SPM
J35918	- Speed Reducer, 29 SPM
37053	- Piston Set Screw
37306	- PVC Seal (2 req)
38710	- Spacer, packing 1"
38711	- Spacer, packing 1-1/4"
38712	- Spacer, packing 1-1/2"
38986	- Spring-Packing Compression 1"
38987	- Spring-Packing Compression 1-1/4" & 1-1/2"
38989	- Valve Spring
41673	- Discharge Check Valve Assy 1/2" FPT
41675	- Suction Check Valve Assy 1/2" FPT
J61523	- Kit, Coupling Chain (1 - 24976, 1 - 33765, 1 - 36400)
J61531	- Kit, Main Bearing Cam (1 - 22263, 1 - 33771)
J61536	- Kit, Coupling Shaft (1 - 24984, 1 - 37059, 1 - 37047)
J61537	- Kit, Main Shaft (1 - 30121, 1 - 37894)
G-SERIES 500 PUMP HEAD	
28828	- 1" Bore CRS
28829	- 1" Bore Stainless Steel S-SERIES
28831	- 1-1/4" Bore Stainless Steel S-SERIES
28831	- 1-1/2" Bore Stainless Steel S-SERIES
G-SERIES 500 PUMP HEAD CAP	
28840	- 1" CRS
28841	- 1" Stainless Steel
28843	- 1-1/4" & 1-1/2" Stainless Steel
H-SERIES 500 PISTON	
34188	- 1" Diameter 303 SS
34189	- 1-1/4" Diameter 303 SS
34190	- 1-1/2" Diameter 303 SS
I-SERIES 500 PACKING SET	
33424	1" Bore (Neoprene - Standard)
33425	1-1/4" Bore (Neoprene - Standard)
33426	1-1/2" Bore (Neoprene - Standard)
33431	1" Bore (TFE - Optional)
33432	- 1-1/4" Bore (TFE - Optional)
33433	- 1-1/2" Bore (TFE - Optional)
J-SERIES 500 PISTON HEAD ASSEMBLY	
28933	1" Bore CRS
28934	1" Bore Stainless Steel
28935	1-1/4" Bore CRS
28936	- 1-1/4" Bore Stainless Steel
28937	1-1/2" Bore CRS
28938	1-1/2" Bore Stainless Steel

*Series 400-500 1" parts are interchangeable.

MEC-O-MATIC DIAPHRAGM PUMPS

STINGRAY Series 100 & 200

Mec-O-Matic STINGRAY 100 and 200 Series Selection Guide		US			BCA	K	XXX
MODELS:	Series 100 105 = 8.0 gpd (1.26 lph) max pres.: 100 PSI (6.90 BAR) 110 = 12.0 gpd (1.89 lph) max pres.: 100 PSI (6.90 BAR) 125 = 30.0 gpd (4.73 lph) max pres.: 100 PSI (6.90 BAR) 150 = 60.0 gpd (9.46 lph) max pres.: 100 PSI (6.90 BAR) 175 = 90.0 gpd (14.19 lph) max pres.: 60 PSI (4.14 BAR) Series 200 205 = 8.0 gpd (1.26 lph) max pres.: 100 PSI (6.90 BAR) 210 = 12.0 gpd (1.89 lph) max pres.: 100 PSI (6.90 BAR) 225 = 30.0 gpd (4.73 lph) max pres.: 100 PSI (6.90 BAR) 250 = 60.0 gpd (9.46 lph) max pres.: 100 PSI (6.90 BAR) 275 = 90.0 gpd (14.19 lph) max pres.: 60 PSI (4.14 BAR)						
ELECTRICAL:	XA = 115V, 60 Hz XL = 230V, 50/60 Hz						
LIQUID END MATERIALS:	BCA = PVC / Viton / Ceramic						
CONNECTION SIZES:	K = Tubing .38" PVC Suction / .38" PE Discharge						
SUFFIX CODES:	XXX = Standard						
A completed model should look like "US110XA-BCAKXXX"							

1. Maximum GPD Rating is at Zero PSI.
2. Standard material of construction is: PVC head/fittings, Viton Seats, PTFE faced diaphragm, spring loaded ceramic balls, 4 ft. 3/8" PVC suction tubing, 8 ft. 3/8" polyethelene discharge tubing.
3. KOPkit includes head assembly, diaphragm and head screws.
4. Shipping weight is 8 lbs

STINGRAY Electro Mechanical Series

Mec-O-Matic STINGRAY ELECTRO MECH. Selection Guide		US			XA	BCA	K	XXX
MODELS:	105 = 8.0 gpd (1.26 lph) max pres.: 100 PSI (6.90 BAR) 110 = 12.0 gpd (1.89 lph) max pres.: 100 PSI (6.90 BAR) 205 = 8.0 gpd (1.26 lph) max pres.: 100 PSI (6.90 BAR) 210 = 12.0 gpd (1.89 lph) max pres.: 100 PSI (6.90 BAR)							
TIMER:	D = 24 Hour Timer W = 7 Day Timer							
ELECTRICAL:	XA = 115V, 60 Hz							
LIQUID END MATERIALS:	BCA = PVC / Viton / Ceramic							
CONNECTION SIZES:	K = Tubing .38" PVC Suction / .38" PE Discharge							
SUFFIX CODES:	XXX = Standard							
A completed model should look like "US110XADXABCAXXXX"								

1. Available in 115V 60 cycle only.
2. Maximum GPD Rating is at Zero PSI.
3. Standard material of construction is: PVC head/fittings, Viton Seats, PTFE faced diaphragm, spring loaded ceramic balls, 4 ft. 3/8" PVC suction tubing, 8 ft. 3/8" polyethelene discharge tubing.

MEC-O-MATIC

KOPkits

Mec-O-Matic STINGRAY KOPkit Selection Guide		KUSR_	BCA	K
PRODUCT DESIGNATOR:	1 = Series 100 2 = Series 200			
LIQUID END MATERIALS: Head, Diaph., Seats & Balls	BCA = PVC / Viton / Ceramic			
CONNECTION :	K = Tubing .38" PVC Suction / .38" PE Discharge			

STINGRAY SERIES PARTS PRICE SCHEDULE

PART #	DESCRIPTION	PART #	DESCRIPTION
41403	Discharge Tubing 8 ft PE 3/8"	U8800656	Kit, SR Drive Block Conversion
J41424	Suction tubing 4 ft PVC 3/8"	U8800701	Head Assembly Series 100
U0810545	Spring Clutch	U8800703	Head Assembly Series 200
U0811279	Pump Head Series 200	U8800704	Valve Kit Series 200 (viton)
U0817888	Shoulder Screw 10 - 24 X .58	U8800729	Kit, Head Bolt S100 (4 - U0810036, 4 - L9801300-188)
U0811861	Head Cover Series 100	U8800730	Kit, Head Bolt S200 (4 - U0813501, 4 - L9801300-188)
U0812318	Pump Head Series 100	U8800732	Kit, Foot Pads (4 - U0818379)
U0814211	Compression Nut	U8800735	Kit, Spring (2 - U0812915)
U0818143	Drive Block	L9900700-000	Strain Relief
U0818148	Drive Plate	U0818406	Motor, SR 105/205, 120V, 60Hz
U0818215	Motor Housing	U0818407	Motor, SR 105/205, 240V, 50/60Hz
U0818226	Regulator Housing	U0818408	Motor, SR 110/210, 120V, 60Hz
U0818227	Regulator Top Cover	U0818409	Motor, SR 110/210, 240V, 50/60Hz
U0818256	Output Adjustment Knob	U0818410	Motor, SR 125/225, 120V, 60Hz
U0818257	Wear Plate	U0818411	Motor, SR 125/225, 240V, 50/60Hz
U0818258	Adjustment Knob Bushing	U0818412	Motor, SR 150/250, 120V, 60Hz
U0818339	Adjustment Plate	U0818413	Motor, SR 150/250, 240V, 50/60Hz
U0818340	Adjustment Shaft Assembly	U0818414	Motor, SR 175/275, 120V, 60Hz
U8800412	Tubing Assy, 15', 3/8"	U0818415	Motor, SR 175/275, 240V, 50/60Hz
U8800456	Foot Valve Strainer 3/8" OD Tubing (viton)	24820	Power Cord 120V
U8800470	Diaphragm Kit	24821	Power Cord 240V
U8800525	Relief/Release Plunger Kit (viton)	U0818561	Timer Assy, 24 hr (SR Electro Mech)
U8800554	Cartridge Valve Kit Series 100 (viton)	U0818562	Timer Assy, 7 Day (SR Electro Mech)
U8800606	Injection Fitting	U0818564	Motor Fan SR 105, 110, 205, 210

MISCELLANEOUS TUBING

PART NUMBER	DESCRIPTION	PART NUMBER	DESCRIPTION
U0811307	Tube PE, Transparent, 1/4" OD X 100 ft.	U0818324	Viton Peri. Tube, 3/8" OD X 9'

MEC-O-MATIC WAREWASH PUMPS

Series T-2000 Misting System

Mec-O-Matic Series T-2000 Selection Guide		US275	XA	BCXX112
MODELS:	US275 = 6 oz. per minute max pres.: 100 PSI (6.90 BAR)			
ELECTRICAL:	XA = 115V, 60 Hz			
LIQUID END MATERIALS:	BCXX112 = PVC / Viton / Ceramic			

1. Standard system includes SR275 pump, 24 hour timer, spray nozzle and tubing in a lockable metal cabinet with an industrial gray finish.
2. Available in 115 volt only.

Mec-O-Matic PERISTALTIC PUMPS

Dolphin Series

Mec-O-Matic DOLPHIN Series Selection Guide		UD__	---	---	---	U	XXX
MODELS:	10 = 13.0 gpd (2.05 lph) max pres.: 25 PSI (1.72 BAR) 50 = 60.0 gpd (9.46 lph) max pres.: 25 PSI (1.72 BAR) 75 = 97.0 gpd (15.30lph) max pres.: 25 PSI (1.72 BAR)						
ELECTRICAL:	XA = 115V, 60 Hz XL = Standard 230V, 50/60 Hz, used w/ Model 10 only XB = Standard 230V, 50 Hz, used w/ Models 50 & 75 only XC = Standard 230V, 60 Hz, used w/ Models 50 & 75 only						
LIQUID END MATERIALS:	LSA = Norprene Tubing LBA = Viton Tubing						
CONNECTION SIZES:	U = Tubing .44" I.D. X .25" O.D.						
SUFFIX CODES:	XXX = Standard						
A completed model should look like "UD75-XA-LBAUXXX"							
Mec-O-Matic DOLPHIN KOPkit Series Selection Guide							
KUDXX-LSAU	= Standard KOPkit for all Dolphin Pumps (includes head& tube assembly)						

Junction Box option is available on 230V models at no additional charge. Contact the factory for model numbers. Shipping weight for Dolphin Pumps is 7 lbs.

DOLPHIN SERIES PARTS PRICE SCHEDULE

PART NUMBER	DESCRIPTION	PART NUMBER	DESCRIPTION
J60552	Strainer Assembly w/o valve	U0818616	Gearmotor Assembly, 120V, 10 RPM - D10
24820	Power Cord 120V	U0818617	Gearmotor Assembly, 240V, 10 RPM - D10
24821	Power Cord 240V	U0818618	Gearmotor Assembly, 120V, 50 RPM - D50
U0817630	Lead Assembly	U0818619	Gearmotor Assembly, 240V, 50 RPM - D50
U0817635	Knob	U0818620	Gearmotor Assembly, 120V, 75 RPM - D75
U0817923	Switch, Rocker	U0818621	Gearmotor Assembly, 240V, 75 RPM - D75
U0817942	Screw 10 - 32 X .688", Motor Mount	U8800431	Tubing cut 1/4" X 15 ft. PE
U0819142	Box, Front	U8800637	Tubing Replacement Kit (7/16"Norprene Crm)
U0819143	Box, Back	U8800651	Pump Head Assembly
U0818180	Potentiometer Assembly	U8800712	Injection Fitting
U0818564	Fan D10 (CW)	U8800740	Kit, Timer 120V (1 - U0818183, 1 - U0020522)
U0818565	Fan D50, D75 (CCW)	U8800741	Kit, Timer 240V (1 - U0818460, 1 - U0020522)
U0812955	Screw 8 - 32 X 1/4", Fan	U8800742	Kit, Pump Head Bearings (2 - U0817121)
L9900700-000	Strain Relief	U8800743	Kit, Collars (2 - U0817123)
		U8800758	Kit, Pump Head Tubing (Viton)

MEC-O-MATIC PERISTALTIC PUMPS

VSP Series

Mec-O-Matic VSP Series Selection Guide		UVSP	---	---	---	U	XXX
MODELS:	12 = 12.0 gpd (1.89 lph) max pres.: 25 PSI (1.72 BAR)						
	20 = 20.0 gpd (3.15 lph) max pres.: 25 PSI (1.72 BAR)						
ELECTRICAL:	XP = 24VAC						
	XR = 120V 50/60 Hz						
LIQUID END MATERIALS:	LLA = Norprene Tubing						
	LBA = Viton Tubing						
CONNECTION SIZES:	U = Tubing .38" I.D. X .19" O.D. used w/ UVSP12 only						
	U = Tubing .44" I.D. X .25" O.D. used w/ UVSP20 only						
SUFFIX CODES:	XXX = Standard						
A completed model should look like "UVSP12XRLLAUXXX"							

Shipping weight for all VSP pumps is 6 lbs.

VSP SERIES PARTS PRICE SCHEDULE

PART NUMBER	DESCRIPTION
J60552	Strainer w/o Valve
U0817122	Collar VSP - 12
U0817123	Collar VSP - 20
U0817742	Hose Clamps
U0817923	Switch
24820	Power Cord 120 V
U0819142	Front Housing
U0819143	Rear Assembly
U0818071	Lead Assembly
U0818083	Hole Plug
U0818305	Printed Circuit Board 24V
U0818306	Printed Circuit Board 120V
U0818320	Power Cord 24V
U0818463	Fuse 24V, 1/2 Amp
U0818464	Fuse 120V, 1/8 Amp
U0818667	Gearmotor Kit
U7013397	Tube Kit VSP - 20
U8800431	15" X 1/4" Poly Tubing
U8800651	Pump Head Kit
U8800700	Tube Kit VSP - 12
U8800712	IPF Auto Clean Injection Fitting
U8800739	Kit, Motor Mount (2 - U0818666, 2 - 32946, 2 - U0811297)
U8800742	Kit, Pump Head Bearings (2 - U0817121)
L9900700-000	Strain Relief

MEC-O-MATIC PERISTALTIC PUMPS

Series 2400T Grease Trap Dispenser

Mec-O-Matic 2400T Series Selection Guide		UT24			U	
MODELS:	UT24 = 2.5 gpd (0.39 lph) max pres.: 25 PSI (1.72 BAR) used w/ 2400T & 2400T PLUS UT24 = 3.0 Oz / 1 Min max pres.: 25 PSI (1.72 BAR) used w/ 2400T-DC only					
ELECTRICAL:	-XA = 115V, 60 Hz used w/ 2400T only PXA = 115V, 60 Hz used w/ 2400T PLUS only -AD = 12V DC used w/ 2400T-DC only					
LIQUID END MATERIALS:	LT = Silicone Tubing LB = Viton Tubing LL = Norprene Tubing used w/ 2400T-DC only					
CONNECTION SIZES:	AU = Tubing .31" I.D. X .125" O.D. XU = Tubing .44" I.D. X .25" O.D. used w/ 2400T-DC only					
SUFFIX CODES:	XXX = Standard 109 = Lockabke Latch Cover used w/ 2400T PLUS only					
A completed model should look like "UT24-XA-LBAUXXX"						

- 2400T comes standard with 24 hour mechanical timer. 2400T plus and DC utilizes a 7 day, 8 event programmable timer
- 2400T DC Pump requires 8 "D" cell batteries (not included).
- Shipping weight is 7.5 lbs.

2400T & T PLUS SERIES PARTS PRICE SCHEDULE

PART NUMBER	DESCRIPTION	PART NUMBER	DESCRIPTION
J60552	Strainer Assembly w/o Valve	U0819143	Pump Housing (rear)
U0814047	Wire Clip	U0818061	Toggle Switch
U0817131	Tubing Assy 5/16" X 9" Silicone	U0818084	Lead Assembly 4.5" Yellow (2) Timer
U0817133	Pump Cover (Backing Plate)	U0818564	Fan
U0817742	Hose Clamp	U0818602	Gearmotor Assembly
U0817888	Pump Head Screw	U0818740	Timer (2400T Plus)
U0817942	Screw 10 - 30 X .688", Motor Mount	U8800431	15' X 1/4" PE Tubing
U0817952	Timer (2400T)	U8800712	Injection Fitting
U0818018	Indicator Light	U8800753	Pump Head Assembly Kit (No Tubing)
U0819145	Pump Housing (front-2400T Plus)	U0812955	Hex Screw 8 - 32 X 1/4"
U0819144	Pump Housing (front-2400T)	L9900700-000	Strain Relief

2400T DC SERIES PARTS PRICE SCHEDULE

PART NUMBER	DESCRIPTION	PART NUMBER	DESCRIPTION
U0812955	Screw 6 - 32 X .25" PHP	U0818902	Battery Holder Assembly
U0817888	Shoulder Screw	U0818903	Low Battery Board Assembly
U0818026	Spacer SST (Motor)	U0818904	Ground Wire Connection
U0818061	Toggle Switch	U0819037	12V DC Timer LO AMP
U0818666	Screw 8 - 32 X 1.25 FHP	U8800490	Injection Fitting
U0818881	12V DC Motor	U8800637	7/16" Tubing Kit (Peristaltic)
U0818888	PVC Spacer (Timer)	U8800651	Pump Head Assembly Kit (No Tubing)
U0818895	1/4" X 20' Tubing PE	U8800700	3/8" Tubing Kit
U0818897	Housing Assembly w/lock	U8800742	Kit, Pump Head Bearings (2 - U0817121)
U0818901	Lock Nuts (10-24 NY - Lock)		

Policies and Procedures

1. Manufacturer's Equipment Warranty

- a. Pulsafeeder warrants all pumps and controllers of its manufacture to be free of defects in material or workmanship. Liability under this policy extends for 24 months from date of shipment from the factory. The manufacturer's liability is limited to repair or replacement of any failed equipment or part which is proven defective in material or workmanship upon manufacturer's examination. This warranty does not include removal or installation costs and in no event shall the manufacturer's liability exceed the selling price of such equipment or part.
- b. The manufacturer disclaims all liability for damage to its products through improper installation, maintenance, use or attempts to operate such products beyond their functional capacity, intentionally or otherwise, or any other unauthorized repair. The manufacturer is not responsible for consequential or other damages, injuries or expense incurred through the use of its products.
- c. The above warranty is in lieu of any other warranty, whether expressed or implied. The manufacturer makes no warranty of fitness or merchantability. No agent of ours is authorized to provide any warranty other than the above.

2. Pulsafeeder's Parts and Accessory Warranty

- a. Pulsafeeder, Inc. warrants parts and accessories provided to be free of defects in material or workmanship. Unless otherwise noted below, liability under this policy extends for 90 days from date of shipment from the factory when sold as service parts. (Replaceable elastomeric parts are expendable and are not covered by any warranty either expressed or implied.)
- b. This policy is extended to a full 12 months from the date of installation or 18 months from shipment from the factory whichever comes first on the following accessories:
 Intelliscan
 Digital Glycol Feeders
 Analog Timers
 Water Meters
 Flow Controllers
- c. MicroTrac and MicroVision toroidal probes are warranted for 24 months from date of shipment from the factory when purchased in conjunction with the controller.
 All other electrodes/probes and sensors are considered maintenance items and such are warranted for six (6) months from the date of shipment when purchased in conjunction with the controller.
 Any electrodes/probes and sensors purchased as spare parts are warranted for 90 days from date of shipment.
- d. The manufacturer's liability is limited to repair or replacement of any failed equipment or part which is proven defective in material or workmanship upon manufacturer's examination. This warranty does not include removal or installation costs and in no event shall the manufacturer's liability exceed the selling price of such equipment or part.
- e. The manufacturer disclaims all liability for damages to its products through improper installation, maintenance, use or attempts to operate such products beyond their functional capacity, intentionally or otherwise, or any unauthorized repair. The manufacturer is not responsible for consequential or other damages, injuries or expense incurred through the use of its products.
- f. The above warranty is in lieu of any other warranty, whether expressed or implied. The manufacturer makes no warranty of fitness or merchantability. No agent of ours is authorized to provide any warranty other than the above.

3. Process for All Returned Goods

- a. Please contact our Customer Service Department to request a RMA (Return Material Authorization) number prior to returning any goods. The following information will be required:
 Billing and ship-to address
 Model number and serial number
 Contact name and phone number
 Reason for return
 Purchase order (where applicable)
 A packing slip will be provided to the shipper and MUST accompany the product being returned. Packages received without our proper packing list will be refused by the receiver.
- b. All material must be returned freight prepaid.
- c. All material must be properly packaged to prevent damage in shipment.
- d. All products MUST be wiped and flushed clean of any and all chemicals, solvents or buffers and be warranted to be safe for handling. You will be requested to acknowledge the condition of the product being returned on our packing list. Any product received that is deemed to be unsafe for handling or without this acknowledgement will be refused by our receiver.
- e. RMA for returning product for credit is effective for 90 days from the date of issue. After 90 days if the product has not been returned to Pulsafeeder the RMA number will be cancelled, and a new request must be made by the customer to continue with the return procedure.

4. Non-Warranty Return Procedure

- a. If you are experiencing a concern with your Pulsafeeder product, first consult the distributor, dealer or Regional Sales Manager or the operation and maintenance manual for assistance. If service of your non-warranty unit is necessary, you must request a return material authorization. A RMA form will be issued and must be used as the packing list attached to the outside of the box. Please send the unit freight prepaid with the RMA number visibly displayed on the outside of the carton. All products MUST be wiped and flushed clean of any and all chemicals, solvents or buffers and be warranted to be safe for handling. You will be requested to acknowledge the condition of the product being returned on our packing list. Any product received that is deemed to be unsafe for handling or without this acknowledgement will be refused by our receiver.
- b. The charges listed in the following table will apply.

Product	Repair Cost
Pumps and Pump Accessories – within 5 years of sale date	Current List Price x .50 x Part Discount Multiplier
Controllers and Controller Accessories within 5 years of sale date	Current List Price x .50 x Part Discount Multiplier
Any item older than 5 years from date of sale	With purchase order, \$50 bench fee to evaluate. The \$50 bench fee may be applied towards repair cost of unit or towards a new controller

- c. Extended warranty on repair goods will be offered only when the repairs were made by the factory on non-warranty units.
 - i. Microprocessor Controls – 1 year from date of shipment
 - ii. Electronic Controls – 6 months from date of shipment (excluding electronic parts)
 - iii. Standard metering pumps – 3 months from date of shipment

- 5. Credit for Return of New, Unused Equipment**
- No equipment will be accepted beyond six months after date of shipment from factory for credit.
 - Only new, unused and undamaged standard equipment will be accepted for return to stock.
 - All credits are based on evaluation and acceptance of material as new and unused by Pulsafeeder. You will be requested to acknowledge the condition of the product being returned on our packing list. Any product received that is deemed to be unsafe for handling or without this acknowledgement will be refused by our receiver.
 - A restocking fee of 25% will apply to returned goods. When a PO is provided for a replacement item at the time of the return request the restocking fee will be 15%. Note: any product mounted on a panel or skid will be charged a 50% re-stocking fee.
 - A request for a Returned Material Authorization (RMA) number must be made prior to returning product to Pulsafeeder.
 - All equipment shall be returned with the RMA Packing List form attached to the outside of the box.
 - If any chemical, solvent or buffer has been introduced into the product it must be wiped and flushed clean of any and all substances prior to returning to Pulsafeeder.
 - All material shall be returned freight prepaid.
 - Private label products or Engineered Panel Mount Systems are not returnable.
- 6. Pricing Errors**
- Pulsafeeder does their very best to avoid errors in billing. You will receive a confirmation of your order within 24 hours of order entry. If upon review the customer feels there is a discrepancy, they should contact Pulsafeeder Customer Service as soon as possible to resolve.
 - Should an invoice be received that the customer believes to have incorrect pricing, they should notify Pulsafeeder Customer Service to investigate.
- 7. Missing Items**
- If a product is received by the customer with an item missing the customer must notify Pulsafeeder Customer Service within 7 days of receipt of the product by the end user. A replacement item will be sent at no charge as quickly as possible.
 - If a shipment is received by the customer with a line item missing they must notify Pulsafeeder Customer Service within 7 days of receipt of the product by the end user. If the customer had been billed for that item, a credit will be issued against the original Sales Order and a new Sales Order will be created for the replacement product.
- 8. Damaged Items**
- Should the customer receive an order that was damaged in transit, the customer must notify the carrier directly to initiate a claim on the day of delivery.
 - Should the customer receive a product with damaged components due to improper packaging they should notify Pulsafeeder Customer Service within 7 days of receipt of product by end user. A replacement item will be sent at no charge as quickly as possible.
- 9. Technical Support Services Available**
- Pulsafeeder's Technical Sales Support team is available *to provide all your sales and support needs. The principle mission of this group is to sell and support our customer base in a timely and effective manner. This includes the ability to provide in-field service training, assistance in start-up of our products and perform field repair of goods when required.*
 - Scope
Pulsafeeder, Inc. factory Field Service Technicians are available throughout the World for field services on all Pulsafeeder products. Services include:
 - Maintenance Training Seminars, including Classroom slide presentations and or Hands-on Training. The seminar will take approximately four to five hours, and if time permits minor repair and or adjustments may be made to the customer's pumps, controllers or accessories.
 - Pre-start up inspections and start up testing/calibration of pumps, controllers and accessories.
 - Field repairs of pumps controllers and accessories
 - Diagnosing and recommending solutions to systems problems.

Fee Schedule	Service Rate ⁽¹⁾
Field Repairs and Start-ups	
Normal 8 hour day	\$98.00/hour
Overtime (in excess of 8 hrs, each day)	\$148.00/hour
Sundays, National Holiday	\$195.00/hour
Travel time to job site and return	\$87.00/hour
Travel expenses (air fare, hotel, car and meals)	Chargeable to customer at cost
Minimum charge	4 hours labor, plus travel time and expenses
End User Training Seminars	
Normal work day	\$750.00/day plus expenses (air fare, car rental, hotel and meals at cost)
Sundays, National Holiday	\$1495.00/day plus expenses (air fare, car rental, hotel and meals at cost)

⁽¹⁾ All rates listed in this section are actual hourly and daily rates, not reference rates

TERMS & CONDITIONS

- 1 . AGREEMENT. The contract of sale resulting from Seller's documentation together with these terms and conditions ("Contract") constitutes the entire agreement between the parties hereto, except as modified in writing signed by both the Seller and Purchaser. The Seller is Pulsafeeder, Inc. and the Purchaser is identified in the Contract. Any terms in a purchase order, irrespective of their materiality, which are either different from or additional to Seller's conditions of sale, are objected to and are excluded unless the Seller expressly agrees in writing to such terms. Execution of such forms by Seller to accommodate Purchaser's procurement or accounting procedures or to evidence agreed up on change orders shall not be construed as assent to Purchaser's terms. Acceptance of the goods shipped shall constitute assent to Seller's conditions of sale. This Contract shall be binding up on Purchaser and Seller, and on their successors and assigns.
- 2 . PROPOSAL OR QUOTATION. A proposal shall not become binding up on Seller until it has been executed and returned by Purchaser. An oral quotation shall not be considered an offer: only a written confirmation thereof incorporating Seller's terms and conditions shall constitute an offer.
- 3 . CREDIT. Credit terms of payment must have the approval of Seller's Credit Department and must be specified in writing on Seller's invoice or in the Contract. If Purchaser's credit is found by Seller to be unsatisfactory . Seller may rescind or terminate this Contract. If at any time during the term of this Contract Purchaser's financial responsibility becomes impaired or unsatisfactory to Seller, Seller reserves the right to stop shipment on notification to Purchaser, project owner and surety with a demand for payment in advance or at time of delivery for future deliveries or to require other security satisfactory to Seller and in the absence thereof, to cancel the unfilled portion of the Contract. Seller will notify Purchaser promptly of its decision to stop shipments and give an advance notice to the extent this is possible. In the absence of credit terms, sales are for cash.
- 4 . PAYMENT. Specific terms of payment for this order shall be set forth on the reverse side of this Contract or identified and appended hereto. Purchaser agrees to make payment at Seller's location specified in this Contract in lawful money of the United States. Purchaser further agrees to make all payments when due to Seller in accordance with the agreed terms of payment in this Contract without reference to Purchaser's agreement with or payments by the owner and with no right of retention.
- 5 . INTEREST AND COSTS. Purchaser agrees to pay interest at 1.5% per month (to the extent permitted by law) on all delinquent balances if and when assessed by Seller, and any attorney's fees or court costs arising out of and made necessary in collection of its obligation to Seller created by this Contract.
- 6 . TAXES. Any federal, state or local tax assessment, fee, duty or charge hereafter imposed on or measured by the products purchased hereunder shall be for Purchaser's account unless Purchaser furnishes Seller an acceptable exemption certificate from such tax, fee, duty or charge prior to shipment.
- 7 . FORCE MAJEURE. Seller shall make delivery in accordance with the terms of this Contract or within a reasonable time in the absence of any commitment, but Seller shall not be liable for delays or defaults in delivery caused by floods, fires, storms, or other acts of God, by war or act of public enemy (or civil disturbance), strikes, lock outs, shortages of labor or raw materials and supplies (including fuel) or production facilities, transportation service or equipment shortages or failures, action of any governmental authority or other conditions beyond Seller's reasonable control.
- 8 . CANCELLATION. If Purchaser desires to cancel or change any portion of this Contract, he must make such request in writing to Seller. Seller may, in its sole discretion, accept or reject any such request. If accepted, the Purchaser nonetheless must take delivery and make payment to Seller for all material manufactured and in process of manufacture at time of notice, and all special materials ordered at time of notice and for which Seller must take delivery , unless otherwise agreed by Seller in writing. All such materials must be removed from Seller's premises within 30 days after payment and payment will due at time of notice. Seller also reserves the right to make a cancellation charge in the event of cancellation by the Purchaser of an order placed in Seller's shipping schedule and acknowledged by Seller.
- 9 . INSPECTION AND TESTING . Seller's standard specifications and tests apply to all orders. All charges for inspections or tests not regularly furnished are for Purchaser's account and subject to prior negotiation. All inspections shall be conducted at Seller's plant, and failure of Purchaser to avail himself of inspection privileges shall be deemed a waiver of such privileges.
- 10 . PRICES. Prices are subject to change without notice. Orders based on published prices and accepted for scheduled shipment will be invoiced at Seller's applicable price in effect on the scheduled date of shipment, unless otherwise specifically noted on the order acknowledgment. All prices will be in accordance with applicable government regulations. Orders specifying palletizing or special packaging will involve special charges.
- 11 . DELAYS. All orders are accepted subject to Seller's ability to make delivery at the time and in the quantities specified, and Seller shall not be liable for damages for failure to make partial or complete shipment or for any delay in making shipments. Purchaser shall be liable for any added expenses incurred by Seller because of Purchaser's delay in furnishing requested information to Seller, delay resulting from order changes by Purchaser, or delay in unloading shipments at delivery point.
- 12 . SHIPMENT. Seller will select method of shipment and routing when transportation charges are for account of Seller. When shipping instructions are specified by the Purchaser, all costs will be for the account of the Purchaser. The foregoing includes, but is not limited to, carriers charges for notification prior to delivery, demurrage, delay in unloading, diversion, or reconsignment.
- 13 . TITLE. Title to products transfers up on delivery to Purchaser at the F.O.B. point of delivery which will be clearly set forth in the shipment terms of this Contract. On receipt of title, Purchaser is then responsible for proper protection of product, placement, compliance with all regulations and ordinances, and will indemnify Seller against all claims for personal injuries or property damage arising from the storage, use or handling of such products.
- 14 . IN TRANSIT CLAIMS. Claims for damage or shortage in transit must be made against the carrier by the owner of the shipment according to the F.O.B. terms of the Contract. Purchaser has the responsibility to inspect shipments before or during unloading to identify any such damage or shortage and see that appropriate notation is made on the delivery tickets or an inspection report furnished by the local agent of the carrier in order to support a claim.
- 15 . CLAIMS. Notice of Claims against Seller hereunder for any reason, must be made to Seller in writing promptly after discovery and within any applicable warranty period. Failure to give such notice to Seller shall constitute a waiver by Purchaser of any right later to assert such a claim.
- 16 . RETURNS. Returned goods shall be accepted for credit only if in salable condition and only with evidence of Seller's prior written consent. Seller will assess charges for freight both ways and any costs necessary to restore such goods to the regular plant inventory . The amount of credit given will depend further up on the degree of salability of products accepted in opinion of Seller.
- 17 . PATENTS. Seller agrees to defend, and to protect Purchaser against loss or damage arising out of any legal action for patent infringement in connection with the manufacture of its products sold to Purchaser, provided Seller is notified promptly of any such action with complete information and is given an opportunity to defend.
- 18 . WARRANTY : LIMITATION OF LIABILITY . Seller warrants title to each individual product sold under this Contract and further warrants for a period of eighteen (18) months from ship date or one (1) year from date of installation, whichever comes first, but only to the extent and limit of the purchase price paid for such individual product, that such product conforms to the specifications set forth in the Contract and is free from defects in material and workmanship under normal service and use for which it was designed. Seller's sole obligation and Purchaser's exclusive remedy under this warranty shall be limited to one of the following, as selected by Seller: delivering to Purchaser a replacement for any product or part thereof determined by Seller to be defective, repairing such product or part, or refunding the purchase price (or an equitable portion thereof) paid for such product or part by Purchaser. SELLER MAKES NO WARRANTY OF FITNESS OR MERCHANTABILITY, AND NO OTHER WARRANTY, WHETHER EXPRESS OR ARISING BY OPERATION OF LAW, COURSE OF DEALING, USAGE OF TRADE OR OTHERWISE IMPLIED SHALL EXIST IN CONNECTION WITH SELLER'S PRODUCTS OR ANY SALE OR USE THERE OF. Purchaser must notify Seller promptly and within the warranty period of any claim under this warranty. Seller's warranty extends only to the first purchaser of a product from Seller or Seller's authorized distributor. All goods not manufactured by Seller are warranted only to the extent of the warranties of the original manufacturer. Seller disclaims any liability arising from tort, including strict liability , and Seller further disclaims any liability (whether arising under this or any other provision of this Contract or otherwise) for any costs (including costs of removal or replacement), liabilities, lost profits, loss of good will or any other general, special, incidental or consequential damages incurred by Purchaser in connection with this Contract or any product purchased there under.
- 19 . LAW . This order shall be governed by and shall be construed by the law of the State of New York .
- 20 . GOVERNMENTAL REGULATIONS. Seller warrants that no code, law, regulation or ordinance of the United States, a state or any other governmental authority or agency or any applicable Executive Order has been violated in the manufacture or sale of the items covered by this Agreement and warrants that the equipment, supplies, and/or articles covered thereby conform with all such requirements.
- 21 . NUCLEAR FINANCIAL PROTECTION. Purchaser agrees to procure and maintain, as available to it, nuclear energy liability insurance, in a form of policy approved by the Nuclear Regulatory Commission, and protection, as available, against liability for nuclear incidents not covered by such insurance through an indemnity agreement, as provided in Section 170 of the Atomic Energy Act of 1954, as amended, or any succeeding comparable statutory provision, and the regulations thereunder. Such financial protection shall be effective prior to the time any equipment purchased from us is used or installed at or in connection with any nuclear facility and shall cover us as an insured party . To the extent that such financial protection is not suitable to Purchaser. Purchaser agrees to use its best efforts to cause such financial protection to be obtained by eligible parties. We will cooperate with Purchaser and representatives of the nuclear energy insurance syndicates in complying with all underwriting requirements and with those insurance recommendations which may be mutually agreed up on. Notwithstanding any representations or warranties made by us elsewhere in these conditions of sale, we shall not be responsible for any bodily injury or property damage liability or any other public liability for any nuclear incidents, whether or not in respect of or arising in connection with use or installation of our equipment at any nuclear facility or in connection with any such facility . Purchaser hereby assumes any liability which might otherwise be imposed up on us and agrees to indemnify us and hold harmless from any such liability and costs or expenses in connection therewith.

