

KVM Accessories

Belkin Secure KVM Mounting Brackets

PART #	DESCRIPTION
F1D006	Desk mount for F1DN10xB/C/P
F1D008	Desk mount for F1DN104E/F/O/W



Belkin Secure Desktop Controller Unit (DCU)

PART #	DESCRIPTION
F1DN002R	4 Button DCU for 4 port Belkin Secure KVM Switches, with LCD Display
F1DN003R	3 Button DCU for 4-16 port Belkin Secure KVM Switches, with LCD Display



Belkin Secure CAC Reader


PART #	DESCRIPTION
F1DN005U	USB Smart Card/CAC Reader



Belkin Smart Cables

SKVM PC Connection Combo Cables, Single Output PC

CONNECTS	DESCRIPTION	PART #	RECOMMENDED USAGE
HDMI to HDMI	HDMI to HDMI High Retention KVM Combo Cable, 6'	F1DN1CCBL-HH-6	F1DN102KVM-UN-3 F1DN104KVM-UN-3
	HDMI to HDMI High Retention KVM Combo Cable, 10'	F1DN1CCBL-HH-10	
DVI DL to HDMI	DVI-D to HDMI High Retention KVM Combo Cable, 6'	F1DN1CCBL-DH-6	
	DVI-D to HDMI High Retention KVM Combo Cable, 10'	F1DN1CCBL-DH-10	
USB-C to DP	USB-C to DP KVM Active Combo Cable, 6'	F1DN1CCBL-CP-6	F1DN102KVM-UN-3 F1DN104KVM-UN-3 F1DN104P-3 F1DN104Q-3
	USB-C to DP KVM Active Combo Cable, 10'	F1DN1CCBL-CP-10	
mDP to DP	MiniDP to DP KVM Combo Cable, 6'	F1DN1CCBL-MP-6	(Single DP Connection)
	MiniDP to DP KVM Combo Cable, 10'	F1DN1CCBL-MP-10	
DP to DP	DP to DP KVM Combo Cable, 6'	F1D9019b06	
	DP to DP KVM Combo Cable, 10'	F1D9019b10	
DVI to DVI	DVI-D to DVI-D KVM Combo Cable, 6'	F1D9012b06	F1DN104B-3 F1DN104C-3 F1DN104Q-3 (DVI connection) F1DN108C-3 F1DN116C-3 F1DN204M-3
	DVI-D to DVI-D KVM Combo Cable, 10'	F1D9012b10	
DP to DVI-D	DP to DVI-D Active Combo Cable, 10'	F1D9017b06	
	DP to DVI-D Active Combo Cable, 6'	F1D9017b10	



F1DN2CCBL-HH-06

Belkin Smart Cables

SKVM PC Connection Combo Cables, Dual Output PC

CONNECTS	DESCRIPTION	PART #	RECOMMENDED USAGE
HDMI to HDMI	Dual-Head HDMI to HDMI High Retention KVM Combo Cable, 6'	F1DN2CCBL-HH-6	F1DN202KVM-UN-3 F1DN204KVM-UN-3
	Dual-Head HDMI to HDMI KVM Combo Cable, 10'	F1DN2CCBL-HH-10	
DVI to HDMI	Dual-Head DVI-D to HDMI KVM Combo Cable, 6'	F1DN2CCBL-DH-6	
	Dual-Head DVI-D to HDMI KVM Combo Cable, 10'	F1DN2CCBL-DH-10	
DVI to HDMI and DP to DP	Dual-Head DVI-D to HDMI and DP to DP KVM Combo Cable, 6'	F1DN2CC-DHPP-6	
	Dual-Head DVI-D to HDMI and DP to DP KVM Combo Cable, 10'	F1DN2CC-DHPP-10	
USB-C to DP	Dual-Head USB-C to DP Active KVM Combo Cable, 6'	F1DN2CCBL-CP-6	F1DN202KVM-UN-3 F1DN204KVM-UN-3 F1DN104Q-3 (Dual DP Connection) F1DN104W-3
	Dual-Head USB-C to DP Active KVM Combo Cable, 10'	F1DN2CCBL-CP-10	
mDP to DP	Dual-Head MiniDP to DP KVM Combo Cable, 6'	F1DN2CCBL-MP-6	
	Dual-Head MiniDP to DP KVM Combo Cable, 10'	F1DN2CCBL-MP-10	
DP to DP	Dual-Head DP to DP KVM Combo Cable, 6'	F1D9020b06	
	Dual-Head DP to DP KVM Combo Cable, 10'	F1D9020b10	
DVI to DVI	Dual-Head DVI-D to DVI-D KVM Combo Cable, 6'	F1D9014b06	F1DN104E-3 F1DN104F-3 F1DN108F-3
	Dual-Head DVI-D to DVI-D KVM Combo Cable, 10'	F1D9014b10	

SKVM Monitor or Video Only Cables

CONNECTS	DESCRIPTION	PART #	RECOMMENDED USAGE
DP to DP	DP to DP Cable, 6'	F1DN1VCBL-PP-6	F1DN102KVM-UN-3 F1DN104KVM-UN-3 F1DN202KVM-UN-3
	DP to DP Cable, 10'	F1DN1VCBL-PP-10	
HDMI to HDMI	HDMI to HDMI Cable, 6'	F1DN1VCBL-HH-6	F1DN102KVM-UN-3 F1DN104KVM-UN-3 F1DN202KVM-UN-3 F1DN204KVM-UN-3
	HDMI to HDMI Cable, 10'	F1DN1VCBL-HH-10	
	HDMI to HDMI Cable, 25'	F8V3311b025	
HDMI to DVI DL	HDMI to DVI-DL Cable, 6'	F1DN1VCBL-DH-6	
	HDMI to DVI-DL Cable, 10'	F1DN1VCBL-DH-10	
DP to mDP	DP to MiniDP Cable, 6'	F1DN1VCBL-MP-6	F1DN102KVM-UN-3 F1DN104KVM-UN-3
	DP to MiniDP Cable, 10'	F1DN1VCBL-MP-10	
DVI-D to DVI-D	DVI-D Dual-Link Cable, 3'	F2E7171-03-DV	F1DN104B-3 F1DN104C-3 3F1DN104E-3
	DVI-D Dual-Link Cable, 10'	F2E7171-10-DV	

Other Cables/Adapters

CONNECTS	PART #	RECOMMENDED USAGE
CAC	F1D9013b06	F1D9013b06
	F1D9013b10	F1D9013b10
USB/Audio	F1D9022b06	F1D9022b06
	F1D9022b10	F1D9022b10
DCU	F1D9026-50	F1D9026-50
DVI-A to VGA	F2E4161	F2E4161



Cybersecurity Solutions

THE CHALLENGE

Exponential increases in cyber-attacks present a constant risk to companies' data, IP, and critical infrastructures; thus highlighting the need to extend network isolation to the desktop.

THE SOLUTION

Belkin offers a wide set of NIAP Protection Profile 3.0 certified products designed to maintain air-gap isolation at the desktop while improving operator efficiency and effectiveness.

The ultimate security solution

All Belkin secure switching products are equipped with a host of security features including:

- Optical data diodes assuring unidirectional data flow.
- No shared resources between physically isolated computers.
- Strong authentication and filtering of connected USB devices.
- Secured EDID communication ensuring protection of connected monitors.

Tamper proof system

All Belkin secure switching products are equipped with an end-to-end tamper proof system including:

- Active always-on anti-tamper system disabling product once switch's electronic circuitry is accessed or tampered with.
- A holographic security tamper-evident label on switch enclosure to indicate if product has been opened or compromised.
- Heavy-duty tamper-resistant enclosure with built-in mounting option for simpler desktop deployment.
- Secure "tear-away" packaging for secure delivery of product.

Differences between secure KVM and secure KM switches

Belkin KVMs securely switch control of video, audio, keyboard and mouse between computers. The benefits are many including better space efficiencies, better worker productivity and reduced cost by eliminating extraneous peripherals. Belkin KMs switch only keyboard, mouse and audio while displays are connected directly to their respective computers, enabling full situational awareness across up to 32 monitors. KMs automatically and seamlessly switch channels as operators move the cursor from one monitor to another.

Who are we?

Belkin, a proven technology leader for more than 30 years, provides high-quality customized solutions that align seamlessly to enhance the technologies that businesses, schools, government agencies and other professional organizations depend on for their growth and success. Belkin is dedicated to developing innovative solutions to address the challenges of the modern workplace.



Secure peripheral switching solutions

Secure | Certified | Connected

Contact

For additional product, pricing or general information

For more information visit:
belkin.com/cybersecurity



Product Comparison



Cybersecurity Solutions

Belkin Secure Universal KVM



PART #	F1DN102KVM-UN-3	F1DN202KVM-UN-3	F1DN104KVM-UN-3	F1DN204KVM-UN-3
DESCRIPTION	Secure Universal 2 Port Single Monitor DP/HDMI to DP/HDMI SKVM w/CAC	Secure Universal 2 Port Dual Monitor DP/HDMI to DP/HDMI SKVM w/CAC	Secure Universal 4 Port Single Monitor DP/HDMI to DP/HDMI SKVM w/CAC	Secure Universal 4 Port Dual Monitor DP/HDMI to DP/HDMI SKVM w/CAC
NO. OF COMPUTERS	2	2	4	4
NO. OF DISPLAYS	1	2	1	2
CONSOLE PORTS	3840x2160 pixels (UHD 4K) @60Hz			
MAX RESOLUTIONS SUPPORTED	3840x2160 pixels (UHD 4K) @30Hz, 2560x1600 pixels @30Hz			
CONSOLE MOUSE & KEYBOARD PORTS	USB Type-A female connector (1 designated port for mouse and 1 designated port for keyboard)			
CONSOLE DISPLAY PORTS	1 Combo HDMI 2.0/DP 1.2a	2 Combo HDMI 2.0/DP 1.2a	1 Combo HDMI 2.0/DP 1.2a	2 Combo HDMI 2.0/DP 1.2a
CONSOLE AUDIO JACK	3.5mm female			
REMOTE CONTROL	DCU			
COMPUTER PORTS	USB Type B			
COMPUTER KEYBOARD/MOUSE PORTS	USB Type B			
COMPUTER CAC PORTS	USB Type B			
COMPUTER AUDIO JACK	3.5mm female			
CONSOLE CAC AND BIOMETRICS	USB Type A			
COMPUTER DISPLAY PORTS	1 Combo HDMI 2.0/DP 1.2a	2 Combo HDMI 2.0/DP 1.2a	1 Combo HDMI 2.0/DP 1.2a	2 Combo HDMI 2.0/DP 1.2a
PHYSICAL	Heavy-duty extruded aluminum enclosure with metal faceplate			
ENCLOSURE	Heavy-duty extruded aluminum enclosure with metal faceplate			
DIMENSIONS (W x D x H)	371.5 x 157.5 x 48.3 mm	371.5 x 157.5 x 48.3 mm	371.5 x 157.5 x 48.3 mm	371.5 x 157.5 x 63.5 mm
WEIGHT	1.8 kg.	1.8 kg.	1.8 kg.	2.1 kg.
POWER	12V DC, 1.5A			
POWER REQUIREMENTS	12V DC, 1.5A			
AC INPUT	100 to 240VAC with worldwide interchangeable mains connector			
POWER TYPE	External			

Belkin Secure 2-Port Flip KVM

PART #	F1DN102FLP-DP-3	F1DN102F-3	F1DN102N-3	F1DN102V-3
DESCRIPTION	DP 2-Port, Dual Output FLIP KVM with Audio and Remote Controller	DP 2-Port, Single Output FLIP KVM with Audio and Remote Controller	Secure FLIP 2-Port Ultra High Def KVM with Audio and Remote Controller	Secure FLIP 2-Port DVI-D KVM with Audio and Remote Controller
CONSOLE PORTS	3840x2160 pixels (UHD 4K) @30Hz, 2560x1600 pixels @30Hz			
CONSOLE MOUSE & KEYBOARD PORTS	USB Type-A female connector (1 designated port for mouse and 1 designated port for keyboard)			
CONSOLE DISPLAY PORTS	DisplayPort1.1/1.2	DisplayPort1.1/1.2	HDMI	DVI-D, Single
CONSOLE AUDIO JACK	Via DisplayPort connection			
REMOTE CONTROL	Button RC			
COMPUTER PORTS	USB Type A			
COMPUTER KEYBOARD/MOUSE PORTS	USB Type A			
COMPUTER CAC PORTS	—			
COMPUTER AUDIO JACK	Via DisplayPort connection			
CONSOLE CAC AND BIOMETRICS	—			
COMPUTER DISPLAY PORTS	DisplayPort	DisplayPort	DisplayPort	DVI-D Single-link
PHYSICAL	Impact Resistant ABS Plastic			
ENCLOSURE	Impact Resistant ABS Plastic			
DIMENSIONS (W x D x H)	109.2 x 76.2 x 50.8 mm	109.2 x 76.2 x 25.4 mm	109.2 x 76.2 x 25.4 mm	109.2 x 76.2 x 25.4 mm
WEIGHT	0.82 kg.	0.73 kg.	0.73 kg.	0.73 kg.
POWER	12V, 1.5A DC			
POWER REQUIREMENTS	12V, 1.5A DC	12V, 1.5A DC	12V, 1.5A DC	12V, 1.5A DC
AC INPUT	100-240VAC			
POWER TYPE	External with WW Mains Connectors	External with WW Mains Connectors	External	External

Belkin Secure DVI-I KVM



PART #	F1DN104B-3	F1DN104C-3	F1DN104E-3	F1DN104F-3
DESCRIPTION	Secure DVI-I KVM Switch; 4-Port	Secure DVI-I KVM Switch; 4-Port with CAC	Secure Dual-Head DVI-I KVM Switch; 4-Port	Secure Dual-Head DVI-I KVM Switch; 4-Port with CAC
CONSOLE PORTS	3840x2160 pixels (UHD 4K) @30Hz, 2560x1600 pixels @60Hz			
CONSOLE MOUSE & KEYBOARD PORTS	USB Type-A female connector or PS/2 Mini-DIN 6 pin female connector (1 designated mouse port and 1 designated keyboard port)			
CONSOLE DISPLAY PORTS	DVI-I Dual-link	DVI-I Dual-link	2 x DVI-I Dual-link	2 x DVI-I Dual-link
CONSOLE AUDIO JACK	3.5mm female			
REMOTE CONTROL	DCU			
COMPUTER PORTS	USB Type B			
COMPUTER KEYBOARD/MOUSE PORTS	USB Type B			
COMPUTER CAC PORTS	—			
COMPUTER AUDIO JACK	3.5mm female			
CONSOLE CAC AND BIOMETRICS	—			
COMPUTER DISPLAY PORTS	DVI Dual-link female	DVI Dual-link female	2 x DVI-I Dual-link female	2 x DVI-I Dual-link female
PHYSICAL	Heavy-duty extruded aluminum enclosure with metal faceplate			
ENCLOSURE	Heavy-duty extruded aluminum enclosure with metal faceplate			
DIMENSIONS (W x D x H)	371.5 x 157.5 x 48.3 mm	371.5 x 157.5 x 48.3 mm	371.5 x 157.5 x 63.5 mm	371.5 x 157.5 x 63.5 mm
WEIGHT	1.8 kg.	2.3 kg.	2.3 kg.	2.3 kg.
POWER	12V DC, 1.5A			
POWER REQUIREMENTS	12V DC, 1.5A	12V DC, 1.5A	12V DC, 1.5A	12V DC, 1.5A
AC INPUT	100 to 240VAC			
POWER TYPE	External			

Belkin Secure Displayport KVM



PART #	F1DN104P-3	F1DN104W-3	F1DN104Q-3
DESCRIPTION	Secure Ultra High Def KVM Switch; 4-Port with CAC	Secure DisplayPort Dual-Head KVM Switch; 4-Port with CAC	Secure DisplayPort/DVI Quad-Head KVM Switch; 4-Port with CAC
CONSOLE PORTS	3840x2160 pixels (UHD 4K) @30Hz, 2560x1600 pixels @60Hz		
CONSOLE MOUSE & KEYBOARD PORTS	USB Type-A female connector or PS/2 Mini-DIN 6 pin female connector (1 designated mouse port and 1 designated keyboard port)		
CONSOLE DISPLAY PORTS	1 x HDMI 1.4	2 x HDMI 1.4	3 x HDMI 1.4 & 1 x DVI-I Dual-link
CONSOLE AUDIO JACK	3.5mm female		
REMOTE CONTROL	DCU		
COMPUTER PORTS	USB Type B		
COMPUTER KEYBOARD/MOUSE PORTS	USB Type B		
COMPUTER CAC PORTS	USB Type B		
COMPUTER AUDIO JACK	3.5mm female		
CONSOLE CAC AND BIOMETRICS	—		
COMPUTER DISPLAY PORTS	1 x DisplayPort 1.1/1.2	2 x DisplayPort 1.1/1.2	3 x DisplayPort 1.1/1.2 & 1 x DVI-I Dual-link
PHYSICAL	Heavy-duty extruded aluminum enclosure with metal faceplate		
ENCLOSURE	Heavy-duty extruded aluminum enclosure with metal faceplate		
DIMENSIONS (W x D x H)	317.5 x 157.5 x 48.3 mm	317.5 x 157.5 x 63.5 mm	317.5 x 162.6 x 91.4 mm
WEIGHT	1.8 kg.	2.2 kg.	2.7 kg.
POWER	12V DC, 1.5A		
POWER REQUIREMENTS	12V DC, 1.5A	12V DC, 3A	12V DC, 3A
AC INPUT	100 to 240VAC		
POWER TYPE	External		

Belkin Secure 8/16 Port KVM



PART #	F1DN108C-3	F1DN108F-3	F1DN116C-3
DESCRIPTION	Secure DVI-I KVM Switch; 8-Port with CAC	Secure Dual-Head DVI-I KVM Switch; 8-Port with CAC	Secure DVI-I KVM Switch; 16-Port with CAC
CONSOLE PORTS	3840x2160 pixels (UHD 4K) @30Hz, 2560x1600 pixels @60Hz		
CONSOLE MOUSE & KEYBOARD PORTS	USB Type-A female connector or PS/2 Mini-DIN 6 pin female connector (1 designated mouse port and 1 designated keyboard port)		
CONSOLE DISPLAY PORTS	DVI-I Dual-link	2 x DVI-I Dual-link	DVI-I Dual-link
CONSOLE AUDIO JACK	3.5mm female		
REMOTE CONTROL	DCU		
COMPUTER PORTS	USB Type B		
COMPUTER KEYBOARD/MOUSE PORTS	USB Type B		
COMPUTER CAC PORTS	USB Type B		
COMPUTER AUDIO JACK	3.5mm female		
CONSOLE CAC AND BIOMETRICS	—		
COMPUTER DISPLAY PORTS	DVI-I	2 x DVI-I	DVI-I
PHYSICAL	Heavy-duty extruded aluminum enclosure with metal faceplate		
ENCLOSURE	Heavy-duty extruded aluminum enclosure with metal faceplate		
DIMENSIONS (W x D x H)	432.5 x 42.5 x 195 mm	435 x 87.5 x 195 mm	432.5 x 87.5 x 195 mm
WEIGHT	4.5 kg.	5.9 kg.	6.3 kg.
POWER	12V, 1A DC		
POWER REQUIREMENTS	100-240VAC, 0.9A Max, 50/60Hz	100-240VAC, 0.9A Max, 50/60Hz	100-240VAC, 0.9A Max, 50/60Hz
AC INPUT	100 to 240VAC		
POWER TYPE	Internal		

Belkin Secure KM

PART #	F1DN102K-3	F1DN104K-3	F1DN108K-3
DESCRIPTION	Secure FLIP 2-Port Keyboard/Mouse Switch	Secure 4-Port Keyboard/Mouse Switch	Secure 8-Port Keyboard/Mouse Switch
CONSOLE PORTS	3840x2160 pixels (UHD 4K) @30Hz, 2560x1600 pixels @60Hz		
CONSOLE MOUSE & KEYBOARD PORTS	USB Type-A female connector or PS/2 Mini-DIN 6 pin female connector (1 designated port for mouse and 1 designated port for keyboard)		
CONSOLE DISPLAY PORTS	—	—	—
CONSOLE AUDIO JACK	3.5mm female		
REMOTE CONTROL	DCU		
COMPUTER PORTS	USB Type B		
COMPUTER KEYBOARD/MOUSE PORTS	USB Type B		
COMPUTER CAC PORTS	—		
COMPUTER AUDIO JACK	3.5mm female		
CONSOLE CAC AND BIOMETRICS	—		
COMPUTER DISPLAY PORTS	—	—	—
PHYSICAL	Impact Resistant ABS Plastic		
ENCLOSURE	Impact Resistant ABS Plastic		
DIMENSIONS (W x D x H)	109.2 x 76.2 x 25.4 mm	312.5 x 153.8 x 47.5 mm	432.5 x 195 x 42.5 mm
WEIGHT	0.54 kg.	1.9 kg.	4.2 kg.
POWER	12V, 1A DC		
POWER REQUIREMENTS	12V, 1A DC	12V DC 1.5A	100-240VAC, 0.9A Freq. 50/60Hz
AC INPUT	100-240VAC		
POWER TYPE	External	External	Internal

All models

OPERATING TEMPERATURE	32° to 104° F (0° to 40° C)	HUMIDITY	0-80% RH, non-condensing	MADE IN	Designed and supported in California. Assembled in U.S. TAA compliant.	PRODUCT LIFE-CYCLE	5 Years	WARRANTY	3 Years Standard - Optional Extended up to 5 Years
STORAGE TEMPERATURE	-4° to 140° F (-20° to 60° C)	SECURITY ACCREDITATION	NIAP certified to latest Protection Profile PSS Ver 3.0, which exceeds EAL4 and PP PSS Ver. 2.1. NIAP listed.						



Most Belkin Secure Switching products are certified by NIAP to the latest Common Criteria Protection Profile PSS Ver 3.0, which exceeds EAL4 and PP PSS Ver. 2.1.