



SILENT SENTRY SSH & SHCS Series

Modular Cabinet Design Offers a Customizable Solution:




Applications:

- -80° Freezers
- Vaccine Refrigerators
- Fume Hoods
- Sensitive Lab Equipment
- Operating Room Equipment
- Incubators
- Histology Equipment
- Imaging Equipment
- Mission Critical Medical Devices

Features:

- Internal Transfer Switch
- Automatic Transfer (less than 1 sec)
- Branch Output Circuit Breakers
- Digital Control LCD Screen
- 2 Year Warranty
- 4 Year Prorated Battery Warranty
- Space Saving Design
- No Ventilation Necessary
- No Exhaust or Fumes
- Installs Anywhere within Your Facility
- Audible Low Battery Alarm.



OPTIONS:



Power Outage Alert:

The optional power outage alert system calls you when a power outage occurs. This feature offers you peace of mind and better control when dealing with power failures.



Battery Monitor Kit:

The optional battery monitor kit enables you to remotely monitor the battery during a power outage via the internet, by offering an estimated runtime based upon the rate of discharge.

SILENT SENTRY SSH & SHCS Series

Model Numbers	Watts	Surge Watts	KWH	Waveform	Height (in)	Weight (lbs)	Output Breakers	Voltage	Input Circuit
SSH2020V SHCS2020V	2000	4000	2.4	Modified	43.00	300	3 (20 Amp)	120	30 Amp
SSH2030V SHCS2030V	2000	4000	3.6	Modified	54.50	380	3 (20 Amp)	120	30 Amp
SSH2040V SHCS2040V	2000	4000	4.8	Modified	62.25	460	3 (20 Amp)	120	30 Amp
SSH2060V SHCS2060V	2000	4000	7.2	Modified	77.75	630	3 (20 Amp)	120	30 Amp
SSH2080V SHCS2080V	2000	4000	9.6	Modified	93.25	800	3 (20 Amp)	120	30 Amp
SSH3020V SHCS3020V	3000	6000	2.4	Modified	43.00	300	4 (20 Amp)	120	30 Amp
SSH3030V SHCS3030V	3000	6000	3.6	Modified	54.25	380	4 (20 Amp)	120	30 Amp
SSH3040V SHCS3040V	3000	6000	4.8	Modified	62.25	460	4 (20 Amp)	120	30 Amp
SSH3060V SHCS3060V	3000	6000	7.2	Modified	77.75	630	4 (20 Amp)	120	30 Amp
SSH3080V SHCS3080V	3000	6000	9.6	Modified	93.25	800	6 (20 Amp)	120	30 Amp
SSH4020MS SHCS4020MS	4000	8000	2.4	Pure	43.00	300	6 (20 Amp)	120/240	30 Amp
SSH4060MS SHCS4060MS	4000	8000	7.2	Pure	77.75	630	6 (20 Amp)	120/240	30 Amp
SSH4440MS SHCS4440MS	4400	8800	4.8	Pure	62.25	460	6 (20 Amp)	120/240	30 Amp
SSH4480MS SHCS4480MS	4400	8800	9.6	Pure	93.25	800	6 (20 Amp)	120/240	30 Amp

4000 & 4400 Watt Systems being supplied with 208 volts, will require an Isolation Transformer (Recommended: Hammond Model C1F005GES)

Note: SSH and SHCS models are the same configuration. SHCS models support cold storage appliances, SSH models are for all other applications.

Heat Output:

Full Bulk Charge Mode: 1450 BTU per hr
 Inverting @ Full Rated Wattage: 2250 BTU per hr
 Inverting @ 0 Watts: 85 BTU per hr

UNIT DIMENSIONS

