Liberty Pumps

2448-SERIES SIMPLEX GRINDER PACKAGE

Factory Assembled 24" x 48" Fiberglass Basin 2 hp. Grinder Pump 1-1/4" Discharge GR10 Guide Rail Assembly 2 YEAR WARRANTY



SXG21=3 or SXG24=3 Control Panel with Alarm Included (NEMA 1 or NEMA 4x)

FEATURES:

- Integral ball check valve
- Pre-mounted floats for pump control and alarm
- 4" caulking-type inlet hub
- Galvanized guide rail pipe (stainless optional)
- Factory pre-assembled guide rail system
- Factory pre-assembled schedule 80 PVC discharge piping with union and ball valve
- Fiberglass basin with anti-flotation collar

- Solid gray fiberglass cover (steel and green fiberglass optional)
- All stainless steel supports and brackets pre-mounted
- NEMA 4X junction box for electrical connections, pre-mounted
- Stainless steel cable for pump lift-out

MODELS:

2448SG NEMA 4x panel 2448SGI NEMA 1 panel

2448-SERIES Specifications

• 2 hp., 230V, 1 Phase, 60 Hz, 9.2 Amps, 3450 RPM

(See SG202M literature for complete pump specifications.)

Model SG202M Grinder Pump




Specifications are subject to change without notice.

DIMENSIONAL DATA:

Complete System Weight: approximately 260 lbs. *(includes control panel)*

Top View



SXG24=3 (NEMA 4x) Simplex Control & Alarm

NEMA 4X Enclosure on Model 2448SG

Model SXG21=3 (NEMA 1) or

- NEMA 1 Enclosure on Model 2448SGI
- 3 Float System
- Pump start and run capacitors
- Pump thermal overload protection
- Seal leak indicator light
- HOA switch

PUMP

PANEL

Discharge 1¼"


• Cable length 30'


- Alarm horn and beacon
- UL and cUL listed

(See SG202M literature for complete panel specifications.)

CUSTOMIZED SYSTEMS:

Liberty offers many options to the base 2448SG package, as well as other engineered pump systems. Consult factory for information on customized systems.





Liberty Pumps • 7000 Apple Tree Avenue • Bergen, New York 14416 • Phone 1 (800) 543-2550 Fax (716) 494-1839 Web Site: www.libertypumps.com 7147000 R12/00

Side View