

Universal 2nd Gen SKVM

Universal 2nd Gen SKVM												
Part Number	F1DN102 KVM-UN-4 (W/CAC)	F1DN102 KVM-UNN-4	F1DN202 KVM-UN-4 (W/CAC)	F1DN202 KVM-UNN-4	F1DN104 KVM-UN-4 (W/CAC)	F1DN104 KVM-UNN-4	F1DN204 KVM-UN-4 (W/CAC)	F1DN204 KVM-UNN-4	F1DN108 KVM-UN-4 (W/CAC)	F1DN208 KVM-UN-4 (W/CAC)	F1DN116 KVM-UN-4 (W/CAC)	
No. of Computers	2	2	2	2	4	4	4	4	8	8	16	
No. of Displays	1	1	2	2	1	1	2	2	1	2	1	
CAC/Audio Freeze	Yes	No	Yes	No	Yes	No	Yes	No	Yes	Yes	Yes	
Front Panel Illumination / Multi Color	Yes											
Belkin SKVM Remote Control with Integrated keyboard Compatible	Yes											
CONSOLE PORTS (DEVICES)												
Console Mouse and Keyboard Ports	USB Type-A female connector (1 designated port for mouse and 1 designated port for keyboard) with status indicator lights											
Console Audio Jack	USB Mini (female)											
Console Remote Control Port	RJ14 female											
Console CAC/DPP Port	USB Type-A female connector											
Console Video Port	DisplayPort/HDMI combo connector											
Max Resolution Supported	3840 x 2160 pixels (UHD 4K) @ 60Hz - 2560 x 1600 pixels @ 120Hz											
COMPUTER PORTS												
Computer Audio Jack	1/8" (3.5mm) female											
Computer Keyboard/Mouse Port	USB Type B											
Computer Video Port	DisplayPort/HDMI combo connector											
PHYSICAL												
Dimensions	12.5 (W) x 6.2 (D) x 2.5 (H) in. / 317.5 (W) x 162.6 (D) x 63.5 (H) mm						12.5 (W) x 6.2 (D) x 3.6 (H) in. / 317.5 (W) x 162.6 (D) x 91.4 (H) mm		17.2 (W) x 1.6 (H) x 8.1 (D) in. / 436.9 (W) x 40.6 (H) x 205.7 (D) mm	17.2 (W) x 3.5 (H) x 8.1 (D) in. / 436.9 (W) x 88.9 (H) x 205.7 (D) mm	17.2 (W) x 3.8 (H) x 8.1 (D) in. / 436.9 (W) x 88.9 (H) x 205.7 (D) mm	
Weight	.55 lbs (0.25 kg) (unit w/out cables) for video and USB											
POWER												
Power Requirements	12VDC, 2.5A								12V, 4.0A DC			
AC Input	100-240VAC											
Power Type	External with WW mains connectors								Internal with WW mains connectors on power cord			
ENVIRONMENTAL												
Operating Temperature	32° to 104° F (0° to 40° C) for Video and USB											
Storage Temperature	-4° to 140° F (-20° to 60° C)											
Humidity Storage and Use	0-80% RH, non-condensing											
CERTIFICATION												
Security Accreditation	NIAP Protection Profile PSD Ver. 4.0, Audio Input v 1.0. Keyboard/Mouse v 1.0. Video/Display v 1.0 User Authentication (by model), TEMPEST variants available via an SDIP-55, NATO accredited TEMPEST test facility.											
Regulatory Compliance	FCC Class A, CE, UL, ICES, RCM, RoHS, UKCA											
GENERAL INFORMATION												
Made in	Designed in California. Assembled in USA with USA-based technical support (TAA compliant).											
Product Life-Cycle	5 years											
Warranty	3 years standard (upgradeable to 4 or 5 years)											
Enclosure	Extruded aluminum								Formed steel			

Accessories Universal 2nd Gen SKVM

Universal 2nd Gen SKVM Accessories				
F1DN008KBD	F1D006	F1D008	F1DN-DCUAP-UN-4	F1DN-KVM-CEXTCS
Secure KVM Remote Control w/Integrated Keyboard	Desk mount for F1DN102KVM-UN-4, F1DN202KVM-UN-4, F1DN104KVM-UN-4 (and UNN variants)	Desk mount for F1DN204KVM-UN-4 (and UNN variants)	Belkin PP4,0 SKVM to DCU Adapter	Belkin KVM Console Side CAT5 Extender-Universal Video
F1DN-KVM-HEXRCS	F1DN-KVM-CEXTFI	F1DN-KVM-HEXRFI	F1DN002R	F1DN003R
Belkin KVM Host Side CAT5 Extender-Universal Video	Belkin KVM Console Side Fiber Extender-Universal Video	Belkin KVM Host Side Fiber Extender-Universal Video	4 Button DCU for 4 port Belkin Secure KVM Switches, with LCD Display	3 Button DCU for 4-16 port Belkin Secure KVM Switches, with LCD Display

Universal 2nd Gen SKVM Replacement Parts
0401-00809
Belkin Universal 2- and 4-Port KVM/KM Power Adapter 12V 2.5A, w/ Interchangeable Mains Connector Wall Mount



Universal 2nd Generation SKVM

Belkin's Universal 2nd Generation Secure KVM series combines cutting-edge cybersecurity provisions, video performance, and user experience to deliver a no-compromise solution for the most demanding applications. Compatible with a unique KVM Remote with Integrated Keyboard, combining the KVM channel selection with a backlit, mechanical USB keyboard reduces operator error and declutters the desktop.

The color of efficiency

Customizable port coloring and naming on the front panel of the Universal 2nd Gen facilitates channel identification and reduces operator errors.



- Available in 2-, 4-, 8-, and 16-channel configurations with a choice of single or dual monitors for 1-8 port models, single monitor for 16-port model
- Future-proof design supports current and upcoming video standards at up to 4k@60Hz with optional passive and active TAA compliant cables
- Optional SKVM remote with integrated keyboard supports full KVM switching control for the ultimate operator experience
- Certified for NIAP Protection Profile 4.0 to meet the highest security standards
- USA-based free technical support

Control the KVM from the keyboard

The industry-first Belkin KVM Remote with Integrated Keyboard provides full control of the SKVM, allowing it to be located off the desk for a clean and decluttered workstation. The keyboard's LED backlighting and status indicators mimic the SKVM's front panel configuration to reinforce the security enclave the operator is working on, minimizing operator error while enhancing workspace ergonomics.



Front of Universal 2nd Generation SKVMs



Rear of Universal 2nd Generation SKVMs

Belkin International, Inc.
 12045 E. Waterfront Drive,
 Playa Vista, CA 90094
 (310) 751-5569
belkin.com/cybersecurity

LinkedIn:



SUPPORT
 Secure KVM Support 800-282-2355

SALES
FederalBusinessDivision@belkin.com

Brochure to download:



Universal 2nd Generation SKVM

