Lenovo

ThinkVision T24m-10 61CFRAT2EU

Product

ThinkVision T24m

Machine Type

61CF

Region

EMEA

Display Size

23.8"

View Area

527.04x296.46 mm

Panel

In-Plane Switching

Aspect Ratio

16:9

Resolution

1920x1080

Pixel Pitch

0.2745x0.2745 mm

Dot / Pixel Per Inch

92 dpi

View Angle (H / V)

178 / 178

Pixel Response Time

6 ms

Refresh Rate

60 Hz

Brightness

250 nits

Contrast Ratio

1000:1

Color Gamut

99% sRGB

Multiple Input

HDMI, DP, USB Type-C

USB Port

USB 3.0x5

Camera

None

Speaker

Power Consumption (Typical / Maximum)

17W / 110W

Power Adapter

Integrated

Stand

Tilt, Swivel, Pivot, Height Adjust Stand

Color

Black

Side Bezel Width

2 mm

Dimensions with Stand (HxWxD)

483.4x540.2x261.75 mm

Weight (Including Stand)

12.34lb / 5.6kg

Monitor Cable

USB 3.1 Type-C

ENERGY STAR

Yes

TCO

TCO 7.0

EPEAT

Silver

Low Blue Light / Eye Comfort / Eyesafe Display

Eye Comfort

Base Warranty

3-year

Operating System

Support Windows 7, Windows 10

Presets / User Settings

HDMI:19 / DP:11

On Screen Display

OSD, 8 Languages

Sync Technology

None

CPU / Platform

None / None

Display Ram / Storage / Card Slot

None / None / None

Wireless / Ethernet / Bluetooth

None / None / None

Touch Screen / Digitizer Pen / Battery

None / None / None

Announce Date

2017-08-23

WWW.LENOVO.COM

Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area.

Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. Lenovo provides this publication "as is" without warranty of any kind, either express or implied, including the implied warranties of merchantability or fitness for a particular purpose.



https://psref.lenovo.com

Visit psref website for the latest version of Product specifications Reference.
© Lenovo, 2020. All rights reserved.



Think Visinn T24m-10 MONITOR

23.8"

WLED

16:9

Yes

1920 x 1080

250 cd/m²

72% NTSC

178°/178°

1000:1

3M:1

92

19 W

116 W

<0.5 W

<0.5 W

Internal

90 VAC - 264 VAC

47 Hz - 63 Hz

In-Plane Switching

527.04 (H) x 296.46 (V)

0.2745 (H) x 0.2745 (V)

4 ms (Extreme mode) 6 ms (Normal mode)

SPECIFICATIONS

| וח | 2 | DI | ΙΔ | ·V |
|----|---|----|----|----|

Panel Size Panel Type Backlight Resolution Aspect Ratio Anti-Glare

Screen Dimensions (W x H) (mm) Maximum Brightness (Typical) Viewing Angle (H/V at CR 10:1) Contrast Ratio (Typical) Dynamic Contrast Ratio (Typical)

Pixel Pitch (mm) Dot/Pixel Per Inch (DPI/PPI) Color Gamut (CIE 1931)

Response Time (gray to gray)

POWER CONSUMPTION

Voltage Dynamic Frequency

DIMENSIONS (W x D x H)

Size Packed 422 x 622 x 190 (mm) 16.61" x 24.48" x 7.48" (inches)

Size Unpacked with Stand **Lowest Position**

540.2 x 261.75 x 373.4 (mm) 21.26" x 10.3" x 14.7" (inches)

Highest Position (mm) (inches)

Size Unpacked without Stand (Monitor Head Only)

(mm) 540.2 x 46.45 x 325.98 (inches) 21.26" x 1.82" x 12.83"

Distance from Table to Panel Lowest Pixel at Bottom of Screen (mm / inches)

Highest Pixel at Top of Screen

(mm / inches) Stand Base Footprint Area

(mm / inches)

Weight Packed

Unpacked Monitor Head Only Full Container Load (40' STD / 20' STD)

70.37 / 2.77" 476.8 / 18.77"

250 x 250 / 9.84" x 9.84"

540.2 x 261.75 x 483.4

21.26" x 10.3" x 19"

Starting at 16.39 lbs (7.45 kg) Starting at 11.33 lbs (5.15 kg) Starting at 7.26 lbs (3.3 kg) 1140 / 540 Units

CONNECTIVITY

Typical Maximum

Sleep-Mode

Power Supply

Power Voltage

Switch Off-Mode

Video Input Signals Video Cables Supplied Video Cable Length **USB Hub**

HDMI 1.4 + DisplayPort 1.2a + USB Type-C USB Type-C to Type-C Cable 1.8 m Yes 1 x USB 3.01

(Upstream, by USB Type-C) 4 x USB 3.01 (Downstream, incl. 1BC) Yes (3.5 mm)

Audio-Out

SPECIAL FEATURES

Thin Client Support (Tiny)

(by Tiny Clamp Bracket Kit + VESA Mount)

WHAT'S IN THE BOX

Monitor with Stand 1 x Power Cable 1 x USB Type-C[™] to Type-C[™] Cable Quick Setup Guide

MECHANICAL

Top (mm / inches) Sides (mm / inches)

Tilt Angle (Front / Back) -5° / 30° +/-45° Swivel Angle (Left / Right) Lift Range (mm) 110 +/-90° VESA Mount (mm x mm) Kensington Lock Slot Yes Cable Management Yes Bezel Color Raven Black Bezel Width

Yes (100 x 100)

2 / 0.08" 2 / 0.08"

CERTIFICATIONS

EPEAT Silver **ENERGY STAR Rating** 8.0 ULE Gold

TCO 7.0 / TCO Edge 2.0 RoHS (FU 2002/95/FC) Yes

Windows Certification Windows 7 / Windows 10

China Energy Efficiency Standard Tier 2 TüV Eye Comfort Certification Yes

Depending on many factors such as the processing capability of peripheral devices, file attributes, and other factors related to system configuration and operating environments, the actual transfer rate using the various USB connectors on this device will vary and is typically slower than the data rates as defined by the respective USB specifications: - 5 Gbit/s for USB 3.1 Gen 1; 10 Gbit/s for USB 3.1 Gen 2 & 20 Gbit/s for USB 3.2.





WWW.LENOVO.COM











