

TEC Report No. R-83-030

H. B. ROBINSON FLUENCE REDUCTION ANALYSIS
FOR THE PARTIAL-LENGTH SHIELD ASSEMBLY CONCEPT

Work Performed Under File No. NF-1111.06

Prepared by:

Technology for Energy Corporation
One Energy Center, Pellissippi Parkway
Knoxville, Tennessee 37922

and

Carolina Power and Light Company
Center Plaza Building
P.O. Box 1551
Raleigh, North Carolina 27602

September 1983

831006041B 830930
PDR ADOCK 05000261
PDR

TABLE OF CONTENTS

<u>Section</u>	<u>Page</u>
1. SUMMARY	1-1
1.1 Overview	1-1
1.2 Introduction	1-2
1.3 Background	1-2
1.4 PLSA Description	1-5
1.5 Results and Conclusions	1-6
2. DESCRIPTION OF WORK	2-1
2.1 Introduction	2-1
2.2 Best-Estimate Flux Reduction Analysis	2-1
2.2.1 Analysis Overview	2-1
2.2.2 Source-Term Development	2-2
2.2.3 Synthesis Technique and Reduction Factor Definition	2-4
2.3 References	2-6
3. QUALIFICATION AND VERIFICATION	3-1
3.1 Qualifications of the Analysis Team	3-1
3.2 Code Verification and Benchmarking	3-2
3.2.1 History of Codes	3-2
3.2.2 Past Benchmarking of Methods	3-6
3.2.3 CP&L Plans for Additional Benchmarking	3-8
3.3 References	3-9
4. SUPPORTING MATERIAL	4-1
4.1 Description of the Codes Used in the Analysis	4-1
4.1.1 The GIP Computer Code	4-1
4.1.2 The DOT-IV Computer Code	4-1
4.1.3 The ANISN-W Computer Code	4-3
4.1.4 The Nordheim's Integral Treatment and Working Library Computer Code	4-4
4.1.5 The XSDRNPM Computer Code	4-4
4.1.6 The DIFF Computer Code	4-4
4.1.7 The XPTX Computer Code	4-5
4.1.8 The XMIX Computer Code	4-5
4.1.9 The DC2G Computer Code	4-5
4.1.10 The PDQ7 Computer Code	4-6
4.1.11 The XTG Computer Code	4-6
4.1.12 The XPOSE Computer Code	4-7
4.1.13 The AXFRAC Computer Code	4-7
4.1.14 The DOTSOR Computer Code	4-8

TABLE OF CONTENTS (Continued)

<u>Section</u>	<u>Page</u>
4.1.15 The DOTSYN Computer Code	4-9
4.1.16 The REDUCT Computer Code	4-9
4.2 Cross-Section Library Descriptions	4-9
4.2.1 The CSRL Master Library	4-10
4.2.2 The 102-Group Cross-Section Library	4-11
4.2.3 Two-Group PLSA Cross Sections	4-12
4.2.4 Two-Group Macroscopic Cross Sections	4-14
4.2.5 The ELXSIR 56-Group Cross-Section Library	4-14
4.3 Source-Term Documentation	4-16
4.3.1 Generation of the Reference Distribution	4-16
4.3.2 Generation of Projected Distribution	4-17
4.3.3 Corrections to Source Distribution	4-36
4.3.4 Study of HBR 2 Power History and Westinghouse Capsule Analyses	4-36
4.3.5 Normalization of Sources Input to DOT-IV	4-49
4.4 Geometric Models	4-50
4.4.1 One-Dimensional Model Used for Material Selection Reduction Factor Calculations	4-50
4.4.2 One-Dimensional Eigenvalue Model	4-55
4.4.3 Fuel Pin Cell Model	4-58
4.4.4 DOT-IV Homogeneous R-Z Model	4-58
4.4.5 DOT-IV R- θ Model	4-62
4.4.6 DOT-IV Heterogeneous R-Z Model	4-66
4.5 Number Densities	4-66
4.6 Sample Inputs	4-72
4.7 References	4-117
 5. RESULTS AND CONCLUSIONS	 5-1
5.1 Fluxes at the Pressure Vessel Inner Surface	5-1
5.2 Comparison of Cycle 8 Results with Dosimeter Measurements	5-12
5.3 Projected Fluences and RT-NDT	5-14
5.4 Discussion and Conclusions	5-14
5.4.1 Uncertainties and Sensitivities	5-14
5.4.2 Conservatisms	5-19
5.4.3 Conclusions	5-20
 Appendix A - Résumés	
 Appendix B - AXFRAC Source Listing	

LIST OF TABLES

<u>Table</u>	<u>Page</u>
3-1 Computer Codes and Functions	3-3
4-1 Computer Codes Used in the Reactor Pressure Vessel Fluence Analysis	4-2
4-2 Cross-Section Libraries Used in Analyses	4-10
4-3 Two-Group Diffusion Coefficients in S S-304 PLSA Core Model	4-15
4-4 XTG HBR2 Cycle 8 Averaged Axial Power Distributions	4-21
4-5 XTG HBR2 Cycle 10 Averaged Axial Power Distributions	4-37
4-6 Comparison of Saturation Factors for HBR2 Surveillance Capsules	4-48
4-7 Comparison of Corrected and Reported Saturated Activities for HBR2 Capsules	4-48
4-8 Neutronics Models Used in the Analyses	4-52
4-9 ANISN One-Dimensional Slab Model Zone Assignments	4-54
4-10 Mesh Intervals Used in One-Dimensional Slab Model	4-56
4-11 DOT-IV Homogeneous R-Z Reactor Model Zone Assignments	4-61
4-12 Radial Volume Fractions in the DOT-IV R-Z Model	4-63
4-13 DOT-IV R- θ Reactor Model Zone Assignments	4-65
4-14 DOT-IV Homogeneous R-Z Reactor Model Zone Assignments	4-68
4-15 Material Volume Fractions by Material Region	4-69
4-16 Element Number Densities (atoms/bn-cm) for Reactor Materials	4-70
5-1 Flux, Fluence (above 1 MeV), and RT-NDT at 27 EFPY Radially Along HBR2 Vessel Lower Girth Weld Inner Surface	5-2
5-2 Flux and Fluence (above 1 MeV) Radially Along HBR2 Vessel Inner Surface at Core Midplane	5-4

LIST OF TABLES (Continued)

<u>Table</u>		<u>Page</u>
5-3	Flux and Fluence (above 1 MeV) Axially Along HBR2 Vessel Inner Surface (angle ODEG) RT-NDT at 27 EFPY for Beltline Longitudinal	5-6
5-4	Comparison of Calculated and Measured Saturation Activities for H. B. Robinson Surveillance Capsules	5-13
5-5	Estimated Uncertainties in Calculated Pressure Vessel Surface Fluxes	5-19

LIST OF FIGURES

<u>Figure</u>	<u>Page</u>
1-1 HBR2 PLSA Concept	1-3
1-2 HBR2 PLSA Core Locations	1-4
1-3 HBR2 Calculated Maximum Circumferential Weld Fluence	1-8
4-1 Cycle 8 Normalized Assembly Delta Exposures	4-18
4-2 HBR2 Cycle 8 PDQ Averaged Pin Relative Power Assembly 46 (H-15)	4-19
4-3 HBR2 Cycle 8 PDQ Averaged Pin Relative Power Assembly 47 (G-15)	4-20
4-4 H. B. Robinson 2 Cycle 8 Normalized Core Delta Exposure Distribution	4-28
4-5 H. B. Robinson 2 Quarter Core Averaged Assembly Power Distribution, Cycle 9, Map 414	4-30
4-6 H. B. Robinson 2 Quarter Core Averaged Assembly Power Distribution Cycle 9, Map 431	4-31
4-7 H. B. Robinson 2 Quarter Core Averaged Assembly Power Distribution Cycle 9, Map 444	4-32
4-8 H. B. Robinson 2 Core Averaged Axial Relative Power Distributions Cycle 9	4-33
4-9 Assembly Exposures - Cycle 10, Upper Core	4-34
4-10 Assembly Exposures - Cycle 10, Lower Core	4-35
4-11 H. B. Robinson 2, Cycle 8 Ratio Core Average K/v to Assembly Average K/v	4-44
4-12 H. B. Robinson 2, Cycle 10 Ratio Core Region K/v to Assembly Region K/v	4-45
4-13 K/v as a Function of Exposure	4-46
4-14 Equations Used in AXFRAC and DOTSOR	4-51
4-15 ANISN One-Dimensional Slab Model for Fixed-Source Analysis	4-53
4-16 1-D Slab PLSA Core Model for Eigenvalue Calculations	4-57

LIST OF FIGURES (Continued)

<u>Figure</u>	<u>Page</u>
4-17 Fuel Pin Cell Model Geometry	4-59
4-18 DOT-IV R-Z Reactor Model	4-60
4-19 DOT-IV R- θ Reactor Model	4-64
4-20 DOT-IV Heterogeneous R-Z Model	4-67
5-1 Lower Circumferential Weld Best Estimate Flux Distribution for Cycles 8 and 10	5-8
5-2 Lower Circumferential Weld Best Estimate Reduction Factor for the 36 in. Stainless Steel PLSA Design	5-9
5-3 Axial Flux Distributions for Cycle 8 and Cycle 10 at the Center of the Core Flat	5-10
5-4 Axial Best Estimate Reduction Factor Distribution at the Center of the Core Flats	5-11
5-5 HBR2 Calculated Fluence Based on 36 in Shield Height - Lower Weld Inner Surface	5-15
5-6 HBR2 Calculated Fluence Based on 36 in. Shield Height - Core Midplane Inner Surface	5-16
5-7 HBR2 Calculated Fluence Based on 36 in. Shield Height - Vessel Inner Surface at the Center of Core Flats	5-17

Section 1

SUMMARY

1.1 OVERVIEW

Carolina Power and Light Company (CP&L) has developed a triad of programs aimed toward resolving concerns associated with the Pressurized Thermal Shock (PTS) issue for the H. B. Robinson Unit 2 (HBR2) pressure vessel. These are (1) a materials research program to establish a better estimate of the chemistry of the vessel welds, (2) a probabilistic analysis to assess the risk associated with PTS at HBR2, and (3) a program to reduce fast flux to areas of the vessel experiencing a potentially significant increase in RT_{NDT} . Each program has the independent potential to resolve PTS concerns for HBR2.

This report covers the third program and concludes that the proposed fast flux reduction scheme assures that no portion of the pressure vessel will reach the Nuclear Regulatory Commission's (NRC) screening criteria for RT_{NDT} before the expiration of the operating license (EOL) in 2007, which is presently projected to be about 27 EFPY (effective full power years). The conclusion is based on calculated reduction in fast flux to critical vessel areas due to inclusion of a new assembly design in future reloads. The new design, known as partial length shield assemblies (PLSAs), are presently being fabricated for the next reload (Cycle 10). The calculated results presented in this report are conservative estimates of the flux reduction that will be attained.

1.2 INTRODUCTION

This report documents the detailed analyses performed to evaluate the fast flux to critical vessel welds before and after installation of PLSA's. Qualifications of methods, codes, and personnel performing the analyses are given. Verification of calculated results for which benchmarking measurements exist is included, and CP&L plans for additional benchmarking are outlined. Finally, an estimate of uncertainty in calculated results is derived and applied to projections of vessel EOL RT_{NDT}.

1.3 BACKGROUND

One of CP&L's immediate responses to the PTS issue was a redesign of the HBR2 Cycle 9 (the present operating cycle) reload. The conventional out-in-in pattern was changed to a low-leakage loading pattern (L3P) with gadolinia (Gd₂O₃) used in 208 fuel pins to control peaking. The pattern produced an estimated reduction factor of two in fast flux to critical areas of the vessel. That reduction extended by 3 EFPY the projected time to reach the screening criteria for RT_{NDT}.

The PLSA concept, shown in Figures 1-1 and 1-2, was designed and developed by CP&L engineers¹ to extend the time to reach the screening criteria beyond 13.5 EFPY. Preliminary calculations performed by Technology for Energy Corporation (TEC)² and the Exxon Nuclear Company (ENC)³ were used in choosing shielding material and height. ENC was contracted to fabricate the assemblies and to perform the reload design for Cycle 10. TEC was contracted to perform detailed shielding analyses to quantify the

Figure 1-1. HBR2 PLSA Concept





Figure 1-2. HBR2 PLSA Core Locations



expected fast fluence accumulation rates at the pressure vessel inner surface. This report documents the analyses and auxiliary calculations performed by TEC and CP&L.

1.4 PLSA DESCRIPTION

The PLSA design under fabrication is structurally identical to the standard Exxon fuel currently used at HBR2--upper and lower tie plates, grid straps, instrument and guide tubes, and fuel cladding all remain unchanged. Only within the fuel cladding does the PLSA assembly differ from the standard fuel.

The lower fuel pellet stack will be replaced by a stainless steel rod 0.35 in. in diameter and 42 in. in length. (The calculations in this report assume a 36 in. shield height and thus overestimate the actual flux to the vessel. A change of ± 6 in. in shield zone length is documented in Reference 1 to have minor impact on core operations.) Above the inert rod is an insulator wafer, topped by a 96-in. stack of fuel pellets of the standard 0.3565-in. diameter with an enrichment in the range of 1.2-1.3 w/o. A 6-in. stack of pellets of the natural fissile enrichment topped by another insulator wafer and a plenum spring similar to that in a standard assembly covers the stack of low enrichment pellets.

PLSA assemblies will be loaded in the 12 outermost locations closest to the major axes. The inert shield material in the lower 42 inches of the assemblies will protect the limiting weld--the lower-to-intermediate shell circumferential weld--in its most critical areas near the major

axes. The fissile region has an enrichment chosen to insure the most vulnerable longitudinal weld in the intermediate shell does not reach its fluence limit at the end of the 32 EFPY plant design life. The upper (fertile) shield prevents the upper circumferential weld from becoming limiting. A diagram of the quarter-core symmetric loading of PLSAs with respect to girth weld locations is shown in Figure 1-1.

1.5 RESULTS AND CONCLUSIONS

Shielding analyses compared fast flux (fast fluence accumulation rates) at the pressure vessel inner surface for HBR2 Cycle 8 averaged neutron source distribution to the flux calculated using the projected Cycle 10 averaged distribution. The Cycle 8 source distribution was benchmarked to measured power distributions and was typical of previous cycles. The Cycle 10 source distribution was based on a shield height of 36 in. It was generated using the same methods and models as for Cycle 8 with additional benchmarking to available Cycle 9 measurements. The overall comparisons were thus consistent and, to the extent possible, based on benchmarked sources. The reduction factor for the critical circumferential weld locations, opposite the core flats, was calculated to be 9.2 and is conservative with respect to future cycles because the PLSAs in Cycle 10 are all fresh. The reduction factor for a shield height of 42 in., as the PLSAs are actually being fabricated, is estimated to be 10.7.

The calculated fluxes for Cycle 8 were benchmarked to dosimeter measurements for Capsules S, V, and T, which were removed, respectively, at the end of cycle (EOC)1, EOC3, and EOC8. The average difference between calculated and measured saturated activities for all dosimeters was 1.1% with a standard deviation of 13.6%.


Based on use of PLSAs with a shield height of 36 in. in all future cycles, a Cycle 9 fast flux reduction factor of 2, and assuming worst case weld chemistry the projected maximum fluence above 1 MeV at the lower circumferential weld after 27 EFPY meets the current screening criteria for allowable RT_{NDT} . The estimated maximum fluence for the actual shield height of 42 in. after 30 EFPY is 1.95×10^{19} n/cm². These results assure that use of PLSAs as-built, preclude any region of the HBR2 vessel reaching RT_{NDT} screening criteria before EOL (as seen in Figure 1-3). This conclusion allows ample time to complete ongoing dosimetry programs to measure actual vessel fluxes.

1.6 REFERENCES

1. Dresser, T. M., "Feasibility of the Part-Length Shield Assembly as a Flux Reduction Technique," CP&L, File NF-1111.05, Serial NF-83-219, April 1983.
2. Howell, R. S., Simpkins, W. M., and Chen, H. H., "Preliminary Report Reactor Pressure Vessel Fluence Calculations in Support of the Partial-Length Shield Assembly Concept for the H. B. Robinson Power Plant," TEC, R-83-022, July 1983.
3. Copeland, R. A. et al., "Part Length Shielding Assembly Feasibility Report," ENC, XN-NF-699, March 1983.

Figure 1-3

HBR2 CALCULATED MAXIMUM CIRCUMFERENTIAL WELD FLUENCE BASED ON 36 IN. SHIELD HEIGHT AFTER CYCLE 9



Section 2
DESCRIPTION OF WORK

2.1 INTRODUCTION

The TEC portion of the PLSA analysis project consisted of three phases: (1) selection of the PLSA shield material, (2) selection of the PLSA shield height, and (3) best estimation of the effectiveness of the PLSA design. The preliminary analysis of the first two phases indicated the "optimum" PLSA design to be a 36 to 42 in. stainless steel shield. This section describes the methodology and results of the best-estimate fluence reduction analysis based on this design.

2.2 BEST-ESTIMATE FLUX REDUCTION ANALYSIS

This section describes the analyses performed to provide a best estimate of the effectiveness of the 36-in. stainless steel PLSA design. It is subdivided into three sections: (1) an overview of the analysis -- Section 2.2.1, (2) a discussion of the source-term development -- Section 2.2.2, and (3) a discussion of the synthesis technique used -- Section 2.2.3.

2.2.1 Analysis Overview

The best-estimate flux reduction analysis was performed using Cycles 8 and 10. Cycle 8 was the last cycle for the H.B. Robinson Plant where flux reduction measures were not employed, and Cycle 10 will be the first cycle to employ the PLSA concept. The emphasis of this analysis was placed on the most critical location at the inner surface of the

reactor pressure vessel (i.e., axially at the core major axis and circumferentially at the level of the lower girth weld). To obtain a best estimate of the Cycle 8 and Cycle 10 flux distributions, a realistic three-dimensional source distribution was obtained for both cycles. The development of the source distributions is described in Section 2.2.2 and Section 4.3. These source distributions were used in a series of DOT-IV and ANISN-W transport calculations to develop R, R-Z, and R- θ group-wise flux distributions for both cycles.

The flux distributions were then used in the synthesis method (DOTSYN code) described in Section 2.2.3 to develop group-dependent three-dimensional flux distributions. The effectiveness of the PLSA design was evaluated by considering the ratio of the Cycle 8 to Cycle 10 flux distributions, each integrated over energies greater than 1 MeV (REDUCT code). Specifically, this analysis indicates that at the most critical location the 36-in. PLSA design results in a reduction factor of 9.2. A detailed presentation of the results of this analysis is given in Section 5.

2.2.2 Source-term Development

CP&L provided neutron source distributions for the TEC analyses that represented both a historical reference case and a projected case. This section summarizes the generation of the source distributions.

The following criteria were used to select the distributions:

1. The reference distribution should be typical or averaged to represent past operation at HBR2.

2. The projected distribution should be typical or averaged to represent expected operation after introduction of the PLSAs.
3. Consistent methods should be used to generate the reference and projected distributions.
4. Relative pin power distributions in x-y geometry should be supplied by CP&L since TEC proposed using DOTSOR to convert to neutron source distribution in R- θ geometry. Exposure - dependent K/ν factors should be applied to each assembly prior to DOTSOR processing.

Investigation showed that HBR2 Cycle 8 average power distribution was within a few percent of the measured 8-cycle average distribution¹ for the peripheral assemblies, satisfying Criterion 1. CP&L's analytic models of HBR2, a pin-by-pin, 2-group quarter-core PDQ7 and 3-D 1.5-group coarse-mesh quarter-core XTG, agreed very well with measurements for Cycle 8 and previous cycles. The models were benchmarked to the reference case (Cycle 8) and used consistently to generate the projected power distribution after insertion of the PLSA (Cycle 10), satisfying Criterion 3. Comparisons of preliminary calculations of power distributions for Cycles 10, 11, and 12 with the PLSAs inserted² showed Cycle 10 peripheral assembly powers were typical or greater than those in future cycles. Cycle 10 will have all fresh assemblies in peripheral locations of highest importance with regard to flux at the vessel, and thus represents the worst case loading. The projected Cycle 10 distributions were selected as satisfying Criterion 2. Criterion 4 is addressed in Section 4.3.

For both the reference case (Cycle 8) and the projected case (Cycle 10), the PDQ7 and XTG models were used to deplete the core in steps of 1000-2000 MWD/MTU to nominal cycle lengths. For Cycle 10, two PDQ7

depletions were performed, one typical of the core above the shielded region and another typical of the lower core with shield. The pin-wise relative power distributions from the PDQ7 cases were exposure-weighted to produce a Cycle 8 average, and an upper core and lower core average for Cycle 10. Relative axial distributions were obtained from the XTG cases by normalizing the cycle delta-exposure distributions to an integral of unity in each assembly and in each quarter assembly.

The Cycle 8 average relative power distribution from both PDQ7 and XTG were compared to measured distributions and showed standard deviations of 3% for both radial (PDQ7) and axial (XTG) calculations.

Comparisons with measurements available from Cycle 9 showed that both models continued to follow HBR2 power distributions with a standard deviation of less than 3%. These comparisons are important since the Cycle 9 core contains gadolinia pins not present in previous cycles; gadolinia pins will be used in all future cycles to control inner core power peaking induced by the low-leakage loading patterns.

The computer code AXFRAC was developed to convert relative power distributions from PDQ7 and XTG to DOTSOR input format (which computed neutron sources for DOT R- θ calculations) and to DOT and ANISN input format for R-Z and R calculations.

2.2.3 Synthesis Technique and Reduction Factor Definition

This section provides the details of the synthesis method and reduction factor used in the best-estimate analysis.

Synthesis Analysis

The synthesis method used in this analysis is essentially the same as that used (1) by ORNL in several benchmark analyses, including ANO-1 (as described in Section 3.2.2), and (2) in the EPRI LEPRICON package.³

The method is defined by the following equation:

$$\phi_g(r,z,\theta) = \frac{\phi_g(r,z)}{\phi_g(r)} \phi_g(r,\theta).$$

The CP&L analysis, like the ANO-1 analysis, used DOT-IV to obtain the two-dimensional flux distributions and ANISN to obtain the one-dimensional flux distributions. The ELXSIR cross-section library was used in all transport calculations for both CP&L and ANO-1. Unlike the ANO-1 analysis, the HBR2 analysis relied upon superposition because of the significantly different (r, z) distributions in and above the PLSA shield region. Therefore, in the HBR2 analysis the three-dimensional flux distribution was given by the following equation:

$$\phi_g(r,z,\theta) = \frac{\phi_g^u(r,z)}{\phi_g^u(r)} \phi_g^u(r,\theta) + \frac{\phi_g^L(r,z)}{\phi_g^L(r)} \phi_g^L(r,\theta).$$

The superscripts u and L designate the contribution to the three-dimensional flux distribution resulting from source neutrons originating in the core region (1) from the top of the shield to the top of the core, and (2) from the top of the shield to the bottom of the core, respectively. The three-dimensional source distributions used in these calculations were developed as described in Section 2.2.2 and Section 4.3.

The geometric models used in the DOT and ANISN calculations are described in Section 4.4. The sources and models were developed to give best estimates at the lower circumferential weld at the center of the core flats. Sample DOT and ANISN inputs for Cycle 10 are provided in Section 4.6.

Reduction Factor

The efficiency of the PLSA design was evaluated by defining a flux reduction factor consisting of the ratio of the Cycle 8 to Cycle 10 flux for energies greater than 1 MeV. For calculations using the ELXSIR cross-section library the reduction factor is given by the following equation:

$$RF = \frac{\sum_{g=1}^{27} \phi_g^u(r,z,\theta)}{\sum_{g=1}^{27} \phi_g^s(r,z,\theta)}$$

In this equation the superscript *u* indicates the Cycle 8 flux, and the superscript *s* indicates the Cycle 10 flux.

2.3 REFERENCES

1. Attachment to Letter from E. E. Utley to H. R. Denton, CP&L, File NF-1111.04, February 9, 1983.
2. Dresser, T. M. "Feasibility of the Part-Length Shield Assembly as a Flux Reduction Technique," CP&L, File NF-1111.05, Serial NF-83-219, April 1983.
3. Maerker, R. E., M. L. Williams, and B. L. Broadhead. "Summary Documentation of EPRI Workshop on LWR Pressure Vessel Fluence Calculations with LEPRICON Code System," ORNL, meeting held at Palo Alto, California, April 18-19, 1983.

Section 3

QUALIFICATION AND VERIFICATION

3.1 QUALIFICATIONS OF THE ANALYSIS TEAM

For purposes of analysis and review, a joint team was formed consisting of members from CP&L and TEC. The primary team members were (1) W. K. Cantrell, (2) H. H. Chen, (3) C. W. Craven, (4) T. M. Dresser, (5) R. S. Howell, (6) J. C. Robinson, (7) W. M. Simpkins, and (8) M. L. Williams. The team has both a strong academic background and experience in all areas related to the flux reduction project. All individuals on the team hold degrees in nuclear engineering--five Ph.D.s, one M.S., and two B.S.s (one with two years graduate work). Complete résumés for the team members are included in Appendix A.

The team has more than 80 man-years of radiation transport, core physics, and related experience. This experience base includes methods development, code development, benchmarking, and applications. The experience of the team was developed in a variety of work areas including consulting, national laboratories, utilities, and universities.

Of particular significance to this project was direct involvement at the Oak Ridge National Laboratory (ORNL) with methods development for the LEPRICON system and ELXSIR cross-section library. Both were developed for the Electric Power Research Institute (EPRI), specifically for performing light water reactor (LWR) fluence analysis. Further, this

experience included benchmarking of LEPRICON modules and ELXSIR to measurements at Unit 1 of Arkansas Nuclear One (ANO-1), at the Pool Critical Assembly (PCA), and at the Pool Side Facility (PSF).^{7,8}

3.2 CODE VERIFICATION AND BENCHMARKING

This section briefly covers the qualifications of the primary computer codes used in the fluence reduction project. The first subsection summarizes the benchmarking background of the codes, while the second subsection covers specific past benchmarking of methods/codes used in the best-estimate analysis of the PLSA effectiveness. The final subsection covers CP&L's plans for continued benchmarking.

3.2.1 History of Codes

The codes used in this project and their primary functions are listed in Table 3-1. A more detailed discussion of the code functions is provided in Section 4.1. The following paragraphs provide a brief background of these codes.

The AXFRAC, DOTSYN, REDUCT, DIFF, XPTX, XMIX, and DC2G codes were written specifically for the CP&L flux reduction project. All other codes in Table 3-1 are standard codes distributed by various groups.

ANISN-W evolved from the ANISN code developed at ORNL. ANISN has a long history of development that originates with the DSN code written at Los Alamos Scientific Laboratory. It has wide acceptance in the nuclear industry and has become an industry standard code.

Table 3-1

COMPUTER CODES AND FUNCTIONS

Code Name	Function
ANISN-W	One-dimensional radiation transport
DOS	Two-dimensional radiation transport and cross section mixing
AXFRAC	Source preparation
DOTSOR	R- θ source preparation
DOTSYN	Flux synthesis
REDUCT	Reduction factor analysis
XPOSE	Generate exposure-dependent diffusion parameters
PDQ-7	Relative x-y power distribution
XTG	Relative axial power distribution
AMPX-II	Cross section collapsing
DIFF	Preparation of two-group diffusion constants
XPTX	Preparation of two-group diffusion constants
XMIX	Preparation of two-group diffusion constants
DC2G	Preparation of two-group diffusion constants

The version of ANISN used in this project is traceable to the standard ANISN-W distributed by the Radiation Shielding Information Center (RSIC) at ORNL. Its installation on the University Computing Company (UCC) CYBER was verified by standard calculations distributed with the code by RSIC. During this project the code was compared to a VAX 11/780 version of ANISN-ORNL and was found to produce the same results using the slab geometry model and cross sections used in the flux reduction project (model described in Section 4.4.2).

The Discrete Ordinates System (DOS) principally consists of the two-dimensional radiation transport code DOT and the cross-section mixing code GIP. These codes have a long history of development and benchmarking at ORNL. They also have been used, benchmarked, and accepted by the nuclear industry and have become industry standards. The version used in this project is the latest distributed by RSIC (i.e., DOT 4.3 - 1982). Installation on the UCC-CYBER system was verified by use of the standard calculations distributed with the source code. Specific benchmark analyses using DOT 4.3 are described in Section 3.2.2.

DOTSOR was produced by ORNL for EPRI as part of the LEPRICON package for LWR fluence analysis. It is used to convert power distributions into DOT R- θ source distributions. DOTSOR was used in the ANO-1 benchmark analysis at ORNL (see Section 3.2.2). Installation on the UCC-IBM was verified by TEC using the ANO-1 data. In the CP&L fluence reduction project, the R- θ sources produced by DOTSOR were verified by comparing the sources listed in the DOT balance tables to assembly powers.

DOTSYN, like DOTSOR, was produced by ORNL (M. L. Williams) for EPRI as part of the LEPRICON package. This module produces a three-dimensional flux distribution from one- and two-dimensional flux distributions using the synthesis technique described in Section 2.2.3. The DOTSYN methodology was used in the ANO-1, PCA, and PSF benchmarks discussed in Section 3.2.2 as well as other analyses. The version of DOTSYN used in the CP&L fluence reduction analysis was produced specifically for this analysis, but was written by the same author that produced the code for EPRI. The version used in the CP&L analysis was verified by comparison to hand calculations.

PDQ7V2/010 (ARMP-compatible) is an industry standard multigroup fine-mesh diffusion code provided by EPRI through UCC.

XTGPWR (Version DMAY80) is the Exxon Nuclear Corporation's design nodal simulator, and differs from CP&L's version TNRO5010 because it has been expanded to model 24 axial nodes. Version DMAY80 was made available to CP&L by ENC through UCC for the PLSA studies.

XPOSE (Version DMAR78) is ENC's revised LEOPARD code supplied to CP&L through UCC. It is used to provide two-group diffusion parameters (MND thermal treatment) for fueled regions in CP&L's PDQ and XTG models.

AMPX-II was developed at ORNL. It has been used to develop many benchmarked cross-section libraries, including the 218-group neutron library produced by an NRC-sponsored program⁷ for criticality safety studies and the 56-group ELXSIR library produced for EPRI. The CP&L fluence reduction project used AMPX-II to reduce the 218-group library to a 102-group

neutron library (36 thermal groups) and then to a 2-group library for production of 2-group diffusion constants.

AXFRAC, REDUCT, DIFF, XPTX, XMIX, and DC2G were produced specifically for the CP&L fluence reduction project. The functions of each of these codes are described in Section 4.1. Each code was verified by comparing results with hand calculations and comparing intermediate results.

3.2.2 Past Benchmarking of Methods

The PCA located at ORNL is a low-power critical facility that has been used for several NRC-sponsored experiments to benchmark LWR pressure vessel (PV) fluence calculational methods. The methods used by TEC for this analysis of the H. B. Robinson vessel are essentially the same as used by ORNL in their calculations of the PCA experiments.^{1,2} These methods are basically a DOT-IV³ P3-S8 transport calculation using a VITAMIN-C⁴-based cross-section library, and are consistent with the ASTM-recommended procedures set forth in E706(II). Leakage in the third dimension of the PCA configuration was accounted for by using a synthesis approximation similar to that used by TEC in the H. B. Robinson Plant analysis. This approximation was verified for the PCA midplane analysis by comparison with 3-D Monte Carlo results.⁵ With these methods ORNL was able to predict the experimental dosimeter reaction rates to an agreement of about 5% at the front of the simulated PV and about 10% at the T/4 position.¹ This accuracy is within the acceptable criteria for RPV fluence calculations.⁶

Further benchmarking of the methods used by TEC was performed by ORNL for the NRC at the Oak Ridge Research Reactor (ORR) Pool Side Facility

(PSF). One experiment completed at this facility is the "Westinghouse Perturbation Experiment."⁷ In this experiment a Westinghouse dosimeter surveillance capsule (as used in the H. B. Robinson Plant) was placed in the neutron field of the PSF, along with a simulated thermal shield and PV. Calculations of the dosimeter reaction rates in the capsule agreed with the experimental results within about 10%. Off-midplane results were also obtained for the perturbation experiment, and it was found that the 3-D synthesis procedure, as used by TEC, was able to accurately account for the axial variation in the measured reaction rates, even with an asymmetrical core source distribution.⁷

A final validation of the fluence analysis methods used by TEC is given by benchmark results for the Arkansas Nuclear One, Unit 1, PWR owned by Arkansas Power and Light. This Babcock & Wilcox (B&W) plant has been calculated by ORNL for EPRI using virtually identical methods and data as TEC used for the H. B. Robinson Plant: DOTSOR⁸ was used for the source generation, the ELXSIR⁸ cross-section library was used, the transport calculations were performed with DOT-IV, and the DOTSYN synthesis was used.⁸ Although the results of this study have not yet been published, they have been quoted at several meetings, and TEC and CP&L have been informed of the following results⁹:

For the cavity measurements outside the RPV at the midplane, the calculations agreed with the measured results within about 10% for essentially all dosimeters. There were no in-vessel measurements, and the off-midplane cavity comparisons are inconclusive because of cavity streaming effects.

Note that cavity streaming does not significantly affect in-vessel results, which are of interest in the present H. B. Robinson analysis.

In summary, the methods used by TEC for the H. B. Robinson RPV fluence calculation are state of the art and conform to ASTM recommended procedures. They have been benchmarked in other studies sponsored by the NRC and EPRI. The methods satisfy the target accuracies specified by the NRC for RPV fluence calculations,⁶ and represent the best available technology for the H. B. Robinson analysis.

3.2.3 CP&L Plans for Additional Benchmarking

Capsules S, V, and T were removed from HBR2, respectively, at the ends of Cycles 1, 3, and 8. Relative to a major axis, their locations were 10°, 20°, and 0°, respectively. Measurements of dosimeter activities from these capsules are used here to provide benchmarks for the base case calculations.

For the present Cycle 9 (and planned for future cycles) dosimeters are placed outside the vessel, covering many angles and axial elevations. Additional in-vessel dosimetry is presently being evaluated in order to establish relationships between the outside-of-vessel dosimeter responses and within-vessel measurements.

The Cycle 10 measured power distribution will provide early benchmarks for the accuracy of sources used in the projected case calculations presented here. Measurements of the out-of-vessel dosimeters at EOC will provide benchmarks for extended calculations with the present models. We will thus have timely indications of any significant revisions to the final estimates of this analysis.

3.3 REFERENCES

1. Stallman, F. W., et al. Reactor Calculation Benchmark PCA Blind Test Results, ORNL/NUREG/TM-428, Oak Ridge National Laboratory, 1981.
2. Maerker, R. E. "Sn Transport Calculations of the PCA Experiments with Some Estimated Uncertainties," Trans. Am. Nucl. Soc., Vol. 34, p. 628, 1980.
3. Rhoades, W. A., and Childs, R. L. An Updated Version of the DOT 4 One- and Two-Dimensional Neutron/Photon Transport Code, ORNL-5851, Oak Ridge National Laboratory, 1982.
4. RSIC Data Library Collection, VITAMIN-C, 171 Neutron Group, 36 Gamma-Ray Group Cross Sections in AMPX and CCCC Interface Formats for Fusion and LMFBR Neutronics, DLC-41, Oak Ridge National Laboratory, 1978.
5. Moudlin, P. J., and R. E. Maerker. "Supplementary Neutron Flux Calculations for the ORNL Pool Critical Assembly Pressure Vessel Facility," Proceedings of Fourth ASTM-EURATOM Symposium on Reactor Dosimeter, NUREG/CP-0029, Vol. 2, Gaithersburg, Maryland, 1982.
6. McElroy, W. N., et al. "Surveillance Dosimetry of Operating Power Plants," Proceedings of Fourth ASTM-EURATOM Symposium on Reactor Dosimeter, NUREG/CP-0029, Vol. 2, Gaithersburg, Maryland, 1982.
7. Maerker, R. E., and M. L. Williams. "Calculations of the Westinghouse Perturbation Experiment at the Poolside Facility," Proceedings of Fourth ASTM-EURATOM Symposium on Reactor Dosimeter, NUREG/CP-0029, Vol. 2, Gaithersburg, Maryland, 1982.

8. Maerker, R. E., M. L. Williams, and B. L. Broadhead. "Summary Documentation of EPRI Workshop on LWR Pressure Vessel Fluence Calculations with the LEPRICON Code System," Electric Power Research Institute, Palo Alto, 1983.
9. Williams, M. L. Personal communication.

Section 4
SUPPORTING MATERIAL

4.1 DESCRIPTION OF THE CODES USED IN THE ANALYSIS

This analysis used the computer codes that are listed in Table 4-1. For the codes distributed by either RSIC or EPRI or obtained from ENC, the description on the following pages consists of excerpts from the user manuals distributed with the computer codes. For a more detailed description of the codes, the user manuals listed in the references in Section 4 should be consulted. All other computer codes were written in the process of this analysis and are described in this report.

4.1.1 The GIP Computer Code

The GIP¹ code accepts nuclide-organized microscopic cross-section data in the ALC1 format. GIP prepares a group-organized file of microscopic and/or macroscopic cross sections for use by the DOT or ANISN computer codes. The macroscopic cross-section mixtures are prepared by GIP using the mixing table contained in the input data stream for the specific case. This mixing table consists of the microscopic nuclide identifiers, the associated number density, and the resultant mixture identifier.

4.1.2 The DOT-IV Computer Code

DOT IV² determines the flux or fluence of particles throughout a one- or two-dimensional geometric system due to sources either generated as a result of particle interaction with the medium or incident upon the

Table 4-1

COMPUTER CODES USED IN THE REACTOR PRESSURE VESSEL FLUENCE ANALYSIS

Code Name	Source of Code
DOS a. GIP b. DOT-IV	Radiation Shielding Information Center
ANISN-W	Radiation Shielding Information Center
AMPX-II a. NITAWL b. XSDRNPM	Radiation Shielding Information Center
DIFF	Technology for Energy Corporation
XPTX	Technology for Energy Corporation
XMIX	Technology for Energy Corporation
DC2G	Technology for Energy Corporation
PDQ-7	Electric Power Research Institute
XTG	Exxon Nuclear Corporation
XPOSE	Exxon Nuclear Corporation
AXFRAC	Carolina Power and Light
DOTSOR	Electric Power Research Institute
DOTSYN	Technology for Energy Corporation
REDUCT	Technology for Energy Corporation

system from external sources. The principal application is to the deep-penetration transport of neutrons and photons.

The Boltzman transport equation is solved using either the method of discrete ordinates or the diffusion theory approximation. In the discrete ordinates method, the primary mode of operation, balance equations are solved for the flow of particles moving in a set of discrete directions in each cell of a space mesh, and in each group of a multigroup energy structure. Iterations are performed until all implicitness in the coupling of cells, directions, groups, and source regeneration has been resolved.

4.1.3 The ANISN-W Computer Code

ANISN-W³ solves the one-dimensional Boltzman transport equation for neutrons or gamma rays. The geometry may be slab, spherical, or cylindrical. The source may be fixed, or fission, or a subcritical combination of the two.

The solution technique is an advanced discrete ordinates method that represents a generalization of the method originated by G. C. Wick and developed and extended to curvilinear geometry by B. G. Carlson at Los Alamos Scientific Laboratory. ANISN-W was designed to solve deep penetration problems in which angle-dependent spectra are calculated in detail. ANISN-W includes techniques for handling general anisotropic scattering, pointwise convergence criteria, and alternate step-function difference equations that effectively remove the oscillating flux distributions sometimes found in discrete ordinates solutions.

4.1.4 The Nordheim's Integral Treatment and Working Library (NITAWL) Computer Code

NITAWL⁴ is responsible for reading the general AMPX master library formatted cross sections, performing resonance self-shielding calculations, and collecting the data into a working library. The actual neutron resonance self-shielding calculation employs the Nordheim integral treatment, though the narrow resonance and an infinite mass treatment are available as alternate methods.

4.1.5 The XSDRNPM Computer Code

The XSDRNPM⁴ module is provided in the AMPX system for two purposes. First, it provides a one-dimensional transport capability for calculating reaction rates, eigenvalues, and critical dimensions. Second, it allows spatial cross-section weighting to be performed. XSDRNPM supports four weighting options: (1) cell weighting, (2) zone weighting, (3) region weighting, and (4) "inner" cell weighting. Additionally, XSDRNPM can use "inscatter" and "outscatter" approximations and calculate transport cross sections for use in diffusion theory applications.

4.1.6 The DIFF Computer Code

The DIFF code is used to compute the space-dependent diffusion coefficients by employing the equation of Fick's law. DIFF inputs the 102-group angular fluxes at the mesh interval boundaries from a flux tape produced by the XSDRNPM code. It calculates the total flux and current at each mesh boundary and collapses the fluxes and currents from 102 groups to 2 groups. Then the 2-group diffusion coefficients at each mesh boundary are calculated from the Fick's law generation. The flux

gradient at the mesh boundary is obtained by linearly differencing the fluxes at the nearby mesh boundaries. The 2-group diffusion coefficients in each region are calculated by space-averaging the diffusion coefficients over the interior mesh boundaries within each spatial region.

4.1.7 The XPTX Computer Code

The XPTX computer code is used to compute multigroup microscopic transport cross sections for nuclides in a working cross-section library. The transport cross-section calculation is based upon both the "inscatter" and "outscatter" approximations. The transport cross-section weighting function used in the inscatter approximation of the transport cross-section calculation is calculated by the XSDRNPM code.

4.1.8 The XMIX Computer Code

The XMIX code is used to compute the macroscopic transport cross sections in each material region. XMIX inputs the microscopic transport cross sections generated from the XPTX code and the number densities of nuclides in the region.

4.1.9 The DC2G Computer Code

The DC2G code is used to compute the 2-group diffusion coefficients in each region by collapsing the 102-group diffusion coefficients using the 102-group transport cross-section weighting function for that region. The 102-group diffusion coefficients in region k are calculated by

$$D_g^k = \frac{1}{3 \sum_{t,r}^k} \quad \text{for } g = 1 \text{ to } 102$$

where Σ_{trg}^k is the macroscopic transport cross section in group g and in region k .

4.1.10 The PDQ 7 Computer Code

The PDQ7/HARMONY⁵ is a multigroup diffusion-depletion code. PDQ7 determines the spatial flux and power distribution from a specified geometry and material description. The HARMONY portion of the code performs the depletion phase of the problem by solving the differential equations describing the time behavior of the nuclide concentrations for that time interval. The new distribution of nuclide concentrations are used in the generation of few-group macroscopic cross sections for the next spatial calculation.

The CP&L PDQ7/HARMONY setup for the Robinson core is a 125 x 125 mesh with explicit description of the core, baffle, barrel, outside water, thermal shield, and vessel. Twenty-four isotopes are tracked for each mesh interval.

4.1.11 The XTG Computer Code

XTG⁶ is a modified two-group coarse mesh reactor simulator. The model is designed to accept regular or MND group cross sections and simulate the reactor for any steady-state situation. The conditions under which the cross sections were generated are input, and XTG uses this information to store all cross sections on a common base (i.e., zero boron, zero Xenon). The cross sections are recalled and modified to fit the reactor conditions and account for Doppler effects, time and power dependent iodine and xenon, boron, power and moderator density changes, burnable poison, and control rods.

The PWR model was designed and tested at four nodes per assembly; however, it can be operated at one node per assembly if full core calculations are performed or if the centerline of the reactor does not bisect the central assemblies. The shuffling logic also assumes four nodes per assembly.

4.1.12 The XPOSE Computer Code

XPOSE⁷ is identical in most ways to the LEOPARD code which combines the MUFT and SOFOCATE models with CINDER depletion. The original model has been expanded to include some trans-plutonium elements as well as Np-237 and Pu-238. In addition, the thermal energy range has been extended to 1.855 eV to allow the Pu-240 resonance at 1.056 eV to be treated in the thermal part of the code. The group structure is finer, and spatial self-shielding effects⁰ are accounted for in a detailed manner.

Edits are automated in XPOSE so that output is formatted for input to XTG or PDQ7.

4.1.13 The AXFRAC Computer Code

AXFRAC provides input to DOTSOR to normalize the pin-wise relative power distributions from PDQ7 and split the distributions into upper-core and lower-core regions according to the axial distributions from XTG. In addition, correction factors equal to the ratio of core-average κ/ν to assembly average κ/ν are applied to the normalization (DOTSOR then provides κ/ν corresponding to core average exposure).

A second function of AXFRAC is to provide neutron sources for the R-Z DOT and R ANISN calculations necessary for the synthesis of 3-D flux distributions.

The choice was made for the synthesis to model the R-Z and R distributions to represent the core along its major axis since the critical areas for vessel fluence accumulation are opposite the core flats. The R-Z source synthesized by AXFRAC from the PDQ7 and XTG relative power distributions does not assume the R and Z distributions are separable. The R distribution is somewhat arbitrary and is normalized by the ANISN calculation in the final synthesis. A listing of AXFRAC is given in Appendix B.

4.1.14 The DOTSOR Computer Code

The function of the DOTSOR⁸ computer code is to produce a distributed neutron source in R- θ geometry for input to the DOT-IV transport code, given a specified power distribution in X-Y coordinates. The code was specifically developed for application to LWR calculations in which the reactor core region can be specified easily on an X-Y coordinate grid, whereas the ex-core configuration is described by cylindrical geometry.

The DOTSOR calculation accepts the core power distribution as input, converts this distribution from the X-Y geometry to the R- θ geometry, and converts the R-THETA power density to a neutron source density. The factor to convert from core power density to neutron source density is determined as a function of the core burnup. The final R- θ neutron source is punched out in card format suitable for input into the DOT-IV computer code.

4.1.15 The DOTSYN Computer Code

The DOTSYN computer code was written at TEC to perform the flux synthesis calculations. This code receives as input the geometry description for the DOT-IV R- θ model, the geometry input for the DOT-IV R-Z model, the geometry input for the ANISN-W radial model, and the associated multigroup neutron fluxes for these models. DOTSYN then uses these values to compute the three-dimensional neutron fluxes using the flux synthesis technique specified in Section 2.2.3. This synthesis technique utilized the same methods as those used in the analysis of the Arkansas Nuclear One, Unit 1 (ANO-1), in the development of the EPRI LEPRICON⁸ package.

4.1.16 The REDUCT Computer Code

The REDUCT computer code is used to compute the reactor pressure vessel fluence reduction factor for the partial length shield assembly. The reduction factor is computed as the ratio of the flux greater than 1 MeV for the pre- and post-PLSA fluxes calculated in the DOTSYN computer code. The resulting three-dimensional reduction factor is traced on the printed output for specified regions of the problem geometry.

4.2 CROSS-SECTION LIBRARY DESCRIPTIONS

The five cross-section libraries listed in Table 4-2 were used in this analysis. Each of the following sections describes one of the listed libraries. For standard libraries obtained from sources outside of the analysis team, the descriptions provided are excerpts from the documentation provided by the source. A more complete description of the

cross-section libraries is provided in the references for these libraries.

Table 4-2
CROSS-SECTION LIBRARIES USED IN ANALYSES

Library Name	Supplier
CSRL master library	Radiation Shielding Information Center
102 group library	Technology for Energy Corporation
PLSA 2 group cross sections	Technology for Energy Corporation
Core 2 group cross sections	Carolina Power and Light
ELXSIR cross-section library	Electric Power Research Institute
XPOSE cross-section library	Exxon Nuclear Company

4.2.1 The CSRL Master Library

The CSRL⁹ master library used in this analysis was specifically generated for criticality safety studies. The library contains data for the fuel, structural, and neutron-absorbing materials and is a data base for the generation of fine- or broad-group cross sections for shipping cask calculations and other criticality safety neutronics analyses. The group structure of the library was chosen to fit the important cross-section structure of materials likely to appear in criticality safety problems. Emphasis was placed on the resonance and thermal energy ranges. The 218-group structure contains 140 epithermal groups above and 78 thermal groups below 3.05 eV.

4.2.2 The 102-Group Cross-Section Library

The 102-group cross-section library was generated from a number of cell calculations using AMPX II modules NITAWL and XSDRNPM. The cell calculations consist of 1-D neutron transport calculations for the mockups of the fuel pin, "water hole" in a fuel assembly, shield pin in the PLSA, and slab zones of core baffle and water.

NITAWL was used both to perform neutron resonance self-shielding calculations for the resonance absorbers U-235 and U-238, and to convert the 218-group AMPX master cross-section library into the working format suitable for later neutron transport calculations. The Nordheim integral treatment was specified as the method of the neutron resonance self-shielding calculations for U-235 and U-238. The Dancoff correction factor for the cylindrical fuel element lattice under consideration was calculated using the method described in Reference 10.

Following the self-shielding calculations, XSDRNPM was used to perform eigenvalue calculations for the 2% and 3% UO₂ fuel pin cells. Fixed-source calculations were performed for the water hole cells and baffle-water, water-baffle-water 1-D slab zones. The U-235 fission spectrum was used as the isotopic surface source in the fixed-source calculations for the baffle-water zone, and the fission spectrum-1/E-Maxwellian cross-section weighting function was used as the source in the water-baffle-water zone calculation. The orders of angular quadrature and scattering were 8 and 3, respectively, for both eigenvalue and fixed-source calculations. Reflected and white boundary conditions were used at the left and right boundaries in the fuel cell calculations.

Reflected and vacuum boundary conditions were used in the fixed-source calculations.

The 102-group cell-averaged cross-section library for each cell calculation was generated by cell-weighting and group-collapsing the 218-group working libraries. Out of these 102 groups, 36 groups fall into the thermal group region of the final 2-group structure. The upper energy boundary of the thermal groups in the 102-group structure was set at 1.86 eV. The zone-weighting option was specified in the zone calculations to generate the zone-averaged 102-group cross-section libraries.

4.2.3 Two-Group PLSA Cross Sections

After the 102-group cell-averaged and zone-averaged cross sections had been generated, XSDRNPM was employed to perform an S_{16}, P_3 eigenvalue calculation for the 1-D slab core model with SS-304 as the PLSA shield material. Reflected and vacuum boundary conditions were used at the left and right boundaries, respectively. Zone-weighting was specified in the calculation to generate zone-averaged cross sections. The 102-group cross-section structure was collapsed to a 2-group structure. The cut-off energy for thermal neutrons was set to 1.86 eV.

Two-group diffusion constants for the SS-304 PLSA were calculated from the 2-group cross-section library generated by the 1-D slab XSDRNPM calculation as described above. These two-group constants were employed in the CP&L diffusion codes for the neutron flux and power distribution calculations for the actual core configuration. The two-group constants consist of the diffusion coefficients, macroscopic absorption, removal, and fission cross sections.

The thermal group diffusion coefficient using the mixed number density (MND) procedure was calculated for each of the regions. First, the thermal group transport cross section using the outscatter approximation was calculated by collapsing the outscatter transport cross sections in the thermal groups of the 102-group structure using the zone-averaged total flux as a weighting function in each zone. Then the MND diffusion coefficient for the thermal group was calculated from the equation:

$$D_2^{\text{MND}} = \frac{1}{3 \sum_{\text{tr}2}^{\text{MND}}} ,$$

$$\sum_{\text{tr}2}^{\text{MND}} = \sum_{\text{tr}2} + (V_R - 1) \sum_{\text{a}2} ,$$

$$V_R = \frac{\sqrt{\pi}}{2} (293/T)^{1/2} (\bar{v}_{\text{th}}/220) ,$$

\bar{v}_{th} = the neutron velocity in the zone,

T = the moderator temperature in the zone in °K,

$\sum_{\text{a}2}$ = the thermal group absorption cross section in the zone, and

$\sum_{\text{tr}2}$ = the flux-averaged outscatter transport cross section in the zone.

Note that V_R represents the Maxwellian-corrected average thermal neutron velocity normalized to 2200 m/s.

4.2.4 Two-Group Macroscopic Cross Sections

The cross-section data needed to solve the two-group diffusion equation are the absorption cross sections Σ_{a1} and Σ_{a2} , fission cross sections $\nu\Sigma_{f1}$ and $\nu\Sigma_{f2}$, and the removal cross section Σ_{R1} in each zone of the SS-304 PLSA core model. The microscopic cross sections for soluble boron in the thermal group for the MND procedure were also calculated.

The two-group constants were used in a PDQ calculation with the same geometric model as used in the 102-group XSDRNPM calculation for comparison purposes. The two-group constants and differences between the diffusion and transport calculations are summarized in Table 4-3.

Only the PLSA constants from this study were used in the actual cycle 10 PDQ calculations; but the comparison shows they model the proper effect on fission rate near the fuel-PLSA interface.

4.2.5 The ELXSIR 56-Group Cross-Section Library

The ELXSIR⁸ (EPRI LWR X sections for irradiation studies) P3, multigroup cross-section library was generated to serve as the standard DOT-IV library in the LEPRICON system for LWR dosimetry calculations. The cross sections are mainly applicable to problems concerning the transport of epithermal and high-energy neutrons from the core volume to the pressure vessel and cavity region of a LWR. These types of problems are frequently encountered in computing surveillance dosimetry activation

Table 4-3

TWO-GROUP DIFFUSION CONSTANTS AND SLAB MODEL COMPARISONS

Zone	1	2	3	4	5
Material	U(2%)O ₂	U(3%)O ₂	U(3%)O ₂	S.S.-304 PLSA	S.S.-304 PLSA
D ₁	1.47E+00	1.38E+00	1.24E+00	1.22E+00	1.45E+00
^{MND} D ₂	3.33E-01	3.30E-01	3.20E-01	2.89E-01	2.79E-01
\sum_a^1	8.31E-03	8.79E-03	9.36E-03	1.52E-03	1.68E-03
\sum_a^2	8.76E-02	1.16E-01	1.15E-01	7.01E-02	6.92E-02
\sum_R^1	1.87E-02	1.79E-02	2.01E-02	2.38E-02	2.88E-02
\sum_f^1	4.61E-03	5.72E-03	5.92E-03	0.0	0.0
\sum_f^2	1.22E-01	1.80E-01	1.78E-01	0.0	0.0

% Error

Fission rate	-0.974	1.45	0.318	-	-
Eigenvalue	1.15				

and/or the accumulated pressure vessel fluence or radiation damage. Although thermal and epithermal cross sections are included in the library, the group structure emphasizes the higher energy range. The cross sections were not generated for application to reactor criticality calculations. Of the 56 neutron groups in the ELXSIR library, the upper 27 energy groups represent energies greater than 1.0 MeV. Specifically, the upper 27 energy groups represent energies greater than 1.0026 MeV.

4.3 SOURCE-TERM DOCUMENTATION

This section provides additional supportive detail on the development of the three-dimensional source distribution as outlined in Section 2.2.2.

4.3.1 Generation of the Reference Distribution

In order to meet criterion 3 of Section 2.2.2, CP&L analytical models were used to generate both reference and projected distributions. The models are 2-D, 2-group, pin-by-pin, quarter-core using PDQ7/HARMONY^{5,11}, and 3-D, 1.5-group, coarse-mesh quarter-core using the nodal simulator, XTGPWR.⁶ Cross sections for both models are supplied by XPOSE, ENC's LEOPARD-based code.⁷ CP&L has used these models to perform design review and core follow functions for five cycles. The models are "best-estimate".

The Cycle 8 average radial-relative pin power distribution was obtained as the exposure-weighted average of distributions given by an eight-step depletion of the cycle with PDQ 7/HARMONY. TEC was supplied the eight-step distributions and the exposure-weighted average on tape at UCC.

Figure 4-1 compares normalized assembly delta exposures for Cycle 8 obtained with the PDQ7 model and measured (i.e., accumulated by the TOTE code).¹² The PDQ7 distribution for each assembly corresponds to the cycle-averaged pin distribution supplied to TEC. The standard deviation of PDQ7-measured differences is 3.1% and indicative of the uncertainty in the assembly-relative power distributions from the PDQ7 model.

The pin distributions supplied to TEC were normalized to a core-wide pin average of unity (split pin cells count as whole pins). Figures 4-2 and 4-3 show the averaged distributions for Locations H-15 and G-15 (closest to the vessel) normalized to an assembly average of unity.

Axial distributions were obtained from XTG simulation of Cycle 8. The cycle delta exposures obtained from XTG were normalized both assembly-wise and four-node-per-assembly-wise and supplied to TEC through UCC as shown in Table 4-4. The normalization is that each 24-axial node distribution (covering active fuel length) sums to unity.

Figure 4-4 compares the core-averaged distribution corresponding to the assembly distributions supplied to TEC with the measured distributions obtained from TOTE. The standard deviation of XTG-measured differences is about 3% on a nodal basis and indicates the uncertainty in the axial distributions from XTG.

4.3.2 Generation of Projected Distribution

PLSAs are scheduled to occupy the core flats in HBR2 beginning with Cycle 10. Since the PLSA-fueled region will contain new fuel (on the core flats), the selection of Cycle 10 as typical of future cycles will



Carolina Power & Light Company

INCORE ANALYSIS UNIT

ENGINEERING CALCULATION
(COMPUTER INPUT)

PREPARED BY: K. Cantrell

DATE: 5/4/83

PAGE NO.

CHECKED BY: K. Karcher

DATE: 8/17/83

OF

SUBJECT:
CYC 8 Normalized Assembly Delta Exposures

COMPUTER PROGRAM: PDQ7-TOTE	VERSION:	PRODUCTION DEVELOPMENT <input type="checkbox"/>	TAPE NO. OR FILE NAME:
REACTOR: HBR#2	CYCLE: 8	EXPOSURE:	STATE:

	H	G	F	E	D	C	B	A
8	1 .680 .702	2 9 1.054 1.086	3 17 .944 .996	4 24 .933 .964	5 31 1.166 1.152	6 37 1.141 1.147	7 42 .939 .953	8 46 .846 .809
9	9 1.058 1.091	10 .934 .980	11 18 1.148 1.174	12 25 .992 1.029	13 32 1.183 1.183	14 38 .964 .988	15 43 1.210 1.166	16 47 .709 .672
10	17 .951 .990	18 1.155 1.172	19 .963 1.003	20 26 1.174 1.189	21 33 .981 1.010	22 39 1.099 1.096	23 44 1.028 .983	
11	24 .943 .965	25 1.000 1.026	26 1.179 1.183	27 1.088 1.117	28 34 .946 .976	29 40 1.173 1.140	30 45 .733 .698	
12	31 1.183 1.140	32 1.193 1.171	33 .988 1.010	34 .950 .975	35 .921 .934	36 41 .743 .724	PDQ07 Measured (TOTE)	
13	37 1.148 1.105	38 .968 .968	39 1.103 1.094	40 1.174 1.143	41 .742 .723			
14	42 .936 .933	43 1.208 1.144	44 1.028 .981	45 .733 .700				
15	46 .843 .798	47 .707 .664						

Figure 4-1
Cycle 8 Normalized Assembly
Delta Exposures

Std. Dev. of PDQ07-TOTE Differences = 3.1%

Figure 4-2.

HBR2 CYC8 PDQ AVERAGED PIN RELATIVE POWER

ASSEMBLY 46 (H-15)

1.23	1.23	1.24	1.23	1.23	1.23	1.22	1.21
1.24	1.26	1.27	1.26	1.25	1.26	1.23	1.20
1.29	1.30	0.00	1.28	1.28	0.00	1.24	1.19
0.00	1.28	1.29	1.29	1.27	1.25	1.20	1.16
1.22	1.21	1.23	0.00	1.25	1.22	1.17	1.13
1.14	1.14	1.16	1.19	1.21	0.00	1.15	1.10
1.12	1.10	1.10	1.13	1.16	1.15	1.09	1.05
0.00	1.06	1.05	1.08	0.00	1.09	1.03	1.00
1.02	1.00	1.00	1.03	1.06	1.04	.99	.95
.94	.94	.96	.98	1.00	0.00	.94	.90
.91	.90	.92	0.00	.94	.91	.87	.83
0.00	.86	.87	.87	.85	.83	.80	.76
.77	.77	0.00	.76	.76	0.00	.72	.68
.63	.64	.65	.64	.63	.63	.61	.58
.49	.49	.49	.48	.48	.48	.47	.46

Figure 4-3.

HBR2 CYC8 PDQ AVERAGED PIN RELATIVE POWER

ASSEMBLY 47 (G-15)

1.45	1.47	1.48	1.48	1.48	1.47	1.45	1.42	1.40	1.38	1.33	1.28	1.22	1.12	.96
1.44	1.47	1.50	1.49	1.48	1.48	1.45	1.41	1.39	1.37	1.32	1.26	1.19	1.07	.87
1.42	1.47	0.00	1.50	1.49	0.00	1.47	1.42	1.40	0.00	1.31	1.24	0.00	1.02	.82
1.38	1.42	1.46	1.47	1.48	1.46	1.43	0.00	1.36	1.32	1.27	1.19	1.10	.96	.77
1.34	1.38	1.42	1.44	0.00	1.38	1.33	1.30	1.26	1.24	0.00	1.15	1.04	.91	.73
1.30	1.34	0.00	1.38	1.34	1.28	1.23	1.20	1.16	1.14	1.12	1.08	0.00	.86	.69
1.24	1.27	1.32	1.32	1.25	1.19	1.17	1.15	1.10	1.05	1.03	1.01	.93	.80	.64
1.18	1.20	1.24	0.00	1.20	1.13	1.12	0.00	1.05	.99	.97	0.00	.86	.73	.60
1.12	1.15	1.19	1.18	1.12	1.06	1.04	1.02	.97	.92	.90	.88	.80	.69	.55
1.06	1.09	0.00	1.11	1.07	1.01	.96	.93	.90	.87	.85	.82	0.00	.64	.51
.98	1.00	1.03	1.03	0.00	.96	.92	.89	.85	.83	0.00	.75	.68	.58	.46
.90	.92	.94	.93	.93	.90	.87	0.00	.81	.77	.73	.67	.61	.52	.41
.80	.83	0.00	.83	.81	0.00	.78	.74	.72	0.00	.64	.59	0.00	.46	.37
.69	.70	.70	.69	.67	.67	.64	.61	.59	.56	.53	.49	.45	.39	.32
.54	.53	.53	.52	.51	.50	.48	.46	.44	.42	.39	.37	.33	.30	.26

Table 4-4

XTG HBR2 Cycle 8 Averaged Axial Power Distributions

ASSEMBLY-WISE AXIAL SOURCE DISTRIBUTIONS
EAST-SOUTHEAST OCTANT
FORMAT(2I3,2X,8F9.5,2(/,8X,8F9.5))
COORDINATES 24 AXIAL NODE RELATIVE SOURCE DISTRIBUTION, TOP TO BOTTOM

1	1	0.02661	0.03843	0.04226	0.04416	0.04412	0.04454	0.04530	0.0451
		0.04476	0.04450	0.04426	0.04401	0.04365	0.04343	0.04325	0.0430
		0.04284	0.04274	0.04274	0.04259	0.04237	0.04068	0.03788	0.0266
2	1	0.02452	0.03639	0.04179	0.04397	0.04469	0.04490	0.04493	0.0448
		0.04467	0.04452	0.04437	0.04423	0.04410	0.04398	0.04387	0.0438
		0.04375	0.04374	0.04373	0.04360	0.04305	0.04125	0.03644	0.0248
2	2	0.02615	0.03770	0.04263	0.04445	0.04496	0.04498	0.04486	0.0446
		0.04447	0.04428	0.04410	0.04392	0.04375	0.04359	0.04344	0.0433
		0.04323	0.04317	0.04313	0.04302	0.04255	0.04103	0.03671	0.0259
3	1	0.02593	0.03727	0.04219	0.04410	0.04473	0.04486	0.04481	0.0446
		0.04454	0.04438	0.04422	0.04407	0.04392	0.04378	0.04366	0.0435
		0.04347	0.04341	0.04334	0.04316	0.04260	0.04096	0.03657	0.0258
3	2	0.02410	0.03588	0.04139	0.04369	0.04454	0.04479	0.04481	0.0447
		0.04464	0.04453	0.04443	0.04433	0.04425	0.04417	0.04411	0.0440
		0.04405	0.04405	0.04403	0.04386	0.04323	0.04131	0.03632	0.0247
3	3	0.02602	0.03736	0.04229	0.04419	0.04482	0.04492	0.04484	0.0446
		0.04453	0.04436	0.04421	0.04405	0.04390	0.04376	0.04364	0.0435
		0.04344	0.04337	0.04329	0.04309	0.04250	0.04085	0.03649	0.0258
4	1	0.02580	0.03700	0.04187	0.04379	0.04448	0.04473	0.04486	0.0448
		0.04469	0.04454	0.04439	0.04422	0.04406	0.04392	0.04379	0.0436
		0.04357	0.04349	0.04338	0.04315	0.04253	0.04087	0.03651	0.0258
4	2	0.02536	0.03661	0.04164	0.04370	0.04447	0.04473	0.04480	0.0447
		0.04465	0.04453	0.04440	0.04427	0.04415	0.04403	0.04393	0.0438
		0.04377	0.04371	0.04361	0.04338	0.04272	0.04095	0.03643	0.0256
4	3	0.02382	0.03549	0.04103	0.04344	0.04440	0.04474	0.04482	0.0448
		0.04473	0.04465	0.04456	0.04448	0.04442	0.04436	0.04431	0.0442
		0.04425	0.04423	0.04417	0.04394	0.04320	0.04119	0.03614	0.0245
4	4	0.02413	0.03573	0.04123	0.04363	0.04459	0.04492	0.04497	0.0449
		0.04482	0.04471	0.04460	0.04449	0.04440	0.04431	0.04423	0.0441
		0.04413	0.04408	0.04397	0.04368	0.04289	0.04087	0.03591	0.0246
5	1	0.02291	0.03415	0.03954	0.04193	0.04294	0.04380	0.04499	0.0451
		0.04516	0.04511	0.04503	0.04495	0.04488	0.04482	0.04477	0.0447
		0.04471	0.04469	0.04462	0.04437	0.04363	0.04161	0.03655	0.0249
5	2	0.02330	0.03478	0.04034	0.04284	0.04392	0.04445	0.04477	0.0448
		0.04487	0.04483	0.04477	0.04471	0.04466	0.04462	0.04459	0.0445
		0.04456	0.04454	0.04446	0.04419	0.04339	0.04129	0.03614	0.0245
5	3	0.02488	0.03608	0.04125	0.04349	0.04443	0.04477	0.04488	0.0448
		0.04479	0.04469	0.04458	0.04447	0.04436	0.04427	0.04419	0.0441
		0.04405	0.04397	0.04382	0.04348	0.04266	0.04070	0.03601	0.0252
5	4	0.02437	0.03564	0.04101	0.04343	0.04448	0.04489	0.04500	0.0449
		0.04492	0.04483	0.04473	0.04462	0.04453	0.04444	0.04438	0.0443
		0.04425	0.04417	0.04399	0.04359	0.04265	0.04050	0.03559	0.0246
5	5	0.02278	0.03440	0.04036	0.04324	0.04456	0.04511	0.04530	0.0453
		0.04527	0.04520	0.04511	0.04502	0.04494	0.04488	0.04483	0.0447
		0.04475	0.04466	0.04446	0.04396	0.04282	0.04026	0.03471	0.0232
6	1	0.02332	0.03475	0.04032	0.04288	0.04402	0.04459	0.04492	0.0450

		0.04502	0.04496	0.04488	0.04481	0.04474	0.04467	0.04462	0.04458
		0.04454	0.04449	0.04436	0.04402	0.04314	0.04099	0.03589	0.02449
6	2	0.02469	0.03588	0.04110	0.04338	0.04435	0.04476	0.04493	0.04494
		0.04488	0.04479	0.04468	0.04456	0.04445	0.04435	0.04426	0.04418
		0.04410	0.04401	0.04384	0.04347	0.04262	0.04063	0.03594	0.02520
6	3	0.02262	0.03404	0.03987	0.04272	0.04407	0.04469	0.04497	0.04507
		0.04508	0.04507	0.04504	0.04501	0.04498	0.04497	0.04496	0.04496
		0.04496	0.04491	0.04475	0.04430	0.04321	0.04072	0.03525	0.02376
6	4	0.02012	0.03174	0.03834	0.04186	0.04366	0.04457	0.04502	0.04526
		0.04538	0.04547	0.04554	0.04561	0.04569	0.04579	0.04589	0.04599
		0.04608	0.04609	0.04594	0.04537	0.04393	0.04072	0.03416	0.02180
6	5	0.01985	0.03177	0.03869	0.04241	0.04430	0.04520	0.04561	0.04578
		0.04583	0.04584	0.04583	0.04583	0.04584	0.04586	0.04589	0.04593
		0.04595	0.04590	0.04565	0.04496	0.04334	0.03990	0.03309	0.02075
7	1	0.02337	0.03452	0.04011	0.04282	0.04412	0.04472	0.04500	0.04509
		0.04511	0.04507	0.04502	0.04497	0.04492	0.04489	0.04485	0.04483
		0.04479	0.04470	0.04449	0.04399	0.04285	0.04040	0.03517	0.02419
7	2	0.02005	0.03161	0.03817	0.04169	0.04352	0.04446	0.04496	0.04523
		0.04538	0.04548	0.04557	0.04565	0.04574	0.04585	0.04595	0.04606
		0.04615	0.04616	0.04600	0.04543	0.04398	0.04078	0.03424	0.02189
7	3	0.01953	0.03117	0.03798	0.04170	0.04365	0.04465	0.04517	0.04543
		0.04558	0.04568	0.04576	0.04584	0.04592	0.04602	0.04613	0.04623
		0.04632	0.04633	0.04613	0.04549	0.04391	0.04049	0.03367	0.02122
7	4	0.01906	0.03086	0.03795	0.04191	0.04399	0.04505	0.04556	0.04580
		0.04592	0.04598	0.04603	0.04607	0.04613	0.04619	0.04627	0.04635
		0.04640	0.04637	0.04611	0.04536	0.04360	0.03990	0.03280	0.02033
8	1	0.01923	0.03094	0.03791	0.04180	0.04387	0.04493	0.04547	0.04574
		0.04588	0.04595	0.04601	0.04606	0.04613	0.04620	0.04628	0.04636
		0.04641	0.04637	0.04610	0.04534	0.04358	0.03994	0.03294	0.02057
8	2	0.01895	0.03074	0.03786	0.04186	0.04399	0.04508	0.04562	0.04589
		0.04601	0.04608	0.04612	0.04617	0.04622	0.04628	0.04635	0.04643
		0.04647	0.04641	0.04612	0.04532	0.04350	0.03974	0.03260	0.02017

4-NODE-PER-ASSEMBLY AXIAL SOURCE DISTRIBUTIONS

EAST-SOUTHEAST OCTANT

FORMAT(2I3,2X,8F9.5,2(/,14X,8F9.5))

COORDINATES 24 AXIAL NODE RELATIVE SOURCE DISTRIBUTION, TOP TO BOTTOM

1	1	0.02661	0.03843	0.04226	0.04416	0.04412	0.04454	0.04530	0.04515
		0.04476	0.04450	0.04426	0.04401	0.04365	0.04343	0.04325	0.04308
		0.04284	0.04274	0.04274	0.04259	0.04237	0.04068	0.03788	0.02663
2	1	0.02480	0.03667	0.04198	0.04409	0.04475	0.04494	0.04500	0.04488
		0.04470	0.04452	0.04435	0.04419	0.04403	0.04388	0.04376	0.04367
		0.04360	0.04357	0.04356	0.04344	0.04291	0.04117	0.03649	0.02503
2	2	0.02641	0.03792	0.04277	0.04453	0.04500	0.04501	0.04491	0.04471
		0.04450	0.04429	0.04409	0.04390	0.04371	0.04353	0.04337	0.04323
		0.04312	0.04306	0.04301	0.04289	0.04243	0.04094	0.03669	0.02599
2	3	0.02619	0.03772	0.04265	0.04447	0.04497	0.04498	0.04485	0.04466
		0.04446	0.04427	0.04409	0.04391	0.04374	0.04358	0.04343	0.04331
		0.04322	0.04316	0.04312	0.04301	0.04254	0.04103	0.03672	0.02593
3	1	0.02424	0.03611	0.04160	0.04386	0.04464	0.04485	0.04486	0.04477
		0.04465	0.04451	0.04439	0.04427	0.04417	0.04407	0.04398	0.04393
		0.04390	0.04390	0.04390	0.04377	0.04319	0.04133	0.03638	0.02473
3	2	0.02619	0.03772	0.04265	0.04447	0.04497	0.04498	0.04485	0.04466
		0.04446	0.04427	0.04409	0.04391	0.04374	0.04358	0.04343	0.04331
		0.04322	0.04316	0.04312	0.04301	0.04254	0.04103	0.03672	0.02593

3	3	0.02591	0.03749	0.04251	0.04438	0.04492	0.04495	0.04482	0.04464
		0.04445	0.04427	0.04411	0.04395	0.04379	0.04364	0.04351	0.04340
		0.04332	0.04327	0.04324	0.04313	0.04266	0.04111	0.03673	0.02581
4	1	0.02564	0.03704	0.04206	0.04403	0.04470	0.04484	0.04480	0.04468
		0.04454	0.04439	0.04424	0.04410	0.04396	0.04383	0.04372	0.04363
		0.04356	0.04352	0.04346	0.04330	0.04272	0.04104	0.03655	0.02565
4	2	0.02371	0.03557	0.04120	0.04359	0.04448	0.04476	0.04480	0.04474
		0.04466	0.04456	0.04448	0.04440	0.04433	0.04427	0.04422	0.04419
		0.04418	0.04420	0.04420	0.04404	0.04338	0.04140	0.03624	0.02443
4	3	0.02400	0.03581	0.04136	0.04369	0.04454	0.04478	0.04480	0.04472
		0.04462	0.04452	0.04442	0.04433	0.04425	0.04418	0.04412	0.04409
		0.04407	0.04408	0.04407	0.04392	0.04329	0.04137	0.03632	0.02463
4	4	0.02600	0.03740	0.04235	0.04425	0.04484	0.04492	0.04482	0.04466
		0.04449	0.04433	0.04417	0.04401	0.04386	0.04372	0.04360	0.04349
		0.04341	0.04335	0.04328	0.04311	0.04256	0.04095	0.03658	0.02585
4	5	0.02608	0.03740	0.04231	0.04420	0.04482	0.04492	0.04484	0.04469
		0.04453	0.04436	0.04420	0.04405	0.04390	0.04376	0.04363	0.04352
		0.04343	0.04335	0.04327	0.04307	0.04248	0.04083	0.03650	0.02588
5	1	0.02622	0.03750	0.04232	0.04417	0.04476	0.04487	0.04482	0.04469
		0.04453	0.04437	0.04420	0.04403	0.04388	0.04373	0.04359	0.04347
		0.04338	0.04330	0.04322	0.04303	0.04247	0.04088	0.03659	0.02597
5	2	0.02427	0.03600	0.04144	0.04371	0.04454	0.04478	0.04481	0.04474
		0.04464	0.04453	0.04443	0.04433	0.04423	0.04415	0.04408	0.04402
		0.04399	0.04399	0.04395	0.04378	0.04315	0.04127	0.03634	0.02481
5	3	0.02441	0.03614	0.04155	0.04378	0.04460	0.04482	0.04482	0.04474
		0.04463	0.04451	0.04439	0.04429	0.04419	0.04410	0.04402	0.04396
		0.04393	0.04392	0.04388	0.04371	0.04308	0.04123	0.03637	0.02493
5	4	0.02608	0.03740	0.04231	0.04420	0.04482	0.04492	0.04484	0.04469
		0.04453	0.04436	0.04420	0.04405	0.04390	0.04376	0.04363	0.04352
		0.04343	0.04335	0.04327	0.04307	0.04248	0.04083	0.03650	0.02588
5	5	0.02605	0.03731	0.04222	0.04414	0.04480	0.04492	0.04485	0.04472
		0.04456	0.04440	0.04425	0.04410	0.04395	0.04381	0.04368	0.04357
		0.04348	0.04340	0.04330	0.04307	0.04244	0.04075	0.03640	0.02584
6	1	0.02625	0.03746	0.04226	0.04408	0.04469	0.04485	0.04487	0.04477
		0.04462	0.04445	0.04428	0.04410	0.04393	0.04377	0.04363	0.04350
		0.04339	0.04329	0.04318	0.04296	0.04237	0.04077	0.03652	0.02601
6	2	0.02526	0.03660	0.04168	0.04376	0.04453	0.04478	0.04483	0.04477
		0.04467	0.04454	0.04441	0.04428	0.04415	0.04403	0.04393	0.04384
		0.04377	0.04371	0.04362	0.04339	0.04273	0.04094	0.03635	0.02544
6	3	0.02528	0.03660	0.04167	0.04375	0.04453	0.04476	0.04478	0.04472
		0.04461	0.04449	0.04437	0.04425	0.04413	0.04402	0.04392	0.04385
		0.04379	0.04373	0.04365	0.04343	0.04277	0.04099	0.03642	0.02551
6	4	0.02349	0.03523	0.04088	0.04335	0.04434	0.04469	0.04478	0.04478
		0.04472	0.04465	0.04459	0.04452	0.04447	0.04443	0.04439	0.04437
		0.04437	0.04437	0.04433	0.04411	0.04337	0.04130	0.03611	0.02435
6	5	0.02376	0.03546	0.04103	0.04345	0.04441	0.04474	0.04481	0.04478
		0.04471	0.04463	0.04455	0.04448	0.04441	0.04436	0.04431	0.04428
		0.04426	0.04425	0.04420	0.04398	0.04324	0.04122	0.03614	0.02452
6	6	0.02423	0.03581	0.04127	0.04363	0.04456	0.04486	0.04491	0.04485
		0.04476	0.04465	0.04454	0.04443	0.04434	0.04425	0.04418	0.04413
		0.04409	0.04405	0.04397	0.04371	0.04296	0.04098	0.03606	0.02477
6	7	0.02420	0.03580	0.04127	0.04366	0.04461	0.04493	0.04497	0.04492
		0.04482	0.04470	0.04459	0.04448	0.04438	0.04429	0.04421	0.04414
		0.04410	0.04404	0.04393	0.04364	0.04286	0.04086	0.03594	0.02467
7	1	0.02535	0.03653	0.04149	0.04350	0.04426	0.04460	0.04485	0.04485

		0.04476	0.04463	0.04449	0.04434	0.04420	0.04407	0.04395	0.04385
		0.04376	0.04368	0.04358	0.04334	0.04270	0.04097	0.03651	0.02574
7	2	0.02536	0.03655	0.04152	0.04357	0.04435	0.04465	0.04479	0.04478
		0.04469	0.04457	0.04444	0.04431	0.04418	0.04406	0.04396	0.04387
		0.04379	0.04372	0.04361	0.04338	0.04271	0.04096	0.03648	0.02570
7	3	0.02552	0.03671	0.04167	0.04370	0.04447	0.04472	0.04478	0.04473
		0.04463	0.04451	0.04438	0.04425	0.04413	0.04401	0.04390	0.04382
		0.04374	0.04367	0.04356	0.04332	0.04266	0.04092	0.03646	0.02574
7	4	0.02387	0.03550	0.04100	0.04340	0.04436	0.04471	0.04481	0.04479
		0.04473	0.04465	0.04457	0.04449	0.04442	0.04436	0.04431	0.04427
		0.04425	0.04423	0.04416	0.04392	0.04319	0.04119	0.03618	0.02465
7	5	0.02415	0.03576	0.04121	0.04357	0.04450	0.04482	0.04488	0.04484
		0.04475	0.04465	0.04455	0.04445	0.04436	0.04428	0.04421	0.04416
		0.04412	0.04408	0.04400	0.04374	0.04301	0.04104	0.03612	0.02476
7	6	0.02420	0.03580	0.04127	0.04366	0.04461	0.04493	0.04497	0.04492
		0.04482	0.04470	0.04459	0.04448	0.04438	0.04429	0.04421	0.04414
		0.04410	0.04404	0.04393	0.04364	0.04286	0.04086	0.03594	0.02467
7	7	0.02403	0.03565	0.04119	0.04363	0.04463	0.04497	0.04504	0.04499
		0.04489	0.04478	0.04466	0.04455	0.04445	0.04436	0.04428	0.04422
		0.04416	0.04410	0.04397	0.04365	0.04282	0.04075	0.03576	0.02447
8	1	0.02328	0.03451	0.03982	0.04211	0.04306	0.04387	0.04502	0.04517
		0.04514	0.04506	0.04497	0.04487	0.04478	0.04470	0.04463	0.04458
		0.04454	0.04451	0.04443	0.04420	0.04348	0.04154	0.03660	0.02513
8	2	0.02289	0.03443	0.04007	0.04262	0.04374	0.04433	0.04473	0.04487
		0.04489	0.04487	0.04482	0.04478	0.04475	0.04472	0.04470	0.04470
		0.04471	0.04471	0.04466	0.04441	0.04361	0.04146	0.03618	0.02436
8	3	0.02359	0.03512	0.04063	0.04307	0.04411	0.04456	0.04477	0.04483
		0.04480	0.04475	0.04468	0.04461	0.04456	0.04450	0.04446	0.04443
		0.04442	0.04440	0.04432	0.04406	0.04329	0.04124	0.03617	0.02462
8	4	0.02469	0.03597	0.04119	0.04345	0.04438	0.04472	0.04484	0.04482
		0.04475	0.04466	0.04456	0.04446	0.04436	0.04427	0.04419	0.04413
		0.04408	0.04401	0.04390	0.04360	0.04282	0.04087	0.03613	0.02515
8	5	0.02513	0.03635	0.04147	0.04366	0.04454	0.04483	0.04489	0.04484
		0.04475	0.04463	0.04452	0.04439	0.04427	0.04417	0.04408	0.04400
		0.04392	0.04384	0.04369	0.04337	0.04259	0.04068	0.03607	0.02531
8	6	0.02456	0.03590	0.04123	0.04358	0.04455	0.04490	0.04498	0.04494
		0.04486	0.04474	0.04464	0.04452	0.04441	0.04432	0.04424	0.04417
		0.04411	0.04403	0.04387	0.04352	0.04267	0.04062	0.03579	0.02483
8	7	0.02457	0.03588	0.04122	0.04359	0.04459	0.04495	0.04503	0.04499
		0.04490	0.04479	0.04468	0.04456	0.04445	0.04435	0.04427	0.04420
		0.04413	0.04403	0.04386	0.04348	0.04258	0.04049	0.03565	0.02477
8	8	0.02339	0.03493	0.04067	0.04336	0.04455	0.04503	0.04518	0.04518
		0.04512	0.04503	0.04494	0.04484	0.04475	0.04468	0.04462	0.04457
		0.04452	0.04444	0.04425	0.04381	0.04277	0.04041	0.03512	0.02384
8	9	0.02264	0.03423	0.04020	0.04311	0.04447	0.04505	0.04526	0.04530
		0.04526	0.04520	0.04513	0.04505	0.04499	0.04494	0.04490	0.04487
		0.04484	0.04476	0.04456	0.04406	0.04290	0.04031	0.03472	0.02326
9	1	0.02253	0.03379	0.03927	0.04174	0.04282	0.04373	0.04495	0.04516
		0.04519	0.04515	0.04509	0.04503	0.04499	0.04494	0.04491	0.04489
		0.04488	0.04487	0.04481	0.04455	0.04377	0.04168	0.03649	0.02475
9	2	0.02304	0.03448	0.04006	0.04260	0.04373	0.04433	0.04475	0.04490
		0.04492	0.04489	0.04484	0.04479	0.04475	0.04472	0.04469	0.04468
		0.04468	0.04467	0.04460	0.04432	0.04351	0.04137	0.03618	0.02451
9	3	0.02367	0.03511	0.04059	0.04305	0.04412	0.04460	0.04483	0.04489
		0.04487	0.04481	0.04474	0.04466	0.04460	0.04453	0.04448	0.04445


		0.04442	0.04438	0.04427	0.04398	0.04316	0.04108	0.03605	0.02465
9	4	0.02477	0.03594	0.04112	0.04339	0.04435	0.04473	0.04486	0.04486
		0.04480	0.04472	0.04462	0.04451	0.04441	0.04432	0.04424	0.04418
		0.04411	0.04403	0.04388	0.04353	0.04270	0.04072	0.03601	0.02520
9	5	0.02495	0.03606	0.04120	0.04347	0.04444	0.04481	0.04492	0.04491
		0.04484	0.04474	0.04463	0.04452	0.04441	0.04432	0.04424	0.04416
		0.04408	0.04398	0.04381	0.04342	0.04254	0.04052	0.03584	0.02519
9	6	0.02424	0.03545	0.04082	0.04328	0.04437	0.04481	0.04495	0.04497
		0.04492	0.04484	0.04476	0.04467	0.04459	0.04452	0.04446	0.04441
		0.04436	0.04428	0.04410	0.04369	0.04272	0.04053	0.03559	0.02468
9	7	0.02411	0.03532	0.04076	0.04329	0.04443	0.04489	0.04505	0.04505
		0.04500	0.04492	0.04483	0.04474	0.04466	0.04459	0.04453	0.04448
		0.04442	0.04432	0.04412	0.04367	0.04264	0.04036	0.03534	0.02447
9	8	0.02264	0.03423	0.04020	0.04311	0.04447	0.04505	0.04526	0.04530
		0.04526	0.04520	0.04513	0.04505	0.04499	0.04494	0.04490	0.04487
		0.04484	0.04476	0.04456	0.04406	0.04290	0.04031	0.03472	0.02326
9	9	0.02207	0.03379	0.04000	0.04309	0.04456	0.04520	0.04544	0.04549
		0.04546	0.04539	0.04531	0.04523	0.04516	0.04512	0.04508	0.04505
		0.04501	0.04492	0.04469	0.04414	0.04286	0.04007	0.03424	0.02261
10	1	0.02323	0.03467	0.04023	0.04275	0.04387	0.04447	0.04487	0.04500
		0.04499	0.04494	0.04487	0.04479	0.04473	0.04467	0.04462	0.04458
		0.04456	0.04452	0.04441	0.04411	0.04329	0.04118	0.03608	0.02457
10	2	0.02484	0.03604	0.04118	0.04339	0.04429	0.04468	0.04488	0.04491
		0.04484	0.04474	0.04462	0.04449	0.04437	0.04426	0.04416	0.04407
		0.04399	0.04390	0.04376	0.04345	0.04268	0.04081	0.03621	0.02543
10	3	0.02502	0.03623	0.04136	0.04355	0.04445	0.04480	0.04492	0.04491
		0.04483	0.04472	0.04460	0.04447	0.04434	0.04423	0.04412	0.04403
		0.04394	0.04384	0.04368	0.04334	0.04254	0.04063	0.03606	0.02539
10	4	0.02326	0.03473	0.04038	0.04303	0.04422	0.04474	0.04495	0.04501
		0.04499	0.04494	0.04488	0.04482	0.04476	0.04471	0.04467	0.04465
		0.04462	0.04456	0.04441	0.04403	0.04307	0.04080	0.03559	0.02420
10	5	0.02289	0.03432	0.04009	0.04287	0.04416	0.04473	0.04497	0.04505
		0.04505	0.04501	0.04497	0.04493	0.04489	0.04486	0.04485	0.04484
		0.04482	0.04478	0.04462	0.04419	0.04314	0.04072	0.03535	0.02392
10	6	0.02071	0.03230	0.03869	0.04201	0.04368	0.04450	0.04491	0.04512
		0.04523	0.04530	0.04536	0.04542	0.04549	0.04557	0.04565	0.04575
		0.04582	0.04584	0.04570	0.04520	0.04389	0.04090	0.03461	0.02236
10	7	0.02031	0.03196	0.03851	0.04198	0.04374	0.04461	0.04504	0.04525
		0.04537	0.04544	0.04549	0.04556	0.04563	0.04571	0.04580	0.04589
		0.04597	0.04598	0.04583	0.04527	0.04386	0.04071	0.03421	0.02188
10	8	0.02012	0.03191	0.03863	0.04221	0.04402	0.04490	0.04531	0.04549
		0.04557	0.04562	0.04565	0.04568	0.04571	0.04576	0.04582	0.04589
		0.04594	0.04593	0.04573	0.04511	0.04361	0.04033	0.03370	0.02136
10	9	0.02003	0.03202	0.03893	0.04262	0.04447	0.04534	0.04572	0.04585
		0.04588	0.04586	0.04583	0.04580	0.04578	0.04578	0.04579	0.04581
		0.04581	0.04574	0.04547	0.04478	0.04318	0.03976	0.03300	0.02073
11	1	0.02342	0.03484	0.04043	0.04301	0.04417	0.04471	0.04498	0.04506
		0.04504	0.04498	0.04490	0.04482	0.04474	0.04467	0.04462	0.04457
		0.04452	0.04445	0.04430	0.04392	0.04299	0.04079	0.03569	0.02439
11	2	0.02454	0.03573	0.04099	0.04333	0.04434	0.04477	0.04494	0.04497
		0.04492	0.04483	0.04473	0.04462	0.04451	0.04442	0.04433	0.04426
		0.04418	0.04408	0.04390	0.04352	0.04262	0.04057	0.03583	0.02508
11	3	0.02433	0.03552	0.04086	0.04327	0.04434	0.04479	0.04496	0.04498
		0.04494	0.04487	0.04477	0.04468	0.04459	0.04451	0.04444	0.04437
		0.04430	0.04420	0.04401	0.04360	0.04264	0.04050	0.03565	0.02488

11	4	0.02241	0.03380	0.03969	0.04260	0.04400	0.04466	0.04496	0.04508
		0.04512	0.04511	0.04509	0.04507	0.04506	0.04505	0.04506	0.04507
		0.04507	0.04503	0.04486	0.04440	0.04327	0.04072	0.03517	0.02364
11	5	0.02192	0.03328	0.03932	0.04239	0.04391	0.04464	0.04499	0.04513
		0.04519	0.04521	0.04521	0.04522	0.04523	0.04524	0.04527	0.04531
		0.04533	0.04530	0.04512	0.04461	0.04338	0.04065	0.03489	0.02327
11	6	0.01985	0.03142	0.03807	0.04166	0.04353	0.04448	0.04497	0.04523
		0.04539	0.04549	0.04558	0.04568	0.04578	0.04589	0.04601	0.04613
		0.04624	0.04627	0.04611	0.04553	0.04406	0.04079	0.03413	0.02170
11	7	0.01952	0.03120	0.03804	0.04177	0.04372	0.04470	0.04519	0.04544
		0.04558	0.04566	0.04574	0.04582	0.04591	0.04600	0.04611	0.04622
		0.04631	0.04632	0.04613	0.04549	0.04391	0.04047	0.03362	0.02114
11	8	0.01952	0.03142	0.03843	0.04225	0.04421	0.04517	0.04561	0.04580
		0.04588	0.04590	0.04591	0.04592	0.04595	0.04599	0.04604	0.04609
		0.04613	0.04608	0.04582	0.04511	0.04344	0.03989	0.03293	0.02053
11	9	0.01952	0.03167	0.03886	0.04278	0.04476	0.04570	0.04608	0.04621
		0.04621	0.04617	0.04611	0.04605	0.04600	0.04598	0.04596	0.04595
		0.04591	0.04579	0.04546	0.04467	0.04289	0.03922	0.03218	0.01987
12	1	0.02370	0.03485	0.04032	0.04292	0.04414	0.04470	0.04495	0.04503
		0.04503	0.04498	0.04492	0.04486	0.04480	0.04475	0.04470	0.04467
		0.04462	0.04454	0.04434	0.04388	0.04284	0.04052	0.03545	0.02450
12	2	0.02066	0.03220	0.03857	0.04189	0.04358	0.04443	0.04489	0.04513
		0.04526	0.04534	0.04541	0.04547	0.04554	0.04562	0.04570	0.04579
		0.04586	0.04587	0.04573	0.04521	0.04389	0.04091	0.03464	0.02242
12	3	0.02022	0.03175	0.03825	0.04170	0.04347	0.04439	0.04487	0.04514
		0.04530	0.04540	0.04549	0.04557	0.04567	0.04577	0.04588	0.04599
		0.04609	0.04611	0.04597	0.04543	0.04404	0.04092	0.03446	0.02212
12	4	0.01990	0.03145	0.03806	0.04162	0.04348	0.04444	0.04494	0.04521
		0.04537	0.04548	0.04557	0.04567	0.04577	0.04589	0.04600	0.04612
		0.04622	0.04625	0.04610	0.04553	0.04407	0.04083	0.03422	0.02180
12	5	0.01959	0.03118	0.03793	0.04161	0.04355	0.04455	0.04506	0.04533
		0.04549	0.04560	0.04569	0.04579	0.04589	0.04600	0.04611	0.04624
		0.04633	0.04636	0.04618	0.04556	0.04402	0.04064	0.03387	0.02142
12	6	0.01924	0.03090	0.03781	0.04164	0.04366	0.04469	0.04522	0.04550
		0.04565	0.04575	0.04584	0.04593	0.04602	0.04612	0.04624	0.04636
		0.04645	0.04646	0.04626	0.04558	0.04394	0.04039	0.03343	0.02092
12	7	0.01909	0.03090	0.03800	0.04195	0.04402	0.04507	0.04557	0.04581
		0.04593	0.04598	0.04602	0.04606	0.04611	0.04618	0.04626	0.04633
		0.04639	0.04635	0.04609	0.04534	0.04358	0.03989	0.03278	0.02031
13	1	0.02302	0.03417	0.03988	0.04271	0.04410	0.04475	0.04505	0.04516
		0.04519	0.04518	0.04513	0.04509	0.04506	0.04504	0.04502	0.04500
		0.04497	0.04488	0.04465	0.04410	0.04286	0.04027	0.03487	0.02385
13	2	0.01982	0.03137	0.03801	0.04161	0.04351	0.04449	0.04501	0.04529
		0.04545	0.04556	0.04565	0.04574	0.04584	0.04595	0.04606	0.04617
		0.04626	0.04628	0.04610	0.04549	0.04398	0.04068	0.03402	0.02165
13	3	0.01944	0.03103	0.03782	0.04154	0.04351	0.04454	0.04507	0.04536
		0.04553	0.04565	0.04575	0.04585	0.04596	0.04607	0.04619	0.04631
		0.04641	0.04643	0.04625	0.04561	0.04403	0.04060	0.03376	0.02128
13	4	0.01933	0.03103	0.03794	0.04174	0.04374	0.04477	0.04528	0.04555
		0.04569	0.04579	0.04586	0.04593	0.04601	0.04609	0.04619	0.04629
		0.04637	0.04637	0.04615	0.04547	0.04383	0.04031	0.03337	0.02089
13	5	0.01915	0.03093	0.03797	0.04188	0.04394	0.04499	0.04550	0.04576
		0.04588	0.04595	0.04599	0.04604	0.04609	0.04616	0.04624	0.04633
		0.04638	0.04635	0.04609	0.04536	0.04363	0.03999	0.03293	0.02046
13	6	0.01893	0.03079	0.03798	0.04201	0.04414	0.04521	0.04572	0.04596

		0.04606	0.04610	0.04613	0.04615	0.04620	0.04625	0.04631	0.04637
		0.04641	0.04635	0.04606	0.04527	0.04345	0.03966	0.03247	0.02002
13	7	0.01881	0.03082	0.03817	0.04231	0.04449	0.04556	0.04606	0.04626
		0.04632	0.04632	0.04630	0.04629	0.04628	0.04629	0.04632	0.04634
		0.04633	0.04622	0.04588	0.04501	0.04308	0.03917	0.03188	0.01949
14	1	0.01946	0.03109	0.03793	0.04171	0.04371	0.04475	0.04528	0.04556
		0.04571	0.04580	0.04588	0.04595	0.04602	0.04611	0.04621	0.04630
		0.04637	0.04635	0.04611	0.04540	0.04373	0.04022	0.03335	0.02099
14	2	0.01915	0.03081	0.03776	0.04163	0.04369	0.04477	0.04532	0.04561
		0.04577	0.04587	0.04595	0.04603	0.04611	0.04621	0.04631	0.04642
		0.04650	0.04648	0.04624	0.04551	0.04380	0.04018	0.03317	0.02072
14	3	0.01901	0.03079	0.03788	0.04185	0.04395	0.04503	0.04557	0.04584
		0.04596	0.04603	0.04608	0.04612	0.04618	0.04625	0.04632	0.04640
		0.04645	0.04640	0.04613	0.04535	0.04356	0.03985	0.03273	0.02028
15	1	0.01889	0.03071	0.03789	0.04194	0.04410	0.04521	0.04575	0.04600
		0.04612	0.04617	0.04620	0.04623	0.04627	0.04632	0.04638	0.04645
		0.04647	0.04640	0.04608	0.04524	0.04336	0.03953	0.03234	0.01995
15	2	0.01875	0.03062	0.03787	0.04198	0.04417	0.04529	0.04583	0.04609
		0.04620	0.04625	0.04627	0.04629	0.04633	0.04637	0.04643	0.04647
		0.04649	0.04641	0.04608	0.04522	0.04330	0.03941	0.03215	0.01975
15	3	0.01869	0.03067	0.03805	0.04223	0.04445	0.04556	0.04609	0.04631
		0.04639	0.04640	0.04639	0.04638	0.04637	0.04638	0.04641	0.04642
		0.04641	0.04629	0.04592	0.04501	0.04303	0.03906	0.03174	0.01937

Figure 4-4

H.B. ROBINSON 2 CYCLE 8
NORMALIZED CORE DELTA EXPOSURE DISTRIBUTION



show conservatism with respect to estimating flux reduction at critical welds. In order to model Cycle 9, which is the present operating cycle, and Cycle 10, cross sections not available from XPOSE were obtained from ENC for CP&L's PDQ7 and XTG models. Specifically, ENC supplied cross sections for 208 fuel pins containing four weight percent Gd_2O_3 loaded in the Cycle 9 core and additional Gd_2O_3 pins for the Cycle 10 loading. Cross sections were provided to represent the Gd_2O_3 pins in PDQ7 and the Gd_2O_3 assemblies in XTG.¹⁴ In addition, equivalent parameters were generated by TEC to represent the shield portion of the PLSA in CP&L's diffusion models as described in Sections 4.2.3 and 4.2.4.

Cycle 9 was depleted to nominal EOC in the PDQ7 and XTG models to provide a starting point for Cycle 10. Cycle 9 is at present past mid-cycle, but comparisons between PDQ7 and measured power distributions to this point are presented in Figures 4-5 through 4-7. XTG-measured comparisons are shown in Figure 4-8. Differences between analytic and measured distributions are consistent with the uncertainties quoted before and show that the models, including Gd_2O_3 cross sections, follow HBR2 well.

In order to model Cycle 10 in PDQ7, two cases were depleted; one representative of the axial region in which the PLSA contains active fuel, and the second representative of the axial region in which the PLSA contains shield material (SS304). In each case, the pin power distributions obtained in the PDQ 7 depletion were averaged (exposure-weighted) as was done for Cycle 8. The normalization in each plane was to a pin average of unity with no internormalization between planes. Figures 4-9 and 4-10 show the normalized cycle delta exposures for the two regions and correspond to the averaged pin distributions supplied to DOTSOR.

Figure 4-5

H. B. Robinson Unit 2
 Quarter Core Averaged Assembly Power Distribution

Cycle 9 Map 414 09/01/82 D-206 Steps 00180MWD/MTU 92.8%HF 92.8%HF *CP&L PDQ*

	H	G	F	E	D	C	B	A
1	1.229	1.414	1.114	1.187	1.061	0.893	0.876	0.316
	1.228	1.405	1.092	1.149	1.035	0.886	0.873	0.315
	-0.048	-0.674	-2.013	-3.152	-2.442	-0.785	-0.266	-0.449
2	1.411	1.213	1.280	1.056	1.281	1.010	0.823	0.238
	1.408	1.206	1.265	1.042	1.266	1.011	0.821	0.237
	-0.273	-0.531	-1.151	-1.283	-1.170	0.092	-0.158	-0.434
3	1.110	1.277	1.136	1.206	1.114	1.240	0.844	
	1.089	1.267	1.140	1.207	1.118	1.253	0.858	
	-1.857	-0.742	0.316	0.076	0.346	1.061	1.718	
4	1.189	1.056	1.202	1.031	1.149	1.124	0.680	
	1.150	1.040	1.212	1.040	1.155	1.147	0.704	
	-3.343	-1.505	0.823	0.843	0.565	2.064	3.505	
5	1.075	1.291	1.112	1.146	1.020	0.754	PREDICTED (CP&L PDQ)	
	1.020	1.252	1.122	1.171	1.047	0.780	MEASURED (INCORE)	
	-5.071	-3.025	0.880	2.177	2.609	3.435	% DIFF (P-M)/P*100	
6	0.933	1.026	1.247	1.127	0.754			
	0.891	0.992	1.272	1.164	0.786			
	-4.458	-3.302	1.981	3.343	4.229			
7	0.895	0.836	0.851	0.683				
	0.869	0.816	0.856	0.712				
	-2.879	-2.430	0.502	4.224				
8	0.313	0.241						
	0.307	0.237						
	-1.932	-1.900						

STD. DEV. OF DIFFERENCES = 2.15 %

Figure 4-6

H. B. Robinson Unit 2
Quarter Core Averaged Assembly Power Distribution

Cycle 9 Map 431 01/11/83 D-216 Steps 03363MWD/MTU 93.4XHFP *CP&L PDQ*

	H	G	F	E	D	C	B	A
1	1.036	1.199	1.020	1.235	1.068	0.953	1.029	0.393
	1.042	1.203	1.016	1.218	1.044	0.930	1.021	0.398
	0.577	0.304	-0.399	-1.390	-2.289	-2.428	-0.770	1.229
2	1.197	1.052	1.153	1.015	1.248	1.049	0.961	0.294
	1.191	1.050	1.149	1.011	1.232	1.033	0.956	0.297
	-0.544	-0.274	-0.378	-0.421	-1.271	-1.533	-0.489	1.211
3	1.016	1.151	1.042	1.135	1.084	1.240	0.923	
	1.015	1.148	1.042	1.146	1.094	1.239	0.918	
	-0.125	-0.190	-0.029	0.991	0.877	-0.145	-0.461	
4	1.236	1.014	1.131	1.006	1.149	1.134	0.721	
	1.234	1.010	1.130	1.024	1.172	1.150	0.727	
	-0.166	-0.464	-0.031	1.772	1.955	1.461	0.862	
5	1.077	1.252	1.081	1.146	1.127	0.807	PREDICTED (CP&L PDQ)	
	1.059	1.228	1.069	1.159	1.155	0.829	MEASURED (INCORE)	
	-1.665	-1.944	-1.072	1.133	2.541	2.721	% DIFF (P-M)/P*100	
6	0.986	1.059	1.243	1.134	0.807			
	0.963	1.039	1.235	1.148	0.830			
	-2.363	-1.900	-0.687	1.265	2.792			
7	1.042	0.970	0.927	0.722				
	1.029	0.963	0.928	0.732				
	-1.196	-0.671	0.178	1.412				
8	0.387	0.295						
	0.379	0.296						
	-1.942	0.171						

STD. DEV. OF DIFFERENCES = 1.32 %

Figure 4-7

H. B. Robinson Unit 2
 Quarter Core Averaged Assembly Power Distribution

Cycle 9 Map 444 08/25/83 D-213 Steps 08357MWD/MTU 93.0ZHFP *CP&L PDQ*

	H	G	F	E	D	C	B	A
1	0.905	1.045	0.956	1.314	1.060	1.010	1.241	0.508
	0.937	1.078	0.967	1.303	1.034	0.985	1.231	0.507
	3.447	3.115	1.114	-0.840	-2.481	-2.475	-0.752	-0.082
2	1.044	0.936	1.049	0.974	1.182	1.075	1.173	0.380
	1.073	0.962	1.063	0.975	1.166	1.063	1.164	0.379
	2.773	2.772	1.370	0.197	-1.352	-1.203	-0.823	-0.053
3	0.953	1.047	0.951	1.043	1.022	1.199	1.013	
	0.963	1.064	0.966	1.053	1.027	1.201	1.015	
	1.031	1.607	1.626	0.935	0.496	0.158	0.176	
4	1.313	0.972	1.039	0.957	1.113	1.095	0.739	
	1.295	0.968	1.046	0.965	1.117	1.100	0.744	
	-1.376	-0.400	0.655	0.828	0.383	0.415	0.629	
5	1.065	1.183	1.018	1.110	1.255	0.838	PREDICTED (CP&L PDQ)	
	1.027	1.158	1.016	1.114	1.256	0.839	MEASURED (INCORE)	
	-3.504	-2.122	-0.179	0.355	0.129	0.156	% DIFF (P-M)/P*100	
6	1.036	1.080	1.199	1.094	0.837			
	0.999	1.056	1.193	1.094	0.837			
	-3.621	-2.237	-0.477	-0.063	-0.075			
7	1.246	1.177	1.013	0.739				
	1.234	1.173	1.017	0.740				
	-0.926	-0.322	0.392	0.233				
8	0.497	0.379						
	0.505	0.385						
	1.652	1.431						

STD. DEV. OF DIFFERENCES = 1.33 %

Figure 4-8

H. B. Robinson Unit 2
Core Averaged Axial Relative Power Distributions

			Axial Level (from top)	Measured (INCORE)	Predicted (XTG)	% Difference (P-M)/P*100
Cycle 9	Map 414	180MWD/MTU	1	.615	.574	-7.14
			2	.962	.918	-4.79
			3	1.091	1.046	-4.30
			4	1.122	1.104	-1.63
			5	1.155	1.135	-1.76
			6	1.141	1.152	0.95
			7	1.150	1.156	0.52
			8	1.114	1.147	2.88
			9	1.093	1.123	2.67
			10	1.026	1.071	4.20
			11	.912	.954	4.40
			12	.619	.620	0.16

Std. Dev. of Differences = 3.54 %

Cycle 9	Map 432	3780MWD/MTU	1	.670	.635	-5.51
			2	.968	.955	-1.36
			3	1.051	1.041	-0.96
			4	1.061	1.065	0.38
			5	1.087	1.076	-1.02
			6	1.076	1.084	0.74
			7	1.101	1.093	-0.73
			8	1.087	1.101	1.27
			9	1.100	1.107	0.63
			10	1.072	1.099	2.46
			11	1.002	1.031	2.81
			12	.724	.714	-1.40

Std. Dev. of Differences = 2.10 %

Cycle 9	Map 436	5445MWD/MTU	1	.693	.652	-6.29
			2	.981	.963	-1.87
			3	1.048	1.036	-1.16
			4	1.050	1.052	0.19
			5	1.073	1.059	-1.32
			6	1.059	1.066	0.66
			7	1.087	1.076	-1.02
			8	1.078	1.089	1.01
			9	1.102	1.102	0.00
			10	1.081	1.106	2.26
			11	1.023	1.054	2.94
			12	.727	.746	2.55

Std. Dev. of Differences = 2.39 %

PREPARED BY: <u> K Cantrell </u>	DATE: <u> 7/30/83 </u>	PAGE NO.	
CHECKED BY: <u> K. Karcher </u>	DATE: <u> 8/17/83 </u>	<u> </u> OF <u> </u>	
SUBJECT: HBR2 Cycle 10 Assembly Exposures and Cycle Deltas			
COMPUTER PROGRAM: PDQ7	VERSION:	PRODUCTION DEVELOPMENT <input type="checkbox"/>	TAPE NO. OR FILE NAME:
REACTOR: HBR2	CYCLE: 10 Upper Core	EXPOSURE: Core Avg. Delta = 10429	STATE: HFP ARO

	H	G	F	E	D	C	B	A
8	13597 0 13597 1.304	24982 13146 11836 1.135	33607 23607 10000 .959	13746 0 13746 1.318	34232 23607 10625 1.019	23890 11153 12737 1.221	13334 0 13334 1.279	4566 0 4566 .438
9	24964 13151 11813 1.133	23884 12022 11862 1.137	22158 10481 11677 1.120	32798 22369 10429 1.000	20158 7517 12641 1.212	22307 9786 12521 1.201	12356 0 12356 1.185	3664 0 3664 .351
10	33482 23570 9912 .950	22169 10565 11604 1.113	34110 24103 10007 .960	13626 0 13626 1.307	30808 20301 10507 1.008	29466 19206 10260 .984	9917 0 9917 .951	
11	13550 0 13550 1.299	32773 22395 10378 .995	13659 0 13659 1.310	34313 24159 10154 .974	20227 8445 11782 1.130	11406 0 11406 1.094	7457 0 7457 .715	
12	34134 23570 10564 1.013	20146 7527 12619 1.210	30857 20344 10513 1.008	20223 8444 11779 1.129	11035 0 11035 1.058	24953 19963 4990 .478		
13	23952 11274 12688 1.217	22311 9821 12490 1.198	29451 19197 10254 .983	11402 0 11402 1.093	24963 19975 4988 .478	EOC BOC Delta Relative Delta		
14	13302 0 13302 1.276	12332 0 12332 1.182	9908 0 9908 .950	7453 0 7453 .715				
15	4558 0 4558 .437	3658 0 3658 .351						

Figure 4-9
Assembly Exposures - Cycle 10,
Upper Core



Carolina Power & Light Company

INCORE ANALYSIS UNIT

ENGINEERING CALCULATION
(COMPUTER INPUT)

PREPARED BY: K Cantrell DATE: 7/28/83 PAGE NO. _____

CHECKED BY: K. Karcher DATE: 8/17/83 OF _____

SUBJECT: HBR2 Cycle 10 Assembly Exposures and Cycle Deltas

COMPUTER PROGRAM: PDQ7	VERSION: 2	PRODUCTION DEVELOPMENT <input type="checkbox"/>	TAPE NO. OR FILE NAME: RPDQ101
REACTOR: HBR2	CYCLE: 10 Lower Core	EXPOSURE: Core Avg. Delta 10392	STATE: HFP ARO

	H	G	F	E	D	C	B	A
8	15171 0 15171 1.460	26257 13146 13111 1.262	34640 23607 11033 1.062	14952 0 14952 1.439	34645 23607 11038 1.062	23136 11153 11983 1.153	9795 0 9795 0.943	0 0 0 0.0
9	26237 13151 13086 1.259	25139 12022 13119 1.262	23347 10481 12866 1.238	33722 22369 11353 1.092	20748 7517 13231 1.273	21848 .9786 12062 1.161	9711 0 9711 0.934	0 0 0 0.0
10	34508 25570 8938 0.860	23353 10565 12788 1.231	35154 24103 11051 1.063	14963 0 14963 1.440	31533 20301 11232 1.081	29626 19206 10420 1.003	9263 0 9263 0.891	
11	14740 0 14740 1.418	33693 22395 11298 1.087	14999 0 14999 1.443	35303 24159 11144 1.072	21239 8445 12794 1.231	12139 0 12139 1.168	7641 0 7641 0.735	
12	34542 23570 10972 1.056	20735 7529 13208 1.271	31582 20344 11238 1.081	21235 18444 12791 1.231	12121 0 12121 1.166	25399 19963 5436 0.523		
13	23198 11274 11924 1.147	21851 9821 12030 1.158	29611 19197 10414 1.002	12136 0 12136 1.163	25410 19975 5435 0.523	EOC MWD/MTU BOC MWD/MTU Delta Relative Delta		
14	9765 0 9765 0.940	9690 0 9690 0.932	9254 0 9254 0.890	7638 0 7638 0.735				
15	0 0 0 0.0	0 0 0 0.0						

Figure 4-10
Assembly Exposures - Cycle 10,
Lower Core

Axial distributions were obtained from XTG simulation of Cycle 10 by the same procedure as described for Cycle 8 and shown in Table 4-5 as provided to TEC through UCC.

4.3.3 Corrections to Source Distributions

Nominal full power at HBR2 is 2300 MWt; the loaded core contains 157 assemblies with 204 pins per assembly. These factors are appropriate for converting the relative power distributions to absolute pin powers. DOTSOR uses an exposure-dependent κ/ν to convert power distribution to neutron distribution; however, only one core-average exposure may be specified for each distribution. Figures 4-11 and 4-12 show the ratio of assembly-average κ/ν to core-average κ/ν at the average core exposures for Cycles 8 and 10, respectively. The exposure-dependent κ/ν is taken from XPOSE, as shown in Figure 4-13, and the average exposures are taken from the PDQ7 models. In generating the 3-D neutron source distributions, these factors make an additional correction, accounting for variances in κ/ν with exposures.

4.3.4 Study of HBR2 Power History and Westinghouse Capsule Analyses

During the burnup of a pressurized water reactor (PWR) reload core employing out-in-in strategy, there is a continuous power/flux flattening due to higher exposure of the inner core and "hot spots." A linear fit of relative power in Assembly A-8 (center assembly on a flat) for Cycle 8 gives the following multiplier as a function of core-average cycle exposure to the cycle average power of the assembly:

$$m = 0.9455 + .10896 \times 10^{-4} *(\text{CAVCEX in MWD/MTU}) \quad (4.1)$$

Table 4-5

XTG HBR2 Cycle 10 Averaged Axial Power Distributions

ASSEMBLY-WISE AXIAL SOURCE DISTRIBUTIONS -- CYCLE 10
 EAST-SOUTHEAST OCTANT
 FORMAT(2I3,2X,8F9.5,2(/,8X,8F9.5))

COORDINATES		24 AXIAL NODE RELATIVE SOURCE DISTRIBUTION, TOP TO BOTTOM							
1	1	0.01734	0.02857	0.03553	0.03958	0.04193	0.04337	0.04432	0.04497
		0.04547	0.04586	0.04619	0.04648	0.04675	0.04700	0.04724	0.04742
		0.04755	0.04757	0.04737	0.04672	0.04516	0.04171	0.03460	0.02131
2	1	0.02051	0.03119	0.03703	0.04033	0.04226	0.04346	0.04423	0.04476
		0.04514	0.04542	0.04565	0.04584	0.04601	0.04615	0.04626	0.04634
		0.04636	0.04628	0.04603	0.04543	0.04412	0.04139	0.03573	0.02408
2	2	0.02046	0.03167	0.03751	0.04068	0.04248	0.04356	0.04426	0.04473
		0.04507	0.04533	0.04553	0.04570	0.04585	0.04597	0.04606	0.04612
		0.04613	0.04606	0.04583	0.04529	0.04411	0.04155	0.03601	0.02404
3	1	0.02139	0.03185	0.03757	0.04071	0.04257	0.04369	0.04441	0.04490
		0.04524	0.04549	0.04569	0.04584	0.04596	0.04605	0.04611	0.04612
		0.04607	0.04592	0.04559	0.04493	0.04361	0.04091	0.03535	0.02401
3	2	0.01993	0.03129	0.03737	0.04069	0.04257	0.04371	0.04444	0.04494
		0.04529	0.04556	0.04577	0.04595	0.04611	0.04622	0.04631	0.04635
		0.04634	0.04623	0.04595	0.04533	0.04403	0.04124	0.03534	0.02305
3	3	0.02026	0.03098	0.03713	0.04056	0.04255	0.04376	0.04454	0.04507
		0.04545	0.04574	0.04597	0.04615	0.04631	0.04642	0.04650	0.04654
		0.04650	0.04635	0.04600	0.04528	0.04381	0.04081	0.03465	0.02270
4	1	0.01092	0.02795	0.03537	0.03981	0.04245	0.04408	0.04518	0.04596
		0.04655	0.04703	0.04743	0.04778	0.04810	0.04839	0.04862	0.04877
		0.04882	0.04869	0.04830	0.04739	0.04544	0.04138	0.03335	0.01223
4	2	0.01985	0.03040	0.03661	0.04018	0.04233	0.04367	0.04456	0.04517
		0.04562	0.04596	0.04623	0.04646	0.04664	0.04678	0.04688	0.04691
		0.04684	0.04662	0.04618	0.04534	0.04371	0.04053	0.03422	0.02231
4	3	0.01044	0.02715	0.03476	0.03942	0.04222	0.04398	0.04515	0.04599
		0.04663	0.04715	0.04758	0.04797	0.04833	0.04865	0.04892	0.04912
		0.04920	0.04912	0.04873	0.04777	0.04567	0.04132	0.03290	0.01182
4	4	0.01868	0.02940	0.03598	0.03986	0.04221	0.04369	0.04466	0.04533
		0.04582	0.04620	0.04652	0.04678	0.04700	0.04717	0.04730	0.04737
		0.04733	0.04714	0.04669	0.04577	0.04395	0.04040	0.03354	0.02120
5	1	0.02028	0.03068	0.03674	0.04032	0.04250	0.04389	0.04481	0.04545
		0.04591	0.04626	0.04654	0.04678	0.04695	0.04707	0.04711	0.04703
		0.04678	0.04631	0.04558	0.04450	0.04275	0.03962	0.03369	0.02245
5	2	0.01894	0.02981	0.03623	0.04000	0.04227	0.04371	0.04467	0.04534
		0.04585	0.04624	0.04656	0.04684	0.04707	0.04726	0.04736	0.04735
		0.04719	0.04683	0.04621	0.04520	0.04345	0.04015	0.03376	0.02171
5	3	0.01932	0.02987	0.03619	0.03996	0.04228	0.04375	0.04472	0.04539
		0.04589	0.04627	0.04657	0.04683	0.04704	0.04719	0.04728	0.04728
		0.04715	0.04683	0.04624	0.04522	0.04339	0.03999	0.03357	0.02180
5	4	0.01685	0.02786	0.03494	0.03923	0.04187	0.04356	0.04469	0.04548

		0.04607	0.04654	0.04693	0.04728	0.04758	0.04784	0.04804	0.04815
		0.04815	0.04796	0.04746	0.04641	0.04433	0.04031	0.03274	0.01974
5	5	0.00899	0.02566	0.03372	0.03890	0.04214	0.04419	0.04556	0.04653
		0.04725	0.04783	0.04831	0.04874	0.04913	0.04948	0.04976	0.04995
		0.05001	0.04984	0.04927	0.04797	0.04532	0.04019	0.03101	0.01024
6	1	0.01787	0.02912	0.03608	0.04032	0.04294	0.04462	0.04574	0.04652
		0.04709	0.04754	0.04791	0.04822	0.04848	0.04864	0.04865	0.04842
		0.04782	0.04671	0.04511	0.04335	0.04108	0.03745	0.03096	0.01937
6	2	0.01783	0.02904	0.03596	0.04016	0.04275	0.04441	0.04552	0.04630
		0.04687	0.04732	0.04769	0.04801	0.04826	0.04844	0.04847	0.04830
		0.04780	0.04686	0.04547	0.04384	0.04164	0.03799	0.03142	0.01964
6	3	0.01834	0.02918	0.03590	0.03999	0.04252	0.04414	0.04521	0.04596
		0.04651	0.04693	0.04728	0.04757	0.04780	0.04795	0.04801	0.04792
		0.04761	0.04698	0.04600	0.04462	0.04248	0.03876	0.03206	0.02026
6	4	0.00861	0.02528	0.03355	0.03887	0.04220	0.04433	0.04576	0.04676
		0.04751	0.04812	0.04863	0.04909	0.04951	0.04986	0.05013	0.05027
		0.05024	0.04992	0.04918	0.04771	0.04491	0.03964	0.03026	0.00967
6	5	0.01610	0.02766	0.03530	0.03996	0.04282	0.04461	0.04575	0.04651
		0.04704	0.04742	0.04771	0.04794	0.04813	0.04826	0.04833	0.04831
		0.04814	0.04776	0.04701	0.04563	0.04314	0.03859	0.03046	0.01742
7	1	0.00809	0.02532	0.03460	0.04071	0.04460	0.04711	0.04878	0.04997
		0.05086	0.05158	0.05219	0.05273	0.05318	0.05348	0.05353	0.05309
		0.05168	0.04852	0.04314	0.03946	0.03601	0.03112	0.02322	0.00702
7	2	0.00839	0.02550	0.03450	0.04043	0.04421	0.04664	0.04826	0.04940
		0.05025	0.05093	0.05151	0.05202	0.05244	0.05274	0.05281	0.05245
		0.05129	0.04866	0.04417	0.04089	0.03755	0.03262	0.02460	0.00773
7	3	0.01430	0.02590	0.03412	0.03941	0.04274	0.04486	0.04625	0.04722
		0.04794	0.04850	0.04898	0.04939	0.04974	0.05001	0.05013	0.05002
		0.04950	0.04837	0.04654	0.04443	0.04146	0.03653	0.02818	0.01549
7	4	0.00698	0.02506	0.03392	0.03955	0.04304	0.04524	0.04667	0.04764
		0.04835	0.04891	0.04937	0.04977	0.05012	0.05040	0.05058	0.05060
		0.05038	0.04980	0.04872	0.04692	0.04380	0.03822	0.02849	0.00749
8	1	0.00832	0.03095	0.04313	0.05103	0.05596	0.05899	0.06087	0.06205
		0.06284	0.06339	0.06380	0.06411	0.06429	0.06428	0.06384	0.06246
		0.05880	0.04919	0.00338	0.00250	0.00217	0.00182	0.00130	0.00054
8	2	0.00842	0.03112	0.04318	0.05099	0.05586	0.05885	0.06069	0.06185
		0.06261	0.06315	0.06353	0.06382	0.06399	0.06397	0.06357	0.06230
		0.05893	0.05000	0.00365	0.00280	0.00246	0.00209	0.00151	0.00064

4-NODE-PER-ASSEMBLY AXIAL SOURCE DISTRIBUTIONS -- CYCLE 10

EAST-SOUTHEAST OCTANT

FORMAT(2I3,2X,8F9.5,2(/,14X,8F9.5))

COORDINATES 24 AXIAL NODE RELATIVE SOURCE DISTRIBUTION, TOP TO BOTTOM

1	1	0.01734	0.02857	0.03553	0.03958	0.04193	0.04337	0.04432	0.04497
		0.04547	0.04586	0.04619	0.04648	0.04675	0.04700	0.04724	0.04742
		0.04755	0.04757	0.04737	0.04672	0.04516	0.04171	0.03460	0.02131
2	1	0.02027	0.03095	0.03686	0.04022	0.04219	0.04341	0.04420	0.04474
		0.04513	0.04543	0.04566	0.04587	0.04605	0.04621	0.04634	0.04643
		0.04647	0.04641	0.04617	0.04557	0.04425	0.04147	0.03572	0.02398
2	2	0.02023	0.03153	0.03740	0.04058	0.04240	0.04349	0.04421	0.04469
		0.04504	0.04531	0.04552	0.04571	0.04587	0.04600	0.04611	0.04618
		0.04620	0.04614	0.04593	0.04541	0.04425	0.04169	0.03613	0.02400
2	3	0.02067	0.03184	0.03762	0.04075	0.04252	0.04358	0.04427	0.04473
		0.04506	0.04531	0.04550	0.04566	0.04580	0.04592	0.04600	0.04605

		0.04605	0.04596	0.04573	0.04519	0.04403	0.04151	0.03605	0.02419
3	1	0.02076	0.03143	0.03720	0.04044	0.04234	0.04350	0.04426	0.04478
		0.04514	0.04542	0.04563	0.04581	0.04596	0.04609	0.04619	0.04625
		0.04625	0.04616	0.04589	0.04528	0.04399	0.04130	0.03574	0.02418
3	2	0.02067	0.03184	0.03762	0.04075	0.04252	0.04358	0.04427	0.04473
		0.04506	0.04531	0.04550	0.04566	0.04580	0.04592	0.04600	0.04605
		0.04605	0.04596	0.04573	0.04519	0.04403	0.04151	0.03605	0.02419
3	3	0.02070	0.03181	0.03762	0.04078	0.04256	0.04363	0.04431	0.04478
		0.04510	0.04535	0.04554	0.04570	0.04584	0.04594	0.04602	0.04606
		0.04605	0.04596	0.04572	0.04516	0.04397	0.04141	0.03589	0.02409
4	1	0.02182	0.03228	0.03781	0.04085	0.04260	0.04366	0.04434	0.04480
		0.04512	0.04536	0.04553	0.04567	0.04577	0.04585	0.04590	0.04591
		0.04586	0.04572	0.04541	0.04479	0.04356	0.04102	0.03576	0.02461
4	2	0.02011	0.03148	0.03750	0.04073	0.04255	0.04365	0.04435	0.04482
		0.04517	0.04543	0.04564	0.04582	0.04597	0.04609	0.04618	0.04623
		0.04623	0.04614	0.04589	0.04533	0.04411	0.04146	0.03571	0.02343
4	3	0.02005	0.03143	0.03747	0.04073	0.04257	0.04367	0.04438	0.04486
		0.04521	0.04547	0.04568	0.04585	0.04600	0.04613	0.04621	0.04626
		0.04626	0.04616	0.04591	0.04534	0.04409	0.04139	0.03559	0.02330
4	4	0.02125	0.03208	0.03784	0.04095	0.04272	0.04378	0.04445	0.04491
		0.04523	0.04546	0.04564	0.04578	0.04589	0.04596	0.04601	0.04601
		0.04596	0.04581	0.04550	0.04487	0.04361	0.04099	0.03545	0.02385
4	5	0.02030	0.03101	0.03715	0.04058	0.04257	0.04378	0.04456	0.04509
		0.04547	0.04576	0.04598	0.04617	0.04631	0.04642	0.04650	0.04653
		0.04648	0.04633	0.04597	0.04524	0.04377	0.04076	0.03460	0.02268
5	1	0.02095	0.03142	0.03734	0.04063	0.04255	0.04372	0.04448	0.04499
		0.04536	0.04563	0.04584	0.04601	0.04614	0.04624	0.04631	0.04633
		0.04628	0.04612	0.04577	0.04507	0.04366	0.04081	0.03494	0.02341
5	2	0.01988	0.03121	0.03731	0.04068	0.04260	0.04376	0.04451	0.04501
		0.04537	0.04565	0.04586	0.04604	0.04619	0.04631	0.04638	0.04642
		0.04639	0.04626	0.04595	0.04529	0.04394	0.04108	0.03510	0.02283
5	3	0.01970	0.03103	0.03720	0.04062	0.04258	0.04377	0.04453	0.04505
		0.04541	0.04569	0.04592	0.04610	0.04626	0.04638	0.04646	0.04650
		0.04648	0.04635	0.04603	0.04536	0.04397	0.04104	0.03496	0.02263
5	4	0.02030	0.03101	0.03715	0.04058	0.04257	0.04378	0.04456	0.04509
		0.04547	0.04576	0.04598	0.04617	0.04631	0.04642	0.04650	0.04653
		0.04648	0.04633	0.04597	0.04524	0.04377	0.04076	0.03460	0.02268
5	5	0.01929	0.02991	0.03643	0.04017	0.04238	0.04374	0.04462	0.04523
		0.04567	0.04601	0.04629	0.04652	0.04671	0.04687	0.04698	0.04705
		0.04703	0.04688	0.04649	0.04568	0.04401	0.04063	0.03385	0.02156
6	1	0.01098	0.02808	0.03548	0.03989	0.04248	0.04409	0.04516	0.04592
		0.04650	0.04696	0.04735	0.04769	0.04800	0.04828	0.04852	0.04868
		0.04874	0.04865	0.04829	0.04742	0.04552	0.04151	0.03351	0.01231
6	2	0.02003	0.03063	0.03679	0.04030	0.04239	0.04369	0.04454	0.04513
		0.04555	0.04587	0.04613	0.04634	0.04652	0.04665	0.04674	0.04677
		0.04671	0.04652	0.04611	0.04532	0.04375	0.04064	0.03440	0.02249
6	3	0.01990	0.03048	0.03668	0.04023	0.04236	0.04367	0.04454	0.04514
		0.04558	0.04590	0.04617	0.04639	0.04656	0.04670	0.04680	0.04683
		0.04678	0.04660	0.04619	0.04538	0.04378	0.04063	0.03432	0.02238
6	4	0.01062	0.02748	0.03502	0.03959	0.04232	0.04401	0.04515	0.04595
		0.04657	0.04706	0.04748	0.04785	0.04818	0.04849	0.04875	0.04894
		0.04903	0.04896	0.04860	0.04769	0.04567	0.04144	0.03314	0.01200
6	5	0.01024	0.02694	0.03465	0.03937	0.04220	0.04397	0.04515	0.04600
		0.04665	0.04717	0.04761	0.04800	0.04836	0.04870	0.04898	0.04919
		0.04929	0.04923	0.04886	0.04791	0.04578	0.04137	0.03278	0.01160

6	6	0.01864	0.02922	0.03591	0.03984	0.04221	0.04369	0.04466	0.04533
		0.04582	0.04621	0.04652	0.04679	0.04701	0.04720	0.04734	0.04741
		0.04739	0.04722	0.04679	0.04588	0.04406	0.04045	0.03340	0.02100
6	7	0.01887	0.02952	0.03604	0.03989	0.04222	0.04368	0.04465	0.04531
		0.04580	0.04618	0.04649	0.04675	0.04696	0.04713	0.04726	0.04732
		0.04727	0.04708	0.04662	0.04570	0.04389	0.04038	0.03361	0.02140
7	1	0.01085	0.02782	0.03526	0.03974	0.04241	0.04408	0.04520	0.04600
		0.04661	0.04710	0.04751	0.04788	0.04821	0.04850	0.04873	0.04887
		0.04890	0.04874	0.04830	0.04735	0.04535	0.04125	0.03320	0.01215
7	2	0.01983	0.03034	0.03655	0.04014	0.04231	0.04367	0.04458	0.04520
		0.04566	0.04601	0.04629	0.04653	0.04672	0.04687	0.04696	0.04697
		0.04688	0.04664	0.04615	0.04527	0.04362	0.04042	0.03412	0.02226
7	3	0.01965	0.03016	0.03641	0.04005	0.04226	0.04365	0.04457	0.04521
		0.04568	0.04604	0.04633	0.04657	0.04677	0.04692	0.04702	0.04705
		0.04697	0.04674	0.04627	0.04538	0.04369	0.04043	0.03404	0.02213
7	4	0.01057	0.02729	0.03483	0.03945	0.04223	0.04398	0.04516	0.04600
		0.04664	0.04715	0.04759	0.04797	0.04832	0.04864	0.04891	0.04908
		0.04915	0.04904	0.04862	0.04765	0.04555	0.04126	0.03296	0.01195
7	5	0.01032	0.02690	0.03454	0.03927	0.04214	0.04394	0.04515	0.04602
		0.04668	0.04722	0.04767	0.04807	0.04844	0.04877	0.04905	0.04925
		0.04934	0.04924	0.04883	0.04783	0.04566	0.04123	0.03272	0.01173
7	6	0.01887	0.02952	0.03604	0.03989	0.04222	0.04368	0.04465	0.04531
		0.04580	0.04618	0.04649	0.04675	0.04696	0.04713	0.04726	0.04732
		0.04727	0.04708	0.04662	0.04570	0.04389	0.04038	0.03361	0.02140
7	7	0.01872	0.02959	0.03605	0.03988	0.04221	0.04369	0.04466	0.04533
		0.04582	0.04620	0.04651	0.04677	0.04698	0.04715	0.04727	0.04733
		0.04727	0.04707	0.04660	0.04565	0.04383	0.04034	0.03368	0.02140
8	1	0.02018	0.03054	0.03667	0.04025	0.04242	0.04379	0.04470	0.04533
		0.04579	0.04614	0.04642	0.04665	0.04684	0.04696	0.04702	0.04698
		0.04681	0.04644	0.04583	0.04484	0.04314	0.03997	0.03387	0.02241
8	2	0.01852	0.02950	0.03602	0.03985	0.04214	0.04359	0.04456	0.04525
		0.04576	0.04617	0.04651	0.04680	0.04705	0.04726	0.04740	0.04744
		0.04734	0.04707	0.04653	0.04560	0.04386	0.04048	0.03386	0.02144
8	3	0.01874	0.02968	0.03614	0.03992	0.04218	0.04361	0.04457	0.04524
		0.04574	0.04613	0.04645	0.04673	0.04697	0.04717	0.04729	0.04733
		0.04723	0.04697	0.04646	0.04554	0.04382	0.04049	0.03396	0.02164
8	4	0.01973	0.03014	0.03638	0.04005	0.04229	0.04371	0.04464	0.04529
		0.04577	0.04613	0.04642	0.04666	0.04686	0.04701	0.04710	0.04710
		0.04698	0.04670	0.04616	0.04521	0.04346	0.04018	0.03385	0.02217
8	5	0.01895	0.02945	0.03591	0.03977	0.04213	0.04364	0.04463	0.04533
		0.04584	0.04623	0.04655	0.04683	0.04706	0.04723	0.04736	0.04740
		0.04733	0.04709	0.04657	0.04560	0.04375	0.04024	0.03356	0.02155
8	6	0.01704	0.02815	0.03507	0.03927	0.04183	0.04347	0.04456	0.04534
		0.04592	0.04638	0.04677	0.04711	0.04741	0.04768	0.04789	0.04801
		0.04803	0.04787	0.04741	0.04643	0.04446	0.04057	0.03320	0.02014
8	7	0.01689	0.02785	0.03491	0.03919	0.04183	0.04351	0.04463	0.04542
		0.04601	0.04648	0.04687	0.04722	0.04753	0.04780	0.04800	0.04813
		0.04814	0.04798	0.04751	0.04649	0.04444	0.04043	0.03286	0.01988
8	8	0.00929	0.02586	0.03374	0.03877	0.04191	0.04392	0.04527	0.04623
		0.04697	0.04756	0.04807	0.04852	0.04894	0.04932	0.04963	0.04985
		0.04995	0.04983	0.04934	0.04814	0.04565	0.04073	0.03176	0.01075
8	9	0.00885	0.02548	0.03361	0.03884	0.04211	0.04420	0.04559	0.04656
		0.04729	0.04787	0.04837	0.04881	0.04921	0.04956	0.04984	0.05004
		0.05009	0.04992	0.04934	0.04802	0.04534	0.04014	0.03084	0.01007
9	1	0.02039	0.03081	0.03681	0.04038	0.04258	0.04398	0.04492	0.04556

		0.04603	0.04638	0.04667	0.04690	0.04707	0.04718	0.04719	0.04707
		0.04675	0.04618	0.04533	0.04416	0.04236	0.03927	0.03352	0.02249
9	2	0.01912	0.02991	0.03630	0.04007	0.04235	0.04380	0.04477	0.04545
		0.04596	0.04636	0.04669	0.04696	0.04720	0.04737	0.04745	0.04740
		0.04717	0.04670	0.04595	0.04485	0.04306	0.03979	0.03355	0.02177
9	3	0.01938	0.03013	0.03644	0.04016	0.04241	0.04383	0.04478	0.04544
		0.04592	0.04630	0.04660	0.04686	0.04707	0.04723	0.04729	0.04724
		0.04703	0.04660	0.04589	0.04483	0.04307	0.03981	0.03368	0.02200
9	4	0.01984	0.03037	0.03652	0.04019	0.04243	0.04386	0.04480	0.04546
		0.04593	0.04629	0.04657	0.04681	0.04699	0.04712	0.04717	0.04712
		0.04692	0.04651	0.04583	0.04476	0.04295	0.03970	0.03363	0.02221
9	5	0.01876	0.02950	0.03595	0.03984	0.04225	0.04378	0.04480	0.04550
		0.04602	0.04641	0.04673	0.04700	0.04723	0.04739	0.04749	0.04749
		0.04735	0.04702	0.04640	0.04532	0.04339	0.03984	0.03326	0.02128
9	6	0.01704	0.02800	0.03502	0.03927	0.04190	0.04358	0.04470	0.04549
		0.04608	0.04655	0.04694	0.04728	0.04759	0.04784	0.04803	0.04812
		0.04809	0.04786	0.04733	0.04625	0.04418	0.04021	0.03275	0.01989
9	7	0.01643	0.02745	0.03474	0.03919	0.04194	0.04369	0.04486	0.04567
		0.04627	0.04674	0.04714	0.04749	0.04779	0.04805	0.04824	0.04835
		0.04833	0.04811	0.04757	0.04645	0.04425	0.04003	0.03216	0.01907
9	8	0.00885	0.02548	0.03361	0.03884	0.04211	0.04420	0.04559	0.04656
		0.04729	0.04787	0.04837	0.04881	0.04921	0.04956	0.04984	0.05004
		0.05009	0.04992	0.04934	0.04802	0.04534	0.04014	0.03084	0.01007
9	9	0.00858	0.02539	0.03371	0.03908	0.04245	0.04457	0.04596	0.04693
		0.04764	0.04819	0.04865	0.04905	0.04939	0.04969	0.04993	0.05008
		0.05008	0.04984	0.04918	0.04774	0.04488	0.03946	0.03000	0.00956
10	1	0.01857	0.02970	0.03633	0.04031	0.04275	0.04431	0.04534	0.04607
		0.04660	0.04702	0.04736	0.04764	0.04788	0.04803	0.04805	0.04787
		0.04741	0.04657	0.04535	0.04388	0.04183	0.03842	0.03217	0.02055
10	2	0.01817	0.02935	0.03608	0.04010	0.04257	0.04414	0.04520	0.04595
		0.04651	0.04694	0.04731	0.04761	0.04787	0.04805	0.04810	0.04797
		0.04757	0.04681	0.04569	0.04427	0.04224	0.03876	0.03233	0.02041
10	3	0.01841	0.02953	0.03616	0.04013	0.04255	0.04410	0.04514	0.04586
		0.04640	0.04682	0.04716	0.04745	0.04769	0.04785	0.04790	0.04779
		0.04744	0.04677	0.04575	0.04441	0.04242	0.03896	0.03259	0.02070
10	4	0.01971	0.03031	0.03657	0.04032	0.04263	0.04410	0.04508	0.04576
		0.04625	0.04662	0.04691	0.04715	0.04733	0.04744	0.04746	0.04734
		0.04701	0.04641	0.04550	0.04424	0.04229	0.03897	0.03291	0.02168
10	5	0.01848	0.02918	0.03583	0.03985	0.04234	0.04392	0.04498	0.04572
		0.04626	0.04667	0.04701	0.04730	0.04753	0.04770	0.04778	0.04775
		0.04754	0.04709	0.04632	0.04510	0.04305	0.03936	0.03257	0.02065
10	6	0.00926	0.02591	0.03384	0.03891	0.04208	0.04412	0.04549	0.04647
		0.04721	0.04780	0.04831	0.04877	0.04919	0.04954	0.04982	0.04998
		0.04996	0.04969	0.04902	0.04768	0.04508	0.04013	0.03122	0.01050
10	7	0.00869	0.02533	0.03354	0.03883	0.04214	0.04426	0.04568	0.04667
		0.04741	0.04800	0.04851	0.04897	0.04938	0.04973	0.05001	0.05018
		0.05019	0.04995	0.04929	0.04789	0.04514	0.03988	0.03051	0.00984
10	8	0.01629	0.02747	0.03502	0.03962	0.04247	0.04427	0.04544	0.04624
		0.04680	0.04721	0.04755	0.04782	0.04805	0.04824	0.04835	0.04838
		0.04827	0.04793	0.04724	0.04594	0.04351	0.03902	0.03090	0.01794
10	9	0.01625	0.02782	0.03541	0.04004	0.04288	0.04465	0.04578	0.04653
		0.04704	0.04740	0.04768	0.04790	0.04807	0.04819	0.04825	0.04823
		0.04806	0.04768	0.04694	0.04557	0.04308	0.03855	0.03048	0.01751
11	1	0.01717	0.02854	0.03583	0.04033	0.04314	0.04493	0.04613	0.04697
		0.04759	0.04807	0.04847	0.04881	0.04908	0.04926	0.04925	0.04897

		0.04824	0.04686	0.04486	0.04281	0.04033	0.03647	0.02973	0.01817
11	2	0.01718	0.02854	0.03578	0.04024	0.04302	0.04480	0.04599	0.04682
		0.04744	0.04792	0.04831	0.04865	0.04893	0.04911	0.04912	0.04887
		0.04820	0.04693	0.04507	0.04312	0.04068	0.03683	0.03007	0.01839
11	3	0.01754	0.02870	0.03580	0.04017	0.04289	0.04463	0.04579	0.04660
		0.04719	0.04765	0.04803	0.04835	0.04861	0.04877	0.04880	0.04859
		0.04802	0.04693	0.04533	0.04354	0.04117	0.03734	0.03060	0.01898
11	4	0.01824	0.02923	0.03600	0.04015	0.04274	0.04440	0.04549	0.04626
		0.04681	0.04725	0.04760	0.04789	0.04812	0.04827	0.04829	0.04813
		0.04768	0.04683	0.04557	0.04399	0.04174	0.03802	0.03145	0.01985
11	5	0.01697	0.02806	0.03523	0.03963	0.04238	0.04413	0.04530	0.04611
		0.04672	0.04719	0.04759	0.04792	0.04820	0.04840	0.04850	0.04846
		0.04818	0.04758	0.04660	0.04515	0.04281	0.03870	0.03132	0.01889
11	6	0.00843	0.02508	0.03344	0.03883	0.04221	0.04438	0.04584	0.04686
		0.04763	0.04825	0.04879	0.04927	0.04970	0.05006	0.05032	0.05045
		0.05037	0.04998	0.04914	0.04758	0.04471	0.03937	0.02991	0.00939
11	7	0.00789	0.02468	0.03332	0.03890	0.04240	0.04463	0.04610	0.04711
		0.04787	0.04847	0.04899	0.04944	0.04983	0.05016	0.05041	0.05054
		0.05048	0.05012	0.04930	0.04771	0.04468	0.03905	0.02919	0.00873
11	8	0.01565	0.02748	0.03527	0.04001	0.04292	0.04473	0.04589	0.04665
		0.04718	0.04756	0.04786	0.04810	0.04828	0.04842	0.04848	0.04844
		0.04824	0.04782	0.04702	0.04560	0.04304	0.03840	0.03012	0.01685
11	9	0.01619	0.02818	0.03586	0.04053	0.04336	0.04511	0.04620	0.04689
		0.04735	0.04765	0.04787	0.04803	0.04813	0.04818	0.04818	0.04807
		0.04782	0.04735	0.04651	0.04506	0.04251	0.03795	0.03000	0.01704
12	1	0.00850	0.02545	0.03430	0.04008	0.04375	0.04612	0.04773	0.04887
		0.04975	0.05046	0.05107	0.05161	0.05207	0.05240	0.05250	0.05218
		0.05110	0.04879	0.04513	0.04204	0.03872	0.03375	0.02555	0.00807
12	2	0.00862	0.02553	0.03427	0.03998	0.04361	0.04595	0.04753	0.04866
		0.04953	0.05022	0.05081	0.05134	0.05179	0.05212	0.05223	0.05195
		0.05096	0.04885	0.04547	0.04254	0.03928	0.03432	0.02609	0.00834
12	3	0.00896	0.02577	0.03424	0.03980	0.04332	0.04560	0.04713	0.04823
		0.04905	0.04971	0.05027	0.05077	0.05120	0.05152	0.05165	0.05144
		0.05064	0.04892	0.04615	0.04354	0.04040	0.03545	0.02721	0.00903
12	4	0.01487	0.02620	0.03417	0.03929	0.04252	0.04460	0.04599	0.04696
		0.04769	0.04828	0.04878	0.04921	0.04959	0.04988	0.05002	0.04991
		0.04939	0.04827	0.04648	0.04442	0.04155	0.03683	0.02876	0.01631
12	5	0.01428	0.02584	0.03389	0.03903	0.04227	0.04433	0.04570	0.04666
		0.04738	0.04795	0.04844	0.04887	0.04925	0.04954	0.04972	0.04972
		0.04940	0.04866	0.04741	0.04562	0.04278	0.03785	0.02932	0.01607
12	6	0.00747	0.02519	0.03375	0.03919	0.04260	0.04477	0.04621	0.04721
		0.04796	0.04857	0.04909	0.04955	0.04996	0.05029	0.05052	0.05060
		0.05044	0.04991	0.04891	0.04721	0.04423	0.03883	0.02934	0.00818
12	7	0.00671	0.02484	0.03381	0.03947	0.04297	0.04517	0.04661	0.04758
		0.04830	0.04886	0.04931	0.04971	0.05006	0.05034	0.05054	0.05060
		0.05045	0.04997	0.04901	0.04729	0.04418	0.03850	0.02851	0.00723
13	1	0.00758	0.02517	0.03497	0.04148	0.04564	0.04830	0.05006	0.05129
		0.05220	0.05293	0.05355	0.05409	0.05452	0.05479	0.05477	0.05418
		0.05238	0.04819	0.04074	0.03633	0.03274	0.02793	0.02041	0.00575
13	2	0.00771	0.02523	0.03489	0.04131	0.04540	0.04803	0.04976	0.05096
		0.05185	0.05256	0.05317	0.05368	0.05410	0.05437	0.05437	0.05382
		0.05217	0.04830	0.04138	0.03721	0.03366	0.02882	0.02117	0.00609
13	3	0.00811	0.02542	0.03470	0.04089	0.04483	0.04735	0.04900	0.05015
		0.05099	0.05166	0.05222	0.05270	0.05309	0.05334	0.05337	0.05293
		0.05159	0.04846	0.04296	0.03933	0.03588	0.03093	0.02306	0.00705

13	4	0.01407	0.02584	0.03436	0.03988	0.04337	0.04558	0.04702	0.04801
		0.04873	0.04930	0.04977	0.05017	0.05050	0.05072	0.05079	0.05055
		0.04976	0.04810	0.04538	0.04282	0.03966	0.03470	0.02652	0.01440
13	5	0.01377	0.02563	0.03410	0.03955	0.04296	0.04512	0.04651	0.04746
		0.04814	0.04867	0.04910	0.04946	0.04978	0.05000	0.05010	0.04997
		0.04948	0.04844	0.04676	0.04466	0.04155	0.03637	0.02768	0.01473
13	6	0.00705	0.02524	0.03413	0.03981	0.04334	0.04555	0.04698	0.04794
		0.04862	0.04915	0.04959	0.04996	0.05027	0.05052	0.05065	0.05061
		0.05029	0.04955	0.04828	0.04634	0.04314	0.03755	0.02800	0.00744
13	7	0.00623	0.02485	0.03419	0.04006	0.04367	0.04590	0.04730	0.04823
		0.04888	0.04937	0.04975	0.05007	0.05034	0.05054	0.05065	0.05059
		0.05029	0.04963	0.04846	0.04654	0.04323	0.03738	0.02732	0.00650
14	1	0.00843	0.03089	0.04290	0.05067	0.05553	0.05853	0.06040	0.06160
		0.06241	0.06300	0.06345	0.06379	0.06402	0.06405	0.06369	0.06247
		0.05920	0.05065	0.00396	0.00308	0.00270	0.00228	0.00163	0.00067
14	2	0.00849	0.03100	0.04295	0.05066	0.05548	0.05846	0.06031	0.06150
		0.06230	0.06287	0.06330	0.06363	0.06386	0.06389	0.06355	0.06239
		0.05927	0.05106	0.00409	0.00323	0.00285	0.00241	0.00173	0.00072
14	3	0.00866	0.03123	0.04304	0.05067	0.05542	0.05834	0.06015	0.06130
		0.06206	0.06260	0.06301	0.06331	0.06350	0.06352	0.06320	0.06213
		0.05928	0.05178	0.00443	0.00360	0.00321	0.00273	0.00199	0.00086
15	1	0.00812	0.03107	0.04354	0.05168	0.05675	0.05984	0.06173	0.06289
		0.06363	0.06412	0.06446	0.06469	0.06481	0.06469	0.06412	0.06245
		0.05806	0.04649	0.00230	0.00141	0.00118	0.00098	0.00069	0.00030
15	2	0.00812	0.03113	0.04356	0.05166	0.05672	0.05980	0.06167	0.06282
		0.06354	0.06403	0.06436	0.06459	0.06469	0.06458	0.06402	0.06241
		0.05816	0.04687	0.00237	0.00150	0.00125	0.00105	0.00076	0.00033
15	3	0.00810	0.03125	0.04362	0.05167	0.05668	0.05973	0.06157	0.06269
		0.06339	0.06386	0.06416	0.06437	0.06445	0.06434	0.06380	0.06228
		0.05829	0.04757	0.00255	0.00169	0.00145	0.00122	0.00088	0.00039

Figure 4-11

H.B. Robinson Unit 2 Cycle 8
Ratio Core Average K/Nu to Assembly Average K/Nu

	H	G	F	E	D	C	B	A
8	43869	13399	25435	26338	16063	16011	25940	4200
	77.4	80.1	78.7	78.6	79.7	79.7	78.6	81.9
	1.031	.997	1.015	1.016	1.001	1.001	1.015	.974
9		26138	12669	24345	13478	28188	6051	3490
		78.6	80.2	78.8	80.1	78.4	81.5	82.2
		1.015	.995	1.013	.997	1.018	.979	.971
10			28309	13378	24899	17318	5101	
			78.4	80.1	78.7	79.6	81.7	
			1.018	.996	1.014	1.003	.976	
11				17161	24192	5918	3626	MWD/MTU
				79.6	78.8	81.5	82.1	K/NU (MEV)
				1.003	1.013	.979	.972	CORE/ASSY RATIO
12					16348	3757		
					79.7	82.1		
					1.002	.972		

ASSEMBLY EXPOSURE = (BOC + EOC) / 2
K/NU VS. EXPOSURE FROM XPOSE (ENC 2.9% 500PPM 573F)

CORE AVERAGE EXPOSURE = (BOC + EOC) / 2 = 15243 MWD/MTU
CORE AVERAGE K/NU = 79.8 MEV

4-40
Figure 4-12
H.B. Robinson Unit 2 Cycle 10

Ratio Bottom Average K/Nu to Bottom Assembly Average K/Nu

	H	G	F	E	D	C	B	A
8	7586	19702	29124	7476	29126	17145	4898	0
	81.2	79.0	78.3	81.2	78.3	79.6	81.8	0
	.984	1.011	1.020	.984	1.020	1.004	.977	0.0
9		18571	16914	28016	14133	15817	4856	0
		79.4	79.6	78.4	80.0	79.7	81.8	0
		1.006	1.004	1.019	.999	1.002	.977	0.0
10			29629	7482	25917	24416	4632	
			78.3	81.2	78.6	78.8	81.8	
			1.020	.984	1.016	1.014	.976	
11				29731	14842	6070	3821	MWD/MTU
				78.3	79.9	81.5	82.1	K/NU (MEV)
				1.020	1.000	.980	.973	CORE/ASSY RATIO
12					6061	22681		
					81.5	78.9		
					.980	1.012		

Ratio Top Average K/Nu to Top Assembly Average K/Nu


	H	G	F	E	D	C	B	A
8	6799	19064	28607	6873	28920	17522	6667	2283
	81.3	79.3	78.4	81.3	78.7	79.5	81.3	82.5
	.982	1.007	1.017	.982	1.015	1.005	.982	.968
9		17953	16320	27584	13838	16047	6178	1832
		79.5	79.7	78.5	80.0	79.7	81.5	82.6
		1.005	1.003	1.018	.998	1.002	.980	.966
10			29107	6813	25555	24336	4959	
			78.3	81.3	78.6	78.8	81.8	
			1.020	.982	1.016	1.014	.977	
11				29236	14336	5703	3729	MWD/MTU
				78.3	79.9	81.6	82.1	K/NU (MEV)
				1.020	.999	.979	.973	CORE/ASSY RATIO
12					5518	22458		
					81.6	78.9		
					.979	1.012		

ASSEMBLY EXPOSURE = (BOC + EOC) / 2
K/NU VS. EXPOSURE FROM XPOSE (ENC 2.9% 500PPM 573F)

CORE AVERAGE EXPOSURE = (BOC + EOC) / 2 = 14750 MWD/MTU
CORE AVERAGE K/NU = 79.9 MEV

Figure 4-13

KAPPA/NU (MEV) VS. EXPOSURE
ENC 2.85 W/O 22GWT TM 573F 500 PPM
XPOSE (XPOSEUX 29/04/83)



A study was performed to assess the effect of this multiplier on the analyses of Capsules S, V, and T, removed from HBR2 at the end of Cycles 1, 3, and 8, respectively. The following quantities, used to determine saturation activity of the removed samples, were determined based on the daily operating history of the plant:

$$F = \sum_{j=1}^N mP_j/P_R (1 - \exp[-\lambda_i(t_j - t_{j-1})]) \exp[-\lambda_i(t_m - t_j)] \quad (4.2)$$

$$EFPD = \sum_{j=1}^N mP_j/P_R [t_j - t_{j-1}] \quad (4.3)$$

where P_R = reference full power

P_j = average power from t_{j-1} to t_j

t_m = time of capsule measurement

λ_i = decay constant of isotope i

These results are compared in Table 4-6 to analogous quantities calculated with the monthly power history as reported in the analyses of the Capsule T.¹⁶ Note that the effect of power flattening and finer time history is small, but is a few percent for some isotopes. The Factor $F(\text{Monthly History})$ in Table 4-6 was used to back out measured dps/s from saturated activities reported for Capsule T.^{16,17} The measured dps/s was reported for Capsules S and V.¹⁸ In Table 4-7, saturated activities computed with $F(\text{Daily History})$ from Table 4-6 are compared to saturated activities reported in the above references. The corrected measured saturation activities shown in Table 4-7 were used for comparisons with calculated activities from the Cycle 8 Synthesis.

Table 4.6

Comparison of Saturation Factors for HBR#2 Surveillance Capsules

	Isotope	Decay Constant (1/day)	F(Daily Hist)	F(Month Hist)	Ratio
Capsule S	Mn-54	.22075E-2	.56211	.52855	1.0635
Capsule V	Co-58	.97079E-2	.86689	.83030	1.0441
	Mn-54	.22075E-2	.75357	.74311	1.0141
	Co-60	.36010E-3	.32483	.32179	1.0094
Capsule T	Co-58	.97079E-2	.06951	.06527	1.0650
	Mn-54	.22075E-2	.36235	.34257	1.0577
	Co-60	.36010E-3	.46115	.45062	1.0234
	Cs-137	.62840E-4	.14594	.14344	1.0174

Table 4.7

Comparison of Corrected and Reported Saturated Activities for HBR#2 Capsules

	Isotope	Corrected A _{Sat} (dps/g)	Reported A _{Sat} (dps/g)
Capsule S (EOC1 10')	Mn-54(Avg)	4.77E6	--
Capsule V (EOC3 20')	Co-58	4.833E7	4.76E7
	Mn-54(Avg)	3.278E6	3.19E6
	Co-60	3.54E5	3.43E5
Capsule T (EOC8 0')	Co-58	1.164E8	1.24E8
	Mn-54(Avg)	8.39E6	8.87E6
	Co-60	7.525E5	7.70E5
	Cs-137(Np)	8.565E7	8.71E7
	Cs-137(U238)	1.297E7	1.32E7

4.3.5 Normalization of Sources Input to DOT-4

A computer program AXFRAC, was written to provide normalization of input to DOTSOR for the HBR2 problem. The program is listed in Appendix B.

DOTSOR converts the PDQ7 relative pin power distribution in X-Y geometry to neutron source distribution in R- θ geometry. To normalize the distribution to absolute neutron source, the correspondence between X-Y zone (assembly) total power and R- θ zone total power must be provided. AXFRAC provided this input to DOTSOR based on the assembly distributions of Figures 4-1 and 4-10, respectively, for the Cycle 8 and Cycle 10 calculations. The K/v corrections given in Figures 4-11 and 4-12 were also applied. The normalization was provided for an upper and a lower section based on integration of XTG assembly-wise axial distribution up to and then beyond the PLSA shield-fuel interface. The splitting is consistent with the synthesis-superposition technique for developing the final 3-D flux distributions.

AXFRAC also developed R-Z and R neutron source distributions for the R-Z DOT and R ANISN calculations that provided the synthesis functions for determining the 3-D flux. It is required that the normalization between these two calculations be consistent (not absolute), since together they provide only the Z shape to the final distribution. To provide greater accuracy in the region of greatest concern, the R-Z and R calculations model the geometry and source along the core major axis. The R-Z source was determined by combining the PDQ7 assembly distributions along the axis with quarter-assembly-wise axial distributions along the axis. The

power density distribution was multiplied by the R-Z mesh volumes and summed along Z to provide the R distribution input to ANISN.

AXFRAC was used to generate DOTSOR, DOT, and ANISN input for Cycle 8 upper core, lower core, and total core cases and for Cycle 10 upper core and lower core cases. The results were verified by hand calculations for sources within each PDQ7 and XTG zone. Equations governing generation of sources are given in Figure 4-14.

4.4 GEOMETRIC MODELS

The models listed in Table 4-8 were used in various stages of this analysis. Each of the following subsections describes one of the geometries used in the analysis.

4.4.1 One-Dimensional Model Used for Material Selection Reduction Factor Calculations

A one-dimensional slab model was developed to provide a preliminary estimate of the fluence reduction at the inner surface of the RPV for the various materials under consideration. The outer fuel assembly in the model was replaced with a PLSA containing either stainless steel, Inconel, Zircaloy, water, or natural uranium to investigate the fluence reduction. The model shown in Figure 4-15 specifically includes the outermost three fuel assemblies, the core baffle, the core barrel, the thermal shield, and the reactor pressure vessel. The material zones used in the model are defined in Table 4-9. The slab geometry

$$S^U(r, \theta, E) = \frac{\overline{kw} \chi(E)}{[\kappa/v(r, E)]^U} \cdot \frac{A(r, \theta)}{A(x, y)} \cdot P_{PDQ}^{Av}(x, y) \cdot \sum_{\text{above shield}}^{r, \theta} P_{XTG}(z)$$

$$S^L(r, \theta, E) = \frac{\overline{kw} \chi(E)}{[\kappa/v(r, E)]^L} \cdot \frac{A(r, \theta)}{A(x, y)} \cdot P_{PDQ}^{Av}(x, y) \cdot \sum_{\text{shield}}^{r, \theta} P_{XTG}(z)$$

$$S^U(r, z, E) = \frac{\overline{kw} \chi(E)}{[\kappa/v(r, E)]^U} \cdot \frac{V(r, z)}{V(x, y)} \cdot \begin{cases} P_{PDQ}^U(o, y) \cdot P_{XTG}(z) & z > \text{shield hgt.} \\ 0 & z < \text{shield hgt.} \end{cases}$$

$$S^L(r, z, E) = \frac{\overline{kw} \chi(E)}{[\kappa/v(r, E)]^L} \cdot \frac{V(r, z)}{V(x, y)} \cdot \begin{cases} 0 & z < \text{shield hgt.} \\ P_{PDQ}^L(o, y) \cdot P_{XTG}(z) & z > \text{shield hgt.} \end{cases}$$

$$S^U(r, E) = \sum_{\text{above shield}} S^U(r, z, E)$$

$$S^L(r, E) = \sum_{\text{shield}} S^L(r, z, E)$$

\overline{kw} = average pin power

$\chi(E)$ = fission spectrum

κ/v = (power/neutrons per fission)

$A(r, \theta)$ = mesh area (in pin cell units) at r, θ

$A(x, y)$ = PDQ pin cell fraction

$V(r, t)$ = mesh volume at r, z

$V(x, y)$ = arbitrary constant (at all x, y)

$P_{PDQ}(x, y)$ = cycle-average power (relative) PDQ

$$P_{PDQ}^{Av}(x, y) = 3/4 \cdot P_{PDQ}^U(x, y) + 1/4 \cdot P_{PDQ}^L(x, y)$$

$P_{XTG}^{r, \theta}(z)$ = cycle-average axial distribution from XTG

$$\overline{kw} \sum_{1/8 \text{ core}}^{Av} P_{PDQ}(x, y) A(x, y) = 1/8 \cdot 2300Mwt$$

$$\sum_Z^{r, \theta} P_{XTG}(z) = 1.0 \text{ at all } r, \theta$$

Figure 4-14. Equations used in AXFRAC and DOTSOR.

Table 4-8

NEUTRONICS MODELS USED IN THE ANALYSES

Model	Purpose
1-D Reduction Model	Used to evaluate fluence reduction characteristics of various materials under consideration for use in the PLSA
1-D Eigenvalue Model	Used to evaluate the effect of the various materials under consideration on the core reactivity
Fuel Pin Cell Model	Used in geometric self-shielding calculation during cross-section generation
DOT-IV Homogeneous R-Z Model	Used in calculations to determine optimum partial length shield height
DOT-IV R- θ Model	Used in preliminary circumferential flux reduction calculations as well as flux calculations for input to the flux synthesis
DOT-IV Heterogeneous R-Z Model	Used in the calculation of the flux for input to the flux synthesis




Figure 4-15. ANISN One-Dimensional Slab Model for Fixed Source Analysis (See Table 4-9 for zone definitions).

Table 4-9

ANISN ONE-DIMENSIONAL SLAB MODEL ZONE ASSIGNMENTS

Zone Number	Description
1	Fuel Assembly 1
2	Fuel Assembly 2
3	Fuel Assembly 3 or Shield Assembly
4	Core Baffle
5	H ₂ O
6	Core Barrel
7	H ₂ O
8	Thermal Shield
9	H ₂ O
10	Reactor Pressure Vessel

dimensions for the various material regions were taken as the radial dimensions at the position corresponding to the center of the core flats. The left boundary was treated as a reflected boundary, and the right boundary was treated as a vacuum boundary. The mesh spacing in this model is listed in Table 4-10.

4.4.2 One-Dimensional Eigenvalue Model


The geometrical configuration of the one-dimensional slab model is shown in Figure 4-16. The model consists of five material regions: three fuel assemblies of different fuel/PLSA materials, one core baffle region, and one region of 18 cm of water serving as the core reflector.

Each of the first three regions is one fuel assembly in thickness. For the base case, three fuel assemblies are composed of fuel having enrichments of 2, 2, and 3 weight percent U-235, respectively. For the PLSA cases, the first two fuel assemblies contain fuel having enrichments of 2 and 3 weight percent U-235, respectively. The third region is a PLSA consisting of one of the following shield materials: stainless steel-304, Inconel-718, Zircaloy-4, water, or depleted UO₂. For all cases except water, the PLSA is identical in geometry and material to a fuel assembly except that the fuel material is replaced by the specified shield material. The detailed design parameters of the fuel assemblies in the calculations were taken from Reference 19. For the case of water as the shield material, the third region is filled with water. No structural materials such as tubes are present. The fourth material region is composed of core baffle which is made of stainless steel (SS-304), and the last region consists of an 18-cm water reflector.

Table 4-10

MESH INTERVALS USED IN ONE-DIMENSIONAL SLAB MODEL

Region	Mesh Intervals (Number)	Interval Width (cm)
Fuel - 1	15	1.4336
Fuel - 2	12	1.4336
	5	0.8602
Fuel - 3	5	0.8602
	9	1.4336
	5	0.8602
Baffle	5	0.5716
H ₂ O-1	7	0.8404
Core Barrel	7	0.7373
H ₂ O-2	7	0.8503
Thermal Shield	3	0.6500
	3	0.9750
	3	0.6500
H ₂ O-3	11	0.8660
Vessel	6	0.8890
	11	1.3335



Fuel Temperature: 1300°F
 Clad Temperature: 600°F
 Water Temperature: 575°F
 Water contains 500 ppm boron

Figure 4-16. One-Dimensional Slab PLSA Core Model for Eigenvalue Calculations.

This reflector is considered to provide an adequate model of the neutron transport effect of the shield and reflector materials beyond the core baffle such as the core-barrel, water, and thermal shield.


The one-dimensional slab eigenvalue analyses employed a reflected boundary condition (i.e., zero current) at the left boundary for all cases, while a vacuum boundary condition was applied at the right boundary.

4.4.3 Fuel Pin Cell Model


The fuel pin cell model shown in Figure 4-17 was developed in order to perform the cell calculations necessary for self-shielding calculations. A fuel pin cell consists of a fuel rod surrounded by boronated water mixture in a square area. This geometry with a square cross-sectional area was transformed to a cylindrical geometry with the same volume of water as in the original pin configuration.

4.4.4 DOT-IV Homogeneous R-Z Model

A two-dimensional R-Z analysis to determine the optimum shield height was performed with the model shown in Figure 4-18. The model utilizes 93 axial intervals and 70 radial intervals for a total of 6510 mesh points. The zones used in the model are listed in Table 4-11. Axially, the model contains regions that describe the shield, the lower fuel assembly structure, the upper fuel assembly structure, and the inactive fuel region. This model was obtained by computing the volume fractions of the various components as a function of the radius. This results in an inner region (zones 2 and 3) that represents the core as a homogeneous fuel assembly mixture; a region of transition (zones 5, 6, 7, 8, and 9) containing seven homogeneous annular regions each with different



(a) Fuel Pin Cell Model



(b) Equivalent Fuel Pin Cell Model

Figure 4-17. Fuel Pin Cell Model Geometry

4-60




Figure 4-18. DOT-IV R-Z Reactor Model

Table 4-11

DOT-IV HOMOGENEOUS R-Z REACTOR MODEL ZONE ASSIGNMENTS

Zone	Description
1	Lower Fuel Assembly Structure
2	Active Core Fuel Assemblies
3	Inactive Core Fuel Assemblies
4	Upper Fuel Assembly Structure
5	Lower Shield Transition Region
6	Active Core Fuel Assemblies Transition Region
7	Upper Shield Transition Region
8	Inactive Core Fuel Assemblies Transition Region
9	Core Baffle and H ₂ O Mixture
10	H ₂ O
11	Core Barrel
12	H ₂ O
13	Thermal Shield
14	H ₂ O
15	Reactor Pressure Vessel

volume fractions for fuel assemblies, core baffle, and water; and a heterogeneous representation of the core barrel, thermal shield, and reactor vessel.

The volume fractions in the transition region vary as shown in Table 4-12 for the shield, fuel, and inactive fuel. The assembly volume fractions listed imply for the case of the shield transition region that any fuel located further from the core center than the innermost edge of the shield assembly is also a shield. This change in the material was necessary since for a true homogeneous radial model the shield would have only a small influence on the average circumferential flux. This change allows a calculation of the reduction factor that is indicative of the reduction in the vessel fluence at the circumferential position corresponding to the center of the core flats. The total volume of the shield assembly in the transition region represents an effective shield thickness of 16 cm.

4.4.5 DOT-IV R- θ Model

A two-dimensional R- θ model that explicitly describes the outer rows of fuel assemblies and the RPV components was developed. The model (shown in Figure 4-19, zones listed in Table 4-13) was defined using the variable mesh option of the DOT-IV computer code. Thus, a separate set of radial boundaries was defined for each of the 60 angular intervals in the one-eighth core model. The total number of radial intervals in any angular segment varied between 78 and 96. A total of 5183 mesh points were contained in the model. The angular boundary conditions and the inner boundary were all reflected. The outer boundary condition was vacuum.

Table 4-12

RADIAL VOLUME FRACTIONS IN THE DOT-IV R-Z MODEL

Transition Reason	Radius (cm)		Assembly	Volume Fraction Baffle	H ₂ O
	Inner	Outer			
1	136.00	142.00	0.9781	0.0211	0.0008
2	142.00	147.00	0.8077	0.1453	0.0470
3	147.00	153.00	0.5235	0.1989	0.2776
4	153.00	157.50	0.3380	0.1353	0.5267
5	157.00	161.25	0.2638	0.0842	0.6520
6	161.25	166.25	0.0656	0.1769	0.7605
7	166.25	168.75	0.0000	0.0295	0.9705




Figure 4-19. DOT-IV R-θ Reactor Model.

Table 4-13

DOT-IV R-ø REACTOR MODEL ZONE ASSIGNMENTS

Zone Number	Description
1	Inner Fuel Assemblies
2-14	Fuel Assemblies
15-16	Fuel Assemblies or Shield Assemblies
17	Core Baffle
18	H ₂ O
19	Core Barrel
20	H ₂ O
21	Thermal Shield
22	H ₂ O
23	Reactor Pressure Vessel

4.4.6 DOT-IV Heterogeneous R-Z Model

The model shown in Figure 4-20 was developed to explicitly describe the fuel-to-pressure-vessel geometry along the core flat. Unlike the model described in Section 4.4.4, this model maintains the heterogeneous nature of the components of the model. This model contains the 13 distinct material regions shown in Figure 4-20 and listed in Table 4-14. This model was selected for use in the flux synthesis and reduction factor calculations because it most closely describes the geometry in the region of greatest interest. Flux synthesis using this model to determine the axial shape functions should provide a better estimate of the flux in the region of the core flat. However, this gain is at the loss of accuracy in the circumferential positions away from the core flat. These regions are of little interest because the partial length shield assemblies will have negligible effects in reducing the vessel fluence in regions away from the core flats.

4.5 NUMBER DENSITIES

All of the models used in this analysis describe only 10 different material regions of the reactor. Each of these 10 regions are listed with the associated volume fraction of the materials that comprise the region in Table 4-15.

Only a few materials are present in the various regions. Number densities for each of these materials are based upon the actual composition as provided in Reference 20. Table 4-16 lists the resulting number densities for each of the materials present in the model regions.




Figure 4-20. DOT-IV Heterogeneous R-Z Model.

Table 4-14

DOT-IV HOMOGENEOUS R-Z REACTOR MODEL ZONE ASSIGNMENTS

Zone	Description
1	Lower Fuel Assembly Structure
2, 3	Active Core Fuel Assemblies
4	Inactive Core Fuel Assemblies
5	Upper Fuel Assembly Structure
6	Lower Shield Region
7	Core Baffle and H ₂ O Mixture
8	H ₂ O
9	Core Barrel
10	H ₂ O
11	Thermal Shield
12	H ₂ O
13	Reactor Pressure Vessel

Table 4-15

MATERIAL VOLUME FRACTIONS BY MATERIAL REGION

Region	Reactor Material	Volume Fraction
Fuel Assembly	H ₂ O	0.5895
	UO ₂ or Alternate	0.2841
	Zircaloy 4	0.1143
	Helium or Void	0.0121
H ₂ O	H ₂	1.0000
Boronated H ₂ (500 ppm)	Boronated H ₂ O	1.0000
Core Baffle	Stainless Steel 304	1.0000
Core Baffle	Stainless Steel 304	1.0000
Thermal Shield	Stainless Steel 304	1.0000
Reactor Pressure Vessel	Carbon Steel	1.0000
Lower Assembly Structure	Inconel 718	0.0226
	Stainless Steel 304	0.2334
	H ₂ O	0.7440
Inactive Fuel Rods	H ₂ O	0.5895
	Zircaloy 4	0.1143
	Inconel 718	2.3280x10 ⁻⁴
Upper Assembly Structure	Stainless Steel 304	0.1447
	Inconel 718	0.0144
	H ₂ O	0.8409

Table 4-16

ELEMENT NUMBER DENSITIES (atoms/bn-cm) FOR REACTOR MATERIALS

Material	Element	Density
2.9 w% UO ₂	O	4.599-2
	U-235	6.751-4
	U-238	2.232-2
2.0 w% UO ₂	O	4.599-2
	U-235	4.659-4
	U-238	2.754-2
3.0 w% UO ₂	O	4.599-2
	U-235	6.987-4
	U-238	2.231-2
Zircaloy 4	Fe	1.494-4
	Cr	7.641-5
	Zr	4.279-2
Stainless Steel 304	C	3.220-4
	Mn	1.760-3
	P	7.035-5
	S	4.523-5
	Si	1.721-3
	Cr	1.766-2
	Ni	7.616-3
	Fe	5.938-2
Inconel 718	Ni	4.411-2
	C	1.643-4
	Mn	1.796-4
	Fe	1.590-2
	Si	3.512-4
	Cr	1.802-2
	Al	1.097-3
	Mo	1.543-3
Carbon Steel	Fe	8.270-2
	Mn	1.200-3
	Si	1.000-4
	P	1.380-5
	S	2.220-5
	C	7.440-4

Table 4-16 (Continued)

Material	Element	Density (Number)
Natural UO ₂	O	4.598-2
	U-235	1.641-4
	U-235	2.283-2
575°F H ₂ O	H	4.739-2
	O	2.370-2
Boronated H ₂ O	H	4.739-2
	O	2.370-2
	B-10	4.219-6
	B-11	1.556-5

*4.599-2 denotes 4.599×10^{-2}

4.6 SAMPLE INPUTS

This section contains sample input files for each major transport analysis required in the best-estimate flux reduction factor. These files consist of (1) DOT R-Z input for analysis of the top of core-Cycle 10, (2) DOT R-Z input for analysis of the bottom of core-Cycle 10, (3) DOT R- θ input for the top of core-Cycle 10, (4) DOT R- θ input for the bottom of core-Cycle 10, (5) ANISN-W input for the top of core-Cycle 10, (6) ANISN-W input for the bottom of core-Cycle 10.

Input for the PDQ7 and XTG diffusion calculations requires history files stored on magnetic tapes and cross-sections that are proprietary to Exxon Nuclear Company. These are not presented here but are available for NRC review upon request.

4-73

DOT R-Z INPUT CYCLE 10 TOP OF CORE

The image displays a large, empty grid structure. It consists of approximately 40 vertical columns and 6 horizontal rows of small, evenly spaced dots. These dots are arranged in a regular pattern, creating a grid that is typical of a punched-card layout or a specialized data table. The grid is contained within a rectangular border.



DOT R-Z INPUT CYCLE 10 BOTTOM OF CORE

1. 237-2 2. 312-2
1. 956-2 3. 927-3
2. 372-2 2. 368-2
4. 772-2 2. 368-2
4. 655-2 4. 505-2
4. 306-2 4. 074-2
7. 384-2 3. 259-2
2. 993-2 2. 723-2
4. 654-2 3. 755-2
4. 221-2 2. 054-2
2. 822-2 7. 853-3
1. 653-2 2. 502-3
2. 174-3 3. 329-3
3. 917-3 8. 184-4
3. 280-4 1. 335-4
2. 289-4 8. 048-4
2. 511-4 2. 921-4
4. 182-5 3. 511-5
2. 865-5 3. 083-5
2. 728-5 4. 330-7
1. 530-6 0.
T

MFA U.C.C. NDS/BE L864 V1.6.08.2 23/08/83
16.12.42.LASEROU FROM SV
16.12.42.IP 00003520 WORDS - FILE INPUT , DC 04
16.12.42.LASER.P2.LASER
16.12.43.ACCOUNT.GK7YEC,*****
16.12.43.REWIND,OUTPUT
16.12.43.ROUTE,OUTPUT,DEF,TID=80
16.12.44.UCC,BANNER,DDY R-Z,CYCTO 80Y,INPUT
16.12.45.COPYBR,INPUT,AA
16.12.45.COPYBR,INPUT,BB
16.12.45.REWIND,AA,BB
16.12.45.COPYSBP,BB,OUTPUT
16.12.45.BEGIN,PPRINT,1:OUTPUT,H=AA,FORM=2UP,COP
16.12.45.IES+1
16.12.46.AT CY: 124 SN=GLOBAL
16.12.48.
16.12.48.COPYRIGHT, 1981, UNIVERSITY COMPUTING C
16.12.48.OMpany
16.12.48.REPRODUCTION PROHIBITED UNLESS SPECIFIC
16.12.48.ALLY
16.12.48.AUTHORIZED BY SEPERATE WRITING.
16.12.48.
16.12.48.RETURN,ZZZZZIN,ZZZZZPO,DAYFILE,DAYFIL
16.12.49.IFE(FILE(AA,AS),H1)
16.12.49.COPYBR,AA,ZZZZZIN
16.12.49.ENDIF,H1
16.12.49.COPY,ZZZZZP1,ZZZZZIN
16.12.49.RETURN,ZZZZZP1
16.12.49.UCC,BANNER(G=ZZZZZIN, BIN,54)
16.12.51.REWIND,OUTPUT
16.12.51.COPY,OUTPUT,ZZZZZIN
16.12.51.IFE((T.AND.(DT.NE.YX0)),GLOOP)
16.12.51.SUMMARY
16.12.51.MS 58498 WORDS (68738 MAX USED)
16.12.51.MM 300008 MAX SCM
16.12.51.CPR 1.186
16.12.51.IOR 469
16.12.51.SRU 1.535
16.12.51. DATE 09/09/83
16.12.51.DAYFIL

DOT R-θ INPUT CYCLE 10 TOP OF CORE

211.2857+2	311.3500+2	711.4027+2	511.5000+2	211.5800+2
111.5385+2	1.6471+2	211.6800+2		
31170.021	41175.182	41181.134	71187.959	151197.485
217.0000+1	9.728+1	111.0000+2	111.0700+2	21112.8372
118.87	211.2000+2	31125.00	31135.00	711.4048+2
211.5800+2	111.5210+2	1.5487+2	211.6800+2	
31170.021	41175.182	41181.134	71187.959	151197.485
117.0000+1	2183.7308	97.462	411.0000+2	11115.833
211.2000+2	11125.00	21130.00	41135.00	611.4078+2
311.5800+2	211.5244+2	1.5531+2	211.6800+2	
31170.021	41175.182	41181.134	71187.959	151197.485
217.0000+1	1190.7672	97.690	311.0000+2	511.2000+2
511.111+2	511.5000+2	311.5800+2	211.5282+2	211.5600+2
31170.021	41175.182	41181.134	71187.959	151197.485
217.0000+1	1190.9708	97.961	111.0000+2	31107.0
411.5800+2	511.4150+2	511.5000+2	311.5800+2	111.5327+2
211.6800+2				
31170.021	41175.182	41181.134	71187.959	151197.485
217.0000+1	1181.2007	88.254	111.0000+2	11106.557
21130.00	51135.00	511.4194+2	511.5000+2	411.5800+2
111.5378+2	1.6600+2	211.5868+2		
31170.021	41175.182	41181.134	71187.959	151197.485
217.0000+1	1191.4182	88.555	111.0000+2	21105.00
511.3500+2	511.4236+2	511.5000+2	411.5800+2	111.9426+2
1.6600+2	111.5717+2			
31170.021	41175.182	41181.134	71187.959	151197.485
317.0000+1	211.0000+2	111.2000+2	11127.00	11132.00
511.4274+2	511.5000+2	1.5800+2	411.5816+2	1.6600+2
111.5782+2				
31170.021	41175.182	41181.134	71187.959	151197.485
317.0000+1	211.0000+2	11115.00	120.00	511.2106+2
511.4306+2	1.5000+2	411.5138+2	411.5800+2	1.6477+2
211.6800+2				
31170.021	41175.182	41181.134	71187.959	151197.485
317.0000+1	211.0000+2	11115.00	120.00	1011.2127+2
111.4332+2	211.4898+2	511.5000+2	1.5800+2	511.5891+2
211.6800+2				
31170.021	41175.182	41181.134	71187.959	151197.485
317.0000+1	211.0000+2	111.1500+2	1.2000+2	1011.2148+2
411.3500+2	111.4121+2	411.4357+2	211.6000+2	211.5372+2
511.5800+2	211.6800+2			
31170.021	41175.182	41181.134	71187.959	151197.485
317.0000+1	211.0000+2	11115.00	120.00	511.2170+2
411.3886+2	311.4382+2	1.4809+2	511.5000+2	511.5800+2
211.5800+2				
31170.021	41175.182	41181.134	71187.959	151197.485
317.0000+1	211.0000+2	11115.00	11120.00	711.2193+2
111.2289+2	511.3500+2	111.4810+2	111.4704+2	511.6000+2
511.5800+2	211.6800+2			
31170.021	41175.182	41181.134	71187.959	151197.485
317.0000+1	211.0000+2	11115.00	111.2000+2	211.2232+2
511.2643+2	711.3500+2	111.4456+2	111.4752+2	511.5000+2
511.5800+2	211.6800+2			
31170.021	41175.182	41181.134	71187.959	151197.485
317.0000+1	211.0000+2	115.00	1.1877+2	111.2000+2
911.2291+2	711.3500+2	111.4525+2	111.4822+2	511.5000+2
511.5800+2	211.6800+2			
31170.021	41175.182	41181.134	71187.959	151197.485
317.0000+1	211.0000+2	311.1130+2	211.2000+2	511.2358+2
511.3500+2	111.4604+2	1.4903+2	511.5000+2	511.5800+2
211.6800+2				
31170.021	41175.182	41181.134	71187.959	151197.485
217.0000+1	1182.25	1+2	1.0189+2	511.0481+2
711.2429+2	511.3500+2	211.4885+2	511.50	511.5800+2
31170.021	41175.182	41181.134	71187.959	151197.485
217.0000+1	1182.25	100.00	511.0226+2	311.2000+2
511.3500+2	111.4771+2	1.5000+2	511.5073+2	511.5800+2
31170.021	41175.182	41181.134	71187.959	151197.485
217.0000+1	8.5518+1	1.0000+2	511.0281+2	411.2000+2
511.2565+2	101135	1.4850+2	1.5000+2	411.5154+2
511.5800+2	211.6800+2			
31170.021	41175.182	41181.134	71187.959	151197.485
217.0000+1	9.1858+1	1.0000+2	511.0336+2	211.2000+2
511.2835+2	1011.3500+2	1.4823+2	111.5000+2	411.5238+2
511.5800+2	211.6800+2			
31170.021	41175.182	41181.134	71187.959	151197.485
217.0000+1	118.8409+1	1.0000+2	511.0393+2	211.2000+2
511.2703+2	511.3500+2	111.4735+2	1.5000+2	211.5012+2
511.5319+2	511.5800+2	211.6800+2		
31170.021	41175.182	41181.134	71187.959	151197.485
117.0000+1	118.5585+1	1.0000+2	511.0446+2	211.2000+2
511.2767+2	511.3500+2	511.4278+2	1.5000+2	211.5088+2
211.5388+2	511.5800+2	211.6800+2		
31170.021	41175.182	41181.134	71187.959	151197.485
117.0000+1	118.3105+1	1.0000+2	511.0500+2	211.2000+2
411.2833+2	211.3500+2	511.3851+2	1.5000+2	211.5187+2
211.5477+2	511.5800+2	211.6800+2		
31170.021	41175.182	41181.134	71187.959	151197.485
117.0000+1	118.2077+1	1.0000+2	511.0553+2	311.2000+2
211.2888+2	1111.3500+2	111.5000+2	211.5243+2	111.5556+2
511.5800+2	211.6800+2			
31170.021	41175.182	41181.134	71187.959	151197.485
117.0000+1	118.2472+1	1.0000+2	211.0604+2	211.2000+2
128.00	11129.5	211.3149+2	1111.3500+2	211.5000+2
111.5629+2	511.5800+2	211.6800+2		
31170.021	41175.182	41181.134	71187.959	151197.485
117.0000+1	118.2885+1	1.0000+2	211.0671+2	211.2000+2
11.2755+2	311.3042+2	1111.3500+2	211.5000+2	211.5413+2
511.5800+2	211.6800+2			
31170.021	41175.182	41181.134	71187.959	151197.485
117.0000+1	118.3552+1	1.0000+2	211.0756+2	1.2000+2
311.2312+2	211.3179+2	1111.3500+2	311.5000+2	111.5537+2
511.5800+2	211.6800+2			
31170.021	41175.182	41181.134	71187.959	151197.485
117.0000+1	118.4243+1	1.0000+2	111.0831+2	117.31
41120.00	111.3238+2	1111.3500+2	411.5000+2	1.5545+2
1.5800+2	411.5965+2	211.6800+2		
31170.021	41175.182	41181.134	71187.959	151197.485
117.0000+1	118.4726+1	1.0000+2	111.0883+2	1.1707+2
411.2000+2	1.3514+2	1111.3500+2	511.5000+2	1.5735+2
111.5800+2	311.6057+2	211.6800+2		
31170.021	41175.182	41181.134	71187.959	151197.485
117.0000+1	118.5225+1	1.0000+2	1.0955+2	1.1459+2
511.2000+2	1.3383+2	1111.3500+2	511.5000+2	211.5800+2
311.5151+2	211.6800+2			
31170.021	41175.182	41181.134	71187.959	151197.485
117.0000+1	118.5646+1	111.0000+2	1.1012+2	111.1258+2
511.2000+2	1111.3500+2	511.5000+2	311.5800+2	211.6231+2
211.6800+2				
31170.021	41175.182	41181.134	71187.959	151197.485
117.0000+1	118.5956+1	111.0000+2	111.1130+2	511.2000+2
1111.3500+2	411.5000+2	111.5552+2	211.5800+2	211.5178+2
211.6800+2				
31170.021	41175.182	41181.134	71187.959	151197.485
117.0000+1	118.6278+1	111.0000+2	111.1093+2	1111.2000+2
1111.3500+2	211.5000+2	211.5395+2	1.5800+2	411.5979+2
211.6800+2				
31170.021	41175.182	41181.134	71187.959	151197.485
117.0000+1	118.6743+1	111.0000+2	1.0817+2	111.1151+2
1111.2000+2	1.3500+2	1011.3630+2	1.5000+2	411.5144+2

UCC UNIVERSITY COMPUTING

31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 117.0000+1 118.7298+1 1.0000+2 1.0611+2 1.1224+2
 11116.74 111120.00 111.3500+2 811.3718+2 1.4455+2
 211.5000+2 211.5419+2 511.5800+2 211.8600+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 117.0000+1 118.7488+1 1.0000+2 1.11.0424+2
 211.1295+2 1111.2000+2 211.3500+2 511.3808+2
 211.4694+2 1.5000+2 411.5148+2 511.5400+2 211.8600+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 117.0000+1 118.8381+1 1.0000+2 411.0255+2 211.1363+2
 1111.2000+2 211.3500+2 311.3888+2 311.4358+2 1.4903+2
 511.5000+2 511.5800+2 211.8600+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 217.0000+1 118.8930+1 311.0000+2 111.1434+2
 1111.2000+2 311.3500+2 1.3975+2 311.4130+2
 211.4688+2 511.5000+2 511.5800+2 211.8600+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 217.0000+1 218.9388+1 511.0000+2 311.1482+2
 1111.2000+2 311.3500+2 1.3952+2 311.4048+2 311.4482+2
 511.5000+2 511.5800+2 211.8600+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 217.0000+1 8.8668+1 1193.868 98.381 511.0000+2 311.1554+2
 1111.2000+2 111.3500+2 211.3773+2 211.4122+2 311.4483+2
 511.5000+2 511.5800+2 211.8600+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 217.0000+1 9.0495+1 9.8825+01 511.0000+2 211.1635+2
 1111.2000+2 511.3500+2 211.4221+2 311.4564+2
 511.5000+2 511.5800+2 211.8600+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 217.0000+1 9.1140+1 9.5327+1 511.0000+2 1.1718+2
 811.2000+2 1.3248+2 811.3500+2 211.4322+2 211.4688+2
 511.5000+2 511.5800+2 211.8600+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 217.0000+1 8.977 118.3528+1 711.0000+2 1.1828+2
 811.2000+2 211.3054+2 711.3500+2 211.4453+2 1.4603+2
 511.5000+2 511.5800+2 211.8600+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 217.0000+1 89.121 91.821 219.2947+1 711.0000+2 411.2000+2
 411.2827+2 411.3500+2 211.4808+2 511.5000+2 511.5800+2
 211.8600+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 217.0000+1 8.3840+1 119.3881+1 711.0000+2 311.2000+2
 611.2582+2 811.3500+2 111.4783+2 1.5000+2 511.5108+2
 511.5800+2 211.8600+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 117.0000+1 8.8337+1 9.4851+1 711.0000+2 1.2000+2
 1.2195+2 811.2367+2 1011.3500+2 1.4805+2 111.5000+2
 311.5285+2 511.5800+2 211.8600+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 117.0000+1 118.6805+1 9.5860+1 711.0000+2 1.2000+2
 1.2183+2 811.2325+2 1111.3500+2 1.5000+2 211.5064+2
 211.8428+2 511.5800+2 211.86+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 117.0000+1 118.5328+1 9.6812+1 411.0000+2 111.2000+2
 711.2480+2 1111.3500+2 111.5000+2 211.8228+2
 111.5597+2 511.5800+2 211.8600+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 117.0000+1 8.3823+1 2188.923 98.015 411.0000+2
 1.1749+2 311.2000+2 511.2802+2 1111.3500+2
 1.5000+2 311.5108+2 111.5882+2 511.5800+2
 211.8600+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 117.0000+1 218.2580+1 211.0000+2 111.1558+2 511.2000+2
 511.2750+2 1011.3500+2 1.4881+2 211.5000+2 311.5300+2
 511.5800+2 211.8600+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 117.0000+1 218.1255+1 211.0000+2 211.1378+2 811.2000+2
 411.2805+2 811.3500+2 211.4828+2 1.5000+2 511.5058+2
 511.5800+2 211.8600+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 117.0000+1 218.0004+1 97.00 100.00 211.0183+2
 211.1201+2 711.2000+2 311.3088+2 811.3500+2
 211.4401+2 1.4828+2 511.5000+2 511.5800+2
 211.8600+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 7.0000+1 317.5808+1 1.0000+2 211.0293+2 311.1033+2
 511.2000+2 111.3234+2 411.3500+2 211.4185+2
 211.4604+2 511.5000+2 511.5800+2 211.8600+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 7.0000+1 417.7880+1 1.0000+2 111.0429+2 811.0872+2
 1011.2000+2 1.3408+2 311.3500+2 211.3873+2
 411.4392+2 511.5000+2 511.5800+2 211.8600+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 7.0000+1 417.6559+1 1.0000+2 103.00 105.71
 811.0718+2 1111.2000+2 1.3500+2 111.3591+2
 211.3781+2 511.4185+2 511.5000+2 511.5800+2
 211.8600+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488

5**
 1.7333E+07 1.4191E+07 1.2214E+07 1.1052E+07 1.0000E+07 8.8071E+06
 8.1873E+06 7.4082E+06 7.0488E+06 6.0463E+06 4.9855E+06 4.0857E+06
 3.8788E+06 3.0119E+06 2.7253E+06 2.5924E+06 2.4680E+06
 2.3653E+06 2.3457E+06 2.2313E+06 2.1225E+06 1.9205E+06 1.8268E+06
 1.8530E+06 1.4857E+06 1.3534E+06 1.2248E+06 1.0028E+06 8.0718E+05
 0.0
 895

4R1 8R6 11R11 17R15 2R17 5R18 4R19 5R20 5R21 8R22 16R23
 4R1 8R6 11R11 17R15 2R17 5R18 4R19 5R20 5R21 8R22 16R23
 4R1 8R6 11R11 17R15 2R17 5R18 4R19 5R20 5R21 8R22 16R23
 4R1 8R6 11R11 17R15 2R17 4R18 4R19 5R20 5R21 8R22 16R23
 4R1 8R6 11R11 8R15 5R16 2R17 4R18 4R19 5R20 5R21 8R22 16R23
 4R1 8R6 5R11 7R12 17R16 2R17 4R18 4R19 5R20 5R21 8R22 16R23
 4R1 3R6 5R7 12R12 17R16 2R17 4R18 4R19 5R20 5R21 8R22 16R23
 5R1 8R7 14R12 17R16 3R17 4R18 4R19 5R20 5R21 8R22 16R23
 5R1 8R7 11R12 17R16 3R17 3R18 4R19 5R20 5R21 8R22 16R23
 5R1 7R7 11R12 17R16 2R17 3R18 4R19 5R20 5R21 8R22 16R23
 5R1 8R7 12R12 17R16 3R17 3R18 4R19 5R20 5R21 8R22 16R23
 5R1 8R7 12R12 17R16 3R17 2R18 4R19 5R20 5R21 8R22 16R23
 4R1 3R7 12R12 13R16 6R17 2R18 4R19 5R20 5R21 8R22 16R23
 4R1 8R7 12R12 7R16 10R17 4R18 4R19 5R20 5R21 8R22 16R23
 4R1 8R7 18R12 2R16 10R17 9R18 4R19 5R20 5R21 8R22 16R23
 4R1 8R7 16R12 2R13 6R17 12R18 4R19 5R20 5R21 8R22 16R23
 4R1 8R7 12R12 5R13 4R17 16R18 4R19 5R20 5R21 8R22 16R23
 4R1 7R7 8R12 9R13 2R17 17R18 4R19 5R20 5R21 8R22 16R23
 4R1 7R7 3R12 15R13 2R17 17R18 4R19 5R20 5R21 8R22 16R23
 4R1 4R7 3R6 16R13 2R17 17R18 4R19 5R20 5R21 8R22 16R23
 4R1 3R7 7R8 16R13 2R17 16R18 4R19 5R20 5R21 8R22 16R23
 5R1 7 10R8 17R13 3R17 15R18 4R19 5R20 5R21 8R22 16R23
 5R1 3 11R8 18R12 2R17 15R18 4R19 5R20 5R21 8R22 16R23
 3R1 2R3 12R12 16R13 2R17 14R18 4R19 5R20 5R21 8R22 16R23
 3R1 2R3 10R8 16R13 3R17 14R18 4R19 5R20 5R21 8R22 16R23
 3R1 3R3 10R8 16R13 3R17 13R18 4R19 5R20 5R21 8R22 16R23
 2R1 3R3 9R8 12R12 7R14 3R17 12R18 4R19 5R20 5R21 8R22 16R23
 2R1 3R3 10R8 8R13 10R14 3R17 12R18 4R19 5R20 5R21 8R22 16R23
 2R1 3R3 10R8 3R13 16R14 3R17 11R18 4R19 5R20 5R21 8R22 16R23
 2R1 3R3 7R8 2R13 18R14 3R17 11R18 4R19 5R20 5R21 8R22 16R23
 2R1 3R3 6R8 9 18R14 3R17 9R18 4R19 5R20 5R21 8R22 16R23
 2R1 3R3 4R6 4R6 19R14 2R17 8R18 4R19 5R20 5R21 8R22 16R23
 2R1 3R3 3R6 5R9 19R14 2R17 8R18 4R19 5R20 5R21 8R22 16R23

2R1 3R3 2R5 5R5 15R14 3R17 7R18 4R19 5R20 5R21 5R22 15R23		
2R1 3R3 5 7R9 15R14 3R17 7R18 4R19 5R20 5R21 5R22 15R23		
2R1 4R3 8 5R9 15R14 3R17 7R18 4R19 5R20 5R21 5R22 15R23		
2R1 4R3 8R9 17R14 5R17 5R18 4R19 5R20 5R21 5R22 15R23		
2R1 2R3 15R9 15R14 4R17 5R18 4R19 5R20 5R21 5R22 15R23		
2R1 4R3 4 15R9 12R14 5R17 10R18 4R19 5R20 5R21 5R22 15R23		
2R1 3R3 4 17R9 5R14 4R17 12R18 4R19 5R20 5R21 5R22 15R23		
2R1 3R3 2R4 15R9 5R14 4R17 14R18 4R19 5R20 5R21 5R22 15R23		
2R1 3R3 5R4 15R9 4R14 4R17 15R18 4R19 5R20 5R21 5R22 15R23		
3R1 2R3 4R4 15R9 14 4R17 15R18 4R19 5R20 5R21 5R22 15R23		
3R1 3R3 5R4 20R8 10 4R17 15R18 4R19 5R20 5R21 5R22 15R23		
3R1 3R3 5R4 20R8 10 4R17 15R18 4R19 5R20 5R21 5R22 15R23		
3R1 3 5R4 15R9 5R10 3R17 15R18 4R19 5R20 5R21 5R22 15R23		
3R1 3 5R4 10R9 5R10 3R17 15R18 4R19 5R20 5R21 5R22 15R23		
5R1 3 10R4 10R9 11R10 3R17 15R18 4R19 5R20 5R21 5R22 15R23		
5R1 2 11R4 5R9 14R10 3R17 15R18 4R19 5R20 5R21 5R22 15R23		
3R1 2 10R4 4R9 17R10 3R17 15R18 4R19 5R20 5R21 5R22 15R23		
2R1 2 10R4 9 20R10 3R17 13R18 4R19 5R20 5R21 5R22 15R23		
2R1 2R2 10R4 5 22R10 3R17 12R18 4R19 5R20 5R21 5R22 15R23		
2R1 2R2 5R4 2R5 22R10 3R17 11R18 4R19 5R20 5R21 5R22 15R23		
2R1 4R2 5R4 4R5 20R10 4R17 11R18 4R19 5R20 5R21 5R22 15R23		
2R1 3R2 3R4 5R5 17R10 4R17 13R18 4R19 5R20 5R21 5R22 15R23		
2R1 3R2 3R4 10R5 14R10 4R17 15R18 4R19 5R20 5R21 5R22 15R23		
2R1 5R2 3R4 11R5 11R10 3R17 15R18 4R19 5R20 5R21 5R22 15R23		
1 5R2 3R4 14R5 7R10 3R17 15R18 4R19 5R20 5R21 5R22 15R23		
1 5R2 2R4 20R5 5R10 3R17 20R18 4R19 5R20 5R21 5R22 15R23		
7R2 4 23R5 2R10 3R17 21R18 4R19 5R20 5R21 5R22 15R23		
555 15R25 5 17 5 17 5 17 13		
2555 25R30		
555		
1573+12 157489+10 148559+10 157515+10 255751+10 201257+10 233514+10	1	1
271491+10 255355+10 272581+10 275994+10 289715+10 218391+10 282345+10	1	2
235974+10 277721+10 277973+10 225155+10 259842+10 249305+10 244827+10	1	3
126514+10 1278+12 128024+10 855548+9 894587+9 112848+10 108085+10	1	4
917897+9 552427+8 555355+8 79592+10 739375+8 471174+9 455052+8 458219+8	1	5
417294+8 283594+8 457	1	6
2248+12 175589+10 155884+10 157447+10 22511+11 225782+10 289359+10	2	1
272332+10 233979+10 272979+10 277099+10 145993+10 275866+10 275531+10	2	2
271356+10 278726+10 211071+10 174704+10 155045+10 251035+10 244973+10	2	3
12549+11 124062+10 56272+10 104777+10 92241+9 717242+9 107845+10	2	4
100056+10 84323+8 872153+8 810294+8 39562+10 59858+10 412455+8 420511+8	2	5
431122+8 25453+10 452	2	6
18876+11 146408+10 157797+10 153322+10 265788+10 14823+11 255078+10	3	1
230495+10 244737+10 271659+10 275298+10 289909+10 234026+10 273952+10	3	2
172501+10 257335+10 231759+10 2335+12 237525+10 24331+11 242847+10	3	3
125264+10 126532+10 111111+10 102937+10 118055+10 100501+10 735711+8	3	4
102721+10 377901+8 586402+8 555585+8 890663+8 572174+8 398287+8 349403+8	3	5
433932+8 303554+8 452	3	6
229512+10 150431+10 151858+10 176355+10 255147+10 244558+10 208+13	4	1
22023+11 219952+10 270234+10 271938+10 213994+10 251257+10 149403+10	4	2
252109+10 209242+10 235481+10 217488+10 188741+10 242933+10 238618+10	4	3
123229+10 124278+10 834785+8 105954+10 114344+10 10551+11 873847+8	4	4
563453+8 911034+8 853184+8 784781+8 715749+8 850747+8 571797+8 489855+8	4	5
475231+8 292573+8 442	4	6
23562+11 191562+10 114148+10 180581+10 255003+10 150278+10 153051+10	5	1
215390+10 248226+10 267282+10 28903+11 275807+10 278378+10 275713+10	5	2
255349+10 262412+10 25378+11 244414+10 239844+10 234278+10 233662+10	5	3
120712+10 120571+10 118825+10 115184+10 110857+10 105914+10 101187+10	5	4
845972+8 897773+8 831481+8 773429+8 70827+10 83443+10 572544+8 490178+8	5	5
404815+8 237132+8 442	5	6
235355+10 12915+11 158889+10 157914+10 252824+10 248523+10 262818+10	6	1
264575+10 258922+10 264714+10 264878+10 26559+11 269428+10 269583+10	6	2
257151+10 260072+10 255197+10 247805+10 240583+10 235595+10 231914+10	6	3
231188+10 120185+10 120408+10 119001+10 115872+10 111688+10 107289+10	6	4
102012+10 558802+8 57555+8 840811+8 890155+8 525008+8 651987+8 526359+8	6	5
332475+8 413915+8 232215+8 442	6	6
184173+10 157155+10 188519+10 189892+10 250847+10 255595+10 25912+11	7	1
258805+10 252408+10 25388+11 253431+10 25052+11 253482+10 25559+11	7	2
271934+10 272518+10 240411+10 270059+10 245339+10 217635+10 233768+10	7	3
106525+10 23742+11 231447+10 118529+10 120575+10 758358+8 88759+10	7	4
11356+11 108299+10 417445+8 880729+8 538409+8 538282+8 537553+8 520883+8	7	5
55583+10 5681+10 421549+8 40751+10 274034+8 442	7	6
228804+10 188217+10 193171+10 20889+11 217574+10 257514+10 259971+10	8	1
263198+10 264427+10 224655+10 203024+10 23375+11 250558+10 25577+11	8	2
270958+10 123718+10 271612+10 231534+10 235884+10 200134+10 230459+10	8	3
217274+10 21585+11 247548+10 243949+10 234182+10 224718+10 11758+11	8	4
116428+10 889305+8 105352+10 789338+8 76655+10 852841+8 86421+10	8	5
317172+8 750356+8 67229+10 532704+8 578553+8 301419+8 35531+8 357591+8	8	6
245377+8 452	8	7
224508+10 214857+10 226001+10 224425+10 211081+10 280918+10 23483+11	9	1
207377+10 250977+10 254885+10 272043+10 282711+10 19482+11 268705+10	9	2
254017+10 218808+10 248278+10 173259+10 182085+10 230448+10 218954+10	9	3
118526+10 115322+10 771354+8 931643+8 925434+8 92541+8 911126+8	9	4
850455+8 350445+8 591841+8 554812+8 605501+8 315404+8 402573+8 421228+8	9	5
341212+8 235588+8 442	9	6
205915+10 228785+10 182474+10 180811+10 193752+10 252725+10 258424+10	10	1
213318+10 245702+10 204857+10 184432+10 261912+10 258759+10 182556+10	10	2
250719+10 287234+10 207754+10 242558+10 170057+10 157363+10 235481+10	10	3
222562+10 21191+10 113839+10 108653+10 109247+10 684782+8 589423+8	10	4
550401+8 571934+8 803277+8 748057+8 583023+8 623584+8 532787+8 436877+8	10	5
395154+8 226227+8 313889+8 208474+8 432	10	6
195243+10 194453+10 177847+10 210593+10 220118+10 283458+10 225889+10	11	1
225812+10 284935+10 254594+10 285257+10 15275+10 259935+10 205355+10	11	2
251503+10 246482+10 247454+10 245053+10 152514+10 17872+11 215975+10	11	3
204885+10 107929+10 104073+10 502055+9 893517+8 852362+8 528112+8	11	4
774193+8 805449+8 251374+8 585889+8 413577+8 385159+8 417258+8 283418+8	11	5
212385+8 245592+8 172714+8 442	11	6
152851+10 223798+10 212101+10 119203+10 153438+10 283451+10 213603+10	12	1
250585+10 243021+10 251082+10 219951+10 259435+10 19489+11 277512+10	12	2
254138+10 242675+10 24884+11 581583+8 194633+10 224058+10 219782+10	12	3
208745+10 195055+10 101817+10 555967+8 718783+8 714369+8 830648+8	12	4
532537+8 281485+8 831441+8 580126+8 502574+8 253755+8 355549+8 335877+8	12	5
283058+8 235013+8 182215+8 132822+8 432	12	6
170027+10 204177+10 22555+11 195555+10 200099+10 240546+10 240985+10	13	1
259248+10 210947+10 173126+10 190988+10 190325+10 23157+11 225238+10	13	2
211745+10 155057+10 109559+10 199483+10 182687+10 525044+8 655915+8	13	3
579428+8 836171+8 718512+8 833249+8 588781+8 505536+8 451715+8 378039+8	13	4
280038+8 206025+8 129588+8 452	13	5
182855+10 213451+10 224515+10 221351+10 201213+10 261508+10 251142+10	14	1
189984+10 23459+11 242244+10 257871+10 255435+10 245487+10 259409+10	14	2
205922+10 158293+10 101884+10 22578+11 179405+10 174125+10 185317+10	14	3
175005+10 780585+8 735588+8 565212+8 801889+8 562247+8 441311+8 314198+8	14	4
522	14	5
192445+10 204492+10 22387+11 185219+10 255524+10 252539+10 218085+10	15	1
210293+10 255955+10 247496+10 252802+10 257578+10 258042+10 21041+11	15	2
54843+10 234555+10 0 237551+10 24908+11 241511+10 215187+10 225558+10	15	3
18985+10 208417+10 187852+10 185458+10 171733+10 159455+10 619305+8	15	4
479711+8 572	15	5
182093+10 155555+10 223143+10 175005+10 233745+10 252529+10 2071+12	15	6
218553+10 253971+10 248455+10 251351+10 255148+10 102449+10 107313+10	15	7
255972+10 259541+10 180102+10 234998+10 239322+10 234214+10 228317+10	15	8
220175+10 209108+10 200188+10 190938+10 177407+10 162051+10 141905+10	15	9
582	15	10
151827+10 154488+10 158148+10 202403+10 189585+10 242784+10 259488+10	17	1
259557+10 202403+10 244885+10 249512+10 254395+10 172548+10 242472+10	17	2
251577+10 250158+10 243971+10 235204+10 227563+10 222995+10 215955+10	17	3
209257+10 200819+10 189159+10 175355+10 150154+10 134671+10 582	17	4
13107+11 231771+10 178019+10 218008+10 242029+10 211473+10 145858+10	18	1
255181+10 100324+10 245179+10 241959+10 245405+10 248556+11 25159+11	18	2

11202	11	20913	11	1971769	10	187499	10	175127	10	156553	10	129198	10	572	18	4
137264	10	192269	10	213041	10	183527	10	260614	10	230733	10	163225	10		19	1
250855	10	23826	11	241694	10	23887	11	241961	10	241317	10	241427	10		19	2
240969	10	239246	10	237895	10	236409	10	231917	10	226744	10	22382	11		19	3
202942	10	138011	10	206862	10	196434	10	104555	10	112562	10	148622	10		19	4
11481	11	572													19	5
188529	10	207891	10	222227	10	191886	10	213803	10	234024	10	247309	10		20	1
236623	10	226295	10	221706	10	220152	10	227023	10	240361	10	223721	10		20	2
195633	10	246248	10	245818	10	136553	10	183173	10	219729	10	120638	10		20	3
218158	10	174748	10	180201	10	156121	10	179057	10	13362	11	147033	10		20	4
111577	10	572													20	5
181043	10	184309	10	198734	10	182873	10	248864	10	248587	10	238113	10		21	1
220488	10	213892	10	214817	10	200062	10	157827	10	220018	10	221778	10		21	2
238217	10	244487	10	187897	10	220198	10	240698	10	149815	10	233378	10		21	3
233335	10	198009	10	217388	10	211038	10	187341	11	172502	10	189176	10		21	4
114008	10	131851	10	139374	10	10707	11	582							21	5
181414	10	212533	10	172472	10	157092	10	201029	10	203561	10	238487	10		22	1
217024	10	204318	10	210581	10	213312	10	130142	10	201959	10	188138	10		22	2
220887	10	220409	10	221503	10	237142	10	242846	10	188021	10	180528	10		22	3
206895	10	227289	10	227625	10	220924	10	172375	10	189783	10	197088	10		22	4
190597	10	118571	10	130495	10	144506	10	13544	10	103891	10	582			22	5
150381	10	219134	10	198041	10	213884	10	202265	10	222203	10	204289	10		23	1
207328	10	208964	10	111424	10	128627	10	217388	10	132933	10	186185	10		23	2
159417	10	22083	11	221008	10	238485	10	240508	10	214568	10	228591	10		23	3
135482	10	235475	10	224927	10	219944	10	154705	10	182448	10	192507	10		23	4
191127	10	189133	10	171588	10	102288	10	111991	10	129648	10	984478	9	582	23	5
189492	10	1915	12	205501	10	2204	17	21589	10	20531	11	108506	10		24	1
21171	11	213384	10	17933	11	219508	10	201703	10	204821	10	142529	10		24	2
221495	10	220068	10	220251	10	233041	10	228284	10	242302	10	184718	10		24	3
219054	10	230142	10	2259	11	21307	10	208077	10	202029	10	188335	10		24	4
184941	10	878388	8	172101	10	184944	10	111508	10	12248	11	948385	5	542	24	5
152048	10	182484	10	218043	10	200121	10	202725	10	208942	10	20985	11		25	1
135388	10	178898	10	212133	10	218111	10	217589	10	124214	10	222073	10		25	2
220328	10	212034	10	238573	10	153081	10	115998	10	240619	10	937784	8		25	3
181111	10	221363	10	181581	10	905442	9	201389	10	931051	9	148642	10		25	4
164454	10	109998	10	118919	10	118025	10	88825	9	552					25	5
175301	10	173878	10	219727	10	217187	10	188171	10	203279	10	208417	10		26	1
150618	10	204388	10	212053	10	185353	10	172072	10	217824	10	205138	10		26	2
170024	10	221465	10	231519	10	234887	10	237154	10	237705	10	216554	10		26	3
221884	10	104888	10	18944	11	206846	10	197174	10	173566	10	170334	10		26	4
183974	10	151493	10	140823	10	130087	10	117827	10	987538	9	891713	9	542	26	5
15188	11	207009	10	2178	12	178933	10	221277	10	20738	11	135804	10		27	1
213148	10	212848	10	148719	10	216027	10	22453	11	182374	10	221723	10		27	2
228301	10	231899	10	205587	10	103224	10	230279	10	223877	10	148778	10		27	3
200222	10	19788	11	187391	10	17884	11	171588	10	185887	10	159241	10		27	4
15007	11	139457	10	123463	10	106884	10	84438	10	532					27	5
123814	10	193581	10	191137	10	188087	10	204387	10	207754	10	194918	10		28	1
120495	10	214247	10	216347	10	219882	10	107217	10	227488	10	225388	10		28	2
221884	10	227142	10	228189	10	171752	10	213477	10	215491	10	209368	10		28	3
202343	10	198408	10	198221	10	191033	10	184925	10	17822	11	188193	10		28	4
158944	10	115011	10	488019	9	118284	10	91207	10	532					28	5
153748	10	195512	10	171434	10	188538	10	187132	10	208451	10	195808	10		29	1
207695	10	218837	10	218795	10	223126	10	209452	10	228217	10	993394	9		29	2
221887	10	222865	10	218283	10	214918	10	214697	10	213178	10	208749	10		29	3
202948	10	194529	10	1897	12	104813	10	824482	9	18851	11	15315	10		29	4
138899	10	12408	11	107323	10	819482	9	522							29	5
191709	10	209289	10	175222	10	220817	10	222902	10	194435	10	192538	10		30	1
178788	10	17355	11	203072	10	218482	10	21973	10	21383	10				30	2
228028	10	227142	10	221442	10	221488	10	218189	10	13718	11	188728	10		30	3
187288	10	117124	10	188203	10	187688	10	108534	10	794092	9	140441	10		30	4
573152	9	102804	10	988772	9	78284	9	522							30	5
182735	10	227371	10	175438	10	220288	10	188458	10	178908	10	177831	10		31	1
190504	10	181855	10	225189	10	225581	10	220347	10	229047	10	22908	11		31	2
230128	10	119202	10	190337	10	224622	10	188773	10	188541	10	195572	10		31	3
122855	10	180854	10	17132	11	14827	11	140746	10	144838	10	102805	10		31	4
11375	11	378238	9	703385	9	502									31	5
208043	10	214378	10	213418	10	211558	10	198539	10	218089	10	19882	11		32	1
188642	10	227693	10	232585	10	235472	10	212911	10	221909	10	227708	10		32	2
229025	10	170322	10	229064	10	228988	10	106012	10	158483	10	19754	11		32	3
185088	10	178815	10	147424	10	157268	10	148058	10	135888	10	88888	9		32	4
112173	10	713282	9	891489	9	833428	9	492							32	5
214588	10	191075	10	187894	10	178981	10	209098	10	184285	10	224452	10		33	1
228479	10	238182	10	243884	10	247278	10	124823	10	221708	10	214903	10		33	2
225378	10	180868	10	717682	9	220375	10	208685	10	193083	10	183884	10		33	3
149382	10	458836	9	149489	10	145681	10	127807	10	131207	10	122819	10		33	4
74281	9	501374	8	784072	9	883733	9	482							33	5
200882	10	241352	10	188478	10	222374	10	219485	10	219238	10	225578	10		34	1
240275	10	245378	10	130423	10	234043	10	233742	10	220488	10	221882	10		34	2
212438	10	185379	10	142938	10	115829	10	198088	10	180789	10	172209	10		34	3
183345	10	154097	10	143428	10	136181	10	892282	9	807088	9	109272	10		34	4
889388	9	849929	9	892354	9	487818	9	482							34	5
188958	10	237218	10	148248	10	223845	10	229287	10	221622	10	248542	10		35	1
254423	10	238882	10	228801	10	209088	10	140205	10	218388	10	218543	10		35	2
214788	10	212477	10	204098	10	130875	10	194514	10	183224	10	171807	10		35	3
180378	10	152212	10	13884	11	138409	10	128129	10	106718	10	102468	10		35	4
843159	9	859865	9	820599	9	48813	10	482							35	5
246857	10	248728	10	189208	10	225489	10	231481	10							

Table with 3 columns: ID, Value, and Index. Rows include data points like 255748+10, 250851+10, 743073+8, etc.

Table with 3 columns: ID, Value, and Index. Rows include data points like 813888+9, 710225+8, 582, etc.

Table with 3 columns: ID, Value, and Index. Rows include data points like 232858+10, 208058+10, 184484+10, etc.

Table with 3 columns: ID, Value, and Index. Rows include data points like 221872+10, 204887+10, 222147+10, etc.

Table with 3 columns: ID, Value, and Index. Rows include data points like 248218+10, 245139+10, 251207+10, etc.

Table with 3 columns: ID, Value, and Index. Rows include data points like 88+8, 4.075-5, 1.750-4, etc.

MFA U.C.C. NDS/BE L584 V1.6.06.2 23/06/83
16.09.51.LASER22 FROM 9Y
16.09.51.IP 00005184 WORDS - FILE INPUT , DC 04
16.09.51.LASER.P2.LASER
16.09.51.ACCOUNT,GRYTEC,9----
16.09.52.REWIND,OUTPUT
16.09.52.ROUTE,OUTPUT,DEF,TID=80
16.09.53.UCC,BANNER,DOY R-Y,CYCTO YOP,INPUT
16.09.54.COPYBR,INPUT,AA
16.09.55.COPYBR,INPUT,BB
16.09.56.REWIND,AA,BB
16.09.56.COPYBR,BB,OUTPUT
16.09.55.BEGIN,PPRINT,,I=OUTPUT,H=AA,FORM=ZUP,COP
16.09.55.IES+1
16.09.56.AT CY= 124 SN=GLOBAL
16.09.59
16.09.59. COPYRIGHT, 1981, UNIVERSITY COMPUTING C
16.09.59. MPANY
16.09.59. REPRODUCTION PROHIBITED UNLESS SPECIFIC
16.09.59. ALLY
16.09.59. AUTHORIZED BY SEPERATE WRITING.
16.09.59.
16.09.59.RETURN,ZZZZZIN,ZZZZZPO,DAYFILE,DAYFIL
16.09.59.IFE(FILE(AA,AS),M1)
16.09.59.COPYBR,AA,ZZZZZIN
16.09.59.ENDIF,M1
16.10.00.COPY,ZZZZZP1,ZZZZZIN
16.10.00.RETURN,ZZZZZP1
16.10.00.UCC,BANNERTOZZZZZIN, ,BIN,54)
16.10.04.REWIND,OUTPUT
16.10.04.COPY,OUTPUT,ZZZZZIN
16.10.04.IFE((Y.AND.(DY.RE.YKD)),DLOOP)
16.10.05.SUMMARY
16.10.05.MS 54496 WORDS (66736 MAX USED)
16.10.05.MM 300008 MAX SCH
16.10.05.CPR 1.184
16.10.05.IDR .490
16.10.05.SAU 1.874
16.10.05. DATE 09/09/83
16.10.05.DAYFIL

DOT R-θ INPUT CYCLE TO BOTTOM OF CORE

211.2857+2 311.3500+2 711.4027+2 511.5000+2 211.5500+2
 111.5185+2 1.5471+2 211.8500+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 317.0000+1 9.725+1 111.0000+2 111.0700+2 21112.8372
 118.87 211.2000+2 21125.00 21135.00 711.4048+2 511.5000+2
 211.5800+2 111.5250+2 1.5497+2 211.8500+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 117.0000+1 2187.7508 87.482 411.0000+2 11115.833 118.12
 211.2000+2 11125.00 21130.00 41135.00 811.4078+2 511.5000+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 317.0000+1 1190.7872 87.890 311.0000+2 511.2000+2 411.3500+2
 217.0000+1 1190.7872 87.891 111.0000+2 31107.0 51120.00
 411.3500+2 511.4160+2 511.5000+2 311.5500+2 111.5377+2
 211.5800+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 217.0000+1 1191.2007 88.258 111.0000+2 11105.557 21120.00
 21130.00 51135.00 511.4184+2 511.5000+2 411.5800+2
 111.6378+2 1.6600+2 211.8568+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 217.0000+1 1191.4162 88.558 111.0000+2 21105.00 51120.00
 511.3500+2 511.4236+2 511.5000+2 411.5800+2 111.6426+2
 1.6500+2 111.6717+02
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 317.0000+1 211.0000+2 111.2000+2 11127.00 11132.00 51135.00
 511.4274+2 511.5000+2 1.6500+2 411.5815+2 1.6500+2
 111.6752+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 217.0000+1 211.0000+2 1115.00 120.00 511.2105+2 511.3500+2
 511.4305+2 1.5000+2 411.5135+2 411.5800+2 1.6477+2
 211.8500+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 317.0000+1 211.0000+2 1115.00 120.00 1011.2127+2 511.3500+2
 111.4322+2 211.4898+2 511.5000+2 1.5800+2 511.8891+2
 211.8500+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 317.0000+1 211.0000+2 111.1500+2 1.2000+2 1011.2148+2
 411.3500+2 111.4121+2 411.4357+2 211.5000+2 211.6372+2
 511.5800+2 211.8500+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 317.0000+1 211.0000+2 1115.00 120.00 511.2170+2 111.3500+2
 411.3888+2 311.4382+2 1.4909+2 511.5000+2 511.5800+2
 211.8500+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 317.0000+1 211.0000+2 1115.00 11120.00 711.2182+2
 111.3258+2 511.3500+2 111.4410+2 111.4704+2 511.5000+2
 511.5800+2 211.8500+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 317.0000+1 211.0000+2 1115.00 111.2000+2 211.2232+2
 511.2843+2 711.3500+2 111.4458+2 111.4752+2 511.5000+2
 511.5800+2 211.8500+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 317.0000+1 211.0000+2 115.00 1.1887+2 111.2000+2
 911.2281+2 711.3500+2 111.4525+2 111.4822+2 511.5000+2
 511.5800+2 211.8500+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 317.0000+1 211.0000+2 311.1130+2 211.2000+2 511.2358+2
 511.3500+2 111.4804+2 1.4803+2 511.5000+2 511.5800+2
 211.8500+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 217.0000+1 1192.25 1+2 1.0189+2 511.0491+2 311.2000+2
 711.2429+2 511.3500+2 211.4689+2 51150 511.5800+2 211.8500+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 217.0000+1 1192.25 100.00 511.0228+2 311.2000+2 711.2489+2
 511.3500+2 111.4771+2 1.5000+2 511.5073+2 511.5800+2 211.8500+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 217.0000+1 9.5155+1 1.0000+2 511.0281+2 411.2000+2
 511.2585+2 101135 1.4850+2 1.5000+2 411.5184+2
 511.5800+2 211.8500+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 217.0000+1 9.1888+1 1.0000+2 511.0335+2 211.2000+2
 511.2635+2 1011.3500+2 1.4933+2 111.5000+2 411.6238+02
 511.5800+2 211.8500+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 217.0000+1 118.8408+1 1.0000+2 511.0383+2 211.2000+2
 511.2703+2 511.3500+2 111.4735+2 1.5000+2 211.5012+2
 311.5319+2 511.5800+2 211.8500+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 117.0000+1 118.5568+1 1.0000+2 511.0445+2 211.2000+2
 511.2767+2 511.3500+2 511.4278+2 1.5000+2 211.5088+2
 211.5395+2 511.5800+2 211.8500+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 117.0000+1 118.3108+1 1.0000+2 511.0500+2 311.2000+2
 411.2833+2 211.3500+2 511.3851+2 1.5000+2 211.5167+2
 211.5477+2 511.5800+2 211.8500+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 117.0000+1 118.2077+1 1.0000+2 511.0553+2 311.2000+2
 211.2888+2 1111.3500+2 111.5000+2 211.5243+2 111.5555+2
 511.5800+2 211.8500+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 117.0000+1 118.2472+1 1.0000+2 211.0604+2 211.2000+2
 126.00 11129.5 211.3148+2 1111.3500+2 211.5000+2 211.5318+2
 111.5229+2 511.5800+2 211.8500+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 117.0000+1 118.2955+1 1.0000+2 211.0671+2 211.2000+2
 1.2755+2 311.3042+2 1111.3500+2 211.5000+2 211.5473+2
 511.5800+2 211.8500+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 117.0000+1 118.3552+1 1.0000+2 211.0756+2 1.2000+2
 311.2312+2 211.3147+2 1111.3500+2 311.5000+2 111.5537+2
 511.5800+2 211.8500+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 117.0000+1 118.4243+1 1.0000+2 111.0831+2 117.31
 41120.00 111.3228+2 1111.3500+2 411.5000+2 1.5645+2
 1.5800+2 411.5855+2 211.8500+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 117.0000+1 118.4725+1 1.0000+2 111.0893+2 1.1707+2
 411.2000+2 1.3314+2 1111.3500+2 511.5000+2 1.5736+2
 111.5800+2 311.6057+2 211.8500+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 117.0000+1 118.5225+1 1.0000+2 1.0858+2 1.1459+2
 511.2000+2 1.3393+2 1111.3500+2 511.5000+2 211.5800+2
 311.6151+2 211.8500+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 117.0000+1 118.5646+1 111.0000+2 1.1012+2 111.1285+2
 11.2000+2 1111.3500+2 511.5000+2 311.5800+2 211.6231+2
 211.8500+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 117.0000+1 118.5958+1 111.0000+2 111.1130+2 511.2000+2
 1111.3500+2 411.5000+2 111.5522+2 211.5800+2 211.5174+2
 211.8500+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 117.0000+1 118.6278+1 111.0000+2 111.1083+2 1111.2000+2
 1111.3500+2 211.5000+2 211.5395+2 1.5800+2 411.5879+2
 211.8500+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 117.0000+1 118.6743+1 111.0000+2 1.0817+2 111.1151+2
 1111.2000+2 1.3500+2 1011.3530+2 1.5000+2 411.5144+2

UCC UNIVERSITY COMPUTING

117.0000+1 118.7288+1 1.0000+2 1.0611+2 1.1224+2
 1115.74 11120.00 111.3500+2 611.3718+2 1.4858+2
 211.5000+2 211.5419+2 511.5800+2 211.6800+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 117.0000+1 118.7848+1 1.0000+2 111.0428+2
 211.1285+2 1111.2000+2 211.3500+2 511.3805+2
 211.4594+2 1.5000+2 411.9148+2 511.5800+2 211.6800+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 117.0000+1 118.8381+1 1.0000+2 411.0255+2 211.1383+2
 1111.2000+2 211.3500+2 311.3888+2 311.4358+2 1.4903+2
 511.5000+2 511.5800+2 211.6800+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 217.0000+1 118.8920+1 311.0000+2 111.1434+2
 1111.2000+2 311.3500+2 1.3975+2 311.4130+2
 211.4886+2 511.5000+2 511.5800+2 211.6800+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 217.0000+1 218.9388+1 511.0000+2 311.1492+2
 1111.2000+2 311.3500+2 1.3952+2 311.4046+2 311.4482+2
 511.5000+2 511.5800+2 211.6800+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 217.0000+1 8.9888+1 1183.888 98.381 511.0000+2 311.1854+2
 1111.2000+2 111.3500+2 211.3773+2 211.4122+2 311.4483+2
 511.5000+2 511.5800+2 211.6800+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 217.0000+1 9.0488+1 9.8825+01 811.0000+2 211.1835+2
 1111.2000+2 511.3500+2 211.4221+2 311.4564+2
 511.5000+2 511.5800+2 211.6800+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 217.0000+1 9.1148+1 9.5327+1 811.0000+2 1.1718+2
 811.2000+2 1.3348+2 611.3500+2 211.4322+2 211.4868+2
 511.5000+2 511.5800+2 211.6800+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 317.0000+1 88.977 91.977 119.3528+1 711.0000+2 1.1828+2
 811.2000+2 211.3084+2 711.3500+2 211.4453+2 1.4803+2
 511.5000+2 511.5800+2 211.6800+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 317.0000+1 89.121 91.821 219.2947+1 711.0000+2 411.2000+2
 411.2827+2 811.3500+2 211.4608+2 511.5000+2 511.5800+2
 211.6800+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 217.0000+1 8.9940+1 119.3881+1 711.0000+2 311.2000+2
 611.2582+2 811.3500+2 111.4783+2 1.5000+2 511.9109+2
 511.5800+2 211.6800+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 117.0000+1 8.8337+1 9.4851+1 711.0000+2 1.2000+2
 1.2185+2 811.2387+2 1011.3500+2 1.4805+2 111.5000+2
 311.5285+2 511.5800+2 211.6800+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 117.0000+1 118.8805+1 9.5880+1 711.0000+2 1.2000+2
 1.2153+2 811.2325+2 1111.3500+2 1.5000+2 211.5084+2
 211.5428+2 511.5800+2 211.88+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 117.0000+1 118.9338+1 9.6912+1 411.0000+2 111.2000+2
 711.2480+2 1111.3500+2 111.5000+2 211.5229+2
 111.5997+2 511.5800+2 211.6800+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 117.0000+1 8.3923+1 2188.823 98.015 411.0000+2
 11789+2 211.2000+2 811.2802+2 1111.3800+2
 1.5000+2 311.5106+2 111.5882+2 511.5800+2
 211.6800+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 117.0000+1 218.2580+1 211.0000+2 111.1584+2 511.2000+2
 511.2750+2 1011.3500+2 1.4881+2 211.5000+2 311.5300+2
 511.5800+2 211.6800+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 117.0000+1 218.1258+1 211.0000+2 211.1378+2 611.2000+2
 411.2805+2 811.3500+2 211.4828+2 1.5000+2 511.5058+2
 511.5800+2 211.6800+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 117.0000+1 218.0004+1 97.00 100.00 211.0183+2
 211.1201+2 711.2000+2 311.3088+2 611.3500+2
 211.4401+2 1.4828+2 511.5000+2 511.5800+2
 211.6800+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 7.0000+1 317.8808+1 1.0000+2 211.0293+2 311.1033+2
 911.2000+2 111.3234+2 411.3500+2 211.4185+2
 211.4804+2 511.5000+2 511.5800+2 211.6800+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 7.0000+1 417.7880+1 1.0000+2 111.0429+2 611.0872+2
 1011.2000+2 1.3409+2 311.3500+2 211.3975+2
 411.4392+2 511.5000+2 511.5800+2 211.6800+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488
 7.0000+1 417.8588+1 1.0000+2 103.00 106.71
 911.0718+2 1111.2000+2 1.3500+2 111.3581+2
 211.3781+2 511.4184+2 511.5000+2 511.5800+2
 211.6800+2
 31170.021 41175.182 41181.134 71187.959 151197.485 217.488

S**
 1.7333E+07 1.4191E+07 1.2214E+07 1.1052E+07 1.0000E+07 8.8071E+06
 8.1873E+06 7.4082E+06 7.0488E+06 6.0853E+06 4.9889E+06 4.0657E+06
 3.8788E+06 3.0119E+06 2.7253E+06 2.5824E+06 2.4880E+06
 2.3853E+06 2.3457E+06 2.2313E+06 2.1225E+06 1.9205E+06 1.8288E+06
 1.8630E+06 1.4857E+06 1.3534E+06 1.2248E+06 1.0026E+06 9.0718E+05
 0.0
 835

4R1 8R6 11R11 17R15 2R17 5R18 4R19 5R20 5R21 8R22 18R23
 4R1 8R6 11R11 17R15 2R17 5R18 4R19 5R20 5R21 8R22 18R23
 4R1 8R6 11R11 17R15 2R17 5R18 4R19 5R20 5R21 8R22 18R23
 4R1 8R6 11R11 17R15 2R17 4R18 4R19 5R20 5R21 8R22 18R23
 4R1 8R6 11R11 8R15 8R16 2R17 4R18 4R19 5R20 5R21 8R22 18R23
 4R1 8R6 5R11 7R12 17R16 2R17 4R18 4R19 5R20 5R21 8R22 18R23
 4R1 3R6 5R7 12R12 17R16 2R17 4R18 4R19 5R20 5R21 8R22 18R23
 5R1 8R7 14R12 17R18 3R17 4R18 4R19 5R20 5R21 8R22 18R23
 5R1 8R7 11R12 17R18 3R17 3R18 4R19 5R20 5R21 8R22 18R23
 5R1 7R7 11R12 17R16 2R17 3R18 4R19 5R20 5R21 8R22 18R23
 5R1 8R7 12R12 17R18 3R17 3R18 4R19 5R20 5R21 8R22 18R23
 5R1 8R7 12R12 17R18 3R17 2R18 4R19 5R20 5R21 8R22 18R23
 4R1 3R7 12R12 13R16 3R17 2R18 4R19 5R20 5R21 8R22 18R23
 4R1 8R7 12R12 7R18 10R17 4R18 4R19 5R20 5R21 8R22 18R23
 4R1 8R7 18R12 2R18 10R17 9R18 4R19 5R20 5R21 8R22 18R23
 4R1 8R7 12R12 2R18 3R17 12R18 4R19 5R20 5R21 8R22 18R23
 4R1 8R7 12R12 5R13 4R17 18R18 4R19 5R20 5R21 8R22 18R23
 4R1 7R7 8R12 9R13 2R17 17R18 4R19 5R20 5R21 8R22 18R23
 4R1 7R7 3R12 15R13 2R17 17R18 4R19 5R20 5R21 8R22 18R23
 4R1 4R7 3R8 18R13 2R17 17R18 4R19 5R20 5R21 8R22 18R23
 4R1 3R7 7R8 18R13 2R17 16R18 4R19 5R20 5R21 8R22 18R23
 5R1 7 10R8 17R13 3R17 15R18 4R19 5R20 5R21 8R22 18R23
 5R1 3 11R8 18R13 3R17 15R18 4R19 5R20 5R21 8R22 18R23
 3R1 2R3 12R8 18R13 2R17 14R18 4R19 5R20 5R21 8R22 18R23
 3R1 2R3 10R8 18R13 3R17 14R18 4R19 5R20 5R21 8R22 18R23
 3R1 3R3 10R8 18R13 3R14 3R17 13R18 4R19 5R20 5R21 8R22 18R23
 2R1 3R3 9R8 12R13 7R14 3R17 12R18 4R19 5R20 5R21 8R22 18R23
 2R1 3R3 10R8 8R13 10R14 3R17 12R18 4R19 5R20 5R21 8R22 18R23
 2R1 3R3 10R8 3R13 14R14 3R17 11R18 4R19 5R20 5R21 8R22 18R23
 2R1 3R3 7R8 2R13 18R14 3R17 11R18 4R19 5R20 5R21 8R22 18R23
 2R1 3R3 6R8 9 18R14 3R17 5R18 4R19 5R20 5R21 8R22 18R23
 2R1 3R3 4R8 4R8 18R14 2R17 9R18 4R19 5R20 5R21 8R22 18R23
 2R1 3R3 3R8 5R8 18R14 2R17 8R18 4R19 5R20 5R21 8R22 18R23

2R1 3R1 2R2 3R2 1R14 2R17 3R18 4R19 5R20 6R21 8R22 16R23
2R1 3R2 4 7R9 1R14 3R17 7R18 4R19 5R20 6R21 8R22 16R23
2R1 4R2 8 5R9 1R14 4R17 5R18 4R19 5R20 6R21 8R22 16R23
2R1 4R2 8R3 17R14 5R17 5R18 4R19 5R20 6R21 8R22 16R23
2R1 2R2 15R9 1R14 4R17 5R18 4R19 5R20 6R21 8R22 16R23
2R1 4R2 4 15R9 12R14 5R17 10R18 4R19 5R20 6R21 8R22 16R23
2R1 3R1 4 17R9 5R14 4R17 12R18 4R19 5R20 6R21 8R22 16R23
2R1 3R2 2R4 15R9 5R14 4R17 14R18 4R19 5R20 6R21 8R22 16R23
2R1 3R2 5R4 15R9 4R14 4R17 15R18 4R19 5R20 6R21 8R22 16R23
3R1 2R2 4R4 15R9 14 4R17 15R18 4R19 5R20 6R21 8R22 16R23
3R1 3R2 5R4 20R9 10 4R17 15R18 4R19 5R20 6R21 8R22 16R23
3R1 3R2 5R4 20R9 10 4R17 15R18 4R19 5R20 6R21 8R22 16R23
3R1 3 4R4 15R9 5R10 3R17 15R18 4R19 5R20 6R21 8R22 16R23
3R1 3 4R4 10R9 5R10 3R17 15R18 4R19 5R20 6R21 8R22 16R23
5R1 3 10R4 10R9 11R10 3R17 15R18 4R19 5R20 6R21 8R22 16R23
5R1 2 11R4 5R5 14R10 3R17 15R18 4R19 5R20 6R21 8R22 16R23
3R1 2 10R4 4R5 17R10 3R17 15R18 4R19 5R20 6R21 8R22 16R23
2R1 2 10R4 9 20R10 3R17 13R18 4R19 5R20 6R21 8R22 16R23
2R1 2R2 10R4 5 22R10 3R17 12R18 4R19 5R20 6R21 8R22 16R23
2R1 2R2 5R4 2R5 22R10 3R17 11R18 4R19 5R20 6R21 8R22 16R23
2R1 4R2 5R4 4R5 20R10 4R17 11R18 4R19 5R20 6R21 8R22 16R23
2R1 3R2 3R4 5R5 17R10 4R17 13R18 4R19 5R20 6R21 8R22 16R23
2R1 3R2 3R4 10R5 14R10 4R17 15R18 4R19 5R20 6R21 8R22 16R23
2R1 5R2 3R4 11R5 11R10 3R17 15R18 4R19 5R20 6R21 8R22 16R23
1 5R2 3R4 14R5 7R10 3R17 15R18 4R19 5R20 6R21 8R22 16R23
1 5R2 2R4 20R5 5R10 3R17 20R18 4R19 5R20 6R21 8R22 16R23
1 7R2 4 23R5 2R10 3R17 21R18 4R19 5R20 6R21 8R22 16R23
5R5 16R25 9 17 9 17 9 17 13
20R5 28R20
969*
594738+9 508208+9 451557+9 500373+9 740133+9 573859+9 558982+9 745947+9 1 1
585584+9 714214+9 597637+9 719837+9 519432+9 554586+9 522522+9 588204+9 1 2
398551+9 420761+9 477527+9 457017+9 450375+9 522 1 3
889362+9 532883+9 563484+9 500358+10 848553+9 843855+9 74871+10 748744+9 2 1
629189+9 715557+9 701185+9 371705+9 57572+9 847814+9 588551+9 579299+9 2 2
407157+9 326811+9 30135+10 480452+9 450783+9 522 2 3
571709+9 441114+9 567162+9 457895+9 734289+9 624103+9 728994+9 839921+9 3 1
557345+9 71258+10 897575+9 720537+9 554805+9 840052+9 375087+9 80863+10 3 2
427504+9 410833+9 414804+9 455051+9 451785+9 522 3 3
893617+9 488797+9 457978+9 527006+9 73855+10 888834+9 580313+9 807443+9 4 1
593649+9 709756+9 691529+9 538447+9 804837+9 350195+9 634723+9 448087+9 4 2
463731+9 411689+9 350359+9 450597+9 455704+9 517 4 3
710262+9 581222+9 344731+9 480204+9 738647+9 456779+9 514342+9 589084+9 5 1
573206+9 702842+9 582522+9 589778+9 678751+9 850012+9 605732+9 588506+9 5 2
508378+9 465206+9 448368+9 437276+9 450912+9 517 5 3
712146+9 392037+9 479848+9 502251+9 730788+9 711617+9 739888+9 731678+9 5 1
720698+9 588888+9 575551+9 668926+9 661374+9 643152+9 617503+9 578123+9 6 2
542347+9 488509+9 453756+9 445443+9 434854+9 448971+9 517 6 3
555574+9 807391+9 570151+9 583309+9 725725+9 732423+9 733388+9 726151+9 7 1
722121+9 715088+9 704717+9 658934+9 674854+9 874185+9 67848+10 866889+9 7 2
573697+9 617733+9 536726+9 442345+9 452689+9 20139+10 446745+9 450466+9 7 3
812 7 4
689789+9 8718+11 585471+9 625834+9 854804+9 748271+9 747555+9 748850+9 8 1
742838+9 52797+9 624805+9 589067+9 844227+9 582055+9 31345+10 8 2
682983+9 561573+9 555472+9 442234+9 48554+10 444058+9 370968+9 461482+9 8 3
461475+9 447775+9 431113+9 522 8 4
57379+10 855295+9 588482+9 679536+9 635618+9 756727+9 67486+10 664712+9 8 1
692358+9 792285+9 598901+9 705904+9 473110 821171+9 55283+10 481331+9 8 2
485147+9 342123+9 353334+9 447655+9 427922+9 812 8 3
53724+9 493352+9 555948+9 574197+9 523647+9 782964+9 74591+9 523088+9 10 1
892785+9 570045+9 504981+9 888808+9 893716+9 480857+9 890891+9 834784+9 10 2
488557+9 506397+9 328531+9 335879+9 466395+9 43895+10 420335+9 807 10 3
500773+9 194543+9 140422+9 335755+9 525787+9 483488+9 588386+9 538611+9 11 1
745019+9 893845+9 688958+9 488878+9 525787+9 483488+9 588386+9 538611+9 11 2
523333+9 507822+9 311184+9 358884+9 432530+9 517 11 3
501271+9 684213+9 645141+9 361167+9 235710 787351+9 619783+9 72252+10 12 1
693113+9 728905+9 588257+9 682310+9 502723+9 701402+9 888555+9 890518+9 12 2
555098+9 129035+9 403007+9 457028+9 450127+9 425075+9 400407+9 502 12 3
523486+9 524217+9 690137+9 588854+9 578232+9 581853+9 55192+10 684038+9 13 1
542587+9 431285+9 455849+9 441113+9 532518+9 500847+9 439897+9 338377+9 13 2
228242+9 419089+9 384415+9 592 13 3
593855+9 652858+9 654706+9 667025+9 684393+9 74852+10 735032+9 528849+9 14 1
54127+10 675404+9 679542+9 898858+9 618544+9 849582+9 589921+9 14 2
228555+9 503181+9 384272+9 378855+9 402308+9 384803+9 592 14 3
582853+9 625477+9 58285+10 582229+9 774553+9 763076+9 618524+9 83369+10 15 1
70292+10 87258+10 671301+9 800342+9 670506+9 838988+9 850871+9 600221+9 15 2
0 58939+10 808745+9 582787+9 513015+9 530842+9 501727+9 488755+9 15 3
439353+9 409941+9 362877+9 364557+9 592 15 4
591819+9 588014+9 580908+9 533202+9 678414+9 754481+9 588641+9 808001+9 18 1
8999+11 670886+9 668956+9 678142+9 271198+9 278644+9 688726+9 885104+9 18 2
457742+9 589313+9 591841+9 571146+9 550094+9 523602+9 58529+9 685427+9 18 3
431843+9 399298+9 367002+9 328526+9 582 18 4
488522+9 585045+9 598405+9 613528+9 55189+10 898142+9 734328+9 72541+10 17 1
558446+9 670247+9 655833+9 874701+9 455837+9 63678+10 651383+9 840755+9 17 2
618419+9 590141+9 594773+9 844325+9 518147+9 500288+9 478389+9 460436+9 17 3
404410+9 365928+9 311821+9 582 17 4
703817+9 709117+9 543064+9 839341+9 704851+9 608293+9 415603+9 718208+9 18 1
278748+9 57259+10 882535+9 857899+9 881528+9 84842+9 850907+9 834615+9 18 2
518478+9 803233+9 581795+9 58374+10 541054+9 515507+9 494839+9 470641+9 18 3
442914+9 405853+9 352755+9 29741+9 572 18 4
422033+9 590371+9 850549+9 588319+9 76025+10 888305+9 45804+10 706803+9 18 1
658488+9 888889+9 857245+9 852463+9 647092+9 843458+9 83745+10 828829+9 19 2
622295+9 515158+9 59735+10 578091+9 566718+9 508517+9 330183+9 509642+9 19 3
477775+9 252342+9 268244+9 353770+9 257515+9 577 19 4
58424+10 838885+9 57898+10 582243+9 826868+9 678198+9 707882+9 887115+9 20 1
629705+9 61252+10 804125+9 64544+10 552341+9 604859+9 528088+9 680248+9 20 2
554821+9 36123+10 481252+9 576133+9 31175+10 562743+9 448851+9 40603+10 20 3
395723+9 448508+9 329029+9 389738+9 267864+9 572 20 4
468875+9 585323+9 807522+9 55693+10 735988+9 72533+10 682571+9 629758+9 21 1
605182+9 604386+9 559522+9 438406+9 610497+9 612909+9 655763+9 570375+9 21 2
459914+9 59869+10 852758+9 402837+9 626128+9 624048+9 526088+9 575284+9 21 3
553455+9 489787+9 448018+9 488474+9 294585+9 337098+9 352134+9 268439+9 21 4
552 21 5
559449+9 551844+9 527344+9 479479+9 612414+9 618253+9 683037+9 63001+10 22 1
500134+9 603895+9 808496+9 388854+9 57023+10 472588+9 617929+9 618046+9 22 2
577143+9 562533+9 671657+9 518414+9 495202+9 658253+9 520925+9 618558+9 22 3
597416+9 46342+10 508792+9 525967+9 506986+9 315718+9 34509+10 37688+10 22 4
353101+9 267943+9 562 22 5
483751+9 672559+9 606137+9 653035+9 616305+9 588729+9 594232+9 501659+9 23 1
607168+9 320438+9 358947+9 620251+9 738661+9 526858+9 449106+9 621415+9 23 2
620354+9 599025+9 671265+9 598173+9 630112+9 377259+9 55057+10 619547+9 23 3
504242+9 424812+9 483357+9 541319+9 518225+9 603699+9 463355+9 277046+9 23 4
304795+9 345767+9 260585+9 562 23 5
584633+9 587868+9 629336+9 655815+9 648764+9 588762+9 315671+9 613598+9 24 1
516122+9 516557+9 617585+9 576006+9 582095+9 405774+9 627461+9 622966+9 24 2
2215+9 588514+9 664678+9 678924+9 546113+9 612413+9 641978+9 616416+9 24 3
933454+9 676524+9 558322+9 542699+9 42746+10 242483+9 471764+9 397753+9 24 4
703633+9 732559+9 255323+9 542 24 5
458923+9 511859+9 852297+9 586204+9 801385+9 601497+9 610511+9 38350+10 25 1
517988+9 612781+9 815279+9 624485+9 354837+9 633473+9 626523+9 588328+9 25 2
5893+10 432841+9 327485+9 678689+9 26324+10 508335+9 621387+9 508534+9 25 3
25275+10 562768+9 25873+10 416828+9 457261+9 305888+9 329443+9 32047+10 25 4
244104+9 582 25 5
542052+9 638821+9 674245+9 648709+9 494934+9 603859+9 603872+9 438585+9 26 1
595036+9 61624+10 58507+10 497165+9 627185+9 590001+9 486989+9 633283+9 26 2
860295+9 86878+10 746529+9 575129+9 614577+9 628604+9 307678+9 663328+9 26 3
803186+9 55827+10 489074+9 478296+9 450847+9 425705+9 391095+9 355162+9 26 4
313765+9 249488+9 153633+9 542 26 5
467677+9 636727+9 651005+9 527032+9 558018+9 60737+10 386358+9 621492+9 27 1

Table with multiple columns of numerical data, organized in rows and columns. Includes a vertical label 'UNIVERSITY COMPUTING COMPANY' on the left side.

UNIVERSITY COMPUTING COMPANY

***** CYBER PAGE PRINT - END OF JOB LASERIE
***** CYBER PAGE PRINT - END OF JOB LASERIE
***** CYBER PAGE PRINT - END OF JOB LASERIE
***** CYBER PAGE PRINT - END OF JOB LASERIE
***** CYBER PAGE PRINT - END OF JOB LASERIE
***** CYBER PAGE PRINT - END OF JOB LASERIE
***** CYBER PAGE PRINT - END OF JOB LASERIE
***** CYBER PAGE PRINT - END OF JOB LASERIE
***** CYBER PAGE PRINT - END OF JOB LASERIE
***** CYBER PAGE PRINT - END OF JOB LASERIE

ANISN-W INPUT CYCLE TO TOP OF CORE

0	0	0	0	0	0
0	0	0	0	0	0
0	0	0	0	0	0
13020E-02	10271E-02	10215E-02	10252E-02	12285E-02	12370E-02
12370E-02	12532E-02	12826E-02	12826E-02	13183E-02	13163E-02
13163E-02	13183E-02	13183E-02	13640E-02	13640E-02	46189E-03
46189E-03	46189E-03	46189E-03	46189E-03	55174E-03	55174E-03
55174E-03	55174E-03	55174E-03	55174E-03	55174E-03	55174E-03
55131E-03	55131E-03	55131E-03	0	0	0
0	0	0	0	0	0
0	0	0	0	0	0
0	0	0	0	0	0
0	0	0	0	0	0
0	0	0	0	0	0
0	0	0	0	0	0
0	0	0	0	0	0
23535E-02	18555E-02	18455E-02	18532E-02	22205E-02	22380E-02
22350E-02	22832E-02	23185E-02	23185E-02	23783E-02	23783E-02
23783E-02	23783E-02	23783E-02	24856E-02	24856E-02	83489E-03
83489E-03	83489E-03	83489E-03	83489E-03	89731E-03	89731E-03
89731E-03	89731E-03	89731E-03	89731E-03	89731E-03	89731E-03
89853E-03	89853E-03	89853E-03	0	0	0
0	0	0	0	0	0
0	0	0	0	0	0
0	0	0	0	0	0
0	0	0	0	0	0
0	0	0	0	0	0

J== FO.
T
L== FO.
A== 3170. 21100. 41115. 41130. 151140.895 21182.360 31185.217
31170.021 41175.152 41181.134
71187.858 151187.455 217.455
S== F1.
S== O.2R0.0604938
O ARC.0453704
O O.0453704 O.0452982 O.0453704 1M3
O O.0604928 O.0453704 1M2 1M4
7== .3085057 - .2182178 1M1
- 5172134 - .5773503 - .2182178 1M2
- 8184885 - .7857958 - .5773503 - .2182178 1M3
- 8759 - .8511897 - .7857958 - .5773503 - .2182178 1M4
885 17R1 18R2 3R3 4R4 4R5 5R6 5R7 5R8 18R9
935 29 33 9 21 8 21 9 21 17
1955 F3
T

MFA U.C.C. NOS/BE L864 V1.6.05.2 23/08/83
15.20.05.LASER18 FROM BV
15.20.06.IP 00003008 WORDS - FILE INPUT , DC 04
15.20.06.LASER,P2.LASER
15.20.07.ACCOUNT,CKYTEL,-----
15.20.08.REWIND,OUTPUT
15.20.08.ROUTE,OUTPUT,DEF.TID*8D.
15.20.08.UCC,BANNER,ANISNW,CYC10 YDP,INPUT
15.20.10.COPYBR,INPUT,AA
15.20.10.COPYBR,INPUT,BB
15.20.10.REWIND,AA,BB
15.20.10.COPYSBF,BB,OUTPUT
15.20.11.BEGIN,PPRINT,,I=OUTPUT,H=AA,FORM*2UP,CDF
15.20.11.IES*1
15.20.12.AT CY= 124 SN*GLOBAL
15.20.14
15.20.14.COPYRIGHT, 1981, UNIVERSITY COMPUTING C
15.20.14.OMPANY
15.20.14.REPRODUCTION PROHIBITED UNLESS SPECIFIC
15.20.14.ALLY
15.20.14.AUTHORIZED BY SEPERATE WRITING.
15.20.14
15.20.14.RETURN,ZZZZZIN,ZZZZZPD,DAYFILE,DAYFIL
15.20.15.IFE(FILE(AA,AS),M1)
15.20.15.COPYBR,AA,ZZZZZIN
15.20.15.ENDIF,M1
15.20.15.COPY,ZZZZZP1,ZZZZZIN
15.20.15.RETURN,ZZZZZP1
15.20.15.UCC,BANNER(I=ZZZZZIN,.BIN,54)
15.20.25.REWIND,OUTPUT
15.20.25.COPY,OUTPUT,ZZZZZIN
15.20.25.IFE((Y.AND.(BY.NE.YXD)).DLODP)
15.20.25.SUMMARY
15.20.25.MS 54848 WORDS (65088 MAX USED)
15.20.25.MM 305008 MAX SCM
15.20.25.CPR 1.153
15.20.25.IOR .464
15.20.25.SRU 1.518
15.20.25. DATE 08/09/83
15.20.29.DAYFIL

UCC UNIVERSITY COMPUTING CENTER ANY

***** CYBER PAGE PRINT - END OF JOB LASER18
***** CYBER PAGE PRINT - END OF JOB LASER18
***** CYBER PAGE PRINT - END OF JOB LASER18
***** CYBER PAGE PRINT - END OF JOB LASER18
***** CYBER PAGE PRINT - END OF JOB LASER18
***** CYBER PAGE PRINT - END OF JOB LASER18
***** CYBER PAGE PRINT - END OF JOB LASER18
***** CYBER PAGE PRINT - END OF JOB LASER18
***** CYBER PAGE PRINT - END OF JOB LASER18
***** CYBER PAGE PRINT - END OF JOB LASER18
***** CYBER PAGE PRINT - END OF JOB LASER18
***** CYBER PAGE PRINT - END OF JOB LASER18
***** CYBER PAGE PRINT - END OF JOB LASER18
***** CYBER PAGE PRINT - END OF JOB LASER18
***** CYBER PAGE PRINT - END OF JOB LASER18

ANISN-W INPUT CYCLE 10 BOTTOM OF CORE

***** 55 55 ***** 55 55 55 55
***** 55 55 ***** 55 55 55 55
55 55 55 55 55 55 55 55 55 55
55 55 55 55 55 55 55 55 55 55
***** 55 55 ***** 55 55 55 55
***** 55 55 ***** 55 55 55 55
55 55 55 55 55 55 55 55 55 55
55 55 55 55 55 55 55 55 55 55
***** 55 55 ***** 55 55 55 55
***** 55 55 ***** 55 55 55 55

***** 55 55 ***** 55 55 55 55
***** 55 55 ***** 55 55 55 55
55 55 55 55 55 55 55 55 55 55
55 55 55 55 55 55 55 55 55 55
***** 55 55 ***** 55 55 55 55
***** 55 55 ***** 55 55 55 55
55 55 55 55 55 55 55 55 55 55
55 55 55 55 55 55 55 55 55 55
***** 55 55 ***** 55 55 55 55
***** 55 55 ***** 55 55 55 55

***** 55 55 ***** 55 55 55 55
***** 55 55 ***** 55 55 55 55
55 55 55 55 55 55 55 55 55 55
55 55 55 55 55 55 55 55 55 55
***** 55 55 ***** 55 55 55 55
***** 55 55 ***** 55 55 55 55
55 55 55 55 55 55 55 55 55 55
55 55 55 55 55 55 55 55 55 55
***** 55 55 ***** 55 55 55 55
***** 55 55 ***** 55 55 55 55

88500
1-0 RADIAL HS ROBINSON MODEL - CYCLE 10 BOTTOM
1599 1 0 3 8 2 1 0 9 78 0 27 5 6 32 2R0 2R124 22
1 0 0 20 2 1 22 1 1 32 1 1 0
1599 22 1 4 1 42088 52 5 2 4 1 22
1799

40880E-08 30841E-08 31312E-08 30823E-08 30572E-08 32801E-08
22801E-08 31288E-08 25008E-08 25008E-08 22828E-08 22828E-08
22828E-08 22828E-08 22828E-08 19148E-08 19148E-08 0

17880E-08 13321E-08 13524E-08 13258E-08 14500E-08 14187E-08
14187E-08 13518E-08 10801E-08 10801E-08 87731E-08 87731E-08
87731E-08 87731E-08 87731E-08 82708E-08 82708E-08 0

34084E-08 25851E-08 28041E-08 28717E-08 27921E-08 27260E-08
27260E-08 28028E-08 20789E-08 20789E-08 18818E-08 18818E-08
18818E-08 18818E-08 18818E-08 18826E-08 18826E-08 0

73375E-08 58253E-08 58092E-08 55385E-08 80142E-08 58761E-08
58761E-08 58062E-08 44801E-08 44801E-08 40538E-08 40538E-08
40538E-08 40538E-08 40538E-08 34304E-08 34304E-08 0

28410E-04 19134E-04 19428E-04 19183E-04 20827E-04 20349E-04
20349E-04 19414E-04 18515E-04 18515E-04 14038E-04 14038E-04
14038E-04 14038E-04 14038E-04 11880E-04 11880E-04 0

***** CYBER PAGE PRINT - END OF JOB LASERTY
***** CYBER PAGE PRINT - END OF JOB LASERTY
***** CYBER PAGE PRINT - END OF JOB LASERTY
***** CYBER PAGE PRINT - END OF JOB LASERTY
***** CYBER PAGE PRINT - END OF JOB LASERTY
***** CYBER PAGE PRINT - END OF JOB LASERTY
***** CYBER PAGE PRINT - END OF JOB LASERTY
***** CYBER PAGE PRINT - END OF JOB LASERTY
***** CYBER PAGE PRINT - END OF JOB LASERTY
***** CYBER PAGE PRINT - END OF JOB LASERTY

4.7 REFERENCES

1. Rhoades, W. A., and M. B. Emmett. DOS: the Discrete Ordinates System, ORNL/TM-8362, September 1982.
2. Rhoades, W. A., and R. L. Childs. An Updated Version of the DOT 4 One- and Two-Dimensional Neutron/Photon Transport Code, ORNL-5851, July 1982.
3. RSIC Computer Code Collection, ANISN-W, CCC-255, ORNL, 1975.
4. RSIC Computer Code Collection, AMPX-II, PSR-63, ORNL, 1978.
5. Pfeifer, C. J. "PDQ-7 Reference Manual II," WAPD-TM-947(L), BAPL, February 1971.
6. XN-CC-28, Revision 5. "XTG - A Two-Group Three-Dimensional Reactor Simulator Utilizing Coarse-Mesh Spacing (PWR Version)," Exxon Nuclear Company, July 1979.
7. Skogen, F. B. "XPOSE - The Exxon Nuclear Revised LEOPARD," XN-CC-21, Revision 2, Exxon Nuclear Company, April 1975.
8. Maerker, R. E., M. L. Williams, and B. L. Broadhead. "Summary Documentation of EPRI Workshop on LWR Pressure Vessel Fluence Calculations with the LEPRICON Code System," Electric Power Research Institute, Palo Alto, 1983.
9. RSIC Data Library Collection, CSRL. DCL-43, ORNL, 1978.
10. Reactor Physics Constants. ANL-5800, Argonne National Laboratory, July 1963.
11. Breen, R. J., et al. HARMONY: System for Nuclear Reactor Depletion Computations, WAPD-TM-478, BAPL, January 1965.
12. Leggett, W. D., III. TOTE - A Code for Totaling Local Burnup, Isotopics, and Uranium Values, WCAP-7309, WNES, March 1969.
13. Attachment to Letter from E. E. Utley to H. R. Denton, CP&L, File NF-1111.04, February 9, 1983.
14. Telecommunication from I. Z. Stone to W. K. Cantrell, Exxon Nuclear Company, March 21, 1983.
15. Telecommunication from R. S. Howell to W. K. Cantrell, Technology for Energy Corporation, June 22, 1983.

16. WCAP-10304, Analysis of Capsule T from the H. B. Robinson Unit 2 Reactor Vessel Radiation Surveillance Program, EPRI RP-1021-3, March 1983.
17. Yanichko, S. E., et al. "Analysis of Capsules from CP&L, H. B. Robinson Unit 2 Reactor Vessel Radiation Surveillance Program," WNES, December 18, 1982.
18. Norris, E. B. Reactor Vessel Material Surveillance Program for H. B. Robinson Unit 2 Analysis of Capsule V, SWRI 02-4397, October 19, 1976.
19. Nonproprietary Fuel Design Data for Exxon Nuclear's H. B. Robinson No. 2--Region 7 Reload Assemblies, Exxon Nuclear Company, Inc., August 1975.
20. Letter from E. E. Utley to H. R. Denton, CP&L, February 9, 1983.

Section 5

RESULTS AND CONCLUSIONS

The synthesis procedure was used to construct group flux distributions from DOT and ANISN results for critical areas of interest for both the Cycle 8 and Cycle 10 cores. These areas included the locations of S, V, and T surveillance capsules for Cycle 8, and the pressure vessel inner surface axially at 0 degrees, radially at the lower circumferential weld, and radially at the core midplane for both cycles. Summing the top 27 ELXSIR group fluxes gave distributions of the flux above 1 Mev.

The detailed results are presented in this section along with dosimeter activations and fluences above 1 MeV computed with the flux results. The calculated activations are compared with measurements for the HBR2 capsules and projections of max. fluences (based on current RT-NDT screening criteria) are given.

5.1 FLUXES AT THE PRESSURE VESSEL INNER SURFACE

Fluxes above 1 MeV for the Cycle 8 and Cycle 10 cases are given in Tables 5-1 through 5-3 for the pressure vessel inner surface along the lower girth weld, along the core midplane, and axially at the core major axis, respectively. Figures 5-1 and 5-2 depict graphically the flux and flux reduction factor, FRF (defined as the ratio Cycle 8 flux/Cycle 10 flux), distributions for the lower circumferential weld, while Figures 5-3 and 5-4 depict the same quantities axially for the vessel surface at the core major axis (0 degrees). The beltline longitudinal weld is at 4 degrees where flux is slightly less than at 0 degrees. The maximum

Table 5-1

FLUX, FLUENCE (ABOVE 1MEV), AND RT-NDT AT 27 EPFY
 RADIALLY ALONG HBR2 VESSEL LOWER GIRTH WELD INNER SURFACE

ANGLE DEG	CYC 8 FLUX	CYC 10 FLUX	EOC 8 FLUENCE	27 EPFY FLUENCE	(*) RT-NDT DEG. F
.48	.6396E+11	.6958E+10	.1450E+20	.1949E+20	300.1
1.43	.6366E+11	.6974E+10	.1443E+20	.1942E+20	299.9
2.38	.6306E+11	.7010E+10	.1430E+20	.1930E+20	299.5
3.34	.6216E+11	.7067E+10	.1409E+20	.1912E+20	298.9
4.11	.6108E+11	.7136E+10	.1385E+20	.1890E+20	298.2
4.80	.6005E+11	.7206E+10	.1361E+20	.1870E+20	297.5
5.77	.5833E+11	.7324E+10	.1322E+20	.1836E+20	296.4
6.84	.5586E+11	.7507E+10	.1266E+20	.1788E+20	294.8
7.88	.5304E+11	.7739E+10	.1202E+20	.1734E+20	292.9
8.95	.4972E+11	.8060E+10	.1127E+20	.1674E+20	290.7
10.02	.4624E+11	.8496E+10	.1048E+20	.1617E+20	288.6
10.94	.4326E+11	.8990E+10	.9806E+19	.1575E+20	287.1
11.69	.4084E+11	.9443E+10	.9259E+19	.1544E+20	285.9
12.30	.3894E+11	.9838E+10	.8827E+19	.1522E+20	285.0
12.77	.3743E+11	.1013E+11	.8486E+19	.1504E+20	284.3
13.20	.3604E+11	.1043E+11	.8170E+19	.1488E+20	283.7
13.62	.3469E+11	.1072E+11	.7863E+19	.1473E+20	283.1
14.07	.3328E+11	.1102E+11	.7543E+19	.1457E+20	282.4
14.78	.3115E+11	.1149E+11	.7061E+19	.1435E+20	281.5
15.79	.2883E+11	.1219E+11	.6536E+19	.1421E+20	281.0
16.85	.2693E+11	.1294E+11	.6104E+19	.1420E+20	280.9
17.91	.2543E+11	.1365E+11	.5765E+19	.1427E+20	281.2
18.87	.2439E+11	.1427E+11	.5528E+19	.1439E+20	281.7
19.74	.2358E+11	.1479E+11	.5346E+19	.1451E+20	282.2
20.60	.2293E+11	.1525E+11	.5198E+19	.1463E+20	282.7
21.40	.2242E+11	.1560E+11	.5083E+19	.1471E+20	283.0
22.12	.2200E+11	.1587E+11	.4987E+19	.1477E+20	283.3
22.84	.2160E+11	.1606E+11	.4896E+19	.1480E+20	283.3
23.51	.2122E+11	.1616E+11	.4810E+19	.1476E+20	283.2
24.13	.2085E+11	.1619E+11	.4726E+19	.1469E+20	282.9
24.93	.2039E+11	.1617E+11	.4622E+19	.1457E+20	282.4
25.89	.1976E+11	.1595E+11	.4481E+19	.1429E+20	281.3
26.69	.1919E+11	.1564E+11	.4351E+19	.1397E+20	279.9
27.34	.1877E+11	.1539E+11	.4255E+19	.1372E+20	278.9
27.98	.1837E+11	.1514E+11	.4165E+19	.1347E+20	277.8
28.50	.1807E+11	.1492E+11	.4096E+19	.1327E+20	277.0
28.88	.1784E+11	.1476E+11	.4045E+19	.1312E+20	276.3
29.27	.1761E+11	.1458E+11	.3992E+19	.1295E+20	275.6
29.80	.1727E+11	.1432E+11	.3915E+19	.1271E+20	274.5
30.44	.1688E+11	.1398E+11	.3826E+19	.1242E+20	273.1
31.05	.1650E+11	.1365E+11	.3741E+19	.1213E+20	271.8
31.62	.1615E+11	.1332E+11	.3661E+19	.1185E+20	270.5
32.19	.1579E+11	.1298E+11	.3579E+19	.1156E+20	269.1
32.65	.1550E+11	.1271E+11	.3514E+19	.1133E+20	267.9
33.12	.1517E+11	.1240E+11	.3440E+19	.1106E+20	266.6

33.73	.1478E+11	.1202E+11	.3350E+19	.1074E+20	264.9
34.33	.1438E+11	.1164E+11	.3261E+19	.1042E+20	263.2
35.09	.1390E+11	.1117E+11	.3151E+19	.1002E+20	261.1
35.93	.1340E+11	.1069E+11	.3039E+19	.9617E+19	258.9
36.71	.1296E+11	.1027E+11	.2939E+19	.9257E+19	256.8
37.49	.1256E+11	.9886E+10	.2848E+19	.8932E+19	254.9
38.27	.1221E+11	.9543E+10	.2769E+19	.8642E+19	253.1
39.05	.1192E+11	.9250E+10	.2702E+19	.8396E+19	251.6
39.84	.1168E+11	.8998E+10	.2647E+19	.8187E+19	250.2
40.63	.1148E+11	.8794E+10	.2603E+19	.8019E+19	249.1
41.43	.1134E+11	.8632E+10	.2570E+19	.7887E+19	248.3
42.22	.1123E+11	.8510E+10	.2547E+19	.7789E+19	247.6
43.01	.1117E+11	.8423E+10	.2532E+19	.7721E+19	247.2
43.81	.1113E+11	.8368E+10	.2522E+19	.7678E+19	246.9
44.60	.1111E+11	.8341E+10	.2518E+19	.7657E+19	246.7

(**)

$$RT-NDT = -56 + 283. \cdot (F/E19) \cdot 0.194 + 2 \cdot SIG$$

$$2 \cdot SIG = 34$$

Table 5-2

FLUX AND FLUENCE (ABOVE 1MEV) RADIALLY
ALONG HBR2 VESSEL INNER SURFACE AT CORE MIDPLANE

ANGLE DEG	CYC 8 FLUX	CYC 10 FLUX	EOC 8 FLUENCE	27 EPY FLUENCE
.48	.6977E+11	.4155E+11	.1582E+20	.4160E+20
1.43	.6945E+11	.4138E+11	.1574E+20	.4142E+20
2.38	.6880E+11	.4104E+11	.1560E+20	.4106E+20
3.34	.6783E+11	.4053E+11	.1538E+20	.4053E+20
4.11	.6665E+11	.3993E+11	.1511E+20	.3989E+20
4.80	.6552E+11	.3936E+11	.1485E+20	.3928E+20
5.77	.6365E+11	.3843E+11	.1443E+20	.3827E+20
6.84	.6097E+11	.3712E+11	.1382E+20	.3684E+20
7.88	.5788E+11	.3566E+11	.1312E+20	.3523E+20
8.95	.5426E+11	.3401E+11	.1230E+20	.3337E+20
10.02	.5045E+11	.3236E+11	.1144E+20	.3147E+20
10.94	.4717E+11	.3105E+11	.1069E+20	.2990E+20
11.69	.4452E+11	.3002E+11	.1009E+20	.2865E+20
12.30	.4244E+11	.2925E+11	.9620E+19	.2769E+20
12.77	.4079E+11	.2863E+11	.9247E+19	.2692E+20
13.20	.3926E+11	.2807E+11	.8900E+19	.2622E+20
13.62	.3778E+11	.2753E+11	.8564E+19	.2554E+20
14.07	.3623E+11	.2697E+11	.8213E+19	.2483E+20
14.78	.3389E+11	.2616E+11	.7684E+19	.2379E+20
15.79	.3135E+11	.2539E+11	.7108E+19	.2272E+20
16.85	.2926E+11	.2489E+11	.6634E+19	.2192E+20
17.91	.2763E+11	.2459E+11	.6263E+19	.2135E+20
18.87	.2648E+11	.2445E+11	.6004E+19	.2099E+20
19.74	.2561E+11	.2437E+11	.5806E+19	.2074E+20
20.60	.2490E+11	.2433E+11	.5645E+19	.2054E+20
21.40	.2435E+11	.2429E+11	.5520E+19	.2038E+20
22.12	.2389E+11	.2422E+11	.5415E+19	.2023E+20
22.84	.2346E+11	.2412E+11	.5318E+19	.2007E+20
23.51	.2305E+11	.2395E+11	.5225E+19	.1987E+20
24.13	.2265E+11	.2373E+11	.5134E+19	.1964E+20
24.93	.2215E+11	.2341E+11	.5022E+19	.1933E+20
25.89	.2148E+11	.2284E+11	.4870E+19	.1883E+20
26.69	.2087E+11	.2222E+11	.4730E+19	.1831E+20
27.34	.2041E+11	.2175E+11	.4627E+19	.1792E+20
27.98	.1998E+11	.2128E+11	.4529E+19	.1753E+20
28.50	.1965E+11	.2089E+11	.4455E+19	.1722E+20
28.88	.1941E+11	.2061E+11	.4400E+19	.1700E+20
29.27	.1916E+11	.2031E+11	.4343E+19	.1675E+20
29.80	.1879E+11	.1987E+11	.4261E+19	.1641E+20
30.44	.1837E+11	.1934E+11	.4164E+19	.1598E+20
31.05	.1796E+11	.1882E+11	.4072E+19	.1557E+20
31.62	.1758E+11	.1832E+11	.3985E+19	.1518E+20
32.19	.1719E+11	.1780E+11	.3896E+19	.1478E+20
32.65	.1688E+11	.1739E+11	.3826E+19	.1446E+20
33.12	.1652E+11	.1693E+11	.3746E+19	.1410E+20

33.73	.1609E+11	.1637E+11	.3648E+19	.1366E+20
34.33	.1566E+11	.1581E+11	.3551E+19	.1323E+20
35.09	.1514E+11	.1514E+11	.3433E+19	.1270E+20
35.93	.1460E+11	.1445E+11	.3310E+19	.1215E+20
36.71	.1412E+11	.1384E+11	.3201E+19	.1168E+20
37.49	.1369E+11	.1330E+11	.3103E+19	.1124E+20
38.27	.1331E+11	.1281E+11	.3017E+19	.1086E+20
39.05	.1299E+11	.1239E+11	.2945E+19	.1053E+20
39.84	.1273E+11	.1203E+11	.2885E+19	.1026E+20
40.63	.1252E+11	.1174E+11	.2838E+19	.1003E+20
41.43	.1236E+11	.1151E+11	.2803E+19	.9857E+19
42.22	.1225E+11	.1134E+11	.2778E+19	.9726E+19
43.01	.1218E+11	.1121E+11	.2761E+19	.9634E+19
43.81	.1214E+11	.1113E+11	.2751E+19	.9575E+19
44.60	.1212E+11	.1109E+11	.2747E+19	.9547E+19

Table 5.3

FLUX AND FLUENCE (ABOVE 1MEV) AXIALLY
ALONG HBR2 VESSEL INNER SURFACE (ANGLE 0 DEG)
AND
RT-NDT AT 27 EFPY FOR BELTLINE LONGITUDINAL WELD

IN ABOVE FUEL BOT	CYC 8 FLUX	CYC 10 FLUX	EOC 8 FLUENCE	27 EFPY FLUENCE	(*) RT-NDT DEG. F
-3.35	.8838E+10	.6928E+09	.2003E+19	.2532E+19	
-2.54	.1201E+11	.9364E+09	.2723E+19	.3438E+19	
-1.73	.1458E+11	.1135E+10	.3305E+19	.4172E+19	
-.92	.1704E+11	.1327E+10	.3864E+19	.4877E+19	
-.26	.1909E+11	.1488E+10	.4329E+19	.5465E+19	
.26	.2067E+11	.1613E+10	.4687E+19	.5918E+19	
.91	.2255E+11	.1760E+10	.5113E+19	.6456E+19	
1.89	.2545E+11	.1984E+10	.5769E+19	.7284E+19	
3.40	.2976E+11	.2317E+10	.6746E+19	.8516E+19	
5.24	.3478E+11	.2736E+10	.7884E+19	.9968E+19	
7.08	.3953E+11	.3170E+10	.8961E+19	.1137E+20	
8.92	.4392E+11	.3611E+10	.9957E+19	.1268E+20	
10.76	.4795E+11	.4057E+10	.1087E+20	.1391E+20	
12.61	.5156E+11	.4501E+10	.1169E+20	.1505E+20	
14.45	.5477E+11	.4944E+10	.1242E+20	.1608E+20	
16.29	.5758E+11	.5391E+10	.1305E+20	.1702E+20	
18.13	.6006E+11	.5860E+10	.1362E+20	.1790E+20	
19.97	.6217E+11	.6370E+10	.1409E+20	.1871E+20	
21.81	.6396E+11	.6958E+10	.1450E+20	.1949E+20	
23.65	.6543E+11	.7665E+10	.1483E+20	.2026E+20	202.3
25.49	.6662E+11	.8552E+10	.1510E+20	.2108E+20	204.1
27.33	.6753E+11	.9687E+10	.1531E+20	.2198E+20	206.0
29.17	.6822E+11	.1117E+11	.1546E+20	.2303E+20	208.1
30.69	.6868E+11	.1287E+11	.1557E+20	.2416E+20	210.3
31.70	.6894E+11	.1430E+11	.1563E+20	.2508E+20	212.1
32.54	.6913E+11	.1557E+11	.1567E+20	.2589E+20	213.6
33.38	.6926E+11	.1692E+11	.1570E+20	.2672E+20	215.1
34.22	.6940E+11	.1831E+11	.1573E+20	.2759E+20	216.6
35.07	.6953E+11	.1975E+11	.1576E+20	.2848E+20	218.2
35.74	.6970E+11	.2097E+11	.1580E+20	.2926E+20	219.5
36.26	.6976E+11	.2188E+11	.1581E+20	.2982E+20	220.4
36.91	.6973E+11	.2302E+11	.1581E+20	.3049E+20	221.5
37.89	.6969E+11	.2476E+11	.1580E+20	.3152E+20	223.2
39.46	.6962E+11	.2741E+11	.1578E+20	.3310E+20	225.6
41.78	.6977E+11	.3076E+11	.1582E+20	.3514E+20	228.7
44.43	.7001E+11	.3383E+11	.1587E+20	.3703E+20	231.4
47.09	.7013E+11	.3619E+11	.1590E+20	.3848E+20	233.4
49.74	.7015E+11	.3795E+11	.1590E+20	.3954E+20	234.8
52.40	.7012E+11	.3920E+11	.1590E+20	.4028E+20	235.8
55.06	.7007E+11	.4007E+11	.1588E+20	.4079E+20	236.5
57.71	.7000E+11	.4067E+11	.1587E+20	.4113E+20	236.9
60.37	.6994E+11	.4107E+11	.1586E+20	.4136E+20	237.2

63.02	.6988E+11	.4132E+11	.1584E+20	.4149E+20	237.4
65.68	.6983E+11	.4148E+11	.1583E+20	.4157E+20	237.5
68.33	.6977E+11	.4155E+11	.1582E+20	.4160E+20	237.6
70.99	.6974E+11	.4157E+11	.1581E+20	.4161E+20	237.6
73.65	.6970E+11	.4155E+11	.1580E+20	.4158E+20	237.5
76.30	.6967E+11	.4150E+11	.1579E+20	.4155E+20	237.5
78.96	.6963E+11	.4142E+11	.1579E+20	.4149E+20	237.4
81.61	.6961E+11	.4132E+11	.1578E+20	.4142E+20	237.3
84.27	.6956E+11	.4118E+11	.1577E+20	.4133E+20	237.2
86.92	.6953E+11	.4104E+11	.1576E+20	.4124E+20	237.1
89.58	.6947E+11	.4086E+11	.1575E+20	.4111E+20	236.9
92.24	.6941E+11	.4066E+11	.1573E+20	.4098E+20	236.7
94.89	.6931E+11	.4042E+11	.1571E+20	.4082E+20	236.5
97.55	.6920E+11	.4015E+11	.1569E+20	.4063E+20	236.3
100.20	.6903E+11	.3983E+11	.1565E+20	.4040E+20	236.0
102.86	.6882E+11	.3944E+11	.1560E+20	.4011E+20	235.6
105.52	.6851E+11	.3896E+11	.1553E+20	.3975E+20	235.1
108.17	.6809E+11	.3836E+11	.1544E+20	.3929E+20	234.5
110.83	.6752E+11	.3763E+11	.1531E+20	.3871E+20	233.7
113.48	.6676E+11	.3674E+11	.1514E+20	.3800E+20	232.7
116.14	.6578E+11	.3566E+11	.1491E+20	.3712E+20	231.5
118.79	.6451E+11	.3438E+11	.1463E+20	.3605E+20	230.0
121.45	.6289E+11	.3287E+11	.1426E+20	.3475E+20	228.1
124.11	.6082E+11	.3107E+11	.1379E+20	.3318E+20	225.7
126.76	.5815E+11	.2891E+11	.1318E+20	.3125E+20	222.7
129.42	.5473E+11	.2632E+11	.1241E+20	.2888E+20	218.8
132.07	.5049E+11	.2333E+11	.1145E+20	.2607E+20	213.9
134.39	.4589E+11	.2032E+11	.1040E+20	.2316E+20	208.4
135.96	.4214E+11	.1804E+11	.9554E+19	.2090E+20	203.7
136.94	.3950E+11	.1653E+11	.8955E+19	.1936E+20	200.3
137.59	.3770E+11	.1552E+11	.8546E+19	.1833E+20	197.9
138.11	.3622E+11	.1472E+11	.8210E+19	.1749E+20	
138.76	.3432E+11	.1370E+11	.7781E+19	.1643E+20	
139.72	.3158E+11	.1227E+11	.7160E+19	.1492E+20	
140.85	.2840E+11	.1072E+11	.6439E+19	.1323E+20	
141.98	.2529E+11	.9283E+10	.5733E+19	.1162E+20	
142.94	.2277E+11	.8184E+10	.5163E+19	.1036E+20	
143.59	.2110E+11	.7472E+10	.4784E+19	.9530E+19	
144.11	.1976E+11	.6903E+10	.4480E+19	.8869E+19	
144.76	.1808E+11	.6201E+10	.4099E+19	.8045E+19	
145.81	.1555E+11	.5200E+10	.3524E+19	.6839E+19	
147.14	.1283E+11	.4206E+10	.2909E+19	.5593E+19	
148.46	.1045E+11	.3378E+10	.2370E+19	.4527E+19	
149.79	.8414E+10	.2693E+10	.1908E+19	.3629E+19	
150.84	.7094E+10	.2259E+10	.1608E+19	.3052E+19	
151.49	.6313E+10	.2004E+10	.1431E+19	.2713E+19	
152.01	.5693E+10	.1804E+10	.1291E+19	.2444E+19	
152.66	.4942E+10	.1562E+10	.1120E+19	.2120E+19	
153.67	.3933E+10	.1241E+10	.8917E+18	.1685E+19	
154.90	.2955E+10	.9307E+09	.6699E+18	.1265E+19	
156.13	.1947E+10	.6137E+09	.4413E+18	.8339E+18	

(*) RT-NDT = -56 + (-10 + 470*CU + 350*CU*NI)*(F/E19)**.27 + 2*SIG
 2*SIG = 2 * 17 + 60, CU = 0.27, NI = 0.2




Figure 5-1. Lower Circumferential Weld Best Estimate Flux Distribution for Cycles 8 and 10.




Figure 5-2. Lower Circumferential Weld Best Estimate Reduction Factor for the 36 inch Stainless Steel PLSA Design.




Figure 5-3. Axial Flux Distributions for Cycle 8 and Cycle 10 at the Center of the Core Flat.




Figure 5-4. Axial Best Estimate Reduction Factor Distribution at the Center of the Core Flats.

flux (energy above 1 MeV) at the vessel inner surface for the Cycle 8 case is $7.015E+10$ n/cm² which is in excellent agreement with $6.882E+10$ reported in Reference 1 for Capsule T measurements. The maximum along the lower circumferential weld for Cycle 8 is $6.396E+10$ n/cm² at the core major axis; at the corresponding lower weld position for Cycle 10 the flux is $6.958E+9$, giving a reduction factor of 9.2. Vessel surface fluxes at the core midplane (major axis) are $6.977E+10$ for Cycle 8 and $4.155E+10$ for Cycle 10, both within 1 percent of maximum for the respective cases.

5.2 COMPARISON OF CYCLE 8 RESULTS WITH DOSIMETER MEASUREMENTS

Dosimeter cross-sections for detectors measured in HBR2 Capsules S, V, and T were computed with a spectrum from a 56-group ANISN-W calculation simulating the core major axis for the Cycle 8 case. The capsules were not modeled explicitly, and the spectrum was taken from the interface between the thermal shield outer surface and the downcomer water. Group cross-sections from the ELXSIR library were averaged as

$$\sigma (E>1\text{MeV}) = \frac{\sum_{g=1}^{56} \sigma_g \phi_g}{\sum_{g=1}^{27} \phi_g}$$

These cross-sections were used with the synthesis fluxes (energy above 1 MeV) at the capsule locations to give calculated saturation activities for each dosimeter. The results are shown in Table 5-4 and comparisons with corrected measurements made. The average percent difference between calculated and measured for all dosimeters is 1.1% with a standard deviation of 13.6%. The half-life of Mn-54 (313 days) is midrange compared to other dosimeters, and the reaction $\text{Fe}54 (n,p) \text{Mn}54$ generally

Table 5-4

Comparison of Calculated and Measured Saturation Activities
for H. B. Robinson Surveillance Capsules

Reaction		0 Deg(EOCB)	10 Deg(EOC1)	20 Deg(EOC3)
		Measured Saturated Activity(1)		
Cu(n,a)Co		7.525E+5	-	3.54E+5
Ni(n,p)Co		1.164E+8	-	4.833E+7
Fe(n,p)Mn		8.39E+6	4.77E+6	3.278E+6
U(n,f)Cs		1.297E+7	-	-
Np(n,f)Cs		8.565E+7	-	-
	X-section(2)	Calculated Saturation Activities		
Cu(n,a)Co	.5545E-3	7.123E+5	-	2.904E+5
Ni(n,p)Co	.09287	1.2775E+8	-	5.209E+7
Fe(n,p)Mn	.06857	8.572E+6	6.147E+6	3.495E+6
U(n,f)Cs	.3484	1.087E+7	-	-
Np(n,f)Cs	2.879	9.313E+7	-	-
		Per Cent Difference (Calc-Meas)/Calc*100		
Cu(n,a)Co		-5.6	-	-22.1
Ni(n,p)Co		8.9	-	7.2
Fe(n,p)Mn		2.1	22.4	8.7
U(n,f)Cs		-19.3	-	-
Np(n,f)Cs		8.0	-	-
Calculated Flux(E>1MeV)		1.958E+11	1.404E+11	7.984E+10

(1) Section 4.3.4, Table 4-8

(2) Averaged over spectrum from 1-D 56-group ANISN (ELXSIR library) just outside thermal shield (no explicit model of capsules).

considered most reliable. The comparisons are 2.1% for capsule T, 8.7% for capsule V, and 22% for capsule S (EOC1). It is noted the Cycle 8 source distribution was least representative of Cycle 1.

5.3 PROJECTED FLUENCES AND RT-NDT

Based on the synthesis fluxes, fluences above 1 Mev at EOC 8 and at 27 EFPY and RT-NDT (27 EFPY) were computed for the vessel inner surface along the lower circumferential weld, along the core midplane, and axially at the major axis.

At EOC 8 the vessel had been exposed 7.2 EFPY; Cycle 9 was projected to add 0.8 EFPY at a flux reduction factor of 2. RT-NDT was computed with the limit formulas from SECY-82-465, Appendix E. The projection to 27EFPY is shown because it is the point at which the screening criteria is first reached by any part of the vessel. RT-NDT₀ was taken as -56F and the axial weld compositions of 0.27% Cu and 0.2% Ni were used. Maximum 0.35% Cu and 1.2% Ni were assumed for the girth welds. Results are tabulated in Table 5-1 for the lower girth weld and Table 5-3 for the beltline longitudinal weld. The fluences are plotted in Figures 5-5 through 5-7.


5.4 DISCUSSION AND CONCLUSIONS

5.4.1 Uncertainties and Sensitivities

Table 5-5 lists estimated uncertainties in the source calculations along with sensitivities determined for the synthesis-superposition technique for constructing 3-D fluxes. The bases for estimating uncertainties in

Figure 5-5

HBR2 CALCULATED FLUENCE ($E > 1\text{MEV}$) BASED ON 36 IN. SHIELD HEIGHT
LOWER WELD INNER SURFACE



HBR2 CALCULATED FLUENCE (E>1MEV) BASED ON 36 IN. SHIELD HEIGHT CORE MIDPLANE INNER SURFACE





Figure 5-7

HBR2 CALCULATED FLUENCE ($E > 1\text{MEV}$) BASED ON 36 IN. SHIELD HEIGHT
VESSEL INNER SURFACE (0 DEGREE)



the sources are the comparisons with the averaged Cycle 8 power measurements, corroborated by the Cycle 9 state-point comparisons. The radial component contains additional uncertainty for pin distribution within an assembly. The superposition estimate is based on comparisons of fast flux at the vessel inner surface calculated first assuming the Cycle 8 case to be a one-axial region core and second assuming a two-axial region core. (The latter case was used for all comparisons with the Cycle 10 case and calculations of FRF.) The estimate for uncertainty in the synthesis is based on comparisons of fast flux at the vessel inner surface calculated for the Cycle 10 case first assuming separable axial and radial source distributions in the DOT R-Z and ANISN problems and second representing the axial distributions as a function of radius. (The latter more closely represents the actual case and was used for all comparisons with Cycle 8). This comparison gave differences ranging from less than 1% at the core midplane to 12% at the top and bottom of the problem. The 5% shown in Table 5-4 represents the region of the lower circumferential weld. The RMS combination of these estimates is 7.75%, which gives a 2-sigma uncertainty of 15.5% for calculated fluxes at the vessel inner surface, lower circumferential weld region.

Table 5-4 lists the calculated-measured differences of dosimeter saturation activities for the HBR2 measured capsules. All comparisons fall within $\sqrt{2}$ times the estimated calculational 2-sigma. This would be expected if measurement and calculational uncertainties are equal.

Table 5-5

ESTIMATED UNCERTAINTIES IN CALCULATED PRESSURE VESSEL SURFACE FLUXES

Radial Source Distribution	5.0%
Axial Source Distribution	3.0%
Synthesis Sensitivity	5.0%
Superposition Sensitivity	1.0%
RMS Combination	7.75%
2-Sigma	15.5%

5.4.2 Conservatisms

The synthesis calculations contain two major conservatisms with respect to calculated fluxes at the limiting vessel inner surfaces. First, water outside the core in the downcomer region was modeled at 575F instead of the nominal full power 547F. The density difference is approximately 4% and results in higher calculated fluxes to the vessel (in both the Cycle 8 and Cycle 10 cases). Second, the analysis was performed assuming a shield height of 36 in. in the PLSAs, whereas they are being fabricated to a height of 42 in. The flux reduction at the lower weld to be expected from the additional height is estimated by the FRF from the present calculation at 6 in. below the weld. This value is 10.7 and results in the calculated time to reach allowable RT-NDT increasing to 30 EFPY, more than 10% margin in the present calculations.

5.4.3 Conclusions

The use of the 42 in. stainless steel PLSA design on the core flats of HBR2 cores commencing with Cycle 10 will sufficiently shield critical welds to preclude reaching present screening criteria for pressure vessel RT-NDT before projected expiration of operating license.

APPENDIX A

Résumés of Key Personnel

WELDON KERMIT CANTRELL

Senior Engineer - Incore Analysis

EDUCATION:

North Carolina State University: B.S., Nuclear Engineering (1975)
Graduate Work 8/75 - 6/77

SUMMARY OF EXPERIENCE:

Mr. Cantrell's primary responsibilities with CP&L have centered around development of computer programs and methods for use in reactor design, operations, and fuel management support.

His early duties included neutronics design review, start-up support, and operations follow for H. B. Robinson Unit 2, a PWR. Considerable experience with the design codes, PDQ07, XPOSE (LEOPARD), and processors, on both IBM and CDC mainframes was attained. He maintained and verified the operations support codes, INCORE, TOTE, and FOLLOW; he wrote and implemented FDELTAI, a code automating calibration of ex-core detectors.

He participated in start-up physics tests at HBR2 for Cycles 6, 7, and 9. He helped develop and implement specific plant procedures for verifying reactivity measurements during these tests.

More recently he has worked on the benchmarking and validation of Scandpower's FMS codes, particularly the cross-section code, RECORD, and participated in preparation of CP&L's Topical Report on BWR Steady-State Analysis Methods.

Prior to joining CP&L, Mr. Cantrell worked as a graduate teaching assistant in the Nuclear Engineering Department, North Carolina State University.

PROFESSIONAL ACHIEVEMENTS AND ACTIVITIES:

Registered Professional Engineer, North Carolina, February 1982

Member American Nuclear Society

Member National Society of Professional Engineers

WELDON KERMIT CANTRELL (continued)

PROFESSIONAL ACHIEVEMENTS AND ACTIVITIES: (continued)

Member Professional Engineers of North Carolina

Member American Association for the Advancement of Science

PAPERS AND PUBLICATIONS:

W. K. Cantrell, et al, "The INCORE Code: Production Version PNR16010 and Auxiliary Codes Documentation," NF-1106.01, CP&L, March 1983.

K. E. Karcher, W. K. Cantrell, and D. W. Schroeder, "A Description and Validation of Steady-State Analysis Methods for Boiling Water Reactors: Topical Report," NF-1583.01, CP&L, February 1983.

R. R. Wojnarowski, W. K. Cantrell, and T. M. Dresser, "H. B. Robinson Unit 2 - Cycle 9 Startup Test Report," NF-908.01, CP&L, September 1982.

W. K. Cantrell, T. M. Dresser, and K. E. Kutcher, "H. B. Robinson Unit 2 Cycle 8 Startup and Operations Analysis," NF-1101.03, CP&L, October 1980.

W. K. Cantrell and T. M. Dresser, "Neutronics Analysis Techniques for H. B. Robinson Cycle 7 Design," NF-1101.03, CP&L, July 1980.

W. K. Cantrell, P. S. Shieh, and D. W. Schroeder, "B2C4 Reload Design Verification Using the SCANDPOWER BWR Model," NF-1101.03, NF-80-394, CP&L, June 1980.

W. K. Cantrell, P. S. Shieh, and D. W. Schroeder, "B1C3 Reload Design Verification Using the SCANDPOWER BWR Model," NF-1101.03, NF-80-283, CP&L, May 1980.

W. K. Cantrell, et al, "H. B. Robinson Unit 2 Nuclear Peaking Factor Uncertainties Cycles 4, 5, and 6," NF-1049, CP&L, December 1979.

T. M. Dresser and W. K. Cantrell, "H. B. Robinson Unit 2 Cycle 7 Startup Test Report," NF-908.01, CP&L, September 1979.

W. K. Cantrell and T. M. Dresser, "H. B. Robinson Unit 2 Cycle 7 Startup and Operations Neutronics Design Analysis," NF-1101.03, CP&L, September 1979.

WELDON KERMIT CANTRELL (continued)

PAPERS AND PUBLICATIONS: (continued)

W. K. Cantrell, "H. B. Robinson Unit 2 -- Cycle 6 Core Performance Report," NF-901.01, CP&L, May 1979.

T. M. Dresser and W. K. Cantrell, "H. B. Robinson Unit 2 Cycle 7 Safety Analysis and Fuel Management Design Review," NF-401.1003, CP&L, April 1979.

T. M. Dresser and W. K. Cantrell, "H. B. Robinson Unit 2 Cycle 6 Startup Test Report," NF-908.01, CP&L, June 1978.

T. M. Dresser and W. K. Cantrell, "H. B. Robinson Unit 2 Cycle 6 Neutronics Design Evaluation," NF-401.0903, CP&L, February 1978.

THOMAS MAXWELL DRESSER

Senior Engineer - Fuel Projects

EDUCATION:

University of Maryland: B.S., cum laude, Nuclear Engineering/
Computer Science (1979)

SUMMARY OF EXPERIENCE:

Mr. Dresser's background experience at CP&L centered around development of computer programs and methods for core design, operations, and fuel management of PWRs. His present responsibilities are in contract administration and procurement of nuclear fuel and related services in support of fuel cycle front end requirements.

His previous duties included neutronics design review, start-up support, and operations follow for the PWR, H. B. Robinson Unit 2. He gained extensive experience in the maintenance and verification of the nodal simulator, XTGPWR, and the cross-section generator, XPOSE(LEOPARD), in both IBM and CDC environments. He developed, benchmarked, and implemented the code system, EXSPACK, for plant computations of estimated critical position (ECP), xenon transient worth, and shutdown margin required boron concentration.

He participated in start-up physics tests at HBR2 for Cycles 6-9, serving as Start-up Engineer for Cycle 9.

Mr. Dresser is co-inventor of the Part Length Shield Assembly (PLSA) concept which maximizes local fast neutron shielding with minimal adverse impact to core performance.

Mr. Dresser worked extensively with EXXON Nuclear personnel in the development of the low leakage reload strategy for HBR2 Cycles 9 through 13. The strategy leads to extended equilibrium cycle length commencing with Cycle 11.

PROFESSIONAL ACHIEVEMENTS AND ACTIVITIES:

Member American Nuclear Society

Member Tau Beta Pi

THOMAS MAXWELL DRESSER (continued)

PAPERS AND PUBLICATIONS:

T. M. Dresser, "Feasibility of the Part Length Shield Assembly as a Flux Reduction Technique," NF-1111.05, CP&L, April 1983.

I. Z. Stone and T. M. Dresser, "Final Reload Design for H. B. Robinson Unit 2 Cycle 10, Batch XN-7, Region 13," PWR:043:82, ENC, December 1982.

R. R. Wojnarowski and T. M. Dresser, "FOLLOW (PNR07010) Documentation," NF-1101.01A, NF-2183.008, October 1982.

R. R. Wojnarowski, W. K. Cantrell, and T. M. Dresser, "H. B. Robinson Unit 2 Cycle 9 Startup Test Report," NF-908.01, CP&L, September 1982.

T. M. Dresser, "H. B. Robinson Unit 2 Cycle 8 Core Performance Report," NF-901.01, CP&L, April 1982.

T. M. Dresser, "CP&L's CDC Version of XTGPWR," NF-1101.01, CP&L, December 1981.

T. M. Dresser, "EXSPACK (PNR02010): The Estimated critical position/Xenon transient/Shutdown margin, PACKAGE Program and Users' Manual," NF-1106.01, CP&L, December 1980.

W. K. Cantrell, T. M. Dresser, and K. E. Kutcher, "H. B. Robinson Unit 2 Cycle 8 Startup and Operations Analysis," NF-1101.03, CP&L, October 1980.

W. K. Cantrell and T. M. Dresser, "Neutronics Analysis Techniques for H. B. Robinson Cycle 7 Design," NF-1101.03, CP&L, July 1980.

T. M. Dresser and W. K. Cantrell, "H. B. Robinson Unit 2 Cycle 7 Startup Test Report," NF-908.01, CP&L, September 1979.

W. K. Cantrell and T. M. Dresser, "H. B. Robinson Unit 2 Cycle 7 Startup and Operations Neutronics Design Analysis," NF-1101.03, CP&L, September 1979.

T. M. Dresser and W. K. Cantrell, "H. B. Robinson Unit 2 Cycle 7 Safety Analysis and Fuel Management Design Review," NF-401.1003, CP&L, April 1979.

T. M. Dresser and W. K. Cantrell, "H. B. Robinson Unit 2 Cycle 6 Startup Test Report," NF-908.01, CP&L, June 1978.

T. M. Dresser and W. K. Cantrell, "H. B. Robinson Unit 2 Cycle 6 Neutronics Design Evaluation," NF-401.0903, CP&L, February 1978.

JAMES C. ROBINSON

Vice President, Products Group

EDUCATION:

The University of Tennessee: B.S., Nuclear Engineering (1960)

The University of Tennessee: M.S., Nuclear Engineering (1961)

The University of Tennessee: Ph.D., Engineering Science (1966)

SUMMARY OF EXPERIENCE:

Dr. Robinson is a founder of TEC and is Vice President of Products. He also serves as a senior advisor in company instrumentation development activities, field services, and surveillance and diagnostics activities.

Prior to the founding of TEC, Dr. Robinson was a full Professor of Nuclear Engineering at The University of Tennessee. He served as a consultant to the Development Section of the Instrumentation and Controls Division of the Oak Ridge National Laboratory from 1964 to 1976. He played a significant role in establishing the reputation of that group as the center of excellence for noise analysis as applied to surveillance and diagnostic activities to the nuclear power industry.

In addition to surveillance and diagnostic activities, Dr. Robinson has been active in analytical methods development activities. This includes the application of finite element methods to nuclear analysis, variational approximate methods applied to integral parameters, sensitivity analysis, generalized perturbation theory, and the development of space-time kinetics codes.

Dr. Robinson also has contributed significantly to the determination of reactivity from (a) rod drops (inverse kinetics methods), (b) noise analysis, and (c) modified source multiplication techniques. The thrust of the development was toward large fast reactors, but the methodology is applicable to large thermal systems as well.

An internationally recognized expert in the fields of (a) methods development and (b) surveillance and diagnostics, Dr. Robinson is the author of many papers in these areas.

PROFESSIONAL ACHIEVEMENTS AND ACTIVITIES:

Member, American Society for Engineering Educators

Member and Fellow of American Nuclear Society

Reviewer for Nuclear Science and Engineering and other technical publications

Registered Professional Engineer, State of Tennessee

CLYDE W. CRAVEN, JR.

Vice President, Director of Engineering Programs

EDUCATION:

University of Tennessee: B.S., Nuclear Engineering (1961)

University of Tennessee: M.S., Nuclear Engineering (1963)

University of Tennessee: Ph.D., Engineering Sciences (1965)

SUMMARY OF EXPERIENCE:

At Technology for Energy Corporation (TEC), Dr. Craven is responsible for the overall marketing of engineered systems and services to electric utilities and the government sector.

Before employment at TEC, Dr. Craven was the Director of Engineering Technology at System Development Corporation. He directed a nationwide staff of the Systems Management and Engineering Division.

Previous to his employment at System Development Corporation, Dr. Craven was Vice President of Science Applications, Inc. (SAI). At SAI he was the program manager for their initial involvement in the Department of Energy's Strategic Petroleum Reserve (SRP) program which entailed direction of environmental impact statements for various alternative oil storage sites.

Before employment at SAI, Dr. Craven worked for the Oak Ridge National Laboratory (ORNL). At ORNL he was Director of the Regional and Urban Studies Department and was responsible for developing and directing engineering, political science, and legal research programs.

PROFESSIONAL ORGANIZATIONS, HONORS, AND AWARDS:

American Society Engineering Management
American Association for the Advancement of Science
American Nuclear Society
Listed in Who's Who in the Southwest

PUBLICATIONS:

Approximately 20 publications in the fields of systems analysis, nuclear cross sections, reactor physics, and regional environmental systems analysis.

ROBERT S. HOWELL

Supervisor, Nuclear Engineering Section

EDUCATION:

The University of Tennessee (Chattanooga): B.A., Physics (1971)

Texas A&M University: M.S., Health Physics/Nuclear Engineering (1972)

The University of Tennessee: Ph.D., Nuclear Engineering (1981)

SUMMARY OF EXPERIENCE:

At TEC Dr. Howell is the supervisor of the Nuclear Engineering Section and specializes in particle transport, criticality analysis, and radiation protection. He is responsible for development of Class A atmospheric dispersion and dose assessment model capabilities for nuclear power plant emergency response facilities, and has been actively involved in engineering analysis (including detector response correlations), for incorporation in emergency plans. He has served as the project engineer on several projects, including a recent CRBR hypothetical core disruptive accident analysis.

Prior to joining TEC, he was employed as a Staff Scientist with Science Applications, Inc. Responsibilities in the area of radiation shielding included such analyses as (1) the Clinch River Breeder Reactor Coolant Pipe Chaseway neutron streaming benchmark using the MORSE/BREESE Monte Carlo code, (2) discrete ordinates analysis of radiation dose rates within a proposed spent fuel storage facility, and (3) radiation dose assessments within the reactor containment building of WPPSS Units 1 and 4 using a mixed albedo-full transport Monte Carlo model. Typical criticality safety analyses included both unit and interaction analyses under accident and normal conditions for a variety of equipment and areas within the GE fuel fabrication plant.

As an applied Health Physicist at Oak Ridge National Laboratory, Dr. Howell's major responsibilities included providing general health physics services and consultation to research and craft personnel within the thermonuclear, reactor, and environmental science research areas; at the 86 in. cyclotron; and at various high-level hot cell facilities (fission products and curium) during cell decontamination.

ROBERT S. HOWELL (continued)

Prior to employment at ORNL, he served as the Senior Health Physicist for a joint NASA/USAF contractor at the Kennedy Space Center/Cape Canaveral Air Force Station. Major responsibilities included implementation of the radiation protection program; providing health physics services and technical consultation; preparation and review of technical documents and operating procedures pertaining to radiation protection; and preparation of contingency plans for use and launch of multi-hundred thousand curie plutonium sources.

PROFESSIONAL ACHIEVEMENTS AND ACTIVITIES:

American Nuclear Society

Health Physics Society

Society for Risk Analysis

HANCHANG H. CHEN (JOHN)

Nuclear Engineer

EDUCATION:

National Tsing Hua University: B.S., Nuclear Engineering (1970)

National Tsing Hua University: M.S., Nuclear Engineering (1973)

The University of Tennessee: Ph.D., Nuclear Engineering (1980)

SUMMARY OF EXPERIENCE:

Dr. Chen, as a nuclear engineer in the Nuclear Engineering Department, is responsible for engineering work involving the analyses of pressure vessel neutron fluence using AMPX, ANISN, and DOT-IV, the calculation of source term release rate calculations for atmospheric effluents, the assessment of radiological doses associated with emergency (NUREG-0654) and routine (10CFR50, Appendix I) conditions, and the development of an atmospheric dispersion and dose assessment capability for nuclear power plant emergencies.

Prior to his current position, Dr. Chen was a systems engineer in the Digital Systems Department. He was responsible for system software development, testing and integration for the computer-based gaseous effluent monitoring system.

Prior to assuming his current position, Dr. Chen was involved in research and development work which included designing and implementing a computer-based signal conditioning system; heat transfer and thermal analyses; implementing computer software for digital filtering; and developing and implementing a transient, 2-D discrete-element model for the simulation of radionuclide transport by groundwater flow.

Dr. Chen also had primary responsibility for a project involving groundwater migration of buried low-level radioactive waste. He has developed and implemented a computer code for plume element atmospheric transport and dispersion for the radiological dose assessment due to the release of radioactive gaseous effluents and later implemented an atmospheric dispersion computer code on a minicomputer.

Prior to joining TEC, Dr. Chen was an instructor of nuclear engineering at Tsing Hua University, Taiwan. His teaching and research fields included digital system and logic circuit design, minicomputer hardware and software systems, design and implementation of computer interfaces, and software consultation projects.

HANCHANG H. CHEN (continued)

PROFESSIONAL ACHIEVEMENTS AND ACTIVITIES:

Member of the Honor Society of Phi Kappa Phi

Member of the American Nuclear Society

PUBLICATIONS:

"Neutron Activation Analysis of Underground Water in the Wells of Blackfoot Disease Affected Area in Taiwan," J. Nucl. Sci. Taiwan, 1974.

"Sensitivity Analysis for Transport of Radionuclide in a Groundwater Flow System," Trans. Am. Nucl. Soc., Vol. 39, p. 498 (1981).

WILLIAM M. SIMPKINS

Staff Engineer

EDUCATION:

The University of Tennessee: B.S., Nuclear Engineering (1979)

The Univeristy of Tennessee: M.S., Nuclear Engineering (1981)

SUMMARY OF EXPERIENCE:

While at TEC, Mr. Simpkins' primary responsibilities have included performing both neutronics and thermal hydraulic calculations using large computer systems as well as software development for micro/mini computer based systems.

Mr. Simpkins has aided in the investigation of alternate reloading schemes for the Clinch River Breeder Reactor (CRBR) using a two dimensional neutron transport code. He has been responsible for determining the propagation of a neutron pulse through the CRBR shield using a one dimensional, time dependent neutron transport code. He has aided in the implementation of a two dimensional pebble bed reactor thermal hydraulic code on the IBM 360.

Mr. Simpkins has assisted in the software development for a PDP-11 based rotating machinery analysis system. He has been responsible for the software development for a microcomputer "INTEL 8080" based gaseous effluent radiation monitor. He performed both a thermal and a stress analysis for an irradiation capsule to be inserted into the Oak Ridge Reactor. He has aided in the analysis of experimental gamma thermometer data to determine the thermometer sensitivity.

Prior to joining TEC, Mr. Simpkins was employed as a research assistant at The University of Tennessee. He was responsible for software development for microcomputer-based surveillance systems. Programming languages included PDP-11 assembler and Fortran.

PROFESSIONAL ACHIEVEMENTS AND ACTIVITIES:

Member, Tau Beta Pi Honor Society

MARK L. WILLIAMS

Oak Ridge National Laboratory, Consultant

EDUCATION:

Louisiana State University: B.S., Engineering Science (1973)

Georgia Institute of Technology: M.S., Nuclear Engineering (1974)

The University of Tennessee: Ph.D., Nuclear Engineering (1979)

SUMMARY OF EXPERIENCE:

Performed shielding analysis for Fast Flux Test Facility, Clinch River Breeder Reactor, Gas Cooled Fast Reactor, and tokamak fusion reactor.

Performed LMFBR core physics studies.

Developed time-dependent perturbation theory for reactor burn-up calculations.

In charge of multi-year project funded by the Electric Power Research Institute (EPRI) to improve reactor physics codes used by utilities for LWR analysis.

Participated in study to determine radiation damage to PWR pressure vessels (Benchmarked LEPRICON to the Arkansas Nuclear One Reactor).

PROFESSIONAL ACHIEVEMENTS AND ACTIVITIES:

Tau Beta Pi, Phi Kappa Phi, American Nuclear Society, biographical listing in International Biography, Who's Who in the South and Southwest.

Thermal Reactor Data Testing Committee of Cross-Section Evaluation Working Group (CSEWG); reviewer for Nuclear Science and Engineering and Nuclear Technology journals; lecturer University of Tennessee short-course on "Computational Methods in Nuclear Engineering"; Contributing author to CRC Handbook of Nuclear Reactor Calculations; ORNL student coordinator for Engineering Physics Division.

APPENDIX B
AXFRAC Source Listing

AXFRAC SOURCE LISTING

Header section containing multiple rows of 'SS' characters and some numbers, likely a data header or separator.

Second header section with 'SS' characters and numbers, similar to the first section.

Third header section with 'SS' characters and numbers, continuing the header information.

```
PROGRAM AXFRAC (INPUT,OUTPUT,PUNCH,TAPES=INPUT,
1 TAPES=OUTPUT,TAPET=PUNCH)
CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCAXF
PURPOSE: 1. TO SPLIT SOURCE POWERS FOR INPUT TO DQYSDR ACCORDING
2. TO AXIAL DISTRIBUTIONS FROM XTC. (FOR MBR#2)
3. TO GENERATE R-Z AND R NEUTRON SOURCE DENSITIES ALONG
PLATS FOR INPUT TO DQY AND ANISH
INPUT: (TAPES)
1. BOTTOM RELATIVE POWERS FROM P007 FOR 37 XY SOURCES
2. TOP RELATIVE POWERS FROM P007 FOR 37 XY SOURCES
3. KAPPA/NU CORRECTIONS FOR LOWER SE OCTANT
4. # OF R,Z OF 2,Z# FUEL STARTS,Z# PLSA ENDS,Z# FUEL STOPS
R-MESH (CM), Z-MESH (CM)
5. XTC AXIAL DISTRIBUTIONS FROM CP&L
OUTPUT: (TAPES)
1. TOTAL, BOTTOM SFT, AND TOP SFT SOURCES FOR INPUT TO
DQYSDR X-Y 8*8 ARRAY AND R-Y 11*8 ARRAY
2. TOTAL, BOTTOM, AND TOP SOURCES FOR R-Z DOT (98*8 ARRAY)
3. ENERGY DEPENDENT R SOURCES FOR R ANISH
REFERENCE: W.K.CANTRELL 7/30/83
DIMENSION CARD(12),FB(28),FT(28),AX(24),XY(37),RT(23),VXY(37)
DIMENSION BXY(37),BRY(23),YXY(37),YRY(23),IXY(37),IRY(23),JRY(23)
DIMENSION AKNU(28)
DIMENSION AXO(87,24),DRMESH(100),DZMESH(100),PRMESH(125)
1 XZMESH(24),IRM(18),RZSDR(78,93),BRSDR(79),YRSDR(78),
2 DUM(24),CHI(58),ROUT(78),RZBX(37),RZTX(27)
3 PINB(8),PINT(8),CARD1(12)
DATA XY/37*0.0/
DATA RT/23*0.0/
DATA BRT/23*0.0/
DATA TRT/23*0.0/
DATA VXY/0.25,8*0.5,7*1.0,0.0,5,8*1.0,0.0,5,6*1.0,0.0,5,6*1.0/
DATA IXY/1,2,4,7,11,16,21,25,2,3,5,8,12,17,22,28,3,11,6,9,13,
1 18,23,4,12,20,10,14,19,24,5,13,21,14,15,20,89/
DATA IRT/99,10,13,14,15,16,17,18,19,20,21,22,23,24,25,28,7*1/
DATA JRY/89,27,21,28,35,8,14,22,29,36,7,15,23,30,8,18,7*1/
DATA IRM/1,2,5,8,13,18,25,32,41,50,59,68,75,82,85/
DATA PRMESH/0.71501,124*1.43002/
DATA XZMESH/24*15.24/
DATA CHI /4.075E-5,1.780E-4,3.388E-4,7.300E-4,2.528E-3,1.465E-3,
1 4.270E-3,2.885E-3,1.263E-2,3.148E-2,5.018E-2,3.227E-2,
2 7.71E-2,2.358E-2,2.267E-2,2.17E-2,1.95E-2,3.927E-3,
3 2.372E-2,3.388E-2,4.772E-2,3.388E-2,4.858E-2,4.858E-2,
4 4.308E-2,4.074E-2,7.384E-2,7.289E-2,2.993E-2,2.723E-2,
5 4.634E-2,3.768E-2,4.221E-2,4.082E-2,2.522E-2,7.653E-3,
6 1.653E-2,2.602E-2,1.74E-2,3.329E-3,3.917E-3,8.184E-4,
7 8.280E-4,1.935E-4,2.288E-4,8.048E-4,2.511E-4,2.921E-4,
8 8.182E-5,8.511E-5,2.685E-5,3.093E-5,2.728E-5,4.130E-5,
9 1.530E-6,0.0 /
READ (5,*) BXY
READ (5,*) TXY
READ (5,*) AKNU
READ (5,*) NR,NZ,NFS,NPLSA,NPE
READ (5,*) [DRMESH(1),1=1,NR],[DZMESH(1),1=1,NZ]
WRITE (6,470) BXY
```

UNIVERSITY COMPUTING COMPANY

	WRITE (6,480) TXV	AXF 130
	WRITE (6,490) AKNU	AXF 132
		AXF 134
		AXF 136
	COMPUTE CORE AVG RELATIVE DIST. (76-26 TOP-BOTTOM SPLIT)	AXF 138
		AXF 140
	DD 110 I=1,36	AXF 142
	XV(I)=BKV(I)=0.25+TXV(I)=0.75	AXF 144
	CONTINUE	AXF 146
110	CONVERT PDD7 RELATIVE DIST. TO MW7	AXF 148
	CORRECT FOR DIFFERENCES IN KAPPA/NU	AXF 150
		AXF 152
	AMW=2300.0/157.0	AXF 154
	DD 120 I=1,37	AXF 156
	RZBKV(I)=BKV(I)	AXF 158
	RZTXV(I)=TXV(I)	AXF 160
	J=IKV(I)	AXF 162
	BKV(I)+VKV(I)=XV(I)=AKNU(J)=AMW	AXF 164
	TXV(I)+VXV(I)=KV(I)=AKNU(J)=AMW	AXF 166
120	CONTINUE	AXF 168
		AXF 170
	PUT AVERAGE POWER IN R-Y ZONE 1	AXF 172
		AXF 174
	BRT(1)=3.1415927/8.0*70.0+70.0+12.5*(8.466+2.54)**2	AXF 176
	BRT(1)=157.0/8.0*(8.466+2.54)**2-BRT(1)	AXF 178
	BRT(1)=BRT(1)/((8.466+2.54)**2)=AKNU(6)=AMW	AXF 180
	TRT(1)=BRT(1)	AXF 182
		AXF 184
	CORRESPOND X-Y AND R-T SOURCES	AXF 186
		AXF 188
	DD 130 I=2,16	AXF 190
	J=JRT(I)	AXF 192
	BRT(I)=BKV(J)	AXF 194
	TRY(I)=TXV(J)	AXF 196
	IF (I.EQ.2.OR.I.EQ.5) BRT(I)=BRT(I)/2.0	AXF 198
	IF (I.EQ.2.OR.I.EQ.5) TRT(I)=TRT(I)/2.0	AXF 200
130	CONTINUE	AXF 202
		AXF 204
	READ AXIAL DISTRIBUTIONS AND SUM INTO BOTTOM AND TOP FRACTIONS	AXF 206
		AXF 208
	READ (6,500) CARD	AXF 210
	WRITE (6,510) CARD	AXF 212
	READ (6,500) ARD	AXF 214
	READ (6,500) ARD	AXF 216
	READ (6,500) ARD	AXF 218
	READ (6,500) ARD	AXF 220
	DD 140 I=1,26	AXF 222
	READ (6,5) M,J,AX	AXF 224
	WRITE (6,520) M,J,AX	AXF 226
	SUM=0.0	AXF 228
	DD 140 K=19,24	AXF 230
	SUM=SUM+AX(K)	AXF 232
140	CONTINUE	AXF 234
	FB(I)=SUM	AXF 236
	SUM=0.0	AXF 238
	DD 150 K=1,18	AXF 240
	SUM=SUM+AX(K)	AXF 242
150	CONTINUE	AXF 244
	FT(I)=SUM	AXF 246
160	CONTINUE	AXF 248
		AXF 250
	DISTRIBUTE RADIAL DISTRIBUTIONS BY AXIAL FRACTIONS AND SUM	AXF 252
		AXF 254
	DD 170 L=1,36	AXF 256
	J=IKV(L)	AXF 258
	BKV(L)=BKV(L)=FB(J)	AXF 260
	TXV(L)=TXV(L)+FY(J)	AXF 262
	XV(L)=BKV(L)+TXV(L)	AXF 264
170	CONTINUE	AXF 266
	F1=0.0	AXF 268
	DD 180 L=1,8	AXF 270
	F1=F1+FB(L)	AXF 272
	F2=F2+FT(L)	AXF 274
180	CONTINUE	AXF 276
	F1=F1/11.0	AXF 278
	F2=F2+FT(11)+FT(12)	AXF 280
	F2=F2/11.0	AXF 282
	BRT(1)=BRT(1)+F1	AXF 284
	TRT(1)=TRT(1)+F2	AXF 286
	RT(1)=TRT(1)+BRT(1)	AXF 288
	DD 190 L=2,16	AXF 290
	J=JRT(L)	AXF 292
	BRT(L)=BRT(L)+FB(J)	AXF 294
	TRY(L)=TRY(L)+FY(J)	AXF 296
	RT(L)=BRT(L)+TRT(L)	AXF 298
190	CONTINUE	AXF 300
		AXF 302
	COMPUTE R-Z PIN AND NODAL MESH	AXF 304
		AXF 306
	DD 200 I=1,126	AXF 308
	PRMESH(I)=PRMESH(I-1)+PRMESH(I)	AXF 310
200	CONTINUE	AXF 312
	XZMESH(I)=XZMESH(I)+DZMESH(NFS)	AXF 314
	DD 210 I=2,24	AXF 316
	XZMESH(I)=XZMESH(I-1)+XZMESH(I)	AXF 318
210	CONTINUE	AXF 320
		AXF 322
	ECHO R-Z INPUT	AXF 324
		AXF 326
	WRITE (6,530) PRMESH,XZMESH,(DRMESH(I),I=1,NR)	AXF 328
	WRITE (6,540) (DZMESH(I),I=1,NZ)	AXF 330
	WRITE (6,550) NR,NZ,NFS,NPLSA,WFE,CHI	AXF 332
		AXF 334
	READ QUARTER-ASSEMBLY AXIAL DISTRIBUTIONS AND INVERT	AXF 336
		AXF 338
	READ (6,500) CARD1	AXF 340
	WRITE (6,510) CARD1	AXF 342
	READ (6,500) ARD	AXF 344
	READ (6,500) ARD	AXF 346
	READ (6,500) ARD	AXF 348
	READ (6,500) ARD	AXF 350
	DD 220 I=1,87	AXF 352
	READ (6,520) M,MM,(AXO(I,J),J=1,24)	AXF 354
	WRITE (6,520) M,MM,(AXO(I,J),J=1,24)	AXF 356
220	CONTINUE	AXF 358
	DD 230 J=1,24	AXF 360
	K=25-J	AXF 362
	DUM(K)=AXO(I,J)	AXF 364
230	CONTINUE	AXF 366
	DD 240 J=1,24	AXF 368
	AXO(I,J)=DUM(J)	AXF 370
240	CONTINUE	AXF 372
250	CONTINUE	AXF 374
		AXF 376
		AXF 378
		AXF 380
	COMPUTE PDD SOURCE DENSITY ALONG FLAYS	AXF 382
		AXF 384
	DD 260 I=1,8	AXF 386
	J=IKV(I)	AXF 388
	PINB(I)=RZBKV(I)=AKNU(J)=AMW	AXF 390
	PINT(I)=RZTXV(I)=AKNU(J)=AMW	AXF 392

UCC UNIVERSITY COMPUTING CENTER

UNIVERSITY COMPUTING COMPANY

```

COMPUTE R-Z SOURCE
NEND=NPE-1
NREND=NR-1
DO 270 J=NFS,NEND
DO 270 L=1,24
IF [DZMESH(J).LT.XZMESH(L)] GO TO 280
270 CONTINUE
280 CONTINUE
DO 310 I=1,NREND
DO 290 M=1,125
IF [DMESH(I).LT.PRMESH(M)] GO TO 300
290 CONTINUE
300 CONTINUE

PICK AXIAL DISTRIBUTION BEHIND PLSA

IO=IRM(M/B+1)
IF [M.GT.114] GO TO 310
IF [M.LE.114] MP=8
IF [M.LE.98] MP=7
IF [M.LE.83] MP=6
IF [M.LE.68] MP=5
IF [M.LE.53] MP=4
IF [M.LE.38] MP=3
IF [M.LE.23] MP=2
IF [M.LE.8] MP=1

IF [L.LE.6] SPIN=PINB(MP)
IF [L.GT.6] SPIN=PIINT(MP)
VP=1.0/[(8.488-2.54)**2+16.24]
RZSOR(I,J)=SPIN*AXO(I,O,L)*VP
310 CONTINUE
320 CONTINUE

INTEGRATE FOR R SOURCE
I=NR-1
I2=N2-1
NPLSAM=NPLSA-1
DO 330 J=1,IR
DO 330 J=1,NPLSAM
BRSOR(I)+BRSOR(I)+RZSOR(I,J)=(DZMESH(J+1)-DZMESH(J))
330 CONTINUE
DO 340 J=NPLSA,NEND
TRSOR(I)+TRSOR(I)+RZSOR(I,J)=(DZMESH(J+1)-DZMESH(J))
340 CONTINUE
350 CONTINUE

WRITE RESULTS
WRITE (6,560) CARD
DO 360 I=1,36
J=IXY(I)
WRITE (6,570) I,BXY(I),TXV(I),XV(I),FB(J),FT(J)
360 CONTINUE
WRITE (6,570) I,BXY(37),TXV(37),XV(37)
TOTB=0.0
TOTY=0.0
TOTZ=0.0
DO 370 I=1,37
TOTB=TOTB+BXY(I)
TOTY=TOTY+TXV(I)
TOTZ=TOTZ+XV(I)
370 CONTINUE
WRITE (6,580) TOTB,TOTY,TOTZ
WRITE (6,590) CARD
I=1
WRITE (6,570) I,BRT(I),TRT(I),RT(I),F1,F2
DO 380 I=2,18
J=IXY(I)
WRITE (6,570) I,BRT(I),TRT(I),RT(I),FB(J),FT(J)
380 CONTINUE
DO 390 I=17,23
WRITE (6,570) I,BRT(I),TRT(I),RT(I)
390 CONTINUE
TOTB=0.0
TOTY=0.0
TOTZ=0.0
DO 400 I=1,23
TOTB=TOTB+BRT(I)
TOTY=TOTY+TRT(I)
TOTZ=TOTZ+RT(I)
400 CONTINUE
WRITE (6,580) TOTB,TOTY,TOTZ
WRITE (6,600) CARD
WRITE (6,610) BXY
WRITE (6,620) CARD
WRITE (6,610) TXV
WRITE (6,630) CARD
WRITE (6,610) XV
WRITE (6,640) CARD
WRITE (6,650) BRT
WRITE (6,660) CARD
WRITE (6,650) TRT
WRITE (6,670) CARD
WRITE (6,660) RT
WRITE (6,680) CARD
WRITE (6,690) ((RZSOR(I,J),I=1,IR),J=1,IZ)
WRITE (6,700) CARD
WRITE (6,490) ((TRSOR(I,J),I=1,IR),J=1,NPLSAM)
NZUP=I2-NPLSA
WRITE (6,710) IR,NZUP,IR
WRITE (6,720) CARD
NPLSA2=NPLSA-2
WRITE (6,730) IR,NPLSA2,IR
WRITE (6,690) ((RZSOR(I,J),I=1,IR),J=NPLSA,I2)
WRITE (6,740) CARD
DO 420 I=1,27
DO 410 J=1,IR
ROUT(J)=CHI(I)+BRSOR(J)
410 CONTINUE
WRITE (6,750) I,(ROUT(J),J=1,IR)
420 CONTINUE
WRITE (6,760) CARD
DO 440 I=1,27
DO 430 J=1,IR
ROUT(J)=CHI(I)+TRSOR(J)
430 CONTINUE
WRITE (6,750) I,(ROUT(J),J=1,IR)
440 CONTINUE
WRITE (6,770) CARD
DO 480 I=1,27
DO 450 J=1,IR
ROUT(J)=CHI(I)+TRSOR(J)+BRSOR(J)
450 CONTINUE
WRITE (6,750) I,(ROUT(J),J=1,IR)
460 CONTINUE
STOP

```

```

AXF 336
AXF 338
AXF 340
AXF 402
AXF 404
AXF 406
AXF 408
AXF 410
AXF 412
AXF 414
AXF 416
AXF 418
AXF 420
AXF 422
AXF 424
AXF 426
AXF 428
AXF 430
AXF 432
AXF 434
AXF 436
AXF 438
AXF 440
AXF 442
AXF 444
AXF 446
AXF 448
AXF 450
AXF 452
AXF 454
AXF 456
AXF 458
AXF 460
AXF 462
AXF 464
AXF 466
AXF 468
AXF 470
AXF 472
AXF 474
AXF 476
AXF 478
AXF 480
AXF 482
AXF 484
AXF 486
AXF 488
AXF 490
AXF 492
AXF 494
AXF 496
AXF 498
AXF 500
AXF 502
AXF 504
AXF 506
AXF 508
AXF 510
AXF 512
AXF 514
AXF 516
AXF 518
AXF 520
AXF 522
AXF 524
AXF 526
AXF 528
AXF 530
AXF 532
AXF 534
AXF 536
AXF 538
AXF 540
AXF 542
AXF 544
AXF 546
AXF 548
AXF 550
AXF 552
AXF 554
AXF 556
AXF 558
AXF 560
AXF 562
AXF 564
AXF 566
AXF 568
AXF 570
AXF 572
AXF 574
AXF 576
AXF 578
AXF 580
AXF 582
AXF 584
AXF 586
AXF 588
AXF 590
AXF 592
AXF 594
AXF 596
AXF 598
AXF 600
AXF 602
AXF 604
AXF 606
AXF 608
AXF 610
AXF 612
AXF 614
AXF 616
AXF 618
AXF 620
AXF 622
AXF 624
AXF 626
AXF 628
AXF 630
AXF 632
AXF 634
AXF 636
AXF 638
AXF 640
AXF 642
AXF 644
AXF 646
AXF 648
AXF 650
AXF 652
AXF 654
AXF 656

```

470	FORMAT (1M1// ECHO OF INPUT: // " BOTTOM X-Y DISTRIBUTION", 6F8.3/24X	AXF 668
475	1X, 6F8.3/24X, 7F8.3/24X, 7F8.3/24X, 6F8.3, 16X, F8.3)	AXF 669
480	FORMAT (// " TOP X-Y DISTRIBUTION", 6F8.3/24X, 7F8.3/24X, 7F8.3/24X	AXF 670
485	1, 7F8.3/24X, 6F8.3, 16X, F8.3)	AXF 671
490	FORMAT (// " KAPPA/NU CORRECTIONS", F8.3/24X, 2F8.3/24X, 3F8.3/24X,	AXF 672
495	4F8.3/24X, 5F8.3/24X, 6F8.3/24X, 4F8.3/24X, 2F8.3)	AXF 673
500	FORMAT (12A6)	AXF 674
510	FORMAT (//12A6//)	AXF 675
520	FORMAT (213, 2X, 6F8.5, 2(//, 6X, 6F8.5))	AXF 676
530	FORMAT (1M1// ECHO OF INPUT FOR R-2 SOURCES: // " PDO PIN MESH: //1AXF	AXF 677
535	12(10F8.3), 6F8.3, // " XTC 2 MESH: //4(6F8.3) // " DOT R MESH: //10(10F8.3)	AXF 678
540	FORMAT (// " DOT 2 MESH (BOTTOM TO TOP): //10(10F8.3/1)	AXF 679
550	FORMAT (// " DOT R MESHES " .15// " DOT 2 MESHES " .15// " FUEL STARTS "	AXF 680
555	115// " PLSA ENDS " .15// " FUEL ENDS " .15// " CHI (U235): //6(10X, 10E12.5/AXF	AXF 681
560	FORMAT (1M1, " OUTPUT BEGINS: //1M, 12A6// " FRACTIONS OF ASSEMBLY	AXF 682
565	10WER IN BOTTOM 3FT AND TOP 9FT OF CDRE // " XY SDR", Y10, "BOTTOM",	AXF 683
570	2T25, "TOP", T40, "TOTAL", T65, "FRAC-B", T70, "FRAC-T //)	AXF 684
575	FORMAT (16, T10, F8.4, T25, F8.4, T40, F8.4, T65, F8.4, T70, F8.4)	AXF 685
580	FORMAT (// " TOTAL", Y10, F8.4, T25, F8.4, T40, F8.4, T65, F8.4, T70, F8.4)	AXF 686
590	FORMAT (1M1// //1M, 12A6// " FRACTIONS OF R-THETA POWER IN BOTTOM 3FT	AXF 687
595	1 AND TOP 9FT OF CDRE // " R-T SDR", Y10, "BOTTOM", T25, "TOP", T40, "TOAXF	AXF 688
600	FORMAT (1M1// " CARDS FOR R-T DOTSOR: // " B // " // " 12A6, "BOTTOM")	AXF 689
610	FORMAT (6E12.5)	AXF 690
620	FORMAT (// " B // " // " 12A6, "TOP")	AXF 691
630	FORMAT (// " B // " // " 12A6, "TOTAL")	AXF 692
640	FORMAT (1M1// " 11 // " // " 12A6, "BOTTOM")	AXF 693
650	FORMAT (6E12.5)	AXF 694
660	FORMAT (// " 11 // " // " 12A6, "TOP")	AXF 695
670	FORMAT (// " 11 // " // " 12A6, "TOTAL")	AXF 696
680	FORMAT (1M1// " SOURCE CARDS FOR R-2 DOT: // " B // " // " 12A6, "TOTAL	AXF 697
685	1// ")	AXF 698
690	FORMAT (6E12.5)	AXF 699
700	FORMAT (1M1// " B // " // " 12A6, "BOTTOM")	AXF 700
710	FORMAT (13, "Z", 13"O", 12)	AXF 701
720	FORMAT (1M1// " B // " // " 12A6, "TOP")	AXF 702
730	FORMAT (13, "Z", 13"O", 12)	AXF 703
740	FORMAT (1M1// " SOURCE CARDS FOR ANISN : // " 17 // " // " 12A6, "BOTTOM	AXF 704
745	1// ")	AXF 705
750	FORMAT (" GROUP", 13(6E12.5))	AXF 706
760	FORMAT (1M1// " 17 // " // " 12A6, "TOP")	AXF 707
770	FORMAT (1M1// " 17 // " // " 12A6, "TOTAL")	AXF 708
END		AXF 709

MFA U.C.C. NDS/BE L684 V1.6.08.2 23/08/83
16.30.55.LASER4T FROM 0V
16.30.55.IP 00003848 WORDS - PILE INPUT , DC 04
16.30.55.LASER.P2.LASER
16.30.55.ACCOUNT.GKYTEC.-----
16.30.55.REWIND.OUTPUT
16.30.55.ROUTE.OUTPUT.DEF.TID=2D
16.30.55.UCC.BANNER.AXFRAC.SOURCE.LISTING
16.32.14.COPYBR.INPUT.AA
16.32.14.COPYBR.INPUT.BB
16.32.15.REWIND.AA.BB
16.32.15.COPYBR.BB.OUTPUT
16.32.15.BEGIN.PPRINT, 1=OUTPUT, N=AA, FORM=2UP.COP
16.32.15.IE51
16.32.17.AT CV= 124 EN=GLOBAL
16.32.20
16.32.20.COPYRIGHT, 1981, UNIVERSITY COMPUTING C
16.32.20.DMPANY
16.32.20.REPRODUCTION PROHIBITED UNLESS SPECIFIC
16.32.20.ALTY
16.32.20.AUTHORIZED BY SEPERATE WRITING.
16.32.20
16.32.20.RETURN, ZZZZZIN, ZZZZZPC, DAYFILE, DAYFIL
16.32.20.IFE(FILE(AA, AS), M1)
16.32.20.COPYBR, AA, ZZZZZIN
16.32.21.ENDIF, M1
16.32.21.COPY, ZZZZZP1, ZZZZZIN
16.32.21.RETURN, ZZZZZP1
16.32.21.UCC.BANNER(D=ZZZZZIN, .BIN, 64)
16.32.23.REWIND.OUTPUT
16.32.23.COPY.OUTPUT, ZZZZZIN
16.32.24.IFE((Y.AND.(5V.NE.YX0)), DLDDP)
16.32.24.SUMMARY
16.32.24.MS 68486 WORDS (68736 MAX USED)
16.32.24.MM 300008 MAX SCM
16.32.24.CPR 1.136
16.32.24.IDR .671
16.32.24.SRU 1.507
16.32.24.
16.32.24.DATE 08/09/83
16.32.24.DAYFIL

***** CYBER PAGE PRINT - END OF JOB LASER4T
***** CYBER PAGE PRINT - END OF JOB LASER4T
***** CYBER PAGE PRINT - END OF JOB LASER4T
***** CYBER PAGE PRINT - END OF JOB LASER4T
***** CYBER PAGE PRINT - END OF JOB LASER4T
***** CYBER PAGE PRINT - END OF JOB LASER4T
***** CYBER PAGE PRINT - END OF JOB LASER4T
***** CYBER PAGE PRINT - END OF JOB LASER4T
***** CYBER PAGE PRINT - END OF JOB LASER4T
***** CYBER PAGE PRINT - END OF JOB LASER4T