

October 17, 2023
Public Hearing

The current proposal is:

Preservation Department – Item 11, LPC-24-01774

**1000 Fifth Avenue – The Metropolitan Museum of Art –
Individual and Interior Landmark
Borough of Manhattan**

To testify virtually, please join Zoom

Webinar ID: 871 4086 7205

Passcode: 524349

By Phone: 1 646-558-8656 US (New
York) 877-853-5257 (Toll free) US
888 475 4499 (Toll free)

Note: If you want to testify virtually on an item, join the Zoom webinar at the agenda's "Be Here by" time (about an hour in advance). When the Chair indicates it's time to testify, "raise your hand" via the Zoom app if you want to speak (*9 on the phone). Those who signed up in advance will be called first.

**THE
MET**

THE METROPOLITAN
MUSEUM OF ART


**THE GREAT HALL
DIGITAL DISPLAY SCREENS**

NYC LANDMARKS
PRESERVATION COMMISSION
SUBMISSION


**BEYER
BLINDER
BELLE**


REVISION 1
SEPTEMBER 13, 2023



1. EXISTING CONDITIONS AND HISTORY



SHADED AREA SHOWS
EXTENT OF INTERIOR LANDMARK









GREAT HALL, LOOKING SOUTH, 1902

The space was used as an entrance hall and a gallery.



GREAT HALL, LOOKING SOUTH, 1907

McKim Mead and White altered the original skylights to provide more natural light.




GREAT HALL, LOOKING NORTH, 1917

New light fixtures were added.



GREAT HALL, LOOKING NORTH, C. 1940'S

The light post fixtures on the balcony parapet have been removed.



GREAT HALL, LOOKING NORTH, 1992

Kevin Roche John Dinkeloo Associates' renovation in 1970 for Museum's 100th Anniversary, including updating the lighting and adding a bold color palette. The current north and south coatrooms and their doorway openings into the Great hall were created at this time.




GREAT HALL, LOOKING NORTH, 2023



GREAT HALL, NORTH END, 2012


From the 1970's until 2020, there were three sets of admission ticket desks in the Great Hall, at each of the north, south and west entrances to the galleries.



TICKETING HALL, 2021


In 2020 the ticket desks were removed and a new ticketing hall was created under the balcony in the southwest quadrant in what had been a retail shop space.

2. PROPOSED DESIGN




1. PLAN - GREAT HALL

SCALE: 1/32" = 1' - 0"





PROPOSED SCREEN

PROPOSED SCREEN







PROPOSED SCREEN


PROPOSED SCREEN



SAMPLE DISPLAY SCREEN CONTENT







NORTH ARCADE - D107






PHOTO OF GREAT HALL WITH TEMPORARY DISPLAY SCREEN INSTALLATION UNDER THE FAR BALCONY, LOOKING SOUTH



PHOTO OF TEMPORARY DISPLAY SCREEN INSTALLATION, LOOKING NORTH




PHOTO OF TEMPORARY DISPLAY SCREEN INSTALLATION, LOOKING SOUTH




PHOTO OF TEMPORARY DISPLAY SCREEN INSTALLATION, LOOKING NORTH



PHOTO OF TEMPORARY DISPLAY SCREEN INSTALLATION AT SOUTH PASSAGE



PHOTO OF EXISTING TEMPORARY DISPLAY SCREEN INSTALLATION, LOOKING NORTH




PHOTO MONTAGE OF PROPOSED DISPLAY SCREEN INSTALLATION, LOOKING NORTH



PHOTO LOOKING INTO TICKETING HALL WITH EXISTING DISPLAY SCREENS



PHOTO OF EXISTING PORTABLE TICKET VENDING MACHINES



SAMSUNG

QMR-B Series UHD Commercial Displays

43"	QM43R-B	65"	QM65R-B
50"	QM50R-B	75"	QM75R-B
55"	QM55R-B	85"	QM85R-B

Upscale the ordinary to the extraordinary.

Slim 4K UHD signage with Dynamic Crystal Color

Experience exceptional Ultra HD picture quality with the Samsung QMR-B Dynamic Crystal Color commercial displays. The QMR-B series provides up to a billion colors so you see more of the picture, while true Ultra HD 4K color, 500-nit brightness and a non-glare panel mean messages will be more colorful and detailed than ever before. Additionally, UHD Intelligent Upscaling enhances standard and high-definition content to the best possible picture quality. With a minimalist slim design and a clean cable management solution, the QMR-B series is easy to install into any type of environment. And the QMR-B series' SMART Signage Platform 6.0 features an embedded media player, for easy content management and playback without an external set-back box or PC.



Contact Us: samsung.com/display

Key Features

- Slim and symmetrical design**
The QMR-B series' slim depth, narrow bezel and symmetrical design vastly simplify mounting and installation, and allow seamless integration into any environment.
- Clean cable management**
The back of the QMR-B series features stylish grooves that cables can be threaded through, keeping connections out of sight.
- 4K Bright, 4K, non-glare picture with 24/7 operation**
Ultra HD coupled with 500-nit brightness and a non-glare panel delivers true 4K color and clarity, 24/7.
- Dynamic crystal color**
Experience crystal-clear, lifelike color with up to a billion shades of color, 64 times more than conventional UHD displays. See every color in a rainbow or every shade in a spectacular sunset.
- Intelligent UHD upscaling**
UHD upscaling is a unique four-step picture improvement process that enhances the clarity and detail of standard and high-definition content to the best possible picture quality.
- HDR powered by HDR10+**
Experience superior brightness, greater detail in blacks, and authentic color with HDR powered by HDR10+.
- Powerful, all-in-one solution**
The embedded MagicINFO player S6, backed by a powerful Tizen operating system, allows for easy content management and playback without the need for a PC.
- Cisco Webex certified**
The QMR-B series displays have undergone the most stringent of all testing by the Webex Device Business Unit and are fully certified. Combined with Cisco WebEx®, the QMR-B series provides the ultimate conferencing solutions.
- MagicINFO**
Our leading-edge digital signage platform makes content management easier, more flexible and more robust.*
- 3-Year commercial warranty**
Samsung commercial displays are designed for reliable operation.


*License sold separately.

Samsung QMR-B Series UHD Commercial Displays

	QM43R-B	QM50R-B	QM55R-B	QM65R-B	QM75R-B	QM85R-B	
Panel	Diagonal Size	Class Measured 43"	50"	55"	65"	85"	
	Type	Edge LED BLU (UH1 (3840 x 2160))	Edge LED BLU (UH1 (3840 x 2160))	Edge LED BLU (UH1 (3840 x 2160))	Edge LED BLU (UH1 (3840 x 2160))	Edge LED BLU (UH1 (3840 x 2160))	Edge LED BLU (UH1 (3840 x 2160))
	Resolution	3840 x 2160	3840 x 2160	3840 x 2160	3840 x 2160	3840 x 2160	3840 x 2160
	Brightness (Typ.)	500	500	500	500	500	500
	Contrast Ratio (Typ.)	4000:1	4000:1	4000:1	4000:1	4000:1	4000:1
	Viewing Angle (H/V)	178 / 178	178 / 178	178 / 178	178 / 178	178 / 178	178 / 178
	Response Time (G to G)	8ms (Typ.)	8ms (Typ.)	8ms (Typ.)	8ms (Typ.)	8ms (Typ.)	8ms (Typ.)
	Display Colors	16.7M (True Display)	16.7M (True Display)	16.7M (True Display)	16.7M (True Display)	16.7M (True Display)	16.7M (True Display)
	Color Gamut	120% (CIE94)	120% (CIE94)	120% (CIE94)	120% (CIE94)	120% (CIE94)	120% (CIE94)
	Color Gamut	92% (DCI-P3, CIE 1976)	92% (DCI-P3, CIE 1976)	92% (DCI-P3, CIE 1976)	92% (DCI-P3, CIE 1976)	92% (DCI-P3, CIE 1976)	92% (DCI-P3, CIE 1976)
Panel Orientation	Landscape / Portrait	Landscape / Portrait	Landscape / Portrait	Landscape / Portrait	Landscape / Portrait	Landscape / Portrait	
Sound	Speaker Type	Built in Speaker (10W + 10W)	Built in Speaker (10W + 10W)	Built in Speaker (10W + 10W)	Built in Speaker (10W + 10W)	Built in Speaker (10W + 10W)	
	Non-Glare Panel	Yes	Yes	Yes	Yes	Yes	
Special Certifications	IP5K Rating	Yes	Yes	Yes	Yes	Yes	
	Cisco Webex Compatible	Yes	Yes	Yes	Yes	Yes	
	Connectivity	DisplayPort 1.2 (1)	DisplayPort 1.2 (1)	DisplayPort 1.2 (1)	DisplayPort 1.2 (1)	DisplayPort 1.2 (1)	DisplayPort 1.2 (1)
		HDMI 2.0 (2)	HDMI 2.0 (2)	HDMI 2.0 (2)	HDMI 2.0 (2)	HDMI 2.0 (2)	HDMI 2.0 (2)
	Input	VIDEO	HDMI 2.0 (2)	HDMI 2.0 (2)	HDMI 2.0 (2)	HDMI 2.0 (2)	HDMI 2.0 (2)
		HDCP	HDCP2.2	HDCP2.2	HDCP2.2	HDCP2.2	HDCP2.2
		Audio	Stereo Mini Jack, HDMI / Audio (Common)	Stereo Mini Jack, HDMI / Audio (Common)	Stereo Mini Jack, HDMI / Audio (Common)	Stereo Mini Jack, HDMI / Audio (Common)	Stereo Mini Jack, HDMI / Audio (Common)
		USB	USB 2.0 x 2	USB 2.0 x 2	USB 2.0 x 2	USB 2.0 x 2	USB 2.0 x 2
	Output	Audio	Stereo Mini Jack	Stereo Mini Jack	Stereo Mini Jack	Stereo Mini Jack	Stereo Mini Jack
		External Control	RS232C (In / Out) thru Stereo Jack, RS45	RS232C (In / Out) thru Stereo Jack, RS45	RS232C (In / Out) thru Stereo Jack, RS45	RS232C (In / Out) thru Stereo Jack, RS45	RS232C (In / Out) thru Stereo Jack, RS45
Power	Power Supply	Internal AC 100 - 240 V, 50 / 60 Hz 110 / 74	Internal AC 100 - 240 V, 50 / 60 Hz 145 / 108	Internal AC 100 - 240 V, 50 / 60 Hz 130	Internal AC 100 - 240 V, 50 / 60 Hz 165	Internal AC 100 - 240 V, 50 / 60 Hz 210	
	Power Consumption	BTU (Max) 375.1	384.4	481.6	618.9	787.7	
	BTU (Max) Sleep Mode	0.5	0.5	0.5	0.5	0.5	
	Dimensions (mm / inch)	Set 967.5 x 527.7 x 48.5 / 38.09" x 20.76" x 1.91"	1297.4 x 643.9 x 46.3 / 51.08" x 25.35" x 1.82"	1293.1 x 707.9 x 46.3 / 50.87" x 27.87" x 1.82"	1453.9 x 811.0 x 46.3 / 57.24" x 32.71" x 1.82"	1681.1 x 963.1 x 49.7 / 66.19" x 37.92" x 1.96"	1897.8 x 1080.8 x 56.7 / 74.72" x 42.51" x 2.23"
Mechanical Spec	Package	1095 x 616 x 151 / 42.71" x 24.27" x 5.94"	1402 x 858 x 165 / 55.17" x 33.77" x 6.50"	1402 x 858 x 165 / 55.17" x 33.77" x 6.50"	1671 x 973 x 181 / 65.81" x 38.31" x 7.13"	2090 x 1267 x 260 / 82.30" x 49.87" x 10.24"	
	Weight (kg / lb)	Set 10 kg / 22.05 lb	13.1 kg / 29.32 lb	13.1 kg / 29.32 lb	16.9 kg / 37.26 lb	21.9 kg / 48.26 lb	
Operation	VESA Mount	200 x 200	200 x 200	200 x 200	400 x 400	400 x 400	
	Bezel Width (Top / Sides / Bottom) (mm)	9.2mm (T/S), 11.2mm (B)	9.2mm (T/S), 11.2mm (B)	9.2mm (T/S), 11.2mm (B)	9.2mm (T/S), 11.2mm (B)	11.5mm (T/S), 12.5mm (B)	
Features	Key	Temperature Sensor, Pivot Display, Clock Battery (168 Hrs. Clock Keeping), Built-in Speaker (10W x 2), Video Wall, Daily Chain, HDCP 2.2, 4EA, HDCP1.4, 7EA, IPSK Rating, Wi-Fi Auto Source Switching and Recovery, LFD Home UI, Button Lock, Hot Key Option, Plug and Play (Initial Setting)	Temperature Sensor, Pivot Display, Clock Battery (168 Hrs. Clock Keeping), Built-in Speaker (10W x 2), Video Wall, Daily Chain, HDCP 2.2, 4EA, HDCP1.4, 7EA, IPSK Rating, Wi-Fi Auto Source Switching and Recovery, LFD Home UI, Button Lock, Hot Key Option, Plug and Play (Initial Setting)	Temperature Sensor, Pivot Display, Clock Battery (168 Hrs. Clock Keeping), Built-in Speaker (10W x 2), Video Wall, Daily Chain, HDCP 2.2, 4EA, HDCP1.4, 7EA, IPSK Rating, Wi-Fi Auto Source Switching and Recovery, LFD Home UI, Button Lock, Hot Key Option, Plug and Play (Initial Setting)	Temperature Sensor, Pivot Display, Clock Battery (168 Hrs. Clock Keeping), Built-in Speaker (10W x 2), Video Wall, Daily Chain, HDCP 2.2, 4EA, HDCP1.4, 7EA, IPSK Rating, Wi-Fi Auto Source Switching and Recovery, LFD Home UI, Button Lock, Hot Key Option, Plug and Play (Initial Setting)	Temperature Sensor, Pivot Display, Clock Battery (168 Hrs. Clock Keeping), Built-in Speaker (10W x 2), Video Wall, Daily Chain, HDCP 2.2, 4EA, HDCP1.4, 7EA, IPSK Rating, Wi-Fi Auto Source Switching and Recovery, LFD Home UI, Button Lock, Hot Key Option, Plug and Play (Initial Setting)	
	Special	Processor On-Chip Cache Memory Clock Speed	Processor On-Chip Cache Memory Clock Speed	Processor On-Chip Cache Memory Clock Speed	Processor On-Chip Cache Memory Clock Speed	Processor On-Chip Cache Memory Clock Speed	
Certification	Safety	Class B	Class B	Class B	Class B	Class B	
	EMC Environment	ENERGY STAR 8.0, EPEAT	ENERGY STAR 8.0, EPEAT	ENERGY STAR 8.0, EPEAT	ENERGY STAR 8.0, EPEAT	ENERGY STAR 8.0, EPEAT	
Accessories	Included	STN-L455F WNN40705E (Landscape Only) WNN7050E CML4000K	STN-L455F WNN40705E (Landscape Only) WNN7050E CML4000K	STN-L455F WNN40705E (Landscape Only) WNN7050E CML4000K	STN-L455F WNN42775E (Landscape Only) WNN7050E CML4500K	N/A WNN82005F, WNN82005G WNN7050E CML4500K	
	Optional	Stand Mount	Specialty	Specialty	Specialty	Specialty	
Service	Warranty	3 Years (Parts/Labor/Backlight)	3 Years (Parts/Labor/Backlight)	3 Years (Parts/Labor/Backlight)	3 Years (Parts/Labor/Backlight)	3 Years (Parts/Labor/Backlight)	

Connectivity

1. USB1 (1.0A)
2. RJ45
3. RS232C In
4. HDMI In 1 (ARC)
5. HDMI In 2
6. DP In
7. USB 2.0 (0.5A)
8. HDMI Audio In
9. Audio Out
10. RS232C Out
11. IR In



ProCare

- Samsung ProCare Indoor Display Solutions**
- Fast Track with White Glove Next Business Day® Service
 - Includes tech-assisted exchange of display; Technician removes original unit, installs replacement and ships non-working unit to Samsung
 - Fast Track Next Business Day Exchange
 - Return shipping label provided, customer returns original unit in new unit's box
 - Available on sizes 32"-85"
 - 3-5 year terms available

Learn More samsung.com/display samsung.com/business_insights.samsung.com
Product Support 1-866-SAM4BIZ
Follow Us [youtube.com/samsungbizusa](https://www.youtube.com/samsungbizusa) [@SamsungDisplay](https://twitter.com/SamsungDisplay) [@SamsungBizUSA](https://www.facebook.com/SamsungBizUSA) [samsungbusinessusa](https://www.instagram.com/samsungbusinessusa)



©2021 Samsung Electronics America, Inc. Samsung is a registered mark of Samsung Electronics Corp., Ltd. Specifications and design are subject to change without notice. Non-metric weights and measurements are approximate. Simulated screen images. All brand, product, service names and logos are trademarks and/or registered trademarks of their respective manufacturers and companies. See samsung.com for detailed information. Printed in USA. DIGSG-QMRB-SPEC-NDV21T

*For Next Business Day exchange and installation, calls must be received by 3 p.m. eastern time




P-Series Low-Profile Flat Mount for Flat Panel Displays

ITEMS: P2642F, P4263F, P5080F, P4263FP
WEIGHT CAPACITY: 130 - 300 LB / 59 - 136 KG.

The P-Series Low-Profile Flat Mounts are for flat panels weighing 130-300 lb. They feature post-installation leveling, lateral alignment, locking security sections and an open mounting frame for easy access to power sources and cables. Products in the P-Series Flat Mount line include the P2642F, P4263F, P5080F and P4263FP* mounts.

- FEATURES**
- 1 Holds flat panel displays less than 1 inch from the wall
 - 2 Post-installation leveling system
 - 3 Lock-It™ security barrel included
- Built-in lateral shift
 - Mounting kit includes wood, concrete and steel stud attachment hardware
 - P5080F model is built of heavy-duty material to withstand the weight of larger displays



P4263FP available in portrait mode for digital menu board applications

Accessories available for shelving and in-wall storage options

Lock-It™ Security barrels to deter removal of flat panel displays

1 (800) 368-9700 | ORDERS@PREMIERMOUNTS.COM PREMIERMOUNTS.COM



The Metropolitan Museum of Art
The Great Hall Digital Displays

Display Screen and Mounting Equipment Information

October 17, 2023
Public Hearing

The current proposal is:

Preservation Department – Item 11, LPC-24-01774

**1000 Fifth Avenue – The Metropolitan Museum of Art –
Individual and Interior Landmark
Borough of Manhattan**

To testify virtually, please join Zoom

Webinar ID: 871 4086 7205

Passcode: 524349

By Phone: 1 646-558-8656 US (New
York) 877-853-5257 (Toll free) US
888 475 4499 (Toll free)

Note: If you want to testify virtually on an item, join the Zoom webinar at the agenda's "Be Here by" time (about an hour in advance). When the Chair indicates it's time to testify, "raise your hand" via the Zoom app if you want to speak (*9 on the phone). Those who signed up in advance will be called first.