

Portable Units Air Conditioners

 **Midea**
Air Conditioning Systems



EasyCool • Easy Operation • Easy Installation

Model
MPPHB-12CRN1-BH9
12,000 BTU

Easy and safe installation accessories included.
115v Applications.

See reverse for product information.



OLDACH
REFRIGERATION, AIR CONDITIONING & VENTILATION SUPPLIER

MPPHB-12CRN1-BH9

Power supply		Ph-V-Hz	115V,1Ph
Cooling	Capacity	Btu/hr	12000
	Input	W	1350
	Current	A	11.7
	EER	W/W	2.60
Moisture Removal (26.7/20.9°C)		Btu/W.h	8.90
Moisture Removal (30/27.1°C)		L/h	1.67
Moisture Removal (35/28.3°C)		L/h	0
Starting current		L/h	2.38
		A	50
Compressor	Model		ASM106E4UCZD
	Brand		GMCC
	Capacity	W	3260
	Input	W	1068
	Rated current(RLA)	A	9.68
	Locked rotor Amp(LRA)	A	55
	Thermal protector		UP3-67
	Thermal protector position		INTERNAL
	Capacitor	uF	70.0
	Refrigerant oil	ml	VG74/300
Indoor side fan motor	Model		YKTS-90-4-14-1
	Input	W	158.0
	Capacitor	uF	15
	Speed(hi/mi/lo)	r/min	1140/1070/970
	Capacitor class		P0
Insulation class			B
Evaporator	a.Number of rows		3.0
	b.Tube pitch(a)x row pitch(b)	mm	21x13.37
	c.Fin spacing	mm	1.3
	d.Fin type (code)		Hydrophilic aluminum
	e.Tube outside dia.and type	mm	Φ7Inner groove tube
	f.Coil length x height x width	mm	240x231x40.11
	g.Number of circuits		2
Indoor side air flow (Hi/Mi/Lo)		m3/h	310/0/0
		CFM	182.35/III
Indoor side noise level(Hi/Mi/Lo)		dB(A)	55.5/0/52.7
Condenser	a.Number of rows		3.0
	b.Tube pitch(a)x row pitch(b)	mm	14.5x12.56
	c.Fin spacing	mm	1.2
	d.Fin type (code)		Unhydrophilic aluminium
	e.Tube outside dia.and type	mm	Φ5Inner groove tube
	f.Coil length x height x width	mm	240x261x37.68
	g.Number of circuits		2
Outdoor side noise level (Hi)		dB(A)	61
Refrigerant type		ozs	R410A
Plug type			LCDI(5-15P)
Power cord type			14#x3
Power cord length		mm	1900
Power cord length		ft	6.23
Control type			(Remote Control)
Operation temp (room temp.)			17-35
		°F	/
Dimension (W*D*H)		mm	355x345x703
		in	13.98x13.58x27.68
Packing (W*D*H)		mm	400x380x870
		in	15.75x14.96x34.25
Net/Gross weight		Kg	25.3/29
		lb	55.78/63.93
Loading quantity 20' /40' /40'HQ		Pieces	174/356/534

Portable Units

Air Conditioners

Specifications Sheet

