

VersaLink B605 Multifunction Printers are built on Xerox<sup>®</sup> ConnectKey<sup>®</sup> Technology. For more information, go to **www.connectkey.com**.

System Specifications	B605/S	B605/X	B605/XL
<b>One-sided Speed</b> A4 / 210 x 297 mm	Up to 55.5 ppm black and wh	ite	
<b>Two-sided Speed</b> A4 / 210 x 297 mm	Up to 49.3 ppm black and wh	ite	
Monthly Duty Cycle <sup>1</sup>	Up to 250,000 pages / month	1	
Recommended Average Monthly Print Volume <sup>2</sup>	Up to 20,000 pages		
Hard Drive	320 GB HDD		
Processor	1.05 GHz ARM Dual Core		
Memory	2 GB		
Connectivity		۲, High-speed USB 3.0, Wi-Fi 802. eless connections supported), NFC	11n and Wi-Fi Direct with optional Wi-Fi C Tap-to-Pair
Controller Features	App Gallery, Xerox <sup>®</sup> Standard	Accounting Tool, Network Accou	rox Extensible Interface Platform®, Xerox Inting Enabled, Role Based Permissions, d from the user interface and print driver)
User Interface Languages		an, Spanish, Brazilian Portuguese Ilish, Czech, Hungarian, Romaniar	, Russian, Dutch, Swedish, Danish, Finnish, 1, Catalan, Ukrainian, Croatian
Device Specifications			
Electrical Requirements			
Europe and Other Geographies	Voltage: 220-240 VAC +/- 10 Frequency: 50/60 Hz +/- 3 % H		
Power Consumption			
Continuous Print <sup>3</sup>	950 watts or less		
Ready (Standby) <sup>3</sup>	79 watts or less		
Energy Saver (Sleep Mode) <sup>3</sup>	1.1 watts or less		
Power Off Mode <sup>3</sup>	0.3 watts or less		
Operating Environment			
Required Temperature Range (Storage)	0° to 35° C		
Required Temperature Range (Operating)	10 to 32° C		
Required Relative Humidity	15% to 85%		

Sound Power Levels				
Running Standby	70 dB(A) or less 43 dB(A) or less			
<b>Sound Pressure Levels</b> Running Standby	58.3 dB(A) or less 29 dB(A) or less			
Boot Time (from Off to UI Ready)	Less than 79 seconds			
Warm-up Time (from Sleep to UI Ready)	Less than 47 seconds			
Dimensions and Weight (Unpackaged)	Width Depth Height Weight			
B605/S and B605/X	470 mm	502.8 mm	643.7 mm	30.5 kg
B605/XL	470 mm	502.8 mm	843.7 mm	32.5 kg
B605/XL with Finisher	470 mm	502.8 mm	843.7 mm	39.3 kg
B605/XL with Mailbox	470 mm	502.8 mm	843.7 mm	37.8 kg
B605/S and B605/X with High Capacity Feeder	724.2 mm	772.1 mm	1,102.7 mm	50.2 kg
B605/XL with High Capacity Feeder	724.2 mm	772.1 mm	1,302.7 mm	52.2 kg
550-sheet Tray	420 mm	464.5 mm	123 mm	6.6 kg
2,000-sheet High Capacity Feeder (includes Caster Base)	724.2 mm	772.1 mm	459 mm	19.7 kg
Stand (includes Caster Base)	724.2 mm	772.1 mm	336 mm	16.6 kg
Caster Base	724.2 mm	772.1 mm	90 mm	8.5 kg
Mailbox	450.8 mm	477.6 mm	248.0 mm	5.3 kg
Finisher	450.8 mm	411.0 mm	248.0 mm	6.8 kg
Dimensions and Weight (Packaged)	Width	Depth	Height	Weight
B605/S and B605/X	594 mm	655 mm	789 mm	38 kg
B605/XL	594 mm	655 mm	996 mm	43 kg
550-sheet Tray	535 mm	584 mm	248 mm	8.5 kg
2,000-sheet High Capacity Feeder(includes Caster Base)	568 mm	663 mm	711 mm	38 kg
Stand (includes Caster Base)	584 mm	629 mm	597 mm	28 kg
Caster Base	585 mm	619 mm	330 mm	18 kg
Mailbox	573 mm	518 mm	386 mm	7.8 kg
Finisher	573 mm	398 mm	386 mm	8.8 kg
Wireless Network Adapter (Wi-Fi Kit)	188 mm	136 mm	55 mm	0.1 kg
Certifications			·	·
To view the latest list of certif	ications, go to www.xerox.	com/OfficeCertifications.		

Print		
First-print-out Time	As fast as 7.5 seconds	
Print Resolution	Up to 1200 x 1200 dpi	
Page Description Languages	PCL <sup>®</sup> 5e, 6 PDF XPS TIFF JPEG HP-GL Adobe <sup>®</sup> PostScript <sup>®</sup> 3 <sup>™</sup>	
Maximum Print Area	4 mm from lead edge of paper, 2 mm from Side and Trail edges of paper	
Print Features	Application Defaults Banner Pages Enable / Disable Bi-directional Real-time Status Booklet Layout Draft Mode Fit to new paper size Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) Job Monitoring (Client or Local User Interface) LAN Fax (requires Fax Kit) N-up Page Layout (up to 16 pages per sheet) Paper Selection by Attribute Personal Print Print Around Enable / Disable Print from USB Sample Set Saved Job Scaling Secure Print Skip Blank Pages Special Pages (exception page programming: covers, inserts, exceptions pages) Store and Recall Driver Settings Stored Jobs Deletion Two-sided Printing (as default) Watermark (predefined and custom) Xerox® Earth Smart Driver Settings	
Print from USB	Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A	
Operating Systems	Windows® 7, 8, 8.1, 10         Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016         macOS® 10.11, 10.12, 10.13         Citrix®         Redhat® Enterprise Linux®         Fedora Core         IBM® AIX®         HP-UX®         Oracle® Solaris         SUSE®         SAP®         Note: For information about supported versions for the above operating systems, please visit our Drivers & Downloads page and specify your device at www.support.xerox.com	
Fonts	PostScript fonts: 136 PCL fonts: 83	
Xerox <sup>®</sup> Mobile Express Driver <sup>®</sup>	Makes it easy for mobile users to find, use and manage Xerox <sup>®</sup> and non-Xerox <sup>®</sup> devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favourite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.	

Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox <sup>®</sup> and non-Xerox <sup>®</sup> devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.	
Xerox <sup>®</sup> Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.	
Сору		
Document Scanner	100-sheet Single-pass Duplex Automatic Document Feeder (DADF)	
Maximum Scan Area	Platen: Up to 215.9 mm x 355.6 mm DADF: Up to 215.9 mm x 355.6 mm	
Simplex Copy Speed	Up to 58 cpm (copies per minute) A4 black and white	
Duplex Copy Speed	Up to 52.2 cpm A4 black and white	
First-copy-out Time	As fast as 5.8 seconds	
Sides (input:output)	1:1, 1:2, 2:2 and 2:1	
Quantity	1 to 999	
Resolution (max.)	Up to 600 x 600 dpi	
Reduction / Enlargement	Variable zoom from 25% to 400% in 1% increments	
Concurrency	Concurrent scanning and printing	
Copy Features	Annotation (Page Numbers, Comments, Date Stamp, Bates Stamping)* Automatic Background Suppression Book Copying with Centre Erase Booklet Copying* Collation Darkness Control Edge Erase Front Cover ID Card Copy Image Enhancement Lighten/Darken N-up Reduce / Enlarge 25 % to 400 % Image Shift Original Orientation Original Size Original Type Page Layout Sample Copy Saturation Sharpness	
Scan		
Capability	Black and white and colour scanning	
Concurrency	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs	
Simplex Input Speed	Black and white: Scan up to 55 ipm A4 Colour: Scan up to 52 ipm A4	
Duplex Input Speed	Black and white: Scan up to 55 ipm A4 Colour: Scan up to 52 ipm A4	
Resolution	600 x 600 dpi	
Bit Depth	24-bit colour / 8-bit grayscale	

Maximum Scan Area	Platen: Up to 215.9 x 355.6 mm Document Feeder: Up to 215.9 x 355.6 mm	
Network Filing Protocols	FTP SMTP SMB	
File Formats	JPG TIFF (single and multi-page) XPS (single and multi-page) PDF (single and multi-page) Searchable PDF via Optical Character Recognition (OCR) Password-protected PDF Linearised PDF (set via embedded web server) and PDF/A	
Scan Driver Compatibility (Network Only)	WIA TWAIN	
Supported Scan Destinations	Scan to Home Scan to USB Scan to Email Scan to Network (FTP or Browse SMB)	
Network Scanning – Softwa	re Solutions	
Xerox® ConnectKey® Apps (Found at the Xerox® App Gallery)	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey Apps to the ConnectKey-enabled device.	
Fax (Available on X and XL	configurations; not available on S configuration)	
Fax <sup>4</sup>		
Fax Speed	33.6 Kbps	
Memory	4 MB	
Resolution	Standard 200x100 dpi, Fine 200x200 dpi, Super Fine 300x300, 400x400, 600x600 dpi	
Compression	MH/MR/MMR/JBIG	
Fax Features	Walk-up Fax, LAN Fax, Direct Fax, Fax Forward to Email Fax dialing via Unified Address Book (up to 2,000 contacts)	
Mobile Solutions and Mobil	e Device Apps	
Apple <sup>®</sup> AirPrint <sup>®</sup>	Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.	
Google Cloud Print™	Google Cloud Print connects print devices to the web, enabling users to print the applications they use every day from smartphones, tablets, Chromebook™ notebook computers and any other web-connected device.	
@PrintByXerox	@PrintByXerox is a free service that allows secure printing from any email-enabled device (computer, phone, tablet, iOS, Android™, Google® Chromebook™ and more) to a Xerox® printer or MFP using a single email address with no IT intervention. No training is needed. End-users simply send attachments to the email address, and release them at the MFP panel.	
Xerox <sup>®</sup> Print Service Plug- in for Android™ (Free at Google Play™ Store)	The Xerox <sup>®</sup> Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play <sup>™</sup> store.	
Xerox® Mobile Link App (Free at Google Play™ Store and Apple® App Store)	The Xerox <sup>®</sup> Mobile Link App allows you to scan, email and fax from your phone or tablet by connecting with our multifunction printers and send data to and print data from cloud storage. It is easy to create Mobile Link One-Touch Workflows between a mobile device and a multifunction printer. Using a manual address or QR code identification for pairing, automatic device discovery makes it easy to find and pair a mobile device with a nearby Xerox <sup>®</sup> multifunction printer.	

Xerox <sup>®</sup> Print Management and Mobility Suite, Xerox <sup>®</sup> Print Management and Mobility Service	Xerox <sup>®</sup> Print Management and Mobility Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version and with a cloud based-version of this solution.	
Security		
Security Features	Access Controls AES 256-bit Encryption Audit Log Certificate Path Validation Certificate Path Validation Certificate Revocation List (CRL)/Status Protocol (OCSP) Detection of external programme falsification (XCP Plug-in) Cisco® Identity Services Engine (ISE) Integration Domain Filtering FIPS 140-2 Firmware Verification Immediate Disk Overwrite IP Address Filtering IPsec Network Authentication Port Filtering Pre-installed Self-Signed Certificates Role Based Permissions Secure Email Secure Fax Secure Fax Secure Print Security Certificate Management Smart Card Enablement (CAC/PIV/.NET) SNMPv3 Status Protocol (OCSP) TLS/SSL	
Accounting		
Xerox <sup>®</sup> Standard Accounti	ng / Network Accounting (Standard)	
Tracking	Copy, Print, Fax, Scan and Email usage	
Accounting	Xerox <sup>®</sup> Standard Accounting Tool Up to 9,999 User Accounts Up to 500 General accounts Network Accounting (Job Based Accounting) Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD Up to 14,000 accounting records (transactions)	
Features	Administrator can manage the feature via the Embedded Web Server.	
Accounting Options – Net	work Accounting (Allows central server to manage all accounting)	
	<ul> <li>Enhanced network accounting with up to the minute data on how the system is being used</li> <li>Comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax</li> <li>Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com</li> <li>Security enhancements include simultaneous support for HTTP/HTTPS protocols</li> <li>Device requests account authentication from third party server enabling larger databases of users and accounts</li> <li>Accept Authentication Login at control panel and pass to third party Networking Account</li> <li>Interface with third party accounting terminal for accounting user interface</li> </ul>	

Paper Handling			
Document Feeder			
Capacity <sup>5</sup>	Single-pass Duplex Automatic Document Feeder (DADF): 100 sheets		
Sizes	Custom sizes: 140 x 140 mm to 216 x 356 mm		
<b>Weights</b> One-sided: Two-sided:	60 to 128 gsm 60 to 128 gsm		
Bypass Tray			
Capacity <sup>5</sup>	150 sheets		
Sizes	Custom sizes: 76 x 127 mm to 216 x 356 mm		
<b>Weights</b> One-sided: Two-sided:	60 to 220 gsm 60 to 176 gsm		
Media Types	Plain Paper Bond Punched Pre-Printed Recycled Envelopes Labels Lightweight Card Stock Card Stock Letterhead Custom 1 - 5		
Tray 1			
Capacity <sup>5</sup>	550 sheets		
Sizes	Custom sizes: 76.2 x 190 mm to 216 x 356 mm		
<b>Weights</b> One-sided: Two-sided:	60 to 220 gsm 60 to 176 gsm		
Media Types	Pre-Printed Recycled Envelopes (Tray 1 only) Labels Lightweight Card Stock Card Stock Letterhead Custom 1 - 5		
Up to 4 Additional Trays (Optional)			
Capacity <sup>5</sup>	550 sheets		
Sizes	Custom sizes: 76.2 x 190 mm to 216 x 356 mm		
<b>Weights</b> One-sided: Two-sided:	60 to 220 gsm 60 to 176 gsm		
Media Types	Pre-Printed Recycled Envelopes (Tray 1 only) Labels Lightweight Card Stock Card Stock Letterhead Custom 1 - 5		

High Capacity Feeder (Optio	onal -Can be combined with 1 additional tray)		
Capacity <sup>5</sup>	2000 sheets		
Sizes	Standard sizes: A4 SEF		
<b>Weights</b> One-sided: Two-sided:	60 to 176 gsm 60 to 176 gsm		
Types	Plain Paper Bond Punched Pre-Printed Recycled Lightweight Card Stock Letterhead Custom 1 - 5		
Total Paper Capacity <sup>5</sup>			
B605/S, B605/X and B605/XL	700 sheets		
Maximum Paper Capacity	3,250 sheets		
Paper Output			
Output Tray			
Capacity <sup>5</sup>	400 sheets with tray full sensor (without Finisher or Mailbox)		
Automatic Two-sided Printing	Standard		
Finisher (Optional on XL; no	t available on S, X)		
Capacity <sup>5</sup>	500-sheet tray, 50-sheet stapling		
Mailbox (Optional on XL; no	ot available on S, X)		
Capacity <sup>5</sup>	Four 100-sheet bins		
Device Management			
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour® / AirPrint® FTP Most protocols not in use can be disabled		
Administrative Protocols	DHCP, SNMP, WINS, HTTP, HTTPS, TLS, SNTP, MDNS		
Xerox <sup>®</sup> CentreWare <sup>®</sup> Web			
	<ul> <li>A Web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system</li> <li>Works with any SNMP-managed printer from any manufacturer</li> <li>Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management</li> </ul>		
Embedded Web Server – Integrated Device Web Page			
Device Status	<ul> <li>Tray status/contents</li> <li>Consumables status</li> <li>Billing / Usage</li> <li>Quick Links</li> <li>Online Support</li> </ul>		
Print Queue Viewing	Job print queue management—view and delete		
Job Submission	Print-ready files (PS, PCL, PDF, XPS, JPEG)		
Device Administration	Allows simple, remote installation setting of configuration options and management of the device		

Browsers	Microsoft® Internet Explorer® Microsoft Edge™ Mozilla™ Firefox® Apple® Safari® Google Chrome™	
Remote Services		
Automated Meter Reading (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox <sup>®</sup> device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.	
Automated Supplies Replenishment (ASR)	Automatically orders supplies for Xerox output devices based on actual usage, eliminating the need to manually manage supplies inventory.	
MaintenanceAssistant	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox <sup>®</sup> , allowing for problems to be solved faster with increased uptime.	
What Comes in the Box		
	VersaLink B605 Multifunction Printer Standard Capacity Print Cartridge –Black: 10,300 print capacity <sup>6</sup> Software and Documentation CD (with User Manual, Quick Install Guide, Safety, Regulatory, Recycling and Disposal Guides, Print Drivers, and Warranty Statement) Installation Guide Quick Use Guides Power cord Fax cord	

Supplies and Accessories	Quantity	Part Number		
Supplies	Supplies			
Extra-High Capacity Toner Cartridge	Black: 46,700 standard pages <sup>6</sup>	106R03944		
High Capacity Toner Cartridge	Black: 25,900 standard pages <sup>6</sup>	106R03942		
Standard Capacity Toner Cartridge	Black: 10,300 standard pages <sup>6</sup>	106R03940		
Drum Cartridge	Black: 60,000 pages <sup>7</sup>	101R00582		
Accessories / Options				
2,000-sheet High Capacity Feeder (includes Caster Base)		097S04948		
550-sheet Tray		097S04949		
Finisher (500 sheets, 50-sheet stapler)		097S04952		
4-Bin Mailbox (100 sheets per bin)		097S04953		
Caster Base		097S04954		
Stand (includes Caster Base)		097S04994		
Wireless Network Adapter (Wi-Fi Kit)		497K16750		

<sup>1</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.
 <sup>2</sup> Expected regular monthly throughput.
 <sup>3</sup> Power states defined per ENERGY STAR® Programme requirements for Imaging Equipment.
 <sup>4</sup> Requires analogue phone line.
 <sup>5</sup> Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks.
 <sup>6</sup> Average standard pages. Declared Yield in accordance with ISO/IEC19752. Yield will vary based on image, area coverage and print mode.
 <sup>7</sup> Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: http://www.office.xerox.com/latest/SUPGL-01.pdf.

www.xerox.com

Configurations vary by geography.

