# HP Deskjet D5560 Printer





Print from virtually anywhere in the home with this affordable wireless printer<sup>1</sup>. Easy to set-up and to use, it's the ideal partner for wireless notebooks. Get HP reliability and high quality results on all your documents, web pages and more.

The HP Deskjet D5560 Printer is designed for users looking for a wireless printer that is both affordable and easy-to-use, and can be trusted to deliver great results on all kinds of everyday print projects, from documents to web pages.

#### Enjoy wireless freedom with HP's most affordable wireless printer<sup>2</sup>.

Give yourself the freedom and flexibility of being able to print from virtually anywhere in the home with HP's most affordable wireless printer<sup>2</sup>. Enjoy secure connectivity plus the convenience of Wi-Fi Protected Setup and a wireless strength indicator. Get up to 3x more black printed pages and 2.5x more colour printed pages with optional high-capacity replacement ink cartridges<sup>4</sup>. ENERGY STAR® qualified. Less waste too – this HP product created from 35% recycled plastic.

### Get set up in no time with easy-to-install software and intuitive controls.

Get connected and printing in no time with one-touch wireless set-up<sup>5</sup> and software that's easy to install and to use. The intuitive control panel makes managing your printer simple too, with just four on-printer buttons: power, resume, wireless and a quick cancel button to stop print jobs and save ink, paper and money. Original HP inks ensure reliable printing with laser quality text and vivid colour graphics. Ink level gauge shows you when you're running low.

#### Print more from the web – more easily – with HP Smart Web Printing<sup>3</sup>.

Make better use of whatever you print from the web with HP Smart Web Printing<sup>3</sup>. Print only what you want to print and nothing more. Combine content from multiple sites onto a single page to save ink and paper – you can even resize and edit before printing. No more clipped pages or print-outs with just a few lines of text and no photos. Ideal for college research, flight bookings, recipes, maps, photos and anything else you print from the web.

- 1 Wireless performance is dependent upon physical environment and distance from access point.
- 2 Wireless performance is dependent upon physical environment and distance from access point
- 3 Requires Microsoft Internet Explorer 6.0 8.0
- $^4$  Compared with HP 300 Black/Colour Ink Cartridges; XL cartridges not included, please purchase separately
- <sup>5</sup> Requires a WPS router with an integrated push-button.

# **Technical specifications**

Black test ÅÅ  Mixed test/Colour graphics A4  Up to 28 ppm Up to 8 ppm Up to 6 ppm Up to 7 ppm Up to 6 ppm Up to 6 ppm Up to 7 ppm Up to 8 ppm Up to 9 ppm Up to 8 ppm Up to 9 ppm Up to 8 ppm Up to 9	Print technology	HP Thermal Inkjet				
Mixed text/colour grouphics A4  10 x 15 or mc clour phote (phote paper)  10 x 15 or mc clour phote (phote paper)  10 x 15 or mc clour phote (phote paper)  10 x 15 or mc clour phote (phote paper)  10 x 15 or mc clour phote (phote paper)  10 x 15 or mc clour phote (phote paper)  10 x 15 or mc clour phote (phote paper)  10 x 15 or mc clour phote (phote paper)  10 x 15 or mc clour phote (phote paper)  10 x 15 or mc clour phote (phote paper)  10 x 15 or mc clour phote (phote paper)  11 x 15 or mc clour phote (phote paper)  12 x 15 or mc clour phote phote paper (phote paper)  13 x 15 or mc clour phote paper (phote paper)  14 x 15 or mc clour phote paper (phote paper)  15 x 15 or mc clour phote paper (phote paper)  16 x 15 or mc clour phote paper (phote paper)  17 x 15 or mc clour phote paper (phote paper)  18 x 15 or mc clour phote paper (phote paper)  18 x 15 or mc clour phote paper (phote paper)  19 x 15 or mc clour phote paper (phote paper)  19 x 15 or mc clour phote paper (phote paper)  10 x 15 or mc clour phote paper (phote paper)  10 x 15 or mc clour phote paper (phote paper)  10 x 15 or mc clour phote paper (phote paper)  10 x 15 or mc clour phote paper (phote paper)  10 x 15 or mc clour phote paper (phote paper)  10 x 15 or mc clour phote paper (phote paper)  10 x 15 or mc clour phote paper (phote paper)  10 x 15 or mc clour phote paper (phote paper)  10 x 15 or mc clour phote paper (phote paper)  10 x 15 or mc clour phote paper (phote paper)  10 x 15 or mc clour phote paper (phote paper)  10 x 15 or mc clour phote paper (phote paper)  10 x 15 or mc clour phote paper (phote paper)  10 x 15 or mc clour phote paper)  10 x 15 or mc clour phote paper (phote paper)  10 x 15 or mc clour phote paper (phote paper)  10 x 15 or mc clour phote paper)  10 x 15 or mc clour phote paper (phote paper)  10 x 15 or mc clour phote paper)  10 x 15 or mc clour phote paper (phote paper)  10 x 15 or mc clour phote paper)  10 x 15 o	Print speed	Document type	Draft	Normal	Best	
10 x 15 cm colour photo (photo paper)   As fast as 31 sec   As fast as 6 sec   As fast as 50 sec   As fast as 51 sec   As fa			Up to 28 ppm	Up to 8 ppm		
Full page colour As [John paper]  As fact as 81 sec						
Dependent upon type, print mode and approximate figures. Exact speed will vary depending on the system configuration, software program and document complexity.  Black: Up to 600 dpl Colour: Up to 4800 x 1200 optimised dpi colour when printing from a computer on selected HP photo papers and 1200 input dpi University of the photo papers and 1200 input dpi Windows Vista's (32bit 8.6 d-bit); Microsoft® Windows® XP Professional (SP1 or higher); any Intel® Pentium® II, Celeron® or compolible processor, 233 MHz or higher; 128 MB RAM (256 MB or higher recommended); 600 MB hard disk space, internet Explorer of or higher; CDROW/DVD drive or Internet connection; USB port; Vindows Vistay8; 800 MHz (64) processor, 512 MRAM, 850 MB hard disk space, internet Explorer of or higher; CDROW/DVD drive or Internet connection; USB port; Windows® 7 ready. Remove information go to high-//www.hp.com/go/windows7. Some features may not evaluable. Microsoft® Windows8 7 ready. Remove information go to high-//www.hp.com/go/windows7. Some features may not evaluable. Microsoft® Windows8 7 ready. Remove information go to high-//www.hp.com/go/windows7. Some features may not evaluable. Microsoft® Windows8 7 ready. Remove information go to high-//www.hp.com/go/windows7. Some features may not evaluable. Microsoft® Windows8 7 ready. Remove information go to high-//www.hp.com/go/windows7. Some features may not evaluable. Microsoft® Windows8 7 ready. Remove fine features may not evaluable with species of the processor; 256 MB RAM; 500 MB available hard disk space; CD ROM; USB port  Memory  Memor						
Software program and document complexity.  Black: Up to 600 dpi Colour: Up to 4800 x 1200 optimised dpi colour when printing from a computer on selected HP photo papers and 1200 input dpi Colour: Up to 4800 x 1200 optimised dpi colour when printing from a computer on selected HP photo papers and 1200 input dpi Windows9: Microsoff® Windows® XP (SP1 or higher/ 32-bit); Mac OS X v10.4, v10.5  Windows9: Microsoff® Windows® XP Professional (SP1 or higher); any intel® Pentium® II, Celleron® or compatible processor, 233 MHz or higher; 120 MB RAM (256 MB RAM (256 MB or higher); any intel® Pentium® III, Celleron® or compatible processor, 123 MHz or higher; any intel® Pentium® II, Celleron® or compatible processor, 123 MHz or higher; 120 MB RAM (256 MB RAM (256 MB); Microsoff® Windows® XP (233 MHz or higher); 200 MB RAM (256 MB RAM (256 MB); Microsoff® Windows® XP (233 MHz or higher); 200 MB RAM (256 MB						
Black: Up to 600 dpl   Colour: Up to 4800 x 1200 optimised dpi colour when printing from a computer on selected HP photo papers and 1200 input dpi   Minimum system requirements						
Colour. Úp to 4800 x 1200 optimised dpi colour when printing from a computer on selected HP photo papers and 1200 input dpi Windows Vistario (32-bit & 6.4-bit); Microsoft® Windows® XP (SP1 or higher), any Intel® Partiturio® II, Celeror® or compatible processor, 233 MHz or higher; 128 MB RAM (256 MB or higher recommended); 600 MB hard disk space, internet Explorer 6 or higher; CDROM/DVD drive or Internet connection; USB port; Windows Vistario, 800 MHz 32-bit (MB) or 64-bit (64) processor, 512 M RAM, 850 MB hard disk space, Internet Explorer, CDROM/DVD drive or Internet connection; USB port; Windows Vistario, 800 MHz 32-bit (MB) or 64-bit (64) processor, 512 M RAM, 850 MB hard disk space, Internet Explorer, CDROM/DVD drive or Internet connection; USB port; Windows Vistario, 800 MHz 32-bit (MB) or 64-bit (64) processor, 512 M RAM, 850 MB hard disk space, Internet Explorer, CDROM/DVD drive or Internet connection; USB port; Windows Vistario, 800 MHz 32-bit (MB) or 64-bit (64) processor, 512 M RAM, 850 MB hard disk space, Internet Explorer, CDROM/DVD drive or Internet connection; USB port; Windows Vistario, 800 MHz 32-bit (MB) or 64-bit (64) processor, 512 M RAM, 850 MB available hard disk space, 100 MB, 900		1 0				
Operating systems compatibility         Windows Visita® (32-bit & 6.4-bit); Microsoft® Windows® XP (SP1 or higher/32-bit); Mac CS X v 10.4, v 10.5           Minimum system requirements         Windows®: Microsoft® Windows® XP Professional (SP1 or higher); any Intel® Pentium® II, Celeron® or compatible processor, 233 MHz or higher; 128 MB RAM (256 MB or higher recommended); 600 MB rad disk space; Internet Explorer 6 or higher; CDROM/DVD drive or Internet connection; USB port; Windows Visita®; 800 MHz 32-bit, 860 or 64-bit (64) processor, 512 MRAM, 850 MB hard disk space, Internet Explorer, CDROM/DVD drive or Internet connection; USB port; Windows® XP Professional x64 not supported.           Mac Moritosh: Mac OS X v 10.4 or v 10.5; PowerPC G3, G4, G5 or Intel® Core processor; 256 MB RAM; 500 MB available hard disk space; CDROM, USB port           Memory         64 MB           Printer languages         HP LIDIL, PMI           Cartridge clignment         +/-0.0508 mm           Duty cycle (monthly, A4)         Up to 3000 pages           Recommended media weight         75 to 280 g/m²           Recommended media         Poper (plain, inkjet, photo), envelopes, transparencies, labels, cards, HP Advanced Media, iron-on transfers, borderless media, panorama           Media sizes         Standard: A4 (210 x 297 mm), A5 (148 x 210 mm), B5 (176 x 250 mm), DL (110 x 220 mm), C6 (114 x 162 mm), A6 (105 x 148 mm), 300 x 100 mm, 130 x 180 mm, 100 x 150 mm, Custom: 76.2 x 127 to 215.9 x 762 mm           Peper input tray         Standard: 1, optional: 1           Media handling/output         Up to 20, transparencies: Up to 1	Print quality	Colour: Up to 4800 x 1200 optimised dpi colour when printing from a computer on selected HP photo papers and 1200 input				
233 MHz or higher; 128 MB RAM (256 MB or higher recommended); 600 MB hard disk space, Internet Explorer 6 or higher; CDRCM/DVD drive or Internet connection; USB part; Windows Vistago, or 44-bit (46) or 46-bit (46) or	Operating systems compatibility	l .				
233 MHz or higher; 128 MB RAM (256 MB or higher recommended); 600 MB hard disk space, Internet Explorer 6 or higher; CDRCM/DVD drive or Internet connection; USB part; Windows Visitage) or 44-bit (46) or 44-bit (46) or 46-bit (46) o	Minimum system requirements	Windows®: Microsoft® Windows® XP Professional (SP1 or higher): any Intel® Pentium® II. Celeron® or compatible processor:				
Memory 64 MB Printer languages HP IDIL, PML Cartridge alignment +/-0.0508 mm Durty cycle (monthly, A4) Up to 3000 pages Recommended media weight 75 to 280 g/m² Recommended media weight 75 to 280 g/m² Recommended media weight 75 to 280 g/m² Recommended media weight 80 sheet input tray, 20-sheet output tray Media sizes Standard: A4 (210 x 297 mm), A5 (148 x 210 mm), B5 (176 x 250 mm), DL (110 x 220 mm), C6 (114 x 162 mm), A6 (105 x 148 mm), 300 x 140 mm, 130 x 180 mm, 100 x 150 mm, Custom: 76.2 x 127 to 215.9 x 762 mm Recommended media 80-sheet input tray, 20-sheet output tray Media handling/input Sheets: Up to 80, Envelopes: Up to 10 Cards: Up to 20, Transparencies: Up to 15, Labels/A4 sheets: Up to 10 Paper input tray Standard: 1, optional: 1 Media handling/output Up to 20 Up to 20 Watts maximum (active), 3.2 watts maximum (standby), 2 watts maximum (powersave), 0.35 watts maximum (off) Interface and connectivity Hispeed USB 2.0, wireless 802: 11 b/g Control panel 4 lights (Power, Resume, Error Indicator, Wireless); 4 Buttons (Power, Cancel, Resume, Wireless) Software included Windows® Use Photo Gallery Uniforms wire included Windows® Use Photo Gallery Uniforms environment Vesight Out of package: 428 kg packaged: 4.2 kg Coperating environment Foreware connectivity Foreware included Sheet Resume, Error Indicator, Wireless); 4 Buttons (Power, Cancel, Resume, Wireless) Coftware included Windows® Use Photo Gallery Uniforms (Power, Cancel, Resume, Wireless) Coftware included Connectivity Foreware included Provision (Power, Cancel, Resume, Wireless) Coftware included Connectivity Foreware included Provision (Power, Cancel, Resume, Wireless) Coftware included Connectivity Foreware included Provision (Power, Cancel, Resume, Wireless) Coftware included Provision (Power, Cance	, .	CD-ROM/DVD drive or Internet connection; USB port; Windows Vista®; 800 MHz 32-bit (x86) or 64-bit (64) processor, 512 M RAM, 850 MB hard disk space, Internet Explorer; CD-ROM/DVD drive or Internet connection; USB port; Windows® 7 ready. Fo				
Memory         64 MB           Printer languages         HP IDIL, PML           Cartridge alignment         +/-0,0508 mm           Duty cycle (monthly, A4)         Up to 3000 pages           Recommended media weight         75 to 280 g/m²           Recommended media weight         Paper (plain, inkjet, photo), envelopes, transparencies, labels, cards, HP Advanced Media, iron-on transfers, borderless media, panorama           Media sizes         Standard: A4 (210 x 297 mm), A5 (148 x 210 mm), B5 (176 x 250 mm), DL (110 x 220 mm), C6 (114 x 162 mm), A6 (105 x 148 mm), 300 x 100 mm, 130 x 180 mm, 100 x 150 mm, Custom: 76.2 x 127 to 215.9 x 762 mm           Paper handling         80 sheet input tray, 20-sheet output tray           Media handling/input         Sheets: Up to 80, Envelopes: Up to 10           Cards: Up to 20, Transparencies: Up to 10, Transparencies: Up to 10           Paper input tray         Standard: 1, optional: 1           Media handling/output         Up to 20           Duplex printing         Manual (driver support provided)           Power requirements         Input voltage 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz); may vary by region, External           Power rousimption         Linetace and connectivity           Interface and connectivity         HisSpeed USB 2.0, wireless 8021 11b/g           Control panel         4 lights (Power, Resume, Error Indicator, Wireless); 4 Buttons (Power, Cancle, Resume, Wireless)		Professional x64 not supported.  Macintosh: Mac OS X v10.4 or v10.5; PowerPC G3, G4, G5 or Intel® Core processor; 256 MB RAM; 500 MB available hard				
Printer languages HP LIDIL, PML Cartridge alignment +/-0.0508 mm  Duty cycle (monthly, A4) Up to 3000 pages  Recommended media weight 75 to 280 g/m²  Recommended media weight Recommended media Paper (plain, inkjet, photo), envelopes, transparencies, labels, cards, HP Advanced Media, iron-on transfers, borderless media, panorama  Media sizes Standard: A4 (210 x 297 mm), A5 (148 x 210 mm), B5 (176 x 250 mm), DL (110 x 220 mm), C6 (114 x 162 mm), A6 (105 x 148 mm), 300 x 100 mm, 130 x 180 mm, 100 x 150 mm, Custom: 76.2 x 127 to 215.9 x 762 mm  Paper handling Bo-sheet input tray, 20-sheet output tray  Media handling/input Sheets: Up to 80, Envelopes: Up to 10, Cards: Up to 20, Transparencies: Up to 15, Labels/A4 sheets: Up to 10  Paper input tray  Media handling/output Up to 20  Duplex printing Manual (driver support provided)  Duplex printing Manual (driver support provided)  Power requirements Input voltage 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz); may vary by region, External  Power consumption 20 wats maximum (active), 3-2 watts maximum (standby), 2 watts maximum (powersave), 0.35 watts maximum (off)  Interface and connectivity Hi-Speed USB 2.0, wireless 802.11b/g  Control panel 4 lights (Power, Resume, Error Indicator, Wireless); 4 Buttons (Power, Cancel, Resume, Wireless)  Software included Windows® Live Photo Gallery  Dimensions (w x d x h) Out of package: 433 x 210 x 164 mm, Maximum: 433 x 485 x 147 mm (with input tray and extension fully extended), packaged: 448 x 219 x 246 mm  Operating environment Environmental ranges: operating temperature: 5 to 40° C; Recommended operating temperature: 15 to 30° C; operating humidity: 20 to 80% RH; Recommended operating temperature: 15 to 80° C; Storage humidity: 20 to 80% RH; Recommended operating temperature: 5 to 40° C; Recommended operating temperature: 40 to 60° C; Storage humidity: 50 to 80% RH; Recommended operating print mode), 2.7 B(A) (idle)  Energy star  Yes  Veranty  Varranty Standard one-year limited hardware warranty. Warranty and support options var	Memory	·				
Duty cycle (monthly, A4)  Up to 3000 pages  Recommended media weight  75 to 280 g/m²  Recommended media weight  Recommended media  Paper (plain, inkjet, photo), envelopes, transparencies, labels, cards, HP Advanced Media, iron-on transfers, borderless media, panorama  Media sizes  Standard: A4 (210 x 297 mm), A5 (148 x 210 mm), B5 (176 x 250 mm), DL (110 x 220 mm), C6 (114 x 162 mm), A6 (105 x 148 mm), 300 x 100 mm, 130 x 180 mm, 100 x 150 mm, Custom: 76.2 x 127 to 215.9 x 762 mm  Reper handling  Bo-sheet input tray, 20-sheet output tray  Media handling/input  Sheets: Up to 80, Envelopes: Up to 10  Cards: Up to 20, Transparencies: Up to 15, Labels/A4 sheets: Up to 10  Reper input tray  Media handling/output  Up to 20  Duplex printing  Manual (driver support provided)  Power requirements  Input voltage 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz); may vary by region, External  Power consumption  20 watts maximum (active), 3.2 watts maximum (standby), 2 watts maximum (powersave), 0.35 watts maximum (off)  Interface and connectivity  Hi-Speed USB 2.0, wireless 802.11b/g  Control panel  4 lights (Power, Resume, Error Indicator, Wireless); 4 Buttons (Power, Cancel, Resume, Wireless)  Software included  Windows® Live Photo Gallery  Dimensions (w x d x h)  Out of package: 433 x 210 x 164 mm, Maximum: 433 x 485 x 147 mm (with input tray and extension fully extended), packaged: 484 x 219 x 246 mm  Weight  Operating environment  Environmental ranges: operating temperature: 5 to 40° C; Recommended operating temperature: 15 to 30° C; operating humidity: 20 to 80% RH; Storage temperature: 40 to 60° C; Storage humidity: 20 to 80% RH; Storage temperature: 40 to 60° C; Storage humidity: 20 to 80% RH; Storage temperature: 40 to 60° C; Storage humidity: 20 to 80% RH; Storage temperature: 40 to 60° C; Storage humidity: 20 to 80% RH; Storage temperature: 40 to 60° C; Storage humidity: 20 to 80% RH; Storage temperature: 40 to 60° C; Storage humidity: 20 to 80% RH; Storage temperature: 40 to 60° C; Storage humidity: 20 to 80% RH; S						
Recommended media weight 75 to 280 g/m²  Recommended media Recommended media Recommended media Recommended media Recommended R		+/-0.0508 mm				
Recommended media  Paper (plain, inkjet, photo), envelopes, transparencies, labels, cards, HP Advanced Media, iron-on transfers, borderless media, panorama  Standard: A4 (210 x 297 mm), A5 (148 x 210 mm), B5 (176 x 250 mm), DL (110 x 220 mm), C6 (114 x 162 mm), A6 (105 x 148 mm), 300 x 100 mm, 130 x 180 mm, 100 x 150 mm, Custom: 76.2 x 127 to 215.9 x 762 mm  Paper handling  80-sheet input tray, 20-sheet output tray  Media handling/input  Sheets: Up to 80, Envelopes: Up to 10 Cards: Up to 20, Transparencies: Up to 15, Labels/A4 sheets: Up to 10  Paper input tray  Standard: 1, optional: 1  Up to 20  Duplex printing  Manual (driver support provided)  Duplex printing  Manual (driver support provided)  Power crequirements  Power requirements  Power orsumption  10 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz); may vary by region, External  Power consumption  Interface and connectivity  Hi-Speed USB 2.0, wireless 802.11b/g  Control panel  4 lights (Power, Resume, Error Indicator, Wireless); 4 Buttons (Power, Cancel, Resume, Wireless)  Software included  Windows® Live Photo Gallery  Out of package: 433 x 210 x 164 mm, Maximum: 433 x 485 x 147 mm (with input tray and extension fully extended), packaged: 484 x 219 x 246 mm  Weight  Out of package: 2.62 kg, packaged: 4.2 kg  Operating environment  Environmental ranges: operating temperature: 5 to 40° C; Recommended operating temperature: 15 to 30° C; operating humidity: 20 to 80% RH; Storage temperature: 15 to 30° C; operating humidity: 5 to 90% RH; noise level per iso 9296: sound power: 6.9 B(A) (blackand-white fast draft print mode), 5.7 B(A) (color normal print mode), 6.0 B(A) (blackand-white normal print mode), 2.7 B(A) (idle)  Finergy star  Supplies life  For information on page yield, visit www.hp.com/go/learnaboutsupplies, or see product packaging  Warranty  Standard one-year limited hardware warranty. Warranty and support options vary by product, country and local legal	Duty cycle (monthly, A4)	·				
Recommended media Paper (plain, inkjet, photo), envelopes, transparencies, labels, cards, HP Advanced Media, iron-on transfers, borderless media, panorama  Media sizes Standard: A4 (210 x 297 mm), A5 (148 x 210 mm), B5 (176 x 250 mm), DL (110 x 220 mm), C6 (114 x 162 mm), A6 (105 x 148 mm), 300 x 100 mm, 130 x 180 mm, 100 x 150 mm, Custom: 76.2 x 127 to 215.9 x 762 mm  Paper handling B0-sheet input tray, 20-sheet output tray Media handling/input Sheets: Up to 80, Envelopes: Up to 10 Cards: Up to 20, Transparencies: Up to 15, Labels/A4 sheets: Up to 10  Paper input tray Standard: 1, optional: 1 Up to 20  Duplex printing Manual (driver support provided) Power requirements Power requirements Input voltage 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz); may vary by region, External Power consumption 20 watts maximum (active), 3.2 watts maximum (standby), 2 watts maximum (powersave), 0.35 watts maximum (off) Interface and connectivity Hi-Speed USB 2.0, wireless 802.11b/g Control panel 4 lights (Power, Resume, Error Indicator, Wireless); 4 Buttons (Power, Cancel, Resume, Wireless) Software included Windows® Live Photo Gallery Dimensions (w x d x h) Out of package: 433 x 210 x 164 mm, Maximum: 433 x 485 x 147 mm (with input tray and extension fully extended), packaged: 484 x 219 x 246 mm  Weight Out of package: 2.62 kg, packaged: 4.2 kg Operating environment Environmental ranges: operating temperature: 5 to 40° C; Recommended operating temperature: 15 to 30° C; operating humidity: 20 to 80% RH; Storage temperature: 15 to 30° C; operating humidity: 20 to 80% RH; Storage temperature: 40 to 60° C; Storage humidity: 5 to 90% RH; noise level per iso 9296: sound power: 6.9 B(A) (black-and-white fast draft print mode), 5.7 B(A) (colon normal print mode), 6.0 B(A) (black-and-white normal print mode), 2.7 B(A) (idle)  Fenergy star  Supplies life For information on page yield, visit www.hp.com/go/learnaboutsupplies, or see product packaging  Warranty	Recommended media weight	75 to 280 a/m²				
Standard: A4 (210 x 297 mm), A5 (148 x 210 mm), B5 (176 x 250 mm), DL (110 x 220 mm), C6 (114 x 162 mm), A6 (105 x 148 mm), 300 x 100 mm, 130 x 180 mm, 100 x 150 mm, Custom: 76.2 x 127 to 215.9 x 762 mm  Paper handling  80-sheet input tray, 20-sheet output tray  Media handling/input  Sheets: Up to 80, Envelopes: Up to 10 Cards: Up to 20, Transparencies: Up to 15, Labels/A4 sheets: Up to 10  Paper input tray  Standard: 1, optional: 1  Wedia handling/output  Up to 20  Nanual (driver support provided)  Power requirements  Input voltage 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz); may vary by region, External  Power consumption  20 watts maximum (active), 3.2 watts maximum (standby), 2 watts maximum (powersave), 0.35 watts maximum (off)  Interface and connectivity  Hi-Speed USB 2.0, wireless 802.11b/g  Control panel  4 lights (Power, Resume, Error Indicator, Wireless); 4 Buttons (Power, Cancel, Resume, Wireless)  Software included  Windows® Live Photo Gallery  Out of package: 2.62 kg, packaged: 4.2 kg  Operating environment  Environmental ranges: operating temperature: 5 to 40° C; Recommended operating temperature: 15 to 30° C; operating humidity: 20 to 80% RH; Recommended operating temperature: 40 to 60° C; Storage humidity: 5 to 90% RH; noise level per iso 9296: sound power: 6.9 B(A) (black-and-white fast draft print mode), 5.7 B(A) (colon normal print mode), 6.0 B(A) (black-and-white normal print mode), 2.7 B(A) (idle)  Energy star  Ves  Supplies life  For information on page yield, visit www.hp.com/go/learnaboutsupplies, or see product, country and local legal	Recommended media	Paper (plain, inkjet, photo), envelopes, transparencies, labels, cards, HP Advanced Media, iron-on transfers, borderless media,				
Media handling/input       Sheets: Up to 80, Envelopes: Up to 10         Cards: Up to 20, Transparencies: Up to 15, Labels/A4 sheets: Up to 10         Paper input tray       Standard: 1, optional: 1         Media handling/output       Up to 20         Duplex printing       Manual (driver support provided)         Power requirements       Input voltage 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz); may vary by region, External         Power consumption       20 watts maximum (active), 3.2 watts maximum (standby), 2 watts maximum (powersave), 0.35 watts maximum (off)         Interface and connectivity       Hi-Speed USB 2.0, wireless 802.11b/g         Control panel       4 lights (Power, Resume, Error Indicator, Wireless); 4 Buttons (Power, Cancel, Resume, Wireless)         Software included       Windows® Live Photo Gallery         Dimensions (w x d x h)       Out of package: 433 x 210 x 164 mm, Maximum: 433 x 485 x 147 mm (with input tray and extension fully extended), packaged: 484 x 219 x 246 mm         Weight       Out of package: 2.62 kg, packaged: 4.2 kg         Operating environment       Environmental ranges: operating temperature: 5 to 40° C; Recommended operating temperature: 15 to 30° C; operating humidity: 20 to 80% RH; Recommended operating humidity: 20 to 80% RH; Storage temperature: 40 to 60° C; Storage humidity: 5 to 90% RH; noise level per iso 9296: sound power: 6.9 B(A) (black-and-white fast draft print mode), 5.7 B(A) (colonormal print mode), 6.0 B(A) (black-and-white normal print mode), 2.7 B(A) (idle)         Energy star <td>Media sizes</td> <td colspan="4">Standard: A4 (210 x 297 mm), A5 (148 x 210 mm), B5 (176 x 250 mm), DL (110 x 220 mm), C6 (114 x 162 mm), A6 (105</td>	Media sizes	Standard: A4 (210 x 297 mm), A5 (148 x 210 mm), B5 (176 x 250 mm), DL (110 x 220 mm), C6 (114 x 162 mm), A6 (105				
Cards: Up to 20, Transparencies: Up to 15, Labels/A4 sheets: Up to 10  Paper input tray Standard: 1, optional: 1  Media handling/output Up to 20  Duplex printing Manual (driver support provided)  Power requirements Input voltage 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz); may vary by region, External  Power consumption 20 watts maximum (active), 3.2 watts maximum (standby), 2 watts maximum (powersave), 0.35 watts maximum (off)  Interface and connectivity Hi-Speed USB 2.0, wireless 802.11b/g  Control panel 4 lights (Power, Resume, Error Indicator, Wireless); 4 Buttons (Power, Cancel, Resume, Wireless)  Software included Windows® Live Photo Gallery  Dimensions (w x d x h) Out of package: 433 x 210 x 164 mm, Maximum: 433 x 485 x 147 mm (with input tray and extension fully extended), packaged: 484 x 219 x 246 mm  Weight Out of package: 2.62 kg, packaged: 4.2 kg  Operating environment Environmental ranges: operating temperature: 5 to 40° C; Recommended operating temperature: 15 to 30° C; operating humidity: 20 to 80% RH; Recommended operating humidity: 20 to 80% RH; Storage temperature: 40 to 60° C; Storage humidity: 20 to 80% RH; noise level per iso 9296: sound power: 6.9 B(A) (black-and-white fast draft print mode), 5.7 B(A) (color normal print mode), 6.0 B(A) (black-and-white normal print mode), 2.7 B(A) (idle)  Energy star  Supplies life For information on page yield, visit www.hp.com/go/learnaboutsupplies, or see product packaging  Warranty Standard one-year limited hardware warranty. Warranty and support options vary by product, country and local legal	Paper handling	· · · · · · · · · · · · · · · · · · ·				
Paper input tray  Standard: 1, optional: 1  Media handling/output  Up to 20  Duplex printing  Manual (driver support provided)  Power requirements  Input voltage 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz); may vary by region, External  Power consumption  20 watts maximum (active), 3.2 watts maximum (standby), 2 watts maximum (powersave), 0.35 watts maximum (off)  Interface and connectivity  Hi-Speed USB 2.0, wireless 802.11b/g  Control panel  4 lights (Power, Resume, Error Indicator, Wireless); 4 Buttons (Power, Cancel, Resume, Wireless)  Software included  Windows® Live Photo Gallery  Dimensions (w x d x h)  Out of package: 433 x 210 x 164 mm, Maximum: 433 x 485 x 147 mm (with input tray and extension fully extended), packaged: 484 x 219 x 246 mm  Weight  Operating environment  Environmental ranges: operating temperature: 5 to 40° C; Recommended operating temperature: 15 to 30° C; operating humidity: 20 to 80% RH; Recommended operating humidity: 20 to 80% RH; Storage temperature:-40 to 60° C; Storage humidity: 5 to 90% RH; noise level per iso 9296: sound power: 6.9 B(A) (blackand-white fast draft print mode), 5.7 B(A) (colon normal print mode), 6.0 B(A) (blackand-white normal print mode), 2.7 B(A) (idle)  Energy star  Supplies life  For information on page yield, visit www.hp.com/go/learnaboutsupplies, or see product packaging  Warranty  Standard one-year limited hardware warranty. Warranty and support options vary by product, country and local legal	Media handling/input	1 7				
Media handling/output         Up to 20           Duplex printing         Manual (driver support provided)           Power requirements         Input voltage 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz); may vary by region, External           Power consumption         20 watts maximum (active), 3.2 watts maximum (standby), 2 watts maximum (powersave), 0.35 watts maximum (off)           Interface and connectivity         Hi-Speed USB 2.0, wireless 802.11b/g           Control panel         4 lights (Power, Resume, Error Indicator, Wireless); 4 Buttons (Power, Cancel, Resume, Wireless)           Software included         Windows® Live Photo Gallery           Dimensions (w x d x h)         Out of package: 433 x 210 x 164 mm, Maximum: 433 x 485 x 147 mm (with input tray and extension fully extended), packaged: 484 x 219 x 246 mm           Weight         Out of package: 2.62 kg, packaged: 4.2 kg           Operating environment         Environmental ranges: operating temperature: 5 to 40° C; Recommended operating temperature: 40 to 60° C; Storage humidity: 20 to 80% RH; Recommended operating humidity: 20 to 80% RH; Storage temperature:-40 to 60° C; Storage humidity: 5 to 90% RH; noise level per iso 9296: sound power: 6.9 B(A) (black-and-white fast draft print mode), 5.7 B(A) (color normal print mode), 6.0 B(A) (black-and-white normal print mode), 2.7 B(A) (idle)           Energy star         Yes           Supplies life         For information on page yield, visit www.hp.com/go/learnaboutsupplies, or see product packaging           Warranty         Standard one-year limited h						
Media handling/output         Up to 20           Duplex printing         Manual (driver support provided)           Power requirements         Input voltage 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz); may vary by region, External           Power consumption         20 watts maximum (active), 3.2 watts maximum (standby), 2 watts maximum (powersave), 0.35 watts maximum (off)           Interface and connectivity         Hi-Speed USB 2.0, wireless 802.11b/g           Control panel         4 lights (Power, Resume, Error Indicator, Wireless); 4 Buttons (Power, Cancel, Resume, Wireless)           Software included         Windows® Live Photo Gallery           Dimensions (w x d x h)         Out of package: 433 x 210 x 164 mm, Maximum: 433 x 485 x 147 mm (with input tray and extension fully extended), packaged: 484 x 219 x 246 mm           Weight         Out of package: 2.62 kg, packaged: 4.2 kg           Operating environment         Environmental ranges: operating temperature: 5 to 40° C; Recommended operating temperature: 40 to 60° C; Storage humidity: 20 to 80% RH; Recommended operating humidity: 20 to 80% RH; Storage temperature:-40 to 60° C; Storage humidity: 5 to 90% RH; noise level per iso 9296: sound power: 6.9 B(A) (black-and-white fast draft print mode), 5.7 B(A) (color normal print mode), 6.0 B(A) (black-and-white normal print mode), 2.7 B(A) (idle)           Energy star         Yes           Supplies life         For information on page yield, visit www.hp.com/go/learnaboutsupplies, or see product packaging           Warranty         Standard one-year limited h	Paper input trav	<u> </u>				
Duplex printing  Manual (driver support provided)  Power requirements  Input voltage 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz); may vary by region, External  Power consumption  20 watts maximum (active), 3.2 watts maximum (standby), 2 watts maximum (powersave), 0.35 watts maximum (off)  Interface and connectivity  Hi-Speed USB 2.0, wireless 802.11b/g  Control panel  4 lights (Power, Resume, Error Indicator, Wireless); 4 Buttons (Power, Cancel, Resume, Wireless)  Software included  Windows® Live Photo Gallery  Out of package: 433 x 210 x 164 mm, Maximum: 433 x 485 x 147 mm (with input tray and extension fully extended), packaged: 484 x 219 x 246 mm  Weight  Out of package: 2.62 kg, packaged: 4.2 kg  Operating environment  Environmental ranges: operating temperature: 5 to 40° C; Recommended operating temperature: 15 to 30° C; operating humidity: 20 to 80% RH; Recommended operating humidity: 20 to 80% RH; Storage temperature:-40 to 60° C; Storage humidity: 5 to 90% RH; noise level per iso 9296: sound power: 6.9 B(A) (black-and-white fast draft print mode), 5.7 B(A) (color normal print mode), 6.0 B(A) (black-and-white normal print mode), 2.7 B(A) (idle)  Energy star  Yes  Supplies life  For information on page yield, visit www.hp.com/go/learnaboutsupplies, or see product packaging  Warranty  Standard one-year limited hardware warranty. Warranty and support options vary by product, country and local legal	· · · · · · · · · · · · · · · · · · ·	· 1				
Power requirements   Input voltage 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz); may vary by region, External	<u> </u>					
Power consumption 20 watts maximum (active), 3.2 watts maximum (standby), 2 watts maximum (powersave), 0.35 watts maximum (off)  Interface and connectivity Hi-Speed USB 2.0, wireless 802.11b/g  Control panel 4 lights (Power, Resume, Error Indicator, Wireless); 4 Buttons (Power, Cancel, Resume, Wireless)  Software included Windows® Live Photo Gallery  Dimensions (w x d x h) Out of package: 433 x 210 x 164 mm, Maximum: 433 x 485 x 147 mm (with input tray and extension fully extended), packaged: 484 x 219 x 246 mm  Weight Out of package: 2.62 kg, packaged: 4.2 kg  Operating environment Environmental ranges: operating temperature: 5 to 40° C; Recommended operating temperature: 15 to 30° C; operating humidity: 20 to 80% RH; Recommended operating humidity: 20 to 80% RH; Storage temperature:-40 to 60° C; Storage humidity: 5 to 90% RH; noise level per iso 9296: sound power: 6.9 B(A) (black-and-white fast draft print mode), 5.7 B(A) (colon normal print mode), 6.0 B(A) (black-and-white normal print mode), 2.7 B(A) (idle)  Energy star  Yes  Supplies life For information on page yield, visit www.hp.com/go/learnaboutsupplies, or see product packaging  Warranty Standard one-year limited hardware warranty. Warranty and support options vary by product, country and local legal						
Interface and connectivity  Hi-Speed USB 2.0, wireless 802.11b/g  Control panel  4 lights (Power, Resume, Error Indicator, Wireless); 4 Buttons (Power, Cancel, Resume, Wireless)  Software included  Windows® Live Photo Gallery  Out of package: 433 x 210 x 164 mm, Maximum: 433 x 485 x 147 mm (with input tray and extension fully extended), packaged: 484 x 219 x 246 mm  Weight  Out of package: 2.62 kg, packaged: 4.2 kg  Operating environment  Environmental ranges: operating temperature: 5 to 40° C; Recommended operating temperature: 15 to 30° C; operating humidity: 20 to 80% RH; Recommended operating humidity: 20 to 80% RH; Storage temperature: 40 to 60° C; Storage humidity: 5 to 90% RH; noise level per iso 9296: sound power: 6.9 B(A) (black-and-white fast draft print mode), 5.7 B(A) (colon normal print mode), 6.0 B(A) (black-and-white normal print mode), 2.7 B(A) (idle)  Energy star  Supplies life  For information on page yield, visit www.hp.com/go/learnaboutsupplies, or see product packaging  Warranty  Standard one-year limited hardware warranty. Warranty and support options vary by product, country and local legal				, , -	vimum (off)	
Control panel 4 lights (Power, Resume, Error Indicator, Wireless); 4 Buttons (Power, Cancel, Resume, Wireless)  Software included Windows® Live Photo Gallery  Out of package: 433 x 210 x 164 mm, Maximum: 433 x 485 x 147 mm (with input tray and extension fully extended), packaged: 484 x 219 x 246 mm  Weight Out of package: 2.62 kg, packaged: 4.2 kg  Operating environment Environmental ranges: operating temperature: 5 to 40° C; Recommended operating temperature: 15 to 30° C; operating humidity: 20 to 80% RH; Recommended operating humidity: 20 to 80% RH; Storage temperature: 40 to 60° C; Storage humidity: 5 to 90% RH; noise level per iso 9296: sound power: 6.9 B(A) (idlackand-white fast draft print mode), 5.7 B(A) (color normal print mode), 6.0 B(A) (black-and-white normal print mode), 2.7 B(A) (idle)  Energy star  Supplies life For information on page yield, visit www.hp.com/go/learnaboutsupplies, or see product packaging  Warranty Standard one-year limited hardware warranty. Warranty and support options vary by product, country and local legal		, , ,	uxillioni (sidilaby), 2 walis iliaxi	illioni (powersave), 0.55 wans ma	XIIIIOIII (OII)	
Software included  Windows® Live Photo Gallery  Out of package: 433 x 210 x 164 mm, Maximum: 433 x 485 x 147 mm (with input tray and extension fully extended), packaged: 484 x 219 x 246 mm  Weight  Out of package: 2.62 kg, packaged: 4.2 kg  Operating environment  Environmental ranges: operating temperature: 5 to 40° C; Recommended operating temperature: 15 to 30° C; operating humidity: 20 to 80% RH; Recommended operating humidity: 20 to 80% RH; Storage temperature: -40 to 60° C; Storage humidity: 5 to 90% RH; noise level per iso 9296: sound power: 6.9 B(A) (black-and-white fast draft print mode), 5.7 B(A) (color normal print mode), 6.0 B(A) (black-and-white normal print mode), 2.7 B(A) (idle)  Energy star  Yes  Supplies life  For information on page yield, visit www.hp.com/go/learnaboutsupplies, or see product packaging  Warranty  Standard one-year limited hardware warranty. Warranty and support options vary by product, country and local legal		1 , , ,				
Dimensions (w x d x h)  Out of package: 433 x 210 x 164 mm, Maximum: 433 x 485 x 147 mm (with input tray and extension fully extended), packaged: 484 x 219 x 246 mm  Weight  Out of package: 2.62 kg, packaged: 4.2 kg  Operating environment  Environmental ranges: operating temperature: 5 to 40° C; Recommended operating temperature: 15 to 30° C; operating humidity: 20 to 80% RH; Recommended operating humidity: 20 to 80% RH; Storage temperature:-40 to 60° C; Storage humidity: 5 to 90% RH; noise level per iso 9296: sound power: 6.9 B(A) (black-and-white fast draft print mode), 5.7 B(A) (color normal print mode), 6.0 B(A) (black-and-white normal print mode), 2.7 B(A) (idle)  Energy star  Yes  Supplies life  For information on page yield, visit www.hp.com/go/learnaboutsupplies, or see product packaging  Warranty  Standard one-year limited hardware warranty. Warranty and support options vary by product, country and local legal						
packaged: 484 x 219 x 246 mm  Weight  Out of package: 2.62 kg, packaged: 4.2 kg  Operating environment  Environmental ranges: operating temperature: 5 to 40° C; Recommended operating temperature: 15 to 30° C; operating humidity: 20 to 80% RH; Recommended operating humidity: 20 to 80% RH; Storage temperature: 40 to 60° C; Storage humidity: 5 to 90% RH; noise level per iso 9296: sound power: 6.9 B(A) (black-and-white fast draft print mode), 5.7 B(A) (color normal print mode), 6.0 B(A) (black-and-white normal print mode), 2.7 B(A) (idle)  Energy star  Yes  Supplies life  For information on page yield, visit www.hp.com/go/learnaboutsupplies, or see product packaging  Warranty  Standard one-year limited hardware warranty. Warranty and support options vary by product, country and local legal			11 : 100 105 1.17		II . I I	
Derating environment  Environmental ranges: operating temperature: 5 to 40° C; Recommended operating temperature: 15 to 30° C; operating humidity: 20 to 80% RH; Recommended operating humidity: 20 to 80% RH; Storage temperature: 40 to 60° C; Storage humidity: 5 to 90% RH; noise level per iso 9296: sound power: 6.9 B(A) (black-and-white fast draft print mode), 5.7 B(A) (colon normal print mode), 6.0 B(A) (black-and-white normal print mode), 2.7 B(A) (idle)  Energy star  Yes  Supplies life  For information on page yield, visit www.hp.com/go/learnaboutsupplies, or see product packaging  Warranty  Standard one-year limited hardware warranty. Warranty and support options vary by product, country and local legal	Dimensions (w x d x h)		Maximum: 433 x 485 x 14/ m	ım (with input tray and extension t	ully extended),	
humidity: 20 to 80% RH; Recommended operating humidity: 20 to 80% RH; Storage temperature: 40 to 60° C; Storage humidity: 5 to 90% RH; noise level per iso 9296: sound power: 6.9 B(A) (black-and-white fast draft print mode ), 5.7 B(A) (color normal print mode), 6.0 B(A) (black-and-white normal print mode), 2.7 B(A) (idle)  Energy star  Supplies life For information on page yield, visit www.hp.com/go/learnaboutsupplies, or see product packaging  Warranty  Standard one-year limited hardware warranty. Warranty and support options vary by product, country and local legal	Weight	Out of package: 2.62 kg, packaged: 4.2 kg				
Supplies life         For information on page yield, visit www.hp.com/go/learnaboutsupplies, or see product packaging           Warranty         Standard one-year limited hardware warranty. Warranty and support options vary by product, country and local legal	Operating environment	humidity: 20 to 80% RH; Recommended humidity: 5 to 90% RH; noise level per i	operating humidity: 20 to 80% so 9296: sound power: 6.9 B(A	RH; Storage temperature:-40 to 6 ) (black-and-white fast draft print n	60° C; Storage	
Supplies life         For information on page yield, visit www.hp.com/go/learnaboutsupplies, or see product packaging           Warranty         Standard one-year limited hardware warranty. Warranty and support options vary by product, country and local legal	Energy star	Yes				
, , , , , , , , , , , , , , , , , , , ,		For information on page yield, visit www.hp.com/go/learnaboutsupplies, or see product packaging				
	Warranty	Standard one-year limited hardware wa requirements.	rranty. Warranty and support op	otions vary by product, country an	d local legal	

## Ordering information

СВ774В HP Deskjet D5560 Printer, HP 300 Black Ink Cartridge, HP 300 Tri-colour Ink Cartridge, USB cable, HP software CD, setup guide, reference guide, power supply and cord

Accessories

	Accessories
Q6264A	HP Hi-Speed USB Cable (6
	ft./1.8 m)
C6520A	HP USB Cable 2.0 (a-b) 3 meter
	Supplies
CC640EE	HP 300 Black Ink Cartridge
CC643EE	HP 300 Tri-colour Ink Cartridge
CC641EE	HP 300XL Black Ink Cartridge
CC644EE	HP 300XL Tri-colour Ink Cartridge

	Media
Q6593A	HP Professional Matt Inkjet
	Paper-200 sht/A4/210 x 297
	mm
Q8691A	HP Advanced Glossy Photo
	Paper-25 sht/10 x 15 cm
	borderless
C5977B	HP Bright White Inkjet Paper-250
	abs / A 4 / 210 y 207 mm

# Service & Support

UG060E HP Care Pack, Next Business Day Exchange Service, 3 years
UG185E HP Care Pack, Exchange Service (standard turn around time), 3

years **UG233E** HP Care Pack, Return to Depot Hardware Support Service, 3 years. (UG233E: Only Baltics, Greece, Poland, Turkey, EEM, Slovenia, Czech Republic, Slovakia, Hungary. UG060E/UG185E: Rest of Europe).

For a complete list of supplies, media and accessories, please refer to the HP website at http://www.hp.com

http://www.hp.com













