



TS-253B-4G (Legacy)		
CPU	Intel® Celeron® J3455 4-core 1.5 GHz processor (burst up to 2.3 GHz)	
CPU Architecture	64-bit x86	
Graphic Processors	Intel® HD Graphics 500	
Floating Point Unit	Yes	
Encryption Engine	Yes (AES-NI)	
Hardware-accelerated Transcoding	Yes	
System Memory	4 GB SODIMM DDR3L (2 x 2 GB)	
Maximum Memory	8 GB (2 x 4GB)	
Memory Slot	2 x SODIMM DDR3L	
	For dual-DIMM configuration, you must use a pair of identical DDR3L modules.	
Flash Memory	4GB (Dual boot OS protection)	
Drive Bay	2 x 3.5-inch SATA 6Gb/s, 3Gb/s	
	The system is shipped without HDD.  For the HDD compatibility list, please visit <a href="https://www.qnap.com/compatibility/">https://www.qnap.com/compatibility/</a>	
Drive Compatibility	3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives	
Hot-swappable	Yes	
M.2 Slot	Optional via a PCIe adapter	
SSD Cache Acceleration Support	Yes	
Gigabit Ethernet Port (RJ45)	2	
	Expandable with an optional PCIe adapter	
10 Gigabit Ethernet Port	Optional via PCIe expansion card	
	Optional via PCIe expansion card	

Wake on LAN (WOL)	Yes
Jumbo Frame	Yes
PCIe Slot	1 Slot 1: PCIe Gen 2 x2 PCIe bandwidth limitations will restrict the NAS 10GbE performance.
USB 3.2 Gen 1 port	5
USB 3.2 Gen 2 (10Gbps) Port	Optional via a PCIe expansion card
USB QuickAccess	1 x USB 3.2 Gen 1 Type-C
SDXC Card Reader	1
IR Sensor	Yes (RM-IR004, RM-IR002, & MCE)
HDMI™ Output	2, HDMI™ 1.4b (up to 3840 x 2160 @ 30Hz)
Audio Input	2 x 3.5mm dynamic microphone input jacks
Audio Output	1 x built-in speaker, 1 x 3.5mm line out jack (for amplifier or headphone amplifier)
Form Factor	Tower
LED Indicators	Power/Status, LAN, USB, HDD1-2, SD card, USB QuickAccess
LCD Display/ Button	Monochrome OLED display with capacitive sensing Enter and Select buttons
Buttons	Power, USB copy, Reset, Capacitive touch buttons (select, enter)
Dimensions (HxWxD)	168 × 105 × 226 mm
Weight (Net)	1.67 kg
Weight (Gross)	2.82 kg
Operating Temperature	0 - 40 °C (32°F - 104°F)
Storage Temperature	-20 - 70°C (-4°F - 158°F)
Relative Humidity	5-95% RH non-condensing, wet bulb: 27°C (80.6°F)
Power Supply Unit	65W adapter, 100-240V
Power Consumption: HDD Sleep Mode	13.07 W
Power Consumption: Operating Mode, Typical	20.42 W
Fan	1 x 7mm, 12VDC
System Warning	Buzzer
Kensington Security Slot	Yes
Standard Warranty	2

Max. Number of 1500 Concurrent Connections (CIFS) - with Max. Memory

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications and refer to the hardware user manual to install compatible QNAP memory modules.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting. QNAP reserves the right to replace partial parts or accessories if the original is no longer available from its manufacturer/supplier. Any replacement would be fully tested and verified to meet strict compatibility and stability guidelines and will deliver identical performance to the original.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.