





TS-h1683XU-RP-E2236-128G (Legacy)			
CPU	Intel® Xeon® E E-2136/E-2236 6-core / 12-thread processor		
CPU Architecture	64-bit x86		
Floating Point Unit	Yes		
Encryption Engine	Yes (AES-NI)		
System Memory	128 GB UDIMM DDR4 ECC (4 x 32GB)		
Maximum Memory	128 GB (4 x 32 GB)		
Memory Slot	4 x UDIMM DDR4		
Flash Memory	5GB (Dual boot OS protection)		
Drive Bay	16 x 3.5-inch SATA 6Gb/s, 3Gb/s		
Drive Compatibility	3.5-inch bays:3.5-inch SATA hard disk drives2.5-inch SATA solid state drives		
Hot-swappable	Yes		
SSD Cache Acceleration Support	Yes		
GPU pass-through	Yes		
Gigabit Ethernet Port (RJ45)	4		
10 Gigabit Ethernet Port	2 x 10GbE SFP+ SmartNIC port, 2 x 10GBase-T port		
Wake on LAN (WOL)	Yes		
Jumbo Frame	Yes		

PCIe Slot	4 Slot 1: PCIe Gen 2 x4 (PCH) Slot 2: PCIe Gen 3 x8 (CPU) Slot 3: PCIe Gen 3 x4 (CPU) Slot 4: PCIe Gen 3 x4 (CPU)	
	Slot 2 and slot 4 are preinstalled with 10GbE network adapters. Card dimensions for PCIe slot $1\sim$ Slot 4: $220\times78.9\times18.76$ mm / $8.66\times3.10\times0.74$ inches. Wider cards can be installed if the next PCIe slot will not be used.	
USB 3.2 Gen 2 (10Gbps) Port	2 x Type-C USB 3.2 Gen 2 10Gbps 4 x Type-A USB 3.2 Gen 2 10Gbps	
Form Factor	3U Rackmount	
LED Indicators	HDD 1-16, Status, LAN, storage expansion port status	
Buttons	Power, Reset	
Dimensions (HxWxD)	130 × 442.4 × 573.5 mm	
	Excludes ear hook and the protruding part of the Power Supply Unit.	
Weight (Net)	17.52 kg	
Weight (Gross)	23.3 kg	
Operating Temperature	0 - 40 °C (32°F - 104°F)	
Storage Temperature	-20 - 70°C (-4°F - 158°F)	
Relative Humidity	5-95% RH non-condensing, wet bulb: 27°C (80.6°F)	
Power Supply Unit	500W(x2), 100-240V	
Power Consumption: Operating Mode, Typical	149 W	
	Tested with WD10EFRX fully populated.	
Fan	System fan: 3 x 80mm, 12VDC	
System Warning	Buzzer	
Standard Warranty	3	
Max. Number of Concurrent Connections (CIFS) - with Max. Memory	10000	

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications and refer to the hardware user manual to install compatible QNAP memory modules.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting. QNAP reserves the right to replace partial parts or accessories if the original is no longer available from its manufacturer/supplier. Any replacement would be fully tested and verified to meet strict compatibility and stability guidelines and will deliver identical performance to the original.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.				