



TVS-882BRT3-i7-32G (Legacy)		
CPU	Intel® Core™ i7-7700 4-core 3.6 GHz processor, Max turbo to 4.2 GHz	
CPU Architecture	64-bit x86	
Graphic Processors	9th-generation Intel® HD Graphics	
Floating Point Unit	Yes	
Encryption Engine	Yes (AES-NI)	
Hardware-accelerated Transcoding	Yes	
System Memory	32 GB UDIMM DDR4 (4 x 8GB)	
Maximum Memory	64 GB (4 x 16 GB)	
Memory Slot	4 x UDIMM DDR4	
Flash Memory	512MB (DOM for dual OS)	
Drive Bay	8 x 3.5-inch SATA 6Gb/s, 3Gb/s	
Drive Compatibility	3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives	
5.25-inch Expansion Bay	1 x 5.25" disc burner or 2 x slim SATA disc burners	
Hot-swappable	Yes	
M.2 Slot	2 x M.2 2242/2260/2280/22110 SATA 6Gb/s slots	
	The M.2 SSD is not included as standard. M.2 SSD operations can easily generate excessive heat. It is recommended to install a heatsink (from QNAP or a third-party provider) on the M.2 SSD.	
SSD Cache Acceleration Support	Yes	
GPU pass-through	Yes	
Gigabit Ethernet Port (RJ45)	4	

Wake on LAN (WOL)	Yes
Jumbo Frame	Yes
Thunderbolt Port	4 (Thunderbolt 3)
	Supports only Thunderbolt connections for Windows & Mac hosts and USB storage devices. Third-party Thunderbolt external storage devices are not supported.
PCIe Slot	3 Slot 1: PCIe Gen 3 x8 Slot 2: PCIe Gen 3 x4 Slot 3: PCIe Gen 3 x4
	2 x PCIe Gen3 x4 ports are preinstalled with two dual-port Thunderbolt 3 extension cards
USB 3.2 Gen 1 port	5
USB 3.2 Gen 2 (10Gbps) Port	Yes (Optional)
IR Sensor	Yes
HDMI™ Output	3, HDMI™ 1.4b
Audio Input	2 x 6.3mm dynamic microphone input jacks
Audio Output	2 x built-in speaker, 1 x 3.5mm line out jack (for amplifiers or speakers)
Form Factor	Tower
LED Indicators	System status, M.2 SSD, 3.5" HDD
LCD Display/ Button	Yes
Buttons	Power, Reset, USB Auto Copy
Buttons Dimensions (HxWxD)	Power, Reset, USB Auto Copy 234.6 × 369.9 × 319.8 mm
	.,
Dimensions (HxWxD)	234.6 × 369.9 × 319.8 mm
Dimensions (HxWxD) Weight (Net)	234.6 × 369.9 × 319.8 mm 11.23 kg
Dimensions (HxWxD) Weight (Net) Weight (Gross)	234.6 × 369.9 × 319.8 mm 11.23 kg 12.32 kg
Dimensions (HxWxD) Weight (Net) Weight (Gross) Operating Temperature	234.6 × 369.9 × 319.8 mm 11.23 kg 12.32 kg 0 - 40 °C (32°F - 104°F)
Dimensions (HxWxD) Weight (Net) Weight (Gross) Operating Temperature Storage Temperature	234.6 × 369.9 × 319.8 mm 11.23 kg 12.32 kg 0 - 40 °C (32°F - 104°F) -20 - 70°C (-4°F - 158°F)
Dimensions (HxWxD) Weight (Net) Weight (Gross) Operating Temperature Storage Temperature Relative Humidity Power Supply Unit Power Consumption:	234.6 × 369.9 × 319.8 mm 11.23 kg 12.32 kg 0 - 40 °C (32°F - 104°F) -20 - 70°C (-4°F - 158°F) 5-95% RH non-condensing, wet bulb: 27°C (80.6°F)
Dimensions (HxWxD) Weight (Net) Weight (Gross) Operating Temperature Storage Temperature Relative Humidity Power Supply Unit	234.6 × 369.9 × 319.8 mm 11.23 kg 12.32 kg 0 - 40 °C (32°F - 104°F) -20 - 70°C (-4°F - 158°F) 5-95% RH non-condensing, wet bulb: 27°C (80.6°F) Input: 100-240V~, 3-1.5A, 60-50Hz; Output: 250W
Dimensions (HxWxD) Weight (Net) Weight (Gross) Operating Temperature Storage Temperature Relative Humidity Power Supply Unit Power Consumption:	234.6 × 369.9 × 319.8 mm 11.23 kg 12.32 kg 0 - 40 °C (32°F - 104°F) -20 - 70°C (-4°F - 158°F) 5-95% RH non-condensing, wet bulb: 27°C (80.6°F) Input: 100-240V~, 3-1.5A, 60-50Hz; Output: 250W 93.82 W
Dimensions (HxWxD) Weight (Net) Weight (Gross) Operating Temperature Storage Temperature Relative Humidity Power Supply Unit Power Consumption: Operating Mode, Typical	234.6 × 369.9 × 319.8 mm 11.23 kg 12.32 kg 0 - 40 °C (32°F - 104°F) -20 - 70°C (-4°F - 158°F) 5-95% RH non-condensing, wet bulb: 27°C (80.6°F) Input: 100-240V~, 3-1.5A, 60-50Hz; Output: 250W 93.82 W Tested with drives fully populated. System fan: 3 × 80mm

Kensington Security Slot	Yes
Standard Warranty	2
Max. Number of Concurrent Connections (CIFS) - with Max. Memory	5000

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications and refer to the hardware user manual to install compatible QNAP memory modules.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting. QNAP reserves the right to replace partial parts or accessories if the original is no longer available from its manufacturer/supplier. Any replacement would be fully tested and verified to meet strict compatibility and stability guidelines and will deliver identical performance to the original.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.