



HP DesignJet T790 PostScript® Printer

The most productive 24-inch HP DesignJet printer¹ for small teams



QUALITY—Quickly produce outstanding results

- Six Original HP inks produce a wide color gamut ideal for color graphics.
- Original HP gray and photo black inks achieve precise line accuracy, dark blacks, and true neutral grays.
- Communicate with precision—produce plans, drawings, and maps with fine line quality, and up to 2400 dpi.
- Print quickly without sacrificing quality—create an A1/D-size print in 32 seconds with Economode.

CONVENIENCE—Speed up printing with easy workflow

- Print TIFF, JPEG, and PDF² files from your printer's USB thumb drive—no computer required.
- If you're on-the-go, attach your document to an email and send it directly to your printer via ePrint.³
- The intuitive touchscreen simplifies navigation and printing.

RELIABILITY—Plug-and-play printer for small teams

- Focus on your design—not printing—with this reliable HP DesignJet printer.
- Quick printing—in-printer processing architecture, added memory for processing even the most complex files.
- Print confidently knowing that, even if you're in a rush, this printer can handle all your files.

For more information, please visit www.totalofficesolution.biz

- ¹ Compared to other 24-inch HP DesignJet T-series printers.
- ² PDF files only available with PostScript® (PS) accessory (optional accessory to be purchased separately) or with the PostScript® version of the printer.
- 3 Local printing requires mobile device and printer to be on the same network (usually Wi-Fi access points bridge wireless to wired connections). Wireless performance is dependent on physical environment and distance from access point. Wireless operations are compatible with 2.4 GHz operations only. Remote printing requires an Internet connection to an HP web-connected printer. Wireless broadband use requires separately purchased service contract for mobile devices. Check with service provider for coverage and availability in your area

Technical specifications

| Print | Line drawings ⁴ | 32 sec/page on A1/D, 93 A1/D prints per hour | |
|----------------------|---|--|--|
| | Colour images ⁵ | Fast: 37 m²/hr (400 ft²/hr) on coated media Best: 2.8 m²/hr (30 ft²/hr) on glossy media | |
| | Print resolution | Up to 2400 x 1200 optimized dpi from 1200 x 1200 input dpi and Optimization For Photo Paper selected | |
| | Margins (top x bottom x left x right) | Roll: 5 × 5 × 5 × 5 mm (0.2 × 0.2 × 0.2 × 0.2 in) Sheet: 5 × 17 × 5 × 5 mm (0.2 × 0.67 × 0.2 × 0.2 in) | |
| | Technology | HP Thermal Inkjet | |
| | Ink types | Dye-based (C, G, M, pK, Y); pigment-based (mK) | |
| | Ink drop | 6 pl (C, G, M, pK); 9 pl (mK, Y) | |
| | Printheads | 3 (G & pK, mK & Y, M & C) | |
| | Line accuracy | +/- 0.1%6 | |
| | Minimum line width | 0.02 mm (0.0008 in) (HP-GL/2 addressable) | |
| | Guaranteed mini- mum line width | 0.06 mm (0.0024 in) (ISO/IEC 13660:2001(E)) ⁷ | |
| Media | Handling | Sheet feed, roll feed, automatic cutter | |
| | Weight | 60 to 328 g/m ² | |
| | Size | 210 to 610-mm (8.3 to 24-in) wide sheets; 279 to 610-mm (11 to 24-in) rolls | |
| | Thickness | Up to 0.8 mm (31.5 mil) | |
| Memory | 8 GB (virtual) ⁸ , 160 GB hard disk | | |
| Connectivity | Interfaces (standard) | Fast Ethernet (100Base-T), Hi-Speed USB 2.0 certified, EIO Jetdirect accessory slot | |
| | Print languages | Adobe® PostScript® 3™, Adobe PDF 1.7, HP-GL/2, TIFF, JPEG, CALS G4, HP PCL 3 GUI | |
| | Drivers (included) | HP-GL/2, HP-RTL drivers for Windows" (optimized for AutoCAD 2000 and higher); HP PCL 3 GUI driver for Mac OS X; PostScript Windows, Linux, and Mac drivers | |
| Dimensions | Printer | 1262 x 702 x 1050 mm (49.7 x 27.6 x 41.3 in) | |
| (w x d x h) | Shipping | 1440 x 766 x 770 mm (56.7 x 30.2 x 30.3 in) | |
| Weight | Printer | 60 kg (132 lb) | |
| | Shipping | 77 kg (170 lb) | |
| What's in the bo | | nter, printheads, introductory ink cartridges, printer stand ⁹ , spindle, quick poster, startup software, power cord | |
| Environmental | | re: 5 to 40°C (41 to 104°F) | |
| ranges | Storage temperature: -25 to 55°C (-13 to 131°F) | | |
| | Operating humidity: 20 to 80% RH | | |
| Acoustic | Sound pressure: 43 dB(A) (active); 29 dB(A) (standby) | | |
| | Sound power: 6.1 B(A) (active); 4.7 B(A) (standby) | | |
| Power consumption | < 120 watts (printing), < 27 watts (ready), < 7 watts (< 25 watts with embedded Digital Front End) (sleep), 0.1 watts (off) | | |
| Jumpuon | Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A max | | |
| Certification | Safety | USA and Canada (CSA certified), EU (LVD and EN60950-1 compliant), Russia (G0ST), Singapore (PSB), China (CCC), Argentina (IRAM), Mexico (NYCE), Korea (KATS) | |
| | Electromagnetic | Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM) China (CCC), Japan (VCCI), Korea (KCC) | |
| | Environmental | ENERGY STAR, WEEE, EU ROHS, China ROHS, REACH, FEMP, EPEAT Bronze | |
| | | 4 4. | |

- Mechanical printing time. Printed in Fast mode with Economode on, using HP Bright White Inkjet Paper (Bond) with Original HP inks.
- Mechanical printing time with Original HP inks.
- 6 +/-0.1% of the specified vector length or +/-0.2 mm (whichever greater) at 23°C (73°F), 50-60% relative humidity, on A0/E printing material in Best or Normal mode with HP Matte Film and Original HP inks.
- Measured on HP Matte Film.
- ⁸ Based on 640 MB RAM.

Warranty

- Stand not included in the box outside of North America and Latin America.
- Only available in Asia Pacific, Japan, and Europe Middle East and Africa.

One-year limited hardware warranty

- FSC® trademark license code FSC®-C017543, see fsc.org. PEFC™ trademark license code PEFC™/29-31-198, see pefc.org. Not all FSC®- or PEFC™-certified products are available in all regions.
- Can be recycled through commonly available recycling programs.
- Not available in Europe, Middle East, and Africa.
- Not available in North America and Latin America.
- Applicable to HP DesignJet T-series Printers, Printers, and eMFPs. True neutral grays produced by printers compatible with the HP Three-black ink set.

Ordering information

| Product | CR648A | HP DesignJet T790 24-in PostScript® Printer |
|--------------------------------------|---------|--|
| Accessories | CN538A | HP DesignJet 3-in Core Adapter |
| | CQ783A | HP DesignJet T7xx 24-in Spindle |
| | Q6663A | HP DesignJet T/Z 24-in Stand ¹⁰ |
| | G6H50B | HP SD Pro 44-in Scanner |
| | G6H51B | HP HD Pro 42-in Scanner |
| | J8025A | HP Jetdirect 640n Print Server |
| Original HP printheads | C9380A | HP 72 Gray and Photo Black Printhead |
| | C9383A | HP 72 Magenta and Cyan Printhead |
| | C9384A | HP 72 Matte Black and Yellow Printhead |
| Original | C9397A | HP 72 69-ml Photo Black Ink Cartridge |
| HP ink cartridges | C9398A | HP 72 69-ml Cyan Ink Cartridge |
| | C9399A | HP 72 69-ml Magenta Ink Cartridge |
| | C9400A | HP 72 69-ml Yellow Ink Cartridge |
| | C9401A | HP 72 69-ml Gray Ink Cartridge |
| | C9403A | HP 72 130-ml Matte Black Ink Cartridge |
| | C9370A | HP 72 130-ml Photo Black Ink Cartridge |
| | C9371A | HP 72 130-ml Cyan Ink Cartridge |
| | C9372A | HP 72 130-ml Magenta Ink Cartridge |
| | C9373A | HP 72 130-ml Yellow Ink Cartridge |
| | C9374A | HP 72 130-ml Gray Ink Cartridge |
| Original HP large format printing | C6035A | HP Bright White Inkjet Paper (FSC* certified) 11 🛟 12 610 mm x 45.7 m (24 in x 150 ft) |
| materials | C6019B | HP Coated Paper (PEFC™ certified) 11 \$\infty\$12 610 mm x 45.7 m (24 in x 150 ft) |
| | C6029C | HP Heavyweight Coated Paper (PEFC™ certified) 11 ♣ 12 610 mm x 30.5 m (24 in x 100 ft) |
| | CZ987A | HP Premium Satin Photo Paper (FSC* certified) ¹¹ 610 mm x 15.2 m (24 in x 50 ft) |
| Service and support | HP603E | HP 3 year Next Business Day Onsite HW Support w/Defective Media Retention for DesignJet T790-24in ¹³ |
| | HP605E | HP 5 year Next Business Day Onsite HW Support w/Defective Media Retention for DesignJet T790-24in |
| | HP995PE | HP 1 year Post Warranty NBD Onsite HW Support w/Defective Media Retention for DesignJet T790-24in ¹⁴ |
| | U7UW5PE | HP 2 year Post Warranty NBD Onsite HW Support w/Defective Media Retention for DesignJet T790-24 |
| | H4518E | HP Network Installation Service for DesignJet High-end and Midrange |
| | U1XV4E | HP Preventive Maintenance Onsite Service for 2 hour for DesignJet Printers (Single Event) |

HP **DesignJet Support Services** offer solutions for business critical environments — installation, extended support and maintenance, as well as variety of value added services.

Use **Original HP inks** and printheads to experience consistent high quality and reliable performance that enable less downtime. These critical components are designed and engineered together as an optimized printing system to provide precise line accuracy as well as dark blacks and true neutral grays. ¹⁹

Eco Highlights



- ENERGY STAR® qualified and EPEAT Bronze registered¹
- Free, convenient HP ink cartridge and printhead recycling²
- FSC®-certified papers and a range of recyclable HP media with a take-back program²

¹ EPEAT registered where applicable and/or supported. See <u>epeat.net</u> for registration status by country. ² Program availability varies.

Please recycle large-format printing hardware and printing supplies



















© Copyright 2016 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency.

Adobe, PostScript, and Adobe PostScript 3 are trademarks of Adobe Systems Incorporated. Windows is a U.S. registered trademark of Microsoft Corporation. Mac and the Mac logo are trademarks of Apple Computer, Inc., registered in the U.S. and other countries.

