



Absorptive Coaxial SP2T Switch 2 - 36GHz



Features

- Ultra Wide Band Operation 2-36GHz
- Functional Bandwidth : 2GHz to 43.5GHz
- TTL compatible driver included
- Fast Switching Speed
- Low Insertion Loss and High Isolation
- Customization available upon request

Electrical Specifications, $T_A = +25\text{ }^\circ\text{C}$, $V_{dd} = +5\text{V}/-5\text{V}$, $TTL = 0 / +5\text{V}$

Description	PN: RFSP2TA0236G									
	SP2T Absorptive Switch									
	Low Power Cold Switching									
Parameters	Min.	Typ.	Max.	Min.	Typ.	Max.	Min.	Typ.	Max.	Units
Frequency Range	2		18	18		26.5	26.5		36	GHz
Insertion Loss		2.2	3.5		3.8	4.5		4.5	5.0	dB
Insertion Loss Temperature Coefficient		0.003			0.003			0.003		dB/°C
Isolation	60	85		50	60		45	55		dB
Input VSWR		1.6	2.0		2.0	2.0		1.8	2.0	: 1
Output VSWR		1.6	2.0		2.0	2.0		1.8	2.0	: 1
RF Input power			23			23			23	dBm
DC Power Dissipation (CW)		0.5			0.5			0.5		W
0.1dB Compression Point($P_{0.1dB}$)		23			23			23		dBm
IIP3		50			45			40		dBm
Switching Speed		50	60		50	60		50	60	ns
Weight	0.71									ounces
Impedance	50									Ω
Bias Current (+5V / -5V)	110/50									mA
Input / Output Connectors	2.92mm-Female									
Finish	Gold Plated									
Material	Aluminum									
Sealing	Hermetically Sealed (Optional)									



Absolute Maximum Ratings

Biasing	+5V±10%/-5V±10%
TTL Control Voltage	0~0.8V/2.8~5V

Note: TTL pins cannot be connected to the negative voltage otherwise the internal driver will be damaged.

Ordering Information

Part No.	ECCN	Description
RFSP2TA0236G	EAR99	SP2T 2-36PIN Diode Switch

Environmental Specifications and Test Standards


Parameter	Standard	Description
Operational Temperature	MIL-STD-39016	-45°C~+85°C
Storage Temperature		-55°C~+125°C
Thermal Shock		1 Hour@ -45°C → 1 Hour @ +85°C (5 Cycles)
Random Vibration		Acceleration Spectral Density 6 (m/s) Total 92.6 RMS
Electrical & Temperature Burn In		Temperature +85°C for 72 Hours
Shock		1. Weight >20g, 50g half sine wave for 11ms, Speed variation 3.44m/s 2. Weight <=20g, 100g Half sine wave for 6ms, Speed variation 3.75m/s 3. Total 18 times (6 directions, 3 repetitions per direction).
Altitude		Standard: 30,000 Ft (Epoxy Sealed Controlled Environment) Optional: Hermetically Sealed (60,000 ft. 1.0 PSI min)
Hermetically Sealed (Optional)	MIL-STD-883	MIL-STD-883 (For Hermetically Sealed Units)

Absorptive Coaxial Single Pole Double Throw Switch 2-36GHz




Typical Performance Plots


Insertion Loss @+25°C




Input VSWR @+25°C




Output VSWR @+25°C




Isolation @+25°C




Insertion Loss @-45°C




Input VSWR @-45°C



Output VSWR @-45°C




Isolation @-45°C







Insertion Loss @+85°C




Input VSWR @+85°C




Output VSWR @+85°C




Isolation @+85°C



Switching Speed




Switching Speed





Outline Drawing:

All Dimensions in mm [inches]



Truth Table

Control Input TTL	Signal Path State
0	J0-J2
1	J0-J1
Control Pin Customization available upon request	



Important Notice

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information. RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.

Absorptive Coaxial Single Pole Double Throw Switch 2-36GHz