

Get a Quote

Overview

JL685A is an Aruba Instant On 1930 48G 4SFP/SFP+ Switch. Aruba Instant On 1930 switches features advanced, smart-managed, fixed configuration Gigabit switches designed for small businesses that are easy-to-deploy and affordable. They're made to handle today's bandwidth-heavy applications like voice and video conferencing, enabling consistent connectivity to enhance performance.

Quick Spec

Figure 1 shows the appearance of JL685A.



Table 1 shows the quick spec.

Model	JL685A
I/O ports and slots	48 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only 4 SFP+ 1/10GbE ports
Dimension	17.42(w) x 11.12(d) x 1.73(h) in (44.25 x 28.24 x 4.39 cm) (1U height)
Processor and memory	ARM Cortex-A9 @ 800 MHz, 512 MB SDRAM, 256 MB flash; packet buffer: 1.5 MB
Throughput (Mpps)	130.95 Mpps
Switching capacity	176 Gbps

Product Details

Figure 2 shows the front panel of JL685A.



Figure 3 shows the back panel of JL685A.



Aruba Instant On 1930 switches provide these key features:

- (1) Smart-managed layer 2+ Ethernet switch series ready to deploy in 8-, 24- and 48-port for non-PoE and Class 4 PoE (i.e. PoE+) models
- (2) PoE to power APs and IoT devices like IP phones, surveillance cameras and door locks
- (3) Two dedicated 1G SFP fiber ports on 8-port models, and four dedicated 1G/10G SFP+ fiber ports on 24-/48-port models to eliminate traffic bottlenecks across your network
- (4) Security controls let you define access in each area of your network, keeping your business data safe
- (5) Convenient mobile app and web-based GUI for set up, management and troubleshooting

Supported Transceivers

Table 2 shows the recommended transceivers.

Model	Description
J4858D	Aruba 1G SFP LC SX 500m MMF XCVR (5 Units)
J4859D	Aruba 1G SFP LC LX 10km SMF Transceivers (5 Units)
J8177D	Aruba 1G SFP RJ45 T 100m Cat5e XCVR (5 Units)
J9150D	Aruba 10G SFP+ LC SR 300m MMF XCVR:Aruba Aruba Campus Transceivers
J9281D	Aruba 10G SFP+ to SFP+ 1m DAC Cable
J9283D	Aruba 10G SFP+ to SFP+ 3m DAC Cable

Compare to Similar Items

Table 3 shows the comparison.

Model	Description	Gig Ports	Uplink Ports	Class 4 PoE
JL680A	Aruba Instant On 1930 8G 2SFP Switch	8	2 SFP	–
JL681A	Aruba Instant On 1930 8G Class4 PoE 2SFP 124W Switch	8	2 SFP	124W
JL682A	Aruba Instant On 1930 24G 4SFP/SFP+ Switch	24	4 SFP/SFP+	–
JL683A	Aruba Instant On 1930 24G Class4 PoE 4SFP/SFP+ 195W Switch	24	4 SFP/SFP+	195W
JL684A	Aruba Instant On 1930 24G Class4 PoE 4SFP/SFP+ 370W Switch	24	4 SFP/SFP+	370W
JL685A	Aruba Instant On 1930 48G 4SFP/SFP+ Switch	48	4 SFP/SFP+	–
JL686A	Aruba Instant On 1930 48G Class4 PoE 4SFP/SFP+ 370W Switch	48	4 SFP/SFP+	370W

Get More Information

Do you have any question about the JL685A?

Contact us now via [Live Chat](#) or sales@router-switch.com.

Specification

JL685A Specification	
I/O ports and slots	48 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only 4 SFP+ 1/10GbE ports
Dimension	17.42(w) x 11.12(d) x 1.73(h) in (44.25 x 28.24 x 4.39 cm) (1U height)
Processor and memory	ARM Cortex-A9 @ 800 MHz, 512 MB SDRAM, 256 MB flash; packet buffer: 1.5 MB
Throughput (Mpps)	130.95 Mpps
Switching capacity	176 Gbps
Operating temperature	32°F to 104°F (0°C to 40°C)
Operating relative humidity	15% to 95% @ 104°F (40°C)
Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
Nonoperating/Storage relative humidity	15% to 95% @ 140°F (60°C)
Altitude	up to 10,000 ft (3 km)
Idle power	16.8 W
PoE	Not Support
Power Supply	Internal power supply

Want to Buy

[Order Now](#)[Get a Quote](#)

Why Router-switch.com

As a leading network hardware supplier, Router-switch.com focuses on original new ICT equipment of [Cisco](#), [Huawei](#), [HPE](#), [Dell](#), [Hikvision](#), [Juniper](#), [Fortinet](#), etc.



200+

Countries we Sold



18,000+

Customers Trusted



\$20,000,000

Inventory Available



50%-98%

Off Global List Price



100%

Safe Online Shopping

Contact Us

- Tel: +1-626-655-0998 (USA) +852-3050-1066 / +852-3174-6166
- Fax: +852-3050-1066 (Hong Kong)
- Email: sales@router-switch.com