

Get a Quote

## Overview

LTO-7 Ultrium 15000 FC Drive Upgrade Kit.

### Quick Specs

Figure 1 shows the appearance of N7P36A.



Table 1 shows the Quick Specs.

Product Number:	N7P36A
Product Description:	LTO-7 Ultrium 15000 FC Drive Upgrade Kit
Product Line:	HPE StoreEver
Connector Type:	29 pin internal SAS (SFF-8482)
Interface (Storage):	8Gb Fibre Channel
Average Seek Access Time:	12 sec
Buffer Size:	1024 MB
Compressed Capacity:	15 TB
Data Transfer Rate:	300 MBps
Data Transfer Rate (Compressed):	750 MBps
Data Transfer Rate (Compressed) (GBph):	2.7
Data Transfer Rate (GBph):	1.08
Form Factor:	5.25" x 1/2H
Form Factor (metric):	13.3 cm x 1/2H
Interface Type:	Serial Attached SCSI 2
Native Capacity:	6 TB

<b>Recording Standard:</b>	Ultrium 6 , Ultrium 7
<b>Recording Standard (for SD):</b>	LTO Ultrium 7
<b>Supported Tape Cartridges (Read and Write):</b>	Ultrium 6 , Ultrium 7
<b>Type:</b>	LTO Ultrium
<b>Form Factor:</b>	5.25" x 1/2H
<b>Form Factor (metric):</b>	13.3 cm x 1/2H

## Get More Information

Do you have any question about the N7P36A?

Contact us now via [Live Chat](#) or [sales@router-switch.com](mailto:sales@router-switch.com).

## Specification

N7P36A Specification	
Header	
Compatibility	PC, Unix
Manufacturer	Hewlett-Packard
Packaged Quantity	1
Product Line	HPE StoreEver
Model	LTO-7 Ultrium 15000 FC Drive Upgrade Kit
Brand	HPE
Interface Provided	
Qty	1
Interface (Storage)	8Gb Fibre Channel
Storage Removable	
Type	LTO Ultrium
Native Capacity	6 TB
Compressed Capacity	15 TB
Media Type	LTO Ultrium
Recording Standard	Ultrium 6, Ultrium 7
Interface Type	8Gb Fibre Channel
Buffer Size	1024 MB
Average Seek Access Time	12 sec
Data Transfer Rate	300 MBps
Data Transfer Rate (Compressed)	750 MBps
Form Factor	5.25 x 1/2H

N7P36A Specification	
Recording Standard (for SD)	LTO Ultrium 7
Data Transfer Rate (Compressed) (GBph)	2.7
Data Transfer Rate (GBph)	1.08
Supported Tape Cartridges (Read and Write)	Ultrium 6, Ultrium 7
Form Factor (metric)	13.3 cm x 1/2H
Storage	
Type	Tape library drive module
Enclosure Type	Internal
Key Features	Encryption
Miscellaneous	
Compliant Standards	BSMI, C-Tick, CAN/CSA C22.2 No. 60950, cCSAus, EN 60950, FCC CFR47 Part 15, IEC 60950, NOM, RRL, TUV, VCCI
Bay Required	
Type	Front accessible
Form Factor	5.25 x 1/2H
Total Qty	1
Form Factor (metric)	13.3 cm x 1/2H
Environmental Parameters	
Min Operating Temperature	50 °F
Max Operating Temperature	104 °F
Humidity Range Operating	20 - 80% (non-condensing)
Power Device	
Type	None
Slot Provided	
Type	None
Storage Controller	
Type	None

## Want to Buy

[Order Now](#)
[Get a Quote](#)

## Why Router-switch.com

As a leading network hardware supplier, Router-switch.com focuses on original new ICT equipment of [Cisco](#), [Huawei](#), [HPE](#), [Dell](#), [Hikvision](#), [Juniper](#), [Fortinet](#), etc.



200+

Countries we Sold



18,000+

Customers Trusted



\$20,000,000

Inventory Available



50%-98%

Off Global List Price



100%

Safe Online Shopping

## Contact Us

---

- Tel: +1-626-655-0998 (USA) +852-3050-1066 / +852-3174-6166
- Fax: +852-3050-1066 (Hong Kong)
- Email: [sales@router-switch.com](mailto:sales@router-switch.com)