

Get a Quote

## Overview

N9K-C93120TX is the Nexus 9300 with 96p 100M/1/10G-T and 6p 40G QSFP. The Cisco Nexus 9300 platform consists of fixed-port switches designed for top-of-rack (ToR) and middle-of-row (MoR) deployment in data centers that support enterprise applications, service provider hosting, and cloud computing environments. They are Layer 2 and 3 nonblocking 10 and 40 Gigabit Ethernet switches with up to 2.56 terabits per second (Tbps) of internal bandwidth.

## Quick Specs

Table 1 shows the Quick Specs.

<b>Product Code</b>	N9K-C93120TX
<b>Ports</b>	96 fixed 1/10GBASE-T and 6 QSFP+ ports
<b>Supported speeds</b>	100 Megabit Ethernet and 1/10 Gigabit Ethernet speeds
<b>40 Gigabit Ethernet uplink ports</b>	6 fixed QSFP+ ports
<b>Physical (H x W x D)</b>	3.5 x 17.5 x 22.5 in. (8.9 x 44.5 x 57.1 cm)
<b>Weight</b>	26 lb (11.8 kg) (without power supplies, fans, or uplink module)

## Product Details

Table 2 shows Cisco Nexus 9300 Platform Switch Features.

Feature	Benefit
<b>Predictable high performance</b>	Latency of 1 to 2 microseconds with up to 1.28 Tbps of bandwidth enables customers to build a robust switch fabric scaling from as few as 200 10-Gbps server ports to more than 200,000 10-Gbps server ports.
<b>Increased integrated buffer space</b>	Up to a total of 50 MB of integrated shared buffer space allows better management of speed mismatch between access and uplink ports.
<b>Designed for availability</b>	Hot-swappable, redundant power supplies and fan trays increase availability.
<b>Flexible airflow configuration</b>	Port-side intake and port-side exhaust airflow configurations are both supported.
<b>CPU, SSD, and memory</b>	Dual-core 2.5-GHz x86 CPUs with 64-GB SSD drive and 16 GB of memory provide enhanced network performance.
<b>Power efficiency</b>	All Cisco Nexus 9000 Series power supplies are 80 Plus Platinum rated.
<b>Advanced optics</b>	Cisco offers a pluggable 40 Gigabit Ethernet QSFP+ transceiver that enables customers to use existing 10 Gigabit Ethernet data center cabling to support 40 Gigabit Ethernet connectivity. This technology facilitates adoption of 40 Gigabit Ethernet with no cable infrastructure upgrade cost.

## The Accessories

Table 3 shows the supported accessories.

Model	Description
<a href="#">N9K-M6PQ-E</a>	Uplink Module for Nexus 9300, 6p 40G QSFP
<a href="#">N9K-M6PQ</a>	Uplink Module for Nexus 9300, 6p 40G QSFP
<a href="#">N9K-M12PQ</a>	Uplink Module for Nexus 9300, 12p 40G QSFP

<a href="#">N9K-M4PC-CFP2</a>	Uplink Module for Nexus 9300, 4p 100G
<a href="#">UCSC-PSU-930WDC</a>	Nexus 9000 930W DC PS, Port-side Intake
<a href="#">UCS-PSU-6332-DC</a>	Nexus 9000 930W DC PS, Port-side Exhaust
<a href="#">N9K-PUV-1200W</a>	Nexus 9300 1200W Universal Power Supply, Bi-directional air flow and Supports AC/HVDC
<a href="#">N9K-C9300-FAN2</a>	Nexus 93128 & 9396 Fan 2, Port-side Intake
<a href="#">N9K-C9300-FAN2-B</a>	Nexus 93128 & 9396 Fan 2, Port-side Exhaust
<a href="#">NXA-FAN-30CFM-F</a>	Nexus 2K/3K/9K Single Fan for 1RU switch, port side exhaust airflow
<a href="#">NXA-FAN-30CFM-B</a>	Nexus 2K/3K/9K Single Fan for 1RU switch, port side intake airflow
<a href="#">N93-LAN1K9=</a>	Enhanced L3 including full OSPF, EIGRP, BGP for Nexus 9200/9300 Platform

## Compare to Similar Items

Table 4 shows the comparison.

Product Code	N9K-C93120TX	<a href="#">N9K-C93128TX</a>
Ports	96 fixed 1/10GBASE-T and 6 QSFP+ ports	96 fixed 1/10GBASE-T ports
Supported speeds	100 Megabit Ethernet and 1/10 Gigabit Ethernet speeds	100 Megabit Ethernet and 1/10 Gigabit Ethernet speeds
Physical (H x W x D)	3.5 x 17.5 x 22.5 in. (8.9 x 44.5 x 57.1 cm)	5.3 x 17.5 x 22.5 in. (13.3 x 44.5 x 57.1 cm)
Weight	26 lb (11.8 kg) (without power supplies, fans, or uplink module)	32.56 lb (14.8 kg) (without power supplies, fans, or uplink module)

## Get More Information

Do you have any question about the Cisco N9K-C93120TX?

Contact us now via [Live Chat](#) or [sales@router-switch.com](mailto:sales@router-switch.com).

## Specification

N9K-C93120TX Specification	
Ports	96 fixed 1/10GBASE-T and 6 QSFP+ ports
Supported speeds	100 Megabit Ethernet and 1/10 Gigabit Ethernet speeds
40 Gigabit Ethernet uplink ports	6 fixed QSFP+ ports
	Advanced QSFP+ optics enable connectivity using existing 10 Gigabit Ethernet fiber. The switch offers 25 MB of additional packet buffer space shared with all ports for more resilient operations.
Power supplies (up to 2)	1200W AC, 930W DC, or 1200W HVAC/HVDC
Typical power (AC)	542W
Maximum power (AC)	948W
Input voltage (AC)	100 to 240V *PSU redundancy is not supported when used in 110V
Input voltage (HVAC)	200 to 277V
Input voltage (DC)	-40V to -72V DC (min-max) -48V to -60V DC (nominal)

Input voltage (HVDC)	-240 to -380V
Frequency (AC)	50 to 60 Hz
Fans	2
Physical (H x W x D)	3.5 x 17.5 x 22.5 in. (8.9 x 44.5 x 57.1 cm)
RoHS compliance	Yes
Weight	26 lb (11.8 kg) (without power supplies, fans, or uplink module)

## Want to Buy

---

Order Now

Get a Quote

## Why Router-switch.com

---

As a leading network hardware supplier, Router-switch.com focuses on original new ICT equipment of [Cisco](#), [Huawei](#), [HPE](#), [Dell](#), [Hikvision](#), [Juniper](#), [Fortinet](#), etc.



200+

Countries we Sold



18,000+

Customers Trusted



\$20,000,000

Inventory Available



50%-98%

Off Global List Price



100%

Safe Online Shopping

## Contact Us

---

- Tel: +1-626-655-0998 (USA) +852-3050-1066 / +852-3174-6166
- Fax: +852-3050-1066 (Hong Kong)
- Email: [sales@router-switch.com](mailto:sales@router-switch.com)