

Cisco SFP-OC3-IR1 Datasheet

For Informational Purposes Only

Data Compiled by SanSpot

Cisco SFP-OC3-IR1 Duplex SFP .155Gbps 15 km SMF DDM 1310nm

SFP-OC3-IR1 Features

- Cisco 100BASE-SX Ethernet SFP
- Up-to 15 km over SMF @ .155Gbps
- 1310nm Duplex SFP Transceiver
- 0°C - 70°C Operating Case Temperature
- SFF-8724 Digital optical monitoring
- Hot-swappable for SFP LC ports
- Cisco 90 day standard warranty
- Cisco SFP can be covered by SMARTnet
- SFP MSA / IEEE Std 802.3
- Cisco SFP-OC3-IR1 is RoHS compliant



Applications

- OC-3/STM-1

Description

The Cisco SFP-OC3-IR1 100BASE-SX Ethernet transceiver is a Duplex SFP transceiver for optical communications, rated for distances up to 15 km and a maximum bandwidth of .155Gbps. The SFP-OC3-IR1 transceiver operates at 1310nm wavelength. The Cisco industry-standard Small Form-Factor Pluggable Interface Converter (SFP) for packet-over-SONET/SDH (POS), optical networking, and ATM applications are hot-swappable optical interfaces that plug into a variety of ports on Cisco router interfaces.

Cisco SFP optics for POS and ATM applications plug into a variety of SFP-based POS, TDM and ATM interfaces on Cisco router products. This line of SFP optics supports : OC-3/STM-1 (155

About this Data Sheet

This data sheet has been compiled by SanSpot as a service to its clients and is based on publicly available information from the manufacturer at the time of this publication. For most up-to-date information, please visit manufacturer website. SanSpot is not responsible for omissions or typographical errors.