

3.5 HDD DATA SHEET

Tough. Ready. Scalable Purpose-built for Connected-Home, SOHO, & Small-to-Medium Business NAS Environments



IronWolf™ is designed for consumer and commercial NAS. Delivering Tough, Ready and Scalable 24x7 performance in multi-bay, networked environments.



Best-Fit Applications

- Consumer and Commercial NAS
- Desktops and Workstations
- Multimedia Servers



Key Advantages

Optimized for NAS with AgileArray™ enables Dual-Plane Balancing and Time-Limited Error Recovery to deliver best-in-class RAID performance in multi-bay systems.

Always On, Always Accessible IronWolf drives are designed for 24x7 usage, allowing users to access their data any time, anywhere.

All-CMR Portfolio All IronWolf drives utilize Conventional Magnetic Recording (CMR) technology for consistent, best-in-class NAS performance.

Up to 12TB Broad range of capacity options to deliver scalable and cost-efficient storage solutions.

Built Tough IronWolf drives are rated for 180TB/year workload, allowing consumer and commercial NAS users to seamlessly store and work with large amounts of networked data.

Superior Reliability and Dependability IronWolf drives are rated for 1M hours MTBF and include a 3-year limited warranty for hassle-free data storage and best-in-class total cost of ownership (TCO)

Rotational Vibration (RV) sensors¹. Built-in RV sensors for vibration tolerance and consistent performance in multi-bay systems.

IronWolf Health Management (IHM)² Actively protect your NAS data with Prevention, Intervention, and Recovery recommendations to ensure peak system health.

Peace of mind with Data Recovery³ IronWolf drives include three years of complimentary Rescue Data Recovery Services - in-house secure facilities, with an industry-leading recovery rate of 95% - so you do not have to incur high recovery costs in the event of accidental data corruption or drive damage.

¹ Refer to specifications table for models supported.

² IHM is enabled on all leading NAS systems. Please check with your NAS vendor or a Seagate sales representative for more details.

³ Rescue services not available in all countries. Contact your Seagate sales representative for further details.



Specifications	12TB	10TB	10TB	8TB	8TB
Capacity	12TB	10TB	10TB	8TB	8TB
Standard Model Number	ST12000VN0008	ST10000VN0008	ST10000VN000	ST8000VN004	ST8000VN002
Interface	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s
Features and Performance					
Drive Bays Supported	1-8 Bays	1-8 Bays	1-8 Bays	1-8 Bays	1-8 Bays
Recording Technology	CMR	CMR	CMR	CMR	CMR
Drive Design (Air or Helium)	Helium	Helium	Air	Air	Air
Workload Rate Limit (WRL)	180	180	180	180	180
Rotational Vibration (RV) Sensor	Yes	Yes	Yes	Yes	Yes
Dual-Plane Balance	Yes	Yes	Yes	Yes	Yes
Error Recovery Control	Yes	Yes	Yes	Yes	Yes
Max. Sustained Transfer Rate OD (MB/s)	210MB/s	210MB/s	210MB/s	210MB/s	202MB/s
Spindle Speed (RPM)	7,200	7,200	7,200	7,200	5,400
Cache (MB)	256	256	256	256	256
Reliability					
Load/Unload Cycles	600,000	600,000	600,000	600,000	600,000
Nonrecoverable Read Errors Rate, Max	1 per 10E15	1 per 10E15	1 per 10E15	1 per 10E15	1 per 10E14
Power-On Hours	8,760	8,760	8,760	8,760	8,760
Mean Time Between Failures (MTBF, hours)	1,000,000	1,000,000	1,000,000	1,000,000	1,000,000
Rescue Data Recovery Services (years) ⁴	3	3	3	3	3
Warranty, Limited (years)	3	3	3	3	3
Power Management					
Startup Current, Typical (12V, A)	1.8	1.8	1.8	1.8	1.8
Average Operating Power	7.3	7.8	10.1	10.1	5.3
Idle Power Average (W)	5.1W	5W	7.8W	7.8W	4W
Standby Mode/Sleep Mode, Typical (W)	1.17/1.17	1.17/1.17	1/1	1/1	0.25/0.25
Voltage Tolerance, Inc. Noise (5V / 12V)	±5% / ±10%	±5% / ±10%	±5% / ±10%	±5% / ±10%	±5% / ±10%
Environmental/Temperature					
Operating Temperature (ambient, min °C)	0	0	0	0	0
Operating Temperature (drive reported, max °C) ⁵	65	65	65	65	65
Nonoperating Temperature (ambient, min / max °C)	-40 / 70	-40 / 70	-40 / 70	-40 / 70	-40 / 70
Environmental/Shock					
Shock, Operating/Nonoperating: 2ms (max)	50Gs/200Gs	70Gs/250Gs	70Gs/300Gs	70Gs/300Gs	80Gs/300Gs
Environmental/Acoustics					
Acoustics, Idle (typical, measured in Idle 1 state) (dBA)	28	28	28	28	25
Acoustics, Seek (typical) (dBA)	30	30	32	32	26
Physical					
Height (mm/in)	26.11mm/1.028in	26.11mm/1.028in	26.11mm/1.028in	26.11mm/1.028in	26.11mm/1.028in
Width (mm/in, max)	101.85mm/4.01in	101.85mm/4.01in	101.85mm/4.01in	101.85mm/4.01in	101.85mm/4.01in
Depth (mm/in, max)	146.99mm/5.787in	146.99mm/5.787in	146.99mm/5.787in	146.99mm/5.787in	146.99mm/5.787in
Weight (g/lb, typical)	690g/1.521lb	690g/1.521lb	720g/1.59lb	720g/1.59lb	630g/1.389lb
Carton Unit Quantity	20	20	20	20	20
Cartons per Pallet/Cartons per Layer	40/8	40/8	40/8	40/8	40/8

⁴ Rescue services are not available in all countries. Contact your Seagate sales representative for more info.

⁵ It is not recommended to operate at sustained drive temperatures above 60°C. Higher temperatures may affect drive health.



Specifications	6TB	6TB	4TB	4TB	3TB
Capacity	6TB	6TB	4TB	4TB	3TB
Standard Model Number	ST6000VN006	ST6000VN001	ST4000VN006	ST4000VN008	ST3000VN006
Interface	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s
Features and Performance					
Drive Bays Supported	1-8 Bays	1-8 Bays	1-8 Bays	1-8 Bays	1-8 Bays
Recording Technology	CMR	CMR	CMR	CMR	CMR
Drive Design (Air or Helium)	Air	Air	Air	Air	Air
Workload Rate Limit (WRL)	180	180	180	180	180
Rotational Vibration (RV) Sensor	Yes	Yes	Yes	Yes	Yes
Dual-Plane Balance	Yes	Yes	Yes	Yes	Yes
Error Recovery Control	Yes	Yes	Yes	Yes	Yes
Max. Sustained Transfer Rate OD (MB/s)	202MB/s	190MB/s	202MB/s	180MB/s	202MB/s
Spindle Speed (RPM)	5,400	5,400	5,400	5,900	5,400
Cache (MB)	256	256	256	64	256
Reliability					
Load/Unload Cycles	600,000	600,000	600,000	600,000	600,000
Nonrecoverable Read Errors Rate, Max	1 per 10E14	1 per 10E14	1 per 10E14	1 per 10E14	1 per 10E14
Power-On Hours	8,760	8,760	8,760	8,760	8,760
Mean Time Between Failures (MTBF, hours)	1,000,000	1,000,000	1,000,000	1,000,000	1,000,000
Rescue Data Recovery Services (years) ⁴	3	3	3	3	3
Warranty, Limited (years)	3	3	3	3	3
Power Management					
Startup Current, Typical (12V, A)	1.8	1.8	1.8	1.8	1.8
Average Operating Power	5.3	5.3	3.7	4.8	3.7
Idle Power Average (W)	4W	4W	3.2W	3.95W	3.2W
Standby Mode/Sleep Mode, Typical (W)	0.25/0.25	0.25/0.25	0.25/0.25	0.5/0.5	0.25/0.25
Voltage Tolerance, Inc. Noise (5V / 12V)	±5% / ±10%	±5% / ±10%	±5% / ±10%	±5% / ±10%	±5% / ±10%
Environmental/Temperature					
Operating Temperature (ambient, min °C)	0	0	0	0	0
Operating Temperature (drive reported, max °C) ⁵	65	65	65	65	65
Nonoperating Temperature (ambient, min / max °C)	-40 / 70	-40 / 70	-40 / 70	-40 / 70	-40 / 70
Environmental/Shock					
Shock, Operating/Nonoperating: 2ms (max)	80Gs/300Gs	70Gs/250Gs	80Gs/300Gs	80Gs/300Gs	80Gs/300Gs
Environmental/Acoustics					
Acoustics, Idle (typical, measured in Idle 1 state) (dBA)	25	26	23	23	23
Acoustics, Seek (typical) (dBA)	26	27	25	25	25
Physical					
Height (mm/in)	26.11mm/1.028in	26.11mm/1.028in	20.2mm/0.795in	26.11mm/1.028in	20.2mm/0.795in
Width (mm/in, max)	101.85mm/4.01in	101.85mm/4.01in	101.85mm/4.01in	101.85mm/4.01in	101.85mm/4.01in
Depth (mm/in, max)	146.99mm/5.787in	146.99mm/5.787in	146.99mm/5.787in	146.99mm/5.787in	146.99mm/5.787in
Weight (g/lb, typical)	630g/1.389lb	610g/1.345lb	490g/1.08lb	610g/1.345lb	490g/1.08lb
Carton Unit Quantity	20	20	25	20	25
Cartons per Pallet/Cartons per Layer	40/8	40/8	40/8	40/8	40/8

⁴ Rescue services are not available in all countries. Contact your Seagate sales representative for more info.

⁵ It is not recommended to operate at sustained drive temperatures above 60°C. Higher temperatures may affect drive health.



Specifications	3TB	2TB	2TB	1TB	1TB
Capacity	3TB	2TB	2TB	1TB	1TB
Standard Model Number	ST3000VN007	ST2000VN003	ST2000VN004	ST1000VN002	ST1000VN008
Interface	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s
Features and Performance					
Drive Bays Supported	1-8 Bays	1-8 Bays	1-8 Bays	1-8 Bays	1-8 Bays
Recording Technology	CMR	CMR	CMR	CMR	CMR
Drive Design (Air or Helium)	Air	Air	Air	Air	Air
Workload Rate Limit (WRL)	180	180	180	180	180
Rotational Vibration (RV) Sensor	No	Yes	No	No	Yes
Dual-Plane Balance	Yes	Yes	Yes	Yes	Yes
Error Recovery Control	Yes	Yes	Yes	Yes	Yes
Max. Sustained Transfer Rate OD (MB/s)	180MB/s	180MB/s	180MB/s	180MB/s	180MB/s
Spindle Speed (RPM)	5,900	5,400	5,900	5,900	5,400
Cache (MB)	64	256	64	64	256
Reliability					
Load/Unload Cycles	600,000	600,000	600,000	—	600,000
Nonrecoverable Read Errors Rate, Max	1 per 10E14	1 per 10E14	1 per 10E14	1 per 10E14	1 per 10E14
Power-On Hours	8,760	8,760	8,760	8,760	8,760
Mean Time Between Failures (MTBF, hours)	1,000,000	1,000,000	1,000,000	1,000,000	1,000,000
Rescue Data Recovery Services (years) ⁴	3	3	3	3	3
Warranty, Limited (years)	3	3	3	3	3
Power Management					
Startup Current, Typical (12V, A)	1.8	1.8	1.8	1.8	1.8
Average Operating Power	4.8	3.1	3.1	3.1	3.1
Idle Power Average (W)	4.8W	2.8W	2.8W	2.8W	2.8W
Standby Mode/Sleep Mode, Typical (W)	0.5/0.5	0.25/0.25	0.25/0.25	0.25/0.25	0.25/0.25
Voltage Tolerance, Inc. Noise (5V / 12V)	±5% / ±10%	±5% / ±10%	±5% / ±10%	±5% / ±10%	±5% / ±10%
Environmental/Temperature					
Operating Temperature (ambient, min °C)	0	0	0	0	0
Operating Temperature (drive reported, max °C) ⁵	65	65	65	65	65
Nonoperating Temperature (ambient, min / max °C)	-40 / 70	-40 / 70	-40 / 70	-40 / 70	-40 / 70
Environmental/Shock					
Shock, Operating/Nonoperating: 2ms (max)	80Gs/300Gs	80Gs/300Gs	80Gs/300Gs	80Gs/300Gs	80Gs/300Gs
Environmental/Acoustics					
Acoustics, Idle (typical, measured in Idle 1 state) (dBA)	23	20	19	21	20
Acoustics, Seek (typical) (dBA)	25	21	21	23	21
Physical					
Height (mm/in)	26.11mm/1.028in	20.2mm/0.795in	26.11mm/1.028in	20.2mm/0.795in	20.2mm/0.795in
Width (mm/in, max)	101.85mm/4.01in	101.85mm/4.01in	101.85mm/4.01in	101.85mm/4.01in	101.85mm/4.01in
Depth (mm/in, max)	146.99mm/5.787in	146.99mm/5.787in	146.99mm/5.787in	146.99mm/5.787in	146.99mm/5.787in
Weight (g/lb, typical)	610g/1.345lb	415g/0.915lb	535g/1.18lb	415g/0.915lb	415g/0.915lb
Carton Unit Quantity	20	25	20	25	25
Cartons per Pallet/Cartons per Layer	40/8	40/8	40/8	40/8	40/8

⁴ Rescue services are not available in all countries. Contact your Seagate sales representative for more info.

⁵ It is not recommended to operate at sustained drive temperatures above 60°C. Higher temperatures may affect drive health.

seagate.com



© 2022 Seagate Technology LLC. All rights reserved. Seagate, Seagate Technology, and the Spiral Logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. AgileArray and IronWolf are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors. Seagate reserves the right to change, without notice, product offerings or specifications. DS1904.21-2207US