

2-WAY BOX SUPPORT



Cat#	2-Way Desc.	Wt. Ea.	Qty/Box
CSP-2W-WC (SS)	4-3/4" x 9-5/8" 18 Gauge Galvanized or Stainless Steel (SS)	0.5 lbs.	50
Cat#	2-Way 1/2 Desc.	Wt. Ea.	Qty/Box
CSP-1/2-WC (SS)	4-3/4" x 4-13/16" 18 Gauge Galvanized or Stainless Steel (SS)	0.25 lbs.	100

Plates also available as complete assemblies with any configuration of components (boxes, connectors, etc.)

**Meets
NEC 3 Foot Rule
From Only
One Support**

Load rating of conduit and box support plates is associated with load rating of box and mounting hardware

Eliminate center KO clamps for up thru 3/4" Conduit, Flex or equal size MC Cable entering all both sides of box at center KO location only.



Use 4-Conduit Block (IP19 or IP20) with QwikBlock (IP21A)

**For all types of raceways installed per NEC.
Accepts 4 or 4^{11/16} & 5" inch square shallow or deep boxes.
If shallow (1 1/2 inch deep) Maximum size = 3/4 inch conduit or equal size flexible conduit or MC Cable entering box.
Suitable for 1/4, 3/8 or 1/2 inch rod for support.**



**PATENT PENDING
PATENTED**



LABELS APPLY TO PRODUCTS ONLY WHERE SHOWN ABOVE

730 Pratt Boulevard • Elk Grove Village, IL 60007
P: (847) 593-8595 • F: (847) 593-8629 • Toll-free (800) 233-8595
E: info@spproducts.com • www.spproducts.com

IP6a