EXECUTIVE SUMMARY Page 1 of 6

| DOLLE | 10 | | Po | werE | dge | R6 | 50 | | TPCx-A | ricing | 2.8.0 |
|--|---------|------------------------|--------------------------------|-------------------|--|---------------------------------|---|-----------|-------------------|-----------|------------|
| TPCx-Al Perform | nance | Total System Cost | | Price/Performance | | | Report Date Nov. 30, 202 Availability Date | | | | |
| | ianoc | 1010 | ai Oyotoi | 11 0031 | 1 110 | | | / (| anabinty | y Date | |
| 2,375.83 AIUCpm@10 | 000 | \$7 | 758,223 | USD | USD/ | \$319.15 USD/AIUCpm@1000 | | | November 30, 2022 | | |
| Framework | (| Оре | Operating System | | O | Other Software | | | Scale Factor | | Streams |
| Cloudera CDP P Cloud Base v7 | | Red | Hat Ent Linux 8 | • | | N | /A | | 1,000 | | 12 |
| Use Case Tin | ne (sec | .) by P | hase | | ■ Training | ■ Se | rving 1 | ■ Servir | ng 2 🔳 | Γhroughpι | ıt (Avg) |
| 10 | | | | | | | | | | | |
| 9 | | _ | | | | | | | | | |
| | | | | | | | | | | • | |
| 8 | | | | | | | | | | | |
| 7 | | | | | | | | | | | |
| 6 | | | | | | | | | | | |
| 5 | | | | | | | | | | | |
| | | | | | | | | | | | |
| 4 | | | | | | | | | | | |
| 3 | | | | | | | | | | | |
| 2 | | | | | | | | | | | |
| 1 | | | | | | | | | | | |
| 0 2,000 | 4,00 | 0 6,0 | 000 8 | ,000 10 | ,000 12 | ,000 | 14,000 | 0 16,0 | 000 18 | 3,000 | 20,000 |
| Physical Storage / Scale Factor | | | Scale Factor / Physical Memory | | | ry Main Data Redundancy Model | | | | | |
| 153.92 | | 0.19 | | | | Replication 3 & RAID | | | | | |
| Servers: Total Processors/Cores/Threads | | 11 22 / 616 / 1,232 | | | | | | | | | |
| Server Type 1x PowerEdge R650 | | - | | | - | | | | | | |
| | | | | | | Xeon(R) Gold 6348 CPU @ 2.60GHz | | | | | |
| • | 56 GiB | 1755 D A I | D Contro | llor | 512 GiB | | | | | | |
| Storage Controller 1 Storage Device 2 | | | | iler 3 SAS SSD | | None 2x 480 | GR RC |)SS: 4x 3 | 3 2 TR F | nt P5600 | MII NI\/Ma |
| - | | | | | SD 2x 480 GB BOSS; 4x 3.2 TB Ent P5600 MU NOCP NIC 1x Intel Ethernet 25G 2-port E810-XXV OCP | | | | | | |
| Connectivity 1x Dell PowerSwitch | | | | | | | | , | | | |

EXECUTIVE SUMMARY Page 2 of 6



TPCx-AI 1.0.2 TPC Pricing 2.8.0

| DYLLLIVIO | | | | Report Date | Nov. 30, 2022 |
|---|---------------------|--------|-------------|------------------|----------------------|
| Description | Part Number | Source | List Price | Qty Extended Pri | ce 1-Yr. Maintenance |
| Hardware | | | | | |
| PowerEdge R650 Server | 210-AYJZ | 1 | \$87,099.92 | 10 \$870,999. | 20 |
| 10x2.5 Front Storage | 379-BEID | 1 | \$0.00 | 10 | |
| NVMe Backplane | 379-BDSX | 1 | \$0.00 | 10 | |
| 2x2.5 Rear Storage | 379-BDTD | 1 | \$0.00 | 10 | |
| Trusted Platform Module 2.0 V3 | 461-AAIG | 1 | \$0.00 | 10 | |
| 2.5" Chassis with up to 10 NVMe Drives, 2x2.5" Rear NVMe Dr | i\321-BGHK | 1 | \$0.00 | 10 | |
| Intel® Xeon® Gold 6348 2.6G, 28C/56T, 11.2GT/s, 42M Cache, 7 | Γu 338-CBCI | 1 | \$0.00 | 10 | |
| Intel® Xeon® Gold 6348 2.6G, 28C/56T, 11.2GT/s, 42M Cache, 7 | Γυ 338-CBCI | 1 | \$0.00 | 10 | |
| Heatsink for 2 CPU configuration (CPU more than 165W) | 412-AAVM | 1 | \$0.00 | 10 | |
| Performance Optimized | 370-AAIP | 1 | \$0.00 | 10 | |
| App DirectMode Intel Optane Persistent Memory 200 series | 370-AGJF | 1 | \$0.00 | 10 | |
| 32GB RDIMM, 3200MT/s, Dual Rank, 16Gb BASE x8 | 370-AGDS | 1 | \$0.00 | 160 | |
| 128GB Optane Persistent Memory 200 Series, 3200MT/s | 370-AGEX | 1 | \$0.00 | 20 | |
| C30, No RAID for NVME chassis | 780-BCDO | 1 | \$0.00 | 10 | |
| No Controller | 405-AACD | 1 | \$0.00 | 10 | |
| No Hard Drive | 400-ABHL | 1 | \$0.00 | 10 | |
| 3.2TB, Enterprise, NVMe, Mixed Use, U2, G4, P5600 with carri | eı400-BLKF | 1 | \$0.00 | 20 | |
| 3.2TB, Enterprise, NVMe, Mixed Use, U2, G4, P5600 Flex Bay | 400-BLKI | 1 | \$0.00 | 20 | |
| Power Saving Dell Active Power Controller | 750-AABF | 1 | \$0.00 | 10 | |
| UEFI BIOS Boot Mode with GPT Partition | 800-BBDM | 1 | \$0.00 | 10 | |
| 4 Very High Performance Fans for 2 CPU | 384-BCUJ | 1 | \$0.00 | 10 | |
| Dual, Hot-plug, Power Supply Fault Tolerant Redundant (1+1) | , 450-AIQX | 1 | \$0.00 | 10 | |
| C13 to C14, PDU Style, 12 AMP, 6.5 Feet (2m) Power Cord, No | | 1 | \$0.00 | 20 | |
| Riser Config 6, Half Length, Low Profile, 1 x16 Slot With R1 Pa | | 1 | \$0.00 | 10 | |
| PowerEdge R650 Motherboard, Barlow Pass Enabled, with Broa 329-BGKP | | 1 | \$0.00 | 10 | |
| iDRAC9 Datacenter 15G with OpenManage Enterprise Advance | | 1 | \$0.00 | 10 | |
| Intel E810-XXV Dual Port 10/25GbE SFP28, OCP NIC 3.0 | 540-BCXW | 1 | \$0.00 | 10 | |
| Standard Bezel for x8 and x10 Chassis | 325-BCHH | 1 | \$0.00 | 10 | |
| BOSS-S2 controller card + with 2 M.2 480GB (RAID 1) | 403-BCMB | 1 | \$0.00 | 10 | |
| No Quick Sync | 350-BBXM | 1 | \$0.00 | 10 | |
| iDRAC, Factory Generated Password | 379-BCSF | 1 | \$0.00 | 10 | |
| iDRAC Group Manager, Disabled | 379-BCQY | 1 | \$0.00 | 10 | |
| No Operating System, No Utility Partition, BOSS | 611-BBBX | 1 | \$0.00 | 10 | |
| No Media Required | 605-BBFN | 1 | \$0.00 | 10 | |
| ReadyRails Sliding Rails With Cable Management Arm | 770-BDMT | 1 | \$0.00 | 10 | |
| No Systems Documentation, No OpenManage DVD Kit | 631-AACK | 1 | \$0.00 | 10 | |
| PowerEdge R650 Shipping | 340-CUQR | 1 | \$0.00 | 10 | |
| R650 Ship 4x3.5, 10x2.5, 8x2.5 NVMe | 340-CUQN | 1 | \$0.00 | 10 | |
| PowerEdge R650 CE CCC Marking, No BIS Marking | 389-DYHZ | 1 | \$0.00 | 10 | |
| US No Canada Ship Charge | 332-1286 | 1 | \$0.00 | 10 | |
| No FGA | 817-BBBB | 1 | \$0.00 | 10 | |
| Basic Next Business Day 36 Months, 36 Month(s) | 709-BBFM | 1 | \$200.00 | 10 | \$2,000.00 |
| Prosupport Plus and 4Hr Mission Critical, 36 Month(s) | 865-BBNF | 1 | \$6,285.59 | 10 | \$62,855.90 |
| No Installation | 900-9997 | 1 | \$0.00 | 10 | 402,033.30 |
| Red Hat Enterprise Linux, Non Factory Install, Requires Licens | | 1 | \$0.00 | 10 | |
| RHEL, 1-2SKT, Physical Node, 1YR Premium Sub,up to 4 Virtua | | 1 | \$0.00 | 10 | |
| , | (continued on the n | | , | • | |

EXECUTIVE SUMMARY Page 3 of 6



PowerEdge R650

TPCx-AI 1.0.2
TPC Pricing 2.8.0

Report Date Nov. 30, 2022

(continued from the previous page)

| Description | Part Number | Source | List Price Qty | Ext | tended Price 1-Yr. Maintenance |
|--|----------------|--------|----------------|-----|--------------------------------|
| PowerEdge R650 Server | 210-AYJZ | 1 | \$66,799.76 | 1 | \$66,799.76 |
| 8x2.5 Front Storage | 379-BEIC | 1 | \$0.00 | 1 | |
| SAS/SATA Backplane | 379-BDSS | 1 | \$0.00 | 1 | |
| No Rear Storage | 379-BDTE | 1 | \$0.00 | 1 | |
| Trusted Platform Module 2.0 V3 | 461-AAIG | 1 | \$0.00 | 1 | |
| 2.5" Chassis with up to 8 Hard Drives (SAS/SATA), 3 PCIe Slo | ots, 321-BGHH | 1 | \$0.00 | 1 | |
| Intel® Xeon® Gold 6348 2.6G, 28C/56T, 11.2GT/s, 42M Cache | e, Tu 338-CBCI | 1 | \$0.00 | 1 | |
| Intel® Xeon® Gold 6348 2.6G, 28C/56T, 11.2GT/s, 42M Cache | e, Tu 338-CBCI | 1 | \$0.00 | 1 | |
| Heatsink for 2 CPU configuration (CPU more than 165W) | 412-AAVM | 1 | \$0.00 | 1 | |
| Performance Optimized | 370-AAIP | 1 | \$0.00 | 1 | |
| 3200MT/s RDIMMs | 370-AEVR | 1 | \$0.00 | 1 | |
| 16GB RDIMM, 3200MT/s, Dual Rank | 370-AEVQ | 1 | \$0.00 | 16 | |
| C7, Unconfigured RAID for HDDs or SSDs (Mixed Drive Type | s Al 780-BCDS | 1 | \$0.00 | 1 | |
| Front PERC H755 Front Load | 405-AAZB | 1 | \$0.00 | 1 | |
| 3.84TB SSD SAS Read Intensive 12Gbps 512 2.5in Hot-plug A | AG D 400-AXPE | 1 | \$0.00 | 4 | |
| Power Saving Dell Active Power Controller | 750-AABF | 1 | \$0.00 | 1 | |
| UEFI BIOS Boot Mode with GPT Partition | 800-BBDM | 1 | \$0.00 | 1 | |
| 4 Very High Performance Fans for 2 CPU | 384-BCUJ | 1 | \$0.00 | 1 | |
| Dual, Hot-plug, Power Supply Fault Tolerant Redundant (1- | +1), 450-AIQX | 1 | \$0.00 | 1 | |
| C13 to C14, PDU Style, 12 AMP, 6.5 Feet (2m) Power Cord, N | Nort 492-BBDI | 1 | \$0.00 | 2 | |
| Riser Config 0, 2CPU, Half Length, Low Profile, 3 x16 Slots, 5 | | 1 | \$0.00 | 1 | |
| PowerEdge R650 Motherboard with Broadcom 5720 Dual Po | ort 1329-BFGW | 1 | \$0.00 | 1 | |
| iDRAC9 Datacenter 15G with OpenManage Enterprise Adva | nce 528-CRVW | 1 | \$0.00 | 1 | |
| Intel E810-XXV Dual Port 10/25GbE SFP28, OCP NIC 3.0 | 540-BCXW | 1 | \$0.00 | 1 | |
| Standard Bezel for x8 and x10 Chassis | 325-BCHH | 1 | \$0.00 | 1 | |
| BOSS-S2 controller card + with 2 M.2 480GB (RAID 1) | 403-BCMB | 1 | \$0.00 | 1 | |
| No Quick Sync | 350-BBXM | 1 | \$0.00 | 1 | |
| iDRAC, Factory Generated Password | 379-BCSF | 1 | \$0.00 | 1 | |
| iDRAC Group Manager, Disabled | 379-BCQY | 1 | \$0.00 | 1 | |
| No Media Required | 605-BBFN | 1 | \$0.00 | 1 | |
| ReadyRails Sliding Rails With Cable Management Arm | 770-BDMT | 1 | \$0.00 | 1 | |
| No Systems Documentation, No OpenManage DVD Kit | 631-AACK | 1 | \$0.00 | 1 | |
| PowerEdge R650 Shipping | 340-CUQR | 1 | \$0.00 | 1 | |
| R650 Ship 8x2.5 | 340-CUQO | 1 | \$0.00 | 1 | |
| PowerEdge R650 CE CCC Marking, No BIS Marking | 389-DYHZ | 1 | \$0.00 | 1 | |
| US No Canada Ship Charge | 332-1286 | 1 | \$0.00 | 1 | |
| No FGA | 817-BBBB | 1 | \$0.00 | 1 | |
| Basic Next Business Day 36 Months, 36 Month(s) | 709-BBFM | 1 | \$200.00 | 1 | \$200.00 |
| No Installation | 900-9997 | 1 | \$0.00 | 1 | , |
| Prosupport Plus and 4Hr Mission Critical, 36 Month(s) | 865-BBMY | 1 | \$4,823.98 | 1 | \$4,823.98 |
| Red Hat Enterprise Linux, Non Factory Install, Requires Lice | | 1 | \$0.00 | 1 | , ,,===== |
| RHEL, 1-2SKT, Physical Node, 1YR Premium Sub,up to 4 Virt | | 1 | \$0.00 | 1 | |

EXECUTIVE SUMMARY Page 4 of 6



PowerEdge R650

TPCx-AI 1.0.2
TPC Pricing 2.8.0

Nov. 30, 2022

Report Date

(continued from the previous page)

| Description | Part Number | Source | List Price | 9 | Qty | Е | xtended Price | 1-Yr. Mai | ntenance |
|--|------------------|--------|------------|------|---------|----|----------------|-----------|------------|
| Dell Networking PowerSwitch S5212-ON | 210-APHW | 1 | \$20,548 | 8.00 | | 1 | \$20,548.00 | | |
| S52XX User Manual | 343-BBLP | 1 | \$0 | 0.00 | | 1 | | | |
| OS10 Enterprise,S5212F-ON | 634-BRXD | 1 | \$0 | 0.00 | | 1 | | | |
| Dell Networking, Cable, SFP28 to SFP28, 25GbE, Passive Coppe | 470-ACET | 1 | \$0 | 0.00 | : | 11 | | | |
| Power Cord, 125V, 15A, 10 Feet, NEMA 5-15/C13, Qty 2 | 450-AAFH | 1 | \$0 | 0.00 | | 1 | | | |
| Dell NW Dual Tray, 4-post, S5212F-ON | 770-BDGQ | 1 | \$0 | 0.00 | | 1 | | | |
| No Installation | 900-9997 | 1 | \$0 | 0.00 | | 1 | | | |
| 3 Years ProSupport Plus Mission Critical 4Hr Onsite Service | 818-3530 | 1 | \$2,930 | 0.98 | | 1 | | | \$2,930.98 |
| 3 Years ProSupport Plus OS10 Enterprise Software Support-Ma | 848-8574 | 1 | \$568 | 8.52 | | 1 | | | \$568.52 |
| Infrastructure | | | | | | | | | |
| Dell 24 Monitor | 210-AIWG | 1 | \$169 | 9.99 | | 1 | \$169.99 | | |
| Optical Mouse - MS116 Black (incld. w/ server) | 570-AAKV | 1 | \$0 | 0.00 | : | 11 | | | |
| Dell KB216 Wired Keyboard English (incld. w/ server) | 580-ADJC | 1 | \$0 | 0.00 | : | 11 | | | |
| DELL EMC NETSHELTER SX 24U RACK - 600MM | A7522217 | 1 | \$0 | 0.00 | | 1 | | | |
| | | | | | Subtota | l | \$958,516.95 | : | 373,379.38 |
| Software | | | | | | | | | |
| Cloudera CDP Private Cloud Base v7.1.7, 24x7 1yr | CDP-PVC-BASE-BUS | 1 | \$134,600 | 0.00 | | 1 | \$134,600.00 | | |
| | | | | | Subtota | ı | \$134,600.00 | | \$0.00 |
| | | | | | Total | | \$1,093,116.95 | : | 573,379.38 |
| Large Purchase Discount (35%)* | | | | | | | -\$382,590.93 | _ | 25,682.78 |

| Pricing: 1 = Dell | Total System Cost (USD): | \$758,223 |
|---|--------------------------|-----------|
| * Discount applies to all line items where Key = 1. Discount based upon total system cost as purchased by a regular customer. | AIUCpm@1000: | 2,375.83 |
| Audited by Doug Johnson, InfoSizing | \$/AIUCpm@1000: | \$319.15 |

Prices used in TPC benchmarks reflect the actual prices a customer would pay for a one-time purchase of the stated Line Items. Individually negotiated discounts are not permitted. Special prices based on assumptions about past or future purchases are not permitted. All discounts reflect standard pricing policies for the listed Line Items. For complete details, see the pricing section of the TPC Benchmark Standard. If you find that the stated prices are not available according to these terms, please inform the TPC at pricing @tpc.org. Thank you.

EXECUTIVE SUMMARY Page 5 of 6



PowerEdge R650

TPCx-AI 1.0.2
TPC Pricing 2.8.0
Report Date Nov. 30, 2022

Numerical Quantities

| AIUCpm@1000 | 2,375.83 | T_Load | 1,051.29 |
|------------------|----------|------------|----------|
| Scale Factor | 1,000 | T_LD | 1,051.29 |
| Streams | 12 | T_{PTT} | 539.33 |
| | | T_{PST1} | 132.23 |
| Kit Version | 1.0.2 | T_{PST2} | 125.34 |
| Execution Status | Pass | T_{PST} | 132.23 |
| Accuracy Status | Pass | T_TT | 54.26 |

Test Times

| 162 | l HIHES |
|--|--|
| Overall Run Start Time Overall Run End Time Overall Run Elapsed Time | 2022-11-13 20:48:57.882 2022-11-14 06:47:52.912 35,935.030 |
| Load Test Start Time | 2022-11-13 21:49:52.611 |
| Load Test End Time | 2022-11-13 22:07:26.619 |
| Load Test Elapsed Time | 1,054.008 |
| Power Training Start Time | 2022-11-13 22:07:26.622 |
| Power Training End Time | 2022-11-14 01:38:09.123 |
| Power Training Elapsed Time | 12,642.501 |
| Power Serving 1 Start Time Power Serving 1 End Time Power Serving 1 Elapsed Time | 2022-11-14 01:38:09.126 2022-11-14 03:14:33.394 5,784.268 |
| Power Serving 2 Start Time | 2022-11-14 03:14:33.397 |
| Power Serving 2 End Time | 2022-11-14 04:48:31.998 |
| Power Serving 2 Elapsed Time | 5,638.601 |
| Scoring Start Time | 2022-11-14 04:53:08.070 |
| Scoring End Time | 2022-11-14 04:59:06.741 |
| Scoring Elapsed Time | 358.671 |
| Throughput Start Time Throughput End Time Throughput Elapsed Time | 2022-11-14 04:59:06.748 2022-11-14 06:47:52.911 6,526.163 |

EXECUTIVE SUMMARY Page 6 of 6



PowerEdge R650

Numerical Quantities (continued)

TPCx-AI 1.0.2
TPC Pricing 2.8.0
Report Date Nov. 30, 2022

Use Case Times & Accuracy Use Case Training (sec) Serving 1 (sec) Serving 2 (sec) Throughput (avg) Accuracy UC01 760.126 330.202 183.356 162.179 0.000 UC02 1,767.185 233.195 236.392 349.423 0.447 UC03 163.555 4.566 16.290 17.075 20.986 UC04 85.620 35.504 34.891 43.331 0.712 UC05 781.675 291.996 286.369 401.790 0.045 44.247 0.214 UC06 534.701 42.902 52.262



