


AXIS A4010-E Reader

Generic touch-free reader

AXIS A4010-E Reader without Keypad is a joint cooperation between Axis and ASSA Abloy designed to perfectly match AXIS A1001 Network Door Controller. The cost-efficient reader has no keypad and its small form factor enables easy placement. Two LED symbols give clearly visible feedback. The reader supports touch-free entry with most entry card formats, and is suitable for both indoor and outdoor installation. IP65 classification makes it ready for harsh environments.

- > **Designed to perfectly match AXIS A1001**
- > **Support for most smart card formats**
- > **2 LED symbols give clearly visible feedback**
- > **Indoor and outdoor ready**
- > **IP65 classified**



AXIS A4010-E Reader

Compatible products AXIS A1001 Network Door Controller

Indications and user interface

Entry authentication Card, Tag

Read range 30–40 mm with recommended cards and tags

Alarm status indication Symbols for: Access granted, Access denied

General

Casing ABS and halogen free halon plastic

Reader technology Generic 13,56 MHz (MIFARE Classic, MIFARE Plus (Level 1 and 3), MIFARE DESFire EV1 and iCLASS^a)

Communication RS-485 – OSDP

Power 12–24V DC
max 2.8 W
Translates to 240 mA@12V

Operating conditions -30 °C to 70 °C (-34 °F to 158 °F)

Storage conditions -50 °C to 70 °C (-58 °F to 158 °F)

Approvals EN/IEC 61000-6-2, EN/IEC 61000-6-3, EN 55024, EN 50130-4, CFR part 15 Subpart C, AS/NZS 4268, RSS-GEN, RSS-210, EN 50581, EN/IEC 60950-22, ETSI EN 300 330-1, ETSI EN 300 330-2, UL294

Dimensions 85 x 46 x 19 mm (3.35 x 1.8 x 0.75 in)
Cable length: 3 m

Weight 128 g (0.28 lb)

Warranty Axis 3-year warranty, see www.axis.com/warranty

a. Extra configuration card needed, sold separately.

Environmental responsibility:

www.axis.com/environmental-responsibility

