

AXIS T8351 Mk II Microphone 3.5 mm

High-performance, low noise analog microphone for superior audio

AXIS T8351 Mk II Microphone 3.5 mm is a high-performance, discreet microphone specially designed for best results in rooms with low ambient noise-levels. This hemispherical microphone collects sound from every direction, and the quality of the recording is superior to that of the network product's internal microphone. AXIS T8351 Mk II is compatible with any network products that supports a 3.5 mm microphone input jack, or a 4-pin audio connector. The microphone is powered by the network product and does not require an external supply. This microphone is ideal for locations where superior audio is required.

- > **Outstanding audio with low noise-level**
- > **Discreet and compact analog microphone**
- > **Hemispherical**
- > **Flexible installation**



AXIS T8351 Mk II Microphone 3.5 mm

Audio	
Supported devices	Network products with support for microphone input
Frequency range	Within 20 Hz - 20 kHz (see graph) ^a
Sensitivity	-22 dB \pm 3 dB ^a
Max SPL	126 dB (10% THD) ^a
SNR	82 dB A-weighted (relative 1 kHz @ 1 Pa, 94 dB SPL) ^a
Directionality	Hemispherical
General	
Casing	IP65-rated Plastic casing Color: NCS S 1002-B
Sustainability	PVC free
Power	2-10 V DC ^b Maximum consumption: 0.006 W
Connectors	3.5 mm stereo plug or terminal block with optional extender
Operating conditions	-20 °C to 60 °C (-4 °F to 140 °F) Humidity 0-75% RH (non-condensing)
Storage conditions	-40 °C to 70 °C (-40 °F to 158 °F)
Approvals	EMC EN 55103-2
	Safety IEC/EN/UL 60950-1, CE
	Environment IEC/EN 60529 IP65, EN 50581
Dimensions	Microphone (LxHxW): 27 x 20 x 20 mm (1.06 x 0.79 x 0.79 in) Cable (LxØ): 5 m x 3.1 mm (197 x 0.12 in) 3.5 mm plug (Ø): 6.2 mm (0.24 in)
Weight	90 g (0.20 lb)
Included accessories	Installation guide, drill template, white cover, mount bracket, doublesided tape 20x10 mm, cable holders, cable gasket M20 3 mm, cable gasket M16 3 mm
Optional accessories	AXIS Audio Extension Cable B, 5m Terminal Block to 3.5 mm Audio Extender For more accessories, see axis.com
Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
Warranty	Axis 3-year warranty and AXIS Extended Warranty option, see axis.com/warranty

a. The audio specifications were produced with the microphone mounted as specified
b. Power is provided by the Axis network product

Environmental responsibility:

www.axis.com/environmental-responsibility

