

## AXIS W700 Docking Station 1-bay

AXIS W700 Docking Station 1-bay enables easy handling of the body worn camera with fast charging, quick, secure and easy data offloading.

- > **Grab and go, ready when you are**
- > **Dock and go, for automatic reliable offloading and fast charging**
- > **Reliable docking connectors**
- > **Splash proof**



## AXIS W700 Docking Station 1-bay

Network		Approvals
<b>Supported protocols</b>	IPv4, IPv6 USGv6, HTTPS, Bonjour, DNS, NTP, TCP, UDP, ICMP, DHCP, ARP	<b>EMC</b> EN 55032 Class B, EN 55035, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class B, ICES-3(B)/NMB-3(B), RCM AS/NZS CISPR 32 Class B
<b>Throughput</b>	100 Mbit/s	<b>Safety</b> IEC/EN/UL 62368-1
General		<b>Environment</b> IEC 60068-2-1, IEC 60068-2-14, IEC 60068-2-2, IEC 60068-2-78
<b>Capacity</b>	1 bay	<b>Network</b> Compatible with NIST SP500-267 throughput
<b>Casing</b>	Plastic casing Color: black NCS S 9000-N	<b>Dimensions</b>
<b>Sustainability</b>	PVC free	Height: 47 mm (1.9 in) Width: 76 mm (3.0 in) Depth: 95 mm (3.8 in)
<b>Power</b>	4.8–5.2 V DC, max 9 W	<b>Weight</b>
<b>Connectors</b>	Shielded RJ45 10BASE-T/100BASE-TX DC input Pogo pin pads	130 g (0.29 lb)
<b>Operating conditions</b>	0 °C to 40 °C (32 °F to 104 °F) Humidity 10–85% RH (non-condensing)	<b>Warranty</b>
<b>Storage conditions</b>	–40 °C to 65 °C (–40 °F to 149 °F) Humidity 10–85% RH (non-condensing)	Axis 3-year warranty, see <a href="https://axis.com/warranty">axis.com/warranty</a>

Environmental responsibility:

[axis.com/environmental-responsibility](https://axis.com/environmental-responsibility)