

AXIS Outdoor Midspan 30 W 1-port

For outdoor installations

Power over Ethernet (PoE) offers an easy, fast and cost-effective solution for powering network products. A midspan injects power and data to the network device with built-in PoE support. No need to replace existing Ethernet switches and cabling infrastructure. AXIS Outdoor Midspan 30 W 1-port is compatible with IEEE 802.3af and 802.3at compliant Axis network devices. The midspan ensures safe and reliable operation in outdoor environments. Furthermore, it offers surge protection for both the AC and the PoE ports ensuring protection to the equipment from outdoor surges up to 6kV.

- > **Outdoor-ready, IP66/67- and NEMA 4X-rated**
- > **IEEE 802.3af and 802.3at**
- > **100 to 240 V AC**
- > **Railway compliant EN 50121-4 and IEC 62236-4**



AXIS Outdoor Midspan 30 W 1-port

Midspans		General	
Function	Data and power are fed to a network video product through an Ethernet cable	Casing	Aluminium IP66/67- and NEMA 4X-rated
Data rate	10/100/1000 Mbps	Sustainability	PVC free
Installation and management	Automatically detects PoE and PoE+ devices and supplies inline power	Mounting	Wall or pole ^a
Data & power		Operating conditions	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 10–100% RH (condensing)
Power	Power over Ethernet IEEE 802.3af Type 1 Class 3 IEEE 802.3at Type 2 Class 4	Storage conditions	-40 °C to 85 °C (-40 °F to 185 °F) Humidity max 95% RH (non-condensing)
Input	AC input voltage: 100 to 240 V AC AC frequency: 50–60 Hz	Approvals	Safety IEC/EN/UL 60950-1, IEC/EN/UL 60950-22, GS Mark per EN 60950-1, CCC EMC EN 55024, EN 55035, EN 55032 Class B, EN 50121-4, IEC 62236-4, EN 61000 3-2, EN 61000 3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Class B, VCCI Class B, RCM AS/NZS CISPR32 Class B, ICES-003 Class B Designed to meet GR-1089-CORE Issue 4 ITU-T K.21 enhanced surge level protection (6 kV on data and AC lines) Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-64, IEC/EN 60529 IP66/67, EN 61373, IEC TR 60721-4-5 Class 5M3, NEMA 250 Type 4X
Output	54 V DC (max 30 W)	Dimensions	170 x 140 x 60 mm (6.69 x 5.51 x 2.36 in)
Power consumption	No remote device connected: 2 W 30 W remote device connected: 36 W	Weight	1.4 kg (3.1 lb)
Connectors	Shielded RJ45, EIA 568A and 568B 3-pin AC power connector (IP68-rated)	Included accessories	Installation guide
Wiring	Data provided over pairs 1/2 and 3/6 for 10/100 Ethernet, over all four pairs for Gigabit Ethernet Power over pairs 4/5 (+) and 7/8 (-)	Optional accessories	AXIS TD9301 Outdoor Midspan Pole mount For more accessories, see axis.com
		Warranty	3-year warranty, see axis.com/warranty

a. Sold as optional accessory

Environmental responsibility:

axis.com/environmental-responsibility