



VALVTECT® X-TENDED PROTECTION+™ GASOLINE TREATMENT All-In-One Formula (GAAI08)

ValvTect® X-Tended Protection+™ All-In-One Gasoline Treatment is specially formulated to prevent ethanol fuel related problems by quickly cleaning up fuel system deposits, controlling moisture to prevent phase separation, stabilizing fuel for longer shelf life, and maintaining octane rating. It contains ValvTect's CorrosionGuard™ Technology to prevent rust & corrosion in gasoline fuel systems.

ValvTect® X-Tended Protection+™ All-In-One Gasoline Treatment helps gasoline powered engines operate at "Beyond Top Tier" performance. A sophisticated detergent package cleans up deposits (gum & varnish) and keeps the engine & fuel system "super clean" & in "like new" condition. Continued use can maximize power, fuel economy, lower maintenance costs and reduce harmful exhaust emissions. Powerful anti-oxidants stabilize and extend the shelf life of both ethanol blended gasolines (up to E85) & recreational (non-ethanol) gasoline for up to 2+ years providing outstanding protection during long term storage. Dispersants help prevent phase separation and accumulation of contaminants. ValvTect's CorrosionGuard™ Technology effectively prevents rust & corrosion in gasoline fuel systems with a combination of corrosion protection additives. The result is outstanding performance and maximum protection of your fuel and fuel system.

Product performance has been documented by ASTM, SAE & NACE corrosion tests with both ethanol & ethanol free grades of gasoline. Tested extensively in BMW, Honda, GM, Ford, Mercedes Benz, VW & Yamaha engines. ValvTect's X-tended Protection+™ All-In-One Gasoline Treatment is an effective and economical option to prevent fuel related problems.

FEATURES AND BENEFITS


- Prevents ethanol and non-ethanol gasoline related problems.
- Cleans up fuel injectors, carburetors, intake valves, intake port and manifold deposits.
- Improves Engine Power & Performance*.
- Reduces fuel consumption*.
- Prevents fuel filter plugging and extends fuel filter life.
- Powerful anti-oxidants stabilize fuel for long term storage and extend the shelf life for up to 2+ years.
- Protects the thermal stability and prevents oxidation to keep fuel fresh during long term storage.
- Helps stop the formation of harmful gum and varnish residues in gasoline stored for long periods of time.
- Helps assure quick starts after long periods of storage.
- Safely controls moisture and helps prevent phase separation with ethanol blended gasoline.
- Contains CorrosionGuard™ technology to prevent rust & corrosion of fuel system. (A rated in NACE tests)
- Helps prevent octane number loss.
- Documented to meet ASTM, SAE, and NACE corrosion test specifications.
- Tested extensively in all types of gasoline engines and under the most severe storage conditions.
- Suitable for all types of gasoline including recreational grade (non-ethanol), ethanol blends up to E85, and other alternative gasoline types. Safe for all 2 cycle & 4 cycle gasoline engines.
- 8 ounces treats up to 40 gallons, 1 ounce treats 5 gallons.

* Based on clean-up of fuel system deposits.

© 2021 ValvTect Petroleum Products, 2220 Highway 70 SE, Suite 100, Hickory, NC 28602 USA • Phone: (800) 728-8258 • WWW.ValvTect.com

ValvTect® X-Tended Protection+™ & CorrosionGuard™ are registered trademark of ValvTect Petroleum Products.

GAAI08PDS1021-1



PRODUCT DATA SHEET

VALVTECT® X-TENDED PROTECTION+™ GASOLINE TREATMENT All-In-One Formula (GAAI08)

APPLICATIONS

This high performance gasoline additive is a very effective multifunctional treatment that can be used to maximize the performance and shelf life of gasoline. It can be easily blended into all types of gasoline and is specially formulated for use in all types of 2 & 4 cycle gasoline engines and applications. This includes passenger, heavy-duty, high performance, marine, agriculture, motorcycle, lawn equipment, stand-by generators & other gasoline engines. This product does not replace the need for 2-cycle oil. This premium product may be used in all automotive & other gasoline engines where improved performance, corrosion protection and longer shelf life of fuel is desired.

BLENDING RECOMMENDATIONS

Product should be added to the fuel storage tank prior to adding fuel. Storage tank should have a 20% heel of gasoline & be free of excess water and/or sludge.

	<u>Treat Rate</u>	
1oz : 5 gallons		8oz : 40 gallons

SAFETY PRECAUTIONS

When handling this product, persons should exercise caution and wear protective goggles, gloves and clothing. See cautions indicated in the corresponding Safety Data Sheet before handling and storing this product.

WARRANTY

We guarantee this product to comply with our published specifications. Since the use of this product is beyond our control, we disclaim responsibility for its performance, handling, use, storage, the results obtained, or any injury of any nature resulting there from. Product warrantee and seller's obligations apply only to replacement of product. Seller assumes no liability for any claim or loss of any other kind. In no event shall seller be liable for indirect punitive, special or consequential damages or expenses. Any warrantee claim shall be governed by and construed in accordance with the laws and jurisdiction of the State of North Carolina.

TYPICAL SPECIFICATIONS

Color (ASTM D1544)	5
Specific Gravity @ 60° F	0.8750
Density, lbs./gal. (approx.)	7.29
Flash Point °F, PMCC	105
Additive Pour Point °F	<-50
Viscosity @ 77° F cSt	N/A



Warning: Cancer –
www.p65warnings.ca.gov



PACKAGING

Available in 12/08 oz bottles per case.