



CONVERSION DUMP HOISTS VC620



CAPACITY RANGE
9 - 27 TON

BODY LENGTHS
12 - 16 FT

CONV. CLASS
E

DUMP CLASS
50

TRUCK FRAME
29-1/2" - 34"

FEATURES

■ VARIETY OF POWER OPTIONS

The VC620 can be fit with our ES (Electric-Single), ED (Electric-Double), DM (Direct-Mount PTO Driven) or LDK (Less Drive Kit - No power or hoses).

■ OPTIONAL SUBFRAME FOR EASY INSTALL

New and improved subframe designed to fit contemporary chassis cabs without modifications to save time and money.

■ UPDATED DESIGN

Low-mounting height scissors design with narrow drop-hinge knuckle.

RELIABILITY & QUALITY

Since 1981, Venco's underbody hoists are highly regarded in the industry and represent an excellent value. Venco offers a full line of underbody hoists designed for use with bodies ranging in lengths from 12" to 16" long, providing dumping capacities of 9 to 27 tons. Venco hoists are encapsulated in a durable abrasive and chemical resistant powder coating. When you purchase an underbody hoist from Venco, all necessary mounting hardware, fasteners, and body prop hardware are included. Venco hoists are covered under a 3 year product warranty.

SPECIFICATIONS

Lifting Capacities:	9 - 27 TONS
Body Length:	12 - 16 FT
Cylinder:	6"
Stroke:	20"
Conversion Class:	E
Dump Class:	50
Mounting Height:	8"
Operation Pressure:	3000/1000 PSI
Subframe Mounting Height:	<i>(If applicable)</i> 9-1/2"
Rail:	4"
ES/ED Power Supply:	Electric 12V DC
DM Power Supply:	PTO
Hydraulic Req:	ES - 8 qt. reservoir ED - 4 qt. reservoir PTO - 21 qt. reservoir
Weight:	
VC416:	625 LBS
VC416 w/ SF:	745 LBS
PTO Pump:	SAE "A" 2-bolt flange, 5/8" - 9 Spline (CCW Rot.) w/ 9 qt. reservoir

ES/ED KITS

(ES) ELECTRIC-SINGLE ACTING PUMP

- Power-Up, Gravity Down
- 8 qt. Reservoir
- 12V DC Electric/Hydraulic Power Unit
- Includes Hoses, Controls, Hydraulic Fittings, Pump & Tank Combo

(ED) ELECTRIC-DOUBLE ACTING PUMP

- Power-Up, Power-Down
- 4 qt. Reservoir
- 12V DC Electric/Hydraulic Power Unit
- Includes Hoses, Controls, Hydraulic Fittings, Pump & Tank Combo

MAXIMUM LOAD CAPACITY CHART

CONVERSION APPLICATIONS VC620					
BODY	CA	OH	40° (TON)	45° (TON)	50°(TON)
13'	84"	42"	24.0	21.4	19.4
13'	102"	24"	16.0	14.3	12.9
13'	108"	18"	14.4	12.9	11.6
13'	114"	12"	13.1	11.7	10.6
13'	120"	6"	12.0	10.7	9.7
14'	102"	36"	18.0	16.1	14.5
14'	108"	30"	16.0	14.3	12.9
14'	114"	24"	14.4	12.9	11.6
14'	120"	18"	13.1	11.7	10.6
14'	124"	14"	12.4	11.0	10.0
14'	126"	12"	12.0	10.7	9.7
15'	102"	48"	20.6	18.4	16.6
15'	108"	42"	18.0	16.1	14.5
15'	114"	36"	16.0	14.3	12.9
15'	120"	30"	14.4	12.9	11.6
15'	124"	26"	13.5	12.0	10.9
15'	126"	24"	13.1	11.7	10.6
15'	138"	12"	11.1	9.9	8.9
16'	114"	48"	18.0	16.1	14.5
16'	120"	42"	16.0	14.3	12.9
16'	124"	38"	14.9	13.3	12.0
16'	126"	36"	14.4	12.9	11.6
16'	138"	25"	12.0	10.7	9.7
16'	144"	18"	11.1	9.9	8.9

DUMP BODY APPLICATIONS VC620 *					
BODY	CA	O.H.	40° (TON)	45° (TON)	50°(TON)
8'	-	12"	24.0	21.4	19.4
9'	-	12"	20.6	18.4	16.6
10'	-	12"	18.0	16.1	14.5
12'	-	12"	14.4	12.9	11.6

DM/LDK KITS

(DM) DIRECT-MOUNT PTO DRIVEN

- Power-Up, Power Down
- Pump: SAE "A" 2-bolt Flange, 5/8" - 9 Spline Shaft CCW Rotation (21 qt reservoir)
- Includes Hoses, Controls, Hydraulic Fittings

(LDK) LESS DRIVE KIT

- **INCLUDES:** Mounting Kit, Rear Hinges & Scissors with Cylinder
- **DOES NOT INCLUDE:** Hoses, Controls, Hydraulic Fittings, Pump & Tank Combo



Venco Venturo Industries LLC
 12110 Best Place | Cincinnati, Ohio 45241
 800-226-2238 | 513-772-8448 Local
info@venturo.com | www.venturo.com

NOTE: Venco hoists are designed for and intended to be used on stationary trucks dumping on firm and level ground. Spreading applications and/or shock unloading are strictly prohibited and will void any warranty.
 Copyright © 2020 Venco Venturo Industries LLC. All Rights Reserved.