

Lug & Ring Terminal Insulators

A more comprehensive line of insulators, offering a wider variety of lug and ring protection. Our lug and ring insulators can be used with starters, generators, alternators, solenoids, and other devices.



258 Series



- Protect large terminal connections from shorts
- Terminal Outside Dia: 2.3" / 58.7mm
- Post Height: 2.0" / 50.8mm
- Inside Grip Diameter: .65" / 16.6mm
- Can accept multiple cables, up to 1/0 ga each

Part #	Cable Entry Size
258N9	Oval, up to 4/0



216T Series



- Snap-on insulator, can be removed without cable
- Terminal Outside Dia: .64" / 16.3mm
- Post Height: .74" / 18.8mm

Part #	Cable Entry Size
216T8	.27" / 6.9mm



400 Series



- Terminal Outside Dia: .6" / 15.2mm
- Post Height: .88" / 22.4mm
- Inside Grip Dia: .44" / 11.2mm
- Terminal Length: 1.19" / 30.3mm

Part #	Cable Entry Size
400N7	.31" / 7.9mm
400N9	.44" / 11.2mm
400E4	.18" / 4.6mm



405 Series



- Terminal Outside Dia: 1.0" / 25.4mm
- Post Height: .98" / 24.8mm
- Inside Grip Diameter: .50" / 12.7mm

Part #	Cable Entry Size
405N1	.13" / 3.3 mm
405N2	.30" / 7.6mm
405N9	.50" / 12.7mm

NEW



406 Series

406N3	.16" / 4.1mm
406N9	.75" / 19mm



470 Series



- Terminal Outside Dia: .85" / 21.6mm
- Post Height: 1.06" / 26.9mm
- Inside Grip Diameter: .63" / 15.9mm
- Terminal Length: 1.81" / 46.0mm

Part #	Cable Entry Size
470N9	.63" / 15.9mm



485 Series



- Terminal Outside Dia: .52" / 12.9mm
- Post Height: .45" / 11.4mm
- Inside Grip Diameter: .25" / 6.4mm
- Cable Entry: .25" / 6.4mm

Part #	Cable Entry Size
485N9	.25" / 6.4mm