

## Technical Specifications

Components	Rack Access Pod, 2 Proximity Card Reader Handles, 2 RJ-45 Style Door switch kits, hardware, 2 HID cards
Accessibility	Remote Access, Proximity Card, Master Key Override, User Access Scheduling
Rack Mounting	0U or 1U; (Basement mounting in an APC NetShelter™ SX rack)
Enclosure Compatibility	APC NetShelter® SX, Chatsworth GlobalFrame™
Alert Notification	Email, E-mail, and Visual Beacon
Mass Configuration	Up to 130 doors with 5 NetBotz appliances
Management Solutions	InfraStruxure™ Central
Appliance Ports	2 A-Link Ports, 2 Door Lock Port (handle), 2 Door Switch (switch)
Power	Power over A-Link
Proximity Card Compatibility	HID Proximity Cards (HID 125kHz proximity technology) Card formats: H10301, H10302, H10304, Corp1000
User Interface	NetBotz Advanced View
Power Supply Recommendation Room Monitor 455	2 Maximum Rack Access Pods can be monitored per appliance; One AP9505i power supply required per 1 or 2 rack access pods
Power Supply Recommendation Rack Monitor 550	13 Maximum Rack Access Pods can be monitored per appliance; One AP9505i power supply required for the third attached pod plus an additional power supply for each additional third pod



Front



Handles



Back



HID Proximity Cards