

SUBMERSIBLE PUMP CLASSIC



Flat suction pump for extracting water up to 2 mm deep

- Aluminium housing with stove enamelling
- Oil-filled motor for continuous operation with overload protection
- Self-aspirating

Application area

Pumping dry flooded cellars and low-lying building sections. Draining pits and soakaways. Pumping out garden ponds and swimming pools when no persons are present. Extracting water during core drilling and concrete cutting work. Draining and refilling containers.

Notice

The device is not suitable for use with salt water or brine.

Art. No.	0993 702 70
P. Qty.	1
Max. feed quantity	70 l/min
Max. delivery height	6 m
Nominal voltage	230 V/AC
Nominal current	1 A
Motor output	190 W
Weight of machine	5 kg
Cable length	10 m
Connection thread	1/2 inch, 3/4 inch, 1 inch
Residual water height	2 mm

Leistungsdaten	
Förderhöhe m	Leistung l/min
1	70
2	63
3	55
4	43
5	28
6	10

Related products	Art. No.
Hose coupling threaded fitting with male thread MT 1 1/4 inch	0886 001 024
Water hose Professional 1/2 in; 50 m	0886 001 200
Water hose Professional 1/2 in; 30 m	0886 001 201
Water hose Professional 3/4 in; 50 m	0886 001 210
Water hose Professional 3/4 in; 25 m	0886 001 211
Water hose Professional 1 in; 50 m	0886 001 220